



US006327414B1

(12) **United States Patent**
Strause et al.

(10) **Patent No.: US 6,327,414 B1**
(45) **Date of Patent: Dec. 4, 2001**

(54) **APPARATUS AND METHOD FOR INTERCONNECTING FIBER CABLES**

(75) Inventors: **Kevin L. Strause**, Keller; **Robert A. Burrous**, Coppell, both of TX (US)

(73) Assignee: **CCS Holdings, Inc.**, Hickory, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/499,713**

(22) Filed: **Feb. 8, 2000**

Related U.S. Application Data

(62) Division of application No. 08/838,556, filed on Apr. 9, 1997, now Pat. No. 6,061,492.

(51) **Int. Cl.⁷** **G02B 6/36**

(52) **U.S. Cl.** **385/135; 385/134**

(58) **Field of Search** **385/134, 135**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,765,709 8/1988 Suillerot et al. 385/135
5,071,220 * 12/1991 Ruello et al. 385/135

5,247,603 9/1993 Vidacovich et al. 385/135
5,479,553 * 12/1995 Daems et al. 385/135
5,706,384 1/1998 Peacock et al. 385/135
5,740,298 4/1998 Macken et al. 385/135
5,835,660 11/1998 Jung et al. 385/137
5,870,519 2/1999 Jenkins et al. 385/135


* cited by examiner

Primary Examiner—Ellen E. Kim

(57) **ABSTRACT**

A apparatus and method are provided to provide a readily rearrangeable interconnection point between two fiber cables. A panel has a series of trays for holding joined fiber pairs. One of the cables is fanned out in equal length fan out tubes and fiber guides are located such that any fan out tube can be routed with its slack managed to any tray in the series of trays. As such, rearrangement of the fan out tubes along the series of trays is readily achieved. The complements of the other cable are routed to the other side of the trays. Inside the trays, the individual fibers are routed to joint holders. The trays are pivotally attached to the panel and hang at a downward angle. The trays are pivotable upward to allow access to lower trays. Opposed fibers are joined and the resulting joint is stored in the trays.

6 Claims, 10 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5






Fig. 6






Fig. 9




Fig. 10




Fig. 11




Fig. 12






Fig. 13



APPARATUS AND METHOD FOR INTERCONNECTING FIBER CABLES

This application is a divisional application of Ser. No. 08/838,556 filed Apr. 9, 1997, is now U.S. Pat. No. 6,061, 492.

TECHNICAL FIELD OF THE INVENTION

The present invention relates to an optical fiber distribution apparatus and method for providing a readily rearrangeable interconnection point directly between two fiber cables.

BACKGROUND OF THE INVENTION

In telecommunication networks from a telecommunication company's central office to its subscribers, existing copper installations are being replaced with optical fiber out to a plurality of fiber nodes that convert the optical signals to electrical signals for transmission to the subscriber over copper drops. As more fiber nodes are added to networks, it becomes increasingly difficult for the central office to handle all the distribution needs of the network. In order to move fiber distribution downstream of the central office into the network, commonly used central office type fiber distribution frames can be used; however, such frames require large amounts of space and even larger cabinets and vaults to house them. They also use jumpers interposed between the feeder cable and distribution cable to allow for reconfigurations. Besides increasing the amount of space needed, the use of jumpers adds another connection point that contributes to connection loss in the network. Other types of fiber interconnection products such as splice closures are limited to mating complements of the feeder cable to complements of the distribution cable and any reconfiguration is limited to fibers within the same complement.

Accordingly a need exists for a fiber distribution apparatus that can be used downstream of the central office to provide a flexible point of demarcation between feeder fibers from the central office and distribution fibers leading to optical nodes. More specifically, a need exists for a compact fiber distribution apparatus that allows any distribution fiber to be joined to any feeder fiber whether at initial installation or later reconfiguration and without the need for jumpers or large space requirements.

SUMMARY OF THE INVENTION

The present invention provides a fiber distribution interface apparatus that in its various aspects can have the advantages of 1) high density of connections between distribution and feeder fibers, 2) ease of disconnecting and reconnecting distribution/feeder joints to effect changes in the network, 3) the flexibility to connect any one feeder fiber to any one distribution fiber regardless of what complement (ganged group of fibers in a cable) either fiber comes from, 4) achieving such flexibility in making/changing connections without jumpers, 5) achieving such with minimum fiber movement, 6) achieving such with simple initial installation—constant length buffer tube fan outs, and 7) accommodating variety of joining and storage options.

Specifically, one aspect of the present invention provides a method of interposing a readily rearrangeable interconnection point between a first fiber cable and a second fiber cable. An end of the first fiber cable is routed to a panel. The first fiber cable has a plurality of first fiber complements and each first fiber complement has a plurality of first fibers. A series of subsets of the plurality of first fiber complements is

routed to a corresponding series of trays mounted on the panel. The first fibers of each subset are routed to joint locations in the subset's respective tray.

An end of the second fiber cable is routed to the panel. The second fiber cable has a plurality of second fiber complements and each second fiber complement has a plurality of second fibers. The second fibers from the second fiber complements are fanned out to create equal length fan out tubes containing at least one fiber. At least a first portion of the fan out tubes are routed to the series of trays. The second fibers in the first portion of fan out tubes are routed to joint locations in the tray. The first portion of the second fibers are joined to corresponding first fibers to create fiber joints, and the fiber joints are located in the trays.

Another aspect of the present invention is an interconnection apparatus for providing a readily rearrangeable interconnection point between a first fiber cable and a second fiber cable. Each fiber cable is of the type having multiple complements of multiple fibers. The apparatus comprises a panel and a series of splice trays. Each splice tray is pivotally mounted to the panel defining a pivot axis. An array of fan out blocks is mounted on the panel. Each fan out block has a complement end for receiving a complement and a fan out end opposite thereto. A plurality of equal length fan out tubes extend from the fan out ends of the array of fan out blocks. A series of fiber guides are located relative to the series of trays and relative to the fan out blocks such that any fan out tube can be routed to any tray without unmanaged slack by routing the fan out tube through the appropriate number of fiber guides before routing the fan out tube to a particular tray.

Another aspect of the present invention is a stubbed interconnection apparatus that provides a readily rearrangeable interconnection point between a first fiber cable and a second fiber cable. Each fiber cable is of the type having multiple complements of multiple fibers. The apparatus comprises a panel and a stack of splice trays. Each splice tray is pivotally mounted to the panel defining a pivot axis. A cable stub installed in the apparatus has a first end for splicing to the first cable, a second end opposite thereto for splicing to the second cable, and a single fiber zone at a midpoint along the stub where single fibers from the cable are separated from each other. At least a portion of the single fiber zone is located in the series of trays.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of an example network incorporating an embodiment of the present invention;

FIG. 2 is a schematic diagram of an embodiment of the interconnect platform of the present invention;

FIG. 3 is a perspective view of the preferred embodiment of the interconnect cabinet of the present invention;

FIG. 4 is a perspective view of the preferred embodiment of the panel used in the present invention;

FIG. 5 is a perspective view of the preferred embodiment of the panel used in the present invention with trays installed thereon;

FIG. 6 is a perspective view of the preferred embodiment of the panel used in the present invention with two trays pivoted up and with storage cassettes installed thereon;

FIG. 7 is a perspective view of the preferred embodiment of the friction hinge used to mount the trays to the panel in the present invention;

FIG. 8 is a perspective view of the preferred embodiment of the fiber guide used in the present invention;

FIG. 9 is an exploded perspective view of the preferred embodiment of the fan out blocks used in the present invention;

FIG. 10 is a perspective view of a representative fan out assembly that may be used in the present invention;

FIG. 11 is a perspective view of the tray used in the preferred embodiment of the present invention;

FIG. 12 is a perspective view of the lid used with the tray of FIG. 11;

FIG. 13 is a perspective view of the strain relief used in the tray of FIG. 11;

FIG. 14 is a perspective view of the card used to store fibers in the present invention; and

FIG. 15 is a schematic diagram depicting an alternative embodiment of the present invention having a stubbed interconnect platform.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT OF THE PRESENT INVENTION

With reference to FIG. 1, a network application incorporating the present invention is shown. A telephone company central office is shown as 10 from which a backbone ring cable, shown as feeder cable 14, is run. Distribution networks 18 branch off of feeder cable 14 to provide telecommunication links to subscribers 22. In the shown network, a tapered portion 24 of the feeder cable is tapered off at a splice closure 26. A separate jacketed cable 28 extends from splice closure 26 to an interconnect cabinet 30 that is one aspect of the present invention. Distribution cables 20 extend from interconnect cabinet 30 into distribution network 18.

Because the depicted application envisions interconnect cabinet 30 being above ground while tapered portion 24 of feeder cable 14 is below ground, a separate jacketed cable 28 would most likely be needed. However, tapered portion 24 and interconnect cabinet 30 can be located such that a separate jacketed cable 28 would not be needed. In such a case, splice closure 26 may not be necessary. For purposes of this patent, the modifier "feeder" will refer to the cable, complements or fibers that are entering the interconnect cabinet from the central office side of the network regardless of whether there are any separate jacketed cables interposed between the actual backbone cable and the interconnect cabinet. The modifier "distribution" will refer to cable, complements or fibers that enter the interconnect cabinet from the subscriber side of the network. However, it should be understood that the present invention could be practiced with the feeder cable installed as described for the distribution cable and the distribution cable installed as described for the feeder cable. Therefore the present invention is for interconnecting a first cable and a second cable.

The present invention can be used with any conventional fiber cable including ribbon fiber cable. Fiber cable typically includes a plurality of "complements" and each complement has multiple fibers. A complement may be, for example, a buffer tube that has up to twelve individual fibers or, as another example, a complement may be one or more ribbon fibers ganged together in a slot of a slotted core cable.

FIG. 2 shows a diagram of the flexible interconnectivity of interconnect platform 29 which may be housed in a cabinet shown by example as cabinet 30 in FIG. 3 or be mounted on a frame or in some other type of closure. Feeder cable 14 enters platform 29 and a representative feeder complement 35 is shown entering joint carrier 36 and a

representative individual feeder fiber 34 is routed to joint 48 also in carrier 36. Distribution cables 20 enter interconnect platform 29 and two representative distribution complements 38 are shown routed to fan out blocks 39 where fibers from one complement are fanned out and a smaller number of distribution fibers, for example one or two, are routed in distribution fan outs 40 to tray 36, and a representative distribution fiber 44 is routed to joint 48. By fanning out the distribution complements into fan outs, any distribution fiber 44 can be readily joined to any feeder fiber 34 without regard to the complement that the distribution fiber is from and as such further allows ready configuration of the interconnections on a fiber to fiber basis as opposed to a complement to complement basis.

In some networks, fibers are routed to subscribers in pairs such that the pair of fibers would never need to be separated. In such networks, fiber pairs can just as easily be substituted in the distribution fan outs 40 as opposed to a single fiber and there will be no loss of flexibility. Thus "fiber to fiber" flexibility may also refer to "fiber pair to fiber pair" flexibility depending on the network.

With reference to FIGS. 3-6, the preferred embodiment of interconnect platform 29 is shown. In this embodiment, interconnect platform 29 is housed in cabinet 30 which has outer housing 70 that defines interior 72 and that has doors 74 which provide access to interior 72. Cables are brought into cabinet 30 through the bottom and the sheath is clamped and the strength member bonded at a point inside the cabinet that is accessible through access panels (not shown) on each side of housing 70.

Mounted in housing 70 is interconnect frame 84. Frame 84 is shown as sheet metal panel 85. Panel 85 has front surface 88 facing toward doors 74 and back surface 90 opposite thereto. Panel 85 also has top 92, bottom 94, first side 96 and second side 98 opposite thereto. Interconnect frame 84 may be assembled from frame pieces instead of a panel as the purpose of frame 84 is to hold various items.

Located above panel 85 is complement management panel 100 with complement slack spools 102a on the left and 102b on the right. Located below panel 85 is complement storage area 104.

Mounted on panel 85 is a series of carriers 110 which are shown, by example, as column 109 of trays 112. Each tray 112 is mounted to panel 85 by a pair of hinges 114 (shown in FIG. 7) that are preferably self-supporting hinges, for example, friction hinges sold by Southco. The friction in the pivoting of these hinges can be adjusted by set screw 116 so that a pair of hinges 114 can hold a fully loaded tray 112 cantilevered at any angle with respect to panel 85. Hinges 114 define pivot axis 118 about which tray 112 is raised and lowered. Pivot axis 118 is horizontal in this embodiment and parallel with the plane of panel 85.

In order to route feeder complements 35 and distribution fan outs 40 into trays 112, fiber guides 128 (shown in more detail in FIG. 8) are mounted in two columns 113a,b on panel 85 outside of where hinges 114 are mounted on panel 85. Fiber guides 128 are shown by example as molded channels 130 with overhanging tabs 132 that extend over channels 130 which help retain fibers in the channels after they are worked into the channel around the overhanging tabs 132. Channels 130 are curved with an entry end 134 curved toward the direction from which the fiber will be coming and exit end 136 which is in line with a corresponding pivot axis 118. As will be explained in more detail, by having exit end 136 in line with pivot axis 118, tray 112 can be designed so that fibers enter the tray along the axis of

pivot such that pivoting of the tray does not appreciably move the fiber.

When fiber guides **128** are attached to panel **85** in column **113a**, curved entry ends **134** of channels **130** are located to the outside of panel **85** (first side **96**) and oriented upward because in the preferred embodiment of cabinet **30**, feeder fiber complements **35** come down from the top of housing **70**. When fiber guides **128** are attached to panel **85** in column **113b**, curved entry ends **134** are located to the outside of panel **85** (second side **98**) and are oriented downward because distribution fan outs **40** come up to trays **112** from being routed around fan out hoops **106**. As can be seen in the preferred embodiment, regardless of the column that fiber guides **128** are located in, curved entry ends **134** are located to the outside relative to straight exit ends **136**. However, it should be understood that fiber guides **128** may be configured and located as desired to accommodate whatever fiber routing is desired to carriers **110**.

An array of fan out blocks **39** is mounted on the second side **98** of panel **85** below which is located a series of large fan out hoops **106**. The fan out blocks **39** and hoops **106** are spaced sufficiently from the right side of trays **112** to permit routing of distribution fan outs **40** from below fan out blocks **39** and over to trays **112** taking into account the minimum bend radius of fiber. With reference to FIGS. **10–11**, the preferred embodiment of fan out block **39** and fan outs **40** is shown. The “Buffer Tube Fan-Out Kit” part number FDI-FAN-OD45 available from Siecor Corporation is the preferred fan out block. Fan out blocks **39** transition one complement to several fan out tubes that either hold a single fiber or a pair of fibers from the complement depending on the network. Blocks **39** have complement end **50** for receiving a feeder complement and fan out end **52** for accommodating fan out assembly **54** of FIG. **10**. Fibers from the complement are threaded through the desired fan outs **40** of assembly **54**. Fan outs **40** allow for ready routing and protection of the fiber. Assembly **54** has bound end **56** that is received in fan out end **52** of block **39** and each fan out **40** has tube end **64**. Fanning out fibers from complements into fan out tubes inside blocks like block **39** is known in the art. Block **39** also has lid **58** for closing over the transition from complement to fan out assembly **54** and mounting rings **60** that allow a series of blocks **39** to be slid on mounting rods **62** (shown in FIG. **4**).

Fiber storage area **108** is located on panel **85** and above column **109** of trays **112**. Fiber storage area **108** is for storing unused distribution fibers for future deployment. As is typical in a fiber network, the ratio of distribution fibers to feeder fibers may be around 2:1. As such, it is preferred that the unused distribution fibers be readily stored and easily movable to be connected to a feeder fiber when the need arises.

With reference to FIGS. **11–13**, the preferred embodiment of trays **112** is shown. Tray **112** is generally flat with bottom wall **140** and outer wall **142** extending up therefrom. Tray **112** has attachment side **144** and free side **146** opposite thereto. Hinges **114** are mounted on hinge mounts **148** on attachment side **144**. Tray **112** has an outer channel **162** that extends around the inside of outer wall **142**. Outer channel **162** has rear portion **164** that has entrances **166a, b** opposite each other. Entrances **166a, b** are located in line with exit ends **136** of channels **130** of fiber guides **128** when tray **112** is mounted on panel **85**. Entrances **166a, b** are also in line with pivot axis **118**. Accordingly, when a fiber is routed from fiber guide **128** which is fixed on panel **85** to tray **112** which can pivot relative to panel **85**, the fiber enters the tray along pivot axis **118** for some distance before turning away from

pivot axis **118** such that pivoting of tray **112** will not appreciably move the fiber. As can be seen, if the fiber were to enter tray **112** at an angle relative to pivot axis **118**, the fiber would be bent and unbent as tray **112** was raised and lowered. It is preferred that such bending of the fiber be avoided.

Outer channel **162** also has front portion **167** that opens to interior **168** of tray **112**. Inner wall **170** separates outer channel **162** from interior **168**. Interior **168** receives feeder fibers and distribution fibers and stores slack of such fibers. Slack is needed to allow easy removal and access to the fiber ends from tray **112** and then replace them in tray **112**.

Joint holder **180** is located in interior **168** of tray **112** on bottom wall **140**. Holder **180** has a series of grooves **182** sized to receive a packaged splice of two fiber ends. Various holders **180** can be used depending on the type of joint to be used between two fibers. For example, connectors may be used to join fibers, in which case, adapters to receive the connectors could be located in tray **112** or some other suitable carrier **110**. An additional example is a holder designed to hold mass splices that are used with ribbon fiber cable.

Tray **112** also has strain relief locations **150a** and **b** that receive a strain relief **172** shown in FIG. **13**. Inner wall **170** has catches **152** that snap over cutouts **154** on the ends of strain relief **172**. Feeder strain relief **172** is preferably a plastic piece with a series of flaps **173** defining grooves **174** sized to receive either the end of a feeder complement **35** or fan out **40** friction pressed therein. Flaps **173** have broadened ends **176** to help retain any complement of fan out pressed therein. Because strain relief **172** is a removable insert, various designs of strain relief can be interchanged and inserted in tray **112** to accommodate the variety of complements and fan outs. For example, a strain relief insert may be structured to accommodate ribbon fiber complements.

Tray **112** also has lid pins **190** located at attachment side **144** for pivoting attachment of lid **192**. Lid **192** is generally planar and has extension **194** that is configured to snap fit over lid pins **190**.

As can be seen in FIGS. **3** and **5–6**, trays **112** preferably hang at a downward angle overlapping each other. In the preferred embodiment, the trays hang downward at approximately a 50 degree angle down from the horizontal and can be pivoted to a 50 degree angle upward from the horizontal. With such overlapping at an angle, the depth of column **109** of trays **112** is significantly reduced and while still allowing ready access to the trays. Specifically, when a tray **112** somewhere in the middle of column **109** needs to be accessed, all the higher trays are raised and hinges **114** retain the higher trays at the angular position to where they are raised. Lid **192** of that tray **112** is then pivoted up to access interior **168** of tray **112**.

In an alternative embodiment, a holder may be used to support the higher trays when accessing a tray. As another alternative, lids **192** can be structured to support trays above them by having its outer edge placed under a catch on the underside of the tray immediately above it. As such, the weight of the trays above the accessed trays is transferred to lid **192** which transfers the weight to the lid pins **190** which are located relative to hinges **114** such that no appreciable moment is created about hinges **114** so as to cause the accessed tray to pivot. When the accessed tray is no longer needed, lid **192** is simply disengaged from the catch and lid **192** and the higher trays are lowered back down to their original location.

In yet another alternative embodiment, the series of trays **112** can be in a row format as opposed to the column format and hang by a vertical axis. Essentially, the arrangement of panel **85** can simply be rotated ninety degrees to create a row format. However, the column format is preferred because of easier access to the interior of trays **112**.

Fiber storage area **108** is used to hold the ends of distribution fibers that are to be saved for later deployment. Any of a variety of storage trays or other items may be located in this area to accomplish such storage. In the preferred embodiment with reference to FIGS. **5** and **14**, storage cards **232** are used for each individual distribution fiber (or pair of fibers if the network uses fiber pairs). Each fiber of pair of fibers **44** is wound in a circle through slits **233** formed between tabs **234** of card **232** and then protective flaps **235** are folded over each side of card **232** and tab **237** is inserted into slots **238** on flaps **285** to hold flaps **285** closed over the circle of fiber **44** to help protect fiber **44**. Card **232** is placed vertically on shelf **236** in storage area **108**. When a stored fiber is later needed, card **232** is removed from shelf **236** and the fiber is unwound from card **232** and that fibers fan out **40** is routed through the appropriate hoops **106** to the desired tray **112** and the fiber **44** is routed around inside tray **112** until the end of the fiber terminates at joint holder **180**. In an alternative embodiment for storage area **108** shown in FIGS. **3** and **6**, storage cassettes **240** can be used to store a plurality of fibers and the cassettes stacked horizontally in storage area **108**.

The preferred installation of fiber in interconnect cabinet **30** will now be described. A predetermined length of the sheath of the feeder cable and distribution cable is stripped back from the cable ends to expose the complements of the cable. This length will depend on the size of panel **85** and other components in cabinet **30** and readily determined by accounting for the routing path and appropriate slack storage. The end of the sheath of the feeder cable is routed up through the left side of cabinet **30** and clamped and its strength member bonded at the left side of interconnect panel **85**. Feeder complements **35** are extended upward to complement management panel **100** and routed around slack spools **102** back to the left side of cabinet **30** where they are directed downward alongside the left side of trays **112**. Each feeder complement is routed to a respective tray **112** through that tray's corresponding fiber guide **128**. With reference to FIG. **11**, a representative feeder complement **35** is routed through entrance **166a** and into outer channel **162** and terminates at strain relief location **150a** in front portion **167** of outer channel **162**. At strain relief location **150a**, representative feeder fiber **34** extends into interior **168** of tray **112** in a clockwise fashion and terminates at joint holder **180**.

The end of the sheath of the distribution cables is routed up through the right side of the cabinet **30** and clamped and its strength member bonded at the right side of panel **85**. Distribution complements **38** are extended upward to complement management panel **100** and routed around slack spools **102** back to the right side of panel **85** where they are directed down to the array of fan out blocks **39**. Distribution fan outs **40** extend down from fan out blocks **39** and are turned upward around the appropriate fan out hoop **106** depending on where the fan out **40** is to be terminated. Fan outs **40** that are to be stored for later deployment are routed around the fan out hoop **106** closest to fan out blocks **39** and routed up to fiber storage area **108** for suitable storage.

Fan out blocks **39** and fan out hoops **106** are located relative to each other and to column **109** of trays **112** such that all distribution fan outs can be the same length yet be routed to any tray or the storage area and have their slack

appropriately managed. For example, a fan out **40** that is to be routed to the lowest tray **112** is routed through all hoops **106** and then over and up into guide **128** on the right side of the lowest tray **112**. However, a fan out **40** that is to be routed to the uppermost tray is routed through two hoops **106** before being turned upward and to guide **128** of the uppermost tray **112**. As can be seen the series of hoops **106** is located such that equal length fan outs **40** can be appropriately managed to terminate at any tray **112**. This equal length fan out feature contributes to the fiber to fiber flexibility of the present invention that allows any distribution fiber to be joined to any feeder fiber regardless of the complement in which the fiber is located.

With reference to FIG. **11**, a representative fan out **40** that is to be terminated in a tray **112** is routed through entrance **166b** into outer channel **162** and terminated at strain relief location **150b** in front portion **167** of outer channel **162**. At strain relief location **150b**, a representative distribution fiber **44** extends into interior **168** of tray **112** in a counter-clockwise fashion and terminates at joint holder **180**.

With the feeder fibers and distribution fibers so installed, opposed pairs of fibers may now be joined and the resulting joints **181** located in tray **112**. The slack of the fibers that is wound in the interior of trays **112** allows the opposed pairs to be removed from the trays and placed in a fusion splicer, joined, and then the resulting joint located in joint holder **180**.

Reconfiguration of fibers in the present invention is readily achieved. If a distribution fiber from the top tray **112** is to be moved to the lowest tray **112**, the top tray is accessed as described above, the distribution fiber is cut from its joint, the fiber and fan out are "unrouted" or removed from the tray and rerouted through the appropriate hoops **106** and over to the lowest tray. Any reconfiguration is possible in view of the fiber to fiber flexibility of the fan outs **40**.

With reference to FIG. **15** an alternative embodiment of the present invention is shown where interconnect platform **29** is stubbed. This particular embodiment may be found particularly useful in applications where ribbon fiber is used that can be mass fusion spliced together; however, it may be used in single fiber applications as well. Instead of having joints located in carriers **110**, the fiber is continuous through the tray due to use of stub **260**. Stub **260** in this embodiment is a ribbon fiber cable **262** that has complements **264** of ribbon fibers **266**. Stub **260** has feeder end **268** that extends outside housing **70** for a desired length to reach tapered portion **24** of feeder cable **14**. Feeder end **268** can be mass fusion spliced to tapered portion **24** as is known in the art for ribbon fiber. Stub **260** also has distribution end **270** that where distribution cables **20** can be mass spliced onto distribution end **270**.

Stub **260** also has single fiber zone **272** where the fibers of stub **260** are not in ribbon form so that they can be readily accessed. If the network needs to be reconfigured, the desired single fiber is cut and the distribution side of the fiber is moved to the desired location and joined to the feeder side of a second cut fiber. With such an embodiment, the initial installation of the interconnect platform in the network is simplified yet it remains readily reconfigurable. This stubbed embodiment is preferably structured with trays and fan outs just as in the preferred embodiment but the key distinction is that single fibers run continuous through carriers **110** as opposed to having joints between two different fibers. In such an embodiment there is no joint within interconnect platform **29** until there is a later reconfiguration.

While the preferred embodiment has been described in the context of mounting interconnect platform **29** in a cabinet, it should be understood that platform **29** can be readily mounted on a frame or housed in a closure. The location of fan out blocks **39** and fan out hoops **106** relative to each other and to series of carriers **110** can be rearranged as the application dictates as long as any fan out can be routed to any carrier **110** and have its slack appropriately managed. For example, in a closure application where space is more restricted, fan out blocks **39** and hoops **106** may be placed on the back of interconnect frame **84** and located such that any fan out can still be routed to any carrier **110**. Such an arrangement could reduce the width of frame **84** and make it more suitable for a closure application.

Although the present invention has been described with respect to certain embodiments, various changes, substitutions and modifications may be suggested to one skilled in the art and it is intended that the present invention encompass such changes, substitutions and modifications as fall within the scope of the appended claims.

What is claimed is:

1. An interconnection apparatus for providing a readily rearrangeable interconnection point between a first fiber cable (**14**) and a second fiber cable (**20**), each fiber cable of the type having multiple complements of multiple fibers, the apparatus comprising:

- (a) a panel (**85**);
 - (b) a stack of splice trays, each splice tray (**112**) pivotally mounted to said panel and defining a pivot axis (**118**); and
 - (c) a cable stub (**260**) having multiple complements (**264**) of multiple fibers (**266**) and a first end (**268**) for splicing to said first fiber cable, a second end (**270**) opposite thereto for splicing to said second fiber cable, and a single fiber zone (**272**) at a midpoint along said cable stub where single fibers from the multiple fibers of said cable stub are separated from each other, at least a portion of said single fiber zone located in at least one of said splice trays.
2. The apparatus of claim **1** wherein said splice trays hang at a downward angle from said panel overlapping each other and are pivotable upward.
3. The apparatus of claim **1** wherein said single fiber zone is sufficiently long to allow any of said single fibers to be cut into a first half and a second half and the second half moved to any other of said splice trays to be joined to another fiber.
4. The apparatus of claim **1** wherein said first end of said cable stub and said second end of said cable stub are ribbon fiber cables.
5. The apparatus of claim **4** wherein said first fiber cable and said second fiber cable are ribbon fiber cables.
6. The apparatus of claim **1** wherein said first fiber cable is a feeder cable and said second fiber cable is a distribution cable.

* * * * *