



US006344967B2

(12) **United States Patent**
Zamora et al.

(10) **Patent No.:** **US 6,344,967 B2**
(45) **Date of Patent:** **Feb. 5, 2002**

- (54) **LAPTOP COMPUTER WITH ERGONOMICALLY ENHANCED INTERFACE FEATURES**
- (75) Inventors: **George G. Zamora, Vail; Daniel James Winarski, Tucson, both of AZ (US)**
- (73) Assignee: **International Business Machines Corporation, Armonk, NY (US)**

5,490,036 A	*	2/1996	Lin et al.	361/680
5,539,615 A	*	7/1996	Sellers	361/680
5,575,576 A		11/1996	Roysden, Jr.	
5,613,786 A	*	3/1997	Howell et al.	400/489
5,706,167 A		1/1998	Lee	
5,717,431 A	*	2/1998	Chia-Ying et al.	345/168
5,729,480 A	*	3/1998	Katoh et al.	364/709.12
5,734,548 A		3/1998	Park	
5,748,185 A	*	5/1998	Stephan et al.	345/173
5,754,395 A		5/1998	Hsu et al.	
5,764,474 A	*	6/1998	Youens	361/680

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(List continued on next page.)

- (21) Appl. No.: **09/824,331**
- (22) Filed: **Apr. 2, 2001**

FOREIGN PATENT DOCUMENTS

JP	7-72954	*	3/1995	G06F/1/16
JP	8-22350	*	1/1996		
JP	11-184604	*	7/1999		

Related U.S. Application Data

- (62) Division of application No. 09/414,188, filed on Oct. 7, 1999.

Primary Examiner—Leo P. Picard
Assistant Examiner—Anatoly Vortman
(74) *Attorney, Agent, or Firm*—Robert M. Sullivan; Bracewell & Patterson, L.L.P.

- (51) **Int. Cl.**⁷ **H05K 5/02; G06F 1/16**
- (52) **U.S. Cl.** **361/680; 361/681; 361/683; 361/686; 345/168**
- (58) **Field of Search** 361/680–683, 361/686, 724–727; 400/492, 472, 473, 477, 479, 488, 489; 341/21, 22; 312/208.1, 208.4; D14/115, 247; D18/1, 7, 52; 345/168, 169; 348/794

(57) **ABSTRACT**



A laptop computer has a base and a cover with a display monitor that are connected together by a hinge. The base and cover have congruent trapezoidal shapes that give the laptop a unique appearance. A pair of segregated right and left keyboards are mounted to the base. Each keyboard is rotated by a small angle from the center of the base to align with the natural position of the arms of the user. The keyboards are further articulated such that their front ends are elevated relative to their rearward ends. Alternate embodiments of the invention utilize various mechanisms for articulating the keyboards. In addition, the keys on each keyboard may be arranged in a curvilinear formation. The laptop has a wedge that is slidably mounted to the rearward end of the base for varying the angle of inclination of the keyboards. The wedge can raise or lower the angle of the keyboards to suit the preference of the user. The laptop also has a pair of touch pads with different sensitivities, as well as a track point or track ball for moving the screen cursor.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,527,149 A	*	7/1985	Swensen	340/365 R
4,568,056 A	*	2/1986	Lewinski	248/677
5,067,834 A	*	11/1991	Szmanda et al.	400/489
5,168,427 A	*	12/1992	Clancy et al.	361/393
5,198,991 A		3/1993	Pollitt	
5,200,883 A	*	4/1993	Kobayashi	361/395
5,228,791 A	*	7/1993	Fort	400/489
5,267,127 A		11/1993	Pollitt	
5,375,800 A	*	12/1994	Wilcox et al.	248/118.1
5,397,189 A	*	3/1995	Minogue	400/489

9 Claims, 5 Drawing Sheets



US 6,344,967 B2

Page 2

U.S. PATENT DOCUMENTS		
5,769,551 A	6/1998	Tsai et al.
5,800,085 A	9/1998	Lee
5,818,360 A *	10/1998	Chu et al. 341/22
5,818,690 A *	10/1998	Spencer 361/680
5,918,957 A *	7/1999	Bovio et al. 312/223.2
5,949,643 A *	9/1999	Batio 361/681
6,008,986 A *	12/1999	Mok 361/687
6,028,768 A *	2/2000	Cipolla 361/687
6,081,207 A *	6/2000	Batio 341/20
6,091,600 A *	7/2000	Jeong 361/680

* cited by examiner

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6







Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17





Fig. 18



LAPTOP COMPUTER WITH ERGONOMICALLY ENHANCED INTERFACE FEATURES

This is a Division of application Ser. No. 09/414,188, filed Oct. 7, 1999, currently pending.

BACKGROUND OF THE INVENTION

1. Technical Field

This invention relates in general to portable computers and in particular to portable laptop computers with ergonomically enhanced keyboard and cursor control interface features.

2. Background Art

In the prior art, laptop computers have keyboards with substantially flat, linear arrays of keys. The keyboards sit square in front of the user and force the user to rotate his or her wrists to awkward, unnatural angles. Unfortunately, discomfort and even carpal tunnel carpal syndrome can develop in users of non-ergonomic keyboards that force the user to uncomfortably flex or rotate his or her wrists. The user's risk of carpal tunnel syndrome may be reduced by keeping the wrists straight. This problem has been especially difficult for laptop computer designers to overcome since laptops are portable and used in varying environments.

One prior art design attempted to alleviate the ergonomically incorrect angles by dividing the keyboard into left and right portions that move apart to a wider spacing when the cover or lid of the laptop was opened. However, this keyboard design remained substantially flat after it was deployed. Another prior art keyboard design exists for non-portable desktop computers, but it is a static design that cannot be collapsed for use with laptop computers. An improved keyboard for laptop computer applications is needed to enhance the ergonomic features of the computer to reduce the risk of carpal tunnel syndrome.

SUMMARY OF THE INVENTION

A laptop computer has a base and a cover with a display monitor that are connected together by a hinge. The base and cover have congruent trapezoidal shapes that give the laptop a unique appearance. A pair of segregated right and left keyboards are mounted to the base. Each keyboard is rotated by a small angle from the center of the base to align with the natural position of the arms of the user. The keyboards are further articulated such that their front ends (nearest to the user) are elevated above or below relative to their rearward ends (nearest to the monitor). Alternate embodiments of the invention utilize various mechanisms for articulating the keyboards. In addition, the keys on each keyboard may be arranged in a curvilinear formation. The laptop has a wedge that is slidably mounted to the rearward end of the base for varying the angle of inclination of the keyboards. The wedge can raise or lower the keyboards to suit the preference of the user. The laptop also has a pair of touch pads with different sensitivities, as well as a track point for moving the screen cursor.

Thus, one object of the invention is to divide the keyboard into two halves to allow the user adjustable rotation of the keyboard halves to promote proper posture with straight or unbent wrists, thus providing an ergonomic laptop.

Another object of the invention is to provide adjustable rotation of the keyboard halves via preloaded flexures and a slidable wedge.

Still another object of the invention is to provide keyboard keys that are staggered in an arcuate pattern in order to conform to the natural curled position of the user's fingers.

Still another object of the invention is to provide a laptop computer with a nonconventional profile that is distinctive and appeals to users.

BRIEF DESCRIPTION OF THE DRAWINGS

So that the manner in which the features, advantages and objects of the invention, as well as others which will become apparent, are attained and can be understood in more detail, more particular description of the invention briefly summarized above may be had by reference to the embodiment thereof which is illustrated in the appended drawings, which drawings form a part of this specification. It is to be noted, however, that the drawings illustrate only a preferred embodiment of the invention and is therefore not to be considered limiting of its scope as the invention may admit to other equally effective embodiments.

FIG. 1 is a top view of a first embodiment of a laptop computer constructed in accordance with the invention.

FIG. 2 is a side view of an elevation wedge for the computer of FIG. 1 taken along the line 2—2 of FIG. 1.

FIG. 3 is a schematic drawing of a rectilinear arrangement of keyboard keys for the computer of claim 1.

FIG. 4 is a schematic drawing of a curvilinear arrangement of keyboard keys for the computer of claim 1.

FIG. 5 is a front sectional view of a lower portion of the wedge and computer of FIGS. 1 and 2 taken along the line 5—5 of FIG. 1.

FIG. 6 is a schematic side view of the computer and wedge of FIGS. 1 and 2 in operation taken along the line 6—6 of FIG. 1.

FIG. 7 is a top view of a second embodiment of the computer of FIG. 1.

FIG. 8 is a top view of a third embodiment of the computer of FIG. 1.

FIG. 9 is an isometric view of a fourth embodiment of the computer of FIG. 1.

FIG. 10 is a top view of the computer of FIG. 9.

FIG. 11 is a schematic side view of a fifth embodiment of the computer and wedge of FIGS. 1 and 2 at a nominal position

FIG. 12 is a schematic side view of the computer of FIG. 11 at an elevated position.

FIG. 13 is a schematic side view of a sixth embodiment of the computer and wedge of FIGS. 1 and 2 at a nominal position.

FIG. 14 is a schematic side view of the computer of FIG. 13 at an elevated position.

FIG. 15 is a schematic side view of a seventh embodiment of the computer and wedge of FIGS. 1 and 2 at a nominal position.

FIG. 16 is a schematic side view of the computer of FIG. 15 at an elevated position.

FIG. 17 is a schematic side view of an eighth embodiment of the computer and wedge of FIGS. 1 and 2 at a nominal position.

FIG. 18 is a schematic side view of the computer of FIG. 17 at an elevated position.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring to FIG. 1, a first embodiment of a laptop computer **100** constructed in accordance with the invention is shown. Laptop **100** has a lid or upper half **110** and a base

or lower half **120** that are connected together by a hinge **115**. Hinge **115** allows the upper half **110** and lower half **120** to rotate relative to each other in a clamshell-like fashion about the X-axis. Laptop **100** is shown in the open position but can be moved to a closed position (not shown) to reduce its size and protect its delicate mechanisms when not in use.

Upper half **110** has a rectangular output display screen **111** for displaying output information to the user. Screen **111** is preferably a liquid crystal display (LCD), but it could use other technologies such as organic light emitting diodes (OLED). Upper half **110** also has a rectangular date and time clock **112** located above screen **111**, and triangular right and left speakers **113**, **114** located on the lateral sides of screen **111**. Note the unique polygonal shape of upper half **110** compared to conventional rectangular-shaped laptop covers or lids.

Lower half **120** has a pair of segregated right and left keyboards **121**, **122** with a plurality of keys **181** for data input to laptop **100**. When viewed from above, keyboard **121** is rotated by a small positive angle THETA (counterclockwise) about the Z-axis from the X-axis. A new coordinate system is defined by keyboard **121** with an X'-axis and a Y'-axis. Similarly, keyboard **122** is rotated clockwise by the same angle THETA in the opposite direction about the Z-axis from the negative X-axis. A coordinate system with an X"-axis and Y"-axis is defined by keyboard **122**. Note that keyboards **121**, **122** are fixed in the trapezoidal configuration shown to match the profile or shape of upper half **110**.

The range for the angle THETA is approximately 5 to 20 degrees, with a preferred value of 12.5 degrees. Keyboards **121**, **122** are rotatably connected to lower half **120** by elements **151**, **152**, respectively. Elements **151**, **152** allow an angle of twist PHI relative to their respective X'-axis and X"-axis. In the preferred embodiment, elements **151**, **152** are flexures made from spring steel that are preloaded to hold keyboards **121**, **122** down against lower half **120**.

As shown in FIGS. 1, 2, and 6, a wedge **170** is mounted to lower half **120** and is slidable relative thereto along a slot **140** that is parallel to the Y-axis. Wedge **170** is coupled to slot **140** with a dovetail **142** (FIG. 5). Dovetail **142** allows precision sliding motion of wedge **170** in the +/- Y direction and keeps wedge **170** attached to lower half **120**. Wedge **170** is used to elevate or lower the forward ends of keyboards **121**, **122** to suit the preference of the user. If the user desires to have laptop **100** in a low position, the keyboards **121**, **122** will be more comfortable to use in a declined position (FIG. 6). Hence, wedge **170** would be moved in the +Y direction. However, if laptop **100** is elevated relative to the user, keyboards **121**, **122** would be more comfortable in an inclined position, so wedge **170** would be moved in the -Y direction.

As shown in FIGS. 1 and 2, wedge **170** has an inclined ramp **183** which is piecewise continuous. A plurality of slots **185**, **187**, **189** are cut into ramp **183** to allow precise and repeatable angulation of keyboards **121** and **122**. However, the user would be free to set wedge **170** at other angles PHI. At the base of wedge **170** dovetail **142** keys the motion of wedge **170** in slot **140**. It is preferred that PHI have a range of -10 degrees to +10 degrees. When the wedge is fully disengaged, PHI would be -10 degrees and when the wedge is fully engaged, PHI would be +10 degrees. Thus, slots **185**, **187**, **189** would represent values of PHI of -5 degrees, 0 degrees or horizontal, and +5 degrees.

The unusual orientation of keyboards **121**, **122** accommodates the anthropometric parameters of the human body.

The shoulder-to-shoulder dimension of adults and older children is significantly wider than the width of a laptop keyboard. Thus, the conventional unitary keyboard employed by traditional laptops must be divided into two portions with each portion rotated by angle THETA in order to properly accommodate the shoulder-to-shoulder dimension of users. If the keyboard is not split and the portions are not rotated, the user must rotate his wrists to an uncomfortable angle to use the keyboard. Holding the wrists at uncomfortable angles for extended periods of time can lead to carpal tunnel syndrome, which can be painful and debilitating.

FIG. 6 shows flexure **151** connecting keypad **121** to wrist pad **127** of lower half **120**. Surface **190** keeps keyboard **121** from depressing more than -10 degrees relative to the horizontal when wedge **170** is not engaged. Then, as wedge **170** is moved in the -Y direction, it increasingly lifts keyboard **121** up to +10 degrees relative to the horizontal. The preloading of flexure **151** keeps the keyboard flexed against the wedge **170**, which holds the keyboard against the wedge and keeps the wedge from shifting under normal keystroke motion. Alternately, element **151** could be a spring-loaded hinge.

Lower half **120** also has wrist pads **126** and **127**. In between wrist pads **126**, **127** is an optional touch-pad **128**. Similarly, in between keyboards **121** and **122** is an optional touch-pad **125**. By running a finger along one touch-pad, the laptop user can direct a cursor **192** on screen **111**. The availability of two touch-pads affords the user two levels of cursor sensitivity without having to continually readjust the sensitivity of the touch-pad in via the computer operating system. Thus, touch-pad **128** could have a coarse sensitivity for rapid and screen-wide motion and touch-pad **125** could have a fine sensitivity for precision motion of the cursor. Such dual-sensitivity pairs of touch pads could have value in computer graphic applications.

In between keyboards **121** and **122** is an optional cursor track point or track ball **124**. Use of the track point **124**, or either of touch pads **125**, **128** replaces a computer mouse. Since a computer mouse is used externally to the laptop body, it typically requires additional desktop space and adds to the weight that the user of the laptop must carry. Hence, cursor track point **124**, and touch pads **125** and **128**, are offered as light weight, miniature alternatives to the computer mouse. Lower half **120** also has an optional handle **130** by which the user may carry laptop **100** when it is closed.

FIGS. 3 and 4 show two possible arrangements of the keys **181** in each of the keyboards **121**, **122**. FIG. 3 shows keys **194** in a rectilinear pattern commonly seen in all computer keyboards. However, since the fingers of the user are not all the same length, keys **196** (FIG. 4) are staggered to accommodate the natural length and arc of the user's fingers. In one embodiment, the individual keys are hexagonal in shape, rather than square or rectangular, to give the user a larger surface area for pushing the keys while maintaining a small keyboard profile.

Referring now to FIG. 7, a second embodiment of the invention is shown as laptop computer **201**. Like laptop **100**, laptop **201** is unconventional in shape by using trapezoidal features and skewed orientations, which distinguish its appearance from prior art designs and enhance its ergonomics. However, the keyboard portions **203**, **205** of laptop **201** are fixed relative to its lower half **207** and are not movable except for the motion of the individual keys thereon. The keys on keyboard portions **203**, **205** may be arranged in either of the patterns shown and described for FIGS. 3 and

4. Lower half **207** also has a pair of touch pads **211**, **213**, a pair of wrist pads **215**, **217**, a track point or track ball **219**, a set of function keys **221** arranged in a triangular formation, and an optional handle **223**. Function keys **221** are located between the rear end of lower half **207** and the rear ends of keyboard portions **203**, **205**. The other elements are described above and operate in a similar manner.

The upper half **231** of laptop **201** is pivotally mounted to lower half **207** on a hinge **233**. Upper half **231** is similar to upper half **110** of laptop **100**, including a rectangular display screen **235**, a triangular speaker **237**, **239** on each side lateral side of screen **235**, and a date and time display **241** above screen **235**. Note that the outer perimeter shape of upper half **231** perfectly matches that of lower half **207**. Thus, when upper half **231** is pivoted to a closed position (not shown) about hinge **233**, it forms a symmetrical, trapezoidal case with lower half **207**.

Referring now to FIG. **8**, a third embodiment of the invention is shown as laptop computer **301**. Laptop **301** is somewhat of a hybrid between laptops **100** and **201**. The lower half **303** of laptop **301** has all the features and functions of laptop **201**, including keyboard portions **305**, **307**, touch pads **311**, **313**, wrist pads **315**, **317**, a track point or track ball **319**, and a triangular set of function keys **321**. The upper half **323** of laptop **301** is pivotally mounted to lower half **303** about a hinge **325**, and has a rectangular profile including a display screen **327**.

When in the open position (shown), lower half **303** also has the same trapezoidal shape as laptop **201**. However, keyboard portions **305**, **307** of laptop **301** are not fixed relative to lower half **303**. Rather, they are pivotally mounted to lower half **303** at their outer rear edges **331**, **333**, respectively, so that laptop **301** can be collapsed into a conventional rectangular-shaped profile when upper half **323** is moved to the closed position (not shown) adjacent to lower half **303**.

A fourth embodiment of the invention is shown in FIGS. **9** and **10**. Laptop computer **401** has an upper half **403**, a lower half **405** and a hinge **407** therebetween. Upper half **403** has a monitor **409** for displaying images. Lower half **405** has a pair of keyboard portions **411**, **413** that are pivotally mounted thereto via pivot elements **415**. Elements **415** are preferably leaf-spring flexures made of spring steel, but could also be hinges or other pivot mechanisms. Keyboard portions **411**, **413** pivot about axes **421**, **423**, respectively. Each keyboard portion **411**, **413** has a device **424** near its inner, rearward corner for assisting rotation about pivot elements **421**, **423**. In addition, keyboard portions **411**, **413** may rotate or pivot to a desired position in a "lazy-susan" fashion about the Z-axis at points **425**, **427**, respectively. These two pivot capabilities of laptop **401** give the user greater ergonomic flexibility in adapting the keyboard portions **411**, **413** to a proper fit. Thus, keyboard portions **411**, **413** are movable to various positions such as those depicted in the previous figures.

The remaining embodiments of the invention disclosed in FIGS. **11**–**19**, illustrate alternate mechanisms for elevating the front edge(s) of the keyboard or keyboard portions (those located nearest to the user). These mechanisms may be employed with conventional designs or any of the designs previously described herein and, thus, should not be limited to the laptop computers designs that appear in the drawings.

Referring now to FIGS. **11** and **12**, laptop computer **501** is the fifth embodiment of the invention. Laptop **501** has a stationary base **503** with a keyboard portion **505**, and a lid **507** containing a display monitor. Lid **507** is pivotally mounted to the rearward end of base **503** with a hinge **509**. A triangular wedge **511** is slidably mounted near the front end of base **503**. Wedge **511** has an inclined surface for engaging the front end of keyboard portion **505**. A pivotal cover **513** extends between the front end of base **503** and the front end of keyboard portion **505**. When wedge **511** is in the disengaged position (FIG. **11**), keyboard portion **505** and cover **513** are substantially horizontal in a conventional configuration. However, when wedge **511** is moved rearward to the engaged position (FIG. **12**), the rear end of keyboard portion **505** is elevated higher than its rearward end at hinge **509** to form a more ergonomically correct configuration. Cover **513** pivots with keyboard portion **505**, but is inclined in the opposite direction.

As shown in FIGS. **13** and **14**, the sixth embodiment of the invention is illustrated as laptop computer **601**. Laptop **601** has a base **603** with a built-in keyboard **605** on its upper surface, and a pivotal lid **607** with a display monitor mounted to the rearward end of base **603** with a hinge **609**. A pivotal leg **611** is hingably mounted to the lower surface of base **603** near its front end. Leg **611** is substantially flat and locates in a recess **613** when it is in its collapsed position (FIG. **13**). When leg **611** is in the collapsed position, keyboard **605** is substantially horizontal. However, when leg **611** is flipped out to its deployed position in front of base **603** (FIG. **14**), the rear end of keyboard **605** is elevated higher than its rearward end at hinge **609** to form a more ergonomically correct configuration. The arcuate range of motion of leg **611** is limited to the diagonal alignment shown to prevent its overextension. The weight of laptop **601** keeps leg **611** in its deployed position until it is retracted by the user.

Referring now to FIGS. **15** and **16**, laptop computer **701** is the seventh embodiment of the invention. Laptop **701** has a stationary base **703** with a keyboard **705**, and a pivotal lid **707** containing a display monitor. Laptop **701** also has upper and lower cylindrical wedges or cam members **709**, **711** at its front end. Upper cam member **709** is mounted to keyboard **705** and lower cam member **711** is mounted to base **703**. Cam members **709**, **711** slidably engage each other along mating inclined cam surfaces that are semi-helical in nature. When cam members **709**, **711** are in their retracted position (FIG. **15**), keyboard portion **705** is substantially horizontal. However, when cam member **709** is rotated to the deployed position (FIG. **16**), the rear end of keyboard portion **705** is elevated higher than its rearward end. Rotating cam member **709** in the opposite direction collapses laptop **701** back to the retracted position.

As shown in FIGS. **17** and **18**, the eighth embodiment of the invention is illustrated as laptop computer **801**. Laptop **801** has a base **803** with a keyboard **805** on its upper surface, and a pivotal lid **807** with a display monitor. A plunger **811** having base and elevation elements is mounted to base **803** and the lower surface of keyboard **805**, respectively, near their front ends. When plunger **811** is in its lower or collapsed position (FIG. **17**), keyboard **805** is substantially horizontal. However, when plunger **811** is "clicked" to its

raised or deployed position (FIG. 18), the rear end of keyboard 805 is elevated higher than its rearward end to form a more ergonomically correct configuration. Plunger 811 may be configured to have a variety of settings and, thus, the elevation of keyboard 805 may be adjusted according to need. Laptop 801 may be returned to its original collapsed position by releasing plunger 811.

The invention has several advantages. The keyboard portions are divided and configured to maximize the user's ergonomic comfort while minimizing the risk of carpal tunnel syndrome. The keyboards can be angled to align with the user's arms and wrists, and the keys can be arranged in a curvilinear formation in order to contour to the length of the user's fingers. In addition, the polygonal or trapezoidal shapes of the various embodiments give the laptops a distinctive appearance.

While the invention has been shown or described in only some of its forms, it should be apparent to those skilled in the art that it is not so limited, but is susceptible to various changes without departing from the scope of the invention.

We claim:

1. A laptop computer, comprising:

a substantially horizontal base having a front end, a rear end, and two lateral side edges;
 a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;
 a keyboard mounted to the base and having a front end, a rear end, and left and right portions that are spaced apart from each other, each of the keyboard portions having a plurality of keys;
 an elevation mechanism mounted to the base for changing a vertical elevation of the front and rear ends of the keyboard relative to each other; and wherein the elevation mechanism comprises a wedge slidably mounted to the front end of the base for engaging the front end of the keyboard and elevating the front end of the keyboard above the rear end of the keyboard.

2. A laptop computer, comprising:

a substantially horizontal base having a front end, a rear end, and two lateral side edges;
 a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;
 a keyboard mounted to the base and having a front end, a rear end, and left and right portions that are spaced apart from each other, each of the keyboard portions having a plurality of keys;
 an elevation mechanism mounted to the base for changing a vertical elevation of the front and rear ends of the keyboard relative to each other; and wherein the elevation mechanism comprises a cam member rotatably mounted to the front end of the base for engaging and elevating the front end of the keyboard above the rear end of the keyboard.

3. A laptop computer, comprising:

a substantially horizontal base having a front end, a rear end, and two lateral side edges;
 a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an

open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;

a keyboard mounted to the base and having a front end, a rear end, and left and right portions that are spaced apart from each other, each of the keyboard portions having a plurality of keys;

an elevation mechanism mounted to the base for changing a vertical elevation of the front and rear ends of the keyboard relative to each other; and wherein

the elevation mechanism comprises a plunger mounted to the front end of the base, the plunger being extensible for adjustably elevating the front end of the keyboard above the rear end of the keyboard.

4. A laptop computer, comprising:

a base having a front end and a rear end;
 a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;
 a keyboard mounted to the base and having a front end, a rear end, and a plurality of keys;
 an elevation mechanism mounted to the front end of base and having a retracted position for maintaining the keyboard in a substantially horizontal orientation, and a deployed position for selectively elevating the front end of the keyboard above the rear end of the keyboard; and wherein the elevation mechanism comprises a wedge slidably mounted to the base and having a ramp surface for slidably engaging the front end of the keyboard to elevate it above the rear end of the keyboard when in the deployed position.

5. The laptop computer of claim 4, further comprising a cover pivotally mounted between the front ends of the keyboard and the base, the cover having a substantially horizontal orientation when the wedge is in the retracted position, and the cover being inclined in an opposite direction to the ramp surface of the wedge when the wedge is in the deployed position.

6. A laptop computer, comprising:

a base having a front end and a rear end;
 a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;
 a keyboard mounted to the base and having a front end, a rear end, and a plurality of keys;
 an elevation mechanism mounted to the front end of base and having a retracted position for maintaining the keyboard in a substantially horizontal orientation, and a deployed position for selectively elevating the front end of the keyboard above the rear end of the keyboard; and wherein the elevation mechanism comprises a cam member rotatably mounted between the front ends of the base and the keyboard.

7. The laptop computer of claim 6 wherein the cam member comprises a cylindrical upper wedge mounted to the keyboard, and a cylindrical lower wedge mounted to the base, the wedges having mating cam surfaces that slidingly engage for moving the upper wedge between the retracted and deployed positions.

9

8. A laptop computer, comprising:
a base having a front end and a rear end;
a lid having a display monitor and pivotally mounted adjacent to the rear end of the base, the lid having an open position wherein it is pivoted away from the base, and a closed position wherein it is located adjacent to and faces the base;
a keyboard mounted to the base and having a front end, a rear end, and a plurality of keys;
an elevation mechanism mounted to the front end of base and having a retracted position for maintaining the keyboard in a substantially horizontal orientation, and

10

a deployed position for selectively elevating the front end of the keyboard above the rear end of the keyboard; and wherein

the elevation mechanism comprises an extensible plunger.

9. The laptop computer of claim **8** wherein the plunger has a base element mounted to the base and a telescopic elevation element mounted between the base element and the keyboard, the elevation element being movable to a plurality of vertical positions relative to the base and the base element.

* * * * *