



US006352287B2

(12) **United States Patent**
Casagrande

(10) **Patent No.:** **US 6,352,287 B2**
(45) **Date of Patent:** **Mar. 5, 2002**

(54) **APPARATUS AND METHOD FOR IMPROVED PATCH FOR BUSINESS FORMS WITH INTEGRATED CARDS**

4,479,838 A	10/1984	Dunsirn et al.	156/247
4,508,365 A	4/1985	Hawes	281/2
4,523,825 A	6/1985	Norris	354/301
4,544,590 A	10/1985	Egan	428/40
4,664,982 A	5/1987	Genovese et al.	428/447

(75) Inventor: **Charles L. Casagrande**, Batavia, IL (US)

(List continued on next page.)

(73) Assignee: **Strata-Tac, Inc.**, Batavia, IL (US)

FOREIGN PATENT DOCUMENTS

(* Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CA	1274979	10/1990	C09F/3/04
DE	4107469	9/1992	B65D/73/00
EP	0613792	9/1994	B42D/5/02
FR	2 691675	12/1993	B42D/15/10
GB	2209993	6/1989	B32B/7/06
JP	58 025 379	2/1983	C09J/7/02
JP	1214485	8/1989	B42D/15/02
JP	1285390	11/1989	B42D/15/02
JP	2121896	5/1990	B42D/15/04
WO	WO 90/11194	10/1990	B42D/15/02
WO	92/05036	2/1992	B42D/15/00

(21) Appl. No.: **09/849,906**

(22) Filed: **May 4, 2001**

Related U.S. Application Data

(63) Continuation of application No. 09/203,733, filed on Dec. 2, 1998, now abandoned.

(60) Provisional application No. 60/067,133, filed on Dec. 2, 1997.

(51) **Int. Cl.**⁷ **B32B 31/04; B32B 31/12**

(52) **U.S. Cl.** **283/81; 283/61; 283/62; 283/72; 283/79; 283/80; 283/94; 283/98; 283/100; 283/101; 283/105; 283/107; 283/108; 283/109; 40/638; 428/13; 428/40; 428/42; 428/43; 428/195; 428/914**

(58) **Field of Search** 283/79, 61, 80, 283/62, 81, 72, 94, 98, 100, 101, 105, 107, 108, 109; 40/638; 428/13, 40, 42, 43, 195, 914

Primary Examiner—Willmon Fridie, Jr.

Assistant Examiner—Mark T. Henderson

(74) *Attorney, Agent, or Firm*—Thompson Coburn LLP; Grant D. Kang; Robert C. Haldiman

(57) **ABSTRACT**


A planar form or structure is used to create a thin card capable of receiving and retaining printed indicia, including written signatures, on both opposing surfaces. The structure and related method allow the exposed carrier surface and the underlying release agent layer to receive and retain printed indicia, including written signatures, while retaining an extremely thin, yet tear-resistant, card structure. The release agent layer solidifies from a liquid to form a film capable of receiving and retaining printed indicia, written signatures, and the like which may be printed or written upon through the peeling away of the transparent lamina layer to expose the underlying release agent layer for receiving the indicia. The resulting structure preferably exhibits a flexibility due to its thickness lying within the range of 15–30 microns plus the thickness of the carrier.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,255,019 A	9/1941	Wolters et al.	156/268
2,896,351 A	7/1959	Johnson	40/702
3,166,186 A	1/1965	Karn	428/42.3
3,252,234 A	5/1966	Goodman	40/638
3,420,364 A	1/1969	Kennedy	206/460
3,996,679 A	12/1976	Warneke	40/1.5
4,248,919 A	2/1981	Davis	428/40

11 Claims, 2 Drawing Sheets



US 6,352,287 B2

Page 2

U.S. PATENT DOCUMENTS

4,742,954 A	5/1988	Shishido	229/92.8	5,318,326 A	6/1994	Garrison	283/101
4,837,088 A *	6/1989	Freedman	428/914	5,320,387 A	6/1994	Carlson	283/75
4,863,772 A	9/1989	Cross	428/40	5,328,538 A	7/1994	Garrison	156/249
4,868,152 A *	9/1989	Foulds et al.	428/914	5,362,106 A	11/1994	Longtin	283/109
4,890,862 A	1/1990	Buchholz	283/62	5,413,532 A	5/1995	Raby	462/2
4,910,058 A	3/1990	Jameson	428/42	5,439,255 A	8/1995	McIntire et al.	283/62
4,925,716 A	5/1990	Haas	428/41	5,462,488 A	10/1995	McKillip	462/26
5,002,312 A *	3/1991	Phillips et al.	283/72	5,466,013 A	11/1995	Garrison	283/107
5,007,191 A *	4/1991	Klein	40/638	5,580,640 A *	12/1996	Kraft et al.	428/914
5,039,652 A	8/1991	Doll et al.	503/206	5,589,025 A	12/1996	Garrison	156/268
5,042,842 A	8/1991	Green et al.	283/101	5,653,473 A *	8/1997	Laszutko et al.	283/81
5,049,443 A	9/1991	Kuszaj et al.	428/332	5,660,896 A	8/1997	Normand et al.	428/13
5,129,682 A	7/1992	Ashby	283/81	5,704,650 A *	1/1998	Laurash et al.	283/81
5,131,686 A	7/1992	Carlson	283/75	5,736,212 A	4/1998	Fischer	428/42.2
5,172,938 A	12/1992	Schmidt	283/109	5,916,665 A	6/1999	Fischer et al.	428/195
5,209,514 A	5/1993	Hebert	283/81	6,190,747 B1	2/2001	Fischer	428/42.2
5,219,183 A	6/1993	McKillip	283/62	6,217,078 B1 *	4/2001	Roth et al.	283/81
5,271,787 A	12/1993	Hoffman et al.	156/268				

* cited by examiner




Fig. 1




Fig. 2





Fig. 3




Fig. 4




FIG. 5

**APPARATUS AND METHOD FOR
IMPROVED PATCH FOR BUSINESS FORMS
WITH INTEGRATED CARDS**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

This is a continuation of U.S. application Ser. No. 09/203/733 filed Dec. 2, 1998, now abandoned, which claims priority to Ser. No. 60/067,133 filed Dec. 2, 1997.

**STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT**

None.

BACKGROUND OF THE INVENTION

This invention relates to an improved patch for business forms with integrated cards. It is quite common for businesses to use business forms which incorporate membership cards or other kinds of cards requiring the signature of the user, or other user indicia, to be added at the time of issuance. The part of the business form which houses the integrated card may be referred to as a patch. Patches traditionally consist of several layers of adhesive, transparent film and other chemical agents. In the business form industry, several problems continue to exist with the present state of the art of the patches utilized.

One major problem relates to the thickness of the patch. In many instances, the patch is so thick that laser printers cannot be used to print on the card. In addition, many of the patches have inconsistent release problems. In other words, end-users often have difficulty removing and/or detaching the card from the business form. Also, other techniques for making patches result in curling of the patches. Moreover, a recurring problem occurs with the use of pattern or dry edge glue application. To facilitate the removal of the card from the patch, adhesive is often applied in patterns, or alternatively, not applied near the edge of the patch. The disadvantage is the adhesive pattern often unattractively appears through the back of the card, after it has been removed from the business form. Finally, many of the existing patches result in a card that cannot be signed.

SUMMARY OF THE INVENTION

The present invention solves many of the problems presently faced by the business form industry by using a lamina-release agent and a thin bottom lamina, which results in a thin patch, easily and consistently released, without curling problems, and does not require pattern or dry edge adhesive application. Being relatively thin, the present invention works in more intricate paper path laser printers and can be produced much more economically than other patches in the industry. In addition, the present invention uses a film that may be manually signed by writing directly onto the film, or printed on using laser printing techniques.

One of the main advantages of the present invention stems from the lamina-release agent. The lamina-release agent is applied in liquid form, as a coating, but later solidifies into a film. The lamina-release agent may be composed of clear polyurethane, acrylic urethane, or any other substance which can be cured from liquid to solid and which performs substantially the same as the clear polyurethane, or the acrylic urethane, films. The use of a lamina-release agent has three purposes: it acts as the plastic laminate that remains on the back of the card; it acts as a dry release agent and detaches from the lamina; and its thickness results in obtain-

ing a signable surface. Thus, by using a lamina-release agent which functions both as a release and lamina, a minimal card thickness is obtained which was not possible with previous patches. Previously, patches use two layers to perform what the present invention does in a single layer.

Another advantage of the present invention is that the clear lamina, which may be a polyester film, at the bottom of the patch is relatively thin and pliable, being only 25 microns thick. Because of its minimal thickness, pattern and dry edge adhesive application is unnecessary. End-users can easily remove the card due to the large difference in stiffness between the upper layers and the bottom layer.

In a first preferred embodiment, the lamina with release agent layer and the permanent adhesive layer may not be necessary if the adhesive is machine applied as part of a manufacturing process.

In a second preferred embodiment, the bottom layer may be composed of any material which cures with the lamina-release agent on top of the bottom layer.

In a third preferred embodiment, in the manufacturing process, a portion of the bottom layer may be removed to expose part of the lamina-release agent. The portion may be removed by means of a dual slit across the width of the patch before the card is adhered to a business form. This permits imaging and duplex printing directly into the lamina-release agent.

BRIEF DESCRIPTION OF THE DRAWINGS

For the purpose of illustrating the invention, there is shown in the drawings forms which are presently preferred; it being understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

FIG. 1 is a cross-sectional view of the patch showing the several layers of the patch.

FIG. 2 is a cross-sectional view of the patch of FIG. 1 showing the layers of the patch.

FIG. 3 is a cross-sectional view of the patch of FIGS. 1 and 2 showing the removal of the card from the patch structure.

FIG. 4 is a diagrammatic view of the manufacturing process for attaching the patch to a business form.

FIG. 5 is a perspective view of an integrated card after separation.

**DETAILED DESCRIPTION OF THE
PREFERRED EMBODIMENTS**

The following detailed description is of the best presently contemplated mode of carrying out the invention. The description is not intended in a limiting sense, and is made solely for the purpose of illustrating the general principles of the invention. The various features and advantages of the present invention may be more readily understood with reference to the following detailed description taken in conjunction with the accompanying drawings.

Referring now to the drawings in detail, where like numerals refer to like parts or elements, there is shown in FIG. 1 a patch **10** initially comprised of the following four layers: a lamina with release agent **12**, a permanent adhesive **14**, a lamina-release agent **16**, and a clear lamina **18**. The layers are stacked with the lamina with release agent **12** being the top layer and the clear lamina **18** being the bottom layer. When the patch is manufactured, the lamina with release agent **12** is used to segregate the permanent adhesive

14 from the other layers of material when rolled and is peeled away during the manufacturing process, exposing the permanent adhesive layer **14** for bonding to the intended surface.

Once the lamina with release agent **12** is removed, the three remaining layers, **14**, **16** and **18**, act as a single unit and are adhered, for example, to the bottom of a paper business form **20**. As shown in FIG. 2, the patch then consists of four layers: a paper business form **20**, a permanent adhesive **14**, a lamina-release agent **16**, and a clear lamina **18**. The first three layers are then die cut at **22L** and **22R** in FIG. 2, through to the bottom of the lamina-release agent **16**. Related, opposed, parallel die cuts (not shown) are simultaneously cut into the patch **10** so as to form the desired geometric shape; in this case a rectangle with rounded corners to form the card C. The clear lamina **18** is not cut and is left attached to the bottom of the business form patch **20**.

As is shown in FIG. 3, once the business form **20**, i.e. the business form **20** with integrated card C, is die cut the pre-determined location for printing on the upperside or face of the card **20** is clearly shown. To facilitate printing or the addition of other elements to the underside of the card C, slits **24L**, **24R** may be added to the clear lamina **18** along the bottom of the patch **10**. In order that the card C does not detach from the business form **28**, a center slit **26** and corresponding opposing slits (not shown) are also placed in the clear lamina layer **18** so that approximately one-half of the card C may be exposed for the purposes of printing information or other indicia of use concerning the end-user prior to affixing a signature or other personal indicia to the card C. Each of these slits **24L**, **24R**, **26** may be either die cut or perforated so that the bottom side of card C can be exposed to the desired amounts. It should be noted that the slits **24L**, **24R** and **26** are positioned inward of the die cuts **22L**, **22R** so that the card C is not inadvertently dislodged from the business form **28** prior to the time when such disengagement is intended.

Referring again to FIG. 3, the integrated card C may be disengaged from the business form **28** by pushing upward from the bottom of the patch **10** (against the clear lamina layer **18**) so that the card C is disengaged with paper layer **20**, permanent adhesive layer **14** and lamina-release agent **16** integrated as a single unit, integrated card C. Integrated card C has a preferred thickness dimension of not more than 25 microns plus the thickness of the paper business form **20** to which the patch **10** is attached. Thus, the extremely thin dry lift integrated card [C] system which is described exhibits the characteristics of being extremely flexible, thin, but with significant resistance to tearing.

It is presently preferred that the lamina with release agent layer **12** be made of a silicon so as to act as a liner separating the remaining layers from the underlying clear lamina layer **18** when rolled for storage. The permanent adhesive layer **14** may be manufactured from any adhesive product presently known or later discovered which will create a permanent adhesion between the layers below (see FIGS. 1 and 2) and the business form (card) layer of FIG. 2. The lamina release agent **16** may be comprised of a coating of clear varnish polyurethane which has a preferred thickness of 0.75 mils, but may range between 0.5 and 1 mil. Other substances which have been found satisfactory for use as the lamina release agent **16** are acrylic urethanes and other compounds which exhibit similar properties of being liquid when applied as a coating and curing into a solid film after drying. The clear lamina layer **18** may be a clear polyester film having a nominal thickness of 1 mil so that there is no need to apply an additional layer of patterned or dry edge adhe-

sive to keep the card in position within the business form **28**. The integrated card C is readily disengagable from the business form **28** as it will pop out easily due to the significant difference in stiffness from the integrated card unit consisting of the top three layers **20**, **14** and **16** in contrast to the bottom layer **18** comprised of the extremely thin polyester film baseliner. Another significant feature of the integrated card C is that, in, addition to the dry release characteristics of the polyurethane coating (layer **16**), that layer (which is exposed when disengaged from the business form **28**), provides a surface which is not only signature compatible, **52**, but which will also accept printed indicia of the end user (**52**). See FIG. 5.

The present invention may be manufactured by feeding rolled business forms **28** into a manufacturing line **30**. The forms **28** may be fed into the line **30** so that the underside (or reverse side) of the form **28** is either inverted or right side up to match the placement of the patch **10** on that side. The patch material **10** is fed into the line from a large roll **32A** or **32B** located above or below the business form web, respectively, so that the patch **10** will be positioned juxtaposed the bottom side of the business form. The patch material **10** is then directed along the web **34** so as to come into contact with a vacuum/cutting unit **36A** or **36B** (located, respectively, above or below the web and adjacent the patch material) which peels off the lamina with release agent **12**, cuts the patch material **10** into appropriate dimensions, and presses (so as to adhere) the patch material **10** to the business forms **28** at pre-determined locations. One or more patches **10** may be adhered to the business form **28** in pre-determined locations as desired by the end-user. Next, the corporate business forms **28** continue to travel along the web **34** until reaching a die cutting station **38** which die cuts from the respective side of the business form through the business form **20**, the permanent adhesive layer **14**, and the lamina-release agent **16**. As the completed business forms with integrated cards C leave the line **30**, they may be rolled, folded or cut and sheeted for storage. The diagrammatic representation of FIG. 4 shows a cut sheet business form (with integrated card C) stack to be bundled for later use.

When end-users receive a business form with one or more integrated cards C, they may easily remove each integrated card C by peeling it away from the form **28**. The end-users may also manually sign, print or write on the bottom of the card as described above. The indicia which may be added to personalize the integrated card C, by adding printed and manually applied end-user information, may be selected from the group of indicia types including end-user name, address, signature, identification numbering, bar-code numbering, company logo and holographic images.

The present invention may be embodied in other specific forms without departing from the spirit or essential attributes thereof and, accordingly, the described embodiments are to be considered in all respects as being illustrative and not restrictive, with the scope of the invention being indicated by the appended claims, rather than the foregoing detailed description, as indicating the scope of the invention as well as all modifications which may fall within a range of equivalency which are also intended to be embraced therein.

I claim:

1. A planar structure with indicia thereon, the planar structure comprising:

at least four layers secured in overlying relation to each other and arranged from top to bottom including: a carrier having a pair of opposing, planar surfaces for carrying indicia thereon, an adhesive layer, a release agent layer, and a transparent lamina;

5

said release agent layer comprising a solidified liquid release agent, said release agent layer being printable on an exposed surface of said release agent layer;

the planar structure further comprising a multi-layer unit which includes the carrier, the adhesive layer, and the release layer;

wherein the planar structure is formed by manipulating the multi-layer unit from an initial position by separating the release agent layer from the underlying transparent lamina layer to release the multi-layer unit from a remainder portion;

whereby said exposed surface of said release agent layer becomes exposed such that said exposed surface is printable when said multi-layer unit is separated from the remainder portion.

2. The structure of claim 1, further comprising additional slits and ties contained in the transparent lamina, said slits and ties being within a perimeter of said multiple-ply unit and said slits and ties providing access to the release agent layer to receive printed indicia prior to and after separation from the remainder position.

3. An information carrying structure having a separable information carrying card comprising:

a paper layer having a top side for carrying information and a bottom side for carrying information;

an adhesive layer in adhesive contact with the bottom side of said paper layer, said adhesive layer being transparent;

a release agent layer having a top side in adhesive contact with said adhesive layer and a bottom side, said release agent layer being transparent and said release agent layer being printable on the bottom side upon exposure of the bottom side of said release agent layer;

a transparent lamina layer having a top side in releasable union with the bottom side of said release agent layer, and said transparent lamina layer having a bottom side; and

die cuts circumscribing an information carrying card, said die cuts extending through said paper layer and said adhesive layer and said release layer but not through said transparent lamina layer, such that an end user may separate the union between said release agent layer and said transparent lamina layer to remove a card defined by said die cuts from said information carrying structure.

4. An information carrying structure having a separable information carrying card of claim 3 wherein said transparent lamina layer includes openings exposing the release agent layer for receiving application of information on the bottom side of said release agent layer before separation of the union between said release agent layer and said transparent lamina layer.

6

5. The information carrying structure having a separable information carrying card of claim 3 wherein said adhesive layer and said release agent layer have a combined thickness between 15–30 microns.

6. The information carrying structure having a separable information carrying card of claim 3 wherein said lamina release agent layer has a thickness between 0.1 mil and 1 mil.

7. The information carrying structure having a separable information carrying card of claim 3 wherein said release agent is thicker than said transparent lamina layer.

8. The information carrying structure having a separable information carrying card of claim 3 wherein said release agent layer is made from material selected of the group consisting of varnish polyurethane and acrylic urethane.

9. The information carrying structure having a separable information carrying card of claim 3 wherein said transparent lamina layer is polyester.

10. The information carrying structure having a separable information carrying card of claim 4 wherein information received on said release agent layer is selected from the group consisting of end user name, address and signature, identification numbering, bar code numbering, company logo and holographic images.

11. An information carrying structure having a separable information carrying card comprising:

a paper layer having a top side for carrying information and a bottom side for carrying information;

an adhesive layer in adhesive contact with the bottom side of said paper layer, said adhesive layer being transparent;

a release agent layer having a top side in adhesive contact with said adhesive layer and a bottom side, said release agent layer being transparent and said release agent layer being printable on the bottom side upon exposure of the bottom side of said release agent layer;

a transparent lamina layer having a top side in releasable union with the bottom side of said release agent layer, and said transparent lamina layer having a bottom side; and said transparent lamina layer being less stiff than a combination of said release agent layer, said adhesive layer and said paper layer; and

die cuts circumscribing an information carrying card, said die cuts extending through said paper layer and said adhesive layer and said release layer but not through said transparent lamina layer, such that an end user may separate the union between said release agent layer and said transparent lamina layer to remove a card defined by said die cuts from said information carrying structure.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,352,287 B2
DATED : March 5, 2002
INVENTOR(S) : Charles L. Casagrande

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6,
Line 45 "caring" should be -- carrying --.

Signed and Sealed this

Twenty-third Day of April, 2002

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line drawn underneath it.

Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,352,287
DATED : March 5, 2002
INVENTOR(S) : Charles L. Casagrande

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6,
Line 45, "caring" should be -- carrying --.

Signed and Sealed this

Twenty-first Day of May, 2002

Attest:



Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office