



US006374976B1

(12) **United States Patent**
Alberni et al.

(10) **Patent No.:** **US 6,374,976 B1**
(45) **Date of Patent:** **Apr. 23, 2002**

(54) **HUB CLUTCH ASSEMBLY**

(75) Inventors: **Fred M. Alberni**, Bellevue, WA (US);
Joseph J. Maloney, Simpsonville, SC (US)

(73) Assignee: **Reliance Electric Technologies, LLC**,
Mayfield Heights, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/675,862**

(22) Filed: **Sep. 29, 2000**

Related U.S. Application Data

(60) Provisional application No. 60/160,232, filed on Oct. 18, 1999.

(51) **Int. Cl.**⁷ **F16D 13/72; F16D 25/08**

(52) **U.S. Cl.** **192/85 CA; 192/70.12; 192/113.34**

(58) **Field of Search** **192/85 CA, 113.34, 192/70.12, 110 B**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,038,575 A	*	6/1962	Hansen	192/85 CA
3,571,884 A		3/1971	Chung	29/200
3,804,219 A	*	4/1974	Cummings	192/85 CA X
3,805,933 A	*	4/1974	Pray	192/85 CA
4,000,793 A		1/1977	Chung	192/105
4,047,452 A		9/1977	Eddy	74/752
4,168,611 A		9/1979	Woyton et al.	60/413
4,189,962 A		2/1980	Chung	74/802

4,281,565 A		8/1981	Lower	74/789
4,411,590 A		10/1983	Meredith	415/26
4,574,926 A	*	3/1986	Bubak	192/70.12 X
4,899,861 A	*	2/1990	Cummings	192/110 B X
5,234,090 A	*	8/1993	Haka	192/85 CA X
5,513,728 A		5/1996	Alberni et al.	188/71.7
5,577,581 A	*	11/1996	Eberwein et al.	192/70.12 X

OTHER PUBLICATIONS

“BOSS Transmission Gold and Platinum Series 200KW–500KW” (no date available).
Talco Inc., Rotary Union On-Line Catalog 9300 Rotary Union, “Quality Craftsmanship For Greater Reliability” (no date available).

* cited by examiner


Primary Examiner—Rodney H. Bonck


(74) *Attorney, Agent, or Firm*—Patrick S. Yoder; Alexander M. Gerasimow; William R. Walbrun

(57) **ABSTRACT**

A power transmission assembly includes a first rotary housing and a second rotary housing disposed within the first housing. A piston housing is disposed between the first and second housing and does not rotate. A clutch plate stack is disposed adjacent to the piston assembly and is engageable to prevent relative rotation of the first and second housings with respect to one another. The rotary housings are supported by a bearing between the housings at one end, and by a series of bearings between the housings and the piston assembly at an opposite end. The arrangement enables the assembly to be supported as an overhung load, while actuating fluid is applied to the piston assembly via a non-rotating manifold.

20 Claims, 7 Drawing Sheets








Figure 2




Figure 4




Figure 5




Figure 6

HUB CLUTCH ASSEMBLY**CROSS REFERENCE TO RELATED APPLICATIONS**

The present is based upon a provisional patent application filed on Oct. 18, 1999 under Ser. No. 60/160,232, entitled "Hub Clutch Assembly."

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates generally to a fluid-actuated hub clutch for use in rotary mechanical transmission and drive systems. More particularly, the invention relates to a clutch device which can be interposed between driving and driven elements, such as on the low-speed side of a gear reducer, and which can be actuated, controlled and monitored via structures provided in a compact, self-contained package.

2. Description of the Related Art

A wide range of applications exist in industry for rotary power transmission devices which can be selectively coupled and uncoupled to a driven load. Power transmitted through such systems originates in a prime mover, such as an electric motor or an internal combustion engine. Power is output from the prime mover via a rotating shaft or hub which is, in turn, connected to a driven load. In many applications the torques and speeds output by the prime mover do not consistently match the requirements of the load, requiring a speed reducer between the prime mover and the driven load. Reducers of this type, typically including one or more stages of intermeshing gears, not only serve to adapt the prime mover speed, but amplify the torque output by the prime mover.

In addition to the prime mover and interfacing hardware for linking the prime mover to a driven load, many power transmission systems require the ability to selectively connect and disconnect the prime mover and the load. Various clutch devices have been proposed and are currently in use for this purpose. Depending upon the load requirements (i.e., torques and speeds passed through the clutch), such clutches may be actuated electrically, by pressurized fluid, by centrifugal structures, and so forth. For large or high inertia loads, such as those found in many industrial, material handling, mining, and similar applications, fluid clutches offer significant advantages of enhanced controllability and efficiency.

Rotary power transmission systems employed in many "heavy duty" applications must often respond to additional needs over and above those of simple torque and speed transmission. In particular, where very large loads are to be driven, inertial factors require that the power transmission systems be adapted to start and stop the loads progressively or in various controlled manners. To accommodate such needs, integrated gear reducers and clutch systems have been developed which offer both gear reduction and controllable fluid clutch operation in a single package. One integrated power transmission system of this type is commercially available from Rockwell Automation Power Systems, Dodge CST Division of Seattle, Washington. Systems of this type offer the significant advantage of permitting controlled starting and stopping of high inertial loads. Where desired, they may also be instrumented to provide for monitoring of loads, temperatures, speeds and so forth. Such integrated power transmission systems are particularly well suited to low-speed, high-inertia applications, such as con-

veyor drives in mining, timber, utility and other industries, as well as to other types of rotary drives such as trommel drives, ball mill drives, and so forth.

While integrated gear reducer and fluid clutch systems are suitable for many applications, in certain situations it would be useful to allow controllable fluid clutches to be installed independently of gear reducers, such as between the gear reducers and driven loads. In particular, there exists a need for a controllable fluid clutch system which can be interposed between a gear reducer coupled to a prime mover, and a driven load, in a separate package from the gear reducer itself. Such clutches would both permit greater flexibility in the selection of a gear reducer, as well as offer the possibility to retrofit existing systems with the improved clutch, while interfacing the retrofitted clutch with gear reducers and other power transmission hardware already in place.

Existing stand-alone fluid clutch systems are not well suited to satisfying these needs. For example, in one known system, a fluid clutch is interposed on a high-speed side of a gear reducer, and interface with the output shaft of a prime mover, and the input shaft of the gear reducer. The clutch package generally requires alignment of the prime mover shaft and the gear box shaft for proper operation. Moreover, provision of the clutch on the input side of the gear reducer limits the controllability of the power transmission system by interposing the multiple elements of the gear reducer between the controlled clutch and the ultimate load.

Other clutch systems have been proposed and are currently in use in which fluid used to actuate the clutch is channeled through a driven shaft. The shaft may be an integral part of downstream power transmission equipment, such as a belt pulley shaft. The actuating fluid is channeled from the shaft to a piston assembly within the fluid clutch which serves to engage and disengage clutch plates. Such structures are not well suited, however, for use with non-channeled shafts, severely limiting their utility in new and retrofit applications in which associated equipment is supplied with conventional (i.e., non-channeled shafting). Accordingly, there is a need for an improved controllable fluid clutch system in which actuating fluid is not required to be channeled through shafting of associated equipment.

In addition to the foregoing issues with clutched power transmission systems, problems often arise in the mating and mounting of the upstream and downstream power transmission components on either side of a clutch. In certain system designs, the clutch may even serve to support driving or driven components on an input or output shaft. In such cases, an extremely reliable and solid connection must be made between the supporting shaft and the clutch. In many cases, the mating elements are specifically machined to fit one another, with little interoperability offered between components of other sizes or configurations. There is also, therefore, a present need for an improved system for coupling a hub, such as a clutch hub, to an input or output shaft. There is a particular need for a system which can provide a sufficiently rigid and reliable connection to allow the clutch, and other components where desired, to be supported on the coupled shaft during operation.

SUMMARY OF THE INVENTION

The invention provides a controllable fluid-actuated clutch designed to respond to these needs. The clutch is formed with an inner hub assembly which may serve as either the input to the clutch or the output from the clutch, depending upon the application. The hub assembly is designed to receive conventional shafting, without the need

to direct actuating fluid through the shafting. A housing surrounds the inner hub and is designed to be coupled to another transmission element, either an input element or an output element, depending upon the application of the clutch. A clutch plate stack is provided between the hub assembly and the housing assembly. The clutch plates of the stack can be selectively engaged by fluid pressure to cause the housing and hub to rotate together, thereby transmitting power through the clutch. The clutch may also include features on the housing to permit it to be interfaced with specific types of drives, such as external gears, trommel drives and the like. The clutch may also be instrumented to provide monitoring and feedback signals representative of operational parameters of the mechanical and fluid components. The resulting structure is both compact and adaptable to both new and retrofit applications.

The clutch may serve as a coupling element between the driving and driven components. In a preferred configuration, an outer housing rotates with the first of the components, such as an output shaft from a gear box, while the hub rotates with an output shaft, such as a pulley shaft, or other driven load. A stationary, or static, piston housing is coupled to a manifold for routing fluids into and out of the clutch. The piston housing includes passages for actuating fluid used to engage and disengage the clutch plate stack, thereby causing engagement and disengagement of the outer housing with the hub. Additional passages in the manifold are provided for receiving and transmitting cooling fluid to internal regions of the clutch. Bearing assemblies between the outer housing, the piston housing, and the hub, support the housings and hub effectively with one another, providing adequate mechanical support for hanging a load or a prime mover supported on the input or output shaft.

In a presently preferred configuration, the clutch hub may be supported on shafts of various sizes via a tapered bushing and bushing adapter arrangement. The tapered bushing extends between the hub and the support shaft, with a support adapter being provided between the tapered bushing and the shaft for applications where the shaft dimensions do not match those of the inner dimensions of the tapered bushing. The tapered bushing may be installed with the adapter in a hydraulic coupling technique, so as to provide an extremely rigid and reliable connection of the hub and shaft with one another. A single size of clutch or hub may thus be employed with variously sized and configured shafts.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other advantages and features of the invention will become apparent upon reading the following detailed description and upon reference to, drawings in which:

FIG. 1 is an elevational end view of a pair of clutches in accordance with the present technique employed on an exemplary application, notably a conveyor drive;

FIG. 2 is a top plan view of the drive shown in FIG. 1;

FIG. 3 is a side elevational view of the conveyor drive of FIGS. 1 and 2, illustrating exemplary position and mounting structures for a support shaft driven by the clutch;

FIG. 4 is a partially sectioned end view of the clutch illustrating passageways for cooling and actuating fluids routed to and from the clutch during operation;

FIG. 5 is a sectional view through line B—B of FIG. 4, illustrating certain of the internal components of the clutch;

FIG. 6 is a sectional view of the clutch along line C—C of FIG. 4, illustrating additional internal components; and

FIG. 7 is an enlarged detailed view of a portion of the clutch illustrated in FIG. 6, showing in somewhat greater detail the internal components, as well as components of the tapered and adapter bushing mounting system;

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Turning now to the drawings, and referring first to FIG. 1, a clutch 10 is illustrated in two separate drive systems of a conveyor arrangement 12. Each clutch 10 is secured between driving components and the driven load. In the illustrated embodiment, the driving components include a motor assembly 14, and a gear reducer 16, an output shaft 18 of a gear reducer serving as the input shaft to each clutch 10 and a pulley 22, also supports the clutch and driving components in the illustrated embodiment. In the conveyor system illustrated, a continuous belt 24 is fed around the pulleys 22 in a conventional manner.

It should be noted that in the present description, reference is made to a conveyor system application for clutch 10. However, the present techniques, structures, and systems may be employed in a wide variety of applications, as well as over a substantial range of ratings and sizes. Moreover, while the present description relates specifically to embodiments in which the clutch is supported on an output shaft as an overhung load, the techniques described herein may also be employed for applications in which one or more of the components is foot mounted, flange mounted, and so forth. The clutch employed in the techniques described herein serves to couple driving and driven components to one another so that the components rotate at approximately the same speed upon full engagement of the clutch. In appropriate applications, the clutch arrangement may also be employed as a brake, with one or more of the input or output components described below being secured against rotation, such that engagement of the clutch causes the other component to be braked to a stop. Similarly, the clutch design described herein may be employed for coupling a gear reducer or other intermediate power transmission component to a driven load, or may be adapted for coupling directly to a prime mover, such as between a motor or engine and a gear reducer.

As illustrated in FIGS. 1, 2 and 3, the exemplary application in conveyor system 12 supports clutches 10 on a machine frame, designated generally by reference numeral 26. In such applications, bearing assemblies 28 will provide for sufficient mechanical support to allow shafts 20 to rotate freely when driven. Idler rollers 30 (see, e.g., FIGS. 2 and 3) may be provided in the conveyor system, along with one or more driven shafts such as in the illustrated embodiment. In applications where clutches 10 are employed for supporting driving components as an overhung load, the components may be positioned generally perpendicular to the centerline of the rotating components of the clutch, as illustrated. The resulting torque arm configuration is generally completed by one or more anti-rotation elements linked to the overhung load, to prevent rotation of the driving components and clutch, and thereby to transmit torque to the load.

Clutch 10 is preferably cooled and lubricated by auxiliary equipment provided adjacent to the load. In the illustrated embodiment, for example, a cooling oil circulation system 32 is provided for each clutch. As will be appreciated by those skilled in the art, such circulation systems typically include pumps, filters, reservoirs, and so forth, for drawing cooling fluid from the clutch, and returning clean and cooled

fluid to the clutch in continuous circulation. A heat exchanger system **34** is coupled to the cooling oil circulation system **32**, and extracts heat from the cooling oil before return to the clutch. Flanged cooling oil inlets and outlets are provided as indicated at reference numerals **36** and **38** in FIG. 2, and described more fully below.

FIG. 4 illustrates a partially sectioned clutch **10** from an end view. Clutch **10** includes an outer housing which rotates with the input shaft as described below. A stationary manifold **42** is supported concentrically within the housing, and serves to direct cooling and actuating fluids to and from the clutch. A box-like fluid conduit **44** is in fluid communication with manifold **42**, and is similarly stationary, for directing cooling oil to the clutch. A similar box-like fluid conduit **46** is secured to the manifold and conducts cooling oil from the clutch. An inlet conduit **48** is in fluid communication with conduit **44**, and a similar conduit **50** is in fluid communication with conduit **46**. Flanges **52** are provided on conduit **48**, with similar flanges **54** being provided on conduit **50**. Flanges **52** and **54** serve to receive sealed piping or hose assemblies (not shown) for conveying cooling fluid to and from the clutch. Depending upon the location and routing of such fluid, the piping components may be provided on one or both sides of the conduits, with an unused side of the conduit being capped.

Flow conduits **44** and **46** are in fluid communication with slotted routing apertures **56** and **58** of manifold **42**. In the illustrated embodiment, for example, two slotted apertures **56** are provided in fluid communication with conduit **44** for receiving cooling fluid and for routing the cooling fluid into internal regions of the clutch as described more fully below. Three similar apertures **58** are provided in fluid communication with outlet conduit **46**. An oil drain **60** is provided for collecting and recirculating portions of the cooling fluid which may escape the flow path established by conduit **44** and **46** as described below. In the illustrated embodiment, a speed pickup **62**, such as a magnetic or inductive proximity sensor is mounted on the manifold. The manifold assembly may serve to support other instrumentation (not shown), such as temperature sensors, pressure sensors, and so forth. Finally, manifold **42** is provided with one or more ports **64** for receiving actuating fluid used to engage the clutch elements as described below.

FIG. 5 illustrates a sectional view of clutch **10** along line B—B of FIG. 4. As shown in the view of FIG. 5, inlet conduit **48** communicates with flow conduit **44** to introduce cooling oil into the clutch, while conduit **50** communicates with conduit **46** to return oil for filtering and cooling. The conduits are stationary, and coupled to manifold **42**. The preferred configuration of the other components secured to the manifold and conduits is described more fully below.

Outer housing **40** is mechanically coupled to shaft **18** via a coupling **66** which, in turn, is bolted to an end plate **68**. End plate **68**, being fixed rigidly to outer housing **40**, causes housing **40** to rotate along with shaft **18** when the prime mover is activated. Shaft **20** is secured to a hub **70**, which serves as an output member of the clutch. Hub **70** is mounted coaxially within housing **40**, and rotates with housing **40** upon engagement of the clutch as described below.

Various arrangements may be provided for securing the mechanical components, including housing **40** and hub **70** to the input and output shafts. In the illustrated embodiment, hub **70** is secured to shaft **20** via a tapered bushing **72** and adapter ring **74** positioned between the hub and the shaft. The bushing and adapter ring are preferably mounted through a hydraulic coupling technique described in greater

detail below. An internal end of hub **70** is capped by a keeper plate **76**. A fastener **78** in the illustrated embodiment is used to draw the shaft **20** and hub **70** into an appropriate location with respect to one another during assembly. Fluid conduits **80** and **82** are provided in hub **70** and extend from an annular end of the hub to locations along the hub corresponding to the location of tapered bushing **72** when assembled. As described below, conduits **80** and **82** serve to provide a fluid bearing and to expand hub **70** during installation of the clutch on shaft **20**.

A piston housing **84** is secured between outer housing **40** and hub **70**, and is rigidly attached to manifold **42**. Piston housing **84**, like manifold **42**, is stationary, and serves both to support the outer housing and hub, and to route fluids for cooling and actuating the clutch. Piston housing **84** thus includes a fluid conduit **86** for routing cooling fluids from conduit **44** into an inner region **88** of the clutch. A similar cooling oil passage **90** formed within the piston housing **84** serves to recuperate cooling fluid and direct the fluid to conduit **46** for removal.

Piston housing **84** also supports an annular piston **92** which is sealed within the housing, but permitted to move axially along the housing for engagement and disengagement of the clutch. Piston **92** is positioned immediately adjacent to a clutch pressure plate **94** of similar annular configuration, and moves the clutch pressure plate axially for clutch engagement and disengagement. The piston **92** is sealed within housing **84** via seal sets **96** bounding a pressure application region or surface **98**. A fluid passage (not shown) is provided in piston housing **84**, between the actuating fluid inlet port **64** (see FIG. 4) and pressure application surface **98** for introducing and relieving pressurized fluid into the region between the piston housing and the piston.

While being permitted to move axially within the piston housing, piston **92** is prevented from rotating within the housing, thereby providing a non-rotating seal around the piston pressure application surface. In the illustrated embodiment, anti-rotation pins **100** are positioned between the piston and piston housing for preventing such rotation. The clutch pressure plate **94**, however, rotates with outer housing **40**, by securement to housing **40** via one or more anti-rotation pins **102**. One or more return springs **104** are positioned between the clutch pressure plate **94** and the outer housing **40** about pins **102**, to force disengagement of the clutch upon relief of pressure from the piston.

The piston housing **84**, piston **92**, and rotating clutch pressure plate **94** form a system for applying force to a clutch plate stack **106** positioned between outer housing **40** and hub **70**. As will be appreciated by those skilled in the art, clutch plate stack **106** includes a series of clutch plates alternatively associated with outer housing **40** and with hub **70**. A first of the clutch plates immediately adjacent to clutch pressure plate **94** preferably rotates with housing **40**. Each clutch plate includes recesses which mesh with projections or teeth **108** and **110** of the hub and of the outer housing, respectively. A backing plate **112** is positioned immediately adjacent to the last plate in the stack, preferably a plate movable with hub **70**.

The components set forth above are positioned within an inner region of the clutch between the housing **40** and hub **70**, bounded on one end by the manifold and piston housing, and on an opposite end by the keeper plate and end plate. Retaining collars **114** and **116** are positioned on either side of the hub, for retaining bearing assemblies, and for sealing the inner components of the clutch for circulation of cooling

fluid therein. In the illustrated embodiment, bearing assemblies are provided for solidly supporting the hub, piston housing, and outer housing on shaft **20**, while allowing for free rotation of these components with respect to one another. In particular, as best illustrated in FIG. **6**, a first bearing set **118** is positioned between outer housing **40** and piston housing **84** adjacent to one end of the clutch. A second bearing set **120** is positioned adjacent to an opposite end of the clutch, and permits relative rotation between the outer housing **40** and the hub **70**. The relatively large spacing between the positions of bearing assemblies **118** and **120** provides excellent resistance to moments applied to the clutch, particularly where the clutch is employed for supporting an overhung prime mover or load. A pair of bearing sets **122** and **124** are positioned between hub **70** and piston housing **84**. Finally, an additional bearing set **126** is positioned between the piston **92** and the clutch pressure plate **94**, and absorbs loading during actuation of the clutch, while permitting relative rotation between the stationary piston and the rotating clutch pressure plate. In a preferred configuration, fall engagement of the clutch provides some small difference in the input and output speeds between housing **40** and hub **70**, thereby maintaining slight relative motion within bearing set **120** to avoid damage to the bearing.

The internal components of clutch **10** are sealed via a series of sealing components positioned between the rotating and non-rotating members. In particular, in the illustrated embodiment, a first seal assembly **128** is provided between housing **40** and piston housing **84**, with a similar seal being provided between manifold **42** and collar **114**. Another annular seal **132** is provided between housing **140** and collar **116**. A further seal **134** is provided between manifold **42** and collar **114**. Finally, an external seal **136** is provided between housing **40** and the components defining the external surface of the manifold. The seals thus provide effective isolation of internal regions of the clutch from the outside environment, both precluding the ingress of contaminants, and retaining lubricating and cooling fluid within the clutch. Lubricating fluid which may bypass seal **128** is captured and drained via drain **64**. Also visible in FIGS. **6** and **7**, where a speed sensor **62** is provided, an appropriate toothed ring **138** may be positioned on collar **114** for providing pulsed signals indicative of the rotational speed of hub **70**. Similar arrangements may be provided for reading speeds of the outer housing **40**.

As noted above, the foregoing structure provides a clutch assembly which may be coupled directly between a driving shaft and a driven shaft. The clutch housing is extremely compact for the torque and speed ratings of the machine, with fluid passages being defined by the static assembly of the manifold, piston housing, and piston assembly. Moreover, the clutch engagement and disengagement technique provided by the arrangement offers the benefit of positive seals **96** which move only in an axial direction, with no rotary motion between the piston and piston housing. In addition, forces of engagement between the piston and the pressure plate are absorbed by the anti-friction bearing **126** secured between these components. The positioning of the other bearing assemblies thus provides all necessary mechanical support between the outer housing **40**, the piston housing **84**, and the hub **70**, while allowing these components to rotate freely with respect to one another.

The embodiment illustrated also facilitates extremely rigid and solid mounting of the hub **70** on the associated shaft **20**. FIG. **7** illustrates in somewhat greater detail the exemplary arrangement of these components within the embodiment. In particular, hub **70** has an inner diameter

which may be fixed for a range of shaft sizes. In the illustrated embodiment, output shaft **20** is a standard shaft configuration, having a right cylindrical outer surface **142**. However, where the shaft outer diameter, indicated by reference numeral **144** in FIG. **7**, is smaller than the internal diameter of hub **70**, and tapered bushing **72**, a combination of a tapered bushing **72** and an adapter ring **74** are employed to secure the components to one another. In the illustrated embodiment, tapered bushing **72** has a tapered outer surface **146** which conforms to a correspondingly tapered inner surface **148** of hub **70**. Seals **150** are received in grooves provided in the hub and in the tapered bushing, forming a sealed region therebetween.

For assembly, pressurized fluid is provided in passages **80** and **82** (see FIG. **5**), such as via a hand-operated hydraulic pump. The pressure thus is introduced at the interface of the tapered surfaces **146** and **148**, between seals **150**. With the adapter ring **174** and shaft **20** positioned within the tapered bushing, increasing pressure causes a fluid film to build slightly at the tapered surface interface, expanding hub **70** slightly, but sufficiently for the appropriate positioning of the tapered bushing, adapter ring, and shaft therein. The slight expansion of hub **70**, indicated by arrow **152** in FIG. **7**, is thus forced during assembly, with the tapered bushing, adapter ring, and shaft **20** being drawn into place, such as by fastener **78** bearing against keeper plate **76**, as indicated by arrow **154** in FIG. **7**. The components may, of course, be relatively positioned by alternative means, such as hydraulically. When the pressure between the hub and tapered ring is released, the hub contracts elastically back to its original dimensions, resulting in a very tight and rigid fit between the hub, the tapered bushing, the adapter ring **74**, and shaft **20**. The dimensions of the adapter ring **74** may be selected to provide the desired fit, depending upon the shaft configuration. Thus, clutch **10** may be employed in a variety of applications and on a variety of shaft sizes and configurations, with only the need to appropriately machine the adapter ring for the particular application. As will be appreciated by those skilled in the art, where adapter ring **74** is sufficiently large or rigid, a longitudinal slot or slots (not shown) may be provided partially or fully through the thickness of the ring to allow circumferential constraint of the ring under the force applied by the tapered bushing and hub.

While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown in the drawings and have been described in detail herein by way of example only. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

What is claimed is:

1. A power transmission assembly comprising:
 - a first housing rotatable with a first shaft;
 - a second housing disposed within the first housing and rotatable with a second shaft;
 - a clutch assembly disposed between the first and second housings and engagable to cause the first and second housings to rotate at generally the same speed; and
 - a non-rotating piston assembly disposed between the first and second housings and including a port which receives pressurized fluid for engagement of the clutch.
2. The assembly of claim **1**, wherein the piston assembly includes a non-rotating piston housing disposed between the

first and second housings, the piston housing channeling pressurized fluid to the piston during operation.

3. The assembly of claim 2, comprising a first bearing assembly disposed intermediate the first housing and the piston housing, a second bearing assembly disposed intermediate the first and second housings, and third and fourth bearing assemblies disposed intermediate the second housing and the piston housing.

4. The assembly of claim 3, wherein first and third bearing assemblies are generally concentrically disposed with respect to one another to transmit loading between the first and second housings via the piston housing.

5. The assembly of claim 1, further comprising a non-rotating manifold ported to direct cooling fluid through an interior volume between the first and second housings.

6. The assembly of claim 1, wherein the second housing includes a hub assembly configured to receive a shaft.

7. A power transmission clutch comprising:

a first rotary housing;

a second rotary housing disposed within the first rotary housing;

a clutch assembly disposed between the first and second rotary housings and engagable to cause the first and second rotary housings to rotate at generally the same speed;

a non-rotating piston assembly disposed between the first and second rotary housings and including a port for receiving pressurized fluid for engagement of the clutch;

a first bearing disposed between the first and second rotary housings;

a second bearing disposed between the first rotary housing and the non-rotating piston assembly; and

third and fourth bearings disposed between the non-rotating piston assembly and the second rotary housing.

8. The clutch of claim 7, wherein the second and third bearings are disposed generally concentrically with respect to one another to transmit loading between the first and second rotary housings.

9. The clutch of claim 8, wherein the piston assembly includes a non-rotating piston housing and a piston axially movable within the piston housing.

10. The clutch of claim 9, further comprising a fifth bearing disposed between the piston housing and the clutch assembly for exerting an actuating force on the clutch assembly while allowing the piston to remain non-rotating.

11. The clutch of claim 7, comprising a fluid passage extending into the piston assembly for delivery of pressur-

ized fluid to the piston assembly for engagement of the clutch, and wherein a sliding labyrinth seal is formed between the piston and the clutch assembly.

12. The clutch of claim 7, comprising a manifold configured to circulate cooling fluid through the clutch.

13. The clutch of claim 12, wherein the manifold is secured to a housing of the piston assembly.

14. The clutch of claim 13, wherein the manifold is concentric with the second rotary housing.

15. A power transmission assembly configured to be supported on a shaft, the clutch comprising:

a first rotary housing;

a second rotary housing rotatably supported within the first rotary housing adjacent to a first end thereof, and

an engagement assembly interposed between the first and second rotary housings and actuatable to provide substantially no respective rotational velocity between the first and second rotary housings; and

an actuation assembly interposed between the first and second rotary housings for actuating the engagement assembly, the second rotary housing being supported within the first rotary housing adjacent to a second end thereof opposite the first end via the engagement assembly.

16. The assembly of claim 15, wherein the second rotary housing is supported within the first rotary housing via a first bearing set disposed adjacent to the first end, and the second rotary housing is supported within the second rotary housing via a second bearing set disposed between the first rotary housing and the engagement assembly and by third and fourth bearing sets disposed between the engagement assembly and the second rotary housing.

17. The assembly of claim 15, wherein the engagement assembly includes a piston housing and a piston slidably disposed within the piston housing.

18. The assembly of claim 15, comprising a non-rotating manifold for transmitting actuating fluid to the engagement assembly.

19. The assembly of claim 18, wherein the manifold includes porting for circulating cooling fluid through the assembly.

20. The assembly of claim 15, wherein the engagement assembly includes a plurality of clutch plates interleaved and engageable with one another under the influence of the engagement assembly.

* * * * *