



US006384883B1

(12) **United States Patent**  
**Ueda et al.**

(10) **Patent No.:** **US 6,384,883 B1**  
(45) **Date of Patent:** **May 7, 2002**

(54) **LIQUID CRYSTAL DISPLAY DEVICE USING A HOLOGRAM, HOLOGRAM SCATTER PLATE, AND PROCESS OF REPLICATING A DIFFUSE REFLECTION TYPE HOLOGRAM**

(75) Inventors: **Kenji Ueda; Hideyuki Iriyama; Akio Morii**, all of Tokyo (JP)

(73) Assignee: **Dai Nippon Printing Co., Ltd.**, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

5,453,338 A	*	9/1995	Suga et al.	430/1
5,499,118 A	*	3/1996	Wreede et al.	359/12
5,506,701 A		4/1996	Ichikawa	349/15
5,594,560 A	*	1/1997	Jelley et al.	359/15
5,629,784 A	*	5/1997	Abileah et al.	349/112
5,659,408 A		8/1997	Wenyon	349/112
5,691,790 A	*	11/1997	Havens et al.	349/113
5,721,600 A		2/1998	Sumiyoshi et al.	349/119
5,721,630 A	*	2/1998	Horner et al.	359/15
5,731,108 A	*	3/1998	Biles	430/1
5,745,203 A		4/1998	Valliath et al.	349/113
5,798,850 A	*	8/1998	Ishikawa et al.	359/12
5,812,229 A	*	9/1998	Chen et al.	349/113
5,843,598 A	*	12/1998	Ueda et al.	430/602
6,127,066 A	*	10/2000	Ueda et al.	430/1

(21) Appl. No.: **09/482,615**

(22) Filed: **Jan. 14, 2000**

**Related U.S. Application Data**

(62) Division of application No. 08/758,093, filed on Nov. 27, 1996, now Pat. No. 6,075,579.

**(30) Foreign Application Priority Data**

Nov. 30, 1995	(JP)	7-312361
Nov. 30, 1995	(JP)	7-312362
Dec. 12, 1995	(JP)	7-322973
Jan. 22, 1996	(JP)	8-008531
Jan. 22, 1996	(JP)	8-008532

(51) **Int. Cl.**<sup>7</sup> ..... **G02F 1/1335; G03H 1/20; G03H 1/04; G02B 5/32**

(52) **U.S. Cl.** ..... **349/112; 349/64; 349/106; 359/12; 359/15; 430/1**

(58) **Field of Search** ..... **349/64, 112, 106; 359/15, 16, 599, 12, 24; 430/1, 2**

**(56) References Cited**

**U.S. PATENT DOCUMENTS**

3,647,289 A	*	3/1972	Weber	355/2
4,239,349 A	*	12/1980	Schaffer	350/347 R
4,285,029 A	*	8/1981	McCoy	362/84
4,660,936 A	*	4/1987	Nosker	350/339 R
4,968,108 A	*	11/1990	Ikeda et al.	350/3.7
4,984,872 A		1/1991	Vick	359/15
5,046,793 A		9/1991	Hockley et al.	359/12
5,333,073 A		7/1994	Suzuki	

**FOREIGN PATENT DOCUMENTS**

JP	1-152486	*	6/1989
JP	7-92328	*	4/1995
JP	8-240868	*	8/1996
JP	8-334752	*	12/1996
JP	9-138396	*	5/1997
JP	09-211452 A	*	8/1997
JP	9-281477	*	10/1997

\* cited by examiner

*Primary Examiner*—William L. Sikes

*Assistant Examiner*—Tarifur R. Chowdhury

(74) *Attorney, Agent, or Firm*—Sughrue Mion, PLLC

**(57) ABSTRACT**

The invention relates to a liquid crystal display device which enables a visual field range to be made wide and luminance drops to be reduced, so that bright displayed images can be presented, and provides a liquid crystal display device comprising, in order from a side of backlight **11**, backlight **11**, scatter plate **12**, and liquid crystal element **20**, wherein a transmission type of hologram scatter plate **13** is located in front of a display surface of liquid crystal display element **20**. Hologram scatter plate **13**, because of having been fabricated by means of single-step or two-step exposure, enables light more or less scattered through scatter plate **12** to be limitedly scattered within a given wide visual field range, so that bright displayed images can be presented over a wide visual field range yet with a reduced luminance drop. Scatter plate **12** may be omitted.

**6 Claims, 12 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5 (a)




FIG. 5 (b)






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG.11 (a)




FIG.11 (b)




FIG.11 (c)






FIG. 12




FIG. 13




FIG. 14




FIG. 15 (a)




FIG. 15 (b)




FIG. 15 (c)




FIG. 16




FIG. 17(a)




FIG. 17(b)




FIG. 18 PRIOR ART




FIG. 19 (a)





FIG. 19 (b)





**LIQUID CRYSTAL DISPLAY DEVICE USING  
A HOLOGRAM, HOLOGRAM SCATTER  
PLATE, AND PROCESS OF REPLICATING A  
DIFFUSE REFLECTION TYPE HOLOGRAM**

This application is a DIV. of Ser. No. 08/758,093 filed Nov. 27, 1996 now U.S. Pat. No. 6,075,579.

**BACKGROUND OF THE INVENTION**

The present invention relates generally to a liquid crystal display device, and more specifically to a liquid crystal display device using a hologram diffuse plate. The present invention is also concerned with a hologram scatter plate used for liquid crystal display devices, etc., and process of replicating a such a diffuse reflection type hologram.

Referring here to a direct-view type of liquid crystal display device, a scatter plate **12** is generally located on the side of a liquid crystal display element **20** opposite to a backlight **11** to diffuse light emanating therefrom, as shown in FIG. **18**, thereby widening a range capable of viewing an image displayed thereon (a visual field range).

A problem with this system is, however, that the efficiency of utilization of light is not high due to the use of a general scatter plate formed of frosted glass, and the angle of field is limited as well. The angle of field may be made wide by use of a plurality of scatter plates, but this offers a problem or gives rise to some considerable luminance drop.

A self-luminous type backlight consumes very large power, and brings about some considerable battery driving time reduction when used with laptop type computers, etc.

**SUMMARY OF THE INVENTION**

In view of such problems associated with the prior art, an object of the present invention is to provide a liquid crystal display device which has a wide visual field range and reduced luminance drops, so that bright displayed images can be presented.

Another object of the present invention is to provide a liquid crystal display device which uses a diffuse reflection type hologram for backlighting so that bright displays can be presented in the light without recourse to any self-luminous backlight. Yet another object of the present invention is to provide a liquid crystal display device which can be used in combination with a self-luminous type backlight, so that battery life can be extended by turning off the self-luminous type backlight or using the self-luminous type backlight at a reduced luminance.

A further object of the present invention is to provide a hologram scatter plate enabling bright displayed images to be presented over a wide range of wavelengths and viewing angle hardly achievable with conventional hologram systems.

A still further object of the present invention is to provide a process of fabricating, by replication, a large diffuse reflection type hologram without joints or recorded joints, which is compatible with increased size and improved quality in connection with backlights, projector screens, combiners, etc. for liquid crystal display devices.

To accomplish the aforesaid objects, the present invention provides a liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a display surface side thereof with a diffuse transmission type hologram capable of diffusing and transmitting light incident from a specific direction only in a direction defined as a viewing region.

In this case, a scatter plate may be located between the liquid crystal display element and a backlight.

The present invention also provides a liquid crystal display device using a hologram, characterized in that between a liquid crystal display element and a backlight there is located a diffuse transmission type hologram capable of diffusing and transmitting light incident from a specific direction only in a direction defined as a viewing region.

In these cases, it is desired that the diffuse transmission type hologram has a property of diffusing and transmitting light only in a direction defined as a viewing region within a plurality of wavelength regions of different colors.

Further, the present invention provides a liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a back surface side thereof opposite to a display surface side thereof with a diffuse reflection type hologram capable of diffusing and reflecting light incident from a specific direction only in a direction defined as a viewing region.

In this case, a diffuse reflection plate or a reflector plate may be located on the back surface side of the diffuse reflection type hologram.

When a TN liquid crystal cell is used as the liquid crystal display element, the diffuse reflection type hologram enables diffuse reflection to occur within a range wherein the contrast of the liquid crystal cell is at least 2. When an STN liquid crystal cell is used as the liquid crystal display element, the diffuse reflection type hologram enables diffuse reflection to occur within a range wherein the contrast of the liquid crystal cell is at least 2.

More illustratively, when a TN liquid crystal cell is used as the liquid crystal display element, it is desired that the diffuse reflection type hologram enable light incident thereon from above and at an angle of about 20° with respect to a normal line thereof to be diffused and reflected within a range defined by an upward angle about 10°, a downward angle of about 40°, and breadth-wise angles of about 60°. When an STN liquid crystal cell is used as the liquid crystal display element, it is desired that the-diffuse reflection type hologram enable light incident thereon from above and at an angle of about 20° with respect to a normal line thereof to be diffused and reflected within a range defined by an upward-angle about 20°, a downward angle of about 30°, and breadth-wise angles of about 30°.

A self-luminous type backlight unit may be located on the back surface side of the diffuse reflection type hologram.

To accomplish the aforesaid objects, the present invention provides a hologram scatter plate which reflects incident light in a direction different from a direct reflection direction thereof, characterized in that a transmission type hologram layer and a back side layer are stacked together in the described order as viewed from an incident side thereof.

In accordance with this aspect, there are three cases where the transmission type hologram layer has both a diffusion function and a diffraction function while the back side layer is a mirror reflection layer; the transmission type hologram layer has diffraction function while the back side layer has a diffuse reflection function; and the transmission type hologram layer has both a diffusion function and diffraction function while the back side layer has diffuse reflection function.

The transmission type hologram layer used may have a diffraction function, or a diffusion function and diffraction function, with respect to a plurality of different wavelengths.

The present invention also includes a liquid crystal display device having any one of the aforesaid hologram scatter



plates located on a back surface side of a liquid crystal display element.

To accomplish the aforesaid objects, the present invention further provides a diffuse reflection type hologram replication process, characterized in that while a photosensitive material film is slid on a fixed diffuse reflection type hologram plate in contact relation thereto, the hologram plate is irradiated from the photosensitive material film with a light beam of linear shape in section that becomes wide in a widthwise direction of the film, so that a diffuse reflection type hologram can be continuously recorded in the photosensitive material film by interference of the incident light beam with a light beam reflected and diffracted by the diffuse reflection type hologram plate.

In this case, it is preferable that the diffuse reflection type hologram plate is fixed on the surface of a transparent rod-like member rounded at least both edges thereof. Such a transparent rod-like member may be exemplified by a semicylindrical member.

It is also desired that a combined index matching and lubricating liquid be contained between the diffuse reflection type hologram plate and the photosensitive material film.

The light beam of linear shape in section used may be exemplified by a light beam that diverges in its linear direction alone.

According to one inventive liquid crystal display device using a hologram wherein on a display surface side of a liquid crystal display element or between a liquid crystal display element and a backlight there is provided a diffuse transmission type hologram capable of diffusing and transmitting light incident from a specific direction only in a direction defined as a viewing region, it is possible to make wide a visual field region where displayed images can be observed and reduce luminance drops, so that bright displayed images can be presented.

According to another inventive liquid crystal display device using a hologram wherein on a back surface side of a liquid crystal display element opposite to a display surface side thereof there is provided a diffuse reflection type hologram capable of diffusing and reflecting light incident from a specific direction only in a direction defined as a viewing region as mentioned above, it is possible to present bright displays in the light without recourse to any self-luminous type backlight.

According to the inventive hologram scatter plate wherein a transmission type hologram layer and a back side layer are stacked together in the described order, it is possible to limit the direction of diffraction and scattering by means of the transmission hologram and increase reflectance over a wide wavelength region by means of the back side layer, so that diffused light having high luminance can be obtained over a wide wavelength and viewing angle range, making bright displays, etc. possible.

According to the inventive diffuse reflection type hologram replication process wherein while a photosensitive material film is slid on a fixed diffuse reflection type hologram plate in contact relation thereto, the hologram plate is irradiated from the photosensitive material film with a light beam of linear shape in section that becomes wide in a widthwise direction of the film, so that a diffuse reflection type hologram can be continuously recorded in the photosensitive material film by interference of the incident light beam with a light beam reflected and diffracted by the diffuse reflection type hologram plate, it is possible to easily fabricate, with no need of using any large hologram plate, a large yet continuous film form of diffuse reflection type

hologram without joints or recorded joints, which has high reflectance and quality, and so is best suited for use with backlights, projector screens, combiners, etc. for liquid crystal display devices.

Still other objects and advantages of the invention will in part be obvious and will in part be apparent from the specification.

The invention accordingly comprises the features of construction, combinations of elements, and arrangement of parts which will be exemplified in the construction hereinafter set forth, and the scope of the invention will be indicated in the claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional schematic of one embodiment of the liquid crystal display device according to the present invention.

FIG. 2 illustrates one optical layout for recording a hologram scatter plate by a single-step exposure technique.

FIG. 3 illustrates another optical layout for recording a hologram scatter plate by the single-step exposure technique.

FIG. 4 illustrates yet another optical layout for recording a hologram scatter plate by the single-step exposure technique.

FIG. 5(a) and FIG. 5(b) illustrate an optical layout for recording a hologram scatter plate by a two-step exposure technique.

FIG. 6 is a sectional schematic of one embodiment of the inventive liquid crystal display device using a diffuse reflection type hologram.

FIG. 7 is a sectional schematic of another embodiment of the inventive liquid crystal display device.

FIG. 8 illustrates an optical layout for recording an intermediate hologram for the fabrication of a diffuse reflection type hologram.

FIG. 9 illustrates an optical layout for recording a diffuse reflection type hologram using the intermediate hologram.

FIG. 10 illustrates one exemplary layer structure of a diffuse reflection type hologram plate and an optical layout for replication from the same.

FIG. 11(a) to FIG. 11(c) illustrate schematically the construction and action of the hologram scatter plate according to the present invention.

FIG. 12 illustrates a method of recording one transmission type hologram used in the present invention.

FIG. 13 illustrates a method of recording another transmission type hologram used in the present invention.

FIG. 14 illustrates a layout for carrying out the replication process of a diffuse reflection type hologram according to the present invention.

FIG. 15(a) to FIG. 15(c) illustrate how to assemble a hologram plate support used in the layout shown in FIG. 1.

FIG. 16 illustrates how to make a diffuse reflection type hologram plate by means of the single-step holography technique.

FIG. 17(a) and FIG. 17(b) illustrates how to make a diffuse reflection type hologram plate by means of the two-step holography technique.

FIG. 18 is a sectional schematic of a conventional liquid crystal display device.

FIG. 19(a) and FIG. 19(b) illustrates a conventional layout for making a diffuse reflection type hologram by a replication technique.



DESCRIPTION OF THE PREFERRED  
EMBODIMENTS

Embodiments of the inventive liquid crystal display device using a hologram, the inventive hologram scatter plate and the inventive process of fabricating a diffuse reflection type hologram will now be explained.

FIG. 1 is a sectional schematic showing one embodiment of the liquid crystal display device according to the present invention, which is similar to a conventional device shown in FIG. 6 in that a backlight 11, a scatter plate 12 and a liquid crystal display element 20 are located in the described order, as viewed from the side of the backlight 11. According to the present invention, a transmission type of hologram scatter plate 13 is located in front of a display surface of the liquid crystal display element 20. The hologram scatter plate 13 is fabricated by means of single-step or two-step exposure techniques which will be described later. The thus produced hologram scatter plate enables light more or less scattered through the scatter plate 12 to be limitedly scattered within a given wide visual field range. Accordingly, bright displayed images can be presented over a wide visual field range with little or no luminance reduction. The liquid crystal display element 20 used herein, for instance, comprises a twisted nematic or other liquid crystal layer 25 sandwiched between two glass substrates 21 and 22, one glass substrate 22 having a uniform opposite electrode 24 on its inner surface and the other glass substrate 21 having on its inner surface independent display electrodes 23 for each liquid crystal cell (R, G, B), and a color filter and a black matrix, although not illustrated. The electrodes 23 and 24 are also provided with orientation layers on their sides opposite to the liquid crystal layer, although again not illustrated. Further, the glass substrate 21 is provided with a polarizing plate 26 on its outer surface while the glass substrate 22 located on the viewing side is provided with a polarizing plate 27 on its outer surface, with their transmission axes perpendicular to one another, for instance. Voltage applied between the transparent display electrodes of the liquid crystal display element 20 is controlled per pixel to change the state of transmission, thereby displaying color images. It is noted here that the hologram scatter plate 13 may have been removed from the position shown in FIG. 1, and alternatively located between the backlight 11 and the liquid crystal element 20.

How to make the transmission type hologram scatter plate 13 used in the instant embodiment by means of holography will now be explained.

The visual field range of a liquid crystal display device is dependent on the angle of diffusion of the hologram scatter plate 13. The smaller the angle of diffusion, the more difficult it is to look at a displayed image. To eliminate this problem, a hologram is recorded in a desired preset visual field range only where scattering and diffraction take place. Single-Step Exposure

FIG. 2 is a schematic illustrative of a holographic layout designed to set a visual field (range) in the vertical direction of the hologram scatter plate 13. A scatter plate 2 is irradiated with laser light 3 from its back side to define scattered light as object light and transmitted light without being scattered as reference light 4, which are then allowed to interfere with each other in a hologram dry plate 1 for recording, thereby making the hologram scatter plate 13. In this case, the scatter plate 2 must be larger than the hologram dry plate 1, because the visual field region (range) of the hologram scatter plate 13 located at the position of the hologram dry plate 1 is then defined by the region of the scatter plate 2.

FIG. 3 is again a schematic illustrative of a holographic layout designed to set a visual field (range) in the vertical direction of the hologram scatter plate 13. A scatter plate 2 is irradiated with laser light 3 from its back side to define scattered light as object light and light incident via a half mirror located between the scatter plate 2 and a hologram dry plate 1 as reference light 4, which are then allowed to interfere with each other in the hologram dry plate 1 for recording, thereby making the hologram scatter plate 13. In this case, too, the scatter plate 2 must be larger than the hologram dry plate 1, because the visual field region (range) of the hologram scatter plate 13 located at the position of the hologram dry plate 1 is defined by the region of the scatter plate 2. The layout shown in FIG. 3 is advantageous over the layout shown in FIG. 2 because it is easier to regulate the light quantity ratio between object light and reference light, and increase the parallelism of reference light 4.

FIG. 4 is a schematic illustrative of a holographic layout designed to determine a visual field in an oblique direction with respect to a hologram scatter plate 13. One or more scatter plates 2, 2' are located at an off-axis position with respect to a hologram dry plate 1. The scatter plates 2 and 2' are then irradiated with laser light 3 and laser light 3' from their back sides, from which scattered light or object light is obliquely incident on the hologram dry plate 1 and reference light 4 is straightforward incident on the hologram dry plate 1. The object light and reference light are then allowed to interfere with each other in the hologram dry plate 1 for recording, thereby making the hologram scatter plate 13. In this case, too, the scatter plates 2 and 2' must be larger than the hologram dry plate 1, because the visual field region (range) of the hologram scatter plate 13 located at the position of the hologram dry plate 1 is defined by the regions of the scatter plates 2 and 2'. In the layout shown in FIG. 4, exposure is done concurrently with the scatter plates 2, 2'. It is to be understood, however, that recording may be carried out by means of multi-exposure while the scatter plates 2, 2' are located the specified positions in a given time interval. Two-Step Exposure

According to this process, an intermediate hologram H1 is first recorded, and the thus recorded intermediate hologram H1 is then used to record a hologram scatter plate 13 that is the end hologram H2. As shown in FIG. 5(a), a scatter plate 2 located in opposition to a hologram dry plate 1 for the intermediate hologram H1 is irradiated with laser light 3 from its back side, from which scattered light or object light is incident on the hologram dry plate 1 and, at the same time, reference light 4 is obliquely incident on the hologram dry plate 1. Both object light and reference light are allowed to interfere with each other in the hologram dry plate 1 to record the intermediate hologram H1.

As shown in FIG. 5(b), the aforesaid intermediate hologram H1 is then used to allow the reconstructing scattered light and reference light to interfere with each other in a hologram dry plate 1' for the end hologram H2 to record the hologram scatter plate 13. In this case, the region of the intermediate hologram H1 with respect to the hologram dry plate 1' defines the visual field region (range) of the hologram scatter plate 13 located at the position of the hologram dry plate 1'. Recording is carried out by irradiating the intermediate hologram H1 using, as reconstructing illumination light, light 4' that is conjugate with respect to reference light 4 used for recording the intermediate hologram H1. The thus scattered light or object light is incident on the hologram dry plate 1' simultaneously with the straightforward incidence of reference light 4" thereon, so that both object light and reference light can interfere with each other



in the hologram dry plate 1' to obtain the end hologram scatter plate 13. It is here to be noted that, as is the case with the aforesaid single-step exposure, three processes may be envisaged for reference light 4" for making the end hologram H2 (FIGS. 2 to 4).

Illustrative examples of-recording the hologram scatter plate 13 as shown in FIGS. 2 to 5 will now be explained.

#### ILLUSTRATIVE EXAMPLE 1

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form the hologram dry plate 1. Using the optical system shown in FIG. 2, hologram recording was carried out under the following conditions:

Size of scatter plate 2: 60 cm×80 cm

Size of hologram dry plate 1: 6 cm×8 cm

Distance between scatter plate 2 and dry plate 1: 30 cm  
Laser light 3, 4: 514.5 nm wavelength (argon laser)

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between object light and reference light 4: approximately 1:1

The hologram recorded under such conditions was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain a hologram scatter plate having a visual field in one prescribed direction and capable of achieving bright scattering.

#### ILLUSTRATIVE EXAMPLE 2

A hologram photosensitive material (Omnidex 706 made by Du Pont) was applied on a glass substrate to form the hologram dry plate 1. Using the optical system shown in FIG. 3, hologram recording was carried out under the following conditions:

Size of scatter plate 2: 60 cm×80 cm

Size of hologram dry plate 1: 6 cm×8 cm

Distance between scatter plate 2 and dry plate 1: 30 cm

Laser light 3, 4: 457 nm wavelength (argon laser: B)  
: 550 nm wavelength-(dye laser: G)  
: 647 nm wavelength (krypton laser: R)

Reference light 4: Vertical incidence/parallel light turned back by half-mirror 5

Object light: Vertical incidence/light scattered by scatter plate 2

Exposure: 60 mJ/cm<sup>2</sup> (exposure ratio between R, G and B: 3:2:1) (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between object light and reference light 4: approximately 1:1

The hologram recorded under such conditions was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain a hologram scatter plate having a visual field in one prescribed direction and capable of achieving bright yet white scattering.

#### ILLUSTRATIVE EXAMPLE 3

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form the hologram dry plate 1. Using the optical system shown in FIG. 4, hologram multi-recording was carried out under the following conditions:

Size of scatter plates 2, 2': 60 cm×80 cm

Size of hologram dry plate 1: 6 cm×8 cm

Distance between scatter plates 2, 2' and dry plate 1: 50 cm

Laser light 3, 4: 514.5 nm wavelength (argon laser)

Reference light 4: Vertical incidence/parallel light

Object light (first incidence): Incidence at +30°/light scattered by scatter plate 2'

Object light (second incidence): Incidence at -30°/light scattered by scatter plate 2'

Exposure: First exposure at 5 mJ/cm<sup>2</sup>

Second exposure at 15 mJ/cm<sup>2</sup>

(both at an intensity of 1 mW/cm<sup>2</sup>)

The hologram recorded under such conditions was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain a hologram scatter plate having a visual field in two prescribed directions and capable of achieving bright scattering.

#### ILLUSTRATIVE EXAMPLE 4

A hologram photosensitive material (8E56 made by AGFA) was applied on a glass substrate to form a hologram dry plate. Using the optical system shown in FIG. 5(a), the intermediate hologram H1 was recorded under the following conditions:

Size of scatter plate 2: 6 cm×8 cm

Size of hologram dry plate 1: 60 cm×80 cm

Distance between scatter plate 2 and dry plate 2: 30 cm

Laser light 3, 4: 514.5 nm wavelength (argon laser)

Reference light 4: Incidence at 40°/parallel light

Object light: Vertical incidence/light scattered by scatter plate 2

Exposure: 150 μJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between object light and reference light 4: approximately 1:1

Then, a hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form the hologram dry plate 1'. Using the optical system shown in FIG. 5(b), the end hologram H2 was recorded under the following conditions:

Size of intermediate hologram H1: 60 cm×80 cm

Size of hologram dry plate 1': 6 cm×8 cm

Distance between intermediate hologram H1 and hologram dry-plate 1': 30 cm

Laser light 4', 4'': 514.5 nm wavelength (argon laser.)

Reference light 4'': Vertical incidence/parallel light

object light: Incidence at 40°/light reconstructed from intermediate hologram H1

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between object light and reference light 4'': approximately 1:1

The hologram recorded under such conditions was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain a hologram scatter plate having a visual field in one prescribed direction and capable of achieving bright scattering.

Another embodiment of the inventive liquid crystal display device using a hologram will now be explained.

According to the principle of this embodiment wherein the diffusion range of a diffuse reflection type hologram used as a backlight is in alignment with a practical viewing range of the liquid crystal display device, it is possible to achieve bright displays without making narrow the viewing region that the liquid crystal display device has.

Reference is first made to a diffuse reflection type hologram designed such that light incident thereon from a specific direction is diffused and reflected in only a direction



defining a viewing region. A hologram having scatter function is known as a Lippmann hologram using a scatter plate in the form of a subject from an article entitled "Holographic and Interferometric Viewing Screens" (by Dietrich Keyerhofer, APPLIED OPTICS/Vol. 12, No. 9/September 1973), U.S. Pat. No. 5,046,793, etc. To limit the viewing region of the diffuse reflection type hologram used in the present invention, processes ordinarily used for Lippmann holograms are used.

To make the diffuse reflection type hologram, a subject or diffuse plate **42** formed of frosted glass is assumed to be located at a position where a backlight forming a part of a liquid crystal display device is to be located, as shown in FIG. 8. A transmission type of hologram dry plate **45** is then located at a position to define a practical viewing region, whereupon the scatter plate **42** is illuminated from its back side with one coherent light **41** of given wavelength obtained by halving light emanating from the same light source, so that scattered light **43** leaving the front side of the scatter plate **42** or object light can be incident on the transmission type of hologram dry plate **45**. At the same time, another coherent light of given wavelength emanating from the same light source or reference light **44** is incident on the dry plate **45** at a given angle from the same side as the scatter plate **43**. In this way, a first hologram or transmission type hologram is recorded on the transmission type of hologram dry plate **45**.

Then, the first hologram, shown at **47** in FIG. 9, is located at the position of the former transmission type of hologram dry plate **45**, and a reflection type of hologram dry plate **50** formed of photopolymer as an example (Lippmann hologram dry plate) is now located at the position of the scatter plate **42**, as shown in FIG. 9. The hologram **47** is then irradiated with reconstructing illumination light **46** that is opposite in the direction of propagation to, and the same in wavelength as, the recording reference light **44**, so that diffracted light **48** from the hologram **47** or object light can be incident on the reflection type of hologram dry plate **50**. On the other hand, reference light **49** that propagates opposite to incident light assumed to be used with the liquid crystal display device is incident on the opposite side of the reflection type of hologram dry plate **50**. In this way, a second hologram or reflection type hologram is recorded on the reflection type of hologram dry plate **50**.

By use of this process it is possible to make the diffuse reflection type hologram with its viewing region limited to the range of the first hologram **47**. A hologram obtained from this hologram plate by contact replication, too, may be used as a diffuse reflection type hologram in which the direction of diffraction (scattering) of the plate is kept intact.

More illustratively, the scatter plate **42** and reflection type of hologram dry plate **50** are each 155 mm in height and 205 mm in breadth, and the transmission type of hologram dry plate **45** (the first hologram **47**) is 280 mm in height and 350 mm in breadth. While the reflection type of hologram dry plate **50** is spaced 300 mm away from, and inclined at an angle of 5° with, the scatter plate **42**, the reference light **49** is incident on the reflection type of hologram dry plate **50** at a downward angle of 20° with respect to the normal line thereof, so that the light incident at an angle of about 20° from above can be uniformly diffused and reflected within a range defined by an upward angle of about 20°, a downward angle of about 30° and breadth-wise angles of about 30°. This range is in substantial coincidence with a viewing range of an STN liquid crystal display element wherein a contrast of at least 2 is obtainable. It should be here understood that by making modification to the recording layout it is possible

to bring that range in substantial coincidence with a viewing range of a TN liquid crystal display element wherein a contrast of at least 2 is obtainable. In this case, light incident at an angle of about 20° from above is permitted to be uniformly diffused and reflected within a range defined by an upward angle of about 10°, a downward angle of about 40° and breadth-wise angles of about 60°.

In this connection, it is to be noted that in the process of making such a diffuse reflection type hologram as mentioned above, its optical properties may often vary due to its swelling and shrinkage although depending on the hologram photosensitive material used. However, such variations can be compensated for by making correction for recording angle and selecting recording wavelength while taking the inclination, and spacing variation of interference fringes into account.

By increasing the half bandwidth of diffraction wavelength by allowing the hologram to have a multilayer structure, or contact heating (JP-A-3-46687) of color tuning film wherein monomers, plasticizers or the like are diffused into a Lippmann hologram dry plate formed of photopolymer as an example for diffraction wavelength control, it is also possible to increase the quantity of diffused and reflected light and, hence, enhance the luminance of displays. By using a plurality of different wavelengths for one or more layers it is further possible to achieve full-color displays.

As shown in section in FIG. 6, a diffuse reflection type hologram **31** obtained as mentioned above is located on the backlight side of a liquid crystal display device **20**, thereby making it possible to construct a liquid crystal display device in which illumination light **32** incident from the display side of the liquid crystal display element **20** is diffused and reflected only within an angle range  $\theta$  coincident with the viewing region of the liquid crystal display device to present bright displays even in the light without recourse to any self-luminous type backlight. The liquid crystal display element **20** used herein, for instance, comprises a twisted nematic or other liquid crystal layer **25** sandwiched between two glass substrates **21** and **22**, one glass substrate **22** having a uniform opposite electrode **24** on its inner surface and the other glass substrate **21** having on its inner surface independent display electrodes **23** for each liquid crystal cell (R, G, B), and a color filter and a black matrix, although not illustrated. The electrodes **23** and **24** are also provided with orientation layers on their sides opposite to the liquid crystal layer, although again not illustrated. Further, the glass substrate **21** is provided with a polarizing plate **26** on its outer surface while the glass substrate **22** located on the viewing side is provided with a polarizing plate **27** on its outer surface, with their transmission axes perpendicular to one another, for instance. Voltage applied between the transparent display electrodes of the liquid crystal display element **20** is controlled per pixel to change the state of transmission, thereby displaying color images. It is noted here that by providing a diffuse reflection plate or reflector plate on the back side of the diffuse reflection type hologram **31** in the layout shown in FIG. 6, it is possible to achieve great luminance improvements.

By taking advantage of a reflection type hologram capable of diffracting a specific wavelength alone and transmitting light in other wavelength region, it is possible to set up an arrangement wherein a self-luminous type backlight **34** is located in combination with the back side of a diffuse reflection type hologram **31**, as shown in FIG. 7. According to this arrangement the self-luminous type backlight **34** can be used to illuminate the hologram **31** with light **35** there-



from when the liquid crystal display device is used in a dark place. When the liquid crystal display device is used in the light, the self-luminous type backlight **34** is used at a reduced luminance or turned off, so that the hologram **31** can be illuminated with diffused and reflected light **33** of extra-

aneous light **32**. It is thus possible to extend the battery driving time of a portable computer or the like, with which a liquid crystal display device is used.

One example of how to make the diffuse reflection type hologram **31** will now be explained. This diffuse reflection type hologram is to backlight an STN liquid crystal display element.

#### Recording of Transmission Type Hologram Plate

Using the layout shown in FIG. **8** under the following conditions, one transmission type hologram is recorded for each wavelength, three such holograms in all.

Recording wavelength: 476.5 nm (Ar laser), 576 nm (Ar laser+Dye laser), and 647.1 nm (Kr laser)

Photosensitive material: 8E56 made by AGFA (476.5 nm, 576 nm) used: 8E76 made by AGFA (647.1 nm)

Exposure: 300  $\mu\text{m}/\text{cm}^2$  (476.5 nm, 647.1 nm)  
500  $\mu\text{m}/\text{cm}^2$  (576 nm)

#### Recording of Reflection Type Hologram Plate

The aforesaid three transmission type holograms are used in the optical layout shown in FIG. **9** to record holograms of respective wavelengths on a single-layer dry plate formed of each of the following three photosensitive material films.

Recording wavelength: 476.5 nm (Ar laser), 576 nm (Ar laser+Dye laser), and 647.1 nm (Kr laser)

Photosensitive : HRF750X180 (647.1 nm) made by Du Pont

material used : HRF750X181 (576 nm) made by Du Pont  
HRF750X182 (476.5 nm) made by Du Pont

Exposure: 30  $\text{mJ}/\text{cm}^2$  per exposure

After this, layer stacking is carried out by post-recording treatments, viz., irradiation with UV at 200  $\text{mJ}/\text{cm}^2$  and a 2-hour heating at 120° C., as shown in FIG. **10**. That is, a layer structure is obtained, which is made up of 1t glass (of 1 mm in thickness), optical adhesive U-471 (made by Kyouritsu Kagaku Co., Ltd), three hologram film layers (HRF750X180, HRF750X181, HRF750X182), 4t glass (of 4 mm in thickness), optical adhesive U-471 (made by Kyouritsu Kagaku Co., Ltd.), and ND (neutral density) glass NG (of 4 mm in thickness and 1% in transmittance, and made by Shot).

#### Replication of Reflection Type Hologram Plate

As shown in FIG. **10**, while a photosensitive film is brought into close contact with the 1t glass (of 1 mm in thickness) side of the aforesaid reflection type hologram used as a plate, recording light including three wavelengths is concurrently or successively incident on the photosensitive film to cause interference of diffracted light from the hologram layer with the incident light in the photosensitive film for replication.

Recording wavelength: 476.5 nm (Ar laser), 576 nm (Ar laser+Dye laser), and 647.1 nm (Kr laser)

Photosensitive material used: HRF700X71-20 made by Du Pont

Exposure: 30  $\text{mJ}/\text{cm}^2$  per exposure

Following this, post-recording treatments, viz., irradiation with UV at 200  $\text{mJ}/\text{cm}^2$  and a 2-hour heating at 120° C. are carried out to obtain the following layer structure.

#### Layer Structure of Back Side Plate of Liquid Crystal Display

In order from the liquid crystal side:

Polarizing plate (LL-(82)-18 made by Sunlit Co., Ltd.):  
**27** (FIGS. **1** & **2**)

Adhesive layer (HJ-9150W made by Nitto Denko.Co., Ltd.)

Hologram

Color tuning film (GA2-RED made by Du Pont)

Adhesive layer (HJ-9150W made by Nitto Denko Co., Ltd.)

Aluminum deposited adhesive tape (FNS KESHI S50 mad by Rintech Co., Ltd.)

As shown in FIG. **6**, the thus fabricated diffuse reflection type hologram **31** having the polarizing plate **27** was located on the backlight side of the liquid crystal display element **20** to thereby obtain a liquid crystal display device which can uniformly diffuse and reflect light incident at an angle of 20° from above within a range defined by an -upward angle of about 20°, a downward angle of about 30°, and breadth-wise angles of about 30°, and enables bright color displays to be presented in the light without recourse to any self-luminous type backlight.

While the inventive liquid crystal display device using a hologram has been described with reference to some embodiments, it should be understood that the present -invention is in no sense limited to such embodiments, and many other modifications may be possible.

The hologram scatter plate according to the present invention comprises a transmission type hologram layer and a back side layer, as viewed from an incident side thereof. This hologram scatter plate is broken down into three types depending on where the scatter function is performed. As shown schematically in FIG. **11**, a first type of the hologram scatter plate **53** comprising the transmission hologram layer **51** and the back side surface **52** allows only the transmission hologram layer **51** to have diffusion and diffraction functions and the back side surface **52** to be provided in the form of a mirror reflection layer (FIG. **11(a)**); a second type allows the transmission hologram layer **51** to have diffraction function alone and the back side layer **52** to have a diffuse reflection function (FIG. **11(b)**); and a third type allows the transmission type hologram **51** to have diffusion and diffraction functions and the back side layer **52** to have diffuse reflection function (FIG. **11(c)**). Note that reference numeral **62** represents illumination light.

In either case, a hologram that is of the volume phase yet transmission type is used for the hologram **51**, and incident light **62** and light reflected at the back side layer **52** are diffracted through the transmission type hologram **51** in any desired direction.

Referring now to how to make such a transmission -type hologram **51** by means of holography, the hologram having diffraction function alone (FIG. **11(b)**) is recorded on a dry plate **54** formed of photopolymer, etc., for recording a volume phase type hologram by permitting parallel object light **55** to be almost vertically incident on the dry plate **54** and parallel reference light **56** to be incident on the dry plate **54** from a direction corresponding to the direction of illumination light **62** for interference in the dry plate **54**, as shown in FIG. **12**. The hologram having both diffraction function and diffusion function (FIGS. **11(a), (c)**) is recorded on the dry plate **54** formed of photopolymer, etc., for forming a volume phase type hologram by locating a scatter plate **57** in front of the dry plate **54**, permitting illumination light **58** to be incident on the scatter plate **57** to provide light



scattered through the scatter plate **57** and directly transmitted light in the form of object light, while permitting parallel light incident from a direction corresponding to illumination light **62** to be incident on the dry plate **54** in the form of reference light **59** for interference purposes, as shown in FIG. **13**.

The back side layer **52** herein used may be of the mirror reflection type wherein a reflecting metal such as aluminum, and silver is deposited on the upper or lower surface of a substrate film by means of evaporation or a metal foil is applied thereon. Alternatively, the back side layer **52** may be of the diffuse reflection type that is composed of a thin, mirror-finished metal plate. For instance, use may be made of a metal or other reflecting substrate subjected to surface matting, etc. to have a fine asperity pattern thereon, a substrate film having a scattering center therein and deposited on its back surface with a reflecting metal by means of evaporation or applied on its back surface with a metal foil, etc., a substrate film treated on one surface to have a fine asperity pattern and deposited on the other surface with a reflecting metal or applied thereon with a metal foil, etc., a photo diffusion film formed of a resin film which is coated or printed on one surface thereof with a photo diffusion ink having at least one fine particle dispersed therein, said at least one fine particle selected from the group consisting of an inorganic bead, an inorganic filler, an organic bead and a hollow bead, a photo diffusion film formed of a transparent resin in which said at least one fine particle is dispersed, or a known photo diffusion film having a reflecting metal deposited on its back surface by means of evaporation or a metal foil, etc. applied on its back surface.

Examples of the aforesaid substrate film having a scattering center, and the substrate film surface-treated to have a fine asperity pattern thereon are polyethylene (PE) film, uniaxially stretched polyethylene film, biaxially polyethylene film, stretched polypropylene (OPP) film, nonstretched polypropylene (CPP) film, ethylene-vinyl acetate copolymer (EVA) film, ionomer film, ethylene-ethyl acrylate copolymer (EEA) film, ethylene-acrylic acid copolymer (EAA) film, ethylene-methacrylic acid copolymer (EMAA) film, ethylene-methyl methacrylate copolymer (EMMA) film, ethylene-methyl acrylate copolymer (EMA) film, polyester film, nylon film, triacetylcellulose film, ethylene-vinyl alcohol copolymer (EVOH) film, polyvinylidene chloride (PVDC) film, biaxially stretched polyvinylidene chloride film, polyvinylidene fluoride film, polyacrylonitrile (PA) film, polybutylene terephthalate (PBT) film, polyethylene terephthalate (PET) film, polyethylene terephthalate (PEN) film, amorphous polyethylene terephthalate (A-PET) film, polystyrene film, polyvinyl chloride film, polyvinyl alcohol film, polycarbonate (PC) film, polymethyl methacrylate (PMMA) film, polyurethane film, fluorocarbon resin film, polymethylpentene film, polybutene film, polyimide film, and polyacrylate film. Various co-extruded films may be used as well. These substrate films must be capable of supporting layer stacks, and so have a thickness of 1  $\mu\text{m}$  to 500  $\mu\text{m}$ , preferably 10  $\mu\text{m}$  to 100  $\mu\text{m}$ .

If required, an adhesive layer may be interleaved between the transmission type hologram layer **51** and the back side layer **52**. The adhesive layer may contain adhesives such as elastomer adhesives, for instance, those based on natural rubber, reclaimed rubber, chloroprene rubber, nitrile rubber, styrene-butadiene rubber, and thermoplastic elastomers; synthetic resin adhesives such as those based on epoxy resin, and polyurethane; chemical reaction type adhesives such as those based on reaction type acrylic, and cyano acrylate; UV curable adhesives; EB curable adhesives; ethylene-vinyl

acetate copolymer resin hot-melt adhesives; polyamide adhesives; polyester adhesives; thermoplastic elastomer adhesives; hot-melt adhesives such as reactive hot-melt adhesives; aqueous adhesives or water-soluble adhesives; emulsion adhesives; latex adhesives; and inorganic adhesives. For bonding, the thermoplastic adhesives may be cured by heating to a temperature higher than their softening points while they are interleaved between layers forming a stack; the UV and EB curable adhesives may be cured by irradiation with ultraviolet radiation, and electron beams while they are interleaved between layers forming a stack; and the tacky adhesives may be cured as such while they are interleaved between layers forming a stack.

Examples of the three hologram diffuse plates shown in FIG. **11** will now be explained.

#### EXAMPLE 1 FOR HOLOGRAM DIFFUSE PLATE

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form a hologram recording dry plate. Using the optical system shown in FIG. **13** under the following conditions, hologram recording was carried out.

Laser wavelength: 514.5 nm (argon laser)

Reference light **59**: 30° from normal of dry plate **54**/parallel light

Object light: Vertical incidence of illumination light **58** on scatter plate **57**/light transmitted and scattered through scatter plate **57**

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **59** and object light: approximately 1:1

The obtained hologram was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain the transmission type hologram **51**. Applied on this hologram **51** was a mirror-finished, aluminum-deposited PET film (Metalumy TS #300 made by Toray Industries, Inc.) in the form of the back side layer **52**, with a double-sided adhesive film (MC2000 made by Nitto Denko Co., Ltd.) interleaved between them, thereby obtaining the inventive scatter plate **53** (FIG. **11(a)**).

#### EXAMPLE 2 FOR HOLOGRAM DIFFUSE PLATE

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form a hologram recording dry plate. Using the optical system shown in FIG. **12** under the following conditions, hologram recording was carried out.

Laser wavelength: 514.5 nm (argon laser)

Reference light **56**: 30° from normal of dry plate **54**/parallel light

Object light **55**: Vertical incidence/parallel light

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **56** and object light **55**: approximately 1:1

The obtained hologram was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain the transmission type hologram **51**. Applied on this hologram **51** was a light-scattering back side film (FNS KESHI S50 made by Rintec Co., Ltd.) in the form of the back side layer **52**, with a double-sided adhesive film (MC2000 made by Nitto Denko Co., Ltd.) interleaved between them, thereby obtaining the inventive scatter plate **53** (FIG. **11(b)**).



EXAMPLE 3 FOR HOLOGRAM DIFFUSE  
PLATE

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form a hologram, recording dry plate. Using the optical system shown in FIG. 13 under the following conditions, hologram recording was carried out.

Laser wavelength: 514.5 nm (argon laser)

Reference light **59**: 30° from normal of dry plate **54**/parallel light

Object light: Vertical incidence of illumination light **58** on scatter plate **57**/light transmitted and scattered through scatter plate **57**

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **59** and object light: approximately 1:1

The obtained hologram was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain the transmission type hologram **51**. Applied on this hologram **51** was a light-scattering back side film (FNS KESHI S50 made by Rintec Co., Ltd.) in the form of the back side layer **52**, with a double-sided adhesive-film (MC2000 made by Nitto Denko Co., Ltd.) interleaved between them, thereby obtaining the inventive scatter plate **53** (FIG. 11(c)).

EXAMPLE 4 FOR HOLOGRAM DIFFUSE  
PLATE

A hologram photosensitive material (Omnidex 352 made by Du Pont) was applied on a glass substrate to form a hologram recording dry plate. Using the optical system shown in FIG. 13 under the following three sets of conditions, hologram recording was carried out.

First Set of Conditions

Laser Wavelength: 488 nm (argon laser)

Reference light. **59**: 30° from normal of dry plate **54**/parallel light

Object light: Vertical incidence of illumination light **58** on scatter plate **57**/light transmitted and scattered through scatter plate **57**

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **59** and object light: approximately 1:1

Second set of conditions

Laser wavelength: 550 nm (dye laser)

Reference light **59**: 30° from normal of dry plate **54**/parallel light

Object light: Vertical incidence of illumination light **58** on scatter plate **57**/light transmitted and scattered through scatter plate **57**

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **59** and object light: approximately 1:1

Third set of conditions

Laser wavelength: 647 nm (krypton laser)

Reference light **59**: 30° from normal of dry plate **54**/parallel light

Object light: Vertical incidence of illumination light **58** on scatter plate **57**/light transmitted and scattered through scatter plate **57**

Exposure: 60 mJ/cm<sup>2</sup> (at an intensity of 1 mW/cm<sup>2</sup>)

Intensity ratio between reference light **59** and object light: approximately 1:1

Each of the thus obtained holograms was irradiated with ultraviolet radiation at 100 mJ/cm<sup>2</sup>, and then heated at 120° C. for 2 hours to obtain a transmission type hologram. Three such holograms were stacked together with double-sided adhesive films (MC2000 made by Nitto Denko Co., Ltd.) interleaved between them. Applied on the backmost side of the stack was a light scattering back side film (FNS KESKI S50 made by Rintech Co., Ltd.) in the form of the back side layer **52**, with a double-sided adhesive film (MC2000 made by Nitto Denko Co., Ltd.) interleaved between them, thereby obtaining the inventive scatter plate **53** (FIG. 11(c)).

While the hologram scatter plate according to this invention has been described with reference to some examples, it should be understood that the invention is never limited to these examples whatsoever, and so many other modifications may be possible.

A hologram, when used with a large liquid crystal display or a projector screen, must have a large area. To fabricate a large-area diffuse reflection type hologram, hologram plates must be joined together with joints recorded therein.

So far, a diffuse reflection type hologram has been fabricated by superposing a photosensitive material film on a surface of a plane plate form of diffuse reflection hologram backed with a light absorbing layer, stacking a protective glass on the photosensitive material film, and permitting laser light to be incident on the whole assembly from the protective glass so that the incident light, and light reflected and diffracted from the plate can interfere with each other in the photosensitive material film to thereby replicate the plate, as shown in FIG. 19(a), or winding a film form of diffuse reflection hologram backed with a light absorbing layer around a cylinder, winding a photosensitive material film around the hologram film in contact relation thereto, with an index matching liquid contained between them, and permitting laser light to be incident on a part of the hologram film such that it can cross the photosensitive material film at a position where the photosensitive material film comes into close contact with the hologram film, while rotating the cylinder in a direction shown by an arrow, whereby the incident light, and light reflected and diffracted from the hologram film can be made to interfere successively with each other to make the hologram film by replication, as shown in FIG. 19(b).

In the process shown in FIG. 19(a), however, the size of the diffuse reflection type hologram to be fabricated is limited to the size of the hologram plate used; that is, to fabricate a large-area diffuse reflection type hologram there is no option all but to join together a plurality of holograms. With the process shown in FIG. 19(b), a continuous diffuse reflection type hologram having a large area may be fabricated because the hologram film wound around the cylinder has joints therein. However, such joints remain recorded in the replicated hologram film.

In what follows, the inventive process of replicating a diffuse reflection type hologram used-with liquid crystal display devices, etc. will be explained with reference to a specific embodiment.

FIG. 14 illustrates one exemplary layout for carrying out the replication process according to the present invention, and FIG. 15 shows how to assemble a hologram plate support used in carrying out the same. In the present invention, a plate form of diffuse reflection hologram **61** to be replicated is applied, in-striped forms, on the surface of a semicylindrical transparent member **62** in its generating line direction. A photosensitive material film **63** is brought into close contact with the hologram plate **61** while a droplet form of index matching liquid or lubricant **65** is fed between



them through a dropping feeder 64. While the photosensitive material film 63 is slid in the circumferential direction of the transparent member 62 that crosses the striped form of hologram plate 61, it is fed in a direction shown by an arrow of FIG. 14. In this feeding process, at a position where the photosensitive material film 63 is in close contact with the hologram plate 61, laser light 66 is permitted to be incident on the hologram plate 61 from the photosensitive material film 63 such that it crosses the photosensitive material film 63 and provides a full coverage to the longitudinal -direction of the hologram plate 61. The incident light, and light reflected and diffracted from the hologram plate 61 are thus made to interfere successively with each other in the photosensitive material film 63, so that a large diffuse reflection type hologram that is continuously extended in the moving direction of the photosensitive material film 63 can be fabricated by replication.

An absorbing glass 68 is applied on the plane back side of the semicylindrical transparent member 62, with an adhesive layer 67 interleaved between them, for the purpose of preventing interference of the incident light with reflected light obtained by internal reflection at this plane of laser light 66 transmitted through the hologram plate 61, which may otherwise cause unnecessary interference fringes to be recorded. Instead of this, an absorbing layer may be provided on the back side of the hologram plate 61.

To apply the hologram plate 61 on the semicylindrical surface of the semicylindrical transparent member 62, an absorbing glass 68 is applied on the back side of the semi-cylindrical transparent member 62, as shown in FIG. 15(a). Alternatively, a rectangular recording film 61' is previously made, which has the hologram plate 61 recorded on a transversally striped middle region thereof and has a width smaller than the length of the transparent member 62, as shown in FIG. 15(b). Then, this recording film 61' may be applied on the semicylindrical surface of the semicylindrical transparent member 62, as shown in FIG. 15(c). In the layout shown in FIG. 14, it is to be noted that the axis (generating line) of the semicylindrical transparent member 62 may be directed either horizontally or vertically.

Available for the fabrication of the diffuse reflection type hologram 61 are some methods, two of which are shown; FIG. 16 illustrates a single-step holography method and FIG. 17 depicts a two-step-holography method. According to the single-step holography method shown in FIG. 16, a reflection type of hologram dry plate 71 formed of photopolymer as an example (a Lippmann hologram dry plate) is located at a predetermined diffuse reflection region with respect to a scatter plate 70 formed typically of frosted glass. The scatter plate 70 is illuminated from its back side with one coherent light 72 of given wavelength obtained by halving light emanating from the same light source so that scattered light 74 or object light leaving the front side of the scatter plate 70 can be incident on the reflection type of hologram dry plate 71. At the same time, another coherent light 73 of given wavelength emanating from the same light source or reference light is incident on the opposite side of the dry plate 71, said reference light propagating opposite to light assumed to be incident on the diffuse reflection type hologram plate 61, so that the diffuse reflection type hologram plate 61 can be recorded on the reflection type of hologram dry plate 71.

According to the two-step holography method shown in FIG. 17, a transmission type of hologram dry plate 75 is located at a predetermined diffuse reflection region with respect to a scatter plate 70 formed typically of frosted glass, as shown in FIG. 17(a). The scatter plate 70 is illuminated

from its back side with one coherent light 72 of given wavelength obtained by halving light emanating from the same light source, so that scattered light 74 leaving the front side of the scatter plate 70 or object light can be incident on the transmission type of hologram dry plate 75. At the same time, another coherent light 76 of given wavelength emanating from the same light source or reference light is incident on the same side of the dry plate 75 at any desired angle, so that a first or transmission type hologram can be recorded on the transmission type of hologram dry plate 75.

Then, this first hologram, shown at 77 in FIG. 17(b), is located at the position of the former transmission type of hologram dry plate 75, and a reflection type of hologram dry plate 80 is now located at the position of the scatter plate 70. The hologram 77 is irradiated with reconstructing illumination light 78 that is opposite in the direction of propagation to, and the same in wavelength as, the recording reference light 76 such that a real image of the hologram 77 can be formed at a position of the reflection type of hologram dry plate 80 (corresponding to the position of the scatter plate 70 shown in FIG. 17(a)), whereupon diffracted light 79 from the hologram 77 or object light is incident on the reflection type of hologram dry plate 80. At the same time, reference light 81 that propagates opposite to incident light assumed for the diffuse reflection type hologram 61 is incident on the opposite side of the reflection type of hologram dry plate 80, whereby a second or diffuse reflection type of hologram plate is recorded on the reflection type of hologram dry plate 80. In this way, it is possible to fabricate the diffuse reflection type hologram plate 61 with a viewing region limited to the range of the first hologram 77.

It is here to be noted that instead of the thus fabricated hologram plate 61, a hologram plate fabricated from the same by contact replication, too, may be used.

One illustrative example of the inventive replicating process will be explained. An adhesive layer 67 formed of U-471 made by Kyoritsu Kagaku Co., Ltd. was applied on a semi-cylindrical glass block 62, using NG4 made by Shot Co., Ltd. as an absorbing glass 68. Then, a hologram plate 61 was fixed on the glass block 62 with an index matching liquid made of xylene contained between them. The hologram plate 61 used was optically characterized in that light incident upwardly on the recording surface at an angle of incidence of 20° with respect to the normal line thereof can be diffused and reflected within a range defined by an upward angle of 20°, a downward angle of 20° and breadth-wise angles of 30° with respect to the normal line. While a roll form of photosensitive material film 63 was slid on the surface of the hologram plate 61 applied on the semicylindrical glass block 62, using an index matching liquid again formed of xylene as lubricant, the hologram plate 61 was irradiated through the roll form of photosensitive material film 63 with laser light 66 controlled by a cylindrical lens such that it diverges only in the generating direction of the glass block 62, whereby the laser light, and diffracted light from the hologram plate 61 could be made to interfere with each other to achieve continuous recording of the diffuse reflection type hologram on the photosensitive material film 63.

The inventive diffuse reflection type hologram replication process has been described with reference to some, examples, it should be understood that the present invention is by no means limited to such examples at all, and so many other modifications may be made.

As can be seen from the foregoing explanations, according to the first inventive liquid crystal display device using a hologram wherein on a display surface side of a liquid



crystal display element or between a liquid crystal display element and a backlight there is provided a diffuse transmission type hologram capable of diffusing and transmitting light incident from a specific direction only in a direction defined as a viewing region, it is possible to make wide a visual field region where displayed images can be observed and reduce luminance drops, so that bright displayed images can be presented. It is here to be noted that the present invention may be modified such that the visual field range can be arbitrarily set to observe images only in a plurality of different directions, and it is not always required to locate a scatter plate on the backlight side.

According to the second inventive liquid crystal display device using a hologram wherein on a back surface side of a liquid crystal display element opposite to a display surface side thereof there is provided a diffuse reflection type hologram capable of diffusing and reflecting light incident from a specific direction only in a direction defined as a viewing region as mentioned above, it is possible to present bright displays in the light without recourse to any self-luminous type backlight.

According to the inventive hologram scatter plate wherein a transmission type hologram layer and a back side layer are stacked together in the described order, it is possible to limit the direction of diffraction and scattering by means of the transmission hologram and increase reflectance over a wide wavelength region by means of the back side layer, so that diffused light having high luminance can be obtained over a wide wavelength and viewing angle range, so making bright displays, etc. possible. It is here to be noted that the transmission type hologram layer, if it has diffraction function, or diffusion function and diffraction function, with respect to a plurality of different wavelengths, especially, three wavelengths in R, G and B regions, can then present displays brighter (three times as bright on calculation) than those obtained with a hologram layer having diffraction function, or diffusion function and diffraction function, with respect to a single wavelength.

According to the inventive diffuse reflection type hologram replication process wherein while a photosensitive material film is slid on a fixed diffuse type hologram plate in contact relation thereto, the hologram plate is irradiated from the photosensitive material film with a light beam of linear section that becomes wide in a widthwise direction of the film, so that a diffuse reflection type hologram can be continuously recorded in the photosensitive material film by interference of the incident light beam with a light beam reflected and diffracted by the diffuse reflection type hologram plate, it is possible to easily fabricate, with no need of using any large hologram plate, a large yet continuous film form of diffuse reflection type hologram having neither joints nor recorded joints therein, which has high reflectance and quality, and so is best suited for use with backlights, projector screens, combiners, etc. for liquid crystal display devices.

What we claim is:

1. A liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a back surface side thereof opposite to a display surface side thereof with a diffuse reflection type hologram itself capable of diffusing and reflecting light of selected wavelengths incident from a specific direction only in a direction defined as a viewing region, wherein said hologram has a different optical function with respect to different respective wavelengths, wherein the diffuse reflection type hologram comprises a duplicate hologram of a single photosensitive layer.

2. A liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a back surface side thereof opposite to a display surface side thereof with a diffuse reflection type hologram itself capable of diffusing and reflecting light of selected wavelengths incident from a specific direction only in a direction defined as a viewing region, wherein said hologram has a different optical function with respect to different respective wavelengths, wherein the diffuse reflection type hologram comprises a plurality of layers including:

a first hologram recorded on a first photosensitive material using a wavelength produced by a Kr laser;

a second hologram recorded on a second photosensitive material using a wavelength produced by at least one of an Ar and a dye laser;

a third hologram recorded on a third photosensitive material using a wavelength produced by an Ar laser.

3. The liquid crystal display device of claim 2, wherein a color tuning film is laminated on the hologram, wherein said color tuning film broadens a diffraction wavelength range of said hologram layer.

4. A liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a back surface side thereof opposite to a display surface side thereof with a diffuse reflection type hologram itself capable of diffusing and reflecting light of selected wavelengths incident from a specific direction only in a direction defined as a viewing region, wherein said hologram has a different optical function with respect to different respective wavelengths,

characterized in that a diffuse reflection plate or a reflector plate is located on the back surface side of the diffuse reflection type hologram,

wherein the diffuse reflection type hologram comprises a plurality of layers including:

a first hologram recorded on a first photosensitive material using a wavelength produced by a Kr laser;

a second hologram recorded on a second photosensitive material using a wavelength produced by at least one of an Ar and a dye laser;

a third hologram recorded on a third photosensitive material using a wavelength produced by an Ar laser.

5. A liquid crystal display device using a hologram, characterized in that a liquid crystal display element is provided on a back surface side thereof opposite to a display surface side thereof with a diffuse reflection type hologram itself capable of diffusing and reflecting light of selected wavelengths incident from a specific direction only in a direction defined as a viewing region, wherein said hologram has a different optical function with respect to different respective wavelengths,

characterized in that a diffuse reflection plate or a reflector plate is located on the back surface side of the diffuse reflection type hologram,

characterized in that a polarizing plate, a hologram, a color tuning film and a reflecting layer are laminated together in order from a liquid crystal side.

6. A liquid crystal display device of claim 5, characterized in that said hologram is a color hologram with interference fringes recorded thereon in such a way as to diffract a plurality of wavelengths including red, green and blue wavelengths.