



US006405253B1

(12) **United States Patent**
Schutte et al.

(10) **Patent No.:** **US 6,405,253 B1**
(45) **Date of Patent:** **Jun. 11, 2002**

(54) **DYNAMIC ALLOCATION OF A SET OF ADDRESSES TO ROUTER RF MODEM FOR INDIVIDUAL ASSIGNMENT TO HOSTS**

(75) Inventors: **Mark E. Schutte**, Sugarhill; **Scott E. Hrastar**, Duluth, both of GA (US)

(73) Assignee: **Scientific-Atlanta, Inc.**, Lawrenceville, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/710,382**

(22) Filed: **Nov. 9, 2000**

Related U.S. Application Data

(63) Continuation of application No. 08/843,056, filed on Apr. 11, 1997, now Pat. No. 6,178,455.

(60) Provisional application No. 60/035,618, filed on Jan. 17, 1997.

(51) **Int. Cl.**⁷ **G06F 15/173**

(52) **U.S. Cl.** **709/228; 709/242; 709/245; 370/397; 370/399; 370/409**

(58) **Field of Search** **370/397, 399, 370/409; 709/228, 242, 245**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,985,962 A	10/1976	Jones et al.	370/455
4,186,380 A	1/1980	Edwin et al.	714/4
4,207,431 A	6/1980	McVoy	379/22
4,361,851 A	11/1982	Asip et al.	725/14
4,475,123 A	10/1984	Dumbauld et al.	380/211
4,491,983 A	1/1985	Pinnow et al.	359/118
4,528,589 A	7/1985	Block et al.	380/241
4,536,791 A	8/1985	Campbell et al.	725/28
4,577,224 A	3/1986	Ost	380/241
4,601,028 A	7/1986	Huffman et al.	370/217
4,633,462 A	12/1986	Stifle et al.	370/448
4,641,304 A	2/1987	Raychaudhuri	370/447
4,672,533 A	6/1987	Noble et al.	340/5.74

(List continued on next page.)

OTHER PUBLICATIONS

PPP Bridging Control Protocol (BCP); F. Baker et al.; Network Working Group Request for Comments, Jun. 1994; pp. 1-28.

(List continued on next page.)


Primary Examiner—Kenneth S. Kim

(74) *Attorney, Agent, or Firm*—Kenneth M. Massaroni; Kelly A. Gardner; Hubert J. Barnhardt, III

(57) **ABSTRACT**

An asymmetrical network for coupling customer-premises Internet hosts such as personal computers to the Internet. The head end of a CATV system has a high-bandwidth connection to the Internet. The down link connecting the personal computers to the Internet is the cables provided by the CATV system; the up link is a telephone connection to the head end. A router is connected to the down link by means of an RF modem, to the up link by means of an analog modem, and to a LAN which is connected to the Pcs. The router routes IP packets for the hosts that are received on the CATV cable to the hosts via the LAN; it routes IP packets from the hosts that are destined for the Internet to the head end via the telephone line. The asymmetrical network conserves IP addresses and addresses on the CATV cable by dynamically allocating the IP addresses for an RF modem's hosts and an address on the CATV cable for the RF modem in response to a request made by the RF modem via the telephone line. It further saves IP addresses by assigning a non-unique IP address to the router for use inside the LAN. When the CATV system fails, the asymmetrical network automatically begins to use the telephone line as both the up link and the down link, and when the CATV system is restored, the asymmetrical network automatically returns to using the CATV cable as the down link and the telephone line as the up link. A further feature of the asymmetrical network is that the head end components and the RF modem have IP addresses, so that standard TCP/IP protocols can be used to control the asymmetrical network.

25 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS			
4,757,460 A	7/1988	Bione et al.	709/248
4,771,391 A	9/1988	Blasbalg	709/232
4,804,248 A	2/1989	Bhagavatula	385/28
4,823,386 A	4/1989	Dumbauld et al.	380/211
4,858,224 A	8/1989	Nakano et al.	370/217
4,907,224 A	3/1990	Scoles et al.	370/443
4,912,721 A	3/1990	Pidgeon, Jr. et al.	375/149
4,980,886 A	12/1990	Bernstein	370/433
5,012,469 A	4/1991	Sardana	370/322
5,014,125 A	5/1991	Pocock et al.	725/793
5,047,928 A	9/1991	Wiedemer	705/52
5,050,213 A	9/1991	Shear	705/53
5,113,499 A	5/1992	Ankney et al.	340/5.74
5,131,014 A	7/1992	Brunner et al.	370/219
5,136,690 A	8/1992	Becker et al.	345/853
5,142,690 A	8/1992	McMullan, Jr. et al.	725/124
5,155,590 A	10/1992	Beyers, II et al.	725/107
5,157,657 A	10/1992	Potter et al.	370/440
5,159,592 A	10/1992	Perkins	370/338
5,166,930 A	11/1992	Braff et al.	370/235
5,166,931 A	11/1992	Riddle	370/401
5,181,107 A	1/1993	Rhoades	725/105
5,185,860 A	2/1993	Wu	709/224
5,195,092 A	3/1993	Wilson et al.	725/146
5,197,094 A	3/1993	Tillery et al.	463/25
5,208,665 A	5/1993	McCalley et al.	725/119
5,214,390 A	5/1993	Montreuil	329/309
5,226,120 A	7/1993	Brown et al.	709/224
5,235,619 A	8/1993	Beyers, II et al.	375/260
5,239,540 A	8/1993	Rovira et al.	370/345
5,251,324 A	10/1993	McMullan, Jr.	725/14
5,261,044 A	11/1993	Dev et al.	345/357
5,271,041 A	12/1993	Montreuil	375/344
5,276,789 A	1/1994	Besaw et al.	345/440
5,278,833 A	1/1994	Crisler et al.	370/348
5,287,351 A	2/1994	Wall, Jr.	370/206
5,295,140 A	3/1994	Crisler et al.	370/443
5,295,244 A	3/1994	Dev et al.	345/357
5,303,234 A	4/1994	Kou	370/442
5,327,554 A	7/1994	Palazzi, III et al.	725/110
5,333,183 A	7/1994	Herbert	379/112
5,347,304 A	9/1994	Moura et al.	725/131
5,361,259 A	11/1994	Hunt et al.	370/402
5,384,777 A	1/1995	Ahmadi et al.	370/337
5,390,181 A	2/1995	Campbell et al.	370/444
5,404,505 A	4/1995	Levinson	707/10
5,423,003 A	6/1995	Berteau	370/254
5,423,006 A	6/1995	Brown et al.	710/19
5,436,909 A	7/1995	Dev et al.	714/4
5,444,555 A	8/1995	Momona	370/455
5,471,399 A	11/1995	Tanaka et al.	716/11
5,473,599 A	12/1995	Li et al.	370/49
5,481,542 A	1/1996	Logston et al.	725/131
5,483,631 A	1/1996	Nagai et al.	345/329
5,504,921 A	4/1996	Dev et al.	709/223
5,515,361 A	5/1996	Li et al.	370/222
5,515,418 A	5/1996	Yamaguchi et al.	379/34
5,517,488 A	5/1996	Miyazaki et al.	370/449
5,517,502 A	5/1996	Bestler et al.	370/225
5,517,618 A	5/1996	Wada et al.	709/223
5,521,925 A	5/1996	Merakos et al.	370/337
5,533,108 A	7/1996	Harris et al.	379/201
5,534,913 A	7/1996	Majeti et al.	725/114
5,535,206 A	7/1996	Bestler et al.	370/458
5,535,403 A	7/1996	Li et al.	345/348
5,553,095 A	9/1996	Engdahl et al.	375/222
5,553,287 A	9/1996	Bailey et al.	709/221
5,572,640 A	11/1996	Schettler	345/440
5,586,121 A	12/1996	Moura et al.	370/404
5,594,798 A	1/1997	Cox et al.	380/257
5,604,528 A	2/1997	Edwards et al.	725/125
5,608,446 A	3/1997	Carr et al.	725/114
5,610,910 A	3/1997	Focsaneanu et al.	370/351
5,612,959 A	3/1997	Takase et al.	370/390
5,644,706 A	7/1997	Ruigrok et al.	714/48
5,650,994 A	7/1997	Daley	370/259
5,654,746 A	8/1997	McMullan, Jr. et al.	348/6
5,675,732 A	10/1997	Majeti et al.	709/235
5,701,465 A	12/1997	Baughner et al.	707/10
5,703,795 A	12/1997	Mankovitz	345/721
5,706,277 A	1/1998	Klink	370/220
5,708,655 A	1/1998	Toth et al.	370/313
5,708,961 A	1/1998	Hylton et al.	725/81
5,710,884 A	1/1998	Dedrick	709/217
5,712,897 A	1/1998	Ortel	379/22
5,720,025 A	2/1998	Wilkes et al.	714/6
5,721,780 A	2/1998	Ensor et al.	713/155
5,724,492 A	3/1998	Matthews, III et al.	345/419
5,729,682 A	3/1998	Marquis et al.	709/229
5,737,311 A	4/1998	Wyld	370/227
5,737,316 A	4/1998	Lee	370/248
5,751,706 A	5/1998	Land et al.	370/352
5,751,707 A	5/1998	Voit et al.	370/384
5,751,971 A	5/1998	Dobbins et al.	709/238
5,761,602 A	6/1998	Wagner et al.	725/34
5,768,280 A	6/1998	Way	370/486
5,790,548 A	8/1998	Sistanizadeh et al.	370/401
5,790,806 A	8/1998	Koperda	709/202
5,793,753 A	8/1998	Hershey et al.	370/252
5,796,718 A	8/1998	Caterisano	370/217
5,799,002 A	8/1998	Krishnan	370/234
5,799,016 A	8/1998	Onweller	370/401
5,805,591 A	9/1998	Naboulsi et al.	370/395
5,805,596 A	9/1998	Kranzler et al.	370/445
5,808,671 A	9/1998	Maycock et al.	348/180
5,808,886 A	9/1998	Suzuki et al.	700/4
5,812,819 A	9/1998	Rodwin et al.	395/500
5,818,845 A	10/1998	Moura et al.	370/449
5,822,319 A	10/1998	Nagami et al.	370/392
5,828,655 A	10/1998	Moura et al.	370/236
5,828,666 A	10/1998	Focsaneanu et al.	370/389
5,835,696 A	11/1998	Hess	714/10
5,835,725 A *	11/1998	Chiang et al.	709/228
5,841,468 A	11/1998	Wright	725/119
5,845,091 A	12/1998	Dunne et al.	
5,859,852 A	1/1999	Moura et al.	370/449
5,881,234 A	3/1999	Scwob	709/219
5,881,243 A	3/1999	Zaumen et al.	713/201
5,884,024 A	3/1999	Lim et al.	395/187.01
5,884,284 A	3/1999	Peters et al.	705/30
5,892,812 A	4/1999	Pester, III	379/34
5,894,479 A	4/1999	Mohammed	370/401
5,898,780 A	4/1999	Liu et al.	713/155
5,903,572 A	5/1999	Wright et al.	370/524
5,905,714 A	5/1999	Havansi	370/242
5,905,736 A	5/1999	Ronen et al.	370/546
5,956,391 A	9/1999	Melen et al.	379/114.01
5,959,972 A	9/1999	Hamami	370/228
5,966,163 A	10/1999	Lin et al.	725/117
5,999,970 A	12/1999	Krisbergh et al.	709/217
6,018,767 A	1/2000	Fijolek et al.	709/218
6,028,860 A	2/2000	Laubach et al.	370/395
6,032,266 A	2/2000	Ichinohe et al.	714/9
6,049,826 A	4/2000	Beser	709/222
6,052,819 A	4/2000	Barker et al.	714/776
6,055,224 A	4/2000	King	370/217
6,058,421 A	5/2000	Fijolek et al.	709/225
6,065,049 A	5/2000	Beser et al.	709/218
6,070,246 A	5/2000	Beser	713/201
6,073,178 A *	6/2000	Wong et al.	709/229
6,178,455 B1	1/2001	Schutte et al.	709/228

6,208,656 B1 *	3/2001	Hrastar et al.	370/401
6,230,203 B1	5/2001	Koperda et al.	709/229
6,249,523 B1	6/2001	Hrastar et al.	370/401
6,272,150 B1	8/2001	Hrastar et al.	370/486
6,282,208 B1	8/2001	Bowcutt et al.	370/486
6,286,058 B1	9/2001	Hrastar et al.	710/8
6,295,298 B1	9/2001	Hrastar et al.	370/409

OTHER PUBLICATIONS

Data-Over Cable Service Interface Specifications; Cable Modem to Customer Premise Equipment Interface Specification; SP-CMCI-I02-980317; 1988; Cable Television Laboratories; Inc.; pp. 1-40.

Data-Over Cable Service Interface Specifications; Cable Modem Telephony Return Interface Specification; SP-C-MTRI-101-970804; 1997; Cable Television Laboratories, Inc.; pp. 1-74.

Data-Over Cable Service Interface Specifications; Radio Frequency Interface Specification; SPRFIv1.1-101-990311; 1999; Cable Television Laboratories, Inc.; pp. 1-310.

Data-Over Cable Technical Reports; Operations Support System Framework for Data Over Cable Services; TR-DOCS-OSSIW08-961016; 1996; MCNS Holdings, LP; pp. 1-20.

Data-Over Cable Service Interface Specifications; Operations Support System Interface Specification; SP-OSSI-102-990113; 1999; Cable Television Laboratories, Inc.; pp. 1-26.

Data-Over Cable Service Interface Specifications; Operations Support System Interface Specification Radio Frequency Interface; SP-OSSI-RFI-103-990113; 1999; Cable Television Laboratories, Inc.; pp. 1-29.

Data-Over Cable Service Interface Specifications; Operations Support System Interface Specification Baseline Privacy Interface MIB; SP-OSSI-BPI-101-980331; 1997 & 1998; MCNS Holdings, LP; pp. 1-33.

Data-Over Cable Service Interface Specifications; Radio Frequency Interface Specification SP-RFI-104-980724; 1997; Cable Television Laboratories, Inc.; pp. 1-196.

Radio Frequency (RF) Interface Management Information Base for MCNS Complaint RF Interfaces Draft-ietf-ipcdn-rf-interface-mib-04.txt; May 22, 1999, Guenter Roeck (editor); pp. 1-55.

Cable Device Management Information Base for MCNS Complaint Cable Modems and Cable Modem Termination Systems draft-ietf-ipcdn-cable-device-mib-04.txt; May 22, 1998; Guenter Roeck (editor); pp. 1-32.

Baseline Privacy Interface Management Information Base for MCNS Complaint Cable Modems and Cable Modem Termination Systems; R. Woundy; Jan. 17, 1999; pp. 1-35.

Logical IP Subnetworks over IEEE 802.14 Services; Mark Laubach; Mar. 13, 1998; pp. 1-13.

A Distribute Queueing Random Access Protocol for a broadcast Channel; Wenxin Xu and Graham Campbell; Illinois Institute of Technology (Comp. Science Dept.); pp. 1-9.

CBR Channels on a DQRAP-based HFC Network; Chien-Ting Wu, Graham Campbell; Illinois Institute of Technology (Comp. Science Dept.); pp. 1-14.

Interleaved DQRAP with Global TQ; Chien-Ting Wu, Graham Campbell; Illinois Institute of Technology (Comp. Science Dept.); pp. 1-27.

The Extended DQRAP (XDARAP) Algorithm; Chien-Ting Wu, Graham Campbell; Illinois Institute of Technology (Comp. Science Dept.); Dec. 9, 1994; pp. 1-4.

Extended DQRAP (EXQRAP) A Cable TEV Protocol Functioning as a Distributed Switch; Chien-Ting Wu & Graham Campbell; Illinois Institute of Technology (Comp. Science Dept.); pp. 1-7.

A Review of Contention Resolution Algorithms for IEEE 802.14 Networks; Nada Glomie; Yves Saintillan, & David H. Su; National Institute of Standards and Technology; pp. 1-11.

A Review of Contention Resolution Algorithms for IEEE 802.14 Networks; Nada Glomie; Yves Saintillan, & David H. Su; National Institute of Standards and Technology; pp. 1-12.

On IEEE 802.14 Medium Access Control Protocol; Ying-Dar Lin; 1998; pp. 1-13.

On IEEE 802.14 Medium Access Control Protocol; Ying-Dar Lin; 1998; pp. 1-11.

On IEEE 802.14 Medium Access Control Protocol; Ying-Dar Lin; 1998; pp. 1-10.

Extended DQRAP (XDQRAP); Chien Ting Wu et al.; C. S. Dept. Ill. Inst. of Tech.; Jan. 8, 1995 pp. 1-4.

Hybrid-Fiber Coax; Hung Nguyen and Felix Yao; Apr. 22, 1996; pp. 1-11.

Cable Data Modem Performance Evaluation, A Primer for Non-Technical Readers; Cable Television Laboratories, Inc.; Nov. 15, 1996; pp. 1-8.

High Speed Cable Modems, Including IEEE 802.14 Standards; Albert A. Azzam; Chapters 5, 6.

Cable Device Management Information Base for DOCSIS Compliant Cable Modems and Cable Modem Termination Systems; Michael St. Johns; Mar. 30, 1999; pp. 1-54.

Radio Frequency (RF) Interfaces Management Information Base for MCNS/DOCSIS Compliant RF Interfaces; Mike St. Johns, (Editor); Feb. 17, 1999; pp. 1-67.

Telephony-Return Interface (TRI) Management Information Base for DOCSIS complaint Telephony-Return Cable Modems and Cable Modem Termination systems; S. Adiraju, J. Fijolek; Apr. 2, 1999; pp. 1-27.

Data Over Cable System Quality of Service Management Information Base (DOCSIS-QOS MIB); Mike Patrick; J. Harvey; Motorola ING; Jun. 25, 1999; pp. 1-43.

Docsis 1.1 IGMP MIB; H. Abramson, Motorola; Jun. 1999; pp. 1-13.

Publications and Technical Reports of Dolors Sala—Home Page; pp. 1-6.

Scheduling Disciplines for HFC Systems; What can we learn from ATM scheduling?; Dolors Sala, John O. Limb; GA Tech; pp. 1-6.

A Protocol for Efficient Transfer of Data over Fiber/Cable Systems; Dolors Sala, John O. Limb; GA Tech; pp. 1-16.

MAC Protocols for Multimedia Data over HFC Architecture; Dolors Sala Battle; Oct. 27, 1995; pp. 1-28.

An Access Protocol to Support Multimedia Traffic Over Hybrid Fiber/Coax Systems; John O. Limb, Dolors Sala; pp. 1-6.

Simulation of the Performance of XDQRAP under a Range of Conditions; John O. Limb, Dolors Sala, Jason Collins, David Hartman, Daniel Howard; pp. 1-10.

Interleaved DQRAP with Global TQ; Chien-Ting Wu, Graham Campbell; Illinois Institute of Technology, CS Dept.; Jan. 8, 1995; pp. 1-26.

Data Link Protocols; Uyles Black; Bell Atlantic Education Services; PTR Prentice Hall; New Jersey; 1993 pp. 141-159.

- ATM Foundation for Broadband Networks; vol. 1; Ed. 2; Uyles Black; Prentice Hall; NJ; 1999; pp. 260–299.
- The V Series Recommendations; Ed. 2; Uyles Black; McGraw–Hill, Inc.; 1995; pp. 169–184.
- Frame Relay Networks; Ed. 2; Uyles Black; McGraw–Hill, Inc.; 1996; pp. 159–176.
- ISDN; Ed. 2; Gary C. Kessler & Peter V. Southwick; McGraw–Hill, Inc.; 1997; pp. 111–128.
- ISDN & SS7: Architecture for Digital Signaling Networks; Uyles Black; Prentice Hall; NJ; 1997; pp. 31–47.
- ISDN and Broadband ISDN with Frame Relay and ATM; Ed. 4; William Stallings; Prentice Hall; NJ; 1999 pp. 181–216, pp. 312–343.
- R. Droms; Dynamic Host Configuration Protocol; Oct. 1993; pp. 1–39.
- W. Richard Stevens; TCP/IP Illustrated, vol. 1, The Protocols; Chapters 1, 2, 3, 4, 9, 11, 16.
- T. Li et al.; Cisco Hot Standby Router Protocol (HSRP), RFC 2281, Mar. 1998, pp. 1–17.
- Y. Rekhter et al., Address Allocation for Private Internets, RFC 1597, Mar. 1994, pp. 1–8.
- E. Lear et al., Network 10 Considered Harmful (Some Practices Shouldn't be Codified), Jul. 1994, pp. 1–8.
- E. Gerich, Unique Addresses are Good, RFC 1814, Jun. 1995, pp. 1–3.
- Y. Rekhter et al., Address Allocation for Private Internets, RFC 1918 Feb. 1996, pp. 1–8.
- K. Egevang, The IP Network Address Translator (NAT), RFC 1631, May 1994, pp. 1–10.
- P. Srisuresh et al., IP Network Address Translator (NAT) Terminology and Consideration, RFC 2663, Aug. 1999, pp. 1–30.
- P. Srisuresh et al., Load Sharing using IP Network Address Translation (LSNAT), RFC 2391, Aug. 1998, pp. 1–18.
- P. Srisuresh et al., DNS Extensions to Network Address Translators (DNS₁₃ALG), RFC 2694, Sep. 1999, pp. 1–29.
- P. Srisuresh, Security Model with Tunnel–mode IPsec for NAT Domains, RFC 2709, Oct. 1999, pp. 1–11.
- G. Tsirtsis et al., Network Address Translation—Protocol Translation (NAT–PT), RFC 2766, Feb. 2000, pp. 1–21.
- E. Nordmark, Stateless IP/ICMP Translation Algorithm (SIIT), RFC 2765, Feb. 2000, pp. 1–26.
- M. Allman et al., FTP Extensions for IPv6 and NATs, RFC 2428, Sep. 1998, pp. 1–8.
- rfc 1541—*Dynamic Host Configuration Protocol*, R. Droms, Oct. 1993, found at URL <http://www.cis.ohio-state.edu/htbin/rfc/rfc1541.html>.

* cited by examiner




FIG - 1




FIG - 2




FIG - 3




FIG - 4





FIG - 6




FIG - 7




FIG - 8





FIG - 9

FIG - 10



	DEST. IPA	GATEWAY IPA	ROUTING INFO
1103(I)	LOOP BACK IPA 1103	LOOP BACK IPA 1103	
1104	IPA FOR HOST 108 (0) 1109	IPA FOR HOST 108 (0) 1111	LAN 133 1105
	⋮	⋮	⋮
	IPA FOR HOST 108 (N-1)	IPA FOR HOST 108 (N)	1105
1103 (K)	DEFAULT 1115	REUSABLE IPA FOR RF MODEM 106 (j) 117	1105

ROUTING TABLE 1101
FOR HOST 108 (K)


	IP ADDR.	LAN A
1120 (1)	IPA FOR HOST 108 (0) 1121 (0)	LAN A FOR HOST 108 (0) 1123 (0)
1122	⋮	⋮
	1121 (N-1)	1123 (N-1)
1120 (j)	REUSABLE IP ADDR. 1117	LAN A FOR RF MODEM 106(j) 1125

ARP CACHE FOR HOST 108 (K)

1119

FIG - 11

FIG - 12



**DYNAMIC ALLOCATION OF A SET OF
ADDRESSES TO ROUTER RF MODEM FOR
INDIVIDUAL ASSIGNMENT TO HOSTS**

**CROSS REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 08/843,056 filed Apr. 11, 1997, now issued U.S. Pat. No. 6,178,455, which claimed the benefit of United States Provisional Application titled Cable Data Network System, filed Jan. 17, 1997, having Ser. No. 60/035,618, with Scott E. Hrastar, Mark E. Schutte, Roy A. Bowcutt, David A. Sedacca, and Todd A. Merrill listed as inventors. This application also cross-references the following related Applications:

U.S. application Ser. No. 08/833,198, titled Apparatus and Methods for Automatically Rerouting Packets in the Event of a Link Failure, filed Apr. 14, 1997, now issued U.S. Pat. No. 6,286,058, with Scott E. Hrastar, Todd A. Merrill, A and Roy A. Bowcutt listed as inventors;

U.S. application Ser. No. 08/837,073, titled Method of Using Routing Protocols to Reroute Packets during a Link Failure, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,301,233, with Scott E. Hrastar, Todd A. Merrill, and Roy A. Bowcutt listed as inventors;

U.S. application Ser. No. 08/843,061, titled Methods for Dynamically Assigning Link Addresses and Logical Network Addresses, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,208,656, with Scott E. Hrastar and George Horkan Smith listed as inventors;

U.S. application Ser. No. 08/843,056, titled Router which Dynamically Requests a Set of Logical Network Addresses and Assigns Addresses in the Set to Hosts Connected to the Router, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,178,455, with Mark E. Schutte and Scott E. Hrastar listed as inventors;

U.S. application Ser. No. 08/838,833, titled Router for Use with a Link that has a Set of Concurrent Channels, filed Apr. 11, 1997, with Todd A. Merrill, Mark E. Schutte, Roy A. Bowcutt, and Scott E. Hrastar listed as inventors;

U.S. application Ser. No. 08/832,714, titled Method of Dynamically Assigning a Logical Network Address and a Link Address, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,295,298, with Scott E. Hrastar and David A. Sedacca listed as inventors;

U.S. application Ser. No. 08/840,304, titled Router for which a Logical Network Address it which is not Unique to the Router is the Gateway Address in Default Routing Table Entries, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,249,523, with Scott E. Hrastar and George Horkan Smith listed as inventors;

U.S. application Ser. No. 08/835,917, titled Usage Statistics Collection for a Cable Data Delivery System, filed Apr. 10, 1997, now issued U.S. Pat. No. 6,308,328, with Roy A. Bowcutt and Scott E. Hrastar listed as inventors;

U.S. application Ser. No. 08/835,916, titled Two-Tiered Authorization And Authentication For A Cable Data Delivery System, filed Apr. 10, 1997, now issued U.S. Pat. No. 6,324,267, with Scott E. Hrastar and Roy A. Bowcutt listed as inventors; and

U.S. application Ser. No. 08/835,966, titled System and Method for Detecting, Correcting and Discarding Corrupted Data Packets in a Cable Data Delivery System, filed Apr. 11, 1997, now issued U.S. Pat. No. 6,052,819, with James E. Barker, Roy A. Bowcutt, Scott E. Hrastar, Todd A. Merrill, and David A. Sedacca listed as inventors.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention concerns data networks generally and more particularly concerns data networks that employ protocols belonging to the TCP/IP protocol suite and data networks that are asymmetric, that is, data networks in which there is more capacity to move data in one direction than there is in the reverse direction.

2. Description of the Prior Art

In the not-too-distant past, images could be processed and display only by large, special-purpose computer systems. Owners of lower-cost and less-powerful computers such as personal computers had to content themselves with character-based displays. The cost of memory has dropped so quickly and the power of microprocessors has increased so greatly in recent years, however, that modern personal computers are completely capable of processing and displaying images. Indeed, modern graphical user interfaces depend on a large extent on this capability.

Frustratingly enough for users of personal computers, the old problems with images have returned in another area, namely network computing. In network computing, the personal computer or workstation is connected to a network and is able to use the network to fetch the data it is processing from remote locations. The most recent development in network computing is the Internet, a worldwide logical network which permits anyone who has access to the Internet to interactively fetch data including images from just about anywhere in the world. For example, using the Internet, it is possible to fetch pictures of the latest restoration projects in Florence, Italy from that city's home page on the World Wide Web.

The main drawback to interactively fetching data on the Internet is the length of time it takes to retrieve and display images. The problem is so serious that many people set up the program they use to access the Internet so that it does not fetch images. Doing this restricts the user to character data, but greatly decreases the time it takes to access information. The bottleneck in retrieving images from the Internet is not the personal computer, but rather the lack of capacity or bandwidth of the networks over which the images must be fetched. One part of the network where bandwidth is particularly restricted is the analog telephone line that connects most PC users to the Internet. It has been known for years that the bandwidth of the telephone system can be increased by replacing the analog system with a digital system, but all of the known techniques for doing this require extensive modification of the telephone system.

A great many homes do in fact have a high bandwidth connection, namely that provided by cable television. The problem with this connection is that it is one way. A PC may receive data via a home's CATV cable, but it cannot use the cable to send data. Again, ways of making the CATV system bidirectional have been known for years. For example, in the early 1980's, Scientific-Atlanta, Inc. introduced and marketed a product known as the Model 6404 Broadband Data Modem for use with bidirectional CATV systems. Scientific-Atlanta, Inc. has also recently filed U.S. patent applications Ser. No. 08/627,062, filed Apr. 3, 1996, now issued U.S. Pat. No. 5,790,806, and U.S. patent application Ser. No. 08/738,6681, filed Oct. 16, 1996, now issued U.S. Pat. No. 5,966,163, and a continuation-in-part titled System and Method for Providing Statistics for Flexible Billing in a Cable Environment, Koperda, et al, filed Mar. 14, 1997 which describe bidirectional CATV systems. As with the telephone systems, the problem here is not the technology,

but the fact that its introduction requires extensive modification of most existing CATV systems.

Given that many homes have a CATV cable and virtually all homes have an analog telephone line, systems have been proposed in which the CATV cable is used to send data from the Internet to the PC and the telephone line used to return data from the PC to the Internet. These systems take advantage of the fact that by far the most common pattern of interaction between users and networks is for the user to retrieve a large amount of data over the network, for example an image of a restored art work from Florence, examine the image, and then send a few keystrokes over the network. With this kind of interaction, far less bandwidth is needed in the channel that is used to return the keystrokes than in the channel that is used to fetch the image.

An example of such a system is the one disclosed in Moura, et al., Asymmetric Hybrid Access System and Method, U.S. Pat. No. 5,586,121, issued Dec. 17, 1996, and in Moura, et al., Remote Link Adapter for use in TV Broadcast Data Transmission System, U.S. Pat. No. 5,347,304, issued Sep. 13, 1994. In this system, the head end of a cable system has high bandwidth access to the Internet or to other networks and access via CATV cables and the telephone system to households or businesses with PCs. Data received from these networks is sent to PCs connected to the cable system's cables and responses from the PCs are collected via the telephone system and sent to the network. In the home or business, the PC is connected either directly or via a local area network to a device which includes both a radio frequency modem and a standard analog telephone modem. The radio frequency modem is connected to the CATV cable. It receives and decodes the data sent on the CATV cable and provides it to the PC. The telephone modem is connected to a standard telephone line. It receives data from the PC and sends it to the CATV head end, which in turn forwards it to the Internet or other networks.

While systems such as the one disclosed in the Moura references do provide a solution to the bandwidth problem, they have a number of deficiencies, particularly when used in the context of the Internet. Among the deficiencies are the following:

The system of Moura wastes Internet Protocol (IP) addresses for the computers attached to the modem. IP addresses are in short supply. In the system of Moura, however, IP addresses are statically assigned to the PCs and are consequently not available for reuse when a PC is idle or not engaged in an activity which involves network access.

From the point of view of the Internet, the system of Moura is a link level system, that is, the components of the system of Moura do not themselves have IP addresses and cannot themselves execute IP protocols. In particular, IP routing is not used within the system of Moura. One difficulty arising from this situation is that IP routing is centralized in the EP router that connects the head end to the Internet; another is that the modem in the system of Moura cannot function as an IP router.

In Moura, the telephone connection to the modem is used solely to transfer data from the PC and modem to the head end. All data received by the PC and modem is sent via the CATV cable. Consequently, when the CATV system fails, the PC is left without a connection by which it can receive data. This situation is made even less desirable by the fact that CATV systems are far more likely to fail than the telephone system.

The CATV channel to which the modem of Moura responds is statically assigned to a given modem, thereby

rendering the channel unavailable for use by other modems when the PC connected to the given modem is idle or is not engaged in an activity which involves network access.

It is an object of the system disclosed herein to overcome the preceding and other deficiencies of systems like that of Moura.

SUMMARY OF THE INVENTION

The problem of wasting IP addresses by statically assigning them to hosts is solved as follows: when the cable router becomes active, it sends a message requesting a set of IP addresses via the telephone line to the head end, which dynamically assigns the set of IP addresses and sends a message containing the set of IP addresses via the telephone line to the cable router. The cable router then responds to requests by the hosts for IP addresses by assigning them IP addresses from the set.

Other objects and advantages of the invention will be apparent to those skilled in the arts to which the invention pertains upon perusing the following Detailed Description and Drawing, wherein:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an overview of the physical components of the cable data network disclosed herein,

FIG. 2 shows the logical networks to which the IP addresses used in the cable data network belong;

FIG. 3 shows an IP datagram and an Ethernet frame as they are employed in a preferred embodiment;

FIG. 4 shows the channels, superframes, and superpackets used to carry data on the RF link in the preferred embodiment;

FIG. 5 is a block diagram of a preferred embodiment of the RF modem employed in the cable data network;

FIG. 6 is a diagram of the IP addresses and subnetwork masks employed in the cable data network;

FIG. 7 is a diagram that shows how the RF modem receives IP addresses and a <channel,pipe,link ID> triple when the RF modem becomes active;

FIG. 8 is a diagram that shows how IP packets addressed to hosts are rerouted via the telephone network when the RF modem detects a failure in the RF link;

FIG. 9 is a diagram of routing tables for router 100, modem pool 135, RF modem 106, and communications manager 102;

FIG. 10 is a diagram of the ARP cache for communications manager 102;

FIG. 11 is a diagram of a routing table and an ARP cache for a host 108; and

FIG. 12 is a diagram showing how IP addresses and <channel,pipe,LinkID> triples are dynamically assigned.

The reference numbers in the drawings have at least three digits. The two rightmost digits are reference numbers within a figure; the digits to the left of those digits are the number of the figure in which the item identified by the reference number first appears. For example, an item with reference number 203 first appears in FIG. 2.

DETAILED DESCRIPTION

The following Detailed Description will begin with an overview of Internet protocol packets (datagrams) and of the IP addressing architecture employed in the cable data network of the preferred embodiment and will then describe the

physical components of the cable data network of the preferred embodiment. Thereupon the discussion will show how IP addresses are mapped onto these components, how IP addresses are assigned to the components, and how routing of IP packets may be dynamically changed in response to failure of an RF link.

Internet Protocol Packets (data grams): FIG. 3

FIG. 3 shows those parts of an Internet protocol (IP) packet or datagram **301** that are required to understand the following discussion. An IP packet **301** has two main parts, header **303**, which carries control information about the packet, and data **305**, which is the data being transported in the packet. Header **303** has a fixed format and length, while data **305** may have a varying length. All that need be known about the contents of header **303** for the present discussion is that it contains two 32-bit Internet Protocol (IP) addresses, one of which, DEST IPA **307** specifies a destination in the Internet to which IP packet **301** is to be delivered, and the other of which, SRC IPA **309**, specifies the source in the Internet of packet **301**. Sources and destinations of Internet packets **301** are termed herein Internet hosts. An Internet host is an entity in a network which has an IP address and which is capable of responding to at least some of the protocols in the TCP/IP protocol suite. For details on IP addressing and the protocols of the TCP/IP protocol suite, see W. Richard Stevens, *TCP/IP Illustrated: The Protocols*, Addison-Wesley, 1994, which is hereby incorporated by reference into this patent application.

The Internet is a logical network, not a physical network. Internet packets **301** are transported across a variety of different physical networks. While an Internet packet **301** is in a given physical network, it is transported in the same fashion that the physical network transports any kind of data. For example, one common kind of physical network is a LAN that uses the 10 base T protocol. One example of such a LAN is a LAN that uses the Ethernet® protocol developed by Xerox Corporation. In the Ethernet protocol, data moves in packets called frames. Each frame has a preamble **313**, a destination Ethernet address **315**, a source Ethernet address **317**, an ethertype field, which specifies a type of the protocol, a data field **321**, which carries the data, and a frame check sequence **323**, which is an error checking code. When an Ethernet frame **311** is carrying an IP datagram **301**, IP datagram **301** simply occupies data field **301**. It is worth pointing out here that the Ethernet protocol does not examine the contents of data **321**. There may of course be many levels of protocols between an IP datagram **301** and the physical medium upon which the IP datagram is being transported. In the following, only the next level down from the IP level is of concern, and this level is termed generically the link level, with the addresses at that level being termed link addresses. Thus, if the link level employs the Ethernet protocol, the link addresses are DA **315** and SA **317**.

The IP addressing and routing architecture

The IP addressing and routing architecture of the cable data network defines how the IP addresses which are used to route Internet protocol packets (datagrams) in the Internet are mapped onto the networks which make up the cable data network's link level. The architecture has a number of fundamental principles:

Each cable data network defines its own IP addressing domain, i.e., the network defines how IP addresses in a set of IP addresses which has been assigned to the cable data network are assigned to component devices in the cable data network.

All devices in the cable data network which do routing or maintain data bases used in determining routes are IP hosts.

Within the addressing domain, sets of IP addresses are assigned to hosts connected by a LAN to an RF modem, which is in turn connected to a CATV cable that is part of a network in the addressing domain. The RF modem functions as a router for packets addressed to the hosts connected to the LAN.

IP routing in the networks consisting of portions of the cable network is hierarchical. An IP packet addressed to a host is first routed to the proper cable network, then captured by the host's RF modem and finally routed to the host by the RF modem.

The RF modem may receive IP packets addressed to its hosts from two independent link level networks: an RF link level network (for example, a CATV network) and a switched public telephone network. The RF modem may further route outgoing IP packets via the switched public telephone network.

Several advantages flow from these principles:

Because all of the devices that do routing or maintain routing data bases are Internet hosts, IP address assignment, packet rerouting, and network management can be done using the standard DHCP, RIP, and SNMP TCP/IP protocols. For details, see the Stevens reference, supra.

Because the RF modem can receive packets addressed to its hosts not only via the RF link level, but also via the telephone network, if the RF link fails, packets for the hosts can be simply rerouted to the RF modem via the telephone network. Moreover, the rerouting can be done by means of the RIP TCP/IP protocol.

Packets sent to the RF modem via the telephone network may be employed to tune the RF modem to a particular channel in the RF link, making it possible to dynamically assign a channel in the RF link to an RF modem. In effect, a link-level address in the RF link is dynamically assigned to the RF modem.

Because the cable data network can assign its own IP addresses, a mixed static-dynamic policy for assigning addresses may be pursued, with components that are constantly active having statically-assigned IP addresses and components that are intermittently active, such as the RF modems and the hosts attached to them, having dynamically-assigned IP addresses that are assigned at the beginning of activity by the component and are deassigned at the end of activity.

The dynamic assignment of IP addresses to RF modems and their hosts makes it possible to share a small number of IP addresses among a much larger group of users. Moreover, the dynamic assignment of IP addresses can be done by means of the DHCP TCP/IP protocol.

The dynamic assignment of IP addresses to RF modems also makes it possible to share a small number of addresses in the RF link among a much larger group of RF modems.

Network management can be done by means of the SNMP TCP/IP protocol.

The number of IP addresses required in the network is further reduced by giving the RF modems a reusable IP address for use inside the LAN to which a given RF modem's hosts are attached.

Physical Components of the Cable Data Network: FIG. 1

FIG. 1 shows the physical components of cable data network **100** in a preferred embodiment. Cable data network **100** transfers data packets with IP addresses between Internet **150** and hosts **108**, which in a preferred embodiment are PCs or work stations. Cable data network **100** also transfers packets with IP addresses among the components of cable data network **100** and uses Internet **150** to exchange data packets with IP addresses between cable data network **100**

and remotely-located control and management components **111**. These components typically deal with functions such as receiving information about new subscribers or billing.

In a preferred embodiment, cable data network **100** is implemented in a cable television (CATV) system. Packets from Internet **150** that contain the IP address of a host **108(i)** are received in CATV head end **122**, are put in the proper form for transmittal over cable **132** belonging to the CATV system, and are transmitted via cable **132** to RF modem **106(j)** to which destination host **108(i)** is attached. RF modem **106(j)** reads the IP address of host **108** from the packet and routes the packet to host **108(i)**. Packets from host **108(i)** which are intended for a destination in Internet **150** go to RF modem **106(j)**, which routes them via telephone line **131** and public switched telephone network (PSTN) **109** to a telephone modem (Tmodem) **110(k)** in telephone modem pool **135** in head end **122**. Tmodem **110(k)** routes the packet to router **101**, which routes it to Internet **150**. Since public switched telephone network **109** allows bidirectional communication, router **101** may also route packets received from Internet **150** for host **108(i)** to host **108(i)** via tmodem **110(k)** and RF modem **106(j)**. As will be explained in more detail in the following, this route is used in the event of a failure in the CATV portion of network **100**.

Continuing with the details of the implementation of cable data network **100**, data packets are transferred between Internet **150** and CATV head end **122** by means of a transmission medium belonging to a wide-area backbone network **124**. Typically, the transmission medium will be a high-speed, high-capacity fiber optic cable such as a T1 or T3 cable, but it could also be a terrestrial or satellite microwave link. The transmission medium is connected to router **101**, which in a preferred embodiment may be a router belonging to the 7000 series manufactured by Cisco Systems, Inc., San Jose, Calif.

Router **101** is coupled between WAN backbone **124** and local-area network (LAN) **120**, which is the link-level network that connects the components of cable data network **100** which are located in CATV head end **122**. Router **101** may both receive packets from backbone **124** or LAN **120** and provide them to backbone **124** or LAN **120**. Each component connected to LAN **120** has both an IP address and a LAN address on LAN **120**, and router **101** contains a routing table which it uses to route IP packets to IP hosts, including other routers. Router **101** examines every packet it receives on WAN backbone **124** or LAN **120**; if the packet's destination IP address is one of the ones in the routing table, router **101** routes it to the component on LAN **120** which is to receive IP packets having that address; if it is not one of the addresses in the routing table, router **101** routes it to WAN backbone **124**, which takes it to Internet **150**. In each case, router **101** puts the data packet into the proper form to be transmitted via the relevant link-level network.

As will be apparent from the foregoing discussion, LAN **120** and router **101** can be used to route IP packets received from Internet **150** and destined to a host **108** via two routes. The first is via communications manager **102** and cable plant **105**, cable **132**, and RF modem **106**. The second is to host **108** via telephone modem pool **135** and RF modem **106**. Packets from host **108** and from RF modem **106** go via telephone modem pool **135** and LAN **120** to router **101**. In other embodiments, it may also be possible to route packets addressed to RF modem **106** via the first route. Router **101** can finally route packets via Internet **150** between the components in head end **122**, hosts **108**, RF modems **106**, and control and management component **111**.

When packets are to go to a host **108** via cable **132**, they are routed to communications manager **102**, which puts the packets into the proper form for transport by that link-level network. FIG. 4 shows how data is transported on cable **132** in a preferred embodiment. Cable **132** is an RF medium **401** which carries data in a fixed number of channels **403**. Each channel **403** occupies a portion of the range of frequencies transported by cable **132**. Within a channel **403(i)**, data moves in superframes **405**. Each superframe contains a superframe header **414** and a fixed number of fixed-sized superpackets **407**. The only portion of the superframe header that is important to the present discussion is stream identifier (STRID) **415**, which is a unique identifier for the stream of data carried on channel **403**. The combination of a channel's frequency and the stream identifier **415** uniquely identifies the network to which cable **132** belongs in the CATV system. As will be explained in more detail later, this unique identification of the network cable **132** belongs to is used by communications manager **102** to determine which network should receive the IP packets intended for hosts **108** connected to a given RF modem **106(i)**.

Each superpacket **407** contains a header **409** and data **411**. The header contains a link identifier (LinkID) **413** in cable network **132** for an RF modem **106**. The number of superpackets **407** is the number of pipes in channel **403(i)**. When a given RF modem **106(i)** is active, it is associated with a <channel,pipe,link ID> triple, that is, the RF modem **106(i)** is tuned to the channel **403(j)** specified in the triple and watches the superpackets that belong to the pipe specified in the triple. For example, if the RF modem is associated with pipe **3**, it watches superpacket **407(3)** in superframe **405**, and if superpacket **407(3)**'s header **409** contains RF modem **106(i)**'s Link Id **413**, RF modem **106(i)** reads data **411** from superpacket **407(3)**. The <channel,pipe,linkID> triple is thus the link address of RF modem **106(i)** on cable **132**. Data **411** is of course all or part of an IP packet **301**. If the IP address of packet **301** specifies a host **108** connected to RF modem **106(i)**, RF modem **106(i)** routes it to that host **108**.

Returning to communications manager **102**, that component receives IP packets **301** addressed to hosts **108** connected to networks whose link layers are cables **132** connected to head end **105** and routes them to the proper RF modems **106** for the hosts. It does by relating the IP address of an active host **108** to one of the networks and within the network to a <channel,pipe,linkID> triple specifying the RF modem **106** to which the host **108** is connected. As employed in the present context, an active host is one that currently has an IP address assigned to it. Using the information in the routing table, communications manager **102** makes superframes **405** for each channel **403(i)** in the network containing cable **132**. The superframes contain superpackets **407** directed to the RF modems **106** connected to that channel for which communications manager **102** has received IP packets **301**. The superframes are stored in a dual-ported memory which is accessible to QPR modulators **103**.

There is a QPR modulator **103** for each channel **403** in a given network, and the QPR modulator reads the superframes for its channel, digitally modulates the RF signal for the channel according to the contents of the superframes, and outputs the modulated signal to combiner **104**, which combines the outputs from all QPR modulators and provides the combined output to cable plant **105**, which outputs it to cables **132** belonging to the network. The QPR modulators employ quadrature partial response modulation. Of course, any kind of digital RF frequency modulation could be employed as well. It should also be pointed out that any

arrangement could be employed which relates a given RF modem 106 to a portion of the bandwidth of the network to which cable 132 belongs, rather than the <channel,pipe, LinkID> triple used in the preferred embodiment, and that the portion of the bandwidth that carries packets addressed to hosts 108 connected to a given RF modem 106 can be termed in a broad sense the RF modem's channel.

Following cable 132 to RF modem 106, RF modem 106 is connected between cable 132, a LAN 133 to which one or more hosts 108 are connected, and telephone line 131 and provides interfaces to cable 132, LAN 133, and telephone line 131. FIG. 5 shows a block diagram of a preferred embodiment of RF modem 106. The components of RF modem 106 operate under control of CPU 505 and read data from and write data to memory 507, which has three kinds of memory components: static RAM 509, which is nonvolatile, that is, it is writable but retains its contents when RF modem 106 is turned off, dynamic RAM 511, which is volatile, and FLASH RAM 513, which is nonvolatile and writable but will only permit a fixed number of writes. SRAM 509 is used to store data which changes but must be kept across activations of RF modem 106. Examples of such data are the RF modem's telephone number and the addresses of RF modem 106 and hosts 108 on LAN 133. DRAM 511 is used for data that is only valid during an activation, such as the current routing table. FLASH RAM 513 is used for information that changes only rarely, such as the programs executed by CPU 505. In the preferred embodiment, RF modem 106 can load programs it receives in IP packets via telephone line 131 into Flash RAM 513.

Turning to the interfaces and beginning with the interface to cable 132, that interface has two main components, tuner 501 and decoder 503. Tuner 501 can be tuned under control of CPU 505 to a channel 403(i) in cable 132. Tuner 501 further demodulates the superframes 405 it receives on that channel and passes them to decoder 503. Decoder 503 examines superpacket 407(i) for the pipe which carries data addressed to RF modem 106, and if LinkID 413 in superpacket 407(i) specifies RF modem 106, decoder 503 does error correction, decodes the data, and passes it to memory 507. When an IP packet has accumulated in memory 507, CPU 505 examines the destination IP address in the packet, and uses a routing table in memory 507 to determine whether the packet is addressed to a host 108 connected to RF modem 106. If the packet is so addressed, CPU 505 obtains the LAN address corresponding to the IP address. CPU 505 provides the LAN address and the location of the packet in memory 507 to Ethernet integrated circuit 515, which packages the packet into one or more Ethernet frames and outputs it to Ethernet 133.

RF modem may also receive IP packets via phone line 131 and modem chip 517 that are addressed either to the RF modem 106 itself or to one of the hosts 108 connected to RF modem 106. In the first case, RF modem 106 responds to the packet; in the second, it routes the packet to the host as just described for packets from cable 132. When RF modem 106 receives a packet via LAN 133 that is not addressed to RF modem 106 itself, it routes the packet via modem chip 517 and telephone line 131. Included in host 108 is the software 107 necessary to interact with RF modem 106.

Continuing with the portion of the link level that is implemented using the public switched telephone network, modem chip 517 in RF modem 106 is connected by means of a standard analog telephone line 131 to public switched telephone network 109, and RF modem 106 can thus call other telephone numbers via PSTN 109 and be called from other telephone numbers in PSTN 109. In the present case,

when RF modem 106 wishes to set up a session that will permit it to transfer IP packets 301 for a host 108, it calls a telephone number for telephone modem pool 135. The modem pool responds by assigning a telephone modem (Tmodem) 110 to RF modem 106 and assigning RF modem 106 an IP address. As shown in FIG. 1, telephone modem pool 135 is also connected to LAN 120 in head end 122. Telephone modem pool 135 serves as a router with respect to LAN 120 and the telephone connections currently being served as by the tmodems 110 in the modem pool. Once a telephone modem 110 and an IP address have been assigned to RF modem 106, RF modem 106 may send IP packets 301 to the devices connected to LAN 120 and receive IP packets 301 from those devices.

As will be explained in the following, the fact that PSTN 109 provides a bi-directional link between the devices connected to LAN 120 and RF modem 106 is employed to determine where RF modem 106 is in the cable network managed by head end 122, to dynamically assign a <channel,pipe,linkID> triple in cable 132 to RF modem 106, and to provide an alternate route to hosts 108 connected to RF modem 106 when there is a failure in the RF link between head end 122 and RF modem 106.

The remaining device which is connected to LAN 120 is control/management server 125, which in a preferred embodiment is implemented in software executing on a server constructed by SUN Microsystems, Inc., Mountain View, Calif. Control/management server 125 manages CDN 100. It responds to DHCP packets by dynamically allocating IP addresses to hosts 108 and sending SNMP packets to router 101 and communications manager 102 which cause them to set their routing tables as required for the newly-assigned IP address, responds to SNMP trap packets from the devices connected to LAN 120 and from RF modems 106, responds to RIP packets as required to update routings, and maintains the Management Information Database used by the SNMP protocol as well as a list of unassigned IP addresses. A graphical user interface in control/management server 125 shows the current status of CDN 100 and permits operator intervention in the operation of cable data network 100.

IP Addressing Architecture of CDN 100: FIGS. 6 and 2

CDN 100 maintains its own IP address domain. The proprietors of CDN 100 receive a set of 32-bit IP addresses and can apply those addresses to devices connected to CDN 100 as they see fit. FIG. 6 shows 32-bit IP address 601. The 32 bits are divided into two fields: type field 603, which defines the type of IP address 601 and host ID field 613, which identifies a specific host 108. The host IDs are organized into sets of IDs for the networks in the address domain. This is done by means of a technique called classless interdomain routing (CIDR). In this technique, the entire address is a host ID 613 that identifies an individual host; some number of the most significant bits of the host IP address are designated to specify a given network belonging to the domain; these bits are the same for all IP addresses in the given network and make up network ID 605.

Packets with IP addresses that have been assigned using the CIDR technique are routed by means of subnetwork masks. A subnetwork mask 608 is a 32-bit string of bits that is used to mask an IP address, that is, to select that part of the IP address that is currently relevant to the routing process. For example, if the IP address is being routed to the network it belongs to, the only part of the address that is relevant is the part that contains network ID 605. As shown in FIG. 6, in this case, unmasked part 610 selects the bits of network ID 605; masked part 611 hides the remaining bits of

the IP address. Once the packet is in the network identified by network ID **605**, the entire IP address is relevant and none of it is masked.

Using this technique, the proprietors of a domain of IP addresses can easily define the number of hosts in a network. In CDN **100**, the bits of IP address **601** specified by the subnetwork mask that identifies network ID field **605** specify a portion of a metropolitan cable network (for example, a single cable **132**, a single cable plant **105** and the cables radiating from it, or even a single head end **122** and the cables **132** served by it). Host ID field **613** identifies one of the hosts **108** in the network identified by network ID field **605**. As one would expect from the fact that CDN **100** has a relatively small number of CATV cables, a relatively large number of RF modems **106**, and a relatively small number of hosts **108** per RF modem **106**, the number of bits in network ID field **605** is comparatively small.

Comparison of addresses for routing purposes is done using subnetwork masks **608**. The order in which an IP address being routed is compared to addresses in the routing table is by the unmasked length of the address in the routing table. Thus, the address being routed is compared first with addresses that are completely unmasked. For details, see Stevens, supra pp. 7–9 and 140–141.

FIG. 2 shows the IP networks that exist in the cable data network and how they relate to the link level networks. Each addressable component of the cable data network appears in FIG. 2 with the IP addresses and link level addresses that apply to it. As is the case with all IP networks, each host must have its own IP address and must have in addition the address of a gateway in the network to which it can send IP packets for routing. Only one set of the IP networks, namely networks B **208(0 . . . n)** need belong to cable data network IP address domain **202**, that is, the cable data network assigns the addresses in these networks from the set provided to it. In the preferred embodiment, networks A and D also belong to address domain **202**. IP addresses in network A all have network A's NetID **605** and IP addresses in network B **208(i)** all have network B **208(i)**'s NetID **605**. The third IP network is network D **212**. The router for this network is modem pool **135**. In a preferred embodiment, the IP addresses in network D **212** are not visible outside cable data network **100**. In other embodiments, the IP addresses in network D **212** may belong to another domain entirely, for example, one belonging to the telephone company that provides the modem pool.

Continuing with IP network A **206**, this network has LAN **120** as its link level network. LAN **120** connects components of cable data network **100** that are always in use, and consequently, the IP addresses in network A **206** may be statically assigned. Routers with IP addresses in Net A are router **101**, communications manager **102**, and modem pool **135**.

IP network B **208(i)** may be one of several such networks, each of which will have its own statically-assigned NetID **605**. Network B **208(i)** has as its link layer one or more cables **132**, to which RF modems **106** are connected. The router for network B **208(i)** is communications manager **102**. Each active RF modem **206(j)** in network B **208(i)** has a set **210(j)** of IP addresses having network B **208(i)**'s network ID **605** that are available to be assigned to hosts **108** connected to RF modem **206(j)**. An active RF modem **106** is one that has an active host **108** connected to it. Any IP address having the network ID for the network may belong to a given set **210(j)**. The link level network for each set of IP addresses **210(j)** is the LAN **133** connecting the hosts **108** with RF modern **106(j)**. RF modem **106(j)** serves as the

router for that set of addresses. IP addresses of hosts **108** in net B **208(i)** are dynamically assigned by control/management server **125**. When RF modem **106(j)** becomes active, control/management server **125** assigns modem **106(j)** a set of IP addresses for the hosts **108** connected to RF modem **106(j)**. The IP addresses have the NetID **605** for network B **208(i)** and as many host IDs **613** as are required for the hosts **108**. As will be explained in more detail below, every host **108** connected to an RF modem **106(j)** has an IP address for RF modem **106(j)**. Cable data network **100** conserves IP addresses by giving RF modems **106(j)** identical IP addresses on the LANs **133** connecting the RF modems **106** to their hosts **108**.

As indicated before, network **212 D** uses hidden IP addresses belonging to the domain of cable data network **100** in a preferred embodiment, but the IP addresses may also be provided by another party such as a telephone company. The link layer in this network is public switched telephone network **109**. When RF modem **106(j)** dials into modem pool **135**, modem pool **135** dynamically assigns RF modem **106(j)** an IP address. Modem pool **135** also functions as the router in network **212 D**. Modem pool **135** routes incoming IP packets with RF modem **106(j)**'s IP address via network D **212** to RF modem **106(j)**. When the RF link is inoperative, modem pool **135** also routes incoming packets with the IP addresses of the hosts **108** attached to RF modem **106(j)** to RF modem **106(j)**, which routes them further to the hosts. Modem pool **135** additionally routes all outgoing packets received from RF modem **106(j)** via LAN **120** to router **101**.

Router **101** normally routes IP packets destined for network B to communications manager **102** and those destined for network D to modem pool **135**. If there is a failure in network B, router **101** can also route packets destined for a host **108** connected to RF modem **106(j)** to RF modem **106(j)** via network D.

FIG. 2 also shows the IP and link layer addresses by means of which the components of CDN **100** may be reached. Beginning with the components on Net A **206**, router **101** has an IP address **203(b)** of its own in Net A **206** and also has an address **205(a)** on LAN **120** and an address **207** on WAN **124**. Communications manager **102** has an IP address **203(c)** of its own in Net A **206** and an address **205(d)** on LAN **120**. Router **101** also routes all packets to communications manager **102** that are to be carried via the networks B **208** specified in one or more NETID fields **605** in the IP addresses. Continuing with control/management server **125**, that component has an IP address **203(e)** in Net A **206** and a LAN address **205(b)**. Modem pool **135** has an IP address **214(b)** in Net D **212**, a LAN address **205(c)**, and a telephone number **208(a)** in PSTN **109**.

Continuing with network B **208(i)**, a given host **108(k)** has a dynamically-assigned IP address. In the address, the host ID **613** specifies host **108(k)** and the net ID **605** specifies network B **208(i)**. Each host also has a LAN address **211(a)** in LAN **133**. The most complex addressing situation is that of RF modem **106(j)**. RF modem **106(j)** has an IP address **214(a)** in network D **212**, and has a reusable IP address **216**. At the link address level, RF modem **106(j)** is addressed in cable **132** by a <channel,pipe,linkID> triple, has a telephone number **208(b)**, and a LAN address **211(b)** in LAN **133**. Routing and Routing Tables: FIGS. 9–11

Every host in an Internet network has a routing table. The routing table relates destination IP addresses of UP packets that are received in the host to gateway IP addresses of hosts on the same link-level network as the host to which the routing table belongs. If the host is a router, its routing table

will relate IP addresses that are received in the router to IP addresses of hosts on the link-level networks that are connected by the router. Thus, a host can send an IP packet to a host on another link-level network by sending the packet to the router in the host's link-level network that sends packets to the other link-level network. Every host in an Internet network is also capable of executing the ARP protocol, which translates an IP address into a link-level address of the link-level network that the host is connected to.

Actually routing an IP packet received by a host is thus a two-step process. First, the host consults the routing table to find the gateway IP address corresponding to the IP packet's destination IP address; the gateway IP address specifies which host on the link-level network the IP packet is to be sent to; then the host executes the ARP protocol to find the link-level address of the host specified by the gateway IP address. When the host has the link-level address, it puts the IP packet in the form required by the link-level network and sends it to the link-level address. In order to save time in executing the ARP protocol each host also has an ARP cache, which is a table of the current mappings between IP addresses of hosts in the link-level network and the link-level addresses of those hosts. For details on routing tables, see Stevens, supra, pp. 111-117; for details on the ARP protocol, see Stevens, supra, pp.53-64.

FIG. 11 shows a routing table 1101 for a host 108(k) when host 108(k) is connected to cable data network 100. Host 108(k) has only three destinations to which it can route IP packets: to itself; to another host 108(i) connected to LAN 133, or to RF modem 106(j), which is of course a host in LAN 133, but is also the router for all IP packets that have destinations outside LAN 133. There are thus n+2 entries 1103 in routing table 1101, where n is the number of hosts 108 attached to LAN 133. Each entry has three parts: a destination IP address, a gateway IP address, which must be an IP address of a host on LAN 133, and routing information, which indicates among other things whether the host specified by the gateway IP address is a router and the name of the link-layer network upon which the packet is to be routed.

Entry 1103(i) is for the so-called loop-back interface. It has a special IP address that clients and servers on the same host can use to send IP packets to each other. Packets sent to this IP address are processed completely within client 108 and never appear on LAN 133. As can be seen from FIG. 11, the same loopback IP address 1103 is used for both the destination IPA and the gateway IPA. The entries labelled 104 are for the other hosts 108 in set 210(j). Each of these has the full IP address of the given host as both its destination IP address and its gateway IP address. What this means is that when a packet has an IP address that matches the destination IPA in entry 1103(j), its ultimate destination is a host 108(l) and the next step in the routing is for host 108(k) to use the ARP protocol to determine the LAN address corresponding to the packet's gateway IP address and then to send the IP packet to the LAN address.

IP packets whose destination addresses are not in set 210(j) are handled by entry 1103(k), which is the default entry for IP addresses that cannot be routed using other entries 1103. The default IPA 1115 is accordingly the destination IPA. The gateway IPA is the reusable IPA for RF modem 106(j). As will be explained in more detail later, this reusable IPA 1117 does not belong to the set of IP addresses 210(j) that are dynamically assigned to hosts 108 connected to LAN 133 when RF modem 106(j) becomes active. When host 108(k) receives a packet that matches default entry

1103(k), host 108(k) uses the ARP protocol to find the LAN address corresponding to re-usable IPA 1117, that is, the LAN address of RF modem 106(j) and sends the IP packet to RF modem 106(j). Since both the hosts 108 and RF modem 106(j) are connected to LAN 133, the routing info in entries 1104 and 1103(k) specifies LAN 133.

FIG. 10 also shows ARP cache 1119 for host 108(k). Cache 1119 has a cache entry 1120 for each host 108 connected to LAN 133 that currently has an IP address assigned to it, shown at 1122, and a cache entry 1120(j) for RF modem 106(j). In entries 1122, each entry has the IP address 1121 for the host 108 to which the entry belongs and the LAN address 1123 for the host 108; entry 1120(j) has reusable IP address 1117 for RF modem 106(j) and RF modem 106(j)'s LAN address 1125.

FIG. 9 shows the routing tables for router 101, modem pool 135, and RF modem 106.

Beginning with routing table 901 for router 101, for purposes of the present discussion, two routings are of interest in routing table 101. The routing shown by entry 903(i) is for an IP address that specifies a host 108 when the RF link connecting head end 122 to host 108's RF modem 106 is functioning. In entry 903(i), the destination IP address is masked so that only NetID 605 is used for routing. Since that is the case, entry 903(i) matches every destination IP address 307 with that Net ID 605, that is, the net addresses for all of the hosts which are connected to the RF network to which cable 132 belongs. The gateway IP address is IP address 203(c) for communications manager 102. Thus, unless there is an entry 903, whose mask is longer than the one used with entry 903(i), the packet is routed to communications manager 102.

As will be explained in more detail below, as long as the RF link provided by cable 132 to RF modem 106 is functioning, there will only be an entry for the Net ID 605 for the network that RF modem 106 is attached to, and thus all packets directed to hosts 108 attached to modem 106 will be routed via communications manager 102 and cable 132. If all or part of the RF link fails, an entry like that for 903(j) is made in routing table 901 for each host 108 attached to an RF modem 106 whose RF link has failed. In this entry, the unmasked IP address of the host is used as the destination IP address and the gateway IP address is IP address 214(b), which is the address of modem pool 135. As long as entry 903(j) exists in routing table 901, packets addressed to the host 108 specified in the destination IP address will go by way of modem pool 135 and public switched telephone network 109, rather than by way of cable 132.

Continuing with routing table 921 for modem pool 135, this routing table has the same basic structure as routing table 901. Again, there are two entries that are of interest in the present situation. When a given RF modem 106(i) is receiving IP packets addressed to its hosts 108 by way of cable 132, it is still capable of receiving IP packets addressed to RF modem 106(i)'s IP address 214(a), and consequently, there will be an entry 922(j) for that IP address as long as RF modem 106(i) is active. In that entry, the destination IP field 930 and the gateway IP field 932 will both have IP address 214(a).

When RF modem 106(i)'s RF link via cable 132 has failed, there will be another entry 922(i) for each of the hosts 108 attached to RF modem 106(i). This entry's destination IP field 929 will contain the IP address 929 for the host 108, and the gateway IP address field 931 has IP address 214(a) for RF modem 106(i). Thus when the RF link is down, packets for hosts 108 routed to modem pool 135 by router 101 are further routed by modem pool 135 to RF modem 106(i).

Continuing with routing table **933** for RF modem **106**, this routing table has an entry **935** for each host **108** attached to LAN **133** and two others that are of interest in the present context. In the entries **936** for the hosts **108**, each contains the host's IP address as both its destination IP address and gateway IP address. Entry **935(j)**'s destination IP address is the IP address **214(a)** assigned RF modem **106(j)** by modem pool **135** when RF modem **106(j)** became active; the gateway IP address here is again RF modem **106(i)**'s reusable IP address **1117**. This entry routes messages for RF modem **106(j)** received via PSTN **109** to RF modem **106(j)** itself. The final entry, **935(k)**, is the default entry; the gateway IP address is IP address **214(b)** for modem pool **135**, and thus, all remaining packets received by RF modem **106(j)** are routed via PSTN **109** to modem pool **135** and from thence to router **101**.

The routing table for communications manager **102** shown at **949**. Again, there are three entries **951** of interest. Entry **951(i)** routes all IP packets destined for the networks managed by communications manager **937**; in the destination IPA portion of this entry, everything is masked but the net ID portion of the address. Entry **951(j)** routes packets intended for communications manager **937** itself, the destination IPA and the gateway IPA are IPA **203(c)**; for communications manager **102**. Default entry **951(k)**, finally, has as its gateway IPA the IP address **203(b)** of router **101**; consequently, all other IP packets are routed back to router **101** via LAN **120**.

FIG. **10**, finally, shows the implementation of ARP cache **1001** in communications manager **102**. The technique used to implement the table is hashing, which is a standard technique for reducing search time in large tables. In ARP cache table **1001**, the IP addresses **1003** for incoming packets addressed to a host **108** are hashed, that is, they are input to a function **105** which produces small integer values **1009** from the IP addresses. The small integer is used as an index into a hash array **1011**, whose elements are pointers **1013** to lists of IP addresses that hash to the index of element **1013**. Each list entry **1015** has three fields: field **1017** contains a destination IP address; field **1019** is a pointer to the next list entry **1015** in the list, and CCB pointer **1021** is a pointer to a data structure called a CCB block **1023** which specifies the frequency, pipe number, and linkID to which packets having IP address **1017** may be sent. The fields of CCB block **1023** are IP address **1025**, which has the same IP address as IPA **1017**, modulator number **1029**, which effectively specifies the frequency, pipe number **1031**, which specifies the pipe, linkID **1033**, which specifies the RF modem **106**, and next pointer **1035**, which specifies the next CCB block **1023**. Translation of an IP address into the corresponding <channel,pipe number,linkID> triple works by hashing the IP address to get the index of list pointer **1013**, following list pointer **1013** to the list, searching list entries **1015** until one is found that has the IP address being translated as its IP address **1017**, and going to that list entry **1015**'s CCB block **1023** to find the information needed to form the triple. It is worth noting here that it is the structure of ARP cache **1001** which makes it possible in a preferred embodiment to use any IP address in the network of the cable **124** to which an RF modem **106(j)** is attached for a host **108** that is attached to RF modem **106(j)**.

Dynamic Assignment of Resources: FIG. **12**

A problem in the design of networks that employ IP addresses is that the IP addresses are only 32 bits long. The maximum number of address consequently 2^{32} , and the enormous growth of the Internet has resulted in a shortage of IP addresses. One of the techniques that cable data

network **100** employs to reduce the number of IP address needed in cable data network **100** is the dynamic assignment of IP addresses to hosts **108** in network B **208(i)** and of the <channel,pipe,link ID> triples used to specify destinations of data in cable **132** to RF modems **106(j)**. By dynamic assignment is meant here that the IP addresses in a given set of addresses C **210(j)** and the <channel,pipe,link ID> triple listened to by RF modem **106(j)** are assigned to RF modem **106(j)** for the period of time that RF modem **106(j)** is active. When RF modem **106(j)** is not active, the IP addresses are available for assignment to other hosts **108** and the <channel,pipe,link ID> triple is available for assignment to another RF modem **106(k)**. Since only a small percentage of hosts **108** is active at a given time, dynamic assignment makes it possible to share a relatively small number of IP addresses and <channel,pipe,link ID> triples among a much larger number of users. It should be further noted here that the binding between a <channel,pipe,link ID> triple and the set of IP addresses **210(j)** is also dynamic, i.e., what IP addresses correspond to a given <channel,pipe,link ID> triple is decided only when the IP addresses and the <channel,pipe,link ID> triple are assigned.

FIG. **12** shows the system used to do dynamic assignment of IP addresses and <channel,pipe,link ID> triples in a preferred embodiment. Dynamic assignment is handled cooperatively by control/management server **125** and communications manager **102**. Both are hosts in IP network A **206** and have TCP/IP SNMP (simple network management protocol) agents **1203** and **1233**, and control/management server **125** and communications manager **102** can cooperate by means of SNMP messages. For details on SNMP, see Stevens, supra, pp. 359–387.

Control/management server **125** further has a DHCP server **1201** and an IPA manager **1204** executing on it. DHCP server **1201** responds to IP packets belonging to the TCP/IP DHCP (Dynamic Host Configuration) protocol. As will be explained in more detail below, this protocol is employed to dynamically assign an IP host an IP address. Details on the DHCP protocol may be found in R. Droms, *Dynamic Host Configuration Protocol*, RFC 1541, obtainable in March 1997 at the URL www.cis.ohio.state.edu/htbin/rfc/rfc1541.html. The IP addresses themselves are managed by IPA manager **1204**. Communications manager **102** also has executing on it a channel manager **1231**, which manages the <channel,pipe,link ID> triples assigned to RF modems **106**.

Assignment of IP addresses to hosts **108** connected to RF modem **106** and of a <channel,pipe,link ID> triple to RF modem **106** begins when DHCP server **1201** receives a DHCPDISCOVER message from an RF modem **106(j)** that has become active. The DHCPDISCOVER message requests assignment of a number of IP addresses for the hosts **108** attached to RF modem **106(j)**. In the preferred embodiment, the DHCPDISCOVER message includes the IP address **1215** of RF modem **106(j)** (assigned it by modem pool **135**). The vendor-encapsulatedoptions part of the DHCPDISCOVER message includes the following, as shown at **1213** in FIG. **12**:

The number of addresses being requested **1216**. An address is requested for every host **108** connected to RF modem **106(j)**.

<frequency,streamID> pair **1217** and **1219**. These uniquely identify the cable **132** that RF modem **106** is connected to.

The IP addresses of the hosts **108** are assigned by IP address manager **1204**, with the assistance of SNMP agent **1203**. The first step in assigning the IP addresses is deter-

mining which IP network B **208(i)** the cable **132** belongs to that RF modem **106(j)** is connected to. IPA manager **1204** uses <freq,streamID>,NETID> table **1237** to make this determination. Each entry in the table relates a <frequency, streamID> pair to a Net ID. All IP addresses assigned in the IP network B **208** identified by the Net ID must include the Net ID. The information in table **1237** is provided by channel manager **1231** in communications manager **102**.

When IPA manager **1204** has the Net ID, it can assign the IP addresses. IPA manager **1204** has a list **1211(i)** of free IP addresses for each network B **208(i)**, and it takes a set of IP addresses that has the number of addresses specified in address range **1216** from the free list **1211** for the network B **208(i)**. IPA manager **1204** then provides an SNMB set message with the IP addresses to SNNT agent **1203**. As shown by arrow **1241**, SNMP agent **1203** sends the message to SNMP agent **1233** in communications manager **102**.

SNMP agent **1233** passes the message on to channel manager **1231**, which maintains a **1235** of free CCB blocks **1023** for each network. Channel manager **1231** finds a free CCB block in the list for the specified Net ID. The block is for a particular <channel,pipe> pair. Channel manager **1231** fills the IP address from the SNMP message and a link ID for the RF modem **106** into the CCB block **1023** and adds CCB block **1023** to ARP table **1101**. Channel manager **1231** then uses SNMP agent **1233** to send a return message via SNMP agent **1203** to IPA manager **1203**. As shown at arrow **1243**, the return message contains the IP address and the <channel, pipe,link ID> triple that has been assigned to it. Channel manager **1231** adds entries for the newly-assigned IP addresses to its assigned IPA data base **1207**. Each entry contains the IP address and the <channel,pipe,link ID> triple. Now that all of the information needed to relate the IP addresses of RF modem **106(j)**'s hosts **108** to a <channel, pipe,link ID> triple on cable **132** is available, DHCP server **1201** returns a DHCPOFFER IP packet to RF modem **106(j)** which is to receive the IP packets whose destination IP address belong to the set of addresses **210(j)** corresponding to the <channel,pipe,linkID> triple.

In a preferred environment, IP addresses assigned to the hosts belonging to RF modem **106** are deassigned when RF modem **106(j)** becomes inactive. This is detected by modem pool **135** when RF modem **106(j)** hangs up and modem pool **135** sends an SNMP message to SNMP agent **1203** in control/management server **125** informing agent **203** of that fact. Agent **1203** removes the entries for the IP addresses for the hosts **108** connected to RF modem **106(j)** from its data base and returns the IP addresses to IPA manager **1204**, which puts them on the proper free list **1211(i)**. Agent **1203** also sends an SNMP message to SNMP agent **1233** in communications manager **102** informing communications manager **102** that the IP addresses have been deassigned. Agent **1233** passes the IP addresses to channel manager **1231**, which removes the CCB blocks for the IP addresses from ARP table **1101** and returns them to the free CCB block list **1235** for the network to which the addresses belong.

In other embodiment, additional techniques may be employed to ensure that IP addresses and <channel,pipe,link ID> triples that are not being used are deassigned. One technique is the lease mechanism in the DHCP protocol. This mechanism assigns an IP address only for a limited period of time; if another DHCP protocol renewing the lease is not received from RF modem **106(j)** within the limited period of time, the IP address is deassigned. Another is to monitor the number of packets sent to an IP address over a period of time. If there are none, the address is deassigned. The same technique may be used with <channel,pipe,link

ID> triples; if there is no traffic on the <channel,pipe,link ID> triple, it is deassigned. In general, techniques analogous to those used to recover cache entries or memory pages may be used with IP addresses and <channel,pipe,link ID> triples.

Setting up a Session with RF Modem **106**

FIG. 7 shows the interactions **701** between the components of cable data network **100** when a RF modem **106(i)** is inactive and a user of host **108(j)** connected to RF modem **106(i)** wishes to become connected to Internet **150**. The user executes routines in software **107** which cause host **108(j)** to send a setup request to RF modem **106(i)** at modem **106(i)**'s address in LAN **133**, as shown at **702**. Included in the setup request is authentication information such as a user identification and password and the telephone number of telephone modem pool **135**. In the preferred embodiment, the authentication is for all of the hosts **108** connected to RF modem **106**. RF modem **106** responds by first sending a dummy IP address to host **108(j)** and then dialing the telephone number. The dummy IP address has a short lease, i.e., is valid for only a short time. Telephone modem pool **135** responds by setting up a Point-to-Point Protocol (PPP) link via PSTN **109** between RF modem **106** and a tmodem **110(k)**. Once this is done, RF modem **106** sends the authentication information to modem pool **135**, which passes them on to control/management server **125**. Control management server **125** then checks the authentication information, and if it is valid, control/management server **125** assigns an IP address in network D **21Z** to RF modem **106(i)**. It returns the IP address to RF modem **106(i)**. RF modem **106(i)** can now use TCP/IP protocols to communicate with the head end devices connected to LAN **120**.

RF modem **106(i)** must next obtain an IP address for host **108(j)** and the <channel,pipe,link ID> triple which it is to receive packets addressed to host **108(j)**'s IP address on cable **132**. To do this, it sends a DHCPOFFER IP packet **703** to modem pool **135**. Included in the vendor-encapsulated options portion of the protocol are the IP address of RF modem **106(i)** and a <frequency, streamID **405**> pair which RF modem **106(i)** obtains by listening to any frequency on cable **132**. As explained earlier in the discussion of superframes **405**, the <frequency,streamID> pair uniquely identifies which cable **132** RF modem **106(i)** is connected to.

Modem pool **135** receives DHCPOFFER packet **703**, adds modem pool **135**'s IP address to it, and unicasts the packet via net A **206** to DHCP server **1201**. DHCP in control/management server **125** responds to packet **703** and assigns IP addresses for the hosts **108** attached to RF modem **106(j)** and a <channel,pipe,link ID> triple to RF modem **106** as described above. The IP addresses have leases that are long enough for the period for which an RF modem **106** is typically active. Next, control/management server **125** sends a DHCPOFFER packet **715** addressed to RF modem **106**'s IP address. This is routed to modem pool **135**. The OFFER packet contains the following information:

Range of IP addresses for the hosts **108** connected to RF modem **106**.

An IP address for RF modem **106** in Ethernet **133**. As will be explained in more detail below, this IP address is not unique to RF modem **106**.

the subnet mask for the host IP addresses.

IP addresses in network A **206** for a domain name server, for SNMP agent **1203**, for communications manager **102**, and for router **101**.

Information about where RF modem **106** can obtain current firmware.

The <channel,pipe, link ID> triple that has been assigned to RF modem **106**.

Telephone modem pool **135** forwards the DHCP response packet to RF modem **106(i)** (**717**) and RF modem **106(i)** sets its tuner **501** to listen on the specified frequency and its decoder **503** to read superpackets on the specified pipe when they have the RF modem's link ID.

By this time, the lease on host **108(j)**'s dummy IP address is about to expire and host **108(j)** sends a DHCPDISCOVER packet requesting a new IP address. RF modem **106(i)** responds by assigning one of the IP addresses it received in its DHCPOFFER packet to host **108(j)** and sending a DHCPOFFER packet with the IP address to host **108(j)**. Similarly, when RF modem **106(i)** receives a DHCPDISCOVER packet from any of the other hosts **108** attached to LAN **133**, it assigns one of the IP addresses to that host **108** and sends the host **108** a DHCPOFFER packet that contains the assigned IP address.

In other embodiments, RF modem **106(i)** may further respond to the DHCP OFFER packet **715** by sending an acknowledgment IP packet via PSTN **109** and modem pool **135** to communications manager **102** (**719**). Communications manager **102** responds to the acknowledgment by sending an acknowledgment **721** on the cable **132** at the channel and pipe RF modem **106(i)** is listening to. The acknowledgment contains at least RF modem **106(i)**'s Taking Down a Session with RF Modem **106**

As long as any of hosts **108** is connected to Internet **150**, RF modem **106** listens for super packets addressed to it at the <channel,pipe,link ID> triple for RF modem **106** and maintains its connection via the telephone network to modem pool **135**. When the last host **108** shuts down its connection to Internet **150**, RF modem **106** hangs up on the telephone line connecting it to modem pool **135**. Modem pool **135** responds to the fact that RF modem **106** has hung up with a DHCP release message to DHCP server **1201**. The DHCP release message specifies the IP addresses assigned to RF modem **106**.

Server **125** sends an SNMP packet to communications manager **102** instructing it to remove the entries for the IP addresses from its ARP cache **1001**. Communications manager **102** returns the channel,pipe,linkID> triple to its list of free <channel,pipe,linkID> triples. When server **125** receives an SNMP acknowledgment from communications manager **102**, it deletes the entries for the IP addresses for the hosts **108** connected to the IP modem from its data base and returns the IP addresses to its list of free IP addresses. In other embodiments, the DHCP protocols used to get and free IP addresses for hosts **108** may originate with the individual host **108**.

RF Modem **106** as a Proxy DHCP Server

The entities in a network that respond to DHCP protocols are known as DHCP servers. In cable data network **100**, the DHCP server is implemented in software running on control/management server **125**. Additionally, however, each active RF modem **106(i)** functions as a proxy DHCP server. By this is meant that it retains enough information locally to handle DHCP protocols that originate with hosts **108** connected to RF modem **106(i)**. In so doing, it appears to host **108** as a standard DHCP server and further greatly decreases the amount of traffic required to provide hosts **108** with IP addresses.

Standard DHCP servers are always active; thus, the standard Internet client software running on host **108** expects that the DHCP server will always respond to a DHCPDISCOVER packet from a host with a DHCPOFFER packet that contains an IP address for host **108**. RF modem

106, however, is not always active and may have to establish a connection with Network A **206** and use the DHCP protocol to obtain the IP addresses for subnetwork C **210(j)** before it can respond to a DHCPDISCOVER packet from a host **108**. For that reason, when RF modem **106** first becomes active, it provides the host **108** that caused it to become active with a short-lived dummy IP address as previously described. RF modem **106** then obtains a set of IP addresses for its hosts **108** as previously described. Once it has the IP addresses, it responds to DHCPDISCOVER packets from the hosts **108** by assigning the hosts **108** IP addresses from the set. There is thus no need in these cases to send a DHCPDISCOVER packet to modem pool **135** and control/management server **125**.

Automatic Rerouting in the Event of a Failure of the RF Link: FIG. 8

An important advantage of cable data network **100** is that if the RF link to a RF modem **106(i)** fails, cable data network **100** automatically reroutes packets addressed to hosts **18** connected to that RF modem so that they are routed by way of modem pool **135** and public switched telephone network **109** to RF modem **106**. When the RF link is again operative, cable data network **100** automatically again reroutes the packets via the RF link. This automatic fallback and restoration feature takes full advantage of the fact that public switched telephone network **109** is bidirectional and of the fact that an active RF modem **106** has an IP address by means of which it is accessible via modem pool **135** and PSTN **109**.

The automatic fallback and restoration feature is implemented using the TCP/IP routing information (RIP-2) protocol, described beginning at page 29 of Stevens, supra. This protocol is used in networks employing IP addresses to propagate addressing information among the routers in the network. Any other protocol which performs this function could also be employed. Typically, each router in a network will broadcast a RIP packet to the other routers every thirty seconds or so. The RIP packet contains the current routing table of the router sending the RIP packet. The other routers read the RIP packet and update their routing tables accordingly. A triggered RIP packet is sent each time the metric for a route changes. The metric is a value which expresses the cost of sending a packet by the route. Each router keeps track of the time interval since it last received an RIP packet from each of the other routers, and if the time interval exceeds a predetermined maximum, the router removes the routes it received from that router from its routing table.

In the preferred embodiment, when RF modem **106** is active, it is constantly listening to cable **132**. If tuner **501** detects that there is no RF signal on the channel it is listening to or decoder **503** detects that it is no longer receiving superframes **405**, or that it can no longer decode the superpackets **407** it is receiving, or that the number of superpackets **407** with errors has increased above a predetermined threshold, tuner **501** or decoder **503** signals an error condition to CPU **505**. What happens next is shown in FIG. 8. Portion **701** of the figure is the setup scenario of FIG. 7; portion **801** shows how RF modem **106** and system **100** respond when such an error condition occurs.

As shown at **803**, when the error condition occurs, the routing tables in router **101** and communications manager **102** are routing IP packets addressed to hosts **108** via communications manager **102** and cable **132**; IP packets from hosts **108** to IP addresses in Internet **150** are being routed via RF modem **106**, PSTN **109**, telephone modem pool **133**, LAN **120**, and router **101**. This condition is indicated in portion **801** at **803**. At **805**, RF modem **106**

detects a failure in the RF link; RF modem **106** thereupon sends an SNMP trap packet, i.e., an error message that uses the TCP/IP SNMP (Simple Network Management Protocol) addressed to control/management server **125** via PSTN **109** and telephone modem pool **135**. The network management system (NMS) is implemented by programs executing on server **125**, and NMS responds to the trap packet by recording the fact that there has been a failure in the RF link in its system management data bases. The NMS system response may also include other actions such as generating a display showing the problem in the NMS graphical user interface (GUI) or triggering an alarm.

Next, RF modem **106** sends a triggered RIP packet to modem pool **135** with RF modem **106**'s routing table. Modem pool **135** responds to the RIP packet by adding the IP addresses of the hosts **108** to its own routing table **921**. It then sends a triggered RIP packet with the changes to the routers on LAN **120**. Router **101** responds to the RIP packet by adding the IP addresses for the hosts **108** to its routing table **901**. In other embodiments, RF modem **106** may send triggered RIP packets directly to modem pool **135** and router **101**. As explained in the discussion of routing tables above, the result of these changes is that packets addressed to hosts **108** are now routed to hosts **108** via modem pool **135** and PSTN **109**. Control/management server **125** also receives the RIP packet and generates an NMS trap **815** for the NMS system which indicates to it that the fallback setup has been completed. The NMS system stores that information in its data base and changes the displays showing the network accordingly.

It is important to note here that as long as the RF link is operative and RF modem **106** is active, the routing of packets to hosts **108** connected to RF modem **106** does not change. Consequently, when the RF link is operative, RF modem **106** does not produce RIP packets. However, as long as the RF link is inoperative, RF modem **106** periodically produces RIP packets in the fashion of other routers and the RIP packets are sent to modem pool **135** and router **101** as just described. The fallback routing for the IP addresses belonging to the hosts **108** continues as long as RF modem **106** continues to send RIP packets. If RF modem **106** senses that the RF link is again operative, RF modem **106** sends another trigger RIP packet with its routing table, but with the metric for reaching the hosts **108** set so high that modem pool **135** and router **101** remove the entries for the hosts IP addresses. Thereupon, RF modem **106** ceases sending RIP packets. If RF modem simply ceases sending RIP packets, for example because a user has turned it off, the entries for the hosts IP addresses are removed from the routers in the manner described in the discussion of the RIP protocol above.

Reusable IP Addresses for RF Modems **106**: FIGS. **11** and **13**

As mentioned above, a major goal in the design of cable data network **100** is reducing the number of IP addresses required for the cable data network. One technique used to achieve this goal is giving all RF modems **106** in a network the same reusable IP address in the LANs **133** to which the hosts **108** for which RF modem **106** is the router are attached. This is possible because RF modem **106**'s IP address in LAN **133** is used only by hosts **108** attached to LAN **133**; IP packets sent to RF modem **106** from other hosts are sent to IP address **214(a)** in network D **212**, which is provided by modem pool **135**. Since RF modem **106**'s IP address in LAN **133** is not visible outside LAN **133**, the IP address can be the same in all LAN **133**s. As indicated in the discussion of setting up a session above, RF modem **106**

receives its IP address in LAN **133** in the DHCP OFFER packet that contains the IP addresses for its hosts **108** and RF modem **106**'s <channel,pipe,linkID> triple. The savings of IP addresses made possible by this technique are significant. For example, many LANs **133** will be in private households and will have only a single PC as a host **108**. Both the PC and RF modem **106** must have an E address on LAN **133**. It should further be noted that because reusable IP address **117** is used only within the LANs **133** connected to RF modem **106**, there is no need that it even be an IP address in the address domain of cable data network **100**.

Conclusion

The foregoing Detailed Description has disclosed to those skilled in the relevant arts how to make and use a cable data network which is fully integrated into the Internet, which takes advantage of the bidirectional nature of the telephone system to establish a control path between the head end of the cable data network and the RF modems attached to the CATV cable and to provide an alternate path for data being sent to hosts attached to the RF modem in case of failure of the RF link, which dynamically assigns IP addresses to hosts and link addresses to the RF modems, which employs the RF modems as routers, and which saves IP addresses by reusing the IP addresses of RF modems in the LANs to which they are attached.

While the Detailed Description presents the best mode presently known to the inventors of implementing the cable data network, it will be immediately apparent to those skilled in the relevant arts that the principles used to implement the cable data network may be employed in many other circumstances. For example, the RF link may be replaced by any unidirectional link and the telephone line may be replaced by any bidirectional link that is independent of the RF link. Similarly, the LAN that connects the RF modem to the hosts may be replaced by any medium which provides a bidirectional connection between RF modem and hosts.

Moreover, the techniques described herein for dynamically assigning IP addresses to hosts will work with any kind of logical network addresses, including, for example, virtual circuit numbers. Similarly, the techniques described for dynamically assigning <channel,pipe,linkID> triples to RF modems can be used equally well to dynamically assign any kind of link-level address. The techniques will also work with any technique for subdividing the bandwidth of the unidirectional connection among a number of modems.

Finally, the TCP/IP protocols employed in the preferred embodiment may be replaced by any other protocols which have the same effect. In particular, the DHCP protocol may be replaced by any protocol which can be used for dynamic assignment of logical network addresses, the RIP protocol may be replaced by any protocol which communicates changes in routings to routers, and the SNMP protocol may be replaced by any kind of network management protocol.

The foregoing being the case, the Detailed Description is to be understood as being illustrative and not restrictive and the scope of the invention claimed herein is to be determined not by the Detailed Description but rather by the attached claims as interpreted with the full breadth permitted under the patent laws.

What is claimed is:

1. A method employed in at least one server of managing the allocation of a set of addresses to an RF modem, the method comprising the steps performed in the at least one server of:

receiving at least one first packet from the RF modem; determining a number of addresses to allocate to the RF modem based upon information on a plurality of

23

- addresses and upon information in the at least one first packet, the number of addresses being at least two;
 allocating a set of addresses for the RF modem, the set of addresses comprising the number of addresses determined in the determining step, the set of addresses comprising at least two addresses; and
 communicating the set of addresses to the RF modem with at least one second packet, the RF modem capable of assigning each address of the set of addresses to at least one host.
2. The method of claim 1, wherein the information in the at least one first packet comprises the number of addresses to be allocated.
3. The method of claim 1, further comprising the step of maintaining the information on the plurality of addresses, the plurality of addresses comprising allocated addresses and unallocated addresses, the information on the plurality of addresses comprising information on which addresses of the plurality of addresses are allocated addresses and which addresses of the plurality of addresses are unallocated addresses.
4. The method of claim 3, wherein the allocating step changes the information on the plurality of addresses so that the set of addresses for the RF modem is added to the allocated addresses and removed from the unallocated addresses.
5. The method of claim 4, wherein the at least one first packet comprises identifying information for the RF modem that is allocated the set of addresses.
6. The method of claim 5, further comprising the steps of:
 maintaining the identifying information for the RF modem; and
 associating the identifying information for the RF modem with the set of addresses added to the allocated addresses.
7. The method of claim 6, further comprising the steps of:
 ascertaining that the set of addresses is no longer used by the RF modem; and
 deallocating the set of addresses by changing the information on the plurality of addresses so that the set of addresses is removed from the allocated addresses and added to the unallocated addresses.
8. The method of claim 7, further comprising the step of disassociating the identifying information for the RF modem from the set of addresses removed from the allocated addresses and added to the unallocated addresses.
9. The method of claim 7, wherein the ascertaining step further comprises receiving at least one third packet from the RF modem, the at least one third packet comprising the identifying information for the RF modem.
10. The method of claim 9, wherein the at least one third packet is received from the RF modem as a result of the RF modem determining that the at least one host is finished with an assignment of an address from the set of addresses.
11. The method of claim 7, wherein the set of addresses and the plurality of addresses both comprise logical addresses.
12. The method of claim 11, wherein the logical addresses are Internet Protocol (IP) addresses.

24

13. The method of claim 12, wherein the at least one first packet and the at least one second packet conform to a Dynamic Host Configuration Protocol (DHCP).
14. A method employed in an RF modem for obtaining a set of addresses from at least one server, the method comprising the steps performed in the RF modem of:
 sending at least one first packet to the at least one server;
 receiving at least one second packet from the at least one server, the at least one second packet comprising a set of addresses allocated by the at least one server based upon information on a plurality of addresses and upon information in the at least one first packet, the set of addresses comprising at least two addresses; and
 assigning a first address from the set of addresses to at least one host.
15. The method of claim 14, wherein the information on the plurality of addresses is maintained by the at least one server, the plurality of addresses comprising allocated addresses and unallocated addresses, the information on the plurality of addresses comprising information on which addresses of the plurality of addresses are allocated addresses and which addresses of the plurality of addresses are unallocated addresses.
16. The method of claim 14, wherein the at least one first packet comprises identifying information for the RF modem that is allocated the set of addresses.
17. The method of claim 14, wherein the information in the at least one first packet comprises a number specifying how many addresses are to be allocated by the server.
18. The method of claim 14, further comprising the steps of:
 determining that each address of the set of addresses is no longer used by at least one host; and
 communicating at least one third packet to the at least one server, the at least one third packet comprising identifying information for the RF modem.
19. The method of claim 18, wherein the set of addresses and the plurality of addresses both comprise logical addresses.
20. The method of claim 19, wherein the logical addresses are IP addresses.
21. The method of claim 20, wherein at least one first packet and the at least one second packet conform to a Dynamic Host Configuration Protocol (DHCP).
22. The method of claim 14, wherein the assigning step further comprises the steps of:
 receiving a request from the at least one host for an address assignment;
 selecting the first address from the set of addresses; and
 sending a response to the at least one host, the response comprising the first address as a fulfillment of the request for address assignment.
23. The method of claim 22, wherein the first address is a logical address.
24. The method of claim 23, wherein the logical address is an IP address.
25. The method of claim 24, wherein the request and response conform to a Dynamic Host Configuration Protocol (DHCP).

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,405,253 B1
DATED : June 11, 2002
INVENTOR(S) : Schutte et al.

Page 1 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [57], **ABSTRACT,**

Line 9, delete "modern," and insert therefore -- modem, --

Column 1,

Line 19, delete "A" between "Merrill," and "and"

Line 22, delete "Litik" and insert therefore -- Link --

Line 24, delete "6,301,233," and insert therefore -- 6,301,223, --

Line 47, delete "it" between "Address" and "which"

Line 66, delete "Scott E. Urastar," and insert therefore -- Scott E. Hrastar, --

Column 2,

Line 32, delete "Florence." and insert therefore -- Florence, --

Line 60, delete "Apr. 3, 1966," and insert therefore -- Apr. 3, 1996, --

Line 62, delete "08/738,6681," and insert therefore -- 08/732,668, --

Line 65, delete "Koperda, et al," and insert therefore -- Koperda et al., --

Column 3,

Lines 17 and 19, delete "Moura, et al.," and insert therefore -- Moura et al., --

Line 54, delete "1P" and insert therefore -- IP --

Line 55, delete "EP" and insert therefore -- IP --

Column 6,

Line 12, delete "RF modern" and insert therefore -- RF modem --

Column 8,

Line 31, delete "insuperframe" and insert therefore -- in superframe --

Column 9,

Line 7, delete "channel." and insert therefore -- "channel". --

Line 42, delete "exames" and insert therefore -- examines --

Column 10,

Line 15, insert after "explained" the words -- in more detail --

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,405,253 B1
DATED : June 11, 2002
INVENTOR(S) : Schutte et al.

Page 2 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 11,

Line 33, delete "B 208(0 . . n)" and insert therefore -- B 208(0 . . n) --

Line 67, delete "RF modern" and insert therefore -- RF modem --

Column 12,

Line 64, delete "UP" and insert therefore -- IP --

Column 13,

Line 17, delete "lnk-level" and insert therefore -- link-level --

Line 30, delete "itself;" and insert therefore -- itself, --

Line 48, insert a period after "gateway IPA"

Line 62, insert a period between "IPA" and "The"

Column 14,

Line 13, delete "11200)" and insert therefore -- 1120(j) --

Line 38, delete "RF ink" and insert therefore -- RF link --

Column 15,

Line 18, insert -- is -- before "shown"

Line 24, delete the semi-colon after "203(c)"

Line 64, delete "dresses" and insert therefore -- addresses --

Line 65, delete "address" and insert therefore -- addresses --

Column 16,

Line 1, delete "address" and insert therefore -- addresses --

Line 15, delete "if" and insert therefore -- of --

Line 41, delete "www.cis.ohio state.edu/" and insert therefore -- www.cis.ohio-state.edu/ --

Line 56, delete "vendor-encapsulatedoptions" and insert therefore -- vendor-encapsulated-options --

Column 17,

Line 15, delete "SNNT" and insert therefore -- SNMP --

Line 19, insert "list" before "1235"

Line 57, delete "embodiment" and insert therefore -- embodiments --

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,405,253 B1
DATED : June 11, 2002
INVENTOR(S) : Schutte et al.

Page 3 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 18,

Line 11, delete "1080)" and insert therefore -- 108(j) --

Line 35, delete "108(0)'s" and insert therefore -- 108(j)'s --

Column 19,

Line 9, delete "1080)" and insert therefore -- 108(j) --

Line 26, insert "linkID." after "106(i)'s"

Line 42, delete "channel.pipe.linkID>" and insert therefore -- <channel.pipe.linkID> --

Line 47, delete "fist" and insert therefore -- list --

Line 56, delete "aproxy" and insert therefore -- a proxy --

Column 20,

Line 18, delete "RF modet106(i)" and insert therefore -- RF modem 106(i) --

Line 19, delete "18" and insert therefore -- 108 --

Column 21,

Line 45, delete "hosts" and insert therefore -- hosts' --

Line 49, delete "hosts" and insert therefore -- hosts' --

Column 22,

Line 7, delete "E address" and insert therefore -- IP address --

Signed and Sealed this

Eighth Day of October, 2002

Attest:



Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office