



US006408237B1

(12) **United States Patent**
Cho

(10) **Patent No.:** **US 6,408,237 B1**
(45) **Date of Patent:** ***Jun. 18, 2002**

(54) **AIR BAG SYSTEM FOR AN AUTOMOBILE**

(76) Inventor: **Myungeun Cho**, Balcones Station
11900 Jollyville Rd., Austin, TX (US)
78759

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/477,748**

(22) Filed: **Jan. 4, 2000**

(51) **Int. Cl.**⁷ **G06F 17/00**

(52) **U.S. Cl.** **701/45; 180/169; 180/232; 180/271; 340/903; 340/435; 340/436; 280/730.2; 280/736**

(58) **Field of Search** **701/45, 46, 47; 180/167, 169, 232, 271; 340/903, 425.5, 435, 436; 280/730.2, 736**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,071,160 A * 12/1991 White et al. 280/735

5,330,226 A * 7/1994 Gentry et al. 280/735
5,482,314 A * 1/1996 Corrado et al. 280/735
5,646,613 A * 7/1997 Cho 340/903
5,959,552 A * 9/1999 Cho 340/903


* cited by examiner

Primary Examiner—Gertrude Arthur

(57) **ABSTRACT**

An air bag system for an automobile including an external detection system, an internal detection system, a wireless system, a computer processing unit (CPU), at least one external air bag inflation device, and at least one internal air bag inflation device. The air bag system controls inflation size and absorption quantity of an air bag by means that the CPU receives information from the external detection system, the internal detection system, and the wireless system for a calculation based on the information inputted in the CPU and transmits control signal to the relevant parts of the air bag inflation device to enable the external air bag and the internal air bag to effectively inflate for protecting automobile body and object against damage and passengers against personal injury from a collision.

58 Claims, 24 Drawing Sheets






FIG 1





FIG 2






FIG 4




FIG 5






FIG 6






FIG 9




FIG 10




FIG 11




FIG 12




FIG 13




FIG 14




FIG 15




FIG 16




FIG 17




FIG 18




FIG 19




FIG 20




FIG 21




FIG 22




FIG 23




FIG 24




FIG 25




FIG 26




FIG 27




FIG 28




FIG 29




FIG 30




FIG 31

INFORMATION INPUTTED IN CPU

106 : criterion for inflation of an external air bag of the roadway vehicle
107 : inflation sizes and shapes of an external air bag of the roadway vehicle based on various collision situations
108 : absorption quantity of an external air bag of the roadway vehicle in conformity with impact intensity
109 : criterion for estimated injury inflicted to passengers from a collision
110 : inflation sizes and shapes of an internal air bag of the roadway vehicle
111 : absorption quantity of an internal air bag of the roadway vehicle
112 : location of each external air bag inflation device on the roadway vehicle
113 : location of each internal air bag inflation device on the roadway vehicle
114 : minimum allowable time window (MATW)
115 : estimated period of time
116 : nature of the roadway vehicle
117 : net weight of the roadway vehicle
118 : shape of the roadway vehicle and size of the shape
119 : nature of the external air bag of the roadway vehicle

FIG 32

EXTERNAL DETECTION SYSTEM & CPU

120 : moving speed of the roadway obstacle relative to the roadway vehicle

121 : direction of motion of the roadway obstacle relative to the roadway vehicle

122 : moving location of the roadway obstacle relative to the first sensing device on the roadway vehicle based on shape of the roadway obstacle and size of the shape

123 : location of an external air bag inflation device on the roadway obstacle

124 : nature of the roadway obstacle

125 : gross weight of the roadway obstacle

126 : nature of the external air bag on the roadway obstacle

FIG 33

WIRELESS SYSTEM & CPU

123 : location of an external air bag inflation device on the roadway obstacle
124 : nature of the roadway obstacle
125 : gross weight of the roadway obstacle
126 : nature of the external air bag on the roadway obstacle
127 : location of the roadway obstacle
128 : inflation size and shape of an external air bag in an applicable zone of the roadway obstacle
129 : absorption quantity of an external air bag in an applicable zone of the roadway obstacle

FIG 34

INTERNAL DETECTION SYSTEM & CPU

130 : position, posture, and size of passengers
131 : weight of passengers
132 : weight of goods

FIG 35




FIG 36




FIG 37

AIR BAG SYSTEM FOR AN AUTOMOBILE**BACKGROUND OF THE INVENTION**

1. Field of the Invention

The present invention relates to an air bag system against automobile collision and specifically relates to a computer processor based system for controlling air bag inflation size and air bag absorption quantity for reducing injury to passengers and reducing damage to vehicles and objects involved in an accident.

2. Description of the Related Art

Various schemes have been adopted to protect passengers of a vehicle from injuries resulting from collisions. Numerous attempts in the art from bumper construction to air bags to vehicular control and warning systems have come about to protect the occupants of the vehicle. A plethora of patents exemplify various automotive devices known for human protection. For example, U.S. Pat. No. 4,673,937 issued on Jun. 16, 1987 to Davis describes a Doppler radar system for a vehicle providing driver warning, vehicle brake application and air bag deployment. U.S. Pat. No. 5,071,160 issued to White et al. on Dec. 10, 1991 describes a circuit for actuating a vehicle passenger safety restraint such as an air bag. U.S. Pat. No. 5,330,226 issued to Gentry et al. on Jul. 19, 1994 describes an apparatus for controlling actuation of a vehicle occupant restraint system. U.S. Pat. No. 5,482,314 issued to Corrado et al. on Jan. 9, 1996 describes a system for sensing the presence, position, and type of an occupant in a passenger seat of a vehicle for use in enabling or disabling a related air bag activator. U.S. Pat. No. 5,785,347 issued to Adolph et al. on Jul. 28, 1998 describes an occupant sensing and crash behavior system for a motor vehicle determines the presence and location of an occupant to then control the deployment of supplemental restraint systems such as air bag or inflatable seat/shoulder belts. U.S. Pat. No. 5,829,782 issued on Nov. 3, 1998 to Breed et al. describes a vehicle interior identification and monitoring system to identify and monitor contents and/or parts of the passenger compartment of a motor vehicle. U.S. Pat. No. 5,871,232 issued on Feb. 16, 1999 to White describes an occupant position sensing system.

German Patent No. 2 256 146 issued on Jun. 7, 1973 describes a vehicle air cushion to prevent injury during a collision to occupants of an automobile. German Patent No. 3 809 074 issued on Oct. 5, 1989 describes an air bag protection system for a vehicle. German Patent No. 4 005 598 issued on Aug. 29, 1991 describes a method of protecting motor vehicle occupants that involves detecting the acceleration of the vehicle and activating an occupant protection device when a defined level of acceleration is exceeded.

Despite this regard for reducing human danger, in most collisions the damage to the vehicle is unmitigated; creating substantial costs for repair or replacement. Few proposals have been made to reduce the cost of repair or replacement of an automobile involved in a collision. U.S. Pat. No. 4,906,019 issued on Mar. 6, 1990 to Takase et al. describes a motor vehicle collision sensing device. U.S. Pat. No. 5,106,137 issued on Apr. 21, 1992 to Curtis describes a vehicle bumper with combination foam and air bag energy absorber. U.S. Pat. No. 5,314,037 issued on May 24, 1994 to Shaw et al. describes an automobile collision avoidance system. U.S. Pat. No. 5,461,357 issued on Oct. 24, 1995 to Yoshioka et al. describes an obstacle detection device for a vehicle for detecting an obstacle so the vehicle can take a responsive and appropriate action for avoiding the obstacle.

U.S. Pat. No. 5,565,870 issued on Oct. 15, 1996 to Fukuhara et al. describes a radar apparatus that measures a distance to a target and the relative speed of the target. U.S. Pat. No. 5,633,705 issued on May 27, 1997 to Asayama describes an obstacle detecting system for a motor vehicle which is capable of detecting not only the distance to an obstacle existing in front of the motor vehicle and the width thereof, but also its height to thereby allow a motor vehicle control to be effected more appropriately with high reliability. U.S. Pat. No. 5,646,613 issued to Cho on Jul. 8, 1997 describes a system for minimizing automobile collision damage using radiant energy detectors and externally deployed air bags for aiding in damage reduction of automobile collisions. U.S. Pat. No. 5,959,552 issued to Cho on Sep. 28, 1999 describes a system for minimizing automobile collision damage and personal injury using detection sensor unit, computer processing unit (CPU), energy absorbing inflation devices, and external and internal air bag inflation devices.

German Pat. No. 2 922 273 issued on Jan. 22, 1981 describes a vehicle collision safety device with an inflatable air bag that transmits an ultrasonic beam ahead of a vehicle to detect an approaching obstacle. European Patent No. 0 210 079 issued on Jan. 28, 1987 describes a Doppler radar system for a motor vehicle.

However, none of the above inventions and patents taken either singularly or in combination, except U.S. Pat. Nos. 5,646,613 and 5,959,552, describe an air bag system capable of providing collision protection against both personal injuries and automobile body damage. Thus a system for inflation of air bag solving the aforementioned problems is desired.

SUMMARY OF THE INVENTION

The present invention is an air bag system for an automobile. The air bag system serves to provide collision protection against injury to passengers and pedestrians and damage to vehicles and objects. The system includes at least one external air bag inflation device, at least one internal air bag inflation device, an external detection system, an internal detection system, a wireless system, and a computer processing unit. The external detection system is installed in the automobile body, lamp post, and satellite for detecting information relating to vehicles, objects, and pedestrians. The internal detection system is installed in the automobile body for detecting information relating to passengers and goods inside the automobile. The wireless system installed in the automobile body, lamp post, and satellite for providing information to a CPU. The CPU installed in the automobile is provided information by the external detection system, the internal detection system, and the wireless system to process the information to control the function of each related device installed in the external air bag inflation device installed inside of the automobile body and the function of each related device installed in the internal air bag inflation device installed inside of the automobile body.

Accordingly, it is a principal object of the invention to provide an automobile air bag system with the CPU function to control inflation, inflation size of the air bag, and impact absorption of the external and internal air bags.

It is another object of the invention to provide an automobile air bag system with a structure of external and internal air bag inflation devices.

These and other objects of the present invention will become readily apparent upon further review of the following specification and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a preferred embodiment of an air bag system according to the present invention.

FIG. 2 is an illustration of the operation sequence of an air bag system according to the present invention.

FIG. 3 is an environmental view of an air bag system according to a preferred embodiment of the present invention.

FIG. 4 is a block diagram of a preferred embodiment of the wireless system according to the present invention.

FIG. 5 is a first section of an internal detection system according to the present invention.

FIG. 6 is a second section of the internal detection system according to the present invention.

FIG. 7 is an illustration of an air bag inflation device right before inflation according to a preferred embodiment.

FIG. 8 is an illustration of an air bag inflation device during inflicting according to a preferred embodiment.

FIG. 9 is a flow chart of a preferred computer process for calculation of a criterion for inflation of an external air bag in an applicable zone of the roadway vehicle.

FIG. 10 is a flow chart of a preferred computer process for calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle.

FIG. 11 is a flow chart of a preferred computer process for calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle based on disaccord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 12 is a flow chart of a preferred computer process for calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle based on accord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 13 is a flow chart of a preferred computer process for calculation of a criterion for inflation of an internal air bag in an applicable zone of the roadway vehicle based on disaccord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 14 is a flow chart of a preferred computer process for calculation of a criterion for inflation of an internal air bag in an applicable zone of the roadway vehicle based on accord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 15 is a flow chart of a preferred computer process for calculation of an inflation size and shape of an internal air bag in an applicable zone of the roadway vehicle.

FIG. 16 is a flow chart of a preferred computer process for calculation of an absorption quantity of an internal air bag in an applicable zone of the roadway vehicle based on disaccord.

FIG. 17 is a flow chart of a preferred computer process for calculation of an absorption quantity of an internal air bag in an applicable zone of the roadway vehicle based on accord.

FIG. 18 is a flow chart of a preferred computer process for calculation of a moving location of the roadway obstacle relative to the roadway vehicle based on shapes of both the roadway vehicle and the roadway obstacle and the sizes of both the shapes.

FIG. 19 is a flow chart of a preferred computer process for calculation of an anticipated collision point.

FIG. 20 is a flow chart of a preferred computer process for calculation of disaccord between an anticipated collision

point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 21 is a flow chart of a preferred computer process for calculation of accord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle.

FIG. 22 is a flow chart of a preferred computer process for calculation of an anticipated real collision point based on disaccord.

FIG. 23 is a flow chart of a preferred computer process for calculation of an anticipated real collision point based on accord.

FIG. 24 is a flow chart of a preferred computer process for calculation of an anticipated collision point inside of the roadway vehicle.

FIG. 25 is a flow chart of a preferred computer process for comparison of the nature of a roadway obstacle to the nature of the roadway vehicle.

FIG. 26 is a flow chart of a preferred computer process for comparison of the nature of a roadway obstacle to the nature of an external air bag on the roadway vehicle.

FIG. 27 is a flow chart of a preferred computer process for comparison of the nature of an external air bag on the roadway obstacle to the nature of an external air bag on the roadway vehicle.

FIG. 28 is a flow chart of a preferred computer process for comparison of the weight of a roadway obstacle to the weight of the roadway vehicle.

FIG. 29 is a flow chart of a preferred computer process for calculation of an automobile's total combined weight (including automobile body, any passengers, and goods).

FIG. 30 is a flow chart of a preferred computer process for calculation of a minimum allowable distance window.

FIG. 31 is a flow chart of a preferred computer process for calculation of an estimated distance from a detection point at which a roadway obstacle is detected to a point of impact between an external air bag of the roadway vehicle and a roadway obstacle.

FIG. 32 is a listing of information inputted into the CPU according to a preferred embodiment of the present invention.

FIG. 33 is a listing of information obtained by the external detection system and calculated by the CPU according to a preferred embodiment of the present invention.

FIG. 34 is a listing of information obtained by the first wireless apparatus and calculated by the CPU according to a preferred embodiment of the present invention.

FIG. 35 is a listing of information obtained by the internal detection system and calculated by the CPU according to a preferred embodiment of the present invention.

FIG. 36 is a block diagram of a photoelectron system according to a preferred embodiment of the invention.

FIG. 37 is a block diagram of a preferred system for supplying electric energy to relevant parts via the conventional battery from the photoelectron system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is an air bag system for an automobile. An environmental perspective view of an air bag system 10 is shown in FIG. 3. Structural components of the air bag system will be described with reference to FIGS. 1 and 2 and FIGS. 4 through 8 and FIGS. 36 and 37, and software components of the air bag system will be described with reference to FIGS. 9 through 35.

The air bag system may best be appreciated by referring to the block diagram shown in FIG. 1. As suggested by FIG. 1, the information obtained by the external detection system 26, the wireless system 29, and internal detection system 28 is transmitted to the CPU 30 for processing based on the information inputted in the CPU 30 to generate control signals. The control signals are then transmitted by conventional communication means to each related external air bag inflation device 159 and each related internal air bag inflation device 160 for controlling deployment, impact absorption, inflation size of the appropriate external air bags and internal air bags respectively, and then related external air bag and internal air bag must be inflated prior to collision as seen in FIG. 2.

The present invention anticipates the external detection system 26 being designed to incorporate any one of a variety of conventional radiant energy (electromagnetic spectrum) or sonic energy (ultrasonic, acoustic) technologies, each being capable of detecting information relating to the objects situated on the roadway. As illustrated, the external detection system 26 preferably includes a plurality of sensing devices.

For example as seen in FIG. 3;

A first sensing device 40 is installed in the roadway vehicle 12 for detecting information relating to the obstacles surrounding the roadway vehicle 12. The detected information is then transmitted by the first sensing device 40 to the CPU 30 for processing.

A second sensing device 42 is attached to a conventional roadside lamp post 46 positioned along the roadside for detecting information relating to the objects on the roadway from a position above the roadway 19. Information detected by the second sensing device 42 is transmitted to the CPU 30 by a wireless system to be discussed later in this disclosure.

A third sensing device 44 is installed in a conventional communication satellite 48 orbiting about the earth's atmosphere. The third sensing device 44 preferably incorporates a technology that may be developed in the future for detecting information relating to the objects positioned on the earth surface from a position located in the earth's atmosphere. Information detected by the third sensing device 44 is transmitted to the CPU 30 by the wireless system.

A fourth sensing device 45 is installed in a roadway obstacle 27 for detecting information relating to the roadway vehicle and the obstacles surrounding the roadway obstacle 27.

The present invention also requires a detectable coating material 165 that is capable of being easily detected by the external detection system 26. The detectable coating material 165 is required for an efficient execution of the external detection system 26. In distinguishing object there is another device called as the pattern recognition system. The pattern recognition system recognizes an object by comparing an information of the object detected by a sensor to the information stored in the CPU. If the object is slightly different from the information stored in the CPU, the pattern recognition system will recognize the object as the same item, even if it is not the same item. Therefore, the pattern recognition system is not acceptable to be used in the present invention because an error in identification could cause disastrous effects. Using the detectable coating material 165 together with the external detection system 26 allows for the present system to accurately distinguish if the object is able to inflict damage to the vehicle and/or injury to the passengers at collision. It also allows for the present system to

accurately detect if the object should be protected from damage and to know if the roadway obstacle contains an external air bag inflation device 159. In order that the external detection system 26 functions accurately, the Government must dictate which objects are required to be coated with the detectable coating material 165. The object that is able to cause damage to a vehicle, injury to a vehicle's occupants, or be damaged by the vehicle at collision must be coated as shown in FIG. 3. Another detectable coating material 165 different from the material mentioned above needs to be selected for a coating on the external air bag inflation device 159 or on the surface of an outer portion where an external air bag inflation device is internally installed in a vehicle as shown in FIG. 3. These two kinds of coating materials need to be legalized for use as detectable coating material 165.

The wireless system 29 preferably includes a plurality of wireless apparatuses placed at a variety of locations on and surrounding the roadway vehicle 12 to transmit and receive information to and from the CPU 30.

As seen in FIG. 3, the first wireless apparatus 68 is installed in the roadway vehicle 12 for receiving information from a source such as the second wireless apparatus 70, the third wireless apparatus 72, or the fourth wireless apparatus 74 and transmitting the information to the CPU 30 on the roadway vehicle 12 for processing. The first wireless apparatus 68 also receives signal from the fourth sensing device 45 and transmits the information to the CPU 30 on the roadway vehicle 12 for an obtainment of the location of the roadway obstacle. Additionally the first wireless apparatus 68 receives information from the CPU 30 and transmits the information to the second wireless apparatus 70 installed on the roadway obstacle 27.

The third wireless apparatus 72 connected to the third sensing device 44 is installed on a communication satellite 48 in the atmosphere to receive information relating to a roadway situation detected by the third sensing device and transmit the information to the first wireless apparatus 68 of the roadway vehicle.

The fourth wireless apparatus 74 connected to the second sensing device 42 is attached to the top of a roadside lamp post 46 for transmitting information relating to a roadway situation detected by the second sensing device 42 to the first wireless apparatus 68 installed in the roadway vehicle 12.

A representative block diagram of the wireless system 29 is shown in FIG. 4. According to a preferred embodiment of the present invention, the first wireless apparatus 68 receives information from the second wireless apparatus 70, the third wireless apparatus 72, the fourth wireless apparatus 74, and the fourth sensing device 45 then transmits the information to the CPU 30 for processing. The first wireless apparatus 68 also receives information transmitted by the CPU 30 and then transmits that information to the second wireless apparatus 70.

A preferred configuration of the internal detection system 28 may best be appreciated by referring to FIGS. 5 and 6. The internal detection system 28 includes a plurality of sensors (e.g., 50, 52, 54, 56) placed at a variety of locations inside of the roadway vehicle 12 for detecting various characteristics of the passengers situated inside of the roadway vehicle 12 (e.g., sitting posture, position, size of passengers, and weight of passengers and goods).

For example;

A first sensor 50 is installed inside of the automobile overlying the passengers' seat 60 of the roadway vehicle 12 for detecting size, location, posture, and position of the

passengers. The first sensor **50** may incorporate conventional radiant energy electromagnetic spectrum), sonic energy (ultrasonic and acoustic), or camera technology to accomplish the stated functions.

A second sensor **52** is positioned behind the front seats of the roadway vehicle **12** for detecting information relating to the position of passengers seated in the roadway vehicle **12**. The second sensor **52** preferably incorporates conventional technology to accomplish the stated function. According to a preferred embodiment of the invention, the second sensor **52** serves to detect passengers' posture, position, and size based on the number of times a seat belt **62** is wrapped around the second sensor **52**.

At least a third sensor **54** is installed in the passengers' seat **60** for detecting various information relating to the passengers such as posture, size, position, weight, and location in the roadway vehicle **12** by means of sensing passengers' pressure. The third sensor **54** may incorporate conventional technology for accomplishing these functions.

At least a fourth sensor **56** is installed in the bottom portion **64** of the trunk **66** for detecting weight of the goods stored therein by means of sensing goods' pressure. The fourth sensor **56** may incorporate conventional technology for accomplishing this function.

To maximize the efficiency of the air bag **76**, the air bag **76** must inflate completely prior to a collision. Thus the CPU **30** is programmed to control inflation size of the air bag **76**. As seen in FIG. 2, the external air bag inflation device **159** is installed in the roadway vehicle **12** for enabling an external air bag to inflate outwardly from the inside of the roadway vehicle prior to a collision and serves to protect the automobile body **16** of the roadway vehicle **12**, obstacles, passengers, and pedestrians in a collision situation. By contrast, the internal air bag inflation device **160** is installed in an internal section of the roadway vehicle **12** for releasing the internal air bag prior to a collision between the automobile body **16** and passengers in a collision situation. Thereby, the internal air bag serves to protect passengers from personal injuries and death caused by an automobile accident.

Further details relating to each of the aforementioned air bag inflation devices may be better understood by referring to the representative air bag inflation device **80** shown in FIGS. 7 and 8. FIG. 7 shows the state of the air bag inflation device **80** prior to inflation of an air bag **76** contained inside of the air bag inflation device **80**. As shown, the air bag **76** is stored on a roller **155** in a wound up position inside of the air bag inflation device **80** until the air bag **76** is needed against a collision.

By contrast, FIG. 8 shows the shape of the air bag inflation device **80** when the air bag **76** is in a state of inflation. The air bag inflation device **80** comprises an inflator **153**, a roller **155**, a first roller sensor **156**, a second roller sensor **156-1**, a motor **157**, a first absorption device **158**, a second absorption device **158-1**, and an air bag **76** having an external layer **154** and an internal layer **154-1**.

The inflator **153** is a computer-controlled inflation device connected by conventional communication means to the CPU **30** for enabling the CPU **30** to control the operation of the inflator **153** for inflating the air bag **76**. Upon receiving a command signal from the CPU **30**, the inflator **153** is switched on by conventional computer-controlled switching means. The inflator **153** is connected by conventional means to both the external layer **154** and the internal layer **154-1** of the air bag for enabling the inflator **153** to inflate the external layer **154** and the internal layer **154-1**.

The roller **155** is contained inside of the air bag inflation device **80** and rotatably attached thereto for enabling the

roller **155** to be rotated inside the air bag inflation device **80**. A first roller sensor **156** is attached to an inside surface of the air bag inflation device **80** while a second roller sensor **156-1** is attached to the outside surface of the roller **155** or providing a means incorporated with the first roller sensor by which the number of rotations of the roller **155** is detected. The information detected by the first roller sensor **156** and the second roller sensor **156-1** moving past each other during deployment is transmitted by conventional means to the CPU **30** for enabling the CPU **30** to calculate number of revolutions made by the roller **155** during the deployment. Using an attachment means, the air bag **76** is attached to the roller **155** for enabling the air bag **76** to be wound up around the roller **155**, thereby retracting the air bag **76** inside of the air bag inflation device **80**. The roller **155** is capable of being rotated in a first direction **82** for enabling the air bag **76** to be released from the roller **155**.

The motor **157** is attached to the roller **155** to provide a means by which to rotatably drive the roller **155**. The motor is designed to be electrically driven in a second direction **84** for the motor **157** to enable to oppose and stop the rotation of the roller **155** in the first direction **82**. The motor **157** is a conventional motor designed to be controlled by the CPU **30**. The CPU **30** is connected to the motor by conventional communications means for enabling the CPU **30** to control the operation of the motor **157**. Accordingly, by using conventional control means, the motor **157**, the first roller sensor **156**, the second roller sensor **156-1**, and CPU **30** are used in combination to control inflation size of the air bag **76** by controlling position of the roller **155**.

The air bag **76** can be formed with a single layer or preferably formed with multi-layers. But in this description as a sample, external layer **154** and internal layer **154-1** that compose an air bag **76** will be described as seen in FIG. 8. The external layer **154** and the internal layer **154-1** aim at providing higher strength as compared to a conventional single layered air bag. The external layer **154** defines a substantially closed boundary to form a first air space **92** inside of the air bag to form a primary air cushion used to dampen a collision impact on the air bag **76**. Preferably, the external layer **154** has the shape of a conventional air bag. The internal layer **154-1** defines a substantially closed boundary to form a secondary air space **94**, thereby providing a means to further dampen a collision impact on the air bag **76**.

A first absorption device **158** and a second absorption device **158-1**, as relief valves controlled by the CPU **30**, are connected to the external layer **154** and the internal layer **154-1** respectively to provide an absorption means for absorbing collision impact intensity by means of the gas leaking from the air bag **76** made by collision impact pressure at a collision.

According to the present invention, each of the aforementioned absorption devices incorporates conventional technology for enabling the applicable absorption device to be controlled by the CPU **30**. The CPU **30** is programmed to set each absorption device (**158**, **158-1**) according to a controlled opening size of the absorption device based on an anticipated impact intensity so that the air bag **76** becomes to absorb a collision impact by allowing the gas to leak.

Further details relating to a preferred computer process for controlling the air bag system **10** are now described. The present invention uses conventional control system technology in combination with the CPU **30** to control inflation of the air bag for protecting the roadway vehicle, roadway obstacle, pedestrians and passengers from a collision,

wherein the algorithm used for the air bag system **10** is based on the physics relating to the roadway situations. A preferred computer process for calculating a criterion for inflation of an external air bag in an applicable zone of the roadway vehicle **147** is illustrated by the flow chart shown in FIG. **9**. The criterion is calculated by performing the following steps:

1. calculation of an anticipated damage **142** based on following conditions:
 - a. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
 - b. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
 - c. a comparison of the nature of the roadway obstacle to the nature of the roadway vehicle **138** (referring to FIG. **25**);
 - d. an anticipated collision point **134** (referring to FIG. **19**);
2. calculation of an external air bag inflation device in an applicable zone of the roadway vehicle **145** based on the anticipated collision point **134** and the information inputted into the CPU relating to the location of the external air bag inflation device on the roadway vehicle **112** (referring to FIG. **32**);
3. calculation of a criterion for inflation of an external air bag in an applicable zone of the roadway vehicle **147** based on the following information:
 - a. an external air bag inflation device in an applicable zone of the roadway vehicle **145**;
 - b. anticipated damage **142**;
 - c. a criterion for inflation of an external air bag on the roadway vehicle **106** (referring to FIG. **32**); and
 - d. a minimum allowable time window **114** (referring to FIG. **32**) and a minimum allowable distance window **114-1** (referring to FIG. **30**) for the roadway vehicle.

To maximize the efficiency of the external air bag, a complete inflation of the external air bag must be made before a collision within the period of the minimum allowable time (distance) window. Thus, the inflation size of the external air bag must be decided prior to its inflation. A preferred computer process for calculating an inflation size of an external air bag is illustrated by the flow chart shown in FIG. **10**.

First, an amount of space to be occupied by an inflated external air bag of the roadway vehicle **143** is calculated based on the following information:

1. an external air bag inflation device in an applicable zone of the roadway vehicle **145** (referring to FIG. **9**);
2. minimum allowable time window for the roadway vehicle **114** (referring to FIG. **32**);
3. minimum allowable distance window of the roadway vehicle **114-1** (referring to FIG. **30**);
4. an estimated period of time in speed **115** that elapses between a point in time when a roadway obstacle is detected and a point in time when the roadway obstacle collides against an inflated external air bag of the roadway vehicle (referring to FIG. **32**);
5. a distance **115-1** that covers from a detection point on the roadway obstacle when the roadway obstacle is detected by the external detection system to a point of impact between an inflated external air bag of the roadway vehicle and the roadway obstacle (referring to FIG. **31**);
6. an anticipated collision point **134** (referring to FIG. **19**);
7. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**); and

8. a moving location of the roadway obstacle relative to the roadway vehicle considering the shapes of the roadway vehicle and the roadway obstacle and the sizes of both the shapes **133** (referring to FIG. **18**).

Second, the CPU **30** processes a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** based on the following information:

1. When there is disaccord between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle **135**:
 - a. an external air bag inflation device in an applicable zone of the roadway vehicle **145** (referring to FIG. **9**);
 - b. a space to be occupied by an inflated external air bag of the roadway vehicle **143**; and
 - c. inflation sizes and shapes of an external air bag of the roadway vehicle based on various collision situations **107** (referring to FIG. **32**);
2. When there is accord between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle **135-1**, inflation size of an external air bag is calculated to be half the size of an inflated external air bag of the roadway vehicle based on disaccord with the following information:
 - a. an external air bag inflation device in an applicable zone of the roadway vehicle **145** (referring to FIG. **9**);
 - b. a space to be occupied by an inflated external air bag of the roadway vehicle **143**; and
 - c. inflation sizes and shapes of the external air bag of the roadway vehicle based on various collision situations **107** (referring to FIG. **32**).

Safety for the roadway vehicle, the roadway obstacle, pedestrian, and passengers in collision situation depends on the absorption capability of the external air bag in an inflated condition upon subjection to a collision impact. For maximum performance, the CPU **30** is programmed to calculate an absorption quantity of the external air bag based on an anticipated collision situation, in order for the CPU **30** to control the absorption device (valve or port) on the external layer of the air bag **158** and the absorption device (valve or port) on the internal layer of the air bag **158-1**.

A preferred computer process for calculating an absorption quantity of an anticipated impact intensity is described below based on disaccord or accord between an anticipated collision point and the location of an external air bag inflation device on a roadway obstacle. The flow chart in FIG. **11** illustrates a preferred computer process for calculating an anticipated impact intensity **142-1** when disaccord **135** exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle. The CPU **30** calculates an anticipated impact intensity **142-1** based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on disaccord **136** (referring to FIG. **22**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);
5. a comparison of the nature of the roadway obstacle to the nature of the external air bag of the roadway vehicle **139** (referring to FIG. **26**); and

11

6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**).

FIG. **12** shows a flow diagram illustrating a preferred computer process for calculating an anticipated impact intensity **142-1** when accord **135-1** exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle. When accord **135-1** is found, the CPU **30** calculates an anticipated impact intensity **142-1** based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on accord **136-1** (referring to FIG. **23**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);
5. a comparison of the nature of the external air bag of the roadway obstacle to the nature of the external air bag of the roadway vehicle **140** (referring to FIG. **27**);
6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**); and
7. an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128**.

A calculation of an absorption quantity for the external air bag in an applicable zone of the roadway vehicle **149** is based on the following information as seen in FIG. **11** and FIG. **12**:

1. an external air bag inflation device in an applicable zone of the roadway vehicle **145** (referring to FIG. **9**);
2. an anticipated impact intensity **142-1**; and
3. absorption quantities of an external air bag of the roadway vehicle in conformity with impact intensity **108** (referring to FIG. **32**).

A calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128** is made when accord is found through one of the following two procedures:

1. CPU **30** determines an inflation size of external air bag of the roadway obstacle to be half the size of the external air bag of the roadway vehicle at disaccord; or
2. the inflation size of an external air bag in an applicable zone of the roadway obstacle may be obtained by the wireless system **29**.

A preferred computer process for calculation of a criterion for inflation of an internal air bag according to the present invention is now described. A preferred computer process for calculating an anticipated damage **142-2** when disaccord **135** is found between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle is illustrated by the flow chart shown in FIG. **13**. The anticipated damage **142-2** is calculated based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on disaccord **136** (referring to FIG. **22**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);

12

5. a comparison of the nature of the roadway obstacle to the nature of the external air bag on the roadway vehicle **139** (referring to FIG. **26**);

6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**); and

7. a calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle **149** (referring to FIG. **11**).

A preferred computer process for calculating an anticipated damage **142-2** when accord **135-1** is found between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle is illustrated by a flow chart shown in FIG. **14**. When accord **135-1** is found, the anticipated damage **142-2** is calculated based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on accord **136-1** (referring to FIG. **23**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);
5. a comparison of the nature of an external air bag on the roadway obstacle to the nature of an external air bag on the roadway vehicle **140** (referring to FIG. **27**);
6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**);
7. a calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle **149** (referring to FIG. **12**);
8. an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128**; and
9. an absorption quantity of an external air bag in an applicable zone of the roadway obstacle **129** (referring to FIG. **34**).

Next, a criterion for inflation of an internal air bag in an applicable zone of the roadway vehicle **150** is calculated based on the following information as seen in FIG. **13** and FIG. **14**:

1. an internal air bag inflation device in an applicable zone of the roadway vehicle **146**, which is calculated based on an anticipated collision point inside of the roadway vehicle **137** (referring to FIG. **24**) and location of each internal air bag inflation device of the roadway vehicle **113** (referring to FIG. **32**);
2. an anticipated damage **142-2**;
3. a criterion for an estimated injury inflicted to passengers from a collision **109** (referring to FIG. **32**);
4. a minimum allowable time window for the roadway vehicle **114** (referring to FIG. **32**); and
5. a minimum allowable distance window for the roadway vehicle **114-1** (referring to FIG. **30**).

Thereafter, the inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128** is made based on one of the following methods when accord is found between an anticipated collision point and the location of an external air bag of the roadway obstacle:

1. Calculate an inflation size of an external air bag of the roadway obstacle to be half the size of an external air bag of the roadway vehicle where disaccord exists; or

13

2. the inflation size of an external air bag of the roadway obstacle may be obtained by the wireless system **29**.

The present invention anticipates a possibility of injury to be inflicted to passengers when the internal air bag inflates. To avoid the severity of such injury, the passengers need to keep their sitting positions as far as possible from the internal air bag inflation device **160**, but it is unreasonable to expect that the passengers will always sit as far from the internal air bag inflation device **160** without moving. That is, passengers are always apt to be movable and get close to the internal air bag inflation device **160** when a collision occurs. To avoid such dangerous situation, inflation size of the internal air bag must be controlled for protection of the passengers.

A preferred computer process for calculating an inflation size of the internal air bag according to the present invention may best be appreciated by referring to the flow chart shown in FIG. **15**. The volume of space to be occupied by an inflated internal air bag of the roadway vehicle **144** is calculated based on the following information:

1. an anticipated collision point inside of the roadway vehicle **137** (referring to FIG. **24**);
2. position, posture, and size of passengers **130** (referring to FIG. **35**); and
3. an internal air bag inflation device in an applicable zone of the roadway vehicle **146** (referring to FIG. **14**).

The CPU **30** then processes for a calculation of an inflation size and shape of an internal air bag in an applicable zone of the roadway vehicle **151** based on the following information:

1. an internal air bag inflation device in an applicable zone of the roadway vehicle **146**;
2. a volume of space to be occupied by the inflated internal air bag of the roadway vehicle **144**; and
3. an inflation size and shape of an internal air bag of the roadway vehicle **110** (referring to FIG. **32**).

The efficiency of an internal air bag for minimizing injuries to passengers at collision in spite of the use of an external air bag depends on absorption capability of the internal air bag for the impact intensity. According to the present invention, the CPU **30** is programmed to calculate an absorption quantity of the internal air bag based on an anticipated collision situation for controlling the absorption device (valve or port) on the external layer of the air bag **158** and absorption device (valve or port) on the internal layer of the air bag **158-1**.

A preferred computer process for calculating an absorption quantity of an internal air bag according to the anticipated collision situation for maximizing the efficiency of the internal air bag is now described. The first step is the CPU **30** to determine whether accord **135-1** or disaccord **135** exists between an anticipated collision point and the location of the external air bag inflation device on the roadway obstacle. If disaccord **135** is found, an anticipated impact intensity **142-3** is calculated as the flow chart shown in FIG. **16** based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on disaccord **136** (referring to FIG. **22**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);

14

5. a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle **139** (referring to FIG. **26**);

6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**);

7. a calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle **149** (referring to FIG. **11**);

8. position, posture, and size of passengers inside of the roadway vehicle **130** (referring to FIG. **35**); and

9. weight of passengers **131** (referring to FIG. **35**).

If accord **135-1** is found, an anticipated impact intensity **142-3** is calculated by the CPU as the flow chart shown in FIG. **17**, based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);

2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);

3. an anticipated real collision point based on accord **136-1** (referring to FIG. **23**);

4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);

5. a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle **140** (referring to FIG. **27**);

6. a calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**);

7. a calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle **149** (referring to FIG. **12**);

8. an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128**;

9. an absorption quantity of an external air bag in an applicable zone of the roadway obstacle **129** (referring to FIG. **34**);

10. position, posture, and size of passengers inside of the roadway vehicle **130** (referring to FIG. **35**); and

11. weight of passengers **131** (referring to FIG. **35**).

Preferably, as seen in FIG. **16** and FIG. **17**, a calculation of an absorption quantity of an internal air bag in an applicable zone of the roadway vehicle **152** is processed based on the following information:

1. an internal air bag inflation device in an applicable zone of the roadway vehicle **146** (referring to FIG. **13** and FIG. **14**);

2. an anticipated impact intensity **142-3**; and

3. an absorption quantities of an internal air bag of the roadway vehicle **111** (referring to FIG. **32**).

An inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128** is made by one of the two procedures in the following when accord **135-1** is found. The first procedure is to calculate an inflation size of an external air bag of the roadway obstacle to be half the size of an external air bag of the roadway vehicle based on disaccord. Alternatively, the second procedure is to obtain an inflation size of an external air bag in an applicable zone of the roadway obstacle via the wireless system **29**.

A preferred computer process for calculating various information according to the present invention is now described. FIG. **18** shows a flow chart of a preferred computer process for calculating a moving location of the

roadway obstacle relative to the roadway vehicle considering the shapes of the roadway vehicle and the roadway obstacle and the sizes of both the shapes **133**. The information **133** is calculated based on the information of a moving location of the roadway obstacle relative to the first sensing device on the roadway vehicle considering shape of the roadway obstacle and size of the shape **122** (referring to FIG. **33**) and shape of the roadway vehicle and size of the shape **118** (referring to FIG. **32**).

A preferred computer process for calculating an anticipated collision point **134** according to the present invention is understood by referring to FIG. **19**. The anticipated collision point **134** is calculated based on the information of a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**) and the information of a moving location of the roadway obstacle relative to the roadway vehicle considering shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes **133** (referring to FIG. **18** and FIG. **33**).

A preferred computer process for calculating disaccord between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle **135** may best be understood by referring to the flow chart shown in FIG. **20**. The information **135** is calculated by the CPU **30** based on the information of an anticipated collision point **134** (referring to FIG. **19**) and the location of an external air bag inflation device on the roadway obstacle **123** (referring to FIG. **33** and FIG. **34**).

Alternatively, a preferred computer process for calculating accord between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle **135-1** is shown in FIG. **21**. The information **135-1** is calculated by the CPU **30** based on the information of an anticipated collision point **134** (referring to FIG. **19**) and the location of an external air bag inflation device on the roadway obstacle **123** (referring to FIG. **33** and FIG. **34**).

A preferred computer process for calculating an anticipated real collision point based on disaccord **136** may best be understood by referring to the flow chart shown in FIG. **22**. The information **136** is obtained based on the calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**) and a moving location of the roadway obstacle relative to the roadway vehicle considering shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes **133** (referring to FIG. **18**).

A preferred computer process for calculating an anticipated real collision point based on accord **136-1** may best be understood by referring to the flow chart shown in FIG. **23**. The information **136-1** is obtained based on the calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle **148** (referring to FIG. **10**), an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle **128**, and a moving location of the roadway obstacle relative to the roadway vehicle considering shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes **133** (referring to FIG. **18**). The above **128** is made by one of the following two procedures when accord is found. The first procedure is to calculate an inflation size of an external air bag of the roadway obstacle to be half the size of an external air bag of the roadway vehicle based on disaccord. Alternatively, the second procedure is to obtain an inflation size of an external air bag of the roadway obstacle via the wireless system **29**.

A preferred computer process for calculating an anticipated collision point inside of the roadway vehicle **137** may

be best understood by referring to FIG. **24**. A calculation of **137** is made based on the following information:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**);
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**);
3. an anticipated real collision point based on disaccord **136** or accord **136-1** (referring to FIG. **22** and FIG. **23**);
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** (referring to FIG. **28**);
5. position, posture, and size of passengers **130** (referring to FIG. **35**); and
6. weight of passengers **131** (referring to FIG. **35**).

A preferred computer process for a comparison of the nature of a roadway obstacle to the nature of the roadway vehicle **138** according to the present invention is illustrated by the flow chart shown in FIG. **25**. This comparison is based on the information pertaining to the nature of the roadway vehicle **116** (referring to FIG. **32**) and the nature of the roadway obstacle **124** (referring to FIG. **33** and FIG. **34**).

A preferred computer process for a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle **139** according to the present invention is illustrated by the flow chart shown in FIG. **26**. This comparison is based on the information pertaining to the nature of an external air bag of the roadway vehicle **119** (referring to FIG. **32**) and the information pertaining to the nature of the roadway obstacle **124** (referring to FIG. **33** and FIG. **34**).

A preferred computer process for a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle **140** according to the present invention is illustrated by the flow chart shown in FIG. **27**. This comparison is based on information pertaining to the nature of an external air bag of the roadway vehicle **119** (referring to FIG. **32**) and information pertaining to the nature of an external air bag of the roadway obstacle **126** (referring to FIG. **33** and FIG. **34**).

A preferred computer process for a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141** according to the present invention is illustrated by the flow chart shown in FIG. **28**. This comparison is calculated based on the weight of the roadway obstacle **125** (referring to FIG. **33** and FIG. **34**) and a gross weight of the roadway vehicle **117-1** (referring to FIG. **29**).

A preferred computer process for calculating a gross weight of the roadway vehicle **117-1** according to the present invention is illustrated by the flow chart shown in FIG. **29**. The gross weight of the roadway vehicle **117-1** is calculated based on the net weight of the roadway vehicle **117** (referring to FIG. **32**), the weight of all passengers in the roadway vehicle **131** (referring to FIG. **35**), and the weight of the goods in the roadway vehicle **132** (referring to FIG. **35**).

A preferred computer process for calculating a minimum allowable distance window **114-1** according to the present invention is illustrated by the flow chart shown in FIG. **30**. The minimum allowable distance window **114-1** is calculated based on a minimum allowable time window **114** (referring to FIG. **32**), a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**), a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**), and an anticipated collision point **134** (referring to FIG. **19**).

A preferred computer process for calculating a distance **115-1** that begins from a detection point on a roadway

obstacle **27** when the roadway obstacle **27** is detected by the external detection system **26** on the roadway vehicle, to a point of impact between an inflated external air bag of the roadway vehicle **12** and the roadway obstacle **27** is shown in FIG. **31**. The distance **115-1** is calculated based on an estimated period of time in speed **115** that elapses between the point in time when the roadway obstacle **27** is detected and the point in time when the roadway obstacle collides against an inflated external air bag of the roadway vehicle (referring to FIG. **32**), a moving speed of the roadway obstacle relative to the roadway vehicle **120** (referring to FIG. **33**), and a direction of motion of the roadway obstacle relative to the roadway vehicle **121** (referring to FIG. **33**).

A variety of information must be inputted into the CPU **30** prior to using the air bag system **10** to enable the CPU **30** to function according to the present invention. FIG. **32** shows a list of information that is inputted into the CPU **30** by using a computer input device. A more detailed description of this information is provided below.

Reference numeral **106** designates information relating to a criterion for inflation of an external air bag of the roadway vehicle. According to the present invention, establishment of this criterion may be achieved through experimentations. The present invention anticipates a variety of the criteria based on the following conditions:

1. a moving speed of a roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a comparison of the nature of the roadway obstacle to the nature of the roadway vehicle **138**; and
4. a collision point.

Reference numeral **107** designates information relating to inflation sizes and shapes of an external air bag of the roadway vehicle based on various collision situations.

First, the external air bag's inflation sizes are established through experimentation and it is varied according to a volume of space to be occupied by the inflated external air bag **143**.

Second, the volume of space to be occupied by the external air bag is varied according to the following conditions:

1. a minimum allowable time (or distance) window of the roadway vehicle **114** (or **114-1**);
2. an estimated period of time in speed (or distance) **115** (or **115-1**) that covers from a detection point at which a roadway obstacle is detected to a point of impact between an inflated external air bag of the roadway vehicle and the roadway obstacle;
3. an anticipated collision point **134**;
4. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
5. a moving location of the roadway obstacle relative to the roadway vehicle based on shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes **133**; and
6. an external air bag inflation device in an applicable zone of the roadway vehicle **145**.

If disaccord exists between an anticipated collision point and the location of an external air bag of the roadway obstacle, an inflation size of the external air bag of the roadway vehicle is to be settled according to the space to be occupied by the inflated external air bag of the roadway vehicle. Alternatively, if accord exists, the inflation size of the external air bag of the roadway vehicle shall be half the

inflation size of the external air bag of the roadway vehicle when disaccord exists.

Reference numeral **108** designates absorption quantities of an external air bag in conformity with impact intensity. Absorption quantities of an external air bag are approximated based on experimentation. An absorption quantity is varied based on impact intensity. According to the present invention, the impact intensity includes intensity of the impact inflicted to the roadway vehicle, roadway obstacle, passengers, and pedestrians.

Approximations of impact intensity are based on accord or disaccord being found between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle. When there is disaccord, impact intensity is varied based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle **139**; and
6. an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle.

When there is accord, impact intensity is varied based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle **140**;
6. an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle; and
7. an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle.

Reference numeral **109** designates a criterion for estimating injury inflicted to passengers from a collision in spite of an external air bag used and for protecting passengers from a collision. The criterion **109** is used for a calculation of an inflation of an internal air bag of the roadway vehicle. The criterion **109** is derived through experimentation and varied based on two conditions. First, when disaccord exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle, the criterion **109** is varied based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle **139**; and
6. an inflation size and absorption quantity of an external air bag in an applicable zone of the roadway vehicle.

19

Second, when accord exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle, the criterion **109** is varied based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle **140**;
6. an inflation size and an absorption quantity of an external air bag in an applicable zone of the roadway vehicle; and
7. an inflation size and an absorption quantity of an external air bag in an applicable zone of the roadway obstacle.

Reference numeral **110** designates the information that is inputted into the CPU relating to inflation sizes and shapes of an internal air bag of the roadway vehicle. Inflation sizes of an internal air bag is derived through experimentation as the size is varied according to the space to be occupied by an inflated internal air bag of the roadway vehicle. The space is varied based on the following factors:

1. an anticipated collision point inside of the roadway vehicle **137**;
2. position, posture, and size of passengers **130**; and
3. an internal air bag inflation device in an applicable zone of the roadway vehicle **146**.

Reference numeral **111** designates information that is inputted into the CPU relating to absorption quantities of an internal air bag on the roadway vehicle. The absorption quantities are derived through experimentation based on an impact intensity. When disaccord **135** exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle, the absorption quantities of an internal air bag of the roadway vehicle **111** are derived through experimentation based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle **139**;
6. an inflation size and an absorption quantity of an external air bag in an applicable zone on the roadway vehicle;
7. position, posture, and size of passengers **130**; and
8. weight of passengers **131**.

When accord exists between an anticipated collision point and the location of an external air bag inflation device on the roadway obstacle, the absorption quantities of an internal air bag of the roadway vehicle **111** are derived based on the following conditions:

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;

20

2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a collision point;
4. a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle **141**;
5. a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle **140**;
6. an inflation size and an absorption quantity of an external air bag in an applicable zone of the roadway vehicle;
7. an inflation size and an absorption quantity of an external air bag in an applicable zone of the roadway obstacle;
8. position, posture, and size of passengers **130**; and
9. weight of passengers **131**.

Below is a list of additional information that is also inputted into the CPU **30** prior to using the air bag system **10** to enable the CPU **30** to control the inflation of internal and external air bags according to the present invention:

1. an information pertaining to the location of each external air bag inflation device on the roadway vehicle **112**;
2. an information pertaining to the location of each internal air bag inflation device on the roadway vehicle **113**;
3. a minimum allowable time window **114**; (within which an evasive action is not available prior to a collision)
4. an estimated period of time in speed **115**; (which elapses between a point in time when a roadway obstacle is detected and a point in time when the roadway obstacle collides against an inflated external air bag of the roadway vehicle)
5. the nature of the roadway vehicle **116**;
6. the net weight of the roadway vehicle **117**;
7. the shape of the roadway vehicle and size of the shape **118**; and
8. the nature of an external air bag of the roadway vehicle **119**.

Further detailed information generated by the CPU **30** based on the information obtained by the external detection system **26** is listed in the following as shown in FIG. **33**.

1. a moving speed of the roadway obstacle relative to the roadway vehicle **120**;
2. a direction of motion of the roadway obstacle relative to the roadway vehicle **121**;
3. a moving location of the roadway obstacle relative to the first sensing device on the roadway vehicle based on shape of the roadway obstacle and size of the shape **122**; (This information is obtained by the first sensing device **40** of the external detection system **26**.)
4. a location of an external air bag inflation device on the roadway obstacle **123**;
5. nature of the roadway obstacle **124**,
6. weight of the roadway obstacle **125**;
7. nature of an external air bag of the roadway obstacle **126**;
8. a moving location of the roadway obstacle relative to the roadway vehicle based on shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes **133**. (This information is obtained by the second sensing device **42** and the third sensing device **44** of the external detection system **26**.)

Information generated by the CPU 30 based on the information transmitted by the wireless system 29 is listed in the following as shown in FIG. 34.

1. a location of an external air bag inflation device on the roadway obstacle 123;
2. nature of the roadway obstacle 124;
3. weight of the roadway obstacle 125;
4. nature of an external air bag on the roadway obstacle 126;
5. a location of the roadway obstacle 127;
6. an inflation size and shape of an external air bag in an applicable zone on the roadway obstacle 128; and
7. an absorption quantity of an external air bag in an applicable zone on the roadway obstacle 129.

Information generated by the CPU 30 based on the information obtained by the internal detection system 28 is listed in the following as shown in FIG. 35:

1. position, posture, and size of passengers 130;
2. weight of passengers 131;
3. weight of goods 132.

The present invention anticipates that any energy source may be used for supplying electrical energy to the air bag system 10. For example, a block diagram of a preferred embodiment of the air bag system 10 that includes a photoelectron system 161 is shown in FIG. 36. The photoelectron system 161 is being used in various industrial fields and incorporates a technology to convert photon into electricity for supplying electrical energy to the relevant parts of the air bag system 10 where electricity is required for the function of the air bag system 10.

Alternatively, a conventional battery 162 may be used in connection with photoelectron system 161 for supplying energy to the air bag system 10. FIG. 37 shows a block diagram of a preferred embodiment of the air bag system 10 utilizing a conventional battery 162. As shown, electricity generated from the photoelectron system 161 may be used for continuous electric supply to the battery 162 for charging the battery. Accordingly, the battery 162 becomes to supply electric energy eternally without replacement of the battery 162 to the relevant parts of the air bag system 10.

APPENDIX

Technical Terminology of the Present Invention	
Ref No	Terminologies
1.	12 roadway vehicle
2.	16 automobile body
3.	26 external detection system (including first sensing device 40, second sensing device 42, and third sensing device 44)
4.	27 roadway obstacle (including other vehicle, object, and pedestrian)
5.	28 internal detection system (including first sensor 50, second sensor 52, third sensor 54, and fourth sensor 56)
6.	29 wireless system (including first wireless apparatus 68, second wireless apparatus 70, third wireless apparatus 72, and fourth wireless apparatus 74)
7.	30 CPU (computer processing unit)
8.	36 steering wheel
9.	40 first sensing device (installed in the roadway vehicle 12)
10.	42 second sensing device (installed in the roadside lamp post 46)
11.	44 third sensing device (installed in the satellite 48)
12.	45 fourth sensing device (installed in the roadway obstacle 27)
13.	46 roadside lamp post
14.	48 satellite

APPENDIX-continued

Technical Terminology of the Present Invention	
Ref No	Terminologies
15.	50 first sensor (including radiant energy, sonic energy, and camera for detecting sitting posture, position, size, weight of passenger and driver)
16.	52 second sensor (detecting sitting posture, position, size of passenger and driver according to number of sensor's revolution)
17.	54 third sensor (detecting sitting posture, location, size, weight of passenger and driver by use of pressure made by weight of passenger and driver)
18.	56 fourth sensor (installed under the trunk to detect weight of goods by use of pressure made by goods)
19.	60 passengers' seat
20.	62 seat belt
21.	68 first wireless apparatus (installed in roadway vehicle 12)
22.	70 second wireless apparatus (installed in roadway obstacle 27)
23.	72 third wireless apparatus (connected with the third sensing device 44)
24.	74 fourth wireless apparatus (connected with the second sensing device 42)
25.	76 air bag (including external air bag and internal air bag)
26.	80 air bag inflation device (including external air bag inflation device and internal air bag inflation device)
27.	92 first air space
28.	94 secondary air space
29.	104 roadside barrier
30.	104- front bumper
31.	106 criterion for inflation of an external air bag of the roadway vehicle (inputted in CPU)
32.	107 inflation sizes and shapes of an external air bag of the roadway vehicle based on various collision situations (inputted in CPU)
33.	108 absorption quantities of an external air bag of the roadway vehicle in conformity with impact intensity (inputted in CPU)
34.	109 criterion for estimating injury inflicted to passengers from a collision (inputted in CPU) (This criterion is aimed at protection of passengers from being injured from a collision despite of an external air bag used and is for inflation of an internal air bag in an applicable zone of the roadway vehicle.)
35.	110 inflation sizes and shapes of an internal air bag of the roadway vehicle (inputted in CPU)
36.	111 absorption quantities of an internal air bag of the roadway vehicle (inputted in CPU)
37.	112 location of each external air bag inflation device on the roadway vehicle (inputted in CPU)
38.	113 location of each internal air bag inflation device on the roadway vehicle (inputted in CPU)
39.	114 minimum allowable time window (MATW) (Within which a driver is unable to take an evasive action to avoid an anticipated collision under the assumption of no external air bag used.) (inputted in CPU)
40.	114- minimum allowable distance window (MADW) (Within which a driver is unable to take an evasive action prior to a collision.)
41.	115 an estimated period of time in speed (Which elapses between a point in time when a roadway obstacle is detected and a point in time when the roadway obstacle collides against an inflated external air bag of the roadway vehicle.) (inputted in CPU)
42.	115- an estimated distance (Which covers from a detection point at which a roadway obstacle is detected to a point of impact between an inflated external air bag of the roadway vehicle and a roadway obstacle.)
43.	116 nature of the roadway vehicle (inputted in CPU) (comprising body material of the roadway vehicle, solidity, impact absorbability, kind of vehicle)
44.	117 the net weight of the roadway vehicle (inputted in CPU)
45.	117- a gross weight of the roadway vehicle (including weight of passengers and weight of goods)
46.	118 shape of the roadway vehicle and size of the shape (inputted in CPU)

APPENDIX-continued

Technical Terminology of the Present Invention		
Ref No	Terminologies	
47.	119 nature of an external air bag of the roadway vehicle (inputted in CPU) (comprising material, solidity, elasticity of the external air bag of the roadway vehicle)	5
48.	120 a moving speed of the roadway obstacle relative to the roadway vehicle	10
49.	121 a direction of motion of the roadway obstacle relative to the roadway vehicle	
50.	122 a moving location of the roadway obstacle relative to the first sensing device on the roadway vehicle based on shape of the roadway obstacle and size of the shape (This moving location comprises meaning of a moving direction of a roadway obstacle relative to the first sensing device of the roadway vehicle and a distance between the first sensing device of the roadway vehicle and the roadway obstacle.)	15
51.	123 the location of an external air bag inflation device on the roadway obstacle	
52.	124 nature of the roadway obstacle (comprising body material of a roadway obstacle, solidity, impact absorbability, kind of object)	20
53.	125 weight of the roadway obstacle (comprising total weight of the roadway obstacle with occupants and goods)	
54.	126 nature of an external air bag on the roadway obstacle (comprising material, solidity, elasticity of the external air bag of the roadway obstacle)	25
55.	127 a location of the roadway obstacle	
56.	128 an inflation size and shape of an external air bag in an applicable zone of the roadway obstacle	
57.	129 an absorption quantity of an external air bag in an applicable zone of the roadway obstacle	30
58.	130 position, posture, and size of passenger	
59.	131 weight of passenger	
60.	132 weight of goods	
61.	133 a moving location of the roadway obstacle relative to the roadway vehicle based on shapes of the roadway vehicle and the roadway obstacle and sizes of both the shapes (Moving location of the roadway obstacle comprises meanings of moving direction of the roadway obstacle relative to the roadway vehicle and distance between moving roadway vehicle and moving roadway obstacle.)	35
62.	134 anticipated collision point (comprising meaning of physical point of a collision between the roadway obstacle and the roadway vehicle, time or geographical point)	40
63.	135 disaccord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle (This explains that an external air bag inflation device is not installed where an anticipated collision point is expected.)	
64.	135-1 accord between an anticipated collision point and the location of an external air bag inflation device of the roadway obstacle (This explains that an external air bag inflation device is installed where an anticipated collision point is expected.)	45
65.	136 an anticipated real collision point based on disaccord (This indicates a disaccord relation between both collision points on the inflated external air bag of the roadway vehicle and body of the roadway obstacle.)	50
66.	136-1 an anticipated real collision point based on accord (This indicates an accord relation between both collision points on the inflated external air bags of the roadway vehicle and the roadway obstacle.)	
67.	137 an anticipated collision point inside of the roadway vehicle (This means an internal collision point that is calculated for the place where driver or passenger is anticipated to be inflicted.)	55
68.	138 a comparison of the nature of the roadway obstacle to the nature of the roadway vehicle	
69.	139 a comparison of the nature of the roadway obstacle to the nature of an external air bag of the roadway vehicle	60
70.	140 a comparison of the nature of an external air bag of the roadway obstacle to the nature of an external air bag of the roadway vehicle	
71.	141 a comparison of the weight of the roadway obstacle to the weight of the roadway vehicle	65
72.	142 an anticipated damage (for 147)	

APPENDIX-continued

Technical Terminology of the Present Invention		
Ref No	Terminologies	
73.	142-1 an anticipated impact intensity (for 149)	
74.	142-2 an anticipated damage (for 150)	
75.	142-3 an anticipated impact intensity (for 152)	
76.	143 a volume of space to be occupied by an inflated external air bag of the Roadway vehicle (This space must be a little smaller than the space between the roadway obstacle and the location of an external air bag inflation device on the roadway vehicle in order to prevent the roadway obstacle from being hit by the air bag.)	
77.	144 a volume of space to be occupied by the inflated internal air bag of the roadway vehicle (This space must be a little smaller than the space between the passengers and the location of an internal air bag inflation device in order to have passengers prevented from a striking of the air bag.)	
78.	145 an external air bag inflation device in an applicable zone of the roadway vehicle	
79.	146 an internal air bag inflation device in an applicable zone of the roadway vehicle	
80.	147 criterion for inflation of an external air bag in an applicable zone of the roadway vehicle	
81.	148 calculation of an inflation size and shape of an external air bag in an applicable zone of the roadway vehicle	
82.	149 calculation of an absorption quantity of an external air bag in an applicable zone of the roadway vehicle	
83.	150 criterion for inflation of an internal air bag in an applicable zone of the roadway vehicle	
84.	151 calculation of an inflation size and shape of an internal air bag in an applicable zone of the roadway vehicle	
85.	152 calculation of an absorption quantity of an internal air bag in an applicable zone of the roadway vehicle	
86.	153 inflator of an air bag inflation device	
87.	154 external layer of an air bag	
88.	154-1 internal layer of an air bag	
89.	155 roller of an air bag inflation device	
90.	156 first roller sensor	
91.	156-1 second roller sensor	
92.	157 motor for an air bag inflation device	
93.	158 an absorption device (valve or port) on the external layer of the air bag	
94.	158-1 an absorption device (valve or port) on the internal layer of the air bag	
95.	159 an external air bag inflation device	
96.	160 an internal air bag inflation device	
97.	161 photoelectron system	
98.	162 battery	
99.	163 photon	
100.	164 electricity	
101.	165 detectable coating material (This coating material helps the external detection system discern the objects accurately.)	

What is claimed is:

1. An air bag system installed in a vehicle for protecting vehicles, passengers, roadside objects, and pedestrians from being damaged and injured at a collision, the air bag system comprising:

means for using an external detection system for obtaining information relating to a roadway obstacle, a roadway vehicle and roadway conditions;

means for using an internal detection system installed inside of the roadway vehicle for obtaining information on passengers' conditions inside of the roadway vehicle;

means for using a wireless system for obtaining required information to function the air bag system;

means for a computer processing unit (hereinafter referred to as CPU) installed in the roadway vehicle to process

information obtained by said external detection system, said internal detection system, and said wireless system based on information inputted in said CPU, said CPU having a means for calculating of a criterion for inflation of an external air bag, calculating inflation size and shape of the external air bag, and calculating absorption quantity of the external air bag, and said CPU having a means for calculating a criterion for inflation of an internal air bag and calculating absorption quantity of the internal air bag;

means for using at least one external air bag inflation device installed in the roadway vehicle, said at least one external air bag inflation device having an external air bag installed therein for inflating said external air bag prior to a collision over an external portion of the roadway vehicle in an imminent situation to reduce collision damage to the vehicle and obstacles, injury to passengers and pedestrians;

means for using at least one internal air bag inflation device installed in the roadway vehicle, said at least one internal air bag inflation device having an internal air bag installed therein for inflating said internal air bag toward the passengers of the roadway vehicle prior to a collision in an imminent situation to reduce injury to the passengers;

means for deciding an inflation size of each external and internal air bag according to a roller connected to a motor controlled by said CPU installed in an air bag inflation device in the vehicle;

said external air bag inflation device and said internal air bag inflation device comprising:

an air bag, one end of which being attached to a roller for enabling said roller to release said air bag from a retracted condition by the roller rotating in a first direction;

a roller rotatably positioned inside of said air bag inflation device for enabling the roller to rotate for controlling inflation size of said air bag;

a motor attached to the roller for rotatably driving the roller, the motor being rotatable in a second direction for opposing rotation of the roller, by which the releasing of said air bag is stopped at required inflation size to hold the inflation of said air bag;

a first roller sensor attached to an inside surface of said air bag inflation device surrounding the roller to help detect the number of rotations of said roller;

a second roller sensor attached to an outside surface of said roller for providing a means by which number of rotations of the roller is detected;

a first absorption device connected to an external layer of said air bag to provide a primary means for relieving a collision impact intensity imposed on said air bag in an inflated shape;

a second absorption device connected to an internal layer of said air bag to provide a secondary means for relieving a collision impact intensity imposed on said air bag in an inflated shape; and

a photoelectron system used for supplying energy to air bag system, which is currently used in the industries.

2. The system recited in claim 1, wherein said external detection system comprises:

a first sensing device installed in a roadway vehicle for detecting obstacles surrounding the roadway vehicle;

a second sensing device installed on a lamp post along the road for detecting information relating to the roadway conditions;

a third sensing device installed in a communication satellite in the earth's atmosphere for detecting roadway conditions;

a fourth sensing device installed in a roadway obstacle for detecting roadway conditions around the roadway obstacle.

3. The system recited in claim 2, wherein said external detection system further comprises:

a coating material placed on a dangerous object that may possibly give damage to automobile, injury to passengers, or damage to object itself by the automobile at collision, said coating material capable of being detected by said external detection system for distinguishing an obstacle accurately to let said CPU determine whether or not an inflation of the air bag is required against the object; and

said coating material for being placed on said external air bag inflation device or an external surface of the body of the vehicle where said external air bag inflation device is internally installed for having said external detection system easily confirm existence of said external air bag inflation device or a location of said external air bag inflation device if it is therein.

4. The system recited in claim 1, wherein said wireless system comprises:

a first wireless apparatus installed in the roadway vehicle for receiving and transmitting information from and to said CPU;

a second wireless apparatus installed in the roadway obstacle for transmitting information relating to the roadway obstacle to said first wireless apparatus;

a third wireless apparatus installed in a satellite for transmitting information relating to a roadway situation to said first wireless apparatus from a position situated in the earth's atmosphere; and

a fourth wireless apparatus installed on a lamp post for transmitting information relating to a roadway situation to said first wireless apparatus from a position situated along the roadside.

5. The system recited in claim 4, wherein said first wireless apparatus receives and transmits information from and to said CPU and also transmits the information to said second wireless apparatus installed on a roadway obstacle to advise the roadway obstacle on the situation of the roadway vehicle.

6. The system recited in claim 1, wherein each of said first absorption device and said second absorption device is a valve or port.

7. The system recited in claim 6, wherein said valve or port controlled by said CPU controls an absorption quantity of said external air bag.

8. The system recited in claim 6, wherein said valve or port controlled by said CPU controls an absorption quantity of said internal air bag.

9. The system recited in claim 1, wherein said CPU controls inflation size of said external air bag based on said first roller sensor and said second roller sensor.

10. The system recited in claim 1, wherein said CPU controls inflation size of said internal air bag based on said first roller sensor and said second roller sensor.

11. The system recited in claim 1, wherein said CPU controls inflation size of said external air bag by controlling the roller.

12. The system recited in claim 1, wherein said CPU controls inflation size of said external air bag by controlling the motor attached to the roller.

13. The system recited in claim 1, wherein said CPU controls inflation size of said internal air bag by controlling the roller.

14. The system recited in claim 1, wherein said CPU controls inflation size of said internal air bag by controlling the motor attached to the roller.

15. The system recited in claim 1, wherein said CPU is programmed to generate signal for controlling said external air bag inflation device according to the information calculated based on the information obtained by said external detection system and said wireless system and the information inputted in said CPU.

16. The system recited in claim 1, wherein said CPU is programmed to generate signal for controlling said internal air bag inflation device according to a calculation based on the information obtained by said external detection system, said wireless system, and said internal detection system and also the information inputted in said CPU.

17. The system recited in claim 1, wherein said CPU has a processing means for calculating inflation size and absorption quantity under which said internal air bag of said roadway vehicle inflates based on the information stored in said CPU and the information obtained by said external detection system, said internal detection system, and said wireless system.

18. The system recited in claim 1, wherein said photoelectron system is installed in said roadway vehicle for an endless supply of electric energy to the relevant parts of the vehicle for an operation of the air bag system.

19. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on an external air bag inflation device in an applicable zone of said roadway vehicle.

20. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on a minimum allowable time (distance) window.

21. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag on said roadway vehicle based on the time (distance) that elapses from a detected point on said roadway obstacle to a collision point between said external air bag of said roadway vehicle and said roadway obstacle.

22. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on an anticipated collision point.

23. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on a moving speed of said roadway obstacle relative to said roadway vehicle.

24. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on a moving location of said roadway obstacle relative to said roadway vehicle according to shapes of both said roadway vehicle and the roadway obstacle and sizes of both the shapes.

25. The system recited in claim 1, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle based on disaccord or accord between an anticipated collision point and a location of said external air bag inflation device of said roadway obstacle.

26. The system recited in claim 25, wherein said CPU calculates an inflation size of said external air bag of said roadway vehicle when accord exists, to be half the inflation size of said external air bag of said roadway vehicle based on disaccord.

27. The system recited in claim 1, wherein said CPU calculates an absorption quantity of said external air bag of

said roadway vehicle based on disaccord or accord between an anticipated collision point and a location of said external air bag inflation device of said roadway obstacle.

28. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on an anticipated real collision point according to disaccord.

29. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on a comparison of the nature of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to disaccord.

30. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on an anticipated real collision point according to accord.

31. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on a comparison of the nature of said external air bag of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to accord.

32. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on inflation size and shape of said external air bag in an applicable zone of said roadway obstacle according to accord.

33. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on a moving speed of said roadway obstacle relative to said roadway vehicle.

34. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on a direction of motion of said roadway obstacle relative to said roadway vehicle.

35. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on a comparison of the weight of said roadway obstacle to the weight of said roadway vehicle.

36. The system recited in claim 27, wherein said CPU calculates an absorption quantity of said external air bag of said roadway vehicle based on an inflation size and shape of said external air bag in an applicable zone of said roadway vehicle.

37. The system recited in claim 1, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on disaccord or accord existing between an anticipated collision point and a location of said external air bag inflation device of said roadway obstacle.

38. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on an anticipated real collision point according to disaccord.

39. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on a comparison of the nature of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to disaccord.

40. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on an anticipated real collision point according to accord.

41. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in

an applicable zone of said roadway vehicle based on a comparison of the nature of said external air bag of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to accord.

42. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on inflation size and shape of said external air bag in an applicable zone of said roadway obstacle according to accord.

43. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on an absorption quantity of said external air bag in an applicable zone of said roadway obstacle according to accord.

44. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on an inflation size and shape of said external air bag in an applicable zone of said roadway vehicle.

45. The system recited in claim 37, wherein said CPU calculates a criterion for inflation of said internal air bag in an applicable zone of said roadway vehicle based on an absorption quantity of said external air bag in an applicable zone of said roadway vehicle.

46. The system recited in claim 37, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on a comparison of the weight of said roadway obstacle to the weight of said roadway vehicle.

47. The system recited in claim 1, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on disaccord or accord existing between an anticipated collision point and a location of said external air bag inflation device of said roadway obstacle.

48. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on an anticipated real collision point according to disaccord.

49. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on a comparison of the nature of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to disaccord.

50. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in

an applicable zone of said roadway vehicle based on an anticipated real collision point according to accord.

51. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on a comparison of the nature of said external air bag of said roadway obstacle to the nature of said external air bag of said roadway vehicle according to accord.

52. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on an inflation size and shape of said external air bag in an applicable zone of said roadway obstacle according to accord.

53. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on an absorption quantity of said external air bag in an applicable zone of said roadway obstacle according to accord.

54. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on a moving speed of said roadway obstacle relative to said roadway vehicle.

55. The system recited in claim 47, wherein said CPU calculates an absorption quantity of said internal air bag in an applicable zone of said roadway vehicle based on a direction of motion of said roadway obstacle relative to said roadway vehicle.

56. The system recited in claim 47, wherein said CPU calculates an absorption quantity of the internal air bag in an applicable zone of said roadway vehicle based on an inflation size and shape of said external air bag in an applicable zone of said roadway vehicle.

57. The system recited in claim 47, wherein said CPU calculates an absorption quantity of the internal air bag in an applicable zone of said roadway vehicle based on an absorption quantity of said external air bag in an applicable zone of said roadway vehicle.

58. The system recited in claim 47, wherein said CPU calculates an absorption quantity of the internal air bag in an applicable zone of said roadway vehicle based on position, posture, weight, and size of occupants.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,408,237 B1
DATED : June 18, 2002
INVENTOR(S) : Daniel Myung Cho

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [76], should read -- Inventor's Name: **Daniel Myung Cho**

Address : 13404 Tossa Lane, Austin, Tx 78729 --

Signed and Sealed this

Twenty-second Day of October, 2002

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office