



US006444159B2

(12) **United States Patent**
Petre

(10) **Patent No.:** **US 6,444,159 B2**
(45) **Date of Patent:** ***Sep. 3, 2002**

(54) **BLOW MOLD SHELL AND SHELL ASSEMBLY**

(75) Inventor: **Patrick Petre**, Cauville sur Mer (FR)

(73) Assignee: **Sidel, Inc.**, Norcross, GA (US)

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/304,903**

(22) Filed: **May 4, 1999**

(51) **Int. Cl.**⁷ **B29C 49/64**

(52) **U.S. Cl.** **264/520; 249/79; 249/102; 425/526**

(58) **Field of Search** 249/79, 80, 102; 425/522, 526, 529, 541; 264/520

(56) **References Cited**

U.S. PATENT DOCUMENTS

467,881 A 1/1892 Fisher
1,409,591 A 3/1922 Schavoir

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

DE 1916129 10/1969
DE 2545130 4/1977
DE 2545131 4/1977
DE 2545132 4/1977
DE 2545134 4/1977
DE 2550727 5/1977
DE 2545133 6/1977
DE 3613543 C1 12/1986
DE 3743809 1/1989
DE 3934495 C1 12/1990

EP 256777 2/1988
EP 565917 A1 10/1993
FR 2057196 5/1971
FR 2613979 A1 10/1988
FR 2613979 10/1988
FR 2646802 11/1990
FR 2646802 A1 11/1990

(List continued on next page.)

OTHER PUBLICATIONS

“Quick-Change Systems Add to Blow Molders’ Market Reach,” by Patrick A. Toenmeier, *Modern Plastics International*, Aug. 1991 (pp. 30-31).

(List continued on next page.)


Primary Examiner—Robert Davis

(74) *Attorney, Agent, or Firm*—Alston & Bird LLP

(57) **ABSTRACT**

An improved blow mold shell, and a blow mold shell assembly, for use in blow molding containers is disclosed. The blow mold shell comprises an elongate unitary blow mold shell body defining a partial molding cavity, the partial molding cavity having a container neck forming portion and a container body forming portion. A first continuous cooling circuit is defined within the shell with respect to the neck forming portion of the molding cavity. A second separate, and independent, continuous cooling circuit is defined within the shell with respect to the body forming portion of the molding cavity. So constructed, the neck and body portions of a blow mold container may be separately cooled, and/or heat-treated, as desired, during the molding process to allow the sidewall portion of the container to be molded in as thin a sidewall section as possible in contrast to the neck portion of the container. The shell assembly is comprised of two substantially identical ones of the blow mold shells releasably mated to one another, and also includes a base assembly received at the second end of the blow mold shells. The base assembly defines a base portion of the molding cavity, and has a separate cooling circuit for cooling the base forming portion of the molding cavity.

27 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

2,790,994 A	5/1957	Cardot et al.	
2,959,812 A	11/1960	Allen	
3,191,225 A	6/1965	Polka	
3,380,121 A	4/1968	Chittenden et al.	
3,601,858 A	8/1971	Blanchard	425/526
3,651,186 A	3/1972	Hall	
3,753,641 A	8/1973	Turner et al.	
3,768,948 A	10/1973	Horberg, Jr. et al.	249/79
3,784,344 A	1/1974	Korsch	
3,802,823 A	4/1974	Doughty et al.	
3,807,928 A	* 4/1974	Horberg, Jr. et al.	425/526
3,843,286 A	* 10/1974	Horberg, Jr. et al.	425/526
3,854,855 A	12/1974	Pollock et al.	
3,857,660 A	12/1974	Flynn et al.	
3,871,611 A	3/1975	Taketa	
3,993,427 A	11/1976	Kauffman et al.	
4,009,979 A	3/1977	Martin	
4,035,463 A	7/1977	Rosenfranz et al.	
4,046,498 A	9/1977	Appel et al.	
4,072,456 A	2/1978	Appel et al.	
4,092,097 A	5/1978	Appel et al.	
4,117,050 A	9/1978	Appel et al.	
4,120,636 A	10/1978	Appel et al.	
4,151,976 A	5/1979	Schurman	
4,213,750 A	7/1980	Kubota et al.	
4,214,860 A	7/1980	Kleimenhagen et al.	
4,219,526 A	8/1980	Mehnert	
4,233,022 A	11/1980	Brady et al.	425/525
4,268,242 A	5/1981	Natter	
4,318,882 A	* 3/1982	Agrawal et al.	264/520
4,357,288 A	11/1982	Oas et al.	
4,472,128 A	9/1984	Ruhl	
4,500,275 A	2/1985	Ruhl	
4,568,263 A	2/1986	Ruhl	
4,701,121 A	10/1987	Jakobsen et al.	425/526
4,702,456 A	10/1987	Von Holdt	
4,714,421 A	12/1987	D'Agostino	
4,790,741 A	12/1988	Takakusaki et al.	
4,822,543 A	4/1989	Iizuka et al.	425/526
4,834,642 A	5/1989	Voss et al.	
4,861,542 A	8/1989	Oles et al.	
4,872,827 A	10/1989	Noda	
5,041,247 A	8/1991	Kim	
5,064,366 A	11/1991	Voss	
5,096,404 A	3/1992	Janos et al.	
5,116,450 A	5/1992	Spoo et al.	
5,255,889 A	10/1993	Collette et al.	249/102
5,256,341 A	10/1993	Denis et al.	
5,262,116 A	11/1993	Von Holdt, Sr.	
5,277,574 A	1/1994	Denis et al.	
5,284,432 A	2/1994	Wurzer	
5,288,222 A	2/1994	Wieser	
5,295,804 A	3/1994	Dinnan	
5,308,223 A	5/1994	Denis et al.	
5,322,651 A	6/1994	Emmer	
5,326,250 A	7/1994	Doudement	425/541
5,332,384 A	7/1994	Abramat	
5,334,007 A	8/1994	Denis et al.	
5,338,181 A	8/1994	Denis et al.	
5,342,558 A	8/1994	Denis et al.	
5,346,386 A	9/1994	Albrecht et al.	
5,350,289 A	9/1994	Martin	
5,358,396 A	10/1994	Giesen	
5,382,157 A	1/1995	Denis et al.	
5,411,698 A	5/1995	Mero et al.	425/526
5,413,472 A	5/1995	Dietterich et al.	
5,439,368 A	8/1995	Martin	
5,551,860 A	9/1996	Budzynski et al.	
5,551,861 A	9/1996	Baldi	
5,556,648 A	9/1996	Budzynski et al.	

5,683,729 A	11/1997	Valles	425/526
5,968,560 A	10/1999	Briere et al.	425/541
6,113,377 A	* 9/2000	Clark	425/195

FOREIGN PATENT DOCUMENTS

FR	2653058 A1	4/1991	
FR	2653058	4/1991	
FR	2659265 A1	9/1991	
FR	2659265	9/1991	
GB	1456833	11/1976	
GB	1526492	9/1978	
GB	1546234	5/1979	
GB	2009029	6/1979	
GB	1577034	10/1980	
GB	2240300 A	7/1991	
JP	58-36418	* 3/1983	425/526
JP	62-166469	7/1987	
JP	HEI-1-60725	4/1989	
JP	4-137827	12/1991	
JP	5-169522 A	7/1993	
WO	WO 94/03320	2/1994	

OTHER PUBLICATIONS

Patent Abstracts of Japan, vol. 12, No. 286 (M-727), Aug. 5, 1988 (Abstract of Japanese Reference 63-062, 710, dated Mar. 19, 1988).

Wentworth Drawings Set 1 (No date).
Wentworth Drawings Set 2 (No date).
Wentworth Drawings Set 3 (No date).
Wentworth Drawings Set 4 (No date).
Wentworth Drawings Set 5 (No date).
Wentworth Drawings Set 6 (No date).
Wentworth Drawings Set 7 (No date).
Wentworth Drawings Set 8 (No date).
Wentworth Drawings Set 9 (No date).
Wentworth Drawings Set 10 (No date).
Wentworth Drawings Set 11 (No date).
Wentworth Drawings Set 12 (No date).
Wentworth Drawings Set 13 (No date).
Wentworth Drawings Set 14 (No date).
Wentworth Drawings Set 15 (No date).
Wentworth Drawings Set 16 (No date).
Wentworth Drawings Set 17 (No date).
Wentworth Drawings Set 18 (No date).
Wentworth Drawings Set 19 (No date).
Wentworth Drawings Set 20 (No date).
Wentworth Drawings Set 21 (No date).
Wentworth Drawings Set 22 (No date).
Wentworth Drawings Set 23 (No date).
Wentworth Drawings Set 24 (No date).
Wentworth Drawings Set 25 (No date).
Wentworth Drawings Set 26 (No date).
Wentworth Drawings Set 27 (No date).
Wentworth Drawings Set 28 (No date).
Wentworth Drawings Set 29 (No date).
Wentworth Drawings Set 30 (No date).
Wentworth Drawings Set 31 (No date).
Wentworth Drawings Set 32 (No date).
Wentworth Drawings Set 33 (No date).
Wentworth Drawings Set 34 (No date).
Wentworth Drawings Set 35 (No date).
Wentworth Drawings Set 36 (No date).
Wentworth Drawings Set 37 (No date).
Wentworth Drawings Set 38 (No date).
Wentworth Drawings Set 39 (No date).
Wentworth Drawings Set 40 (No date).

Wentworth Drawings Set 41 (No date).
Wentworth Drawings Set 42 (No date).
Wentworth Drawings Set 43 (No date).
Wentworth Drawings Set 44 (No date).
Wentworth Drawings Set 45 (No date).
Wentworth Drawings Set 46 (No date).
Wentworth Drawings Set 47 (No date).
Wentworth Drawings Set 48 (No date).
Wentworth Drawings Set 49 (No date).
Wentworth Drawings Set 50 (No date).
Wentworth Drawings Set 51 (No date).
Wentworth Drawings Set 52 (No date).
Wentworth Drawings Set 53 (No date).
Wentworth Drawings Set 54 (No date).
Wentworth Drawings Set 55 (No date).
Wentworth Drawings Set 56 (No date).
Wentworth Drawings Set 57 (No date).
Wentworth Drawings Set 58 (No date).

Wentworth Drawings Set 59 (No date).
Wentworth Drawings Set 60 (No date).
Wentworth Drawings Set 61 (No date).
Wentworth Drawings Set 62 (No date).
Wentworth Drawings Set 63 (No date).
Wentworth Drawings Set 64 (No date).
Wentworth Drawings Set 65 (No date).
Wentworth Drawings Set 66 (No date).
Wentworth Drawings Set 67 (No date).
Wentworth Drawings Set 68 (No date).
Wentworth Drawings Set 69 (No date).
Wentworth Drawings Set 70 (No date).

Toenmeier, Patrick A., "Quick-Change Systems Add to
blow Molders Market Reach," *Modern Plastics* intional Aug.
1991, pp. 30-31.

* cited by examiner




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5





FIG 6






FIG 8

BLOW MOLD SHELL AND SHELL ASSEMBLY

FIELD OF THE INVENTION

This invention relates in general to stretch blow mold machinery, and to the blow molding of containers. More particularly, this invention relates to an improved blow mold shell having separately defined and independent cooling circuits formed as a part thereof for a container neck forming portion, and a container body sidewall forming portion of the shell, respectively, and to a shell assembly comprised of two substantially identical ones of the shells releasably mated to one another.

BACKGROUND OF THE INVENTION

A large number of beverages, as well as a variety of food products, are packaged in plastic bottles and/or containers. Plastic has proven to be readily adapted to being formed into a variety of shapes and sizes, and a variety of plastics can be used to form bottles to package beverages, for example, non-carbonated, carbonated, refrigerated or pasteurized beverages, as well as containers for semi-solid food products, to include mayonnaise and peanut butter.

The plastics used to form these containers may include high density polyethylene ("HDPE") used primarily for forming milk bottles and for industrial applications, for example forming drums, flasks, and toys; polyvinylchloride ("PVC"), the pioneer polymer used in packaging non-carbonated or slightly carbonated beverages; and polyethylene terephthalate ("PET"), which is a lightweight transparent plastic material having superior resistance to impact, heat, and pressure, and which is 100% recyclable. PET is among the most commonly used plastics for packaging non-carbonated and carbonated liquids, to include water, fruit juices, soft drinks, cooking oil, household cleaning products, as well as liquids which may have required pasteurization or hot filling.

PET containers are typically formed in one of three types of blow molding operations. These operations include extrusion blow molding, injection blow molding, and lastly stretch blow molding in which a preheated preform, also known as parison, is placed between a pair of releasably mated shell halves, a stretch rod is extended within the preform to stretch it to the desired length, and air is injected into the preform through the stretch rod to force the preform against a mold cavity defined within and as part of the mold shell halves.

Although the use of PET in the stretch blow molding of containers has proven to be extremely successful and has gained widespread acceptance in the marketplace, the problem persists in the ability to adequately and precisely control the temperature of the molds during the blow mold process such that the thinnest allowable container sidewall is molded during the formation of the bottle or container. The greatest expense, approximately 90%, of forming a PET container is not the machinery itself, but rather is the cost of the PET used to produce the container. As modern stretch blow mold machines are capable of attaining production rates beyond 50,000 bottles an hour for standard and flat bottles, for example those bottles capable of being manufactured by the SBO family of stretch blow mold machines manufactured by Sidel, Inc., if the cost of the PET preform can be minimized, this savings, when taking into account the number of bottles produced in an hour, and over the course of a machine's lifetime, is quite significant.

When blow-molding a PET container it is desirable to mold the upwardly extending neck portion to have a thicker

sidewall or cross-section than the elongate sidewall or body portion of the container which extends between the neck and a spaced base portion of the container. It is also desirable that the base portion be molded to have a body section thicker than the sidewall. All that is required of the sidewall is that it possess sufficient structural strength such that it will not rupture during handling or packaging, and will also act as a suitable vapor barrier for sealing the product within the container.

It is known to define a cooling channel within the shell holder or a support plate to which a blow mold shell is fastened so that a cooling fluid is passed through in the cooling channel in the attempt to cool, indirectly, the sidewall of the mold. This, however, has generally proven to be ineffective in attaining the molding of thin sidewall sections. An improved blow mold assembly which formed a cooling channel between the shell holder and the exterior of the mold itself is disclosed in U.S. Pat. No. 3,768,948 to Horberg, Jr. et al. The device of Horberg utilizes the exterior sidewall of the mold shell and a cooperating exterior sidewall of a manifold provided as a part of a shell holder to form a single continuous cooling passageway, which passageway is divided into a number of parallel channels in which fluid is introduced at the neck portion of the mold and allowed to flow along the exterior of the shell until it is discharged approximate the base portion of the mold shell.

An improvement over the device of Horberg, et al. was to provide a cooling circuit defined internally within, and as a part of the mold shell itself. This is illustrated in U.S. Pat. No. 3,601,858 to Blanchard, and in U.S. Pat. No. 5,255,889 to Collette, et al. The problem with these internal cooling circuits, however, is that only a single cooling circuit is provided for cooling both the neck and the sidewall portion of the container, for example, as in Collette, and for also cooling the base of the container as shown in Blanchard. Thus, the ability to separately control the temperature of the mold cavity with respect to the neck and the sidewall portions of the container was not possible. This will result in the sidewall of the container being molded in a thicker section than needed along the body portion of the container, which has the undesirable effect of driving up material costs. Although an improvement over the device of Horberg, et al. for example, these latter two patents still failed to provide a means for adequately cooling the body portion of the container within a unitary shell to allow for the molding of a "thin" sidewall.

Several sectional blow mold shell assemblies have been developed in which a plurality of complimentary shaped mold sections may be mated or stacked together for constructing a mold shell (shell half) of a desired shape and size, with each of the individual mold sections being provided with a separate cooling circuit for heat treatment/stress crystallization purposes. Examples of this type of construction are disclosed in U.S. Pat. No. 4,233,022 to Brady, et al.; U.S. Pat. No. 4,701,121 to Jakobsen et al.; U.S. Pat. No. 4,822,543 to Iizuka, et al.; U.S. Pat. No. 5,255,889 to Collette, et al.; and U.S. Pat. No. 5,411,698 to Mero, et al.

The problem with using sectional blow mold shell assemblies, however, is the inherent cost of machining the separate mold sections which together cooperate to form the mold shell, to the required degree of precision for defining a continuously shaped molding cavity without unsightly parting or joint lines between each section in the container where these sections adjoin one another, the complexity of the cooling fluid connections to the mold shell sections, the resultant labor costs involved in assembling these molds, and in changing these molds out when differing shaped and sized bottles and/or packaging containers are to be molded.

What is needed, therefore, but seemingly unavailable in the art, is a unitary blow mold shell with an independent cooling circuit for the neck portion of a molding cavity defined within the shell, and a second independent cooling circuit also defined within the shell for cooling the body or sidewall portion of the container as it is molded. There is also a need for such an improved blow mold shell/shell assembly in which the cooling fluid supply line(s), and fluid discharge line(s), respectively, may be placed in direct sealed fluid communication with these cooling channels without otherwise having to be passed through an intermediate support or holder plate to which the mold shell is otherwise mounted. Lastly, there is a need for an improved method of blow molding containers using such a mold shell which allows for the precise control of the thickness of the sidewall of the container during the blow molding process.

SUMMARY OF THE INVENTION

The present invention provides an improved blow mold shell, a blow mold shell assembly, and a method of blow molding containers which overcome some of the design deficiencies of the known blow mold shells, shell assemblies, and methods. The invention provides a simple, efficient, and cost effective blow mold shell adapted for use in molding containers in which the temperature of a neck forming portion and a body forming portion, respectively, of a partial molding cavity defined within and by the shell may be separately and precisely controlled such that the sidewall of the container may be molded in as thin a cross-section as possible, or desirable.

The improved blow mold shell of this invention is provided as a unitary blow mold shell having a first end and a spaced second end, with an elongate continuous sidewall extending between its first and second ends, respectively. A partial container molding cavity is defined within an interior surface of the blow mold shell. A first cooling fluid circuit or passageway is defined within the shell with respect to a container neck forming portion of the molding cavity, and a second independent cooling fluid circuit or passageway is defined within the shell with respect to the container body forming portion of the molding cavity, which extends in a lengthwise direction between the first and second ends of the shell.

The blow mold shell assembly of this invention is formed by releasably mating two substantially identical ones of the mold shells together. The shell assembly may also be provided with a separate base member constructed and arranged to be received between the two mold shells as they are closed on one another and about a heated plastic preform during the molding process. The base member defines a base forming portion of the container. A separate third cooling fluid circuit or passageway may be defined within the base member to separately cool the base portion of the container.

Due to the unique construction of the blow mold shell and shell assembly described above, an improved method of blow molding a container is provided. This method is particularly well suited for use on a stretch blow machine for forming a container of the type having a neck, a spaced base, and an elongate body extending between the neck and base thereof. The method includes the steps of positioning a preheated tubular preform at a first end of an elongate blow mold shell assembly, stretching the preform in a lengthwise direction from a first end toward the second end of the shell assembly, and injecting pressurized air into the preform to radially expand the preform against a molding cavity defined within and by the shell assembly.

The method also includes the steps of cooling a neck forming portion of the molding cavity by passing a first cooling fluid through a first cooling fluid circuit defined within the mold with respect to the neck forming portion of the mold so that the neck of the container is molded to have a first wall thickness, and separately cooling a body forming portion of the molding cavity by passing a second cooling fluid through a second independent cooling fluid circuit defined within the mold with respect to the body forming portion so that the sidewall of the container is molded to have a second wall thickness along the body of the container.

It is, therefore, an object of the present invention to provide an improved blow mold shell which is constructed such that a neck forming portion of the mold shell can be cooled separately and independently of a body forming portion of the mold shell.

Yet another object of the present invention is to provide an improved blow mold shell which is simple in design and construction, is rugged and durable in use, and is easy to use.

It is to these objects, as well as to the other objects, features and advantages of the present invention, which will become apparent upon reading the specification, when taken in conjunction with the accompanying drawings, to which this invention is directed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view of a pair of the blow mold shells of this invention.

FIG. 2 is an elevational view of one of the blow mold shells of FIG. 1.

FIG. 3 is a top cross-sectional view along line 3—3 of FIG. 1 illustrating the neck cooling circuit defining within the blow mold shell.

FIG. 4 is a side cross-sectional view along line 4—4 of FIG. 1 illustrating a body cooling circuit within the blow mold shell.

FIG. 5 is a fragmentary side cross-sectional view of an illustrative bottom cross port connection formed as a part of the body cooling circuit within the blow mold shell.

FIG. 6 is a top cross-sectional view along line 6—6 of FIG. 2 illustrating an exemplary top cross port connection within the body cooling circuit of the blow mold shell.

FIG. 7 is a side cross-sectional view of the improved blow mold shell assembly of this invention, illustrating also the differing sectional wall thicknesses of a plastic container blow molded therewith.

FIG. 8 is a side cross-sectional view of an alternate embodiment of the blow mold shell of this invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which like reference numerals indicate like parts about the several views, and in which preferred embodiments of the invention are shown. It is understood by those skilled in the art that this invention may be embodied in many different forms, and should not be construed as being limited to the embodiments set forth herein. Rather, the embodiments set forth herein are provided so that the disclosure will be thorough and complete, which embodiments will fully convey the scope of the invention to those skilled in the art.

Referring now to FIG. 1, a pair of substantially identical elongate blow mold blow shells 5 are disclosed, which are

5

substantially identical to one another, and may be completely identical if so desired. Each blow mold shell **5** has a first end **6** and a spaced second end **7**. Extending between the two ends of the blow mold shell is an elongate sidewall **9** having an outwardly facing exterior surface **10** and an interior surface **11** (shown in FIG. 4). Each blow mold shell **5** is fashioned by being machined from a ductile metal, preferably stainless steel, although other types of steel or metals suited for use as blow mold shells may suffice.

As best shown in FIGS. 4 and 7, a partial molding cavity **13** is defined within the interior surface **11** of the blow mold shell. In known fashion, the partial molding cavity will define a container neck forming portion **14** approximate the first end **6** of the blow mold shell, and a container body forming portion **15** extending between the container neck forming portion and the second end **7** of the blow mold shell.

A first cooling circuit **17** is defined internally within, and as a part of, the blow mold shell **5**, and is illustrated in FIG. 3. This first cooling circuit is positioned with respect to the container neck forming portion of the partial molding cavity, and is provided for the purpose of cooling the neck forming portion of the molding cavity during the molding of a container therewith. The first cooling circuit is comprised of an inlet port **18** defined within a flat face **19** formed on the exterior surface of the blow mold shell, and at the first end thereof. The cooling circuit extends toward the interior surface of the blow mold shell along a first leg **20** drilled into the shell, which is cross ported into a second leg **20'** which is drilled into the shell from the interior surface toward the exterior surface thereof. A mirror image cross port leg **20''** is also drilled from the interior surface toward the exterior surface of the shell, and intersects the second leg **20'**. Thereafter, a fourth leg **20'''** is drilled through a discharge port **22** extending toward, and intersecting the third leg of the neck cooling circuit **20''**.

The neck cooling circuit thus defines a continuous circuit extending within the shell with respect to the neck forming portion of the shell. It is intended that a cooling fluid will be passed through this cooling circuit, for example water, ethylene glycol, or an ethylene glycol water mix, for example, for the purposes of cooling the container neck forming portion of the molding cavity such that the neck of the container **95** (FIG. 7) is blown to have first wall section thickness **96** as desired. Advantageously, the neck cooling circuit is included closely adjacent the cavity for maximum efficiency in high temperature applications. It is also anticipated that a heat-treatment fluid, for example a heated oil, may be passed through the first cooling circuit rather than a cooling fluid to heat-treat the container being molded.

The first cooling circuit **17** is supplied with cooling fluid through a cooling fluid supply line **21** sealed on to inlet port **18**. In similar fashion, a cooling fluid discharge line **23** extends from discharge port **22**, and is in sealed engagement therewith. It is anticipated that the supply line and discharge line will each be a length of a flexible fluid-tight hose extending from a supply manifold (not illustrated) provided as a part of a blow mold machine (not illustrated) and into sealed fluid engagement directly with the inlet and discharge ports, respectively, of the blow mold shell. Although it is not illustrated, it is anticipated that, in known fashion, the cooling fluid supply line and the cooling fluid discharge line for the neck cooling circuit of the shell **5** may be passed directly through a shell holder (not illustrated) to which the shell is fastened, rather than through a separate hose or pipeline.

As shown in FIG. 3, the open end of leg **20'**, as well as the open end of leg **20''** of the neck cooling circuit **17** are each

6

sealed by a plug **25**, **26**, respectively. These plugs **25**, **26**, will preferably comprise hydraulic seals or other fluid-tight seals which will be press fit into the openings defined within the surface of the shell once the respective legs of the neck cooling circuit have been drilled within the shell body.

Referring now to FIGS. 3-6, a separate, independent second cooling circuit **28** extends along and is spaced with respect to the container body forming portion **15** of the mold shell **5**. The second cooling circuit is separate, and independent of the first cooling circuit and thus is operated independently of the first cooling circuit in fashion heretofore unknown in the art within a unitary blow mold shell.

The second cooling circuit **28** begins with an inlet port **29** defined within the exterior surface **10** of the blow mold shell **5**. A cooling fluid supply line **30** is received on inlet port **29** in sealed fluid engagement therewith, and preferably comprises a flexible fluid-tight hose, although a rigid pipeline can be used if so desired, as well as for the neck cooling circuit. The inlet port, which is drilled into the body of the shell, includes a side cross port which extends to a first downwardly extending leg **32** of the body cooling circuit. First leg **32** is formed by being drilled downwardly from the top of the shell to a predetermined depth. The side port is drilled into the shell to intersect the top port. An elongate continuous body cooling passageway is drilled within the shell, from the second end **7** toward the first end **6** of the shell, and lies along the body forming portion **15** of the partial molding cavity **13** defined by the shell. The first leg is provided with a top plug **33**, a side plug **34**, and a bottom plug **36** which together seal the top, side, and bottom openings within the shell drilled to define the first leg **32** of the second cooling circuit. Each of these plugs **33**, **34**, and **36** will preferably comprise a hydraulic seal, or plug, identical in construction to plugs **25** and **26**. Each of plugs **33**, **34**, and **36** is press fit into its respective opening defined within the exterior surface of the mold shell.

As best shown in FIG. 5, the end of first leg **32** which extends to the second end **7** of the shell is cross ported to an upwardly extending second leg **41** of the second cooling circuit **28** by a bottom cross port connection **38**. The bottom cross port connection comprises a first leg **39** drilled into the second end of the shell through the opening at the second end of the shell for the first leg of the second cooling circuit, and a second leg **40** which is extended (drilled) through an opening drilled within the second end of the shell to define the upwardly extending second leg **41** (FIG. 6). These two legs **39** and **40** intercept one another as shown such that a continuous fluid passageway is created for allowing the cooling fluid to pass from first leg **32** to second leg **41** of the body cooling circuit. The bottom cross port connection includes a bottom plug **42**, preferably a hydraulic seal, for plugging the opening used to define the second leg **40** of the cross port connection and the second leg **41** of the second cooling circuit. The opening at the bottom of the first leg of the cooling circuit is plugged with the plug **36**, as described above.

The second leg **41** of the body cooling circuit extends upwardly along and with respect to the body forming portion of the mold cavity defined by the shell until it intersects a top cross port connection **43** illustrated in FIG. 6. The top cross port connection is defined by an opening **44** which is drilled into the exterior surface of the blow mold shell, and extends as an elongate continuous longitudinal bore **46** drilled into the shell intermediate the first and second ends of the shell. Once the bore is drilled, the open end **44** thereof is plugged with a hydraulic seal or plug **47** constructed in fashion identical to plug **42**, as well as plugs **36**, **34**, and **33** described

above. So constructed, the cooling fluid which passes upward along second leg **41** will pass along the longitudinal bore **46** toward a third leg **49** of the second cooling circuit, the third leg **49** being drilled within the shell in fashion identical to the second leg **41**, and extending along and spaced with respect to the body forming portion of the molding cavity toward a second bottom cross port connection (not illustrated), preferably constructed in fashion identical to bottom cross port connection **38** of FIG. **5**.

Thereafter, extending upwardly from the second bottom cross port connection will be a fourth leg **50** (FIGS. **3**, **6**) of the second cooling circuit which extends upwardly to a discharge port **51** (FIG. **3**) drilled into the exterior surface of the mold shell in fashion similar to the formation of inlet port **29**. Fourth leg **50** is formed within the shell **5** identically to the formation of first leg **32**, to include the requisite bottom, side, and top ports and plugs, such as side plug **50'** (FIG. **3**), for sealing the passageway within the shell. A cooling fluid discharge line **52** in sealed fluid engagement with the discharge port extends away therefrom, and preferably comprises a length of flexible fluid-tight hose, although rigid piping may be used if so desired.

So constructed, a first cooling fluid may be passed through the first cooling circuit **17**, through the inlet port **18**, and exiting therefrom through the discharge port **22** for cooling the neck forming portion of the molding cavity. A second separate cooling fluid, which may again comprise water, ethylene glycol, or a water ethylene glycol mix, or any other suitable cooling fluid, and which may also include heating fluids, for example heated oils, for either the neck or body looking circuits, is passed continuously through the shell by being introduced into the shell through inlet port **29**, passing downwardly along the shell from the first end toward the second end thereof along first leg **32**, porting over to the second leg through the bottom cross port connection **38**, and passing upwardly along second leg **41** to the top cross port connection **43**. The cooling fluid then passes along the longitudinal bore of the top cross port connection to the third leg **49**, and passes downwardly therein to a second bottom cross port connection, whereupon the fluid is passed upwardly within the shell through the fourth leg **50**, along and with respect to the body forming portion **50** of the molding cavity, and exits the shell through discharge port **51**. Thus, advantageously cooling fluids may be passed through both the first cooling circuit **17** and the second cooling circuit **28**. Alternatively, a cooling fluid may be passed through cooling circuit **17** and a heating fluid may be passed through the second cooling circuit **28**, or vice versa.

A blow mold shell assembly **55** constructed of two of the blow mold shells **5** is illustrated in FIG. **7**. The blow mold shell assembly is formed by taking two substantially identical ones of blow molds shells **5**, the shells need not be identical, but is anticipated that they typically will be, which are releasably mated to one another in known fashion such that the two partial molding cavities **13** (FIG. **4**) thereof, will define a blow mold cavity about a longitudinal axis denoted by the reference character "A" in FIG. **7**. An annular spacer collar **56** is fastened to the second end of each blow mold shell **5**, typically by being screwed thereto. The spacer collar sits intermediate the second end of the blow mold shell, and an annular locking collar **57** sized and shaped for receiving a base assembly **59** therein in locking fashion.

Base assembly **59**, as shown in FIG. **7**, is conventionally constructed and includes a pedestal **60** defining a continuous locking ring **61** therein for being received by the locking collar **57** of the two mold shells **5** as the mold shells are closed about the plastic (PET) preform **90**, shown in phan-

tom lines, used to blow mold a container. A continuous base forming portion **63**, known to those skilled in the art as the "crown" of the container, is removably affixed to the pedestal **60**, and defines the base portion of the container **95** that will be blow molded therein. In known fashion, a third cooling circuit **64** is defined within the base assembly **59**, which includes an inlet passageway **65** defined within the pedestal, a cooling passageway and/or chamber **67** formed within the base assembly along and with respect to the base forming portion **63** of the mold assembly, and a discharge passageway **68** extending away therefrom. Base assembly **59** is reciprocally moved toward and away from the second end of the mold shells in known fashion.

Still referring to FIG. **7**, the two blow mold shells **5** are supported on a respective one of a first shell holder **70**, and a second shell holder **71**. These two shell holders are each fastened to a blow mold machine (not illustrated), typically by being fastened to an operating mechanism of the type disclosed in U.S. Pat. Nos. 5,362,250, and 5,683,729, the provisions of each such patent being incorporated herein fully by this reference, so that as the two mold shells are closed about the preform **90** shown in phantom lines in FIG. **7**, they are also closed about the base assembly **59** for forming a substantially closed blow mold cavity used to define the container **95** to be molded therein.

Due to the construction of blow mold shell **5** as described above, the cooling fluid supply lines **21** and **30** for the neck and body cooling circuits, respectively, as well as the cooling fluid discharge lines **23** and **52** for the neck and body cooling circuits of the shell, respectively, are at the first end of the shell **6**, as best shown in FIGS. **1-3**, such that there is not a need to define a cooling fluid supply or discharge line within the shell holders for the purposes of supplying the respective shells. By being constructed in this manner, it is therefore not necessary to have a sealed interface between the shell holder and the shell for passing cooling fluid into and out of the shell, which thus simplifies the changing over of the shells on a blow mold machine when it is desired to change from producing a container of a first size to a container of second differing size.

Also, by constructing the shells in this manner, it is not necessary to purge the cooling circuits within the shells and shell holders prior to changing the shells out. All that is needed is to remove the cooling fluid supply and discharge lines at the first end of the respective shells, remove the shells from the holders, place new shells in the holders, and then fasten the cooling supply fluid and discharge lines to the mold shells. Although not illustrated herein, it is anticipated that the respective cooling fluid supply and discharge lines which are in sealed fluid engagement with the shell can be equipped with a snap fit connector, the snap fit connector having an integral check valve formed as a part thereof, to further speed and simplify the changing over of the mold shells from a first to a second size.

As shown in FIG. **7**, each one of shell holders **70** and **71** includes an annular mounting ring **72**, i.e. a flange, at the upper end thereof. The mounting ring is sized and shaped to be received within an annular mounting slot **74** defined within the exterior surface **10** at the first end **6** of the blow mold shell **5**. The mounting slot is defined by a pair of shoulders **75**, **76**, as shown in FIGS. **2** and **4**.

Although it is not illustrated herein, it is anticipated, if so desired, that the flat face **19** need not be defined within the exterior surface of the shell, rather the inlet port **18** and the discharge port **22** of the neck cooling circuit **17** may be drilled directly into the arcuate exterior surface of the shell,

as are inlet port **29** and discharge port **51** of the body cooling circuit. Moreover, it is anticipated that a second annular mounting slot (not illustrated) may be defined within the exterior surface of the shell, spaced parallel to and intermediate the mounting slot **74**, and the second end **7** of the blow mold shell so that the blow mold shell of this invention may be easily retrofit to certain of the known types of blow mold machines currently available.

Referring now to FIG. **8**, an alternate embodiment of the blow mold shell **5'** having a first end **6'** and a spaced second end **7'** is illustrated. As with the blow mold shell **5** of FIGS. **1-7**, the blow mold shell **5'** has an elongate sidewall **9'** with an interior surface **11'** which defines a partial mold cavity **13'** defining a container neck forming portion **14'** and container body forming portion **15'**. In the same fashion as described for the first blow mold shell **5** in FIGS. **1-7**, blow mold shell **5'** also has a first or neck cooling circuit **17'**, and a second or body cooling circuit **28'** separately and independently defined within the shell. Here, however, the second cooling circuit **28'** is provided with cooling fluid through the shell holder **70'**, rather than by separate supply lines as shown in FIG. **3**.

As shown in FIG. **8**, therefore, the shell holder **70'** has a fluid supply passageway **81** defined therein which is in registry with the side opening defined (drilled) within the exterior surface of the blow mold shell for the first leg **32'** of the second cooling circuit in which the side plug **34** would otherwise be received, as shown, for example in FIGS. **3** and **4**. Top plug **33'** will plug the top of the first leg **32'** of the body cooling circuit, and the bottom plug **36'** will plug the bottom of the leg. The body cooling circuit will include two bottom cross port connections identical to that shown in FIG. **5** for the two pairs of legs within the cooling circuit, and a top cross port connection similar to that shown in FIG. **6** as well, although neither of these is illustrated in FIG. **8**. The body cooling circuit **28'** is thus a continuous cooling circuit as is body cooling circuit **28** described above.

Still referring to FIG. **8**, a fluid discharge passageway **82** is defined within shell holder **70'** for allowing the cooling fluid to exit from the body cooling circuit **28'** through the side port shown drilled for the fourth leg of the cooling circuit. The fluid discharge passageway **82** of FIG. **8** is defined at the top end of the shell holder **70'** parallel to supply passageway **81**, and is located at the top portion of the fourth leg of the body cooling circuit **28'** such that the fluid passes entirely through the cooling circuit before being discharged from the shell through the shell holder. This is accomplished by passing the fluid through the side discharge port drilled into the fourth leg of the body cooling circuit, such that this opening is in registry with the opening is **82** defined within the shell holder **70'** for allowing the cooling fluid to pass from the blow mold shell.

Referring to FIG. **7**, a tubular PET preform, also known to those skilled in the art as a parison, is illustrated as **90** in phantom line at the upper end **6** of two blow mold shells **5** prior to being molded into a container **95**. The PET preform, in known fashion, has a first threaded end **91** and a second closed end **92**. The preform will extend along axis **A**, and is received within a neck opening **93** at the first end of each shell, formed about axis **A**, as illustrated in FIG. **3**. After the PET preform is pre-heated, it is placed within the neck opening **93** of two shells, and the shells are closed about the preform and the base assembly **59** once it has been moved into position upwardly along axis **A**, such that the shells and the base assembly form a substantially closed blow mold cavity. Once this is done, an elongate stretch rod **94**, in known fashion, is sealed on the threaded end of the preform

and extended therein so that it stretches the preform toward the second end **7** of the blow mold shells **5**. Once this is accomplished, compressed air, or any other suitable fluid, is passed into the preform through the stretch rod, such that the preform expands and takes on the shape of the container neck forming portion **14**, container body forming portion **15** (FIG. **4**) and the container base forming portion **63** (FIG. **7**) of the container **95** illustrated in FIG. **7**.

As the neck cooling circuit **17** is controlled separately from the body cooling circuit **28**, it is possible to control the temperature of the neck separately from the temperature of the body, so that the body portion of the container is molded to be as thin as possible but yet will possess sufficient structural strength and act as a suitable vapor barrier in order to minimize the amount of PET material used to form the preform and the container.

This is best shown in FIG. **7**, which shows a first wall section **96** for the container along the neck/neck forming portion of the molding cavity having a first thickness or section, a thinner second wall section **98** extending along the body forming portion of the molding cavity, namely between the first and second ends of the mold shell, and a thicker third wall section **99** along the base portion of the container. It is anticipated that the neck and base will both be thicker than the sidewall. The base will be cooled separately by the third cooling circuit **64** defined within and as a part of the base assembly **59**, such that in this shell assembly, and this method of molding blow mold containers, the neck, the body, and the base of the container are separately cooled and/or heat-treated in fashion heretofore unknown in the art for a unitary blow mold shell.

It will be appreciated that many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains, having the benefit of the teachings presented in the foregoing description and the associated drawings. It is thus to be understood that the invention is not to be limited to the specific embodiments disclosed herein, and that many modifications and other embodiments of the invention are intended to be included within the scope of the appended claims. For example, although differing embodiments of the invention have been disclosed herein, it is understood that the neck cooling circuit could also be supplied through the shell holder as is the body cooling circuit, that the neck cooling circuit could be provided through the shell holder and the body cooling circuit provided through flexible hoses, or any possible combination thereof. Moreover, although specific terms are employed herein, they are used in a generic and descriptive sense only, and not for the purpose of limiting the described invention or the claims which follow.

I claim:

1. A blow-mold assembly for use in manufacturing a container on a blow-mold machine, said blow-mold assembly comprising:

- a first unitary blow-mold shell having a first end, a spaced second end, and an elongate continuous sidewall extending between said first and second ends, respectively, said sidewall having an interior surface, and an outwardly facing exterior surface;
- a partial container molding cavity defined in said interior surface;
- a first cooling fluid circuit defined within said shell with respect to a container neck forming portion of said molding cavity; and
- an independent second cooling fluid circuit defined within said shell with respect to a container body forming

11

portion of said molding cavity extending between the first and second ends of said shell in a lengthwise direction.

2. The blow-mold assembly of claim 1, further comprising a second elongate blow-mold shell, said second shell being substantially identical in construction to said first shell, said first and second blow-mold shells being constructed and arranged to be releasably mated to one another.

3. The blow-mold assembly of claim 2, further comprising a base member defining a container base forming portion of the blow-mold assembly.

4. The blow-mold assembly of claim 3, said base member being constructed and arranged to be held at the respective second ends of said blow-mold shells as said shells are mated to one another.

5. The blow-mold assembly of claim 3, said base member including a third cooling fluid circuit defined therein with respect to said container base forming portion.

6. The blow-mold assembly of claim 1, said first shell further comprising:

at least one first fluid inlet opening, and at least one first fluid discharge opening, respectively, defined within said shell and in communication with said first cooling circuit; and

at least one second fluid inlet opening, and at least one second fluid discharge opening, respectively, defined within said shell and in communication with said second cooling circuit.

7. The blow-mold assembly of claim 6, further comprising:

at least one first cooling fluid supply line in sealed fluid communication with said at least one first fluid inlet opening, and at least one first cooling fluid discharge line in sealed fluid communication with said at least one first fluid discharge opening; and

at least one second cooling fluid supply line in sealed fluid communication with said at least one second fluid inlet opening, and at least one second cooling fluid discharge line in sealed fluid communication with said at least one second fluid discharge opening, respectively.

8. The blow-mold assembly of claim 7, wherein each respective one of said fluid supply and fluid discharge lines comprises a length of a flexible fluid-tight hose.

9. The blow-mold assembly of claim 6, further comprising:

a shell holder constructed and arranged to receive said first shell thereon, said first shell being fastened to said first shell holder;

a first fluid supply passageway and a first fluid discharge passageway, respectively, defined within said shell holder in registry with said at least one first fluid inlet opening and said at least one first fluid discharge opening, respectively; and

a second fluid supply passageway and a second fluid discharge passageway, respectively, defined within said shell holder in registry with said at least one second fluid inlet opening and said at least one second fluid discharge opening, respectively.

10. The blow-mold assembly of claim 1, said shell further comprising at least one annular mounting slot defined within the exterior surface thereof, said slot being spaced from the first end of the shell and extending perpendicularly with respect to the length thereof.

11. A blow-mold assembly for use in the manufacture of a blow-mold container, the container having a neck, a spaced base, and an elongate body portion extending between the neck and the base thereof, said assembly comprising;

12

a first blow-mold shell and a substantially identical second blow-mold shell, each said shell being constructed and arranged to be releasably mated to the other, and including:

i) a first end, a spaced second end, and an elongate sidewall extending therebetween, the sidewall having an interior surface and an outwardly facing exterior surface;

ii) a partial container molding cavity defined in said interior surface, said molding cavity defining a container neck forming portion at the first end of the shell and a container body forming portion extending in a lengthwise direction between the respective ends of the shell;

iii) a first cooling fluid circuit defined within the shell with respect to said neck forming portion, and an independent second cooling fluid circuit defined within the shell with respect to said body forming portion;

iv) a first fluid inlet opening and a first fluid discharge opening, respectively, defined within the shell and in communication with said first cooling circuit; and

v) a second fluid inlet opening and a second fluid discharge opening, respectively, defined within the shell in communication with said second cooling circuit.

12. The blow-mold assembly of claim 11, wherein said first cooling circuit is constructed and arranged to cool the neck of the container as it is molded as a first cooling fluid is passed therethrough, and wherein said second cooling circuit is constructed and arranged to cool the body of the container as it is molded as a second cooling fluid is passed therethrough.

13. The blow-mold assembly of claim 11, further comprising:

a first cooling fluid supply line in sealed fluid communication directly with said first fluid inlet opening and a first cooling fluid discharge line in sealed fluid communication directly with said first fluid discharge opening; and

a second cooling fluid supply line in sealed fluid communication directly with said second fluid inlet opening, and a second cooling fluid discharge line in sealed fluid communication directly with said second fluid discharge opening.

14. The blow-mold assembly of claim 13, each respective one of said fluid supply and discharge lines comprising a length of a flexible fluid-tight hose.

15. The blow-mold assembly of claim 11, further comprising a base member constructed and arranged to be received between the second ends, respectively, of each said shell as said shells are mated to one another.

16. The blow-mold assembly of claim 15, said base member defining a container base forming portion of the molding cavity, said base member including a third cooling fluid circuit defined therein with respect to said base forming portion, said third circuit having a third fluid inlet opening and a third fluid discharge opening in communication therewith.

17. The blow-mold assembly of claim 16, wherein said third cooling circuit is constructed and arranged to cool the base of the container as it is molded as a third cooling fluid is passed through said third circuit.

18. The blow-mold assembly of claim 11, each said shell further comprising at least one annular mounting slot defined within the exterior surface thereof, said at least one slot being spaced from the first end of the shell and extending perpendicularly with respect to the length of the shell.

13

19. The blow-mold assembly of claim 11, further comprising a first shell holder and a second shell holder, a respective one of said shells being releasably fastened to a respective one of said shell holders.

20. A blow-mold shell adapted for use as part of a blow-mold assembly, said shell comprising:

a unitary shell body having a first end, a spaced second end, and an elongate continuous sidewall extending between the first and second ends thereof;

said sidewall having an interior surface and an outwardly facing exterior surface;

a partial molding cavity defined in said interior surface, said molding cavity defining a container neck forming portion at the first end of said body, and an elongate container body forming portion extending between the first and second ends of said body in a lengthwise direction;

a first cooling fluid circuit defined within said body with respect to the neck forming portion of the mold cavity;

at least one first fluid inlet opening and at least one first fluid discharge opening, respectively, defined within said body and in communication with said first cooling circuit;

a second cooling fluid circuit defined within said body with respect to and along the body forming portion of said mold cavity; and

at least one second fluid inlet opening and at least one second fluid discharge opening, respectively, defined within said body and in communication with said second cooling circuit;

said first and said second cooling circuits being defined within the shell body independently of one another.

21. The blow-mold shell of claim 20, wherein said shell is constructed and arranged to be releasably mated to a substantially identical second one of said shells.

22. The blow-mold shell of claim 20, wherein the second end of said shell is sized and shaped to be at least partially closed about a base member of the blow-mold assembly.

14

23. The blow-mold shell of claim 20, further comprising at least one annular mounting slot defined within the exterior surface of said body, said slot being spaced from the first end of said body and extending perpendicularly with respect to the length thereof.

24. A method of blow-molding a container on a blow-mold machine, the container having a neck, a spaced base, and an elongate body extending between the neck and the base thereof, said method comprising:

a) cooling a neck forming portion of a molding cavity partially defined by a unitary mold shell by passing a first cooling fluid through a first cooling fluid circuit defined within the mold shell with respect to said neck forming portion, and molding the neck of the container such that the neck has a first wall thickness; and

b) cooling a body forming portion of said molding cavity by passing a second cooling fluid through a separate second cooling fluid circuit defined within the mold shell with respect to said body forming portion, and molding the body of the container such that the body has a second wall thickness different than said first wall thickness.

25. The method of claim 24, step b) comprising the step of molding the body of the container so that said second wall thickness is less than said first wall thickness.

26. The method of claim 24, including the steps of providing a base member at the second ends of said mold shells, cooling a base forming portion of the molding cavity defined by said base member by passing a third cooling fluid through a third cooling fluid circuit defined within said base member with respect to said base portion, and molding the base of the container such that the base has a third wall thickness different than said second wall thickness.

27. The method of claim 26, the step of molding the base of the container further comprising the step of molding the base of the container such that said third wall thickness is greater than said second wall thickness.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,444,159 B2
DATED : September 3, 2002
INVENTOR(S) : Petre

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, "Rosenfranz et al." should read -- Rosenkranz et al. --; and insert the following:

-- 3,632,249 1/1972 Pearson --.

Signed and Sealed this

Seventh Day of January, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line drawn underneath it.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office