



US006474767B1

(12) **United States Patent**
Teshigawara et al.

(10) **Patent No.:** **US 6,474,767 B1**
(45) **Date of Patent:** **Nov. 5, 2002**

(54) **CALIBRATION METHOD FOR AN OPTICAL SENSOR, AN ADJUSTMENT METHOD OF DOT PRINTING POSITIONS USING THE CALIBRATION METHOD, AND A PRINTING APPARATUS**

6,076,915 * 6/2000 Gast et al. 347/19
6,109,722 * 8/2000 Underwood et al. 347/19
6,164,749 * 12/2000 Williams 347/19
6,257,143 * 7/2001 Iwasaki et al. 101/481

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Minoru Teshigawara**, Urawa; **Naoji Otsuka**, Yokohama; **Kiichiro Takahashi**, Kawasaki; **Hitoshi Nishikori**, Inagi; **Osamu Iwasaki**; **Toshiyuki Chikuma**, both of Tokyo, all of (JP)

EP 0540245 5/1993
EP 0622237 11/1994
JP 54-56847 5/1979
JP 59123670 7/1984
JP 59138461 8/1984
JP 60-71260 4/1985
JP 4-041252 2/1992
JP 4227578 A * 8/1992 B41J/29/46
JP 7-101101 4/1995
JP 09074467 3/1997

(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

Watabe Yuuji; "Controller for Serial Wire Dot Printer," Apr. 27, 1993; Patent Abstracts of Japan.

(21) Appl. No.: **09/285,844**

* cited by examiner

(22) Filed: **Apr. 5, 1999**

Primary Examiner—Thinh Nguyen
Assistant Examiner—Blain Mouttet

(30) **Foreign Application Priority Data**

(74) *Attorney, Agent, or Firm*—Fitzpatrick, Cella, Harper & Scinto

Apr. 3, 1998 (JP) 10-092121

(51) **Int. Cl.**⁷ **B41J 29/393**

(57) **ABSTRACT**

(52) **U.S. Cl.** **347/19**

(58) **Field of Search** 347/19; 399/49, 399/74; 250/559.1, 252.1


In a complimentary printing by bi-directional scanning of a head or by a plurality of heads, a plurality of patterns in which a print start timing is shifted by a predetermined amount are printed with respect to a reference dot formed by the forward scan of the bi-directional scanning or by one of the plurality heads. In these patterns, an area factor by the dots formed by printing of the patterns is designed to be varied depending upon shifting amount. An average density is read from each of the plurality of patterns, optically. The timing at which the maximum one among average densities read from the patterns is obtained, can be set as the printing registration condition. Further, before the above reading operation, an optical sensor used for this operation is calibrated, for improving accuracies of the reading and the registering. By these processings, printing registration between a forward and a reverse scan of a print head or printing registration between a plurality of print heads in a printing apparatus can be performed simply and with high accuracy.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,313,124 1/1982 Hara 347/56
4,345,262 8/1982 Shirato et al. 347/56
4,459,600 7/1984 Sato et al. 347/65
4,463,359 7/1984 Ayata et al. 347/56
4,558,333 12/1985 Sugitani et al. 347/47
4,570,168 * 2/1986 Sjordal et al. 346/145
4,621,343 * 11/1986 Fujieda et al. 714/53
4,723,129 2/1988 Endo et al. 347/10
4,740,796 4/1988 Endo et al. 347/57
4,878,063 10/1989 Katerberg 347/19
5,245,390 * 9/1993 Ishigaki et al. 399/74
5,250,956 * 10/1993 Haselby et al. 347/19
5,488,397 1/1996 Nguyen et al.
5,564,848 10/1996 Quintana
5,697,011 12/1997 Kobayashi et al. 399/49
5,911,526 * 6/1999 Watanabe 400/74

40 Claims, 53 Drawing Sheets






FIG. 1C

FIG. 1B

FIG. 1A




FIG.2C




FIG.2B

FIG.2A






FIG.3C

FIG.3B

FIG.3A




FIG.4A




FIG.4B




FIG.4C

● CHECKER OR LATTICE PATTERN
○ INVERTED CHECKER OR LATTICE PATTERN




FIG. 5




FIG. 6A




FIG. 6B




FIG.7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG.14A




FIG.14B




FIG.14C




FIG.15




FIG.16




FIG. 17




FIG.18




FIG.19

FIG. 20A




FIG. 20B




FIG. 20C




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 23A




FIG. 23B





FIG. 23C






FIG.24




FIG. 25A




FIG. 25B




FIG. 25C

FIG. 26A




FIG. 26B





FIG. 26C






FIG.27

FIG. 28A





FIG. 28B





FIG. 28C






FIG.29




FIG.30




FIG.31




FIG.32




FIG.33




FIG.34




FIG.35








FIG.36

FIG.37A




**OFFSETTING
AMOUNT:
-4DOTS
(RELATIVE
POSITION)**

FIG.37B





**OFFSETTING
AMOUNT:
-2DOTS
(RELATIVE
POSITION)**

FIG.37C





**OFFSETTING
AMOUNT:
0DOTS
(RELATIVE
POSITION)**

FIG.37D



**OFFSETTING
AMOUNT:
+2DOTS
(RELATIVE
POSITION)**

FIG.37E



**OFFSETTING
AMOUNT:
+4DOTS
(RELATIVE
POSITION)**

 : REFERENCE DOT
(FORWARD SCAN
RECORDING)

 : OFFSETTING OR
SHIFTING DOT
(REVERSE SCAN
RECORDING)






FIG.38

FIG.39A




OFFSETTING
AMOUNT:
-0.5DOTS
(RELATIVE
POSITION)

FIG.39B




OFFSETTING
AMOUNT:
-0.25DOTS
(RELATIVE
POSITION)

FIG.39C




OFFSETTING
AMOUNT:
0DOTS
(RELATIVE
POSITION)

FIG.39D



OFFSETTING
AMOUNT:
+0.25DOTS
(RELATIVE
POSITION)

FIG.39E



OFFSETTING
AMOUNT:
+0.5DOTS
(RELATIVE
POSITION)

 : REFERENCE DOT
(FORWARD SCAN
RECORDING)

 : OFFSETTING OR
SHIFTING DOT
(REVERSE SCAN
RECORDING)

IDEAL
CONDITION




FIG. 40A

CONDITION WHICH
CHANGE IN DENSITY
IS SMALL




FIG. 40B

CONDITION WHICH
CHANGE IN DENSITY
IS LARGE




FIG. 40C

● : REFERENCE DOT
(FORWARD SCAN
RECORDING)

○ : OFFSETTING OR
SHIFTING DOT
(REVERSE SCAN
RECORDING)






FIG.41




OFFSETTING
AMOUNT: +1DOTS

FIG.42A




OFFSETTING
AMOUNT: +0.5DOTS

FIG.42B



OFFSETTING
AMOUNT: 0DOTS



FIG.42C




OFFSETTING
AMOUNT: -0.5DOTS

FIG.42D


PATTERN (a)

-  : REFERENCE DOT
(FORWARD SCAN
RECORDING)
-  : OFFSETTING OR
SHIFTING DOT
(REVERSE SCAN
RECORDING)




OFFSETTING
AMOUNT: +1DOTS

FIG.43A




OFFSETTING
AMOUNT: 1.5DOTS

FIG.43B



OFFSETTING
AMOUNT: 2DOTS



FIG.43C



OFFSETTING
AMOUNT: 2.5DOTS

FIG.43D

PATTERN (b)

-  : REFERENCE DOT
(FORWARD SCAN
RECORDING)
-  : OFFSETTING OR
SHIFTING DOT
(REVERSE SCAN
RECORDING)




FIG. 44




FIG.45





FIG.46



(b) IS CASE WHERE EJECTION SPEED IS LOW WITH RESPECT TO (a)
→ OFFSET OF DEPOSITING POSITION BECOMES LARGE

(c) IS CASE WHERE CARRIAGE SPEED IS LARGE WITH RESPECT TO (b)
→ OFFSET OF DEPOSITING POSITION BECOMES LARGE

FIG.47

OBJECT TO BE ADJUSTED	RESOLUTION (DPI)	DROP SIZE	PRINTER 1 (COLOR OF OBJECT TO BE ADJUSTED)			PRINTER 2 (COLOR OF OBJECT TO BE ADJUSTED)	
			HEAD 1	HEAD 2	HEAD 3	HEAD 4	
REVERSE SCAN DIRECTION, BETWEEN TWO-HEADS	360 X 360	LARGE	Bk/c	LC/c	-	-	
HORIZONTAL SCAN DIRECTION, BETWEEN TWO-HEADS	360 X 360	LARGE	Bk/c	LC/c	-	-	
	180 X 180	LARGE	Bk/c	LC/c	-	-	
	720 X 720	SMALL	Bk/c	LC/c	-	-	
	1,440 X 720	SMALL	Bk/c	LC/c	-	-	
BETWEEN BIDIRECTIONAL-RECIPROCAL HORIZONTAL SCANS	360 X 360	LARGE	Bk	Bk	Bk	Bk	
	180 X 180	LARGE	Bk	Bk	Bk	Bk	
	720 X 720	SMALL	Bk	Bk	Bk	Bk	

HORIZONTAL SCAN SPEED EVERY RESOLUTION:
 180 X 180 → 30 INCH/SEC; 360 X 360 → 20 INCH/SEC
 720 X 720 → 20 INCH/SEC; 1,420 X 720 → 10 INCH/SEC

AMOUNT OF INK EJECTION EVERY DROP SIZE:
 "HEAD 1", "HEAD 4" → LARGE (80 DPI), SMALL (40 DPI)
 "HEAD 2", "HEAD 3" → LARGE (40 DPI), SMALL (15 DPI)

FIG. 48

FIG. 49
FIG. 49A
FIG. 49B





FIG. 49A






FIG.50A



FIG.50B




FIG. 51A




FIG. 51B

**CALIBRATION METHOD FOR AN OPTICAL
SENSOR, AN ADJUSTMENT METHOD OF
DOT PRINTING POSITIONS USING THE
CALIBRATION METHOD, AND A PRINTING
APPARATUS**

This invention is based on patent application Ser. No. 92121/1998 filed on Apr. 3, 1998 in Japan, the content of which is incorporated hereinto by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a calibration method of an optical sensor, as well as an adjustment method of dot printing positions using the calibration method and a printing apparatus. An adjustment of dot printing position is, for example, registration of dot printing positions where printing is performed in the bi-directions of a forward scan and a reverse scan and a printing registration between the heads where printing is performed using a plurality of print heads.

2. Description of the Related Art

The optical sensor which has a light-emitting portion and a light receiving section to irradiate with the light on a measuring object to detect the reflected light and to obtain some information concerning the object is applied to various apparatuses in various fields.

In a field of a printing technique, the sensor is used, for example, on the occasion of printing processing, in order to detect existence of the printing medium which is a printing object and the size (e.g. paper width) thereof. In addition, in order to perform a processing (so-called head shading) which corrects a drive condition of a printing element for obtaining a printing image without unevenness in density, it is sometimes used as a means which reads the unevenness in density which is developed on a predetermined test patterns. In addition, it is effective to use the optical sensor in a printing registration, and hereinafter, a processing of the registration for dot printing positions is described.

In recent years, the office automation instruments such as the personal computer and the word processor which is relatively cheap are widely used, and an improvement in high-speed technique and an improvement in high image quality technique of various recording apparatuses for printing-out the information which are entered by the instruments are developed rapidly. In recording apparatuses, a serial printer using a dot matrix recording (printing) method comes to attention as a recording apparatus (a printing apparatus) which realizes printing of a high speed or high image quality with the low cost. For such printers, as the technique which prints at high speed, for example there is a bi-directional printing method and as the technique which the prints in high image quality, for example, there is a multi scanning printing method. [Bi-directional printing method]

As the improvement in high-speed technique, in a printing head which has a plurality of printing elements, although it is also thought to plan an increase in the number of a printing elements and an improvement in a scanning speed of the print head, it is also an effective method to perform bi-directional printing scanings of the print head.

Although, since there is usually the time required for paper-feeding and paper-discharging or the like, it does not become a simply proportional relation, in the bi-directional printing a printing speed of approximately two times can be obtained as compared with the one-directional printing in the printing apparatus.

For example, when using the print head which the 64 pieces of ejection openings are arranged with 360 dpi (dots/inch) in printing density in a direction different from the printing scanning (main scanning) direction (for example, in a sub-scanning direction which is the feeding direction of the printing medium), a printing is performed on, a printing medium of A4 size set in the direction of the length, the printing can be completed by scanning of approximately 60 times. The reason is that, in one-directional printing, each printing scanning is performed only at the time of the movement in the one direction from the predetermined scanning commencement position, and since non-printing scanning to the inverse direction for returning to the scanning commencement position from a scanning completion position is attended, reciprocation of approximately 60 times is required. On the other hand, printing is completed by the reciprocating printing scanning of approximately 30 times in bi-directional printing, so that printing can be performed and since it becomes possible on at the speed of approximately 2 times, whereby bi-directional printing can be considered to be an effective method for an improvement in a printing speed.

In order to register dot-forming positions (for example, for an ink jet printing apparatus, a deposition or landing position of ink) at a forward trip and a return trip together in such bi-directional printing, using a position detection means such as an encoder, based on the detecting position, printing timing is controlled. However, it has been thought that since to form such a feedback controlled system causes an increase in the cost of the printing apparatus, it is difficult to realize this, in the printing apparatus which is relatively cheap.

(Multi Scanning Printing Method)

Secondly, a multi scanning printing method is explained as one example of the improvement in high image quality technique.

When printing is performed using the print head which has a plurality of printing elements, quality of the printed image depends on performance of a print head itself greatly. For example, in the case of the ink-jet print head, the slight differences, which is generated in a print head manufacturing step, such as variations of a form of ink ejection openings and the elements for generating energy for ejecting ink such as an electro-thermal converting elements (ejection heaters), influence a direction and an amount of ejected ink, and result in the cause which makes the unevenness in density of the image which is formed finally to reduce the image quality.

Specific examples are described using FIGS. 1A to 1C and FIGS. 2A to 2C. Referring to FIG. 1A, a reference numeral **201** denotes a print head, and for simplicity, is constituted by the eight pieces of nozzles **202** (herein, as far as not mentioned specifically, refer to the ejection opening, the liquid passage communicated with this opening and the element for generating an energy used for ink, in summary). A reference numeral **203** denotes the ink, for example, which are ejected as a drop from the nozzle **202**. It is ideal that the ink is ejected from each ejection opening by the approximately uniform amount of discharge and in the justified direction as shown in this drawings. When such discharge is performed, as shown in FIG. 1B, ink dots which are justified in size are deposited or landed on the printing medium and, as shown in FIG. 1C, the uniform images that there is no unevenness in density also as a whole can be obtained.

However, there are the variations in the nozzles in the print head **20** actually as is mentioned above, and when

printing is performed as mentioned above as it is, as shown in FIG. 2A, the variations are caused in size of the ink drops and in the ejecting direction of ink discharged from nozzles and the ink drops are deposit or landed on a printing medium as shown in FIG. 2B. In this drawing, a part of the white paper that an area factor can not be served up to 100% periodically exists with respect to the horizontal scanning direction of the head, moreover, in contrast with this, the dots are overlapped each other more than required or white stripes as shown in the center of this drawing have been generated. A gathering of the landed dots in such condition forms the density distribution shown in FIG. 2C to the direction in which nozzles are arranged, and the result is that, so far as usually seen by eyes of a human, these objects are sensed as the unevenness in density.

Therefore, as a countermeasure of this unevenness in density, the following method has been devised. The method is described using FIGS. 3A to 3C and FIGS. 4A to 4B.

According to this method, in order that the printing with regard to the same region as shown in FIG. 1 and FIG. 2 is made to be completed, the print head 201 is scanned 3 times as shown in FIG. 3A and FIGS. 4A to 4C. The region defining four pixels which is a half of eight pixels as a unit in the direction of length in the drawing has been completed by two passes. In this case, the 8 nozzles of the print head are divided into a group of 4 nozzles of upper half and 4 nozzles of lower half in the drawing and the dots which one nozzle-forms by scanning of one time are the dots that the image data are thinned into approximately a half in accordance with the certain predetermined image data arrangement. Moreover, at the second scanning, the dots are embedded in the image data of the half of the remaining and the regions defined four pixels as the unit are completed progressively. Hereinafter, the printing method described above is referred to as a multi scanning printing method.

Using such printing method, even when the print head 201 which is equal to the print head 201 shown in FIG. 2 are used, the influence to the printed image by the variations of each nozzle is reduced by half, whereby the printed image becomes as shown in FIG. 3B and no black stripe and white stripe as shown in FIG. 2B becomes easy to be seen. Therefore, the unevenness in density is fairly also mitigated as compared with the case of FIG. 2C as shown in FIG. 3C.

When such printing is performed, although at first scanning and at second scanning, the image data are mutually divided in a manner to be complementary each other in accordance with the certain predetermined arrangement (a mask), usually, this image data arrangement (the thinned patterns) as shown in FIG. 4A to FIG. 4C, at every one pixel arranged in rows and columns, it is most general to use the formation which makes to form a checker or lattice matrix.

In a unit printing region (here, per four pixels), printing is completed by the first scanning which forms the dots into the checker or lattice pattern and the second scanning which forms the dots into the inverted checker or lattice pattern.

Moreover, usually, travel (vertical scanning travel) of the printing medium between each main scanning is established at a constant, and in the case of FIG. 3 and FIG. 4, is made to move every four nozzles equally.

(Dot Alignment)

As an example of the other improvement in high image quality technique in the dot matrix printing method, there is a dot alignment technique adjusting the dot depositing position. A dot alignment is an adjustment method adjusting the positions which the dots on the printing medium have formed by any means, and in general, the prior dot alignment has been performed as follows.

For example, a ruled line or the like is printed on a printing medium in depositing registration of the forward scan and the reverse scan upon reciprocal or bi-directional printing by adjusting printing timing in the forward scan and the reverse scan respectively, while a relative printing position condition in reciprocal scan is varied. The results of printing has been observed by a user oneself to select the printing condition where best printing registration is achieved, that is, the condition that printing is performed without offset of the ruled line or the like and to set the condition directly into the printing apparatus by entering through a key-operation or the like or to set the depositing position condition into the printing apparatus by operating a host computer through an application.

Moreover, the ruled line or the like is printed on the medium under printing in the printing apparatus having a plurality of heads, when printing is performed between a plurality of heads, while a relative printing position condition between a plurality of heads is varied, with the respective head. As is mentioned above, the optimum condition that best printing registration is achieved has been selected to vary the relative printing position condition to set the printing position condition into the printing apparatus every each head in the mentioned-above manner.

Here, the case where the offset of the dots has been occurred is described.

(Problems upon Performing Image-formation by Bi-directional Printing)

Due to bi-directional printing, the following problems has been caused.

First, when the ruled line (the ruled line of the longitudinal direction) in the direction perpendicular to the horizontal scan of the print head is printed, between the ruled line element which is printed in the forward scan and the ruled line element which is printed in the reverse scan, the dot depositing positions are not registered and the ruled line is not formed into a straight line, but a difference in level occurs. This is referred to as a so-called "offset in ruled line", and this is considered to be the most general disorder which can be recognized by the usual users. In the many cases, the ruled line is formed by a black color, whereby, though the offset in ruled line has been understood as the problem where a monochrome image is formed generally, a similar phenomenon can be caused in the color image also.

When the multi scanning printing is used along with bi-directional printing in order to improve in high image quality, even though in bi-directional printing the depositing positions are not registered, as an effect of the multi scanning printing the offset in the pixel level is not easy to be seen, but from a macroscopic viewpoint the entire image can be seen unequally and is recognized as an unpleasant figure by the user. This generally is called as a texture, and appears on the image in the specific period where there is the offset in the delicate depositing position, thereby being caused. In a strong image in contrast such as the monochrome it is easy to be seen, moreover, when for the printing medium capable of high-density printing such as a coat paper middle-tones printing is performed, it can be easy to be seen.

(Problems in the Case of Performing the Image Formation using a Plurality of the Print Heads)

In the printing apparatus having a plurality of heads, the problems of the case where the offset in the depositing positions of the dots between a plurality of heads has been occurred is discussed.

When the image printing is performed, several colors are combined to perform the image formation frequently, and it is general to use four colors which added black in addition

to three primary colors of yellow, magenta and cyan and it is used most abundantly. When in the case where a plurality of print heads for printing these colors are used, there is the offset of the depositing positions between the print heads, depending upon the amount of the offset, when a different color one another is about to be printed on the same pixel, a deviation in color matching is caused. For example, magenta and cyan are used to form the blue image, and although the part that the dots of both colors are overlapped becomes blue, the part which is not overlapped each other does not become blue, so that the deviation in color matching (irregular color) that each independent color tone appears is caused. When this occurs partially, it does not become easy to be seen, but when this phenomenon occurs in the direction of scanning continuously, a band-shaped deviation in color matching with a certain specific width is caused, so that the image becomes unequal. In addition, in a region adjacent the image region in the case of in the regions of the same color, when there is no offset in the depositing positions of the dots, a uniform impression and color development differ between the image regions adjacent each other, so that the image that there is a sense of incongruity as the image is formed. Moreover, though this deviation in color matching does not become easy to be seen in the case of an ordinary paper, it becomes easy to be seen, when a favorable printing medium in color development such as a coat paper is used.

Moreover, in the case where a different color is printed on adjoining the pixel, when there is the offset in the depositing positions of the dot, the clearance, that is, the region which is not covered by the ink on the part have caused and, the ground of the printing medium can be seen. This phenomenon frequently is called "white clearance", since the case of a white ground is frequent in the printing medium generally. This phenomenon is easy to be seen in the image high in contrast, and when a black image is formed as a colored background, the white clearance which no ink is deposited between a black and coloration, since a contrast between white and black is high, can be easy to be seen more clearly.

It is effective to perform the above-mentioned dot alignment in order to suppressed occurring of the problems as mentioned above. However, the complicatedness that the user should observe the results which the depositing registration conditions are varied by the eyes to select the optimized the depositing registration condition to perform entering operations is accompanied, and moreover, since fundamentally, a judgment for obtaining the optimum printing position by observing through eyes is enforced on the user, the establishment which is not optimized can be set. Therefore, it is especially unfavorable to the user who is not accustomed to operation.

Moreover, the user is enforced to expense in time and effort at least two times since the user should printing the image to perform the depositing registration and in addition, to perform conditional establishment after observing to perform judgments required, whereby upon realizing the apparatus or a system excellent in operability, it is not only desirable but also is disadvantageous from the viewpoint of a time-consumption.

Namely, it has been desired strongly that the apparatus or system capable of printing the image at a high speed and of the high-quality image without occurring the problem on the image formation as above-mentioned and the problem on the operability is realized at a low cost by designing to be able to register the depositing position without using a feedback controlling means such as an encoder by an opened loop.

SUMMARY OF THE INVENTION

Therefore, the object of the invention is to realize a dot alignment method which is excellent in operational performance and the low cost.

Moreover, the invention, without fundamentally enforcing the user the judgment and the adjustment, is designed to detect the optical characteristics of the printed image to derive the adjustment condition of the optimum dot alignment from the detected results and to set the adjustment condition automatically, thereby to improve the adjustment accuracy thereof.

Furthermore, although it is effective to use an optical sensor, it is useful for further improvement of the processing of the dot alignment to use the optical sensor under the condition which the optical sensor is calibrated appropriately upon realizing such dot alignment method, therefore, the invention provides a calibration method of the optical sensor capable of realizing this. However, the method can be applied to the optical sensor which is used widely in the printing apparatus without limiting to an explanation as follows.

In a first aspect of the present invention, there is provided a calibration method of an optical sensor having a light-emitting portion and a photosensing portion, comprising the steps of:

- modulating electric signals supplied to the light-emitting portion and/or the photosensing portion;
- measuring the optical characteristics of a plurality of patterns having different optical characteristics by the optical sensor;
- allowing to perform the measurement every amount of the modulation of a plurality of steps; and
- acquiring an amount of modulation capable of obtaining the predetermined measurement range from this result.

In a second aspect of the present invention, there is provided a calibration method of an optical sensor having a light-emitting portion and photosensing portion, comprising the steps of:

- modulating electric signals supplied to the light-emitting portion and/or the photosensing portion.
- measuring an optical characteristics of patterns having a predetermined optical characteristics by the optical sensor;
- allowing to perform the measurement every amount of the modulation of a plurality of steps;
- comparing a measured value every the amount of modulation with the predetermined threshold value; and
- selecting an amount where the measured value coincides with or most approximates to the threshold value as the amount of modulation which the predetermined measurement range is obtained, as a result of the comparison.

In a third aspect of the present invention, there is provided a calibration method of an optical sensor having a light-emitting portion and a photosensing portion, comprising the steps of:

- modulating electric signals supplied to the light-emitting portion and/or the photosensing portion;
- measuring an optical characteristics of pattern having a predetermined characteristics by the optical sensor;
- allowing to perform the measurement every amount of the modulation of a plurality of steps;
- comparing a measured value every the amount of modulation with the predetermined threshold value;
- selecting an amount where the measured value coincides with or most approximates to the threshold value, as a result of the comparison;
- measuring optical characteristics of a plurality of patterns having different optical characteristics by the optical

sensor, while modulating in a plurality of steps in the vicinity of the selected amount of modulation; and

acquiring an amount of modulation capable of obtaining the predetermined measurement range from this result.

In a fourth aspect of the present invention, there is provided a printing registration method for processing for performing printing registration in a first printing and a second printing with respect to a printing apparatus for performing printing of an image by the first printing and the second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, the method comprising the steps of:

pattern-forming for controlling the printing head to form a plurality of patterns respectively having optical characteristics corresponding to a plurality of shifting amounts, the plurality of patterns being respectively formed corresponding to the plurality of shifting amounts of relative printing positions of the first printing and the second printing, the patterns being formed by the first printing and the second printing;

measuring respective optical characteristics of the plurality of patterns formed;

calibrating an optical sensor being used in order to perform the measurement; and

acquiring an adjustment value of a dot forming position condition between the first printing and the second printing on the basis of respective optical characteristics of the plurality of patterns measured.

In a fifth aspect of the present invention, there is provided a printing apparatus for performing printing of an image by a first printing and a second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, comprising:

patterns-forming means for controlling a printing head to form a plurality of patterns respectively having optical characteristics corresponding to a plurality of shifting amounts, the plurality of patterns being respectively formed corresponding to the plurality of shifting amounts of relative printing positions of the first printing and the second printing, the patterns being formed by the first printing and the second printing;

means for measuring respective optical characteristics of the related plurality of patterns formed;

means for calibrating an optical sensor being used in order to perform the measurement; and

acquiring means for obtaining an adjustment value of dot forming position conditions between the first printing and the second printing on the basis of respective optical characteristics of the plurality of patterns measured.

In a sixth aspect of the present invention, there is provided a printing system provided with a printing apparatus for performing printing of an image by a first printing and a second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, and a host apparatus for supplying an image data to the printing apparatus, comprising:

patterns-forming means for controlling a printing head to form a plurality of patterns respectively having optical characteristics corresponding to the plurality of shifting amounts, the plurality of patterns being respectively formed corresponding to the plurality of shifting amounts of relative printing positions of the first printing and the second printing, the patterns being formed by the first printing and the second printing;

measuring means for measuring-respective optical characteristics of the related plurality of patterns formed; and

means for calibrating an optical sensor being used in the related measurement; and

acquiring means for obtaining an adjustment value of dot forming position condition between the first printing and the second printing on the basis of respective optical characteristics of the plurality of patterns measured.

In a seventh aspect of the present invention, there is provided a storage medium which is connected to an information processing apparatus and a program stored in which is readable by the information processing apparatus, the program being for making a printing system to perform a method for processing for performing printing registration in a first printing and a second printing with respect to a printing apparatus for performing printing of an image by the first printing and the second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, the method comprising the steps of:

pattern-forming for controlling the printing head to form a plurality of patterns respectively having optical characteristics corresponding to a plurality of shifting amounts, the plurality of patterns being respectively formed corresponding to the plurality of shifting amounts of relative printing positions of the first printing and the second printing, the patterns being formed by the first printing and the second printing;

measuring respective optical characteristics of the plurality of patterns formed;

calibrating an optical sensor being used in order to perform the measurement; and

acquiring an adjustment value of a dot forming position condition between the first printing and the second printing on the basis of respective optical characteristics of the plurality of patterns measured.

Optical characteristics (characteristics of changes in density) with respect to the dot formative positions condition is changed based on the relation of pixel density and a dot diameter, depending upon a formation positions of the dot greatly, whereby from the characteristics the relative dot-formation position can be obtained.

The condition that the dots which are adjacent are in contact with each other is largest in planar dimension, as it approaches from a connecting condition, the planer dimension is decreased in accordance with a change of the formation position. In other words, the density is changed in accordance with the formation position. Moreover, from the relation of the pixel density and a dot diameter, in order to make the area factor to 100%, the dot has a diameter of size of $\sqrt{2}$ times of one pixel, and under the condition that the formation position is registered the overlapped parts exist inescapably in the dots which are adjoined each other, and at that condition, the density becomes maximum. In contrast with this, the formation position is deviated, whereby when the condition that the area factor does not become 100%, that is, the condition which a clearance can be formed is achieved, the density is decreased.

Therefore, the condition that the formation position are registered is the region where the density is changed greatly in the formation position of the dot. When by varying the position registration condition of the formation position of the dot (for example, by making the condition reverse) with respect to the dot as the reference the density is made change, the change in density becomes the similar

characteristics, and accordingly, the characteristics of the change in density have been reversed by directiveness of the adjusting direction simply. using this characteristics, the intersection of the characteristics of two kind changes in density can be determined as the adjusting position where the depositing position of the dot have just registered.

This adjustment method is adapted to the strict adjustment of the depositing position, and a dot alignment (a printing registration) with high accuracy can be realized, since the slight offset of the formation position appears sensitively on the change in density.

Moreover, the adjusting accuracy further can be improved by performing calibration for the optical sensor which is used in such adjustment.

Incidentally, hereafter, the word "print" (hereinafter, referred to as "record" also) represents not only forming of significant information, such as characters, graphic image or the like but also represent to form image, patterns and the like on the printing medium irrespective whether it is significant or not and whether the formed image elicited to be visually perceptible or not, in broad sense, and further includes the case where the medium is processed.

Here, the wording "printing medium" represents not only paper to typically used in the printing apparatus but also cloth, plastic film, metal plate and the like and any substance which can accept the ink in broad sense.

Furthermore, the wording "ink" has to be understood in broad sense similarly to the definition of "print" and should include any liquid to be used for formation of image patterns and the like or for processing of the printing medium.

The above and other objects, effects, features and advantages of the present invention will become more apparent from the following description of embodiments thereof taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A to 1C are illustrations for describing a principle of a dot matrix printing;

FIGS. 2A to 2C are illustrations for describing a generation of an unevenness in density which can be occurred in the dot matrix printing;

FIGS. 3A to 3C are illustrations for describing a principle of a multi scanning printing for preventing from generating the unevenness in density described in FIG. 2A to 2C;

FIGS. 4A to 4C are illustrations for describing a checker or lattice arrangement printing and a inverted checker or lattice arrangement printing used in the multi scanning printing;

FIG. 5 is a perspective view showing a schematic constitution example of an ink jet printing apparatus according to one embodiment of the invention;

FIGS. 6A and 6B are perspective views showing a constitution example of a head cartridge shown in FIG. 5 and a constitution example of an ejection portion thereof respectively;

FIG. 7 is a plane view showing a constitution example of a heater board being used in the ejection portion shown in FIG. 6B;

FIG. 8 is a schematic view describing an optical sensor being used in the apparatus shown FIG. 5;

FIG. 9 is a block diagram showing a schematic constitution of a control circuit in the ink jet printing apparatus according to one embodiment of the invention;

FIG. 10 is a block diagram showing an electric constitution example of a gate array and the heater board shown in FIG. 9;

FIG. 11 is a schematic view for describing a stream of printing data in the inside of the printing apparatus from a host apparatus;

FIG. 12 is a block diagram showing a constitution example of a data transmission circuit;

FIGS. 13A to 13C are schematic views respectively illustrating printing patterns for use in the first embodiment according to the present invention, wherein FIG. 13A illustrates dots in the case where the printing positions are well registered; FIG. 13B, where the printing positions are registered with a slight offset; and FIG. 13C, where the printing positions are registered with a greater offset;

FIGS. 14A to 14C are schematic views respectively illustrating patterns for printing registration for use in the first embodiment according to the present invention, wherein FIG. 14A illustrates dots in the case where the printing positions are well registered; FIG. 14B, where the printing positions are registered with a slight offset; and FIG. 14C, where the printing positions are registered with a greater offset;

FIG. 15 is a graph illustrating the relationship between a printing position offset amount and a reflection optical density in the printing patterns in the first embodiment according to the present invention;

FIG. 16 is a flowchart illustrating schematic processing in the first embodiment according to the present invention;

FIG. 17 is a schematic view illustrating the state in which the printing pattern is printed on a printing medium in the first embodiment according to the present invention;

FIG. 18 is a graph illustrating a method for determining a printing registration condition in the first embodiment according to the present invention;

FIG. 19 a graph illustrating the relationship between measured optical reflection indexes and printing position parameters;

FIGS. 20A to 20C are schematic views respectively illustrating other printing patterns in the first embodiment according to the present invention, wherein FIG. 20A illustrates dots in the case where the printing positions are well registered; FIG. 20B, where the printing positions are registered with a slight offset; and FIG. 20C, where the printing positions are registered with a greater offset;

FIGS. 21A to 21C are schematic views respectively illustrating further printing patterns in the first embodiment according to the present invention, wherein FIG. 21A illustrates dots in the case where the printing positions are well registered; FIG. 21B, where the printing positions are registered with a slight offset; and FIG. 21C, where the printing positions are registered with a greater offset;

FIGS. 22A to 22C are schematic views respectively illustrating still further printing patterns in the first embodiment according to the present invention, wherein FIG. 22A illustrates dots in the case where the printing positions are well registered; FIG. 22B, where the printing positions are registered with a slight offset; and FIG. 22C, where the printing positions are registered with a greater offset;

FIGS. 23A to 23C are schematic views respectively illustrating still further printing patterns in the first embodiment according to the present invention, wherein FIG. 23A illustrates dots in the case where the printing positions are well registered; FIG. 23B, where the printing positions are registered with a slight offset; and FIG. 23C, where the printing positions are registered with a greater offset;

FIG. 24 is a flowchart illustrating printing registration condition judgment processing in a second embodiment according to the present invention;

FIGS. 25A to 25C are schematic views illustrating characteristics depending upon a distance between dots of the printing pattern in the second embodiment according to the present invention, wherein FIG. 25A illustrates dots in the case where the printing positions are well registered; FIG. 25B, where the printing positions are registered with a slight offset; and FIG. 25C, where the printing positions are registered with a greater offset;

FIGS. 26A to 26C are schematic views illustrating characteristics depending upon a distance between dots of the printing pattern in the second embodiment according to the present invention, wherein FIG. 26A illustrates dots in the case where the printing positions are well registered; FIG. 26B, where the printing positions are registered with a slight offset; and FIG. 26C, where the printing positions are registered with a greater offset;

FIG. 27 is a graph illustrating the relationship between a printing position offset amount and a reflection optical density according to the distance between the dots of the printing pattern in the second embodiment according to the present invention;

FIGS. 28A to 28C are schematic views respectively illustrating printing patterns in a third embodiment according to the present invention, wherein FIG. 28A illustrates dots in the case where the printing positions are well registered; FIG. 28B, where the printing positions are registered with a slight offset; and FIG. 28C, where the printing positions are registered with a greater offset;

FIG. 29 is a graph illustrating the relationship between a printing ejection opening offset amount and a reflection optical density in the third embodiment according to the present invention;

FIG. 30 is a flowchart showing one example of an entire algorithm of an automatic dot alignment processing capable of using in the invention;

FIG. 31 is a diagram showing a characteristic of a reflection factor in the case of varying an ink ejection ratio for the predetermined region;

FIG. 32 is a diagram showing results of densities of measurement objects whose reflection factors are different from each other, while varying electric signals of a light-emitting portion of the optical sensor being used in the embodiment;

FIG. 33 is a diagram showing an ideal sensitivity characteristics of the optical sensor;

FIG. 34 is a diagram for illustrating one example of a sensor calibration processing capable of using in the algorithm shown in FIG. 30;

FIG. 35 is a diagram for illustrating an another example of a sensor calibration processing capable of using in the algorithm shown in FIG. 30;

FIG. 36 is a diagram for illustrating a further example of a sensor calibration processing capable of using in the algorithm shown in FIG. 30;

FIGS. 37A to 37E are schematic views for describing an example of a coarse adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIG. 38 is a diagram for describing a manner obtaining adjustment values by the coarse adjustment shown in FIGS. 37A to 37E;

FIGS. 39A to 39E are schematic views for describing an example of a fine adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIGS. 40A to 40C are schematic views as a prerequisite for describing another example of the fine adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIG. 41 is a diagram for describing a characteristics of a printing patterns according to the other example of the fine adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIGS. 42A to 42D are schematic views showing the printing patterns of the other example of the fine adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIGS. 43A to 43D are schematic views showing an inverted patterns to FIGS. 42A to 42D, which are the printing patterns of the other example of the fine adjustment processing of printing registration for bi-directional printing capable of using in the algorithm shown in FIG. 30;

FIG. 44 is a diagram for describing selection of an ink forming the printing patterns being used in a printing registration processing;

FIG. 45 is a flowchart showing another example of an entire algorithm of an automatic dot alignment processing capable of using in the invention;

FIG. 46 is a schematic view showing a constitution example of a print head capable of using for obtaining a different ejection amount;

FIG. 47 is a schematic view describing a offset in an ink depositing position responsive to a horizontal scanning speed and an ink ejecting speed;

FIG. 48 is an illustration for describing a dot alignment processing in response to modes which the printing apparatus has;

FIG. 49 is a diagram showing the relationship of FIGS. 49A and 49B;

FIG. 49A is an illustration showing one example of the printing patterns being formed or used in the dot alignment processing;

FIG. 49B is an illustration showing one example of the printing patterns being formed or used in the dot alignment processing;

FIGS. 50A and 50B are illustrations describing the coarse adjustment and the fine adjustment of the dot alignment-processing by manual operation respectively; and

FIGS. 51A and 51B are illustrations describing the coarse adjustment and the fine adjustment of the automatic dot alignment respectively.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, this invention is described in detail with reference to drawings. Moreover, hereafter, the case where the invention is applied to an ink jet printing apparatus and a printing system using this is described mainly.

1. Summary of Embodiments

(1.1) Summary of a Dot Alignment

In an adjustment method (printing registration) of a dot formation position (an ink-depositing position) and a printing apparatus according to embodiments of the invention, a forward printing and a reverse printing (equivalent to a first and a second printing respectively) in a bi-directional printing which an adjustment of the dot formation position should be performed mutually, or respective printing (a first

printing and a second printing) by a plurality of print heads (e.g. two heads) are on the substantial same position on a printing medium. In addition, printing is performed thereon, varying registration conditions of the relative dot formation position, under a plurality of conditions upon the first printing and the second printing. Namely, varying the relative position condition of the first and the second printing, a pattern including a plurality of patches described below is formed.

Moreover, those density are read using an optical sensor mounted on a horizontal or main scanning member such as a carriage. Namely, the optical sensor on the carriage is moved to the respective position corresponding to the respective patch and a reflected optical density (or an intensity of the reflected light and a reflection factor) is measured successively. Moreover, the condition which the positions of the first and the second printing exceedingly are registered is judged from relative relation of those values. Namely, from the relative relationship between the depositing position condition and the density, an approximation ability of the density for the depositing position condition is calculated. The optimal depositing position condition is determined from the approximation ability. The image pattern which is printed at this time is established in consideration-of the accuracy which the printing apparatus and the print head have.

Concerning the first printing, the pattern elements having a width substantially equal to or more than the maximum offset amount of the accuracy of the depositing position which is predicted with reference to the accuracy may be printed on the printing medium. Concerning the second printing, the pattern elements of the same width is printed under the registration conditions of the respective depositing position. The depositing position condition can be adjusted with the equivalent to the accuracy of the position registration condition of the depositing position or the accuracy above that, according to this manner.

A further first printing and a further second printing are performed using the depositing position condition which is established once, varying the registration condition of the depositing position, under a plurality of conditions in the same manner. The registration condition in this case is set at the higher accuracy than the preceding registration. Namely, based on the result by the first dot alignment, based on the result which registration is performed, said accuracy which is registered is considered to be the largest offset, and from the accuracy which is registered, the patterns having the width equivalent to the maximum offset amount of accuracy of the predicted depositing position are printed by the first printing and the second printing. A dot alignment (a fine adjustment) of higher accuracy has allowed according to this manner.

(1.2) Summary of Entire Algorithm

After performing calibration of the optical sensor, the coarse adjustment is performed. The adjustment ranges of the coarse adjustment is determined from the accuracy of the printing apparatus and the print head. Using the registration condition of the depositing position determined by the coarse adjustment, further the fine adjustment is performed and the dot alignment is carried out with higher accuracy. Therefore, an adjustment pitch can be set more precisely because the adjustment range made narrow. In addition, after performing the adjustment, in order to check whether the dot alignment was performed accurately or not, a check pattern is printed, thus, whether the depositing position is controlled accurately can be checked by the user.

Moreover, an execution range of the dot alignment can be defined as required corresponding to the printing modes, the

construction or the like of which the apparatus. For example, in the printing apparatus using a plurality of print heads, the dot alignments between bi-directional printing and between printing by the plurality of heads are carried out, and in the printing apparatus using only one head, the dot alignment of bi-directional printing have only to be carried out. Moreover, even in the case of one head, when it is possible to eject the ink of a different color tone (a color and/or a density) or when the different amount of ejection can be obtained, for every each color tone or each amount of ejection, the dot alignment may be carried out.

In addition, as is described below, the coarse adjustment and a fine adjustment may not be necessarily performed in above-mentioned order.

(1.3) Identification Patterns

The check patterns are printed using the depositing position set, after performing the dot alignment, in order to check whether the control was performed certainly or not, or such as the result of the dot alignment can identified by the user. Corresponding the respective mode of bi-directional printing and printing using a plurality of heads, and every each printing speed, the ruled line is printed, since the ruled line patterns is easy to be identified. According to this manner, the user can identify the result of the dot alignment which was carried out obviously.

(1.4) Optical Sensor

The optical sensor being used in the embodiment, the sensor which emits light of color which was selected appropriately in response to the color tone of being used in the printing apparatus and the constitution of the head can be used. In other words, printing means corresponding to said colored ink is applied to objects of the dot alignment with respect to light emitted from red LED or infrared ray LED by using the color excellent in absorption characteristics of the light, for example. Black (Bk) or cyan (C) is preferable from the viewpoint of the absorption characteristics, while it is to difficult to obtain sufficient density characteristics and S/N ratio when magenta (M) or yellow (Y) is used. Thus, the color to be used responsive to the characteristics of LED used is selected, thereby to be able to correspond to each color. For example, a blue LED, a green LED or the like in addition to the dot alignment the red LED are installed, thereby with the dot alignment for every each color (C, M, Y) with respect to Black (Bk) can be performed.

(1.5) Manual Adjustment

In the embodiment, the automatic dot alignment processing is designed to perform after performing detection of density using the optical sensor. However, another dot alignment processing also is made possible in preparation for the case or the like where the optical sensor does not operate desirably. Namely, in this case, a usual manual adjustment is performed. The condition which shifts to such manual adjustment is described.

First, it is defined as a calibration error and the dot alignment operation is stopped, when the data obtained by performing of the optical sensor calibration is beyond the range clearly. The status of this condition is communicated to the host computer to display that it is an error through an application. In addition, it is displayed that the manual adjustment is to be carried out to demand the execution. In the other case, when the calibration error were detected, the dot alignment operation is stopped and it may be printed to demand the execution of the manual adjustment on the printing medium fed.

Secondly, a disturbance is described.

The optical sensor can be failed to function, depending upon an incidence of light from the outside. Therefore,

during the dot alignment, when the reflected light becomes extremely strong, it is judged to be that there is a disturbance light and to stop the dot alignment. Moreover, in the same way as the calibration error, the status of the condition is communicated to the host computer to display that it is an error through an application. In addition, It is displayed that the manual adjustment is to be carried out to demand the execution. In the other case, when the calibration error were detected, the dot alignment operation is stopped and it may be printed to demand the execution of the manual adjustment on the printing medium which the paper fed.

However, when the sensor error is temporary as an incidence of the accidental disturbance light, after a certain time interval or after informing to prepare the conditions to the user, the dot alignment processing also is made to be able to start again. Moreover, when an error is caused during the execution of one of various printing registration processing corresponding to the modes described later and other processing, the registration processing is stopped and to perform also another printing registration processing.

(1.6) Recovery Operation

The recovery operation being used in the embodiment is described.

This is designed to make to certainly perform a series of recovery operations such as suction, wiping, preliminary ejection for making the ink ejecting condition of the print head good or to maintain it good, before the automatic dot alignment is carried out.

As the operation timing, the recovery operation is certainly performed before it is carried out when an executive instruction of the automatic dot alignment is generated. According to this operation, under the stabilized ejection condition of the print head, the patterns for the printing registration can be printed, thereby to be able to set corrective conditions for printing registration with higher reliability.

As the recovery operations are not limited to only a series of operations such as suction, wiping, preliminary ejection, but with only preliminary ejection or preliminary ejection and wiping the operation may be performed. The preliminary ejection of this case is set preferably such that the ejection of more frequency than a frequency at the time of a preliminary ejection for printing are performed. Moreover, a frequency and an operation order of such as suction, wiping, preliminary ejection are not especially limited.

Moreover, in response to an elapsed time from preceding suction recovery, whether an execution of suction recovery prior to the automatic dot alignment control is required or not may be judged. In this case, first, immediately before the automatic the dot alignment is performed, it is judged whether the predetermined time has elapsed from the preceding suction. And when the suction operation has been carried out within the predetermined time, the automatic dot alignment is carried out. On the other hand, when the suction operation has not been carried out within the predetermined time, after a series of the recovery operations including the suction recovery has been carried out, the automatic dot alignment can be performed.

Moreover, it may be designed to be judged whether the print head has been performed ink ejection over the predetermined number of times from preceding suction recovery, and when ink ejection over the predetermined number of times has been performed, after the recovery operation is carried out, the automatic dot alignment may be carried out, and in addition, both the elapsed time and the number of ink ejection are turned into judgment and, such that when either has reached the predetermined value, the suction recovery is performed, it may be combined therewith.

According to this manner, carrying out the suction recovery to excessive can be prevented, thereby to be able to contribute in savings of the consumption of the ink and a reduction of the amount of ink discharge to a waste ink-treatment section, as well as the recovery operation prior to the automatic dot alignment can be performed effectively.

Moreover, recovery conditions may be changed in such a manner that the recovery conditions are made variable in response to an elapsed time or the number of ink ejection from preceding suction recovery and when, for example, the-elapsed time is brief, the suction operation is held under a disable condition, and only the preliminary ejection and wiping are performed, and when the elapsed time is long, the suction recovery further is interposed.

2. Constitution Example of a Printing Apparatus

(2.1) Mechanical Constitution

FIG. 5 is a perspective view showing a constitution example of a color ink jet printing apparatus which the invention is preferably embodied or to which is preferably applied and in the drawing, a condition that, detaching the front cover, an inside of an apparatus is exposed is shown.

In the drawing, a reference numeral **1000** denotes an exchangeable type head cartridge and a reference numeral **2** denotes a carriage unit retaining the head cartridge detachably. A reference numeral **3** denotes a holder for fixing the head cartridge **1000** on the carriage unit **2**, and after the head cartridge **1000** is installed within the carriage unit **2**, when the carriage fixing lever **4** is operated, linking to this operation, and the head cartridge **1000** is pressed on and contacted with the carriage unit **2**. Moreover, when the head cartridge **1000** is located by the pressing and contacting, electric contacts for the required signal transmission, which are provided on the carriage unit **2**, are in contact with electric contacts on the side of the head cartridge **1**. A reference numeral **5** denotes a flexible cable for transferring electric signals to the carriage unit **2**. Moreover, a reflective type optical sensor **30** (not shown in FIG. 5) is provided on the carriage.

A reference numeral **6** denotes a carriage motor as a driving source for allowing the carriage unit **2** to travel in the direction of the horizontal scanning reciprocally, and a reference numeral **17** denotes a carriage belt transferring the driving force to the carriage unit **2**.

A reference numeral **8'** denotes a guide shaft guiding the movement, as well as there exists in a manner to extending in the direction of the horizontal scanning to support the carriage unit **2**. A reference numeral **9** denotes a transparent-type photo coupler attached to the carriage unit **2**, and a reference numeral **10** denotes a light-shield board provided on the vicinity of the carriage home position, and when the carriage unit **2** reaches the home position, a light axis of the photo coupler **9** is shielded by the light-shield board **10**, thereby the carriage home position being detected. A reference numeral **12** denotes a home position unit including a recovery system such as a cap member for capping a front face of the ink-jet head and suction means for sucking from the inside of this cap and further a member for performing wiping of the front face of the head.

A reference numeral **13** denotes a discharge roller for discharging the printing medium, and sandwiches the printing medium, cooperating with a spur-shaped roller (not shown) to discharge this out of the printing apparatus. A reference numeral **14** denotes line feed unit and to carry the printing medium in the direction of the vertical scanning by the predetermined amount.

FIGS. 6A is perspective view showing a detail of a head cartridge **1000** shown in FIG. 5. Here, a reference numeral

15 denotes an ink tank accommodating black ink, and a reference numeral **16** denotes the ink tank accommodating a cyan, a magenta and a yellow ink. These tanks are designed to being able attach and detach to the head cartridge body. Each of portions denoted a reference numeral **17** is a coupling port for an each of ink supply pipes **20** on the side of the head cartridge accommodating each color inks, and similarly, a reference numeral **18** is a coupling port for the black ink accommodated in the ink tank **15**, and by said coupling, the ink can be supplied to the print head **1** which is retained in the head cartridge body. A reference numeral **19** denotes an electric contact section, and accompanying with contact with an electric contact section provided on the carriage unit **2**, through a flexible cable electric signals from the body of the printing apparatus control section can be received.

In this embodiment, a head which both a black ink ejecting portion arranging nozzles for ejecting the black ink and a color ink ejecting portion are arranged in parallel is used. The color ink ejecting portion comprises a nozzle groups respectively ejecting yellow ink, magenta and cyan arranged unitarily and in line in response to a range of a black ejection opening arrangement.

FIG. **6B** is a schematic perspective-view partially showing a structure of a main portion of the print head portion **1** of the head cartridge **1000**.

A plurality of ejection openings **22** are formed with the predetermined pitches on the ejection opening face **21** faced with the printing medium **8** spaced the predetermined clearance (for example, approximately 0.5 to 2.0 mm) in FIG. **6B**, and along a wall surface of each liquid passages **24** communicating a common liquid chamber **23** with each ejection opening **22**, the electrothermal converting elements (exothermic resistant element and so on) **25** for generating the energy used for ejecting ink ejection are arranged. In this embodiment, the head cartridge **1000** is installed on the carriage **2** under the positional relationship so that the ejection openings **22** stand in a line in the direction which crosses a scanning direction of the carriage unit **2**. Thus, the print head **1** is constituted in that the corresponding exothermic resistant elements (hereinafter referred to as an ejecting heater) **25** are driven (energized) based on the image signal or ejection signals and to film-boil ink within the liquid passages **24** and to eject the ink from the ejection openings **22** by pressure of the bubbles which are generated by film-boiling.

In this embodiment, although the constitution was mentioned wherein within one print head body, a nozzle group for ejecting the black ink, and nozzle groups for ejecting yellow, magenta, cyan ink are provided and arranged, the invention can not be limited to this manner and the print head having the nozzle group for ejecting the black ink may be provided independent from the print head having the nozzle groups for ejecting the yellow, magenta, cyan ink, and still more, the head cartridges themselves may be independent from each other. Moreover, respective head cartridge may be provided by the nozzle groups of each color which are independent each other. The combination of the print head and the head cartridge is not especially limited.

FIG. **7** is a schematic view of a heater board HB being used in this embodiment. Temperature regulating heaters or sub heaters **80d** for controlling temperature of the head, an ejection section row **80g** in which ink ejecting heaters or main heaters **80c** are arranged and a driving device **80h** are formed on the same board under a positional relationship as shown in this drawing. The heater board is usually a chip of

Si wafer and in addition, by an identical semiconductor deposition process each heater and the driving section required are formed thereon.

Moreover, on the same drawing, especially, a positional relationship of an outside circumference wall section **80f** of a ceiling board for separating a region which the heater board of ejection portion for the black ink is filled with the black ink from a region which is not so. The side of ejecting heaters **80g** of the outside circumference wall section **80f** of the ceiling board functions as the common liquid chamber. Moreover, by a plurality of grooves formed on the outside circumference wall section **80f** corresponding to the ejection section row **80g**, a plurality of liquid passages are formed. Although the color ink ejection sections of yellow, magenta and cyan are constituted in the approximately similar manner, for each ink, by forming the liquid passages for supplying and the ceiling board appropriately, separation or compartmentalization is performed such that different color inks are not mixed each other.

FIG. **8** is a schematic view describing a reflection type optical sensor being used in the apparatus shown in FIG. **5**.

The reflection type optical sensor **30** is mounted on the carriage **2** as described above, and comprises a light-emitting portion **31** and a photosensing portion **32** as shown in FIG. **8**. A light I_{in} **35** which is emitted from the light-emitting portion **31** is reflected on the printing medium **8**, and the reflected light I_{ref} **37** can be detected by the photosensing portion **32**. Moreover, the detected signal is transferred to a control circuit formed on an electric board of the printing apparatus through a flexible cable (not shown), and is converted into a digital signal by the A/D converter. The position which the reflective optical sensor **30** is attached to the carriage **2** is set at the position where the ejection opening section of the print head **1** does not pass in order to prevent splashed droplets of ink or the like from depositing, during printing scanning. This sensor **30** can be constituted a sensor of the low cost because of to be able to use a sensor of relatively low resolution.

(2.2) Constitution of Control System

Secondly, a constitution of a control system for carrying out printing control of the described-above apparatus is described.

FIG. **9** is a block diagram showing one example of the constitution of the control system. In this drawing, a controller **100** is a main control section and, for example, comprises MPU **101** of a microcomputer form, ROM **103** in which a program, a table required and the other fixed data are stored, nonvolatile memory **107** such as EEPROM for storing data adjustment data (may be data obtained every each mode described below) which are obtained by a dot alignment processing described below and are used in printing registration at the time of practical printing, a dynamic RAM in which various data (the described-above printing signal and printing data being supplied to the head or the like), and so on. The number of the print dots and the number of exchange of a print head also can be stored in this RAM **105**. A reference numeral **104** denotes a gate array which performs supplying control of printing data to the print head **1**, and transmission control of data between interface **112**, MPU **101** and RAM **1106** and is also performed. A host apparatus **110** is a source of supply of the image data (a computer performing preparation of data and processing for printing is used, as well as the apparatus may be a form of a reader unit or the like for reading the image also). The image data, the other commands, a status signal or the like are transmitted to controller **100** and are received from controller **100** through the interface (I/F) **112**.

A console **820** has a switch group which receives indicative input by an operator, and comprises a power supply switch **122**, switch **124** for indicating commencement of printing, a recovery switch **126** for indicating starting of the suction recovery, a registration adjustment starting switch **127** for starting registration and an adjustment value set entering section **129** for entering said adjustment value by a manual operation.

A reference numeral **130** denotes a sensor group for detecting conditions of the apparatus, and comprises the above-mentioned reflective optical sensor **30**, the photo coupler **132** for detecting the home position and a temperature sensor **134** provided on the appropriate region in order to detect an environment temperature or the like.

A head driver **150** is a driver for driving the ejection heaters **25** of the print head in response to printing data or the like, and comprises a timing setting section or the like for setting driving timing (ejection timing) appropriately for the dot-formation registration. A reference numeral **151** denotes a driver for driving a horizontal scanning motor **4**, and a reference numeral **162** denotes a motor being used to carry (vertical scanning) the printing medium **8**, and a reference numeral **160** denotes a driver thereof.

FIG. **10** is one example of a circuit diagram showing a detail of each part **104**, **150** and **1** of FIG. **9**. A gate array **104** comprises a data latch **141**, a segment (SEG) shift register **142**, a multiplexer (MPX) **143**, a common (COM) timing generating circuit **144** and a decoder **145**. The print head **1** has a diode matrix, and driving currents flow to ejection heaters (H1 to H64) at the time where a segment signal SEG coincides with a common signal COM, thereby the ink is heated to eject the ink.

The decoder **145** decodes a timing generated by common timing generation circuit **144** to select any one of common signals COM **1** to COM **8**. The data latch **141** latches the printing data read from RAM **105** every 8 bit, and a multiplexer **143** outputs the printing data in accordance with a segment shift register **142** as segment signals SEG **1** to SEG **8**. The output from the multiplexer **143** can be changed every one bit, 2 bits or 8 bits all or the like according to contents of shift register **142** variously as described below.

Describing an operation of a configuration for controlling described below, when the printing signals enter the interface **112**, the printing signals are converted into the printing data for printing between the gate array **104** and MPU **101**. Moreover, the motor driver **151** and **160** are driven, as well as the print head is driven and printing is performed in accordance with the printing data sent to a head driver **150**. Namely, here, although the case which drives the printing head of 64 nozzles has been described, control can be performed under even using the number of other nozzle by the similar configuration.

Secondly, a stream of the printing data in the inside of the printing apparatus is described using FIG. **11**. The printing data sent from the host computer **110** are stored in the receiving buffer RB of the inside of the printing apparatus through an interface **112**. The receiving buffer RB has a capacity-of several kilobytes to tens of kilobytes. After a command analysis is performed with respect to the printing data stored in the receiving buffer RB, they are sent to a text buffer TB.

In a text buffer TB, printing data are maintained and as a intermediate form of one line, the processing which a printing position of each character, a kind of decoration, size, a character (code), an address of a font or the like are added is performed. A capacity of the text buffer TB differs depending upon the kind of the apparatus every each kind,

and comprises a capacity of several lines in the case of serial printer and a capacity of one page in the case of page printer. Furthermore, the printing data stored in the text buffer TB are developed and are stored in a printing buffer PB in the binary-coded condition, and the signals are sent to the print head as the printing data and printing is performed.

The signals are sent to the print head after the binary-coded data stored in the printing buffer PB are covered with a thinning mask patterns of a specific rate in this embodiment. Therefore, the mask patterns can be set after observing the data in the condition being stored in the printing buffer PB. There is also the apparatus of a kind that the printing data stored in the printing buffer PB are developed concurrent with a command analysis and to be written in the printing buffer PB without comprising the text buffer TB depending upon the kind of the printing apparatus.

FIG. **12** is a block diagram showing a constitution example of a data transmission circuit, and such circuit can be provided as a part of controller **100**. In this drawing, a reference numeral **171** denotes a data register for connecting with a memory data bus to read the printing data being stored in the printing buffer in memory and to store temporarily and a reference numeral **172** denotes a parallel-serial converter for converting the data stored in a data register **171** into a serial data, and a reference numeral **173** denotes an AND gate for covering the serial data with the mask, and a reference numeral **174** denotes a counter for controlling the number of data transmission.

A reference numeral **175** denotes a register which is connected with a MPU data bus and is for storing the mask patterns, and a reference numeral **176** denotes a selector for selecting a column position of the mask patterns, and a reference numeral **177** denotes a selector for selecting a row position of the mask patterns.

A data transmission circuit shown in FIG. **12** transfers serially the printing data of 128 bits to the print head **1** according to the printing signal being sent from MPU **101**. The printing data stored in the printing buffer PB in memory are stored temporarily in a data register **171**, and are converted into the serial data by a parallel-serial converter **172**. After the converted serial data are covered by an AND gate **103** with the mask, the data are transferred on the print head **1**. A transmission counter **174** counts the number of transmission bits to terminate the transmission when reaching 128 bits.

A mask register **175** is constituted by four pieces of the mask registers A, B, C and D to store a mask patterns written by the MPU. Each register stores the mask pattern of 4 bits row by 4 bits column. Moreover, a selector **176** selects the mask patterns data corresponding to the column position by providing the value of the column counter **181** as a selective signal. The transmission data is covered with the mask by the mask patterns data selected by the selector **176** and **177** using an AND gate **173**.

In this example, four mask registers are used however, the other number of mask registers may be used. Further, the transmission data may be stored in a print buffer once, instead of directly supplying to the printing head **1** as mentioned above.

3. Embodiment of Dot Alignment Printing Registration

Next, an embodiment of a printing registration which is basic to this embodiment is described.

(3.1) Printing Registration for Bi-directional Printing

FIGS. **13A** to **13C** schematically illustrate printing patterns for printing registration to be used in the present embodiment.

In FIGS. 13A to 13C, white dots 700 represent dots formed on the printing medium during the forward scan (first printing) and hatched dots 710 represent dots formed on the printing medium during the reverse scan (second printing). It should be noted that although in FIGS. 13A to 13C the dots are hatched or not for the purpose of illustration, the dots are formed with the ink ejected from the same printing head, irrespective of the color or density of the ink.

FIG. 13A shows the dots printed in the state in which printing positions in the forward scan and the reverse scan are well registered; FIG. 13B, the printing positions are registered with a slight offset; and FIG. 13C, the printing positions are registered with a greater offset. As is obvious from the FIGS. 13A to 13C, in the present embodiment, the dots are complementarily formed in the forward and reverse scan. Namely, the dots in the odd number of columns are formed in the forward scan, and the dots in the even number of columns are formed in the reverse scan. Accordingly, FIG. 13A, in which the dots formed in the forward scan and the reverse scan are separated by about the diameter of the dot, shows the well registered state.

The printing pattern is designed to reduce the density of the overall printed portion as the printing position is offset. Namely, within a range of a patch as the printing pattern of FIG. 13A, the area factor is about 100%. As the printing positions are offset as shown in FIGS. 13B and 13C, the overlapping amount of the dot (white dot) of the forward scan and the dot (hatched dot) of the reverse scan becomes greater to enlarge the not-printed region, i.e., a region not formed with the dots, thereby decreasing the area factor so as to reduce the density on average.

In the present embodiment, the printing positions are offset by shifting the timing of printing. It is possible to offset on printing data.

In FIGS. 13A to 13C, although one dot in the scanning direction is taken as a unit, a unit may be appropriately set according to precision of printing registration or precision of printing registration detection.

FIGS. 14A to 14C show the case where four dots are taken as a unit. FIG. 14A shows the dots printed in the state in which printing positions in the forward scan and the reverse scan are well registered; FIG. 14B, the printing positions are registered with a slight offset; and FIG. 14C, the printing positions are registered with a greater offset.

What is intended by this pattern is that the area factor is reduced with respect to an increase in mutual offset of the printing positions in the forward scan and the reverse scan. This is because the density of the printed portion is significantly dependent on variations of the area factor. Namely, although the dots are overlapped with each other so as to increase the density, an increase in not-printed region has a greater influence on the average density of the overall printed portion.

FIG. 15 is a graph schematically illustrating the relationship between an offset amount of the printing position and a reflection optical density in the printing patterns shown in FIGS. 13A to 13C and 14A to 14C in the present embodiment.

In FIG. 15, the vertical line represents a reflection optical density (OD value); and the horizontal line, a printing position offset amount (μm). Using the incident light I_{in} 35 and the reflection light I_{ref} 37 shown in FIG. 4, a reflection index $R=I_{ref}/I_{in}$ and a transmission index $T=1-R$. Incidentally, although an optical density may be defined as the reflection optical density using the reflection index R or a transmission optical density using a transmission index T ,

the former is used in the present embodiment and is referred as "the optical density" or "density" simply, if there is no problem.

Assuming that d represents a reflection optical density, $R=10^{-d}$. When the amount of printing position offset is zero, the area factor becomes 100%, and therefore, the reflection index R becomes minimum, i.e., the reflection optical density d becomes maximum. The reflection optical density d decreases as the printing position offsets relatively to any of the plus and minus directions.

(Printing Registration Processing)

FIG. 16 is a flowchart of printing registration processing.

Referring to FIG. 16, first of all, the printing patterns are printed (step S1). Next, the optical characteristics of the printing patterns are measured by the optical sensor 30 (step S2). An appropriate printing registration condition is determined based on the optical characteristics obtained from the measured data (step S3). As graphically shown in FIG. 18 (described later), the point of the highest reflection optical density is found, two straight lines respectively extending through both sides of data of the point of the highest reflection optical density are found by the method of least squares, and then, the intersection point P of these lines is found. Like the above approximation using straight lines, approximation using a curved line as shown in FIG. 19 (described later) may be used. Variations of drive timing are set based on the printing position parameter with respect to the point P (step S4).

FIG. 17 is an illustration showing the state in which the printing patterns shown in FIGS. 13A to 13C or FIGS. 14A to 14C are printed on the printing medium 8. In the present embodiment, nine patterns 61 to 69 different in relative position offset amount between the dots printed in the forward scan and the reverse scan are printed. Each of the printed patterns is also called a patch, for example, a patch 61, a patch 62 and so on. Printing position parameters corresponding to the patches 61 to 69 are designated by (a) to (i). The nine patterns 61 to 69 may be formed by fixing the printing start timing in the forward scan and setting the nine printing start timings in the reverse scan, i.e., a currently set timing, four timings earlier than the currently set timing and four timings later than the currently set timing. The processing as shown in FIG. 16 and printing of the nine patterns 61 to 69 on the basis of the processing can be applied as a part of processing in general algorithm described later.

Then, the printing medium 8 and the carriage 2 are moved such that the optical sensor 30 mounted on the carriage 2 may be placed at positions corresponding to the patches 61-69 as the printed patterns thus printed. In the state in which the carriage 2 is stopped, the optical characteristics are measured one or more times. In this embodiment, a reflection optical density or a transmission optical density is used as an optical density. In spite of this, an optical reflection index, an intensity of reflected light or the like may be used.

In this way, since the optical characteristics are measured in the state in which the carriage 2 is stopped, the influence of noise caused by the driving of the carriage 2 can be avoided. A distance between the sensor 30 and the printing medium 8 is increased to widen a measurement spot of the optical sensor 30 more than the dot diameter, thereby averaging variations in local optical characteristics (for example, the reflection optical density) on the printed pattern so as to achieve highly precise measurement of the reflection optical density of the patch 61 etc.

In order to relatively widen the measurement spot of the optical sensor 30, it is desired that a sensor having a resolution lower than a printing resolution of the pattern,

namely, a sensor having a measurement spot diameter greater than the dot diameter be used. Furthermore, from the viewpoint of determination of an average density, it is also possible to scan a plurality of points on the patch by means of a sensor having a relatively high resolution, i.e., a small measurement spot diameter and to take an average of the thus measured densities as the measured density.

In order to avoid any influence of fluctuations in measurement, it may be possible to measure the reflection optical density of the same patch a plurality of times and to take an average value of the measured densities as the measured density.

In order to avoid any influence of fluctuations in measurement due to the density variations on the patch, it may be possible to measure a plurality of points on the patch to average or perform other operations on them. Measurement can be achieved while the carriage 2 is moved for time saving. In this case, in order to avoid any fluctuation in measurement due to electric noise caused by the driving of the motor, it is strongly desired to increase the times of samplings and average or perform other operations.

FIG. 18 is a graph schematically illustrating an example of data of the measured reflection optical densities.

In FIG. 18, the vertical line represents a reflection optical density; and the horizontal line represents a parameter for varying the relative printing positions in the forward scan and the reverse scan. The parameter is adapted to advance or retard the printing start timing of the reverse scan with respect to the fixed printing start timing of the forward scan.

When measurement results shown in FIG. 18 is obtained in the present embodiment, the intersection point P of the two straight lines respectively extending through two points (the points respectively corresponding to printing position parameters (b), (c) and (e), (f) of FIG. 18) on both sides of the point where the reflection optical density is highest (the point corresponding to a printing position parameter (d) in FIG. 18) is taken as the printing position where the best printing registration is attained. In the present embodiment, the corresponding printing start timing of the reverse scan is set based on the printing position parameter corresponding to this point P. But, when strict printing registration is neither desired nor needed, the printing position parameter (d) may be used.

As graphically shown in FIG. 18, by this method, the printing registration condition can be selected at a pitch smaller or a resolution higher than those of the printing registration condition used for printing the printing pattern 61 etc.

In FIG. 18, the density is not varied significantly irrespective of the variations of the printing condition between the points where the density is high corresponding to printing position parameters (c), (d) and (e). To the contrary, between the points corresponding to printing position parameters (a), (b) and (c) or (f), (g), (h) and (i), the density is varied sensitively relative to the variations of the printing registration condition. When the characteristics of the density close to symmetry as in the present embodiment are exhibited, printing registration can be achieved with higher precision by determining the printing registration condition with the points indicating the variations of the density sensitive to the printing registration condition.

A method according to the present invention for determining the printing registration condition is not limited to the foregoing method. It may be intended that numerical calculation is performed with continuous values on the basis of a plurality of multi-value density data and information of the printing registration condition for use in the pattern

printing, and then, the printing registration condition is determined with precision higher than a discrete value of the printing registration condition for use in the pattern printing.

For example, as an example other than linear approximation shown in FIG. 18, a polynomial approximate expression in which the method of least squares with respect to a plurality of printing registration conditions is obtained by using the density data for printing. The condition for attaining the best printing registration may be determined by using the obtained expression. It is possible to use not only the polynomial approximation but also spline interpolation.

Even when a final printing registration condition is selected from the plurality of printing registration conditions used for the pattern printing, printing registration can be established with higher precision with respect to fluctuations of various data by determining the printing registration condition through numerical calculation using the above-described plurality of multi-value data. For example, in a method for selecting the point of the highest density from the data of FIG. 18, it is possible that the density at the point corresponding to the printing position parameter (d) is higher than that of the point corresponding to the printing position parameter (e) due to the fluctuations. Therefore, in a method for obtaining an approximate line from three points on each of both sides of the highest density point to calculate an intersection point, the influence of fluctuation can be reduced by performing calculation using data of more than two points.

Next, another method for determining printing registration condition shown in FIG. 18 is explained.

FIG. 19 shows an example of data of measured optical reflection indexes.

In FIG. 19, the vertical line represents an optical reflection index; and the horizontal line, printing position parameters (a) to (i) for varying the relative printing positions in the forward scan and the reverse scan. For example, a printing timing of reverse scan is advanced or retarded to vary a printing position. In the example, a representative point on each patch is determined from the measured data, and the overall approximate curve is obtained from the representative point and a minimum point of the curve is determined as a matched point of the printing position.

Although the square or rectangular patterns (patches) are printed with respect to the plurality of printing registration conditions as shown in FIG. 17 in the present embodiment, the present invention is not limited to the construction. It is sufficient that there is only an area where the density can be measured with respect to the printing registration conditions. For example, all of the plurality of printing patterns (patches 61 etc.) in FIG. 17 may be connected to each other. With such pattern, an area of the printing pattern can be made smaller.

However, in the case where such pattern is printed on the printing medium 8 by the ink-jet printing apparatus, the printing medium 8 is expanded and a cocking is caused depending upon the kind of printing medium 8 if the ink is ejected to an area in excess of a predetermined quantity, to possibly deteriorate the precision of deposition of the ink droplets ejected from the printing head. The printing pattern used as shown in FIG. 17 in the present embodiment has the merit of avoiding such phenomenon as much as possible.

In the printing patterns in the present embodiment shown in FIGS. 13A to 13C, a condition where the reflection optical density varies most sensitively relative to the offset of the printing position is that the printing positions in the forward scan and the reverse scan are registered (the condition shown in FIG. 13A), wherein the area factor becomes

substantially 100%. Namely, it is desirable that the region where the pattern is printed should be covered substantially completely with the dots.

However, the foregoing condition is not essential for the pattern, the reflection optical density of which becomes smaller as the offset of the printing positions becomes greater. But, it is desired that a distance between the dots respectively printed in the forward scan and the reverse scan in the state in which the printing positions in the forward scan and the reverse scan are registered should range from a distance where the dots are contacted to a distance where the dots overlap over the dot radius. Therefore, according to the offset from the best condition of printing registration, the reflection optical density varies sensitively. As described below, the distance relationship between the dots is established depending upon the dot pitch and the size of the dots to be formed, or the distance relationship is artificially established in pattern printing when the dots to be formed are relatively fine.

The printing patterns in the forward scan and the reverse scan are not necessarily aligned in the vertical direction.

FIGS. 20A to 20C show patterns in which the dots to be printed in the forward scan and the dots to be printed in the reverse scan are intricate mutually. It is possible to apply the present invention to these patterns. FIG. 20A shows the state in which printing positions are well registered; FIG. 20B, the printing positions are registered with a slight offset; and FIG. 20C, the printing positions are registered with a greater offset.

FIGS. 21A to 21C show patterns where dots are formed obliquely. It is possible to apply the present invention to these patterns. FIG. 21A shows the state in which printing positions are well registered; FIG. 21B, the printing positions are registered with a slight offset; and FIG. 21C, the printing positions are registered with a greater offset.

FIGS. 22A to 22C show patterns in which dots are formed at a plurality of columns in forward and reverse scan with respect to printing position offsetting.

FIG. 22A illustrates dots in the case where the printing positions are well registered; FIG. 22B, where the printing positions are registered with a slight offset; and FIG. 22C, where the printing positions are registered with a greater offset. When printing registration is performed by varying the printing registration condition over a greater range such as a printing start timing, the patterns shown in FIGS. 22A to 22C are effective. In the printing patterns shown in FIGS. 13A to 13C, since the set of the dot arrays to be offset is one for each of the forward scan and the reverse scan, the dot array may overlap with the dot array of another set as the offset amount of the printing position is increased. The reflection optical density does not become further smaller even when the offset amount of the printing position becomes greater. In contrast to this, in the case of the patterns shown in FIGS. 22A to 22C, it is possible to enlarge the distance of the offset of the printing position to cause the dot array to overlap with: the dot array of another set in comparison with the printing patterns of FIGS. 13A to 13C. By this, the printing registration condition can be varied in greater range. This is actually used in a coarse adjustment described below to cope a position shift to 4 dots.

FIGS. 23A to 23C show printing patterns in which dots are thinned on each column.

FIG. 23A illustrates dots in the case where the printing positions are well registered; FIG. 23B, where the printing positions are registered with a slight offset; and FIG. 23C, where the printing positions are registered with a greater offset. It is also possible to apply the present invention to

these patterns. This pattern is effective in the case where the density of the dot formed on the printing medium 8 is great, and the density as a whole becomes too great to measure a difference in density according to the offset of the dots by the optical sensor 30 when the patterns shown in FIGS. 13A to 13C are printed. Namely, by reducing the dots as shown in FIGS. 23A to 23C, a not-printed region on the printing medium 8 is increased to lower the density of the overall patch.

Conversely, when the printing density is too low, the dots are formed by performing printing twice at the same position or only at a part.

The characteristics of the printing pattern to reduce the reflection optical density as the offset amount of the printing position is increased require a condition where the dot printed in the forward scan and the dot printed in the reverse scan are matched in contact in the carriage scanning direction. However, it is not necessary to satisfy such condition. In such case, the reflection density may be lowered as the offset amount of the printing positions in the forward scan and the reverse scan is increased.

(3.2) Printing Registration among a Plurality of Heads

A printing position in a carriage scanning direction between different heads is described. Furthermore, it relates to printing registration in the case where a plurality of kinds of printing mediums, inks, printing heads and so on are used. Namely, the size and density of dots to be formed may be varied depending upon the kind of printing medium or the like to be used. Therefore, in advance of judgment of a printing registration condition, judgment is made as to whether a measured reflection optical density is suitable for the judgment of the printing registration condition. As a result, if it is judged that the measured reflection optical density is not suitable for the judgment of the printing registration condition, the level of the reflection optical density is adjusted by thinning the dots in the printing pattern or overprinting the dots, as described above.

In advance of judgment of the printing registration condition, judgment is made as to whether or not the measured reflection optical density is sufficiently lowered according to the offset amount of the printing position. As a result, if judgment is made that the reflection optical density is inappropriate for performing judgment of the printing registration condition, the dot interval, in the carriage scanning direction set in advance in the printing pattern is modified to again print the printing pattern and measure the reflection optical density.

Concerning the printing pattern explained above, the first one of the two printing heads for the printing registration prints the dots printed in the forward scan, while the second printing head prints the dots printed in the reverse scan, thereby achieving printing registration.

FIG. 24 is a flowchart illustrating printing registration processing in the second embodiment. This processing can be applied as a part of processing in general algorithm described later.

As shown in FIG. 24, at step S121, the nine patterns 61-69 shown in FIG. 17 are printed as the printing patterns. The reflection optical density of the printing pattern is measured in the same manner as in the bi-directional printing.

Next, at step S122, a decision is made as to whether or not the highest one among the measured reflection optical densities falls within a range of 0.7 to 1.0 of an OD value. If the value falls within the predetermined range, the operation proceeds to a next step S123.

If the result at step S122 is that the reflection optical density does not fall within the range of 0.7 to 1.0, the

operation proceeds to step S125. At step S125, the printing pattern is modified to patterns shown in FIGS. 23A to 23C where the dots of the printing pattern are thinned to two thirds when the value is greater than 1.0, and then, the operation is returned to step S121. On the other hand, if the reflection optical density is smaller than 0.7, the printing pattern shown in FIGS. 23A to 23C is overprinted over the printing pattern shown in FIGS. 13A to 13C.

It is also possible to prepare a large number of printing patterns for further modifying the printing pattern so as to repeat the loop from step S121 to step S125 when inappropriateness is judged even in the second judgment. However, in the present embodiment, on the assumption that three kinds of patterns cover almost all cases, the operation proceeds to the next step even when inappropriateness is judged in the second judgment.

Even if the printing medium 8, the printing head or the density of the pattern to be printed with ink is varied, printing registration adapting to such variation becomes possible by the judgment processing at step S122.

Next, at step S123, a decision is made as to whether or not the measured reflection optical density is sufficiently lowered with respect to the offset amount of the printing position, namely, whether or not a dynamic range of the value of the reflection optical density is sufficient. For example, in the case where the value of the reflection optical density shown in FIG. 18 is obtained, a decision is made as to whether or not a difference between the maximum density (the point corresponding to the printing position parameter (d) in FIG. 18) and two next values (the difference between points corresponding to printing position parameters (d) and (b), the difference between points corresponding to printing position parameters (d) and (f) in FIG. 18) is greater than or equal to 0.02. If the difference is smaller than 0.02, judgment is made that the interval of the printing dots of the overall printing pattern is too short, namely, that the dynamic range is not sufficient. Then, the distance between the printing dots is enlarged at step S126, and the processing from step S121 onward is performed.

The processing at steps S123 and S124 will be explained in greater detail with reference to FIGS. 25A to 25C, FIGS. 26A to 26C and FIG. 27.

FIGS. 25A to 25C schematically illustrate the printed portion in the case where the printing dot diameter of the printing pattern shown in FIGS. 20A to 13C is large.

In FIGS. 25A to 25C, white dots 72 represent dots printed by the first printing head, and hatched dots 74 represent dots printed by the second printing head. FIG. 25A illustrates dots in the case where the printing positions are well registered; FIG. 25B, where the printing positions are registered with a slight offset; and FIG. 25C, where the printing positions are registered with a greater offset. As is obvious from comparison of FIGS. 25A and 25B, when the dot diameter is large, the area factor is maintained at substantially 100% even if the printing positions of the white dots and the hatched dots are slightly offset, and thus, the reflection optical density is hardly varied. Namely, the condition where the reflection optical density is sensitively decreased according to variation of the offset amount of the printing position, as described in the first embodiment, is not satisfied.

On the other hand, FIGS. 26A to 26C show the case where the interval between the dots in the carriage scanning direction in the overall printing pattern is enlarged without changing the dot diameter. FIG. 26A illustrates dots in the case where the printing positions are well registered; FIG. 26B, where the printing positions are registered with a slight

offset; and FIG. 26C, where the printing positions are registered with a greater offset. In this case, the area factor is reduced according to occurrence of the offset between the printed dots to lower the entire reflection optical density.

FIG. 27 is a graph schematically illustrating the behavior of the density characteristics in the case where the printing patterns shown in FIGS. 25A to 25C and 26A to 26C are used.

In FIG. 27, the vertical line represents an optical reflection density; and the horizontal line, an offset amount of the printing position. A solid line A indicates variations of the value of the reflection optical density in the case where the printing is performed under a condition where the reflection optical density is sensitively lowered according to the variation of the offset amount of the printing position as set forth, and a broken line B indicates variations of the value of the reflection optical density in the case where the dot interval is smaller than the former case. As can be clear from FIG. 27, when the dot interval is too small, the reflection optical density cannot be varied too much for the above-described reason even if the printing registration condition is deviated from the ideal condition. Therefore, in the present embodiment, the decision at step S123 of FIG. 24 is made to enlarge the distance between the dots based on the result of the decision, thereby establishing the printing condition suitable for performing judgment of the printing registration condition.

In the present embodiment, the initial dot interval is set short. Then, the dot interval is gradually enlarged until the proper dynamic range of the reflection optical density can be attained. However, if the proper dynamic range of the reflection optical density is not obtained even after the dot interval is enlarged four times, the operation proceeds to the next step for making judgment of the printing registration condition. In the present embodiment, the dot interval is adjusted by varying the driving frequency of the printing head while maintaining the scanning speed of the carriage 2. Consequently, the distance between the dots becomes longer as the driving frequency of the printing head becomes lower. In another method for adjusting the distance between the dots, the scanning speed of the carriage 2 may be varied.

In any case, the driving frequency or scanning speed for printing the printing pattern is different from that to be used in actual printing operation. Therefore, after the printing registration condition is judged, the difference in driving frequency or scanning speed must be corrected accordingly. This correction may be performed arithmetically. Alternatively, it is possible to preliminarily prepare data of printing timings relating to the actual driving frequency or scanning speed for each of the nine patterns 61-69 shown in FIG. 17 so as to use the data based on the result of the printing registration condition. Otherwise, in the case shown in FIG. 18, the printing timing to be used for printing can be obtained by linear interpolation.

A method of judgment of the printing registration condition is similar to that of the bi-directional printing. In printing registration in the forward scan and the reverse scan in bi-directional printing, varying the distance between the dots of the printing pattern with respect to the dot diameter as performed in the present embodiment is effective similarly to the present embodiment. In this case, the printing patterns for the forward scan and the reverse scan are prepared for respective printing patterns of several kinds of distances between the dots to be used. Then, data of the printing timings are prepared for the respective printing patterns and the distances between the dots, thus determining the printing timing to be used in printing by performing

linear interpolation based on the result of the judgment of the printing position.

It should be noted that a processing for changing printing patterns and the like shown in the flowchart of FIG. 24 also are applicable to the registration for the bi-directional printing and the registration in the longitudinal direction described as follows which are appropriately modified.

(3.3) Printing Registration in the Longitudinal Direction

Printing registration between a plurality of heads in a direction perpendicular to a carriage scanning direction is described.

In the printing apparatus in the present embodiment, in order to perform correction of a printing position in the direction perpendicular to the carriage scanning direction (auxiliary scanning direction), ink ejecting openings of the printing head are provided over a range wider than a width (band width) in the auxiliary scanning direction of an image formed by one scan so as to permit correction of the printing position at each interval between the ejection openings by shifting the range of the ejection openings to be used. Namely, as a result of shifted correspondence between the data (image data or the like) to be output and the ink ejection openings, it becomes possible to shift the output data per se.

In the printing registration for the bi-directional printing and the printing registration between a plurality of heads in the main scanning direction described above, the printing pattern, in which the measured reflection optical density becomes maximum when the printing position is registered, is used. However, in the present embodiment, the reflection optical density becomes minimum when the printing positions are registered. With an increasing offset amount of the printing positions, the reflection optical density in the pattern is increased.

Even in the case of printing registration in a paper feeding direction as in the present embodiment, similarly to the above description, it is possible to use a pattern, in which the density becomes maximum under the condition where the printing positions are registered and is decreased with an increasing offset amount of the printing positions. For example, it becomes possible to perform printing registration while paying attention to dots formed by ejection openings in the adjacent positional relationship in the paper feeding direction between two heads, for example.

FIGS. 28A to 28C schematically show the printing pattern to be used in the present embodiment.

In FIGS. 28A to 28C, a white dot 82 represents a dot printed by a first printing head, and a hatched dot 84 represents a dot printed by a second printing head, respectively. FIG. 28A illustrates dots in the case where the printing positions are registered, wherein since the above-described two kinds of dots are overlapped, the white dot is not visually perceived; FIG. 28B, where the printing positions are slightly offset; and FIG. 28C, where the printing positions are further offset. As can be seen from FIGS. 28A to 28C, with an increasing offset amount of the printing positions, the area factor is increased to increase an average reflection optical density as a whole.

By offsetting the ejection openings of one of the two printing heads concerned in printing registration, five printing patterns are printed while varying printing registration condition with respect to offsetting. Then, the reflection optical density of the printed patch is measured.

FIG. 29 graphically shows an example of the measured reflection optical density, in which five patterns are illustrated for example.

In FIG. 29, the vertical line represents a reflection optical density; and the horizontal line, an offset amount of the

printing ejection openings. Among the measured reflection optical densities, the printing condition where the reflection optical density becomes the minimum ((c) in FIG. 22) is selected as the condition where the best printing registration is established.

Moreover, a pattern used at a time of execution of each registration processing as described in the above items (3.1) to (3.3) is not limited to only the printing registration in each processing, and it is needless to say that an appropriate change is added if necessary and the above pattern can be used for the other actual printing registration in the same manner.

Further, the items (3.2) and (3.3) show an example in the relationship between two print heads, but can be applied to the relationship between three print heads or more in the same manner, and for example, in the three print heads, printing positions of a first head and a second head are registered and thereafter positions of the first head and a third head have only to be registered.

4. First Example of Algorithm of Dot Alignment Processing

The above is fundamental and next one example of an algorithm of an automatic dot alignment processing will be described.

FIG. 30 shows an outline of an automatic dot alignment processing algorithm in this example, generally comprising: a recovery processing step (step S101); a sensor calibration processing step (step S103); a coarse and a fine adjustment steps of a bi-directional record (steps S105, S107); and an adjustment value confirmation pattern printing processing step (step S111), and these steps are executed for registering depositing positions in respective prints in a forward scan and in a reverse scan under optimum conditions using mainly the same print head.

Moreover, means for activating this algorithm is an input from an activation switch provided in a body of the printing apparatus or applications on a side of the host computer 110, and additionally at a time of apparatus turn-on, a timer activation, etc. as required. Further, these may be combined.

Further, for example, in the case where such a calibration as procures data except in a usable range is caused in a sensor calibration processing, or in the case where a strength of reflection lights are extremely increased by influences of disturbance lights, etc. in a processing of a dot alignment processing, and as the results, a coarse adjustment error or a fine adjustment error occurs, a normal manual adjustment is executed (step S119). This processing will be described below.

In the case where a sensor error is temporary which is caused by reception of accidental disturbance lights, the apparatus informs a user that he takes a time or adjusts conditions and then the dot alignment processing can be again activated. This point was explained in the item (1.5), including explanation of conditioning which are transferred to the manual adjustment.

Hereinafter, processing contents at each step will be in detail described.

(4.1) Recovery Processing

As mentioned above, a recover processing is a sequential operations for setting or holding an ink ejection state of the print head such as sucking, wiping, preliminary ejecting and the like to be normal prior to execution of an automatic dot alignment in a normal state, and the recovery processing is performed prior to the execution in the case where an execution instruction of the automatic dot alignment is

made. Thereby, it is possible to perform printing a pattern for printing registration in a state that an ejection state of the print head is stable and set correction conditions of printing registration with high reliability.

The recovering operations are not limited to a series of operations such as sucking, wiping, preliminary ejecting and the like, but may be only preliminary ejecting or only preliminary ejecting and wiping. It is preferable that the preliminary ejecting in this case is set so as to perform preliminary ejecting having the greater number of ejection than that at a time of printing. Further, in a combination of the number of times of sucking, wiping, preliminary ejecting and order of operations, there are in particular no conditions for limitation.

Further, it may be decided whether execution of sucking recovery prior to automatic dot alignment control is required in response to an elapsed time from sucking recovery at a previous time or not. In this case, it is first decided whether a specified period of time elapses from previous sucking operations immediately before the automatic dot alignment is carried out or not. If the sucking operations are executed within a specified period of time, the automatic dot alignment is, executed. In the meantime, if the sucking recovering operations are not executed within the specified period of time, after a series of recovering operations containing the sucking recovery are executed, the automatic dot alignment can be carried out.

Further, it is decided whether the print head ejects an ink at the specified number of ejection or more from the previous sucking recovery or not, and in the case where the ink is ejected at the specified number of ejection or more, after the recovery operations are executed, the automatic dot alignment may be executed. Further, by use of both the elapsed period of time and the number of ink ejection as decision materials, a combination may be made so that, if any one reaches a specified value, the sucking recover is executed.

Thus, as it is possible to prevent the sucking recovery from being excessively executed, this can contribute to saving of a consumption amount of inks and a reduction of an ink discharge amount to a disused ink processing portion, and also the recovering operations prior to the automatic dot alignment can effectively be carried out.

Further, recovery conditions are variable in response to the elapsed time from the previous sucking recovery or the number of ink ejection, and for example, in the case where the elapsed period of time is short, only preliminary ejection and wiping are carried out without executing the sucking operations, and in the case where the elapsed period of time is long, the recovery conditions may be changed, for example, the sucking recovery is midway executed.

As mentioned above, the recovering operations are executed as required, but a structure of executing the recovery operations is not always required to use, and if the printing apparatus is originally high in reliability, the recovering operations in the automatic dot alignment processing are not required to execute. It is more preferable that high reliability is secured and besides the automatic dot alignment processing is executed.

(4.2) Sensor Calibration

Next, in one example of a calibration of LED included in an optical sensor **30**, a supply power is PWM-controlled so as to perform a calibration so that it is desirably used in a linear area, in order to obtain a specified range as output characteristics of the optical sensor. Specifically, the supply current is PWM-controlled, and a current amount flowing at intervals of 5% is controlled, for example, from a full power

of 100% duty to a power of 5% duty, thereby to obtain an optimum current duty, so that LED of the optical sensor **30** is driven as an example.

The reason why is as follows:

That is, lights are irradiated from the light-emitting side of the optical sensor **30** on a pattern in which printing registration conditions are changed, and in order to decide the optimum printing registration conditions from relative values of the reflected lights output, unless the optimum light amount is irradiated and an optimum electric signal is applied to a photosensing-side, a reliable output difference cannot be obtained.

In order to obtain a sufficient output difference (an output difference between patterns when printing positions are changed at a minimum in actual printing registration patterns), it is strongly desirable that a calibration of a sensor itself (a light-emitting portion side and/or a photosensing portion side) is performed.

This is preferable when correcting variations peculiar to a density sensor (an optical sensor), a sensor mounting tolerance in the printing apparatus, an atmosphere difference such as a state of lights, humidity, an air of an environment (mist, smoke), a temporal change of a sensor itself, influences of an output reduction due to heat storage, mist adhered to the sensor, influences of an output reduction due to paper powders, or the like. Further, from this viewpoint, a sensor calibration method of the invention can be adapted to not only an optical sensor for use in execution of the automatic dot alignment, but also an optical sensor for detecting presence or absence of a printing medium and a paper width, a sensor used for head shading, or the like, namely an optical sensor used in widely obtaining any information from an object to be measured.

Here, a calibration on a side of a luminous portion will be described.

FIG. **31** shows the relationship of reflectivity in the case where an ink deposition rate on a specified area is changed, and as shown in FIG. **31**, there are characteristics that reflectivity is saturated at a certain deposition rate or more (a position A or more). Output characteristics of the sensor itself are to measure a change of reflected lights with respect to irradiated lights on the light-emitting side, and depend firmly on an area factor in a specified area. In this example, since even if the ink is deposited at a deposition rate or more at a position A, the area factor is not substantially changed, the reflectivity is not also changed. Even in the actual printing registration, a range depending largely upon a change of this are factor, namely an unsaturated and linear range of reflectivity instead of the deposition rate is essential.

FIG. **32** shows output characteristics measured when a maximum rated value of an electric signal applied to the light-emitting side is set at 100% and an electric signal (a driving signal) is set at 5%, 25%, 50%, 75% and 100%, in response to a pattern in which reflectivity is changed. If a light amount is too weak, an amount of reflected lights is too small between outputs of patterns of different reflectivity and a difference in output is scant. On the contrary, if a luminous amount is too strong, reflected lights are increased in a pattern of reflectivity inclining toward a white ground in outputting patterns of different reflectivity, and at a time of exceeding detection capability on a side of light reception, there is scarcely a difference from an output of a white ground. Therefore, if such pattern in a reflectivity area exists in actual printing registration patterns, an output difference cannot preferably be obtained. Here, it is material that the output difference in the reflectivity area of the pattern used

for the printing registration can be obtained. In the case where the reflectivity area of the pattern of the actual printing registration is limited to a range of A to B in FIG. 32, output characteristics of (i) to (iv) are linear, but in the case of the actual printing registration, characteristics of (iv) can secure an excellent S/N ratio.

A modulation of a driving signal on the light-emitting side is made in a processing of the MPU 101 inside a printer and the modulation unit amount can be processed in minimum unit which a luminous amount is changed.

The modulation is same in a calibration on a photosensing side, and the optimum electric signal applying conditions can be decided when reflectivity of printing registration patterns are measured by the above method. The modulation of a driving signal of the photosensing side is performed by a processing of the MPU 101 inside the printer and the modulation unit amount can be processed in minimum unit which a luminous amount is changed.

Further, there can be provided a buffer for storing an output value inside the printer and means which the output value can be compared with the threshold value set in a printer section in advance and by which can be processed.

Here, a referencing object to be measured is required in order to perform the above calibration. In this embodiment, the sensor calibration is performed as the assumption of the dot alignment processing, and at the time of the dot alignment, the predetermined patches are printed on a printing medium, whereby a pattern for the sensor calibration which is an object to be measured is printed on the printing medium. The sensor calibration may be performed every each of the dot alignment processes (coarse adjustment and fine adjustment with respect to a bi-directional printing in a first example of the dot alignment processing, in addition, coarse adjustment and fine adjustment between a plurality of heads in a second example described below, and further vertical adjustment) or the sensor calibration pattern may be designed to be printed and formed only at a heading portion (page head) of the printing medium, and a sensor calibration of one time also may be designed to perform prior to a series of dot alignment processes.

Moreover, a printing medium being formed patches for the dot alignment processing as described above is utilized, and in addition, is mounted on a body of the printing apparatus (for example, such structure is added to a platen), and it is possible to utilize a printing medium, a metal plate or the like in which only an object to be measured is separate.

Next, an object to be measured (a calibration pattern) used for a sensor calibration is composed of a color reacting to sensor luminous wavelengths sensitively. The color may be single, or a plurality of colors may be combined if reflectivity is not changed according to positions in a specified area.

Moreover, in the case where the sensor calibration pattern changing reflectivity is used, the pattern may be a pattern which each pattern becomes is an independent patch, and partial patterns changing reflectivity may be continued.

Moreover, in the sensor calibration, after an electric signal is coarsely changed to perform coarse adjustment, it may be minutely changed to make fine adjustment, or it may be minutely changed from the beginning.

Further, in the sensor calibration, while an electric signal to be applied is changed in a processing of a main scan of the carriage, a measurement may be executed, and after the carriage is stopped and it is changed, a measurement may be executed. Furthermore, the calibration may be executed within one scan or within a plurality of scans.

Next, several specified example of a sensor calibration are described.

(4.2.1) First Example of Sensor Calibration Processing

A pattern changing reflectivity is measured by changing an electric signal being applied to the light-emitting side and/or a photosensing side, and by use of the reflectivity closest to sensitivity characteristics (an inclination of output characteristics) preset in ROM, etc. inside a printer or one more than those, hereafter, the printing registration measurements are performed. The pattern changing the above reflectivity may be in a reflectivity area used in an actual registered pattern, or in the whole area of reflectivity (0 to 100%).

FIG. 32 shows results derived by measuring reflection density (an output) of objects to be measured having different reflection indexes (for example, patterns formed at a reflection index at intervals of 10% between 0 to 100%) by changing an electric signal on the light-emitting side. A reflection index is taken in the horizontal axis and reflection density (an output) is taken in the vertical axis in FIG. 32.

FIG. 33 shows ideal sensitivity (output) characteristics in a state that, when the reflection index is changed, reflected lights density (output) is changed linearly. In the case where a duty of an electric signal applied to the light-emitting side is too small and a change amount of the reflected lights from a specified pattern is lower than resolution of the photosensing side, an output change is scant as shown in characteristics (i) of FIG. 32. If a duty is too large, the reflection concentration (output) itself is not changed at a time when the reflected light amount exceeds a maximum detection width of the photosensing side as shown in characteristics (v), similarly. Here, it is a premise that an output change occurs in an all reflection index area (0 to 100%), but an area deriving sufficiently the output change conforming to a reflection index area of the printing registration used actually may be used. Here, conditions deriving sufficiently the output change mean that, in the case where a printing position is offset at a minimum in an actual printing registration pattern, the output change can be obtained.

And, ideal output characteristics as shown in FIG. 33 for using the actual printing registration are provided in a body of the apparatus and a drive duty on the light-emitting side and/or the photosensing side which can approximate to these characteristics (there may be a flexibility to a certain degree, for example, characteristics of 10% down shown by a broken line in FIG. 33 are used) is selected.

(4.2.2) Second Example of Sensor Calibration Processing

An electric signal applied to the light-emitting side and/or a photosensing side is set as a constant amount and the pattern changing a reflection index is measured, and sensitivity characteristics (an inclination of output characteristics) are computed from a plurality of output data (two at a minimum), and in the case where a measured value except a measured value used for computing the sensitivity characteristics is deviated from values estimated from the characteristic curve, the electric signal to be applied is changed and the same decision is repeated. In the case where a plurality of applied amounts are correct from this decision, one having the greatest inclination of the output characteristics there among may be selected, or a certain flexibility has previously been set inside the printer and a selection is performed as required. In the same manner as described above, these output characteristics may be within the range of reflection indexes used in the actual registered pattern, or in the entire reflection index area (0 to 100%).

That is, as shown in FIG. 34, a duty of an electric signal being applied to the light-emitting side and/or the photo-

sensing side is set a constant amount, and reflection density (an output) of a plurality of measured patterns (two at a minimum) is obtained, and imaginary sensitivity characteristics (an inclination of output characteristics) is computed therefrom, and in the case where a measured value except a measured value used for computing the imaginary characteristics is deviated from the characteristic curve (for example, characteristics (iii)), the same operations are repeatedly carried out at a duty other than that, and a duty indicating characteristics ((ii) or (i)) closest to ideal characteristics (a linear inclination) is selected (there may be flexibility to a certain degree).

(4.2.3) Third Example of Sensor Calibration Processing

A specified pattern (a white patch of dot deposition rate 0%, a solid patch formed at the other deposition rate than that or the like) is measured by changing an electric signal applied to the light-emitting side and/or the photosensing side, and the following printing registration measurement is designed to perform by using one which the output value (reflection density) reaches a threshold value previously set inside the printer.

That is, if reflected light density (an output) of an object to be measured in which a reflection index is fixed (for example, only a solid patch formed at the deposition rate of 50%) is measured, the output characteristics can be approximately estimated. One which utilizes these features corresponds to this example.

FIG. 35 shows output characteristics in the case where printing of pattern with a deposition rate of 50% is performed on a printing medium and a calibration on the light-emitting side is performed by using this. When a pulse width (a duty) of an electric signal being applied to the light-emitting side is varied, the output is not changed from a certain duty. This state is the case where reflected lights of a detection width or more on the photosensing side are detected. Then, the output is compared with a threshold value R_{th} prepared beforehand in the printing apparatus, and a duty closest to the threshold value (there may be flexibility to a certain degree) is selected.

(4.2.4) Fourth Example of Sensor Calibration Processing

The described-above processes are combined to execute. Namely, for example, in the processing of the third example, an electric signal is changed to measure and the processing may be designed to switch to the first example or the second example at a time of exceeding the threshold value.

FIG. 36 is an example of a processing algorithm of this example, and as shown in the third example, the predetermined pattern for the sensor calibration (for example, a white patch of a deposition rate 0%) is measured, changing a duty applied to the light-emitting side (steps S201, S205) and the duty is compared with the threshold value set previously (step S203), and one of output characteristics which is linear is selected as shown in the first example from the duty exceeding the threshold value (steps S207, S209, S211). The output characteristics is selected, changing a duty at intervals of 5% in an adjustment procedure using the threshold value, for example, and thereafter a linear area having the greatest inclination is obtained by changing a duty at intervals of 1%. Thereby, a coarse adjustment and a fine adjustment are performed in the sensor calibration and the optimal sensor drive duty is decided accurately and speedily and it becomes possible to be shifted to the subsequent printing registration.

Moreover, the processing procedure of FIG. 36 is used as it is substantially when the fourth example is used, and it is occasionally added modifications, etc. when the first to third examples are used, and it can be positioned as step S103 of FIG. 30.

Further, error processing means is provided in the printing apparatus, taking into consideration the case where even the optimal or suitable duty cannot be decided, despite that any one of the above calibrations is carried out. In this case, as mentioned above, it is possible to again repeat the same processing (an automatic registration adjustment), or to notify a user of a message urging the other means (a manual registration adjustment) from the body of the printing apparatus, the host device or the like.

(4.3) Coarse Adjustment of Printing Registration for Bi-directional Printing

Next, a coarse adjustment of a printing registration for a bi-directional printing (step S105 of FIG. 30) will be explained. In this embodiment, a tolerance precision of a relative depositing position of printing dots when performing bi-directional printing by the printing apparatus and the print head shall be within ± 4 dots. Accordingly, a pattern having a width of 4 dots is used in the coarse adjustment.

FIGS. 37A to 37C show an example of a pattern of a patch for use in the coarse adjustment. A reference dot is formed by a printing in a forward scan, and offset dots in which printing is performed, changing registration conditions, are formed by a reverse scan. In the case where printing is performed in a non-adjustment, an offsetting or shifting amount is defined as 0 dot. The offsets caused when printing is performed in this state (FIG. 37C) are caused by depositing position precision of the printing apparatus and the print head, and are generated due to variations, etc. upon the respective manufacturing. This example can adjust this offset automatically.

FIGS. 37A to 37E show that printing of each pattern is performed within a range of an offsetting amount: ± 4 dots, and it is enough that the offsetting amount in these patterns is 4 dots at a maximum.

A solid line in FIG. 38 shows characteristics of an output (a value after reflected light is received and is converted by an A/D converter) of an optical sensor with respect to the offsetting amount in this case. Moreover, characteristics approximating the output characteristics for the offsetting amount by the polynomial are shown by a broken line. From these approximated characteristics, the point which reflection density is the maximum can be defined as an adjustment value of offset, in other words an adjustment value when bi-directional printing is performed.

Moreover, the adjustment value in this case can be set more finely than an interval of the offset amount. Moreover, the offsetting amount showing a maximum of reflection density may be an adjustment value of the bi-directional printing without making approximation at this time. An interval of the offsetting amount of a pattern may be set as a 2-dot interval and naturally as a 1-dot interval. Moreover, it may be an unequal interval and offsetting with precision of a 1-dot interval or less, and the adjustment can be made if within a scope of tolerance precision of a depositing position and at an interval in which approximate characteristics can be obtained.

(4.4) Fine Adjustment of Printing Registration for Bi-directional Printing

Next, a fine adjustment of a printing registration in a bi-directional printing (step S17 of FIG. 30) is explained. When a fine adjustment is executed with finer adjustment precision, it is a premise that an adjustment is performed within a one-dot interval similarly to the coarse adjustment, and the fine adjustment is performed within ± 0.5 dots. As the fine adjustment is performed with high precision, a pattern with a minimum width is used.

FIGS. 39A to 39E show an example of a pattern used for a fine adjustment. Similarly to a coarse adjustment, a refer-

ence dot is printed by the forward scan printing and an offsetting dot in which printing is performed, changing registration conditions, is printed by a backward scan printing. In the case where printing is performed with a non-adjustment (FIG. 39C), an offset amount is 0 dot. In this example, registration conditions are set at an interval of 0.25 dots. Here, similarly to the coarse adjustment, characteristics approximating output characteristics of an optical sensor with respect to the offsetting amount by the polynomial are acquired, and a point maximizing reflection density from these approximation characteristics can be set as an adjustment value of an offset, in other words, an adjustment value when bi-directional printing is performed.

Moreover, the adjustment value in this example can set more finely than an interval of an offset amount, namely 0.25 dots. Moreover, if the demanded adjustment precision is equal to an interval of an offsetting amount, the offsetting amount showing a maximum of reflection density may be set as an adjustment value of a bi-directional printing without performing approximation.

However, in this example, the following system is used in order to further improve adjustment precision:

This system will be described using FIGS. 40 to 43.

First, in the forward scan and the reverse scan, when dot alignment is performed in the case, as shown in FIG. 40A, which print dots are formed on alternate one dot complementarily with respect to horizontal or main scanning, even if a patch is formed by offsetting a dot formation position in the forward scan printing, there is a case where density change is scant and a preferable density output cannot be obtained as shown in FIG. 40B. On the contrary, there is a case where density change is large compared with an ideal state and a sufficient density output can be obtained as shown in FIG. 40C.

Here, in the case of considering only two dots of the reference dot adjoining each other and an offset dot, when being under the condition which the two dots are contacted each other, the area of the range which is covered with the dots is greatest and even if the dots are separated more than that, the total of the area covered with the dots is not changed. In other words, there is no change in density. On the contrary, when the dots are shifted closer to each other from the contacting condition, the area of the region covered with the dots is reduced in accordance with the change of the depositing position. In other words, density is changed in accordance with the depositing position.

From the relation of the pixel density and a dot diameter, in order to make the area factor to 100%, when the dot is defined as a diameter of size of $\sqrt{2}$ times of one pixel, and under the condition that the formation position is registered the overlapped parts exist inescapably in the dots which are adjoined are each other, there is on overlapped part between adjoining two dots, necessarily. Therefore, the condition that the deposition position are registered can be the region where the density is changed greatly in the deposition position of the dot.

From the above, preferable characteristics of density output can be obtained with respect to depositing position of offsetting dot where each dot is formed at a pitch of two dots or more in the main scanning direction, rather than where each dot is formed at a pitch of one dot shown in FIG. 40A. This will be described later reference to FIGS. 42A to 42D.

As shown in FIG. 41, a change in density (a broken line is one obtained by an approximation by the polynomial) of a patch group (a pattern (a)) formed, changing registration conditions of a depositing position of dots in the reverse scan (a dot offsetting amount) with respect to a reference dot

formed by the forward scan and a change in density (a broken line is one obtained by an approximation by the polynomial) of the patch group (a pattern (b)) obtained by forming dots in the reverse scan at a position which is line-symmetrical every said registration condition with respect to a reference dot become a similar property and the characteristics of the change in density have been reversed by directiveness of the adjusting direction simply. Using this characteristics, the intersection of the characteristics of two kind changes in density can be determined as the adjusting position where the depositing position of the dot have just registered.

Since the offset of the delicate formation position appears sensitively on the change in density, this adjustment method is adapted to the strict adjustment of the depositing position, and a dot alignment (a printing registration) with high accuracy can be realized.

Moreover, in this method, a characteristic curve in response to directiveness of the adjusting direction may be set as an approximate curve acquired from measured values and the approximate curve may be acquired from a plurality of points in the vicinity of an intersecting points.

As is described above, the adjusting position is acquired from an intersecting point of the characteristic curve by using a curve approximation or a linear approximation, but if an adjusting interval is an interval of required precision, the approximation expression of the characteristic curve is not required to acquire. For example, a point where a difference of output OD values (density) of two characteristics is smallest may be defined as an adjusting position and this system is not in particular limited to a configuration using the approximation expression.

When obtaining the pattern (a), as shown in FIGS. 42A to 42D, each patch (FIGS. 42A, 42B, 42D) offsetting the depositing position in the print in the reverse scan at an interval of 0.5 dots in a positive and negative direction (a leftward direction in the drawings is positive) with respect to a patch in which an offsetting or shifting amount is 0 dot (FIG. 42C) may be formed. On the other hand, when obtaining the pattern (b) (an inverse pattern) formed at a position where the dot in the reverse scan is line-symmetrical to the pattern (a) with respect to the reference dot, as shown in FIGS. 43A to 43D, with respect to a patch (FIG. 43C) formed under the condition that the dots in the reverse scan are, first, shifted to a leftward direction of the drawings by two-dots with respect to the case where the offsetting amount is 0 in the pattern (a), each patch (FIGS. 42A, 42B) reducing the offsetting amount by the printing in the reverse or backward scan at an interval of 0.5 dots in a positive direction may be formed, and a patch (FIG. 42D) increasing the offsetting amount by the printing in the backward scan at an interval of 0.5 dots in a negative direction may be formed.

Moreover, in this example, although a dot alignment processing acquiring an intersecting point of characteristics of two patterns for the fine adjustment is performed and the dot alignment processing for the coarse adjustment can also be performed, as a matter of course.

(4.5) Printing of Confirmation Pattern

Finally, a confirmation pattern is printed in order that a user can confirm a success in the dot alignment. A ruler mark pattern, etc. easy to be recognized by the user is used for the confirmation pattern, and bi-directional printing is performed by using an adjusting value acquired by the coarse adjustment and fine adjustment. In other words, printing patterns of two types of an adjustment pattern measuring density for adjusting and a confirmation pattern for confirm-

ing an adjustment are formed on a printing medium (three types if a type at a time of a sensor calibration is added).

Moreover, a specified example of a pattern formed on a printing medium will be explained in a dot alignment processing corresponding to a mode.

(4.6) Effects of this Embodiment, etc.

In the first embodiment of an algorithm of the dot alignment processing, by providing an adjusting system at two stages of the coarse adjustment and the fine adjustment in the printing registration of the bi-directional printing, the algorithm from a maximum of tolerance precision of a relative depositing position of print dots in the body of the printing apparatus and the bi-directional printing of the print head to an adjustment with high precision can be executed through a series of automatic dot alignment sequence.

Moreover, it is possible to reduce a scope of a fine adjustment, namely to adjust speedily by making previously a coarse adjustment. This is effective for improvement in a throughput of the entire sequence. Moreover, in the case where only a manual adjustment is performed by a user, the user is induced midway to decide and an adjustment mistake by error decision may occur, but this can be suppressed by this embodiment.

As explained above, in this embodiment, in a printing method printing respectively by a forward scan and a reverse scan by using the same print head to form images, by acquiring an optimal adjustment value using this dot alignment processing, it becomes possible to perform printing by setting a depositing position in a forward scan and a depositing position in a reverse scan of the print dots under optimal position conditions, thereby to realize the printing method capable of performing bi-directional printing without an offset of the depositing positions.

Moreover, in this example, the coarse adjustment is first performed and then the fine adjustment is performed, and this order can be reversed. The reason will be described later.

Moreover, in the embodiment, fluctuations of an area changing caused by precision in the depositing position of the dots printed are detected as reflection density. Accordingly, it is firmly desirable that the pattern formed for the sensor calibration and the printing registration is performed printing in a color that the print dots have sufficient absorbing characteristics with respect to an incident light. In the case where a red LED is used, Black or Cyan is preferable from the viewpoint of the absorbing characteristics, and sufficient density characteristics and S/N ratios can be obtained. Then, in this example, black dots most superior in the absorbing characteristics were used.

This is because Black enables to absorb lights for all the areas in spectrum characteristics of red lights as shown in FIG. 44. Cyan corresponds to a complementary color of red and has high absorption characteristics, but a red light itself is not an ideal light and has an extent in the spectrum characteristics. Therefore, a spectrum component which cannot be completely absorbed by Cyan dots exists. Accordingly, the absorption characteristics are slightly lower than Black which can absorb in all the areas.

However, it is possible to cope with each color by deciding a color used for dot alignment in response to characteristics of LED used. On the contrary, it is possible to also select LED in response to a color forming the pattern. For example, it is possible to make dot alignment in each of colors (C, M, Y) with respect to Black by mounting a blue LED, a green LED, etc. in addition to a red LED. Moreover, in the case where each color ejection portion (head) is separately constituted and used by being arranged in parallel, it is preferable that every color is performed print-

ing registration. Therefore, a sensor corresponding thereto is prepared and each calibration may be performed as required.

5. Second Example of Algorithm of Dot Alignment Processing

In this example, the case where a dot alignment processing between a plurality of heads is also performed will be explained. That is, in this example, in addition to the dot alignment of the bi-directional printing, vertical and lateral dot alignments between two heads are executed.

FIG. 45 shows an outline of an automatic dot alignment processing algorithm in this example, and this example generally comprises a recovery processing step (step S101); a sensor calibration processing step (step S103); a vertical adjustment step between two heads (step S104); a coarse and fine adjustment step of a bi-directional record (steps S105, S107); a coarse and fine adjustment step in a horizontal scan direction between two heads (steps S108, S109); and an adjustment value confirmation pattern printing processing step (steps S111).

Moreover, means for activating this algorithm is an input from an activation switch provided in the body of the printing apparatus or applications on a side of the host computer 110, and additionally at a time of apparatus turn-on, a timer activation, etc. as required. Moreover, these may be combined.

The recovery processing (step S101) is same as the above example. Moreover, for example, in the case where calibration errors such as procuring of data except a usable range is caused in a sensor calibration processing, or in the case where a strength of reflection lights are extremely increased by influences of disturbance lights, etc. in a processing of a dot alignment processing, and as the results, a coarse adjustment error or a fine adjustment error occurs, a manual adjustment is executed (step S119), etc. These cases are same as the above example.

The sensor calibration processing (step S103) is substantially same as the above example. In this example, since printing registration between a plurality of heads of different colors is carried out, it is possible to differ a formation color of patterns used in the processing from the above example taking this into consideration the printing registration.

After the sensor calibration is executed, a vertical coarse adjustment between two heads is performed as an initial adjustment in this example (step S104).

In the printing apparatus according to this embodiment, in order to correct a printing position in a direction perpendicular to a carriage scan direction (a vertical scan direction), ink ejection openings of each print head (an ejection portion) are provided ranging over a wider range than a maximum width (a band width) in the vertical scan direction of images formed in one time scan, and a range of the ejection openings used for printing are changed, whereby the printing apparatus is constituted so as to correct the printing positions in unit of intervals of the ejection opening. That is, a correspondence of output data (image data, etc.) to an ink ejection openings are shifted, and as this result, the output data itself can be offset.

That is, the vertical adjustment is performed at a position of image data and vertical printing positioning precision depends upon a resolution of the print head and a control resolution in a direction of feeding a printing medium. Therefore, only a coarse adjustment is performed. However, a fine adjustment can be performed in the same manner as the other as required.

The apparatus according to this embodiment uses a head arranging in parallel a Black ink ejection portion arraying a

nozzle group for ejecting ink of black as shown in FIG. 6A and each color ink ejection portion arraying a nozzle group for ejecting each ink of Y, M and C integrally and in an inline manner in response to a range of arraying the ejection openings of Black. Accordingly, in particular, if the printing registration between Black and, for example, C is performed when the vertical dot alignment processing between a plurality of heads (ejecting portions) is performed, nozzle groups of M and Y inks which are manufactured integrally and in an inline manner in the same processing as an ejection opening group of a C ink is substantially performed printing registration with respect to the Black ejection portion, and namely, the dot alignment processing between the plurality of heads (ejecting portions) is completed. Accordingly, in particular, a red LED is adopted as a the light emitting section when the dot alignment processing between the plurality of heads (ejecting portions) is carried out, while it is enough if Black and C inks having sufficient absorption characteristics for a red light are used to form a measuring patch so that the printing registration is carried out.

However, it is possible to correspond to each color by deciding a color used for the dot alignment in response to characteristics of LED used. Conversely, the LED can be selected in response to a color forming a pattern. For example, a blue LED, a green LED, etc. in addition to a red LED may be mounted, whereby the dot alignment can be carried out for Black in each of color ejecting portions (heads). Moreover, in the case where each color ejecting portion (head) is separately constituted and arranged in parallel with each other in the main scanning direction in the printing apparatus, it is preferable that the printing registration is performed in every color. Therefore, a sensor corresponding thereto is prepared and a calibration is carried out as required. The method is also same in a lateral adjustment described below.

Next, similarly to the above example, a coarse adjustment of the bi-directional printing is performed (step S105), and further a fine adjustment of the bi-directional printing is performed and the adjustment is executed with maximum precision (step S107). In the case of the bi-directional printing, an adjustment of relative depositing position precision of a forward scan printing and a reverse scan printing is performed by adjusting a drive timing in each scan. Here, the corresponding adjustment may be only performed in only Black, or may be performed in another color. A processing corresponding to a color relating to a bi-directional printing has only to be performed.

Next, a coarse adjustment in a lateral direction (the horizontal scan direction) between two heads is performed (step S108). Moreover, a lateral fine adjustment is performed (step S109). The lateral adjustment is performed by adjusting a drive timing between respective head. These coarse and fine adjustments are also processed similarly to the description using FIGS. 37 to 43 in the above example in the two heads.

The apparatus according to this embodiment uses a head arranging in parallel a Black ink ejection section arraying a nozzle ejecting an ink of Black as shown in FIG. 6A and each color ink ejecting portion arraying a nozzle group for ejecting an ink of Y, M and C integrally and in an inline manner in response to a scope of arraying the ejecting openings of Black. Accordingly, in particular, if the printing registration between Black and, for example, C is performed when the lateral dot alignment processing between a plurality of heads (ejecting portions) is performed, a nozzle group of M and Y inks which is manufactured in an inline manner in the same processing as an ejection opening group

of a C ink is substantially performed printing registration with respect to a Black ejection section, and namely, the lateral dot alignment processing between the plurality of heads (ejecting portions) is completed. Accordingly, in particular, a red LED is adopted as the light emitting section when the dot alignment processing between the plurality of heads (ejecting portions) is carried out, while it is enough if Black and C inks are used to form a measuring patch so that the lateral printing registration is carried out.

Finally, similarly to the above example, a confirmation pattern is performed printing and this automatic dot alignment sequence is terminated (step S111).

Moreover, in this example, in the lateral dot alignment, not only an adjustment in the forward scan printing between the respective heads is performed, but also an adjustment in the reverse scan printing is performed. This is because that in the case where the dot alignment of the bi-directional printing is adjusted by the single head, even if the adjustment value is used by the other print heads, a depositing position offset occasionally occurs. When an ejection direction of an ink is different in each print head or an ejection speed is different, a state of the bi-directional printing is different in each print head. This is the reason. In such the phenomenon, in the case where only one of adjustment values of the bi-directional printing can be set, the dot alignment is executed by a single print head which the bi-directional printing references. Next, by use of the print head which the bi-directional printing references as a reference even in a lateral direction, the lateral dot alignment is carried out in each of the scan prints. Thereby, it is possible to suppress a generation of offsets of the bi-directional or lateral depositing position caused by the characteristics of the print head.

Moreover, in the case where a plurality of adjustment values of the bi-directional printing can be set, the dot alignment of the bi-directional printing is carried out in each of the print heads, and the lateral dot alignment is carried out only in a single direction, thereby to adjust the depositing position even when the characteristics of each print head are different.

Moreover, at a time of a dot alignment processing or at a time of actual printing operations using the results, the following can be applied for offsetting the depositing position:

In the bi-directional printing, the ejection start position is controlled using an interval equal to a generation interval of a trigger signal of a carriage motor 6, for example. In this case, an interval of 80 nsec (nanoseconds) can be set by a software for the gate array 140, for example. However, only a required resolution is enough and about 2880 dpi (8.8 mm) is sufficient precision.

Concerning a lateral direction of a printing using a plurality of heads, the image data are controlled at an interval of 720 dpi. The offset within one pixel is controlled by changing 720 dpi driving block selecting order between the plurality of heads in a form in which a nozzle group is divided into several blocks and driven in time-sharing, and further the offset of one pixel or more is controlled by offsetting the image data to be printed between the plurality of heads.

Concerning a vertical direction of a printing using the plurality of heads, the image data are controlled at an interval of 360 dpi and the image data to be printed are controlled by offsetting between the plurality of heads.

6. Dot Alignment Processing in Response to Mode, etc.

Next, the case where automatic dot alignment control is modified (a modification in response to a size of a print dot,

for example) in response to a mode, etc. included in the printing apparatus (for example, a mode of performing a high resolution printing, etc. by modifying a size of the print dot) will be explained.

In the case of an ink-jet printing apparatus, a size of printing dots is mainly decided by an ink amount ejected from the print head.

FIG. 46 is an enlarged view showing a constitutional example of an ejection heater portion capable of changing an ejection ink amount. Here, reference numeral 5000 denotes an edge of the heater board HB described in FIG. 7, and this side face is an ink ejecting opening side with respect to an ejection heater. In the shown example, an ejection heater portion 5013 has two ejecting heaters 5002, 5004. Herein, a size of the ejecting heater 5002 on a front side in an ejection opening direction is $L_f=131$ mm in length and $W_f=22$ mm in width, and a size of the ejecting heater 5003 on a rear side is $L_b=131$ mm in length and $W_b=20$ mm in width. Reference numeral 5001 denotes a common wire which is connected to a ground line. Reference numerals 5003, 5005 are separate wires for driving selectively the heaters 5002, 5004 which are connected to a heater driver for turning on/off a heater.

The two ejecting heaters 5002, 5004 are provided in a single ejection opening, whereby in the case where a fine printing is required, any ejecting heater is driven and a bubble is generated in only a corresponding portion. Thereby, printing is performed with ink dots having a relatively small ejection amount to realize a high resolution. On the other hand, in the case where so-called solid printing is performed, both the heaters are driven and a relatively large bubble covering above them is generated, whereby printing is performed with ink dots having a relatively large ejection amount and printing efficiency can be improved.

In such case where the ejecting ink amount is different, an adjustment value of the dot alignment is different in some cases from a viewpoint of the horizontal scan speed, an ejection speed and an ejection angle. Accordingly, in the case where the above-described dot alignment is carried out only for a single ejection amount, the depositing position is different in some cases even if the adjustment value is used for the other ejection amount.

On the contrary, a dot alignment may be carried out in each size of printing dots. That is, an optimal adjustment value is set on respective printing dots, so that it becomes possible to perform printing at a correct depositing position of the printing dots in the respective printing.

Moreover, a carriage speed (a horizontal scan speed), an ejection speed, an ejection angle and the like are factors of changing the depositing position of the printing dots.

For example, with respect to an offset amount Δa of the depositing position in the case (a) of FIG. 47, an offset amount Δb of the depositing position in the case (b) where an ejection speed is small is increased, and an offset amount Δc of the depositing position in the case (c) where a main scan speed is large is also increased. Accordingly, the dot alignment may be executed in each of the horizontal scan speed, the ejection speed and the ejection angle, and such way is actually effective.

FIG. 48 is an illustration for explaining a dot alignment processings in response to modes included in the printer or a configuration of a head.

Here, "printer 1" is a printer having a configuration as shown in FIG. 5, and indicates that "head 1" or "head 2" can be used. The "head 1" and "head 2" are heads of a form shown in FIG. 6A. The "head 1" has the shown configuration, and at a time of the dot alignment processing,

a registration processing (in vertical and lateral directions between the two heads) in Black dots and C dots in response to each mode or a registration processing (in a bi-directional-horizontal scan direction) of Black dots are performed. The "head 2" has ejecting section in which nozzle groups of Black, LC (thin or light cyan) and LM (thin or light magenta) is arrayed in an inline manner, while has ejecting section in which nozzle groups, etc. of C and M are respectively arrayed in an inline manner in a form of arranging in parallel in response to the nozzle group of LC and LM, and at a time of the dot alignment processing, a registration processing (in vertical and lateral directions between the two heads) in LC dots and C dots in response to each mode or a registration processing (in a bi-directional-horizontal scan direction) of Black dots are performed.

The "printer 2" is a printer which performs monochrome printing, and "head 3" or "head 4" arraying nozzle groups ejecting a Black ink can be used.

Moreover, each head has an ejection heater section as shown in FIG. 46 and can obtain a large or small ejection amount corresponding to a resolution. A main scan speed of each resolution can be decided as follows: For example, 30 inch/sec in the case of 180×180 dpi, 20 inches/sec in the case of 360×360 dpi, 20 inches/sec in the case of 720×720 dpi, and 10 inches/sec in the case of 1440×720 dpi. Moreover, an ink ejection amount of each drop size can be set at 80 pl (picoliter) for "large size" in the "head 1" and "head 4" and 40 pl for "small size", and can be set at 40 pl for "large size" in the "head 2" and "head 3" and 15 pl for "small size".

The adjustment of the embodiment can correspond to a bi-directional printing, and lateral and vertical prints of two heads, and further a two-stage adjustment of a coarse adjustment and a fine adjustment can be performed. As shown in FIG. 48, an appropriate adjustment can be executed in response to a configuration of a printer and a head, a combination of a head and the other, and further the adjustment can be performed in each of a resolution, a main scan speed, an ejection speed, etc., respectively. Moreover, as an ejection angle is different according to mounting precision by a print head or precision in manufacturing, it is preferable that the adjustment is executed in each of print heads required.

And, adjustment values decided in each mode are respectively stored in a nonvolatile memory device such as EEPROM (which can be added to a configuration of the controller 100 of FIG. 9, for example). As described above, a one-time dot alignment is executed in each of printing modes and this is stored, whereby the adjustment values. used in response to a printing mode are read out and it becomes possible to perform printing with the adjustment of an optimal depositing position performed in each mode.

Moreover, record contents of FIG. 48 are examples containing a numeric value, and it is needless to say that the present invention is not limited thereto.

Next, an actual adjustment patterns will be illustrated.

FIG. 49 is a diagram showing the relationship of FIGS. 49A and 49B showing an example of an adjustment pattern, which is formed and utilized in a step of a processing to which a basic processing algorithm of FIG. 45 is applied. The shown pattern is formed corresponding to a size of B5 version (182 mm (2580 dots)×257 mm (3643 dots)), and there are formed, from an upper portion of a page, a patch group (i) formed for the sensor calibration as at step S103 of FIG. 45;

a patch group (ii) of 360×360 dpi formed in the vertical coarse adjustment processing between two heads as at step S104;

a patch group (iii) of 360×360 dpi formed in the bi-directional printing coarse adjustment processing as at step S105 (9 patches formed by offsetting from -4 to +4 at an interval of 1 dot);

a patch group (iv) of 360×360 dpi formed in the bi-directional printing fine adjustment processing as at step S107 (5 patches (a) formed by offsetting from -1 to +1 at an interval of 0.5 dots and 5 patches (b) of the inverted pattern), and a patch group (v) of 180×180 dpi similarly;

a patch group (vi) of 720×720 dpi formed in the bi-directional printing coarse adjustment processing as at step S105 (9 patches formed by offsetting from -4 to +4 at an interval of 1 dot);

a patch group (vii) of 360×360 dpi formed in the lateral coarse adjustment processing between two heads as at step S108 (9 patches formed by offsetting from -4 to +4 at an interval of 1 dot); and

a patch group (viii) of 360×360 dpi formed in the lateral (in particular, forward) fine adjustment processing between two heads as at step S109 (5 patches (a) formed by offsetting from -1 to +1 at an interval of 0.5 dots and 5 patches (b) of the inverted pattern), and a patch group (ix) of 360×360 dpi formed in the lateral (reverse) fine adjustment processing between two heads similarly, and each patch group ((x) to (xiv)) of 180×180 dpi, 720×720 dpi and 1440×720 dpi formed in the lateral (bi-directional) fine adjustment processing between two heads similarly (together with the inverted pattern), and

a confirmation pattern (xv) formed in a processing as at step S111 is added to the end.

The adjustment pattern shown therein includes one corresponding to various printing modes, and for example, in the printing apparatus of a single head which is not performed an adjustment between two heads, the adjustment between two heads is not required and only a bi-directional adjustment may be performed. A printing mode to be used in the printing apparatus has to be only contained.

Moreover, a plurality of patterns (patches) formed in each processing are formed in a separated manner in the illustrated example, but as mentioned above, these may be formed connectedly or successively. That is, if a correspondence of each dot formation position condition in each processing to a pattern formation position is reliable, the plurality of patterns may be formed as a successive single-pattern. Moreover, if a correspondence of each processing and a pattern formation position corresponding thereto is reliable, patterns in processings may be successively.

Moreover, in the case where an ejection speed is different according to a color of used inks, the dot alignment is executed in each color, and the optimal adjustment value of the depositing position may be provided in each color.

Moreover, such adjustment may be performed by one operation for all modes provided in the printing apparatus when a processing procedure is activated, and it may be performed in only a mode designated in response to selection by a user, etc.

Moreover, an activation of the adjustment processing is performed by operations of a start switch, etc. provided in the body of printer, and indication through application of the host device 110, and additionally, for example, taking into consideration a temporal change of each section of the printing apparatus and the head, in the case where the adjustment has not been performed for a long-termed period, an adjustment processing can also be activated or urged

using controlling means such as a timer. Moreover, even in the case where a head cartridge 1000 is exchanged, the adjustment processing can be activated or urged.

7. Manual Adjustment and Others

(7.1) Manual Adjustment

Next, a manual adjustment (step S119 in the processing procedure of FIG. 30 or FIG. 45) which is performed will be described below, when the automatic dot alignment sequence cannot be performed.

In the apparatus according to the embodiment, the detection of density is performed using an optical sensor. Another dot alignment method is therefore necessary, for example, when the optical sensor can not be operated electrically or cannot operate optically. In these cases, manual adjustment should be performed. The conditions for shifting to the manual adjustment will be described below.

In order to use the optical sensor, calibration is performed. In this case, if data obtained is clearly outside the usable range, it is a calibration error and the dot alignment operation is stopped. For example, the case where extremely low power of LED in the optical sensor leads to an extremely small quantity of light applied to a measured object, the case where degradation in detection capability caused by the expiration of the life of a photo transistor etc. leads to low power, or the case where the invasion of external light etc. lead to an extremely large quantity of reflected light detected by the photo transistor or the like are the cases where the optical sensor can not be operated normally.

In these cases, status of that condition is sent to the host computer to display the occurrence of an error via an application. In addition, the display to perform the manual adjustment is performed to urge the execution. Alternatively, when a calibration error is detected, the dot alignment operation is stopped and printing urging to perform the manual adjustment may be performed on a printing medium being fed.

In the manual adjustment, a one-dot ruled line pattern is used. A reference ruled line pattern is printed on a printing medium by the first printing and then a plurality of ruled lines which the relative position condition is different (the ruled line which the offsetting amounts is different) are printed by the second printing. The user observe the printed medium to judge which condition is optimal. Therefore, the position which the depositing positions are registered best is designed to be able to observe at the actual dot position for an easier judgment using a one-dot ruled line.

The manual adjustment includes coarse adjustment and fine adjustment. The latter is performed after the former.

In the coarse adjustment, a ruled line pattern corresponding to tolerance limits of the depositing position which a printing apparatus and its print head have is used. For example, if accuracy of tolerance is ±4 dots, the coarse adjustment shown in FIG. 50A is performed.

In FIG. 50A, each of reference lines and shifted lines is defined to be printed by a printing method to be adjusted. In this case, the illustration is shown, assuming that the depositing position would be registered when the offsetting or shifting amount is just 0 dot.

The user observe such pattern to judge which condition gives the best depositing position (whether the registration is registered or not) to store through entering the adjustment value into the body of the printing apparatus or inputting it from the host apparatus (a menu of a printer driver etc.).

Moreover, in order to perform adjustment with higher accuracy, the fine adjustment is performed by printing the pattern shown in FIG. 50B.

In FIG. 50B, the adjustment is performed every 0.5 dots, but it can be selected according to adjustment capability

(resolution and accuracy of adjustment) which a printing apparatus has. As in the coarse adjustment, the user judges which condition gives the best depositing position (whether the registration is registered or not) to perform adjustment. The fine adjustment where adjustment is performed with higher accuracy can be performed on the assumption that the depositing position are adjusted to a certain extent by the coarse adjustment. Without the coarse adjustment, reference lines and shifted lines could be printed on quite different positions respectively. It happens in principle when dot alignment is performed using such a simple ruled line. In this case, only one point is given as the value for adjustment. (7.2) Difference between the Manual Adjustment and the Automatic Alignment

In the above automatic dot alignment, on the other hand, reflection density values (or output values of the optical sensor) are measured and a value for adjustment is determined from the measured values. Unlike the manual adjustment, therefore, fine adjustment can be performed without coarse adjustment.

The image patterns used in the automatic dot alignment are ones for measuring reflection density. As in FIG. 37, for example, patterns with the same width are printed by the first and second prints respectively. Each patch (a solid pattern of 100% or a pattern thinned out to a certain extent at need) is finally printed. Not the position but reflection density of its printed dots is measured using an optical sensor. And an optimal adjusting point for the depositing position is determined based on the characteristics of the reflection density.

The cases where adjusting patterns shown in FIGS. 37 and 39 are used will be considered below.

FIG. 51A shows reflection density when a 4-dot pattern shown in FIG. 37 is shifted beyond the adjustment limits.

Each patch consists of two pattern elements of 4 dots horizontally arranged (the first printing and the second printing). Therefore, if the pattern elements are shifted each other beyond the adjustment limits and the width from +4 to -4 (8 dots) is considered as one cycle, the maximum or minimum value exists in this range and the very same density characteristic will repeat itself at this cycle. That is to say, this characteristic has features as a trigonometric function and can be represented as $A \cos \theta$. Wherein A represents two times amplitude or the difference between the maximum density and the minimum density, n represents offsetting or shift amount by the dot, and m represents the width of accuracy of tolerance or tolerance range; $\theta = 2\pi n/m$.

That is to say, in this automatic dot alignment processing, a plurality of adjusting points exist in terms of density because of simply taking reflection density into consideration (for example, with a point giving the maximum reflection density as a value for adjustment, three points in the above figure correspond to values for adjustment: +8, 0, and -8). However, accuracy of tolerance of the depositing position which a printing apparatus and its print head have is finite. For example, if accuracy of tolerance is ± 4 dots, as is stated above, the maximum and minimum density values are within this range. That is to say, this range includes one cycle. Conversely, determining the width of a pattern used for the coarse adjustment according to accuracy of tolerance of deposition positions which a printing apparatus and its print head have (making width in two pattern elements wider than tolerance limits) ensures the above relationship.

In this way, if an adjusting unit of 1 dot is used, dot alignment can be performed with an accuracy of at least ± 1 dot from this density characteristic. But it depends on accuracy of adjustment.

FIG. 51B shows the result of a one-dot pattern shown in FIG. 39 being shifted beyond the adjustment limits in the fine adjustment.

As in FIG. 37, each patch consists of two one-dot pattern elements (the first and second prints). Therefore, if the pattern elements are shifted each other beyond the adjustment limits and the width from +1 to -1 (two dots) is considered as one cycle, the maximum or minimum value exists in this range and the very same density characteristic will repeat itself at this cycle.

The dot alignment will be considered below. A plurality of adjusting points considered from the density exist. For example, with a point giving the maximum reflection density as a value for adjustment, three points in the above figure correspond to values for adjustment: +2, 0, and -2. Actually, becoming resolution of a fine increment. At this point, an adjusting point for the depositing position may be any one of these three points. Because the fine adjustment will be performed within one dot in the range.

The coarse adjustment with an accuracy of ± 1 dot has been performed and, therefore, the optimal point of the above three can be identified.

The coarse adjustment is a method of coarsely adjusting within accuracy of tolerance of depositing positions which a printing apparatus and its print head have, while the fine adjustment is a method of adjusting with the highest accuracy which the printing apparatus can attain. They are different from each other in adjusting range and adjusting unit.

The two methods can be performed in any order. That is to say, the coarse adjustment may be performed first or the fine adjustment may be performed first. Because they are different in adjusting unit and they do not affect each other's characteristics. And because the above cyclic characteristic exists. This is the greatest difference between the manual adjustment according to the present invention and common manual adjustment. The two methods different in adjusting range and adjusting unit are combined to quickly obtain a correct value for adjustment without wasting printing media.

As stated above, an adjusting pattern used for the manual adjustment is quite different from that used for the automatic dot alignment.

A printing method or printing apparatus to which the present invention applies is characterized by having these two adjusting patterns different from each other in characteristic and can use one of these two adjusting patterns as required. When an optical sensor can not be operated electrically or cannot be used optically by the influence of external light etc., as stated above, the depositing position can be adjusted using the manual adjustment.

8. Others

In each of the above embodiments, an example of an ink jet printing apparatus in which the ink is ejected from its print head on a printing medium to form an image has been shown. However, the present invention is not limited to this configuration. The present invention is also applicable to a printing apparatus of any type which performs printing by moving its print head and a printing medium relatively and to form dots.

However, in the case that an ink jet printing method is applied, the present invention achieves distinct effect when applied to a recording head or a recording apparatus which has means for generating thermal energy such as electrothermal transducers or laser light, and which causes changes in ink by the thermal energy so as to eject ink. This is because such a system can achieve a high density and high resolution recording.

A typical structure and operational principle thereof is disclosed in U.S. Pat. Nos. 4,723,129 and 4,740,796, and it

is preferable to use this basic principle to implement such a system. Although this system can be applied either to on-demand type or continuous type ink jet recording systems, it is particularly suitable for the on-demand type apparatus. This is because the on-demand type apparatus has electrothermal transducers, each disposed on a sheet or liquid passage that retains liquid (ink), and operates as follows: first, one or more drive signals are applied to the electrothermal transducers to cause thermal energy corresponding to recording information; second, the thermal energy induces sudden temperature rise that exceeds the nucleate boiling so as to cause the film boiling on heating portions of the recording head; and third, bubbles are grown in the liquid (ink) corresponding to the drive signals. By using the growth and collapse of the bubbles, the ink is expelled from at least one of the ink ejection orifices of the head to form one or more ink drops. The drive signal in the form of a pulse is preferable because the growth and collapse of the bubbles can be achieved instantaneously and suitably by this form of drive signal. As a drive signal in the form of a pulse, those described in U.S. Pat. Nos. 4,463,359 and 4,345,262 are preferable. In addition, it is preferable that the rate of temperature rise of the heating portions described in U.S. Pat. No. 4,313,124 be adopted to achieve better recording.

U.S. Pat. Nos. 4,558,333 and 4,459,600 disclose the following structure of a recording head, which is incorporated to the present invention: this structure includes heating portions disposed on bent portions in addition to a combination of the ejection orifices, liquid passages and the electrothermal transducers disclosed in the above patents. Moreover, the present invention can be applied to structures disclosed in Japanese Patent Application Laying-open Nos. 123670/1984 and 138461/1984 in order to achieve similar effects. The former discloses a structure in which a slit common to all the electrothermal transducers is used as ejection orifices of the electrothermal transducers, and the latter discloses a structure in which openings for absorbing pressure waves caused by thermal energy are formed corresponding to the ejection orifices. Thus, irrespective of the type of the recording head, the present invention can achieve recording positively and effectively.

The present invention can be also applied to a so-called full-line type recording head whose length equals the maximum length across a recording medium. Such a recording head may consist of a plurality of recording heads combined together, or one integrally arranged recording head.

In addition, the present invention can be applied to various serial type recording heads: a recording head fixed to the main assembly of a recording apparatus; a conveniently replaceable chip type recording head which, when loaded on the main assembly of a recording apparatus, is electrically connected to the main assembly, and is supplied with ink therefrom; and a cartridge type recording head integrally including an ink reservoir.

It is further preferable to add a recovery system, or a preliminary auxiliary system for a recording head as a constituent of the recording apparatus because they serve to make the effect of the present invention more reliable. Examples of the recovery system are a capping means and a cleaning means for the recording head, and a pressure or suction means for the recording head. Examples of the preliminary auxiliary system are a preliminary heating means utilizing electrothermal transducers or a combination of other heater elements and the electrothermal transducers, and a means for carrying out preliminary ejection of ink independently of the ejection for recording. These systems are effective for reliable recording.

The number and type of recording heads to be mounted on a recording apparatus can be also changed. For example, only one recording head corresponding to a single color ink, or a plurality of recording heads corresponding to a plurality of inks different in color or concentration can be used. In other words, the present invention can be effectively applied to an apparatus having at least one of the monochromatic, multi-color and full-color modes. Here, the monochromatic mode performs recording by using only one major color such as black. The multi-color mode carries out recording by using different color inks, and the full-color mode performs recording by color mixing.

Furthermore, although the above-described embodiments use liquid ink, inks that are liquid when the recording signal is applied can be used: for example, inks can be employed that solidify at a temperature lower than the room temperature and are softened or liquefied in the room temperature. This is because in the ink jet system, the ink is generally temperature adjusted in a range of 30° C.-70° C. so that the viscosity of the ink is maintained at such a value that the ink can be ejected reliably.

In addition, the present invention can be applied to such apparatus where the ink is liquefied just before the ejection by the thermal energy as follows so that the ink is expelled from the orifices in the liquid state, and then begins to solidify on hitting the recording medium, thereby preventing the ink evaporation: the ink is transformed from solid to liquid state by positively utilizing the thermal energy which would otherwise cause the temperature rise; or the ink, which is dry when left in air, is liquefied in response to the thermal energy of the recording signal. In such cases, the ink may be retained in recesses or through holes formed in a porous sheet as liquid or solid substances so that the ink faces the electrothermal transducers as described in Japanese Patent Application Laying-open Nos. 56847/1979 or 71260/1985. The present invention is most effective when it uses the film boiling phenomenon to expel the ink.

Furthermore, the ink jet recording apparatus of the present invention can be employed not only as an image output terminal of an information processing device such as a computer, but also as an output device of a copying machine including a reader, and as an output device of a facsimile apparatus having a transmission and receiving function.

Additionally, in the above embodiments, the processing of printing registration is carried out in the side of the printing apparatus. The processing may be carried out in the side of a host computer or the like, appropriately. That is, though a printer driver installed in the host computer 110 shown in FIG. 9 is designed to supply image data made to the printing apparatus, in addition to this, the printer driver may be designed to make test patterns (printing patterns) for printing registration and to supply them to the printing apparatus, and further designed to receive values read from the test patterns, by an optical sensor on the printing apparatus for calculating adjustment amount.

Further, a printing system, in which program codes of software or the printer driver for realizing the foregoing functions in the embodiments are supplied to a computer within the machine or the system connected to various devices including the printing apparatus in order to operate various devices for realizing the function of the foregoing embodiment, and the various devices are operated by the programs stored in the computer (CPU or MPU) in the system or machine, is encompassed within the scope of the present invention.

Also, in this case, the program codes of the software per se performs the functions of the foregoing embodiment.

Therefore, the program codes per se, and means for supplying the program codes to the computer, such as a storage medium storing, are encompassed within the scope of the present invention.

As the storage medium storing the program codes. floppy disk, a hard disk, an optical disk, a CD-ROM, a magnetic tape, a non-volatile memory card, ROM and the like can be used, for example.

In addition, the function of the foregoing embodiments is realized not only by executing the program codes supplied to the computer but also by cooperatively executing the program codes together with an OS (operating system) active in the computer or other application software. Such system is also encompassed within the scope of the present invention.

Furthermore, a system, in which the supplied program codes are one stored in a function expanding board of the computer or a memory provided in a function expanding unit connected to the computer, and then a part of or all of processes are executed by the CPU or the like provided in the function expanding board or the function expanding unit on the basis of the command from the program code, is also encompassed within the scope of the present invention.

According to the invention, an optimal value for the adjustment of the depositing position of the printed dots can be obtained with high accuracy in the first and second printing of each of the forward scan and the reverse scan which the mutual dot-formed positions should be adjusted or the first and second printing of each of a plurality of the print heads. Therefore, a printing method and a printing apparatus can be provided in that the bi-directional printing or printing using a plurality of print heads is performed without the offset in depositing positions.

In addition, an apparatus or system which can printing a high-quality image at high speed can be achieved at low cost without problems about the formation of an image or operation.

Furthermore, this method can be contributed in the further improvement in accuracy by properly calibrating an optical sensor capable of applying for such dot alignment method and others, at the time when performing the processing of the above dot alignment or obtaining information of any kind from an object to be measured, or processing in response to the information, therefore, of performing the processing in response to the information.

The present invention has been described in detail with respect to preferred embodiments, and it will now be apparent from the foregoing to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspect, and it is the invention, therefore, in the apparent claims to cover all such changes to cover all such changes and modifications as fall within the true spirit of the invention.

What is claimed is:

1. A printing registration method for processing for performing printing registration in a first printing and a second printing with a printing apparatus for performing printing of an image by the first printing and the second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, said method comprising the steps of:

pattern-forming for controlling the printing head to form a plurality of patterns having optical characteristics corresponding to a plurality of shifting amounts, the plurality of patterns being formed corresponding to the plurality of shifting amounts of relative printing posi-

tions of the first printing and the second printing, the patterns being formed by the first printing and the second printing;

measuring, by an optical sensor, optical characteristics of the plurality of patterns formed;

calibrating an optical sensor being used in order to perform the measurement,

wherein said calibrating step includes forming patterns for performing the calibration; and

acquiring an adjustment value of a dot forming position condition between the first printing and the second printing on the basis of optical characteristics of the plurality of patterns measured.

2. A printing registration method as claimed in claim 1, wherein the optical sensor has a light-emitting portion and a photosensing portion, and said calibrating step includes the steps of:

modulating electric signals supplied to the light-emitting portion and the photosensing portion;

measuring, by the optical sensor, optical characteristics of a plurality of patterns having different optical characteristics;

allowing to perform the measurement of every amount of the modulation of a plurality of steps; and

acquiring an amount of modulation capable of obtaining a predetermined measurement range.

3. A printing registration method as claimed in claim 1, wherein the optical sensor has a light-emitting portion and a photosensing portion, and said calibrating step includes the steps of:

modulating electric signals supplied to the light-emitting portion and the photosensing portion;

measuring, by the optical sensor, optical characteristics of patterns having predetermined optical characteristics;

allowing to perform the measurement of every amount of the modulation of a plurality of steps;

comparing a measured value of every amount of modulation with a predetermined threshold value; and

selecting an amount where the measured value coincides with or at most is approximately equal to the threshold value as the amount of modulation which the predetermined measurement range is obtained, as a result of the comparison.

4. A printing registration method as claimed in claim 1, wherein the optical sensor has a light-emitting portion and a photosensing portion and said calibrating step includes the steps of:

modulating electric signals supplied to the light-emitting portion and the photosensing portion;

measuring, by the optical sensor, optical characteristics of patterns having predetermined characteristics;

allowing to perform the measurement of every amount of modulation of a plurality of steps;

comparing a measured value of every amount of modulation with a predetermined threshold value;

selecting an amount where the measured value coincides with or at most is approximately equal to the threshold value, as a result of the comparison;

measuring, by the optical sensor, optical characteristics of a plurality of patterns having different optical characteristics, while modulating in a plurality of steps in the vicinity of the selected amount of modulation; and

acquiring an amount of modulation capable of obtaining the predetermined measurement range.

5. A printing registration method as claimed in claim 1, wherein the first printing and the second printing include at least one among a printing in a forward scan and in a reverse scan upon performing printing by bi-directionally scanning the printing head with respect to the printing medium, a printing being a printing by a first printing head and a printing by a second printing head among a plurality of the printing heads in a direction in which the first printing head and the second printing head are relatively scanned with respect to the printing medium, and a printing being a printing by a first printing head and a printing by a second printing head among a plurality of printing heads, respectively, in a direction different from the direction which the first printing head and the second printing head are relatively scanned with respect to the printing medium.

6. A printing registration method as claimed in claim 1, wherein said adjustment value acquiring step derives the adjustment value by calculation employing continuous values on the basis of optical characteristics data obtained from said measuring step by using a linear approximation or a polynomial approximation.

7. A printing registration method as claimed in claim 1, wherein said adjustment value acquiring step includes deriving a printing registration condition including also a printing position parameter more precise than the printing registration condition or a printing position parameter different from the print registration condition.

8. A printing registration method as claimed in claim 1, wherein said pattern-forming step performs a pattern formation in a pitch looser than a pitch of the printing position capable of controlling in the printing apparatus.

9. A printing registration method as claimed in claim 1, wherein, in said pattern-forming step, the dots formed by the first printing and the dots formed by the second printing are arranged, and relative positional relationship of the dots is varied corresponding to the plurality of shifting amount, and a ratio of the dots covering the printing medium is varied, therein to form the plurality of patterns having optical characteristics corresponding to the shifting amounts.

10. A printing registration method as claimed in claim 1, wherein, in response to the performance of said optical sensor, a color tone of a printing agent is used to calibrate the optical sensor, and the formation of patterns is used in the printing registration.

11. A printing registration method as claimed in claim 10, wherein selection of the color tone of the printing agent is performed in response to optical spectrum characteristics of the optical sensor.

12. A printing registration method as claimed in claim 1, wherein the printing registration is performed with respect to the printing apparatus using a first printing head and a second printing head which are arranged in parallel in the scanning direction, on the first printing head a plurality of printing elements for imparting printing agent to the printing medium being arranged at spacing equally in-line in a direction different from the scanning direction, therein performing the first printing, and on the second printing head a plurality of printing elements for imparting the printing agent to the printing medium being arranged at spacing equally in-line in a direction different from the scanning direction, therein performing the second printing.

13. A printing registration method as claimed in claim 12, wherein the printing head for performing the first printing is a printing head using at least one printing agent, and the printing head for performing the second printing is a printing head using a plurality of printing agents of color tones among which at least one color tone is different from the color tone of the printing agent used by the first printing head.

14. A printing registration method as claimed in claim 12, wherein the printing head for performing the first printing is a print head using a black printing agent and the print head for performing the second printing is the printing head using a cyan, magenta, and yellow printing agents, and the optical sensor has a light-emitting portion of red light, and wherein the black and the cyan printing agents are selected corresponding to the light emitting portion and to contribute to the printing registration.

15. A printing registration method as claimed in claim 1, further comprising an interruption step, said printing registration including the calibration processing where any error occurs during the calibration of the optical sensor.

16. A printing registration method as claimed in claim 15, further comprising a step of performing, or stimulating, processing for other performable printing registration during said interruption step.

17. A printing registration method as claimed in claim 16, wherein the processing for the other printing registration includes a processing using means for performing adjustment for the printing registration by a manual operation.

18. A printing registration method as claimed in claim 1, wherein the printing head is a head for performing printing by ejecting the ink.

19. A printing registration method as claimed in claim 18, wherein the printing head includes heating elements for generating thermal energy to make the ink to film boil, as an energy used for ejecting the ink.

20. A printing apparatus for performing printing of an image by a first printing and a second printing with predetermined conditions of a dot forming position on a printing medium by-using a printing head, comprising:

patterns-forming means for controlling a printing head to form a plurality of patterns having optical characteristics corresponding to a plurality of shifting amounts, said plurality of patterns being formed corresponding to said plurality of shifting amounts of relative printing positions of said first printing and said second printing, said patterns being formed by said first printing and said second printing;

means for measuring optical characteristics of the related plurality of patterns formed;

means for calibrating an optical sensor being used in order to perform said measurement,

wherein said calibrating means includes a means for forming patterns for performing said calibration; and acquiring means for obtaining an adjustment value of dot forming position conditions between said first printing and said second printing on the basis of optical characteristics of said plurality of patterns measured.

21. A printing apparatus as claimed in claim 20, wherein said optical sensor has a light-emitting portion and a photosensing portion, and said calibrating means includes:

means for modulating electric signals supplied to said light-emitting portion and said photosensing portion;

means for measuring the optical characteristics of a plurality of patterns having different optical characteristics by said optical sensor;

means for allowing to perform the measurement of every amount of said modulation of a plurality of steps; and means for acquiring an amount of modulation capable of obtaining the predetermined measurement range.

22. A printing apparatus as claimed in claim 20, wherein said optical sensor has a light-emitting portion and a photosensing portion, and said calibrating means includes:

means for modulating electric signals supplied to said light-emitting portion and said photosensing portion;

means for measuring optical characteristics of patterns having a predetermined optical characteristics by said optical sensor;

means for allowing to perform said measurement of every amount of said modulation of a plurality of steps;

means for comparing a measured value of every said amount of modulation with a predetermined threshold value; and

means for selecting an amount where said measured value coincides with or at most is approximately equal to said threshold value as the amount of modulation which the predetermined measurement range is obtained, as a result of said comparison.

23. A printing apparatus as claimed in claim **20**, wherein said optical sensor has a light-emitting portion and a photosensing portion and said calibrating means includes:

means for modulating electric signals supplied to said light-emitting portion and said photosensing portion;

means for measuring, by the optical sensor, optical characteristics of patterns having predetermined characteristics;

means for allowing to perform said measurement of every amount of modulation of a plurality of steps;

means for comparing a measured value of every said amount of modulation with a predetermined threshold value; means for selecting an amount where said measured value coincides with or at most is approximately equal to said threshold value, as a result of said comparison;

means for measuring optical characteristics of a plurality of patterns having different optical characteristics by said optical sensor, while modulating in a plurality of steps in the vicinity of said selected amount of modulation; and

means for acquiring an amount-of modulation capable of obtaining the predetermined measurement range.

24. A printing apparatus as claimed in claim **20**, wherein said first printing and said second printing include at least one among a printing in a forward scan and in a reverse scan upon performing printing by bi-directionally scanning said printing head with respect to said printing medium, a printing being a printing by a first printing head and a printing by a second printing head among a plurality of printing heads, respectively, in a direction in which said first printing head and said second printing head are relatively scanned with respect to said printing medium, and a printing being a printing by a first printing head and a printing by a second printing head among a plurality of print heads, respectively, in a direction different from the direction which said first print head and said second print head are relatively scanned with respect to said printing medium.

25. A printing apparatus as claimed in claim **20**, wherein said adjustment value acquiring means derives said adjustment value by calculation employing continuous values on the basis of optical characteristics data obtained from said measuring means by using a linear approximation or a polynomial approximation.

26. A printing apparatus as claimed in claim **20**, wherein said adjustment value acquiring means includes means for deriving a printing registration condition including also a printing position parameter more precise than said printing registration condition or a printing position parameter different from said print registration condition.

27. A printing apparatus as claimed in claim **20**, wherein said pattern-forming means performs a pattern formation in a pitch looser than a pitch of the printing position capable of controlling in said printing apparatus.

28. A printing apparatus as claimed in claim **20**, wherein, in said pattern-forming means, the dots formed by said first printing and the dots formed by said second printing are arranged, and relative positional relationship of said dots is varied corresponding to said plurality of shifting amount, and a ratio of said dots covering said printing medium is varied, therein to form said plurality of patterns having optical characteristics responsive to said shifting amounts.

29. A printing apparatus as claimed in claim **20**, wherein, in response to the performance of said optical sensor, a color tone of a printing agent is used in said calibration of said optical sensor, and said formation of patterns is used in said printing registration.

30. A printing apparatus as claimed in claim **29**, wherein selection of the color tone of said printing agent is performed in response to optical spectrum characteristics of said optical sensor.

31. A printing apparatus as claimed in claim **20**, wherein printing registration is performed with respect to the printing apparatus using a first printing head and a second printing head which are arranged in parallel in said scanning direction, or said first printing head a plurality of printing elements for imparting printing agent to said printing medium being arranged at spacing equally in-line in a direction different from said scanning direction, therein performing said first printing, and on said second printing head a plurality of printing elements for imparting printing agent to said printing medium being arranged at spacing equally in-line in a direction different from said scanning direction, therein performing said second printing.

32. A printing apparatus as claimed in claim **31**, wherein said printing head for performing said first printing is a printing head using at least one printing agent and the printing head for performing said second printing is a printing head using a plurality of printing agents of color tones among which at least one color tone is different from said color tone of said printing agent used by said first printing head.

33. A printing apparatus as claimed in claim **32**, wherein the printing head for performing said first printing is a print head using a black printing agent and the print head for performing said second printing is the printing head using a cyan, magenta and yellow printing agents, and said optical sensor has a light-emitting portion of red light, and wherein said black and said cyan printing agents are selected corresponding to said light emitting portion and to contribute to said printing registration.

34. A printing apparatus as claimed in claim **20**, further comprising means for interrupting said printing registration including the calibration processing where any error occurs during the calibration of said optical sensor.

35. A printing apparatus as claimed in claim **34**, further comprising means for performing or stimulating the processing for other performable printing registration during said interruption.

36. A printing apparatus as claimed in claim **35**, further comprising means for performing adjustment for said printing registration by a manual operation, and wherein the processing for said other printing registration includes the adjustment using said means.

37. A printing apparatus as claimed in claim **20**, wherein said printing head is a head for performing printing by ejecting the ink.

38. A printing apparatus as claimed in claim **37**, wherein said printing head includes heating elements for generating thermal energy to make the ink to film boil, as an energy for ejecting the ink.

57

39. A printing system provided with a printing apparatus for performing printing of an image by a first printing and a second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, and a host apparatus for supplying an image data to said printing apparatus, comprising:

patterns-forming means for controlling a printing head to form a plurality of patterns having optical characteristics corresponding to said plurality of shifting amounts, said plurality of patterns being formed corresponding to said plurality of shifting amounts of relative printing positions of said first printing and said second printing, said patterns being formed by said first printing and said second printing;

measuring means for measuring optical characteristics of the related plurality of patterns formed; and

means for calibrating an optical sensor being used in the related measurement,

wherein said calibrating means includes a means for forming patterns for performing said calibration; and
 acquiring means for obtaining an adjustment value of dot forming position condition between said first printing and said second printing on the basis of optical characteristics of said plurality of patterns measured.

40. A storage medium which is connected to an information processing apparatus and a program stored in which is readable by the information processing apparatus, said pro-

58

gram being for making a printing system to perform a method for processing for performing printing registration in a first printing and a second printing with a printing apparatus for performing printing of an image by said first printing and said second printing with predetermined conditions of a dot forming position on a printing medium by using a printing head, said method comprising the steps of:

pattern-forming for controlling said printing head to form a plurality of patterns having optical characteristics corresponding to a plurality of shifting amounts, said plurality of patterns being formed corresponding to said plurality of shifting amounts of relative printing positions of said first printing and said second printing, said patterns being formed by said first printing and said second printing;

measuring, by an optical sensor, optical characteristics of said plurality of patterns formed;

calibrating the optical sensor being used in order to perform said measurement,

wherein said calibrating step includes forming patterns for performing the calibration; and

acquiring an adjustment value of a dot forming position condition between said first printing and said second printing on the basis of optical characteristics of said plurality of patterns measured.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 1 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, FOREIGN PATENT DOCUMENTS,

“59123670” should read -- 59-123670 --;

“59138461” should read -- 59-138461 --;

“4227578 A” should read -- 4-227578 A --; and

“09074467” should read -- 09-074467 --.

Item [57], **ABSTRACT**,

Line 6, “plurality” should read -- plurality of --; and

Line 15, “registrating.” should read -- registering. --.

Drawings,

Sheet 31, FIG. 30, “CONFIRMATING” should read -- CONFIRMING --.

Sheet 41, FIGs. 40B and 40C, “WHICH” should read -- IN WHICH --.

Sheet 42, FIG. 41, “WHICH” should read -- AT WHICH --.

Sheet 46, FIG. 45, “RECOED” should read -- RECORD --.

Sheet 48, FIG. 47, “WHICH” (both occurrences) should read -- IN WHICH --.

Column 1,

Line 36, “patterns.” should read -- pattern. --;

Line 45, “printing-out” should read -- printing out --;

Line 45, “are” should read -- is --; and

Line 53, “the” should be deleted.

Column 2,

Line 1, “which” should read -- in which --;

Line 18, “on” should be deleted;

Line 27, “as-an” should read -- as an --;

Line 41, “is” should read -- are --;

Line 44, “an” should be deleted;

Line 57, “are” should read -- is --;

Line 60, “drawings.” should read -- drawing. --; and

Line 63, “that” should read -- in which --.

Column 3,

Line 6, “that an area factor can not” should read -- in which an area factor cannot --;

Line 9, “each” should read -- with each --;

Line 16, “of” should read -- to --;

Line 28, “nozzle-forms” should read -- nozzle forms --; and “of” should be deleted;

Line 41, “becomes” should read -- become --; and

Line 46, “complemental” should read -- complimentary to --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 2 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4,

Lines 7 and 29, "has" should read -- have --;
Lines 25 and 63, "been" should be deleted;
Line 52, "as" should be deleted;
Line 56, "seen, moreover, when" should read -- seen. Moreover, when --;
Line 56, "for" should be deleted;
Line 58, "easy to be" should read -- easily --.

Column 5,

Line 5, "one" should read -- over --;
Line 9, "each" should read -- with each --;
Line 20, "the image that" should read -- in the image --;
Line 34, "which" should read -- in which --;
Line 36, "easy to be" should read -- easily --;
Line 38, "suppressed occurrence" should read -- suppress occurrence --;
Line 50, "should printing" should read -- needs to print --;
Line 58, "occurring" should read -- occurrence of --;
Line 60, "is" should read -- be --; and
Line 60, "to be able" should read -- the ability --.

Column 6,

Line 18, "provided." should read -- provided --;
Line 36, "portion." should read -- portion; --;
Lines 38 and 56, "an" should be deleted;
Lines 38 and 56, "a" should be deleted; and
Lines 46 and 64, "to" should be deleted.

Column 7,

Line 8, "respective" should read -- respect --;
Line 44, "of-the" should read -- of the --; and
Line 60, "patterns-forming" should read -- pattern forming --.

Column 8,

Line 1, "measuring-respective" should read -- measuring respective --;
Line 3, "and" should be deleted;
Line 13, "in" should be deleted;
Line 16, "for performing" should be deleted;
Line 17, "respective" should read -- respect --;
Line 42, "positions" should read -- position --;
Line 47, "planer" should read -- planar --;
Line 52, "to" should be deleted;
Line 52, "of" should be deleted;
Line 55, "adjoined" should read -- adjoined to --;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 3 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 8 (cont'd),

Line 59, "which" should read -- in which --;
Line 61, "are" should read -- is --; and
Line 67, "change," should read -- to change, --.

Column 9,

Line 3, "using this" should read -- Using these --;
Line 6, "have" should read -- has --;
Line 18, "represent to form" should read -- represents forming --;
Line 24, "to" should be deleted;
Line 40, "be occurred" should read -- occur --;
Line 43, "from generating" should read -- genetation of --; and
Line 46, "a" should read -- an --.

Column 10,

Line 33, "a" should read -- is a --.

Column 11,

Lines 35, 48, 54, 58 and 66, "using" should read -- being used --;
Lines 45 and 50, "an" should be deleted; and
Line 60, "manner" should read -- manner of --.

Column 12,

Lines 4, 8, 13, 18, 25 and 27, "using" should read -- being used --;
Line 5, "a" (second and third occurrences) should be deleted;
Line 29, "a" (second occurrence) should read -- an --; and
Line 66, "which" should read -- in which --.

Column 13,

Line 9, "density" should read -- densities --;
Line 24, "consideration-of" should read -- consideration of --;
Line 31, "is" should read -- are --;
Line 44, "is" should read -- has --;
Line 50, "has" should read -- is --; and
Line 61, "made" should read -- is made --.

Column 14,

Line 1, "which" should be deleted;
Line 6, "have" should read -- has --;
Line 20, "Corresponding" should read -- Corresponding to --;
Line 21, "every each" should read -- each and every --;
Line 23, "is easy to be identified." should read -- can be easily identified. --;
Line 25, "obviously." should read -- certainly. --;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 4 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 14 (cont'd),

Line 29, "of" should be deleted;
Line 42, "alignment" should read -- alignment for --;
Line 61, "were" should read -- was --; and
Line 66, "be failed" should read -- fail --.

Column 15,

Line 2, "disturbance" should be deleted;
Line 3, "light" should read -- light disturbance --;
Line 5, "It" should read -- it --;
Line 7, "were" should read -- was --;
Line 16, "processing" should read -- processings --;
Line 23, "to make to certainly perform" should read -- ensure performance of --;
Line 42, "are" should read -- is --;
Line 49, "the" should be deleted;
Line 56, "has" should read -- having --;
Line 59, "been" should be deleted; and
Line 65, "ejection" should read -- ejections --.

Column 16,

Line 2, "excessive" should read -- excess --;
Line 8, "ejection" should read -- ejections --;
Line 10, "the-elapsed" should read -- the elapsed --;
Line 19, "is preferably embodied" should read -- preferably embodies --; and
Line 50, "on" should read -- in --.

Column 17,

Line 4, "being able" should read -- be able to --;
Line 6, "an" should be deleted;
Line 7, "inks," should read -- ink, --;
Line 13, "with" should be deleted;
Line 14, "cable" should read -- cable, --;
Line 20, "a" should be deleted;
Line 24, "perspective-view" should read -- perspective view --;
Line 50, "ink" should read -- inks --;
Line 51, "can not" should read -- cannot --;
Line 54, "ink," should read -- inks, --;
Line 57, "cartridge" should read -- cartridges --; and
Line 58, "independent" should read -- independent from --.

Column 18,

Line 19, "mixed" should read -- mixed with --;
Line 37, "constituted" should read -- constituted of --;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 5 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 18 (cont'd),

Line 37, "of to be" should read -- it is --; and
Line 56, "exchange" should read -- exchanges --.

Column 19,

Line 36, "bit," should read -- bits, --;
Line 41, "variously" should read -- varying --;
Line 51, "under" should be deleted;
Line 51, "nozzle" should read -- nozzles --;
Line 58, "capacity-of" should read -- capacity of --; and
Line 67, "apparatus every each kind," should read -- apparatus, --.

Column 20,

Line 5, "printing,is" should read -- printing is --;
Line 6, "send" should read -- sent --;
Line 8, "a" (first occurrence) should be deleted;
Line 13, "rent" should read -- rently --;
Line 27, "transmission." should read -- transmissions. --;
Line 46, "a" should be deleted; and
Line 57, "supplying" should read -- supplying it --.

Column 21,

Line 17, "scan." should read -- scans. --; and
Line 46, "is" should read -- be --.

Column 22,

Line 1, "referred" should read -- referred to --; and
Line 53, "a" should read -- an --.

Column 23,

Line 30, "is" should read -- are --.

Column 24,

Line 33, "refection" should read -- reflection --.

Column 25,

Line 5, "of" should be deleted;
Line 37, "scan" should read -- scans --;
Line 56, "with:" should read -- with --; and
Line 60, "cope" should read -- cope with --.

Column 26,

Line 1, "This pattern is" should read -- These patterns are --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 6 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 27,

Line 45, "13C" should read -- **23C** --.

Column 29,

Line 5, "are" should read -- is --.

Column 30,

Line 30, "record" should read -- recording --;
Line 55, "are" should read -- is --;
Line 61, "recover" should read -- recovery --; and
Line 62, "operations" should read -- operation --.

Column 31,

Lines 9, 58 and 59, "is" should read -- be --;
Line 23, "is," should read -- is --;
Lines 31 and 34, "ejection" should read -- ejections --;
Line 36, "recover" should read -- recovery --;
Line 41, "a disused" should read -- an unused --; and
Line 46, "ejection," should read -- ejections, --.

Column 32,

Line 11, "photosensing-side," should read -- photosensing side, --;
Line 18, "is" should read -- be --;
Line 38, "that" should read -- in which --; and
Line 48, "are" should read -- is a --.

Column 33,

Lines 10, 18 and 56, "which" should read -- in which --;
Line 15, "side." should read -- side --;
Line 22, "can" should read -- it can --;
Line 30, "every" should read -- for --;
Line 37, "designed" should read -- be designed --;
Line 41, "being formed patches" should read -- having patches being formed --; and
Line 56, "is" should be deleted.

Column 34,

Line 1, "example" should read -- examples --;
Line 23, "lights" should read -- light --;
Line 43, "to" should be deleted; and
Line 49, "an" should read -- a --.

Column 35,

Line 18, "which" should read -- in which --; and
Line 54, "characteristics" should read -- characteristic --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 7 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 36,

Line 40, "which" should read -- at which --.

Column 37,

Line 14, "can" should read -- can be --;
Lines 26 and 37, "which" should read -- in which --;
Line 33, "obtained" should read -- be obtained --;
Line 36, "dot" (first occurrence) should read -- dots --;
Line 37, "are contacted" should read -- contact --;
Line 48, "to" (second occurrence) should be deleted;
Line 52, "are" should read -- to --;
Line 54, "are" should read -- is --;
Line 59, "dot" should read -- dots --; and
Line 62, "reference" should read -- in reference --.

Column 38,

Line 8, "this" should read -- these --;
Line 11, "have" should read -- has --;
Line 22, "an" should be deleted; and
Line 46, "two-dots" should read -- two dots --.

Column 39,

Line 41, "is" should read -- be --;
Line 42, "printing" should read -- by printing --; and
Line 67, "is" (second occurrence) should read -- be --.

Column 40,

Line 19, "(steps" should read -- (step --; and
Line 56, "an" should be deleted.

Column 41,

Line 31, "is" should read -- be --.

Column 42,

Line 1, "is substantially performed" should read -- substantially performs --; and
Line 15, "that" should be deleted.

Column 43,

Line 61, "processings" should read -- processing --.

Column 44,

Line 6, "is" should read -- are --;
Line 6, "has" should read -- having --;
Line 14, "are" should read -- is --;

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 8 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 44 (cont'd),

Line 40, "is" should read -- be --;
Line 47, "values." should read -- values --; and
Line 54, "patterns" should read -- pattern --.

Column 45,

Line 36, "is" should read -- does --;
Line 37, "formed" should read -- form --; and
Line 50, "successively." should read -- successively formed. --.

Column 46,

Lines 12 and 27, "can not" should read -- cannot --;
Line 25, "lead" should read -- leads --;
Lines 39 and 40, "which" should read -- where --; and
Lines 41 and 58, "observe" should read -- observes --.

Column 47,

Line 6, "are" should read -- is --; and
Line 34, "shifted" should read -- shifted over --.

Column 48,

Line 3, "shifted" should read -- shifted over --;
Line 29, "first. Because" should read -- first, because --;
Line 31, "characteristics. And" should read -- characteristics, and --; and
Line 44, "can not" should read -- cannot --.

Column 49,

Line 26, "to" should read -- into --; and
Line 44, "consists" should read -- consist --.

Column 50,

Line 42, "function." should read -- functions. --; and
Line 67, "performs" should read -- perform --.

Column 51,

Line 17, "one" should read -- ones --;
Lines 27 and 29, "printing" should read -- printings --;
Line 28, "which" should read -- in which --;
Line 34, "printing" should read -- print --;
Line 40, "for" should be deleted; and
Line 52, "to cover all such changes" should be deleted.

Column 53,

Line 20, "polynominal" should read -- polynomial --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,474,767 B1
DATED : November 5, 2002
INVENTOR(S) : Minoru Teshigawara et al.

Page 9 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 54,

Line 4, "a" should be deleted;
Line 31, "by-using" should read -- by using --; and
Line 32, "patterns-forming" should read -- pattern-forming --.

Column 55,

Line 2, "a" should be deleted;
Line 35, "amount-of" should read -- amount of --; and
Line 57, "polynominal" should read -- polynomial --.

Column 56,

Line 42, "a" should be deleted; and
Line 66, "film boil," should read -- film-boil, --.

Column 57,

Line 7, "patterns-forming" should read -- pattern-forming --; and
Line 27, "in" should read -- inside, --.

Signed and Sealed this

Ninth Day of September, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line underneath.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office