



US006491642B1

(12) **United States Patent**
Stasz

(10) **Patent No.:** **US 6,491,642 B1**
(45) **Date of Patent:** **Dec. 10, 2002**

(54) **PYRO/PIEZO SENSOR**

(75) Inventor: **Peter Stasz**, St. Paul, MN (US)

(73) Assignee: **Dymedix, Corp.**, Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/852,195**

(22) Filed: **May 9, 2001**

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/416,660, filed on Oct. 12, 1999, now Pat. No. 6,254,545.

(51) **Int. Cl.**⁷ **A61B 5/08**

(52) **U.S. Cl.** **600/529; 600/537**

(58) **Field of Search** 600/529, 532, 600/534, 537, 552, 555, 582; 73/862.68; 310/800

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,530,494 A * 9/1970 Baratta 206/441

4,814,661 A * 3/1989 Ratzlaff et al. 310/328
5,311,875 A * 5/1994 Stasz 600/537
5,913,829 A * 6/1999 Reeves et al. 600/528

* cited by examiner

Primary Examiner—Kevin Shaver


Assistant Examiner—Patricia Mallari

(74) *Attorney, Agent, or Firm*—Nikolai & Mersereau, P.A.; Thomas J. Nikolai

(57) **ABSTRACT**

A combination thermal and vibration sensor for use in sleep monitoring equipment comprises a thin film of a plastic exhibiting both pyroelectric and piezoelectric properties. By providing a layer of foam material totally covering one major surface of the plastic film layer, it is found that the thermal mass of the sensor is changed to the point where the pyroelectric signal can more readily be isolated from the piezoelectric signal using conventional signal processing techniques.

7 Claims, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




Fig. 5

PYRO/PIEZO SENSOR

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of application Ser. No. 09/416,660, filed Oct. 12, 1999 (now U.S. Pat. No. 6,254,545).

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to electronic sensors for monitoring both temperature changes and sound using a single transducer, and more particularly to the construction of such sensors that more readily allows the temperature signal to be separated from the sound signal using conventional signal processing techniques (filtering).

2. Discussion of the Prior Art

In the Stasz U.S. Pat. No. 5,311,875, which is hereby incorporated by reference, there is described a system for electronically monitoring breathing patterns. The system described therein utilizes a plastic film exhibiting both pyroelectric and piezoelectric properties such as a polyvinylidene fluoride (PVDF) film. The film transducer has a conductive electrode on opposed major surfaces thereof and electrical wires connect the electrodes to an electronics module that is designed to separate the transducer output into two separate channels, one being for temperature and the other being for sound or vibration.

Our testing has shown that the signal proportional to temperature variation greatly exceeds that due to noise or vibration by a factor of about 150:1. The temperature-related signal also exhibits a substantially faster response time than the sound signal and is rich in frequency components in the 20 Hz to 50 Hz range. These facts result in a difficulty in preventing the thermal component of the transducer from crossing over into the sound channel, often leading to the occurrence of false positives when both sound signals and temperature signals are being simultaneously monitored.

The problem thus presents itself as to how one may effectively separate the signals when the frequency components of each signal overlap. Resorting to a signal processing approach has proven difficult.

We have found that by modifying the mechanical construction of the pyro/piezo transducer to increase its thermal mass, the effective rise time of the thermal signal is greatly reduced, while not seriously attenuating the sound/vibration-related signal amplitude. Decreasing the rise time of the thermal signal results in a shift of the frequency components thereof so as not to overlap with the frequency components in the sound channel. As such, conventional filtering steps can be performed to produce separate, isolated channels.

SUMMARY OF THE INVENTION

In accordance with the present invention, control over the thermal mass of the transducer described in the aforementioned Stasz patent is achieved by affixing a layer of plastic foam material onto the transducer film on at least one major surface thereof. Thus, in accordance with a preferred embodiment of the present invention, the combination thermal and vibration sensor may comprise a PVDF film of a predetermined shape configuration with first and second major surfaces. A thin layer of a conductive material is deposited upon the first and second major surfaces of the film and electrical leads are attached at one end to the electrodes. An outer moisture impervious layer is adhered to

the electrode on one side of the film and a foam layer of a predetermined thickness and coextensive with the area of the PVDF film is bonded to the opposite major surface. The thickness of the foam layer is directly related to the rise time of the thermal signal. Lowering the rise time of the thermal signal effectively shifts the frequency components comprising the thermal signal so as to no longer overlap with the predominant frequency components of the piezo or sound signal. Now, conventional filtering techniques can be used to separate the two channels.

DESCRIPTION OF THE DRAWINGS

The foregoing features, objects and advantages of the invention will be come apparent to those skilled in the art from the following detailed description of a preferred embodiment, especially when considered in conjunction with the accompanying drawings in which:

FIG. 1 is a front plan view of a pyro/piezo sensor constructed in accordance with the present invention;

FIG. 2 is a side elevation view of the sensor of FIG. 1;

FIG. 3 is a plan rear view of an alternative embodiment;

FIGS. 4A-4E are waveforms helpful in understanding the significance of the improvement afforded by the present invention; and

FIG. 5 is an exploded, isometric view of an alternative embodiment for enhancing the signal to noise ratio of the sound signal.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 1, there is indicated generally by numeral 10 a transducer element constructed in accordance with the present invention. It comprises a laminated construction of a plastic film 12 which exhibits both pyroelectric and piezoelectric properties. A polyvinylidene fluoride (PVDF) whose thickness ranges from about 0.5 to 5 mils has proven suitable. The film 12 and the layers laminated therewith and yet to be described are preferably somewhat triangular in shape, but with the three sides of the triangle being arcuate (concave inward) to define three distinct lobes 14, 16 and 18.

In fabricating the transducer, a thin, flexible layer of conductive material is applied to the opposed major surfaces of the film layer 12, the conductive layers being identified in FIG. 2 by numerals 20 and 22. Without limitation, the electrodes 20 and 22 may comprise carbon or a suitable metal that is sufficiently thin so as not to inhibit the bending and forming of the electrode during use.

As shown in FIG. 1, an elongated insulated conductor 24 has one end 26 thereof connected to the conductive layer 20 while elongated conductor 28 has one end 30 connected to the conductive layer 22 on the opposite side of film 12 from conductive layer 20. Conductors 24 and 28 are terminated in connectors 32 and 34, respectively, to facilitate their attachment to an electronics module (not shown).

Overlaying the conductive layer 22 is a non-conductive tape 36 which is shown as being coextensive with the film layer 12.

Adhered to the conductive layer 20 on the opposed surface of the film layer 12 is a layer 38. Either or both of the non-conductive layers 36 and 38 preferably may comprise a layer of plastic foam having a pressure sensitive adhesive on opposed surfaces thereof whereby the layers 36 and 38 adhere to the conductive layers 22 and 20, respectively. Assuming that the transducer is to be used in sleep-lab

applications for monitoring a patient's breathing pattern, an adhesive on the exposed or outer surface of the foam layer **38** can be used to adhere the transducer to the subject's upper lip, with lobes **14** and **16** being positioned directly in the path of air flow from the subject's nares and with the lobe **18** adapted to overlay the subject's mouth opening. Prior to use, the adhesive is preferably protected by a peel-away layer of release paper, as at **40**, the release paper having a pull-tab **42** extending beyond a border of the layer **38** for ease of gripping.

Because the transducer made in accordance with the present invention is very flexible, it can adhere to the subject's lip and flex with facial movements so that it does not readily detach from the subject's lip. As shown in the embodiment of FIG. **3**, the nonconductive tape layer **36** may not be co-extensive with the film layer, but instead may extend beyond the confines of the transducer film and may include a pressure sensitive adhesive on its undersurface **37** to facilitate attachment of the transducer to a subject being monitored. Again, the adhesive may be protected with a removable release paper to shield the adhesive prior to its application to the subject.

The present invention centers on the use of the covering layers **36** and/or **38** on the transducer described in the aforesaid Stasz '875 patent. Specifically, we have found that it is possible to tailor the rise time of the thermal response signal component so that its frequency components do not overlap with the frequency components of the piezo (sound) signal. That is to say, the covering layers **36** and/or **38** are found to increase the thermal mass of the transducer to the point where the rise time of the thermal signal is reduced to a point where conventional filtering techniques can readily discriminate between the sound channel and the temperature channel as those terms are defined in the Stasz '875 patent. As such, transducers constructed in accordance with the present invention can be tailored to work with electronic signal processing circuitry currently in use in sleep labs, making it unnecessary to provide special electronics for accommodating combination pyro and piezo film transducers.

FIG. **4A** graphically illustrates how the signal from the prior art transducer described in the aforesaid Stasz '875 patent frequently results in false positive in the snoring channel due to the rapid rise and fall time of the pyrosignal in the breathing channel. The false positives are highlighted by being encircled.

FIG. **4B** again shows the behavior of the prior art transducer of the Stasz '875 patent in the presence of a snoring event. The breathing channel shows rhythmic breathing with an episode of snoring bounded by vertical dashed lines. Observing the waveform in the snoring channel, it is again noted that there are several false positives corresponding to the rapid fall time of the pyrosignal.

FIG. **4C** illustrates the waveforms in the breathing and snoring channel when the transducer constructed in accordance with the present is employed with the same sensing circuitry as was used in recording the waveforms of FIGS. **4A** and **4B**. Looking first at the waveform entering the breathing channel in FIG. **4C**, it is immediately apparent that the addition of the foam layer covering the entire transducer film has the effect of significantly decreasing the rise and fall time of the pyro signal. As a result, there are no longer any false positive peaks in the waveform derived from the snoring channel electronics.

The waveform of FIG. **4D** were taken using the transducer of the present invention but with a snoring episode taking

place. Because of the absence of false positives, the output from the snoring or piezo channel is readily recognized and detectable.

FIG. **4E** are waveforms derived from a recording from a polysomnography machine of a type commonly used at a sleep laboratory. Using the transducer of the present invention, the snoring pattern is readily detectable while the pyro signal labeled "air flow" clearly does not introduce false positives into the snoring channel, but instead, reflects air flow due to inhalation and exhalation. The observed difference in the waveforms of FIGS. **4A** and **4C** is due solely to the addition of a foam layer approximately $\frac{1}{16}$ " of an inch thick covering the transducer film **12** over its entire surface.

ALTERNATIVE EMBODIMENT

Referring to FIG. **5**, there is shown an alternative embodiment of the invention designed to enhance the signal-to-noise ratio produced in the sound channel. As in the embodiment of FIG. **1**, the device comprises a laminated structure including a PVDF film layer **50** having a conductive pattern, as at **52**, on the opposed major surfaces thereof. Without limitation, the conductive pattern may be applied as a carbon based ink or metal deposition.

The shape of the film layer **50** is bilaterally symmetrical about a longitudinal axis and includes a generally rectangular center section **54** having obliquely extending rounded arms **56** and **58** projecting from adjacent upper corner portions thereof and laterally extending legs **60** and **62** at the base of the rectangular mid-section **54**. Extending normal to the upper edge of the central portion midway between the obliquely extending arms **56** and **58** is a rectangular tab segment **64**.

A foam layer **66**, corresponding in shape to the film layer **50**, is adhesively bonded to the conductive pattern on the lower side of the film layer with a conductive connector pad **68** that contacts the conductive layer on the PVDF film layer sandwiched therebetween. An elongated flexible lead **70** has an inner conductive wire electrically connected to the conductive pad **68** and it leads to a connector **72** that is adapted to mate with an electronics module. Again, the thickness of the foam layer **66** is selected to provide a desired thermal mass to the sensor and typically would fall into a range of from about 0.001 inch to 0.15 inch. A layer of release paper **74** is adhered to the underside of the foam layer **66** and is adapted to be removed to expose an adhesive layer that is used to adhere the sensor device to a person's upper lip. The release layer **74** is preferably cut along dashed line **75** so that a band of release paper can be left in place if desired to prevent adhesion of the sensor to lip tissue.

A connector pad **76** abuts the conductive layer **52** on the PVDF film layer **50** and provides a means whereby an electrical conductor **78** in a lead **80** becomes conductively joined to the metallization pattern **54**. The lead **80** has a connector **82** on its proximal end.

Disposed in covering relation to the conductive layer **54** and the connector **76** is an outer layer **84** that is preferably cut from a suitable fabric, such as a woven tricot fabric.

In use, the sensor device of FIG. **5** will be removed from a package and at least the portion of the release liner **74** above the cut line **75** stripped there from to expose an adhesive layer on the undersurface of the foam layer **66**. The tab **77** of the release paper that extends beyond the boundary of the foam layer **66** facilitates grasping and removal of the release paper. The device is then applied to the upper lip of a subject such that the laterally extending leg portion of the

5

device overhangs the subject's upper lip while the obliquely extending rounded arms are placed in general alignment with the nares of the nose. The tab 64 is bent outward and adhered by the adhesive to the subject's external nasal septum. The strip of release paper covering the laterally extending leg portions 60 and 62 can be left in place, if desired.

During a snoring episode, the septum vibrates and causes the PVDF film to output a piezoelectric signal that is transmitted to the electronics module, via the leads 70 and 80. The laterally extending leg portions 60 and 62 extend over the subject's upper lip where it is exposed to both temperature changes due to mouth breathing and to snoring noise. Likewise, the laterally extending arms 56 and 58 are positioned to receive air flowing into and out from the subject's nares as a result of respiratory activity.

Again, the presence of the foam layer 66 provides a means for effectively controlling the thermal mass of the device, making it easier to separate a piezo signal from a pyro signal.

This invention has been described herein in considerable detail in order to comply with the patent statutes and to provide those skilled in the art with the information needed to apply the novel principles and to construct and use such specialized components as are required. However, it is to be understood that the invention can be carried out by specifically different equipment and devices, and that various modifications, both as to the equipment and operating procedures, can be accomplished without departing from the scope of the invention itself

What is claimed is:

1. A combination thermal and vibration sensor, comprising:

- (a) a plastic film exhibiting pyroelectric and piezoelectric properties with first and second major surfaces and having a predetermined shape configuration, said predetermined shape configuration including a generally rectangular central segment with first and second obliquely projecting arms at adjacent corners thereof

6

and an elongated tab disposed between said obliquely projecting arms;

- (b) a thin layer of conductive material deposited upon and substantially covering the first and second major surfaces;
- (c) first and second elongated conductive leads individually connected at a first end thereof to the layers of conductive material on the first and second major surfaces;
- (d) a layer of a material for changing the thermal mass of the sensor adhered to the layer of conductive material on at least one of the first and second major surfaces, and coextensive with the predetermined shape configuration of the film; and
- (e) a layer of adhesive on an exposed surface of the layer of material for changing the thermal mass of the sensor for adhering the sensor to a subject's upper lip with the elongated tab adapted to be affixed to the base of the subject's nasal septum.

2. The sensor of claim 1 wherein the layer of adhesive is adapted to adhere the first and second obliquely projecting arms in alignment with the subject's nares when the elongated tab is affixed to the base of the subject's nasal septum.

3. The sensor of claim 1 wherein the material for changing the thermal mass of the sensor is a layer of foamed plastic.

4. The sensor of claim 3 wherein the layer of foamed plastic has a thickness in the range from about 0.001 to 0.150 inches.

5. The sensor of claim 4 wherein the layer of foamed plastic is about $\frac{1}{32}$ inch in thickness.

6. The sensor of claim 1 wherein the layer of material for changing the thermal mass includes a layer of peel-away release paper covering the adhesive on the exposed surface prior to its application to an attachment surface.

7. The sensor of claim 6 wherein the layer of release paper includes a tab extending beyond an edge of said layer of material for changing the thermal mass of the sensor.

* * * * *