



US006502715B2

(12) **United States Patent**
Miorelli

(10) **Patent No.:** **US 6,502,715 B2**
(45) **Date of Patent:** **Jan. 7, 2003**

(54) **DRINKING RECEPTACLE**

(76) Inventor: **Graciela Miorelli**, 2301 Perez, San Antonio, TX (US) 78207

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/005,272**

(22) Filed: **Dec. 5, 2001**

(65) **Prior Publication Data**

US 2002/0166865 A1 Nov. 14, 2002

Related U.S. Application Data

(63) Continuation-in-part of application No. 09/723,058, filed on May 8, 2001, now abandoned.

(51) **Int. Cl.**⁷ **B68D 25/42**

(52) **U.S. Cl.** **220/719; 220/703; 220/718**

(58) **Field of Search** 220/719, 716, 220/717, 718, 704, 703, 731, 698, 702

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,084,084 A * 6/1937 Green
2,885,108 A * 5/1959 Donoghue

3,184,126 A	*	5/1965	Casull	222/487
3,313,447 A	*	4/1967	Spencer	220/719
3,360,161 A	*	12/1967	Smith	220/719
3,744,671 A	*	7/1973	Saunders, Jr.		
3,785,794 A	*	1/1974	Hodges	65/108
4,130,215 A		12/1978	Corey et al.		
4,726,487 A	*	2/1988	Mitri	220/718
4,938,375 A		7/1990	Fantacone		
4,964,527 A	*	10/1990	Martin		
5,253,780 A	*	10/1993	Adado	220/711
5,515,998 A		5/1996	Wang		
5,553,731 A		9/1996	Schuyler		
5,845,807 A		12/1998	De Villiers		
6,189,725 B1	*	2/2001	Monico		
6,202,877 B1	*	3/2001	La Torre et al.	220/254.1


* cited by examiner

Primary Examiner—Joseph M. Moy
(74) *Attorney, Agent, or Firm*—Jackson Walker L.L.P.; Richard R. Ruble

(57) **ABSTRACT**

A drinking receptacle for liquids and frozen food products has an interior, vertical, annular ridge with notches. Liquid from the interior chamber of the receptacle or from dripping of the frozen food product are collected in an annular channel formed between the ridge and an outwardly sloping rim. The notches in the ridge allow liquid to pass from or into the interior chamber of the receptacle.

8 Claims, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

DRINKING RECEPTACLE

This is a continuation-in-part application of application Ser. No. 09/723,058, filed May 8, 2001 now abandoned.

BACKGROUND OF THE INVENTION

The present invention relates to a drinking receptacle. More particularly, the present invention is a cup intended to reduce or eliminate spillage of liquid from around a frozen food retained within the rim of the receptacle.

The prior art is replete with drinking cups and accessories which reduce the tendency of the cup to spill liquid. A well known apparatus is the use of a thin plastic lid or cap to close the top of the receptacle. To enable the withdrawal of the liquid contents from capped receptacles it is necessary to provide a straw opening. These prior art devices are principally designed to retain ice and liquid within the body of the container.

There are far fewer receptacles designed to support a frozen food product such as a snow cone, an ice cream scoop, a frozen ice pop, or ice cream bar. U.S. Pat. No. 5,515,998 discloses a frozen confection holder and receptacle designed to hold the frozen confection in an upright position while being eaten, or while awaiting consumption. A trough-like upper dish is provided with a slot to maintain the stick of the frozen confection in an upright position. There is no teaching in U.S. Pat. No. 5,515,998 for catching drips from any frozen product not supported on a stick. Further, there is no teaching or disclosure of a structure to allow the receptacle to be tilted to facilitate drinking liquids from the upper lip of the receptacle.

The present invention allows for a convenience store to maintain one style of drinking receptacle which functions both to dispense liquids such as soft drinks, water, and coffee, and also be capable of supporting a frozen food product while directing melting drips from the product back into the liquid containment chamber. In the present invention a standard lid may be utilized where desired because the outside diameter of the rim of the present invention may be sized to conventional standards. The vertical, annular support ridge of the present invention within the rim is positioned below the uppermost edge of the rim and, therefore, does not interfere with a standard lid.

The present invention is a significant improvement in the art and solves long-standing standardization of materials problems common in the food and beverage dispensing industry. The receptacle of the present invention may be constructed from any of the standard material compositions used in the industry.

SUMMARY OF THE INVENTION

The present invention is a receptacle which may function as a drinking cup or as a frozen food product drip catcher. A cylindrical cup is provided with an outwardly sloping rim and an interior, vertical annular ridge. The ridge has liquid draining notches which allow liquid to communicate with the space between the rim and the ridge and the interior liquid containment chamber.

The ridge is disposed such that its uppermost edge is below the uppermost edge of the outwardly sloping rim. This allows the receptacle to accept a standard lid for closing the open top of the receptacle.

When a frozen food product such as a snow cone is placed in the receptacle, the product is supported on the interior, annular ridge while the outwardly sloping rim may catch

drips from the melting product. The flowable drips are then directed through the notches in the ridge into the interior liquid containment chamber. This feature allows the consumer to avoid messy drips on his/her hands and/or clothes.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a top front perspective view of the present invention.

FIG. 2 is a side elevation view of the present invention.

FIG. 3 is a cross section view taken along lines A—A of FIG. 2.

FIG. 4 is a top plan view of the present invention.

FIG. 5 is a partial perspective view of the present invention illustrating the flow of liquid through the notches in the ridge to the rim and over the rim edge.

FIG. 6 is a perspective view of the present invention supporting a melting frozen food product on the ridge of the present invention with flowable dripping liquid passing through the notches back into the liquid containment chamber.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 shows a perspective view of the receptacle **10** of the present invention. A generally cylindrical cup **12** has a bottom **14** and upwardly extending side walls **16**. The side walls extend from the bottom **14** to a top section **18**. The top section **18** has an outwardly sloping rim **20** surrounding the open top **22** of the receptacle. A central, vertical axis X extends from the bottom **18** through an interior, liquid containment chamber **24** of the receptacle **10**.

An interior, vertical, annular ridge **26** extends above the liquid containment chamber **24**. The ridge **26** is integral with the side wall structure **16** at the top section **18**. As may be seen from FIG. 1, the ridge **26** is generally parallel to the vertical axis X. The uppermost edge **28** of ridge **26** terminates below the uppermost edge **30** of the rim **20**.

One or more notches **32** are formed in the ridge **26** to allow liquid to flow in the channel **34** into and out of the liquid containment chamber **24** as will be described more fully below. The notches **32** may be as few as one or as many as necessary to ensure that liquid in the channel **34** can pass back into the chamber **24**.

Turning now to FIGS. 2 and 3, the present invention may be seen in a side elevation view. The receptacle **10** from outward appearances looks like a standard drinking cup. The cup may be made of paper, plastic, styrofoam, waxed paper, and the like. Thus, any conventional composition may be used which meets the economic and manufacturing requirements of the producer. The receptacle **10** may accommodate any standard lid (not shown) which might otherwise be used with conventional drinking cups.

FIG. 3 illustrates a cross section view of the present invention taken along line A—A of FIG. 2. It may be seen that the ridge **26** is generally parallel to the central axis X of the receptacle **10**. The uppermost edge **28** of ridge **26** is approximately one-quarter inch below the uppermost edge **30** of the sloping rim **20**. The rim is angled at approximately 45° outwardly from the central axis X.

When the receptacle **10** is tilted, as will be shown below, liquid may accumulate in the channel **34** formed between the inner side **40** of the rim **20** and the outer side **42** of the ridge **26**. If the receptacle **10** contains a liquid such as coffee, the tilting of the receptacle will allow hot liquid to flow in the

3

channel **34**. This is seen in FIG. **5**. Thus, a small portion of the liquid **36** contained in chamber **24** is allowed to enter the channel **34** for cooling, for example, before being withdrawn from the receptacle by the drinker. Further, when the receptacle is straightened the liquid **36** can drain back into the chamber **24**. This cooling effect on the liquid **36** is similar to that achieved when coffee drinkers pour coffee into the support saucer before drinking the hot liquid.

The ridge **26** is shown in FIG. **3** as being formed integral with the side wall **16**. However, it should be understood that a separate ring could be fused to the inner surface **17** of the side wall **16** to create the upwardly extending ridge **26**.

FIG. **4** is a simple illustration showing the top plan view of the present invention **10**. The bottom **14** can be seen with inner side wall surface **17**. Again, it should be understood that the side wall **16** does not have to taper and may be generally straight. However, rim **20** is outwardly sloping and ridge **26** is generally parallel to the central axis X. This creates the channel **34** for draining liquids into or out of the chamber **24**.

FIG. **6** shows the present invention receptacle **10** being utilized to support a frozen food product **50**. The product **50** is suspended above the containment chamber **24** by the ridge **26**. As the product melts, drips **52** of flowable liquid are collected in channel **34** and directed through notches **32** into the liquid containment chamber **24**. In this manner, the user avoids the mess of drip **52** getting on his/her hands and/or clothing.

Certain alternative features of the present invention include the use of notches **32** in the four quadrants of the rim as shown in FIGS. **1** and **4**. The diameter D_1 of the ridge **26** is less than the diameter D_2 of the sloping rim thereby forming the channel **34**. While V-shaped notches are shown in the drawings, it should be understood that any effective cut or hole which allows the drip **52** or liquid **36** to pass from the channel **34** to and from the chamber **24** is within the scope of the present invention.

Although the invention has been described with reference to a specific embodiment, this description is not meant to be construed in a limiting sense. On the contrary, various modifications of the disclosed embodiments will become apparent to those skilled in the art upon reference to the description of the invention. It is therefore contemplated that the appended claims will cover such modifications, alternatives, and equivalents that fall within the true spirit and scope of the invention.

4

What is claimed is:

1. A drinking receptacle for liquids comprising:

a generally cylindrical cup having a bottom and side wall structure extending upwardly from said bottom to a top section including an outwardly sloping rim surrounding an open top of said cup, said cup having a central vertical axis extending from said bottom through an interior liquid containment chamber of said cup; and

a vertical, annular ridge interior of said side wall structure at said top section, said ridge generally parallel to said vertical axis, said ridge extending above said interior liquid containment chamber and terminating below an uppermost edge of said outwardly sloping rim, said ridge having at least one drainage notch whereby liquid in said receptacle may pass between said liquid containment chamber and an inner surface of said outwardly sloping rim and an outer surface of said ridge.

2. The receptacle of claim **1** wherein said vertical, annular ridge is adapted for supporting a frozen food product, said product producing flowable liquid drips upon melting, said receptacle further comprising:

a multiplicity of said drainage notches in said ridge whereby said flowable, liquid drips from said product accumulating between said inner surface of said rim and said outer surface of said ridge flow into said interior liquid containment chamber of said cup.

3. The receptacle of claim **1** wherein said rim has a diameter greater than the diameter of said vertical, annular ridge.

4. The receptacle of claim **3** wherein the uppermost edge of said ridge is at least one-quarter inch below said uppermost edge of said rim.

5. The receptacle of claim **1** wherein said outwardly sloping rim is approximately one-inch wide and slopes outwardly at an angle of approximately 45° from said central vertical axis.

6. The receptacle of claim **2** wherein said multiplicity of said notches is four notches disposed at each quadrant of said annular ridge.

7. The receptacle of claim **1** wherein said receptacle has a composition selected from the group consisting of paper, plastic, styrofoam, and waxed paper.

8. The receptacle of claim **1** wherein said drainage notch is V-shaped.

* * * * *