



US006530125B2

(12) **United States Patent**  
**Shippert**

(10) **Patent No.:** **US 6,530,125 B2**  
(45) **Date of Patent:** **Mar. 11, 2003**

(54) **MULTI-PLANE GRIPPING HANDLE**

(76) Inventor: **Ronald D. Shippert**, 4975 S. Albion St., Littleton, CO (US) 80121

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/900,210**

(22) Filed: **Jul. 6, 2001**

(65) **Prior Publication Data**

US 2003/0009854 A1 Jan. 16, 2003

(51) **Int. Cl.**<sup>7</sup> ..... **B25Q 1/10**

(52) **U.S. Cl.** ..... **16/430; 16/DIG. 12; 16/422; D8/107**

(58) **Field of Search** ..... **16/DIG. 12, 430, 16/431, 422; D8/107, 300, 83**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,162,896	A	*	12/1915	Achberger	.....	16/DIG. 12
1,217,287	A	*	2/1917	Dillinger	.....	16/DIG. 12
1,730,820	A	*	10/1929	Holden	.....	16/DIG. 12
2,520,355	A	*	8/1950	Bell	.....	16/DIG. 12
D182,827	S		5/1958	Latham	.....	D22/3
D193,496	S		8/1962	Jacoff	.....	D93/4
D221,614	S		8/1971	McMahon et al.	.....	D8/94
D230,468	S		2/1974	Fairbairn	.....	D8/107
D245,062	S		7/1977	Grame	.....	D8/83
D252,554	S		8/1979	Lancer	.....	D8/83
D260,849	S		9/1981	West et al.	.....	D8/94
4,414,438	A	*	11/1983	Maier et al.	.....	200/6 A
4,445,011	A	*	4/1984	Hansen	.....	200/52 R
4,885,818	A		12/1989	Arterbury	.....	16/110 R
4,926,521	A	*	5/1990	Gagnepain	.....	16/DIG. 12
4,950,013	A		8/1990	Yonkers	.....	294/49
5,299,497	A	*	4/1994	Dias	.....	16/DIG. 12
D355,831	S	*	2/1995	Hull et al.	.....	D8/107

D357,947	S	*	5/1995	Richer	.....	D21/48
5,440,784	A	*	8/1995	Hull et al.	.....	16/110 R
D373,944	S		9/1996	Thompson et al.	.....	D8/83
D389,720	S		1/1998	Warner et al.	.....	D8/107
D393,791	S		4/1998	Halls et al.	.....	D8/107
5,737,803	A		4/1998	Tisdale	.....	16/111 R
5,761,767	A	*	6/1998	Barton	.....	16/114 R
5,802,960	A		9/1998	Graj et al.	.....	99/403
5,805,256	A	*	9/1998	Miller	.....	348/734
D399,722	S	*	10/1998	Eidsmore et al.	.....	D8/107
D403,228	S		12/1998	Halls et al.	.....	D8/107
D403,946	S	*	1/1999	Shih	.....	D8/303
D404,280	S	*	1/1999	Wen	.....	D8/107
D425,365	S	*	5/2000	Chien	.....	D8/107
6,065,188	A	*	5/2000	Wold et al.	.....	16/430
D426,135	S	*	6/2000	Lee	.....	D8/107
D426,136	S	*	6/2000	Yu	.....	D8/107
D427,030	S	*	6/2000	Wen	.....	D8/1
D454,048	S	*	3/2002	Lin	.....	D8/107


\* cited by examiner


*Primary Examiner*—Thomas B. Will  
*Assistant Examiner*—Alexandra K Pechhold  
(74) *Attorney, Agent, or Firm*—Sheridan Ross P.C.

(57) **ABSTRACT**

A multi-plane gripping handle for use with a multitude of devices is provided which generally comprises a handle section, a thumb section and a butt surface. The size and shape of the handle section and thumb section are selected to optimize the surface contact between the gripping handle and the hand of the user. The handle section and the thumb section each occupy a separate plane and these in planes are arranged in a selected angular relationship with one another to further optimize the gripping surface contact between the hand and the handle. In an alternative embodiment, the gripping handle may be formed in a split-case construction such that alternative devices may be interchangeably inserted into the gripping handle and thus allow for the gripping handle to be used with various devices.

**23 Claims, 7 Drawing Sheets**









FIG. 2






FIG. 5




FIG. 6B




FIG. 6A




FIG. 7A

FIG. 7B




FIG. 8A







FIG. 8B





**MULTI-PLANE GRIPPING HANDLE****FIELD OF THE INVENTION**

The present invention relates to gripping handles that can be part of tools, medical instruments and other devices and more particularly to multi-plane gripping handles having two anatomically shaped surface planes adapted for use with such devices.

**BACKGROUND OF THE INVENTION**

Various types of gripping handles are currently available for use with numerous devices. These handles are intended to provide a surface with which a user may grasp the device for manipulation, such as transportation or implementation, of the device to perform its intended function.

Commonly, present gripping handles take the form of a round, rectangular, hexagonal, or other regular geometric shape in a single plane along the axis of a shaft of the attached device. Unfortunately, these types of handles do not fit the human hand well, and thus a limited surface area of the hand contacts the handle. Additionally, these shapes create a poor friction surface between the handle and the user's hand. The limited surface contact and poor friction surface of these handles have minimal torque capacity. A user is required to exert a great amount of strength, surface friction, and leverage to adequately perform a given task with these handles. In some cases, these disadvantages may create a need for longer lever arms or added elements, such as abrasives or a textured surface, or may increase necessary rest periods during operation. Also, for more complex devices and associated tasks, users of the present handles may require additional training and practice to efficiently utilize a given device for an associated task.

An additional problem with present gripping handles is the permanent interconnection of the handle to the attendant device. In certain situations, an interchangeable gripping handle for use with various devices would provide a cost benefit. In an example from the medical field, a surgeon may require several cannula handle units to perform a liposuction case. Cannulas of various sizes may be desirable to perform work on various portions of the patient. Cannulas, especially smaller bore cannulas, may be difficult, if not impossible, to properly sterilize for reuse. Cannulas which cannot be properly sterilized must be discarded for hygienic reasons. If a permanent gripping handle is provided with each individual cannula, the gripping handle must necessarily be discarded as well. The use of individual cannulas with permanent gripping handles attached becomes expensive. The initial cost of cannulas is greater because of the more complex part. It is also expensive to maintain, e.g., sterilize, repair, or replace, the cannulas.

In view of the foregoing perceived deficiencies, it would be advantageous to provide a gripping handle which includes at least two anatomically-shaped gripping surface planes, wherein each plane has a specified length, width, and thickness and wherein a selected angular relationship exists between the planes. It would be further advantageous to provide a gripping handle wherein the surface planes, lengths, widths, and thicknesses correspond with the normal gripping posture of the average human hand, thereby optimizing the surface contact between the user's hand and the handle. It would also be advantageous to provide a gripping handle which may be used interchangeable with various devices.

**SUMMARY OF THE INVENTION**

The multi-plane gripping handle of the present invention generally includes a handle section, a thumb section, and a

butt surface. The handle section of the present invention includes a palm sidewall, a finger sidewall, an outer surface, and an inner surface. The outer surface has an outer end and an outer common end, and the inner surface has an inner end and an inner common end. The thumb section includes a thumb upper wall, a lower wall, first and second sidewalls, a distal end and an opposite end.

The normal human hand grip occurs in two separate planes, that when combined produce one curvilinear plane. The planes consist of a finger to thumb (FT) plane and a finger to palm (FP) plane. The FT plane, in a normal gripping posture, is created between the index finger and the thumb. The FP plane, in a similar posture, is created between the fingers and the palm of the hand. The dimensions of the handle section, and its individual elements, of the present invention are selected to optimize the contact surface area between the gripping handle and the FP plane. Similarly, the dimensions of the thumb section are selected to optimize the contact surface area between the handle and the FT plane. By fitting the hand in this manner, several advantages are provided. The gripping handle of the present invention requires less strength to grip and provides greater torque transfer due to increased leverage. The gripping handle thereby reduces fatigue and joint stress to the user. Additionally, a user of the gripping handle is able to manipulate the associated device with better accuracy and control.

The multi-plane gripping handle of the present invention is further defined by the angular relationships between the certain elements of the handle. A first angle is determined by the intersection of a line extending through the butt surface and a line extending through the outer surface of the handle section. A second angle is determined by the intersection of a line extending through the butt surface, as in the first angle, and a line extend from the outer common end of the handle section through the distal end of said thumb section. Typically, the first angle is less than 90° and the second angle is in the range of 35° and 55°.

The FT and FP planes described above each have a separate specific gripping strength when occurring separately. However, when the two planes occur together at a proper angular relationship, there is a trapping effect between the hand and the gripping handle. The trapping effect provides a greater torque transfer to the gripping handle of the present invention than achievable by bi-planar gripping alone. As described above, the increase of torque transfer to the handle creates less fatigue and joint stress in the user and requires less strength to perform a similar operation than a gripping handle of the prior art.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a side elevation view of one embodiment of a handle of the present invention shown gripped by a human hand;

FIG. 2 is a side elevation view of another embodiment of a handle of the present invention shown gripped by a human hand;

FIG. 3 is a side elevation view of the handle of FIG. 1;

FIG. 4A is a plan view of the handle embodied in FIG. 3 along a plane parallel to the outer surface of the handle;

FIG. 4B is an end view from the distal end of the handle of FIG. 3;

FIG. 5 is a side elevation view of the handle of FIG. 2;

FIG. 6A is a top plan view of the handle of FIG. 5;

FIG. 6B is an end view of the handle of FIG. 5;

FIG. 7A is side elevation view of an alternative embodiment of the gripping handle of the present invention;

FIG. 7B is an end elevation view of the gripping handle of FIG. 7A;

FIG. 8A is a side elevation view of another alternative embodiment of the gripping handle of the present invention;

FIG. 8B is a side elevation view of the gripping handle of FIG. 8A;

FIG. 9A is a top plan view of an embodiment of a two hand gripping handle of the present invention;

FIG. 9B is a side elevation view of the two hand gripping handle of FIG. 9A; and

FIG. 9C is an end view of the two hand gripping handle of FIG. 9A.

#### DETAILED DESCRIPTION

With reference to FIGS. 1 and 2, two embodiments of a multi-plane gripping handle 20 of the present invention is illustrated as gripped by a human hand H. In each embodiment the multi-plane gripping handle 20 generally comprises a handle section 22, a thumb section 24 joined to the handle section 22, and a butt surface 26 adjacent to the handle section 22 opposite the thumb section 24. The handle section 22 and the thumb section 24, although joined together, are separate segments defining a gripping plane for the human hand. The handle section 22 creates a gripping surface in a finger-palm (FP) plane segment, i.e., the segment between the fingers and the palm of the users hand. The thumb section 24 creates a gripping surface in a finger-thumb (FT) plane segment, i.e., the segment between the index finger and the thumb of the users hand. The orientation of these planes is designed to fit a common grip of the normal human hand thereby increasing the surface contact between a user's hand and the gripping handle 20. The individual elements of the handle section 22 and the thumb section 24 creating these planes is discussed in more detail below.

In FIG. 1, the multi-plane gripping handle 20 is shown in an embodiment with the device 28, in this case a liposuction cannula, interconnected to the outer surface 30 of the handle section 22 near the butt section 26. The handle 20, in this orientation, forms an L-style handle, i.e., the device 28 forms an L-shape with the handle 20.

In FIG. 2, the multi-plane gripping handle 20 of the present invention is shown in a more traditional embodiment wherein the device 28 extends axially from the gripping handle 20. In this embodiment, the device 28 is interconnected with a distal end 32 of the thumb section 24.

With reference to FIGS. 3, 4A, and 4B, the embodiment of the multi-plane gripping handle 20 of FIG. 1 is shown in various views. FIG. 3 shows the handle 20 of FIG. 1 in side elevation view. FIG. 4A shows this embodiment of the handle in plan view as viewed from line "4A—4A". Similarly, FIG. 4B shows this embodiment in plan view as viewed along line "4B—4B." In this embodiment, the device 28 extends through the handle 20 adjacent to, and substantially parallel with, the butt surface 26. The handle section 22 generally comprises a palm sidewall 34, a finger sidewall 36, an outer surface 30, and an inner surface 38 to create a gripping surface in a finger-palm (FP) plane segment, i.e., the segment between the fingers and the palm of the users hand. The cross-sectional area of the handle section 22 is generally ovate as depicted by the crosshatched area of FIG. 3. The palm sidewall 34 and finger sidewall 36 typically are arranged along the major axis of the ovate area, and the outer surface 30 and the inner surface 38 are arranged along the minor axis. However, the generally ovate

area may be varied to some degree such that the palm sidewall 34 and the finger sidewall 36 are substantially flat. The outer surface 30 of the handle section 22 includes an outer end 40 and an outer common end 42. The inner surface 38 of the handle section 22 includes an inner end 44 and an inner common end 46. The outer common end 42 and the inner common end 46 are adjacent to the thumb section 24.

The thumb section 24 generally comprises a thumb upper wall 48, a lower wall 50, a first sidewall 52 and a second sidewall 54 to create a gripping surface in a finger-thumb (FT) plane segment, i.e., the segment between the index finger and the thumb of the users hand. The thumb section 24 also includes a distal end 32 and an opposite end. The opposite end is adjacent to the outer common end 42 and the inner common end 46 of the handle section 22.

The butt surface 26 is a surface extending from the outer end 40 of the handle section outer surface 30 and the inner end 44 of the handle section inner surface 38.

With reference to FIGS. 5, 6A, and 6B, the embodiment of the multi-plane gripping handle 20 of FIG. 2 is shown in various views. FIG. 5 shows the handle 20 of FIG. 2 in side elevation view. FIG. 6A shows this embodiment of the handle 20 in top plan view and FIG. 6B shows this embodiment in end elevation view as viewed from the device 28 end. In this embodiment, the device 28 extends through the handle 20 from the distal end 32 of the thumb section 24 to the butt surface 26 (FIG. 2) substantially parallel with the inner surface 38 of the handle section 22. As described above, the handle section 22 generally comprises a palm sidewall 34, a finger sidewall 36, an outer surface 30, and an inner surface 38 to create a gripping surface in a finger-palm (FP) plane segment, i.e., the segment between the fingers and the palm of the users hand. The cross-sectional area of the handle section 22 is generally ovate as depicted by the crosshatched area of FIG. 5. The palm sidewall 34 and finger sidewall 36 typically are arranged along the major axis of the ovate area, and the outer surface 30 and the inner surface 38 are arranged along the minor axis. As above, the generally ovate area may be varied to some degree such that the palm sidewall 34 and the finger sidewall 36 are substantially flat. The outer surface 30 of the handle section 22 includes an outer end 40 and an outer common end 42, and the inner surface 38 of the handle section 22 includes an inner end 44 and an inner common end 46. The common ends 42 and 46 are adjacent to the thumb section 24.

As above, the thumb section 24 generally comprises a thumb upper wall 48, a lower wall 50, a first sidewall 52 and a second sidewall 54 to create a gripping surface in a finger-thumb (FT) plane segment, i.e., the segment between the index finger and the thumb of the user's hand. The thumb section also includes a distal end 32 and an opposite end 56 adjacent to the handle section 22. The butt surface 26 extends from the outer end 40 of the handle section outer surface 30 and the inner end 44 of the handle section inner surface 38.

Referring again to FIGS. 3 and 5, the multi-plane gripping handle 20 of the present invention is defined by the angular relationships between the various surfaces of the handle 20. A first angle  $\theta_1$  can be defined as being formed at the intersection of a first line  $L_1$  extending generally along the butt surface 26 (a line fitted to the butt surface 26 and preferably no part of the line being located inwardly of the butt surface 26) and a second line  $L_2$  extending generally through the outer surface 30 of the handle section 22 (a line fitted to the outer surface 30 and preferably no part of the line being located inwardly of the outer surface 30). In order

to optimize the fit of the handle **20** to a user's hand, the first angle  $\theta_1$  is typically less than  $90^\circ$ . A second angle  $\theta_2$  can be defined as being formed at the inner section of the first line  $L_1$  and a third line  $L_3$  extending generally from the outer common end **42** of the handle section **22** through the distal end **32** of the thumb section **24** (a line fitted thereto and preferably no part of the line is located inwardly of the outer common end **42** and the distal end **32**). Second angle is typically in the range of  $35^\circ$ – $55^\circ$ . Additionally, the first angle  $\theta_1$  is typically greater than the second angle  $\theta_2$ .

The relationship of the various surfaces may also be defined in an alternative embodiment by a third angle  $\theta_3$ . The third angle  $\theta_3$  is formed between the first line  $L_1$  and a fourth line  $L_4$  extending generally along the lower wall **50** of the thumb section **24** (a line fitted to the lower wall **50** and preferably no part of the line being located inwardly of the lower wall **50**). In this embodiment, the third angle  $\theta_3$  is typically greater than the second angle  $\theta_2$ , and the third angle  $\theta_3$  is closer in magnitude to the first angle  $\theta_1$  than it is to the second angle  $\theta_2$ .

In each of the above embodiments, the dimensions of the handle section **22** and the thumb section **24** may be selected to optimize the fit between a user's hand and the gripping handle **20**. Typically, the length of the handle section **22** is at least twice the length of the thumb section **24**. More typically, the length of the handle section **22** is in the range of 3.5 to 5.5 inches, and the length of the thumb section **24** is in the range of 1.5 to 2.5 inches.

The widths and thickness of the handle section **22** and the thumb section **24** may also be selected to optimize surface contact between a user's hand and the gripping handle **20**. Typically, the handle section is designed with a width in the range of 1.0 to 1.75 inches and a thickness in the range of 0.6 to 1.0 inch. The thumb section typically has a width in the range of 1.0 to 1.75 inches and a thickness in the range of 0.6 to 1.0 inch.

In one specific embodiment designed to fit most human hands, the length of the handle section **22** is about 4.75 inches and the length of the thumb section is about 2 inches. In this embodiment, the width of the handle section **22** is about 1.75 inches, the width of the thumb section **24** is about 1.4 inches and the thicknesses of each section is about 0.8 inch.

Based on the foregoing design constraints, the gripping handle **20** of the present invention may provide up to 33.5 square inches of possible surface area for contact with a user's hand. Most prior art gripping handles provide only about 16 square inches of possible surface area for user contact. In general, and assuming an ergonomic fit between the hand and the gripping handle, there is a direct relationship between the amount of surface of the hand in contact with the gripping handle and the control, grip, and mechanical advantage of the handle and the associated device. The available surface area for contact of the average human hand, palmar surface only, is approximately 26 square inches for the adult male (plus/minus 25%) and 21 square inches for an adult female (plus/minus 25%). Therefore, the gripping handle **20** of the present invention provides an available gripping surface area which may utilize most of the available surface of the human hand.

The increased surface area of contact between a user's hand and the gripping handle **20** provides several advantages. For example, the present gripping handle **20** may allow a torque transfer from the user on the order of 62.5 inch-pounds. In contrast, a linear octagonal handle of the prior art allows torque transfer of approximately 43 inch-

pounds. A user operating a linear rectangular handle will only produce about 30 inch-pounds. The increased ability to transfer torque decreases user fatigue and strain on joints and muscles. Correspondingly, the present gripping handle **20** provides a user with greater control and precision of the attached device **28**.

With reference to FIGS. **7A** and **7B**, an additional embodiment of the split-case gripping handle **60** of the L-style construction of the present invention is shown. The split-case gripping handle **60** of this embodiment has the elements of the gripping handle **20** shown in FIGS. **3**, **4A**, and **4B**, however the split-case handle **60** is constructed of a left handle portion **62** and a right handle portion **64** with common mating surfaces **66**. In the embodiment of FIGS. **7A** and **7B**, the common mating surfaces **66** of the left handle portion **62** and the right handle portion **64** extend from the distal end **32** of the thumb section **24** to the butt surface **26**. The left handle portion **62** and the right handle portion **64** are hingedly interconnected along the butt surface **26**. A device aperture **68** is provided adjacent to the common mating surfaces **66** for insertion of a device **28**.

With reference to FIGS. **8A** and **8B**, a similar additional embodiment of a split-case handle **60** is provided. The split-case handle **60** of this embodiment is a variation on the gripping handle **20** shown in FIGS. **5**, **6A**, and **6B**. As in the L-style construction, the split-case handle has a left handle portion **62** and a right handle portion **64** with common mating surfaces **66**. However, in this embodiment the common mating surfaces **66** extend, over the length of the split-case handle **60**, from the outer surface **30** of the handle section **22** and the thumb upper wall **48** to the inner surface **38** of the handle section **22** and the lower wall **50** of the thumb section **24**. The left handle portion **62** and the right handle portion **64** are hingedly interconnected along the inner surface **38** of the handle section **22** and the lower wall **50** of the thumb section **24**. Again, a device aperture **68** is provided adjacent to the common mating surfaces **66** for insertion of a device **28**.

The various embodiments of the split-case handle **60** may be used in tandem to allow a user to use alternative handle arrangements with a single device **28**. For example, a surgeon performing a liposuction case may opt to use the split-case handle **60** embodiment shown in FIGS. **8A** and **8B** with a selected cannula for a portion of the surgery and later use the same cannula with the split-case handle **60** embodiment of FIGS. **7A** and **7B**. Additionally, a single split-case handle **60** may be used with various devices **28**. For example, a surgeon may elect to interchange cannulas of various sizes and geometries during a liposuction case with the same split case handle **60**. In this example, small bore cannulas which are difficult to sterilize may be discarded after the surgery while the handles **60** may be sterilized for reuse. Since only the cannulas need to be discarded, a cost savings in handle costs is achieved.

Referring now to FIGS. **9A**, **9B**, and **9C**, yet another alternative embodiment of the gripping handle of the present invention, a two-hand gripping handle **70**, is shown in top plan view, side elevation view and end elevation view, respectively. A two-hand gripping handle **70** incorporates two individual gripping handles **20** as described above for use with a device. In this way a tool or other device that requires the use of both hands of a user may be provided with a handle that reduces muscular fatigue, joint stress, and provides increased torque transfer and other advantages as listed above. In the embodiment shown, the two-hand gripping handle **70** has a first hand portion **72** and a second hand portion **74**. Both the first hand portion **72** and the second

hand portion **74** of the two-hand handle **70** generally comprise a handle section **22** and a thumb section **24**. The handle section **22** generally comprises a palm sidewall **34**, a finger sidewall **36**, an outer surface **30**, and an inner surface **38** to create a gripping surface in a finger-palm (FP) plane segment, i.e., the segment between the fingers and the palm of the users hand. The cross-sectional area of the handle section **22** is generally ovate as depicted by the crosshatched area of FIG. 3. The palm sidewall **34** and finger sidewall **36** typically are arranged along the major axis of the ovate area, and the outer surface **30** and the inner surface **38** are arranged along the minor axis. However, the generally ovate area may be varied to some degree such that the palm sidewall **34** and the finger sidewall **36** are substantially flat. The outer surface **30** of the handle section **22** includes an outer end **40** and an outer common end **42**. The inner surface **38** of the handle section **22** includes an inner end **44** and an inner common end **46**. The outer common end **42** and the inner common end **46** are adjacent to the start of the thumb section **24**.

The thumb section **24** generally comprises a thumb upper wall **48**, a lower wall **50**, a first sidewall **52** and a second sidewall **54** to create a gripping surface in a finger-thumb (FT) plane segment, i.e., the segment between the index finger and the thumb of the users hand. The thumb section **24** also includes a distal end **32** and an opposite end **56**. The opposite end **56** is adjacent to the outer common end **42** and the inner common end **46** of the handle section **22**.

In the embodiment of FIGS. 9A, 9B, and 9C, the first hand portion **72** further comprises a butt surface **26**. The butt surface **26** is a surface extending from the outer end **40** of the handle section outer surface **30** and the inner end **44** of the handle section inner surface **38**.

With further reference to FIGS. 9A, 9B, and 9C, the first hand portion **72** is substantially axially aligned with the second hand portion **74**. The thumb section distal end **32** of the first hand portion **72** is adjacently interconnected to the outer end **40** and inner end **44** of the handle section **22** of the second hand portion **74**. It is understood, however, that other embodiments are included in the present invention. For example, a spacing element (not shown) may be provided between the first hand portion **72** and the second hand portion **74** to allow proper ergonomic spacing or leverage between the user's hands based upon the tool or device **28**, e.g., a shovel.

With particular reference to FIG. 9C, the two-hand gripping handle **70** may be further defined by the angular relationship between the first hand portion **72** and the second hand portion **74**. For clarity, the angular relationship is referenced from common elements of both the first hand portion **72** and the second hand portion **74**. In FIG. 9C, the angular relationship, denoted by angle  $\alpha$ , is measured from the handle section outer surface **30** of each the first handle portion **72** and the second handle portion **74**. The angular relationship, i.e., the magnitude of angle  $\alpha$ , is typically in the range of  $0^\circ$  to  $90^\circ$ , and preferably about  $45^\circ$ . The angular relationship, i.e., angle  $\alpha$ , may be fixed at manufacturing. However, it is possible that the angular relationship may be adjustable in certain embodiments of the two-hand gripping handle **70**. The adjustability can be accomplished by conventional means, such as by friction fit, luer lock, or a ratchet-like mechanism.

The foregoing discussion of the invention has been presented for purposes of illustration and description. Further, the description is not intended to limit the invention to the form disclosed herein. Consequently, variation and modifi-

cation commensurate with the above teachings, within the skill and knowledge of the relevant art, are within the scope of the present invention. The embodiments described herein above are further intended to explain the best mode presently known of practicing the invention, and to enable others skilled in the art to utilize the invention as such, or in other embodiments, and with various modifications required by their particular application or uses of the invention. It is intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

To assist in the understanding of the invention and associated drawings, the following list of components and associated numbering are included herein:

#	Component
20	multi-plane gripping handle
22	handle section
24	thumb section
26	butt surface
28	device
30	handle section outer surface
32	thumb section distal end
34	palm sidewall
36	finger sidewall
38	handle section inner surface
40	handle section outer end
42	handle section outer common end
44	handle section inner end
46	handle section inner common end
48	thumb upper wall
50	thumb section lower wall
52	first sidewall
54	second sidewall
56	thumb section opposite end
60	split-case handle
62	left handle portion
64	right handle portion
66	mating surface
68	device aperture
70	two-band gripping handle
72	first handle portion
74	second handle portion

What is claimed is:

1. A handle in combination with a working device, comprising:

a handle section for contact with the palm and fingers of a user including a palm sidewall, a finger sidewall, an outer surface and an inner surface and a butt surface at a bottom of said handle section, said outer surface having an outer end and an outer common end, said inner surface having an inner end and a common inner end, said handle section having a cross-section that is substantially ovate, each of said palm sidewall and said finger sidewall being substantially flat;

a thumb section for contact with the thumb of the user joined to said handle section, said thumb section including a thumb upper wall, a lower wall, a first sidewall and a second sidewall, said thumb section with a distal end and an opposite end joined to said handle section, said thumb section having a front portion with a first length and a back portion with a second length that intersects said front portion to define an angle, said second length being greater than one-half of said first length and said back portion terminating adjacent to said common outer end and said common inner end;

a butt surface extending between said outer end of said handle section outer surface and said inner end of said handle section inner surface; and

- a working device held in said handle section and extending in a direction that is different from perpendicular to said butt surface;
- wherein a first angle is defined between a line extending through said butt surface and a line extending through said handle section outer surface, a second angle is defined between a line extending through said butt surface and a line extending from said outer common end of said handle section through said distal end of said thumb section, said first angle being different from  $90^\circ$ , said first angle being greater than said second angle, and said second angle being in the range of  $35^\circ$ – $55^\circ$ .
- 2.** A handle in combination with a working device, as claimed in claim 1, wherein:
- said finger sidewall has a number of widths extending between said outer and inner surfaces of said handle section.
- 3.** A handle in combination with a working device, as claimed in claim 1, wherein:
- a third angle is defined between a line extending along said lower wall of said thumb section and a line extending along said butt surface, said line extending along said lower wall not extending inwardly of said thumb section, said third angle being greater than said second angle and in which said third angle is closer in magnitude to said first angle than to said second angle.
- 4.** A handle in combination with a working device, as claimed in claim 1, wherein:
- said first angle is in the range of  $65^\circ$ – $85^\circ$ .
- 5.** A handle, as claimed in claim 1, wherein:
- said second angle is about  $45^\circ$ .
- 6.** A handle in combination with a working device, as claimed in claim 1, wherein:
- each of said handle section and said thumb section has a length, said length of said handle section being in the range of 3.5–5.5 inches and said length of said thumb section being in the range of 1.5–2.5 inches.
- 7.** A handle in combination with a working device, as claimed in claim 1, wherein:
- each of said handle section and said thumb section has a width, said width of said handle section being in the range of 1.0–1.75 inches and said width of said thumb section being in the range of 1.0–1.75 inches.
- 8.** A handle in combination with a working device, as claimed in claim 1, wherein:
- each of said handle section and said thumb section has a thickness, said thickness of said handle section being in the range of 0.6–1.0 inch and said thickness of said thumb section being in the range of 0.6–1.0 inch.
- 9.** A handle in combination with a working device, as claimed in claim 1, wherein:
- said working device includes a cannula connected substantially parallel to said butt surface.
- 10.** A handle in combination with a working device, as claimed in claim 1, wherein:
- said thumb section has a width and said handle section has a thickness and in which said width of said thumb section is substantially the same as said thickness of said handle section.
- 11.** A handle in combination with a working device, as claimed in claim 1, further comprising:
- a left handle portion having a first mating surface and a first device recess; and
- a right handle portion having a second mating surface and a second device recess;
- wherein said first and second mating surfaces may be positioned adjacent to one another to form the handle with a device aperture.

- 12.** A handle in combination with a working device, as claimed in claim 11, wherein:
- said left handle portion and said right handle portion are hingedly interconnected.
- 13.** A handle in combination with a working device, as claimed in claim 11, wherein:
- said mating surfaces extend from said distal end of said thumb section to said butt surface.
- 14.** A handle in combination with a working device, as claimed in claim 11, wherein:
- said mating surfaces extend from said outer surface of said handle section and said thumb wall to said inner surface of said handle section and said lower wall of said thumb section.
- 15.** A handle comprising:
- a handle section for contact with the palm and fingers of a user including a palm sidewall, a finger sidewall, an outer surface and an inner surface, said outer surface having an outer end and a common outer end, said inner surface having an inner end and a common inner end, said handle section having a cross-section that is substantially ovate, each of said palm sidewall and said finger sidewall being substantially flat;
- a thumb section for contact with the thumb of the user joined to said handle section, said thumb section including a thumb upper wall, a lower wall, a first sidewall and a second sidewall, said thumb section with a distal end and an opposite end joined to said handle section, said thumb section having a front portion with a first length and a back portion with a second length that intersects said front portion to define an angle, said back portion terminating adjacent to said handle section, said second length being greater than one-half of said first length, a majority of said front portion having a width that is greater than a majority of the widths of each of said outer surface and said inner surface of said handle section; and
- a butt surface extending between said outer end of said handle section outer surface and said inner end of said handle section inner surface.
- 16.** A handle, as claimed in claim 15, wherein:
- a majority of said front portion is wider than said back portion.
- 17.** A handle, as claimed in claim 15, wherein:
- a first angle is defined between a line extending along said butt surface and a line extending along said handle section outer surface, a second angle is defined between a line extending along said butt surface and a line extending from said outer common end of said handle section to said distal end of said thumb section, and a third angle is defined between a line extending along said lower wall of said thumb section and a line extending along said butt surface and in which said line extending along said lower wall does not pass inwardly of said thumb section, said third angle being greater than said second angle and in which said third angle is closer in magnitude to said first angle than to said second angle.
- 18.** A handle, as claimed in claim 15, in combination with:
- a working device connected adjacent to one of: (a) said distal end of said thumb section and (b) said butt surface while being closer to parallel to said butt surface than perpendicular thereto.
- 19.** A handle comprising:
- a handle section for contact with the palm and fingers of a user including a palm sidewall, a finger sidewall, an

## 11

outer surface and an inner surface, said outer surface having an outer end and an common outer end, said inner surface having an inner end and a common inner end, said handle section having a cross-section that is substantially ovate, each of said palm sidewall and said finger sidewall being substantially flat;

a thumb section for contact with the thumb of the user joined to said handle section, said thumb section including a thumb upper wall, a lower wall, a first sidewall, and a second sidewall, said thumb section with a distal end and an opposite end joined to said handle section, said thumb section having a front portion with a first length and a back portion with a second length that intersects said front portion to define an angle, said back portion terminating adjacent to said handle section, said second length being greater than one-half of said first length, a majority of said front portion having a width that is greater than the width of said back portion; and

a butt surface extending between said outer end of said handle section outer surface and said inner end of said handle section inner surface.

**20.** A handle, as claimed in claim **19**, wherein:

a majority of said front portion is wider than each of said outer and inner surfaces of said handle section.

## 12

**21.** A handle, as claimed in claim **19** wherein:

a first angle is defined between a line extending along said butt surface and a line extending along said handle section outer surface, a second angle is defined between a line extending along said butt surface and a line extending from said common outer end of said handle section to said distal end of said thumb section, and a third angle as defined between a line extending along said lower wall of said thumb section and a line extending along said butt surface, said line extending along said lower wall not passing inwardly of said thumb section, said third angle being greater than said second angle and in which said third angle is closer in magnitude to said first angle than to said second angle.

**22.** A handle, as claimed in claim **21**, wherein:

said first angle is in the range of 65°–85° and said second angle is in the range of 35°–55°.

**23.** A handle, as claimed in claim **19**, in combination with:

a working device connected adjacent to one of: (a) said distal end of said thumb section and (b) said butt surface while being closer to parallel to said butt surface than perpendicular thereto.

\* \* \* \* \*