



US006546852B1

(12) **United States Patent**  
**Mazzoni et al.**

(10) **Patent No.:** **US 6,546,852 B1**  
(45) **Date of Patent:** **Apr. 15, 2003**

(54) **METHOD AND MACHINE FOR PACKAGING SKEINS, SHAPED AS RINGS, OF A FLEXIBLE, ELONGATED ELEMENT**

(75) Inventors: **Andrea Mazzoni**, Macerata (IT);  
**Marco Mazzanti**, Porto Potenza Picena (IT)

(73) Assignee: **SICA S.p.A.**, Alfonsine (IT)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 33 days.

(21) Appl. No.: **09/615,750**

(22) Filed: **Jul. 13, 2000**

(30) **Foreign Application Priority Data**

Aug. 5, 1999 (EP) ..... 99830514

(51) **Int. Cl.<sup>7</sup>** ..... **B65B 13/02**

(52) **U.S. Cl.** ..... **100/2; 100/5; 53/204; 53/589; 53/118**

(58) **Field of Search** ..... 53/116, 117, 118, 53/176, 589, 852, 590, 409, 204; 100/12, 5

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,835,194 A 5/1958 Crosby

2,905,078 A 9/1959 Laine  
3,118,367 A \* 1/1964 Lindholm ..... 100/12  
3,675,569 A \* 7/1972 Moor ..... 100/12  
3,973,600 A \* 8/1976 Choromokos ..... 100/12  
4,572,370 A \* 2/1986 Cedenblad et al. .... 206/398  
5,540,142 A \* 7/1996 Mieleszuk et al. .... 100/12

\* cited by examiner

*Primary Examiner*—Rinaldi I. Rada

*Assistant Examiner*—Thanh Truong

(74) *Attorney, Agent, or Firm*—Browdy and Neimark

(57) **ABSTRACT**

A method for packaging skeins shaped as a circular ring of a flexible element of elongated shape, in particular a cable or a hose, wherein the turns are held unitarily to each other, comprises the following phases: sustaining the skein in overhang towards a binding station holding it by the clamping of opposite planar faces of the skein effected in correspondence with at least a first portion of the skein; binding the skein in correspondence with at least its second, free, portion which projects from the first held portion; rotating the skein around its own axis of symmetry by a predetermined angle with respect to the position of the skein in the previous binding phase; and binding the skein again in correspondence with its own rotated position. The invention further relates to a machine that realizes the method.

**13 Claims, 4 Drawing Sheets**





Fig.1






Fig. 2






Fig. 4




Fig. 5



## METHOD AND MACHINE FOR PACKAGING SKEINS, SHAPED AS RINGS, OF A FLEXIBLE, ELONGATED ELEMENT

### BACKGROUND OF THE INVENTION

The present invention relates to the packaging of skeins shaped as circular rings of flexible elements, of elongated shape, such as hoses, cables and the like, and in particular it pertains to a method for packaging the skeins and a packaging machine that implements said method.

The packaging of elongated, flexible, elements into skeins shaped as circular rings currently comprises: a) winding the flexible element onto itself in such a way as to form an ordered succession of turns in mutual contact; and b) connecting the turns together in such a way as to maintain them tightly wound to each other in order to allow the entire skein to be handled as a single body, with no danger that the skein may unravel as a result of the relative displacement of the turns; said connection being hereafter defined with the generic term of binding, regardless of the way said binding is in fact achieved.

The aforesaid packaging is effected by means of various techniques.

A first known packaging procedure provides for the unitary retaining of the turns by means of a certain number of independent bindings, regularly distributed along the skein. Each of these bindings is effected by means of a retaining ring which: is embodied by a strip positioned on its own plane radial to the skein; envelops the turns intersecting their related planes; concatenates with the totality of the turns; and is so tightened as to compress all turns in mutual contact conferring a substantial overall rigidity to the skein.

The aforesaid bindings are obtained by means of machines comprising a certain number of operating heads, or otherwise machines with a single head provided with a plurality of guiding slots, located at regular intervals around the skeins and each forming a ring for holding the turns by dispensing, clamping and cutting a packaging ribbon, commonly called strap, which unwinds from a related coil.

The operating heads are in a well-determined number by construction, so that the related packaging machine can effect a number of bindings exactly corresponding to the number of operating heads, or even a lesser number through the deactivation of one or more heads suitably chosen to allow the formation of bindings regularly distributed along the contour of the skein.

The number and location of the heads with which the machine is provided by construction rigidly condition the operating capabilities of the machine itself. Although in general the possibility of varying the binding pitch is not precluded, the aforesaid packaging machines can in fact produce bindings that are mutually offset according to a rather limited number of different pitches so that such machines are characterized, in actuality, by a high productive rigidity.

A second packaging technique, also known and representing an advance over the previous one, calls for combining with the aforesaid bindings, effected with a strap, a band of plastic film (for instance of heat-shrinking material) which is positioned around the circumference of the skein in such a way as to form an exterior sheath, constituted by a single annular strip that encompasses the cylindrical contour surface of the skein and holds the totality of the turns within it. Such containment sheath serves the fundamental purpose of

preventing the skein from unraveling while in use when, after the holding rings lying on the radial planes of the skein have been cut or untied, a certain length of hose or cable is extracted and cut from the skein itself.

This packaging technique obviously retains unaltered all the limitations, in terms of binding pitch options, of the machines that embody the technology discussed above. Moreover, it requires a greater manufacturing complexity of the packaging machines; and lastly it entails a greater quantity of packaging material, with obvious consequences both in terms of production cost and of the disposal of the skein packing.

A third packaging method, known from the patent document MC 98A000074, describes a technique that calls for each ring shaped skein to be wrapped entirely, and externally, from one side and from the other, with successive wraps of an uninterrupted, extensible ribbon. The wraps are effected in such a way as to form a sheath wherein each wrap is located on a plane transverse to the skein itself and angularly offset with respect to the wraps that immediately precede and immediately follow.

This packaging method presents numerous advantages, such as that of allowing packaging with very thin film, hence with considerable material savings, and that of allowing to draw and cut the cable from the skein, from the beginning to the end thereof, without it ever being possible for the skein to unravel.

### SUMMARY OF THE INVENTION

The aim of the present invention is to eliminate all the drawbacks of the known solutions, ascribable to the execution of bindings with predetermined pitch by means of a packaging method able to allow holding the turns of the skein together with bindings distanced at regular pitches with respect to the axis of symmetry of the skein, of any amplitude; able to be modulated progressively and selectable on each occasion according to the specific packaging in process and in particular to the dimensions of the various skeins and to the characteristics of the hose or of the cable that constitute them.

In accordance with the invention, this aim is attained by a machine for packaging skeins of flexible elements, of elongated shape, in particular cables or hoses, shaped as a circular ring and constituted by an ordered succession of turns, said machine being provided with at least a station for binding the turns, and comprising a feeding station provided with skeins clamping means, wherein such clamping means comprise jaws shaped as circular sectors, which are able to rotate around an axis of rotation passing in proximity to its own vertex; said jaws holding the skeins by means of clamping operated on opposite planar faces of the skein and in correspondence with at least a first portion of said faces; a second portion of said faces being let free from clamping and projecting from jaws towards the binding station; said binding station effecting at least one binding of the turns in correspondence with at least the second portion of the skein and effecting such bindings in appropriate phase relationship with the rotations imparted to the skein by the jaws in the feeding station.

The machine has a general configuration that is suited to allow indifferently to realize all binding types with the sole condition of being equipped with the specific type of head corresponding to the different packaging techniques. If the binding station is of the type able to dispense a packing ribbon or a strap, the machine according to the invention allows to realize radial bindings with no constraint limiting the number and distance between the bindings.



If, vice versa, the binding station is embodied by a wrapping head able to dispense a ribbon of plastic film, able to be deformed elastically and longitudinally and uninterrupted, the packaging machine can be set up to provide one of the possible concrete embodiments of the method as per patent application MC 98A000074.

### BRIEF DESCRIPTION OF THE DRAWINGS

The technical characteristics of the invention, according to the aforesaid aims, can clearly be noted from the content of the claims below and its advantages shall become more readily apparent in the detailed description that follows, made with reference to the accompanying drawings, which represent an embodiment provided purely by way of non limiting example, in which:

FIG. 1 is a perspective overall view of a first embodiment of the machine according to the invention;

FIG. 2 is a top plan view of the machine of FIG. 1;

FIG. 3 is a perspective overall view of a second embodiment of the machine according to the invention;

FIG. 4 is a front side perspective view of the machine shown with some parts removed the better to highlight others;

FIG. 5 is a rear side perspective view of the machine in FIG. 4.

### DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to the drawings of the accompanying figures, a method is described for packaging a flexible element **33** of elongated shape, such as in particular a cable or a hose of plastic or elastic material, in the form of skeins **3** (FIGS. 1 and 3) shaped as a circular ring, comprising a plurality of turns **2**, which are held together, or bound, to allow for the easy and convenient handling, transportation, storage, and use of the elongated element, without the unraveling of the skein **3**.

More specifically, the flexible element **33**, continuously fed in substantially rectilinear form and according to the direction of advance indicated with arrow **6**, is at first repeatedly wound onto itself to form the skein **3** and is then suitably bound in such a way that it remains stable in its wound condition.

The winding is performed conventionally. The packaging of the already wound skein **3**, which instead is the specific subject of the present invention, comprises the following phases:

sustaining the skein **3** in overhang towards a binding station **9** holding it by the clamping of opposite planar faces **4** of the skein **3** effected in correspondence with at least a first portion **5a** of said skein **3**;

binding the skein **3** in correspondence with at least its second, free, portion **5b** which projects from the first held portion **5a**;

rotating the skein **3** around its own axis of symmetry **3a** by a predetermined angle  $\beta$  with respect to the position of the skein **3** in the previous binding phase; and

binding the skein **3** again in correspondence with its own rotated position.

The succession of phases, which can be repeated several times, to effect multiple bindings, as shall become readily apparent below, finds its concrete realization in a packaging machine **1** which essentially comprises: a winding station **12**; a feeding station **8**; and a binding station **9** arranged in series.

The winding station **12** essentially comprises a drum **35** able to rotate around a horizontal axis **14** and a motor-driven reel **13** coaxial to the drum **35**.

The reel **13** is able to rotate around the horizontal axis **14**, integrally with a shaft **20** driven in rotation by a gear motor **21**; it is borne laterally projecting from a vertical side **15** of the machine **1** and it is movable along the axis of rotation of the drum **35**, i.e. perpendicularly to the side **15**, bi-directionally, upon the activation of related actuation means embodied by a fluid-driven linear actuator.

The drum **35** has a first flange **16** fixed and substantially coplanar with the side **15**. A second flange **17** of the drum **35** is supported by a frame **18** translatable on guides **19** oriented parallel to the axis **14** of rotation of the drum **35**.

Adjustment means, comprising an adjusting screw **22** with hand-wheel **23** are operatively situated between the side **15** and the frame **18** that supports the second flange **17**. The actuation of the adjusting means **22,23** allows to move the flanges **16,17** of the drum **35** closer or, vice versa, farther away, in order to allow the forming between them of skeins **3** differing in dimensions and number of layers of turns **2**.

Below the reel **13**, the winding station **12** comprises an L shaped support **24**, fitted with related motor-driving means **25**, which support can be associated to the flanges **16,17** of the drum; it is alternatively movable between the winding station **12** and the binding station **9** and it is able to receive the skein **3** from the drum **35** and to transfer it into the feeding station **8**.

More in particular, upon completion of the skein **3**, the reel **13** is extracted from the drum **35**, perpendicularly to the side **15**, whilst the skein **3**, which remains contained in position between the flanges **16** and **17** of the drum **35** is taken up by the L-shaped support **24**. The latter, which together with its own motor-driving means **25** provides concrete embodiment to more general transfer means operating in phase co-ordination with the motion of the reel **13**, then transfers the skein **3** from the winding station **12** to the feeding station **8** situated downstream.

It is important to note that the movement of extracting and inserting the reel **13**, with respect to the drum **35** and perpendicularly to the side **15**, is very fast so that the skein **3** is freed in a very short time from the central position of the reel **13**, thus being able to be thrust by the L-shaped support **24** without hindrance, whereupon the reel **13** can return to its working position necessary to start a new skein **3**. Since these operations occur in a few seconds, such characteristics are revealed to be significantly advantageous with respect to traditional machines provided with automatic coil winder change and in particular slaved to continuous working lines wherein the products advance at high speed.

The feeding station **8** is provided with a pair of parallel, planar and vertically oriented jaws **10**, between which the skein **3** is positioned, with one supported by the side **15** and the other by the frame **18**.

The jaws **10** preferably have the shape of planar circular sectors, which are able to rotate around an axis of rotation **10a** passing in proximity of their vertex and are movable relatively to each other along the axis of rotation **10a** to be able to translate according to the direction of the axis of rotation **10a**, to vary their relative distance and correspondingly to clamp the skein **3** interposed to them.

For the jaw **10**, which is integral to frame **18**, this freedom of motion is solely for adjustment purposes and it is obtained indirectly as a consequence of the possibility of making the frame **18** translate along its own guides **19**. For the jaw **10** supported instead by the side **15**, the translation is obtained directly and by means of the support of the jaw **10** itself on



## 5

bars **26** oriented parallel to the axis of rotation **10a** and mounted on related sliding guides **27**.

The jaws **10** are driven in rotation around the axis **10a** and, in relative translation, along said axis **10a**, by actuating means comprising first and second linear actuators **28** and **29**, preferably embodied by fluid-driven pistons.

The first linear actuators **28**—whereof only one is visible from the figures—are operatively interposed, in correspondence with a first side of the machine **1**, to the frame **18** and to the corresponding jaw **10** supported thereby; and in correspondence with the opposite side of the machine **1** they are instead interposed to the side **15** and to a revolving frame **30**, which in turn supports the jaw **10**, the bars **26** and the sliding guides **27**. The first linear actuators **28** act on parallel planes, orthogonal to the axis of rotation **10a**.

The second linear actuators **29** instead act in a direction parallel to the axis of rotation **10a** of the jaws moving the related jaw **10** closer to or farther away from the frame **30** that supports it.

The constructive shape of the jaws **10** allows such a positioning of the skeins **3** in the feeding station **8** that the skeins **3**, when they arrive in the feeding station **8**, are held in partial overhang towards the binding station **9**.

The jaws **10** embody, summarily, more general clamping means which, operating on opposite planar faces **4** of the skein **3**, act solely in correspondence with a first portion **5a** thereof; and which allow to impart to the skein **3** angular excursions of desired amplitude, in rotation around its own axis of symmetry **3a**, as a consequence of the activation, suitably coordinated in phase, of the actuator means **28,29**. Lastly, the jaws **10** allow to sustain the skein **3** with a second portion **5b** projecting in overhang towards the binding station **9**.

The binding station **9** can be obtained in general by means of at least two different embodiments, whereof the first one is shown in FIGS. **1** and **2**, the other one instead being shown in FIG. **3**.

In the first embodiment, the binding station **9** is fitted with a single operating head **31** which operates on the second portion **5b** of the skein **3** and which is so designed as to effect bindings of the turns **2** in appropriate phase relationship with the rotations imparted to the skein **3** by the jaws **10** of the feeding station **8**.

The operating head **31** (FIG. **2**) is of conventional construction and it is suited to effect bindings of the type that form a holding ring **11** of the turns **2** of the skein **3**, which ring is oriented transversely to the turns **2** and radially intersects the turns **2** of the skein **3** itself concatenating therewith, as FIG. **1** clearly shows. The holding ring **11** can be obtained by means of a strip of conventional packing ribbon or by means of a strap made of metallic or plastic material.

An alternative construction of the binding station **9** can be obtained by means of an operating head **32**, conventionally shaped in itself, able to effect a wrapping of the second portion **5b** by means of a continuous strip of packing material embodied in particular by a film able to be deformed elastically and longitudinally.

In this case the ring **11** for holding the skein **3** is obviously single and it is constituted by an uninterrupted succession of elementary wraps **11e** which envelop the entire skein **3** solely from the exterior. The elementary wraps **11e** are partly superposed on each other. Moreover, each of the elementary wraps **11e** lies in its own surface, substantially planar, offset in phase with respect to the surfaces whereon the preceding and the following elementary wrap **11e** lie by an appropriate angle  $\beta$  defined around the axis of symmetry **3a** of the skein

## 6

**3** (FIG. **3**). The angles  $\beta$  are programmable with amplitudes varying at will and are not subject to limits of any sort, unlike in traditional machines, wherein bindings can be effected only between one radius and another.

If the elementary wraps **11e** are obtained in such a way as to intersect the planar faces **4** of the skeins **3** substantially along chords of the related circular shape, an outer covering sheath of the entire skein can be obtained, provided with a hole **34** situated in proximity to the axis of the skein **3**; hole which vice versa is lacking if the elementary wraps **11e** are offset in phase in such a way as to intersect the aforesaid planar faces **4** substantially along the various diameters of the circular shape of the planar faces of the skein **3**. The presence or absence of the hole **34** can be advantageous, depending on specific application circumstances. In packages effected by wrapping along the chords the presence on the covering sheath of the skein **3** of a free, through central hole **34** is useful to facilitate gripping and transporting the skein **3** and, briefly, to facilitate its handling.

In the packages wherein the wrapping is instead effected along the diameters, the realization of a totally closed covering, lacking the hole **34**, enables to isolate the skein from possible contact with extraneous substances (in particular dust), whilst allowing to provide a useful surface of the sheath for the application of labels.

The operation of the machine **1** is controlled automatically by direction and control means, not shown herein, which impart the commands in sequence and in suitable phase scan to the winding station **12**, feeding station **8** and binding station **9**.

The detailed description of such operation is omitted as it can be completely deduced, with no need for additions to the preceding discussion. The observation shall merely be provided that, by activating the clamping and rotation of the jaws **10** in appropriate phase relationship with the binding station **9** and with appropriate amplitude of the travel of the first linear actuators **28**, it is possible to impart to the skein **3** rotations of angular amplitude suitable to allow the realization of bindings of the turns **2** positioned around the axis of symmetry **3a** of the skein **3** in any number whatsoever. This feature is very advantageous in that the same machine **1** can be set up with a few simple adjustments, possibly automated and controlled directly by the control means, to tackle packaging problems of a general nature which can be referred to elongated elements **33** with different geometric and physical characteristics; and/or to skeins **3** of different dimensions.

In regard to the fastening of the film employed to bind the skeins **3** by continuous wrapping, it should be observed that at the end of the packaging operation, the film is cut and, with slight pressure, is thrust against the wrapping that has just been obtained whereto it adheres spontaneously by electrostatic adhesion. A different fastening method instead provides for the employment of an adhesive label **37** which is applied to an end of the film strip and to the underlying wrapping, as shown in FIG. **3**.

The machine according to the invention, in addition to allowing to obtain with the utmost operative flexibility the realization of various types of packaging and the achievement of the most suitable packaging for each specific product, also allows a considerable constructive standardization of the packaging machines. The shift from one configuration to another for these machines can be obtained by means of the diversification of only the operating heads **31** or **32**, with the consequent advantageous implications in terms of reduced production costs and, therefore, in terms of reduced sale prices.



Lastly, it is important to observe that the constructive modularity of the machine 1, in particular regard to the feeding station 8 and the binding station 9, can be exploited to realize also autonomous, off-line, winding machines, which can advantageously effect, for instance for protection purposes, also the continuous wrapping with film of a skein 3 which has already been bound with a strap. In this case, then, once the skein 3 has been formed and bound conventionally it can be made to reach the feeding station 8, whereupon the machine 1 executes the wrapping and the final packaging in a manner identical to the one described above.

What is claimed is:

1. Machine for packaging skeins of flexible elements of elongated shape, each skein being shaped as a circular ring having opposite planar faces and an axis of symmetry and being constituted by an ordered succession of turns, said machine comprising: a station for binding the turns; and a feeding station provided with skein clamping means, wherein said clamping means comprise jaws shaped as circular sectors, which are able to rotate around an axis of rotation, said jaws holding one of the skeins by applying a clamping force to the opposite planar faces of a first portion of the skein while the skein is positioned so that the axis of symmetry of the skein corresponds at least approximately to the axis of rotation of said jaws and the opposite planar faces of a second portion of said skein extend beyond said jaws and are thus exposed, wherein said second portion of the skein projects from said jaws towards said binding station; said binding station effecting at least one binding of the turns in correspondence with at least the second portion of the skein and effecting such bindings in appropriate phase relationship with rotations imparted to the skein by said jaws in said feeding station.

2. The machine according to claim 1, wherein jaws are a pair of planar and parallel jaws, between which the skein is positioned, said jaws being movable relatively to each other to vary their mutual distance and correspondingly clamp the interposed skein.

3. The machine according to claim 2, wherein said jaws are oriented vertically.

4. The machine according to claim 3, further comprising a support shaped to associate itself to said jaws of the feeding station and to support the interposed skeins when such skeins are released by the jaws.

5. The machine according to claim 1, wherein said jaws are able to rotate around a direction parallel to the axis of symmetry of the skein.

6. The machine according to claim 5, comprising actuator means that effect the clamping and rotation of said jaws in appropriate phase relationship with said binding station to impart to the skein successive rotations able to expose successive parts of the skein to said binding station.

7. The machine according to claim 6, wherein said actuator means comprise at least a first actuator means operatively interposed between a fixed structure of the machine and at least one of said jaws, and said actuator means impart to said jaws angular excursions which, in combination with the clamping effected by said jaws, transmits to the skein a rotational motion around its own axis of symmetry.

8. The machine according to claim 1, wherein said binding station dispenses a strip of packing material or a strap.

9. The machine according to claim 1, wherein said binding station employs a strip of plastic film capable of being deformed elastically and longitudinally.

10. The machine according to claim 1, further comprising a wrapping station provided with a drum able to rotate around an axis of rotation and with a reel for winding a flexible element on the drum, wherein said reel is mounted coaxial to the drum and is motor-driven to be movable parallel to the axis of rotation of the drum in order to be able to be extracted to free a formed skein contained in the drum, and to be subsequently reintroduced into the drum for the formation of a new skein.

11. The machine according to claim 10, comprising transfer means operating in phase co-ordination with the motion of the reel with respect to the drum to transfer the skein from the winding station to the feeding station.

12. The machine according to claim 11, wherein said transfer means comprise a support shaped to associate itself to the flanges of the drum and to sustain the skein interposed thereto, said support being alternatively movable between the winding station and the feeding station upon activation of related motor-driving means.

13. The machine according to claim 12, wherein said support is shaped as an L and is movable in a space between the flanges of the drum.

\* \* \* \* \*