



US006565445B1

(12) **United States Patent**
Miller

(10) **Patent No.:** **US 6,565,445 B1**
(45) **Date of Patent:** **May 20, 2003**

(54) **TORSIONAL VIBRATION DAMPENING ASSEMBLY**

(75) Inventor: **Jeffrey E. Miller**, Auburn, IN (US)

(73) Assignee: **Auburn Clutch Co., Inc.**, Garrett, IN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/878,763**

(22) Filed: **Jun. 11, 2001**

(51) **Int. Cl.**⁷ **F16D 3/14**

(52) **U.S. Cl.** **464/64; 192/203**

(58) **Field of Search** 464/68, 89, 64; 267/166, 169, 174; 192/203, 209, 210, 210.1, 211

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,321,941 A	*	6/1943	Rose	464/68
2,513,379 A	*	7/1950	Thelander	464/68 X
2,674,863 A	*	4/1954	Thelander	464/68
3,791,170 A	*	2/1974	Schmidt	464/69
4,093,054 A	*	6/1978	Johns	192/209 X
4,197,931 A	*	4/1980	Norcia	192/203
4,646,899 A	*	3/1987	Murakami	192/209
4,693,354 A	*	9/1987	Umeyama et al.	...	192/210.1 X
4,743,217 A	*	5/1988	Tojima et al.	464/64 X
4,765,642 A	*	8/1988	Struzina	280/656
4,789,375 A		12/1988	Bassett		
4,890,712 A	*	1/1990	Maucher et al.	464/68 X
4,991,827 A	*	2/1991	Taylor		
5,099,973 A		3/1992	Flotow et al.		
5,203,750 A		4/1993	Oster		
5,273,372 A	*	12/1993	Friedmann et al.	464/24

5,370,581 A	*	12/1994	Rohrle et al.	464/89 X
5,377,796 A	*	1/1995	Friedmann et al.	464/68 X
5,657,845 A		8/1997	Szadkowski et al.		
5,735,747 A		4/1998	Gehrke		
5,860,889 A		1/1999	Schlosser		
5,951,402 A		9/1999	Baldwin		
6,332,843 B1	*	12/2001	Hashimoto et al.	464/64 X

FOREIGN PATENT DOCUMENTS

GB		589989	*	7/1947	464/64
----	--	--------	---	--------	-------	--------

* cited by examiner


Primary Examiner—Greg Binda

(74) *Attorney, Agent, or Firm*—MacMillan, Sobanski & Todd, LLC

(57) **ABSTRACT**

A torsional vibration dampening assembly includes a hub having a radially outwardly extending flange with a plurality of openings formed therethrough. A pair of cover plates are supported on the hub for rotation relative thereto, each having a corresponding plurality of openings formed there-through. A first stage vibration damper, including an annular central damper element having inner and outer rings secured thereto, extends between the second cover plate and the hub. A second stage vibration damper includes a spring damper assembly provided in each of the openings. Each of the spring damper assemblies includes a coiled spring having ends that react against first and second end caps. A movement restraining structure is provided for restraining the end caps from moving freely relative to one another under the urging of the spring. A hollow cylindrical isolation sleeve is disposed about each of the springs. The isolation sleeves prevent the springs from directly engaging the first and second cover plates and the hub during use, thus lowering the amount of noise that is generated during use of the torsional vibration dampening assembly.

11 Claims, 3 Drawing Sheets







FIG. 1






FIG. 3

TORSIONAL VIBRATION DAMPENING ASSEMBLY

BACKGROUND OF THE INVENTION

This invention relates in general to coupling devices for connecting first and second members together for concurrent rotation. In particular, this invention relates to an improved structure for a torsional vibration dampening assembly for use either as a direct coupling between such first and second members or as a driven disc assembly in a clutch for selectively connecting such first and second members.

Rotational coupling devices are structures that are adapted to connect first and second members together for concurrent rotation. For example, in the context of a vehicle drive train system, a rotational coupling device can be used to connect a source of rotational power, such as a flywheel that is secured to an engine driven crankshaft, to a rotatably driven device, such as an input shaft of a transmission. In some instances, the rotational coupling device provides a direct connection between the two members such that the flywheel constantly rotatably drives the input shaft of the transmission. In other instances, the rotational coupling device is provided within a clutch that selectively connects the two members such that the flywheel intermittently rotatably drives the input shaft of the transmission.

In such a vehicle drive train system, it is known that relatively high frequency torsional vibrations can be transmitted from the engine through the rotational coupling device to the transmission and other components of the drive train system. Such torsional vibrations can generate undesirable noise. To prevent or minimize this from occurring, it is often desirable to provide the rotational coupling device with a torsional vibration dampening assembly. The torsional vibration dampening assembly is adapted to reduce the magnitude of torsional vibrations that are transmitted through the rotational coupling device from the flywheel to the input shaft of the transmission.

To accomplish this, a typical torsional vibration dampening assembly includes two rotary torque transmitting elements that are rotatable relative to one another throughout a limited angular distance. The two rotary torque transmitting elements are connected together by a lost motion connection and by a spring damper drive. The lost motion connection is utilized to establish a positive driving connection between the two rotary torque transmitting elements, while permitting a limited range of free movement therebetween. The spring damper drive is utilized to establish a resilient driving connection between the two rotary torque transmitting elements within the limited range of free movement permitted by the lost motion connection. The spring damper drive can also be utilized to tune the vehicle drive train system so as to prevent or minimize vibrations from occurring therein within the operating speed range of the engine.

Although known torsional vibration dampening assemblies have functioned satisfactorily, it has been found that the torsional vibrations from the engine can still be transmitted from the engine to the transmission and other components of the drive train system, generating undesirable noise. Thus, it would be desirable to provide an improved structure for a torsional vibration dampening assembly that provides better vibration isolation and, consequently, reduces the amount of noise that is generated during use.

SUMMARY OF THE INVENTION

This invention relates to an improved structure for a torsional vibration dampening assembly for use in a rota-

tional coupling device, such as in a vehicle drive train system. The torsional vibration dampening assembly includes a hub having a radially outwardly extending flange. A plurality of openings are formed through the annular flange. A pair of cover plates are supported on the hub for rotation relative thereto. Each of the cover plates has a plurality of openings formed therethrough that correspond in number and location to the openings formed through the annular flange of the hub. A first stage vibration damper extends between the second cover plate and the hub. The first stage vibration damper includes an annular central damper element having inner and outer rings secured thereto. A second stage vibration damper includes a spring damper assembly that is provided in each of the openings formed through the flange of the hub and the first and second cover plates. Each of the spring damper assemblies includes a resilient member, such a coiled spring, having ends that react against first and second end caps. A movement restraining structure is provided for restraining the end caps from moving freely relative to one another under the urging of the spring. A hollow cylindrical isolation sleeve is disposed about the spring and extends axially between the end caps. The isolation sleeve prevents the spring from directly engaging the sides of the openings formed through the first and second cover plates, respectively, and the sides of the opening formed through the flange of the hub during use. As a result, metal to metal contact therebetween is prevented, thus lowering the amount of noise that is generated during use of the torsional vibration dampening assembly.

Various objects and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the preferred embodiment, when read in light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is front elevational view of a torsional vibration dampening assembly in accordance with this invention.

FIG. 2 is an enlarged sectional elevational view of a portion of the torsional vibration dampening assembly illustrated in FIG. 1.

FIG. 3 is an enlarged front elevational view, partially in cross section, of a portion of the torsional vibration dampening assembly illustrated in FIG. 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, there is illustrated a torsional vibration dampening assembly, indicated generally at **10**, in accordance with this invention. The torsional vibration dampening assembly **10** can be provided as a stand alone rotational coupling device that can, as described above, be connected directly between two rotatable members, such as a flywheel (not shown) and an input shaft (not shown) of a transmission in a vehicle drive train system. Alternatively, as also described above, the torsional vibration dampening assembly **10** can be provided as a driven disc assembly in a clutch (not shown) for selectively connecting the flywheel to the input shaft of the transmission in the vehicle drive train system.

As best shown in FIG. 2, the first rotary torque transmitting element of the torsional vibration dampening assembly **10** is embodied as a generally hollow cylindrical hub **11**. The hub **11** has an inner surface having a plurality of longitudinally extending splines **11a** or other similar structures formed therein. As is well known, the hub **11** is adapted to be supported on a shaft (not shown) that, as mentioned

above, can be embodied as the input shaft to the transmission. The shaft upon which the torsional vibration dampening assembly **10** is mounted preferably has a plurality of splines or other similar structures formed thereon that cooperate with the splines **11a** provided on the inner surface of the hub **11**. Thus, the torsional vibration dampening assembly **10** is connected to such shaft for concurrent rotation. The hub **11** further includes an annular flange **11b** that extends radially outwardly from the hub **11** and, in the illustrated embodiment, is formed integrally therewith. A plurality of openings **11c** are formed through the annular flange **11b**. In the illustrated embodiment, six equidistantly spaced openings **11c** are formed through the flange **11b**, although any desired number of such openings **11c** may be formed at any locations. The purpose for such openings **11c** will be explained below.

The second rotary torque transmitting element of the torsional vibration dampening assembly **10** is embodied as a pair of cover plates **12** and **13** that are supported on the hub **11** for rotation relative thereto. The first cover plate **12** is generally flat and annular in shape, having a central aperture **12a** formed therethrough. As a result, a first portion of the hub **11** (located on the left axial side of the flange **11b** when viewing FIG. 2) can extend through the central aperture **12a** of the first cover plate **12**, with a relatively small amount of radial clearance being provided therebetween. A plurality of openings **12b** are formed through the first cover plate **12**. In the illustrated embodiment, six equidistantly spaced openings **12b** are formed through the first cover plate **12**, although any desired number of such openings **12b** may be formed at any locations. Preferably, the openings **12b** formed through the first cover plate **12** correspond in number and location to the openings **11c** formed through the annular flange **11b** of the hub **11**, as described above. If desired, portions of the first cover plate **12** extending about portions of the openings **12b** may be angled outwardly in a first axial direction (toward the left when viewing FIG. 2), such as shown at **12c**. The purpose for such angled portions **12c** will be explained below.

Similarly, the second cover plate **13** is also generally flat and annular in shape. However, the second cover plate **13** has a hollow cylindrical flange **13a** that extends axially therefrom. As a result, a second portion of the hub **11** (located on the right axial side of the flange **11b** when viewing FIG. 2) can extend through the axially extending flange **13a** of the second cover plate **13**, with a relatively large amount of radial clearance being provided therebetween. A plurality of openings **13b** are formed through the second cover plate **13**. In the illustrated embodiment, six equidistantly spaced openings **13b** are formed through the second cover plate **13**, although any desired number of such openings **13b** may be formed at any locations. Preferably, however, the openings **13b** formed through the second cover plate **13** correspond in number and location to the openings **11c** formed through the annular flange **11b** of the hub **11** and to the openings **12b** formed through the first cover plate **12**, as described above. If desired, portions of the second cover plate **13** extending about each of the openings **13b** may be angled outwardly in a second axial direction (toward the right when viewing FIG. 2), such as shown at **13c**. The purpose for such angled portions **13c** will also be explained below.

A first stage vibration damper, indicated generally at **14**, extends between the axially extending flange **13b** of the second cover plate **13** and the second portion of the hub **11**. In the illustrated embodiment, the first stage vibration damper **14** includes an annular central damper element **14a**

having an inner ring **14b** and an outer ring **14c** secured thereto. Preferably, the central damper element **14a** is formed from a material that is relatively resilient, such as an elastomeric material (rubber, for example). The inner and outer rings **14b** and **14c** are preferably formed from a relatively wear-resistant material, such as steel. The inner and outer rings **14b** and **14c** can be bonded or otherwise secured to the central damper element **14a** to form the first stage vibration damper **14**. The first stage vibration damper **14** can be press fit or otherwise secured to or disposed between the axially extending flange **13b** of the second cover plate **13** and the second portion of the hub **11**. The operation of the first stage vibration damper **14** will be explained below.

If desired, a wave washer **15** and a friction washer **16** (see FIG. 2) may be provided about the first portion of the hub **11** between the first cover plate **12** and the flange **11b**. The wave washer **15** and the friction washer **16** are conventional in the art and form no part of this invention. An annular friction disc **17** is secured to the first and second cover plates **12** and **13** for concurrent rotation. In the illustrated embodiment, the friction disc **17** is secured to the first and second cover plates **12** and **13** by a plurality of rivets **18**, although any known securement mechanism can be used. As is well known, the friction disc **17** can either be connected directly to the flywheel or can be selectively frictionally engaged between the flywheel and the pressure plate in a clutch in the vehicle drive train system.

The torsional vibration dampening assembly **10** further includes a second stage vibration damper. In the illustrated embodiment, the second stage vibration damper includes a spring damper assembly, indicated generally at **20**, that is provided in each of the openings **11c** formed through the flange **11b** of the hub **11**. The structure of one of the spring damper assemblies **20** is illustrated in detail in FIG. 3. As shown therein, the illustrated spring damper assembly **20** includes a resilient member, such a coiled spring **21**, having ends that react against first and second end caps, indicated generally at **22** and **23**, respectively. Each of the end caps **22** and **23** has an enlarged head portion **22a** and **23a** that facilitates engagement by the associated end of the spring **21** so as to urge the end caps **22** and **23** outwardly apart from one another. Each of the end caps **22** and **23** further includes a hollow shank portion **22b** and **23b** that extends within and supports the associated ends of the spring **21** so as to maintain co-axial alignment during use.

A movement restraining structure is provided for restraining the end caps **22** and **23** from moving freely relative to one another under the urging of the spring **21**. In the illustrated embodiment, this movement restraining structure is embodied as a resilient spring sleeve **24** that extends between the end caps **22** and **23**, although any other structure that performs this function can be used. In the illustrated embodiment, the spring sleeve **24** is formed from a flat piece of a flexible material, such a metallic material, that is rolled into the general shape of a hollow cylinder such that the opposed edges of the spring sleeve **24** extend longitudinally adjacent to one another. If desired, such opposed edges may be formed having inwardly extending flanges (not shown) to increase the lateral strength thereof. Regardless, however, the spring sleeve **24** is generally C-shaped, and the opposed ends thereof extend within and frictionally engage the interiors of the hollow shank portions **22b** and **23b** of the end caps **22** and **23**, respectively. Thus, relative axial movement of the end caps **22** and **23** under the urging of the spring **21** is inhibited, but not prevented, by the frictional engagement of the spring sleeve **24** with the end caps **22** and **23**.

Lastly, the spring damper assembly **20** includes a hollow cylindrical isolation sleeve **25** that is disposed about the spring **21** and extends axially between the end caps **22** and **23**. The isolation sleeve **25** is provided to prevent the spring **21** from directly engaging the sides of the openings **12b** and **13b** formed through the first and second cover plates **12** and **13**, respectively, and the sides of the opening **11c** formed through the flange **11b** of the hub **11** during use. Such direct engagement can occur, for example, when relatively high frequency torsional vibrations are transmitted from the engine through the torsional vibration dampening assembly **10** to the transmission and other components of the drive train system and can result in the generation of undesirable noise. The isolation sleeve **25** prevents this direct engagement from occurring and, therefore, reduces the amount of such noise. Preferably, the isolation sleeve **25** is formed from a relatively durable, low friction material, such as nylon (which is available under the brand name of Zytel from E. I. duPont de Nemours and Company).

As mentioned above, portions **12c** of the first cover plate **12** extending about portions of the openings **12b** are angled outwardly in a first axial direction (toward the left when viewing FIG. 2), and portions **13c** of the second cover plate **13** extending about portions of the openings **13b** are angled outwardly in a second axial direction (toward the right when viewing FIG. 2). These portions **12c** and **13c** are provided to retain the spring damper assemblies **20** within the openings **12b** and **13b** formed through the first and second cover plates **12** and **13** and within the openings **11c** formed through the flange **11b** of the hub **11**.

As shown in FIG. 3, the spring damper assembly **20** has a relaxed axial length that is somewhat shorter than the axial length of the openings **12b** and **13b** formed through the first and second cover plates **12** and **13**, respectively, and the openings **11c** formed through the flange **11b** of the hub **11**. Thus, axial spaces exist between the end caps **22** and **23** and the adjacent axial ends of the openings **12b** and **13b** formed through the first and second cover plates **12** and **13**, respectively, and the openings **11c** formed through the flange **11b** of the hub **11**. The purpose for this axial spacing will be explained below.

The operation of the torsional vibration dampening assembly **10** will now be described. The first stage vibration damper **14** is provided to urge the first and second cover plates **12** and **13** toward a centered position relative to the flange **11b** of the hub **11** at a relatively low spring rate. When the first and second cover plates **12** and **13** are in a centered position relative to the flange **11b** of the hub **11**, the openings **12b** and **13b** formed through the first and second cover plates **12** and **13**, respectively, are axially aligned with the openings **11c** formed through the flange **11b** of the hub **11**, such as shown in FIG. 3. As mentioned above, in this situation, axial spaces exist between the end caps **22** and **23** and the adjacent axial ends of the openings **12b** and **13b** formed through the first and second cover plates **12** and **13**, respectively, and the openings **11c** formed through the flange **11b** of the hub **11**.

However, when relatively small variations occur in the amount of torque that is being transmitted through the torsional vibration dampening assembly **10**, such as when torque is transmitted through the torsional vibration dampening assembly **10**, the resilient central damper element **14a** of the first stage vibration damper **14** allows the first and second cover plates **12** and **13** to rotate as a unit relative to the flange **11b** of the hub **11** to a limited extent, while continuing to transmit torque therethrough. The resilient central damper element **14a** absorbs at least some of the

relatively small variations in the amount of torque being transmitted through the torsional vibration dampening assembly **10**, thereby reducing the amount of undesirable noise that otherwise might be generated. So long as the magnitude of this relative rotational movement remains relatively small, the end caps **22** and **23** of the second stage vibration damper will remain spaced apart from the axial ends of the openings **12b** and **13b** and the opening **11c** and, therefore, have no effect on the operation of the torsional vibration dampening assembly **10**.

If, however, the magnitude of this relative rotational movement increases as a result of an increase in the amount of torque being transmitted through the torsional vibration dampening assembly **10**, the end caps **22** and **23** of the spring damper assembly **20** will eventually be engaged and compressed between the axial ends of the openings **12c** and **13c** on the one hand and the axial end of the opening **11c** on the other hand. When this occurs, the spring **21** will become compressed, thus exerting a relatively large force that urges the first and second cover plates **12** and **13** back toward a centered position relative to the flange **11b** of the hub **11** at a relatively high spring rate. In this manner, the spring damper assembly **20** functions as a second stage vibration damper, which becomes effective only for relatively large relative rotational movement between the first and second cover plates **12** and **13** and the flange **11b** of the hub **11**.

Throughout this entire operation, the isolation sleeves **25** are disposed between the springs **21** and the adjacent portions of the first and second cover plates **12** and **13**. As a result, metal to metal contact therebetween is prevented, thus lowering the amount of noise that is generated during use of the torsional vibration dampening assembly **10**.

In accordance with the provisions of the patent statutes, the principle and mode of operation of this invention have been explained and illustrated in its preferred embodiment. However, it must be understood that this invention may be practiced otherwise than as specifically explained and illustrated without departing from its spirit or scope.

What is claimed is:

1. A torsional vibration dampening assembly comprising:
 - a first rotary torque transmitting element having an opening formed therethrough;
 - a second rotary torque transmitting element having an opening formed therethrough, said second rotary torque transmitting element being connected to said first rotary torque transmitting element for rotation relative thereto; and
 - a spring damper assembly disposed in said openings formed through said first and second rotary torque transmitting elements, said spring damper assembly including a movement restraining structure, first and second end caps having portions supported on said movement restraining structure for movement relative thereto, a resilient member disposed about said portions of said end caps and reacting between said first and second end caps, and an isolation sleeve disposed about said resilient member to prevent said resilient member from engaging said first and second rotary torque transmitting structures.

2. The torsional vibration dampening assembly defined in claim 1 wherein said first rotary torque transmitting element includes a hollow cylindrical hub having a splined inner surface.

3. The torsional vibration dampening assembly defined in claim 2 wherein said first rotary torque transmitting element further includes an annular flange extending about said hub, said opening being formed through said flange.

7

4. The torsional vibration dampening assembly defined in claim 1 wherein said second rotary torque transmitting element includes a cover plate having said opening formed therethrough.

5. The torsional vibration dampening assembly defined in claim 4 wherein said second rotary torque transmitting element includes a pair of cover plates that are secured together, each of said cover plates having an opening formed therethrough.

6. The torsional vibration dampening assembly defined in claim 1 further including a first stage vibration damper connected between said first rotary torque transmitting element and said second rotary torque transmitting element.

7. The torsional vibration dampening assembly defined in claim 6 wherein said first stage vibration damper includes an elastomeric element.

8. The torsional vibration dampening assembly defined in claim 1 wherein said resilient element is a coiled spring.

9. The torsional vibration dampening assembly defined in claim 1 wherein said isolation sleeve is formed from a relatively durable, low friction material.

8

10. The torsional vibration dampening assembly defined in claim 1 wherein said isolation sleeve is formed from nylon.

11. The torsional vibration dampening assembly defined in claim 1 wherein said first rotary torque transmitting element has a plurality of openings formed therethrough, said second rotary torque transmitting element has a plurality of openings formed therethrough that are respectively associated with said plurality of openings formed through said first rotary torque transmitting element, and a spring damper assembly is disposed in each of said associated openings formed through said first and second rotary torque transmitting element, each of said spring damper assemblies including a movement restraining structure, first and second end caps supported on said movement restraining structure for movement relative thereto, a resilient member reacting between said first and second end caps, and an isolation sleeve disposed about said resilient member to prevent said resilient member from engaging said first and second rotary torque transmitting structures.

* * * * *