

US006573033B1

(12) United States Patent

Simpson et al.

(10) Patent No.: US 6,573,033 B1

(45) Date of Patent: Jun. 3, 2003

(54) X-RADIATION SENSITIVE AQUEOUS-BASED PHOTOTHERMOGRAPHIC MATERIALS AND METHODS OF USING SAME

(75) Inventors: Sharon M. Simpson, Lake Elmo, MN (US); William E. Moore, Macedon,

NY (US)

(73) Assignee: Eastman Kodak Company, Rochester,

NY (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/193,395

(22) Filed: **Jul. 11, 2002**

(56) References Cited

U.S. PATENT DOCUMENTS

4,865,944	A		9/1989	Roberts et al.	
5,840,475	A	*	11/1998	Levy et al	430/619
6,440,649	B 1	*	8/2002	Simpson	430/351

FOREIGN PATENT DOCUMENTS

JP 11-283960 10/1999

11-196657 1/2001

OTHER PUBLICATIONS

K.Becker, E. Klein & E. Zeitler, Naturwissenschafter, 1960, 47, 199.

K. Becker, Beitrag zur Filmdosimetrie energiereicher Quantenstrahlung, Teil I, Fortschr. Roentgenstr., 1961a, 95, 694.

K. Becker, Beitrag zur Filmdosimetrie energiereicher Quantenstrahlung, Teil II, *Fortschr. Roentgenstr.*, 1961, pp 839–847.

JP

Primary Examiner—Thorl Chea (74) Attorney, Agent, or Firm—J. Lanny Tucker; Louis M. Leichter

(57) ABSTRACT

Aqueous-based photothermographic materials that are sensitive to visible or X-radiation contain X-radiation sensitive phosphors in association with specific chemically sensitized tabular silver halide grains. The silver halide grains comprise at least 70 mol % bromide, based on total silver halide, have an average thickness of at least 0.02 μ m and up to and including 0.10 μ m, an equivalent circular diameter (ECD) of at least 0.5 μ m and up to and including 8 μ m, and an aspect ratio of at least 5:1. These materials can be imaged in any suitable fashion but preferably they have one or more photothermographic layers on both sides of the support and can be imaged using X-radiation with or without an associated phosphor intensifying screen.

31 Claims, No Drawings

^{*} cited by examiner

X-RADIATION SENSITIVE AQUEOUS-BASED PHOTOTHERMOGRAPHIC MATERIALS AND METHODS OF USING **SAME**

FIELD OF THE INVENTION

This invention relates to X-radiation sensitive photothermographic materials that comprise very thin tabular grain silver halide emulsions and include X-radiation responsive phosphors. It is particularly directed to X-radiation sensitive photothermographic materials that are coated out of aqueous solutions. The invention also relates to methods of imaging using these materials.

BACKGROUND OF THE INVENTION

Silver-containing photothermographic imaging materials that are developed with heat and without liquid development have been known in the art for many years. Such materials 20 are used in a recording process wherein an image is formed by imagewise exposure of the photothermographic material to specific electromagnetic radiation (for example, visible, ultraviolet, or infrared radiation) and developed by the use of thermal energy. These materials, also known as "dry 25" silver" materials, generally comprise a support having coated thereon: (a) a photocatalyst (that is, a photosensitive compound such as silver halide) that upon such exposure provides a latent image in exposed grains that are capable of image in a development step, (b) a non-photosensitive source of reducible silver ions, (c) a reducing agent composition (usually including a developer) for the reducible silver ions, and (d) a hydrophilic or hydrophobic binder. The latent image is then developed by application of thermal energy.

In such materials, the photosensitive catalyst is generally a photographic type photosensitive silver halide that is considered to be in catalytic proximity to the nonphotosensitive source of reducible silver ions. Catalytic 40 proximity requires intimate physical association of these two components either prior to or during the thermal image development process so that when silver atoms $(Ag^0)_n$, also known as silver specks, clusters, nuclei or latent image, are generated by irradiation or light exposure of the photosen- 45 sitive silver halide, those silver atoms are able to catalyze the reduction of the reducible silver ions within a catalytic sphere of influence around the silver atoms [D. H. Klosterboer, Imaging Processes and Materials, (Neblette's Eighth Edition), J. Sturge, V. Walworth, and A. Shepp, Eds., 50 Van Nostrand-Reinhold, New York, 1989, Chapter 9, pp. 279–291]. It has long been understood that silver atoms act as a catalyst for the reduction of silver ions, and that the photosensitive silver halide can be placed in catalytic proximity with the non-photosensitive source of reducible silver 55 ions in a number of different ways (see, for example, Research Disclosure, June 1978, Item 17029). Other photosensitive materials, such as titanium dioxide, cadmium sulfide, and zinc oxide have also been reported to be useful in place of silver halide as the photocatalyst in photother- 60 mographic materials [see for example, Shepard, J. Appl.Photog. Eng. 1982, 8(5), 210-212, Shigeo et al., Nippon Kagaku Kaishi, 1994, 11, 992–997, and FR 2,254,047 (Robillard)].

The photosensitive silver halide may be made "in-situ," 65 for example by mixing an organic or inorganic halidecontaining source with a source of reducible silver ions to

achieve partial metathesis and thus causing the in-situ formation of silver halide (AgX) grains throughout the silver source [see, for example, U.S. Pat. No. 3,457,075 (Morgan et al.)]. In addition, photosensitive silver halides and sources 5 of reducible silver ions can be coprecipitated [see Yu. E. Usanov et al., J. Imag. Sci. Tech. 1996, 40, 104]. Alternatively, a portion of the reducible silver ions can be completely converted to silver halide, and that portion can be added back to the source of reducible silver ions (see Yu. E. Usanov et al., International Conference on Imaging Science, Sep. 7–11, 1998, pp. 67–70).

The silver halide may also be "preformed" and prepared by an "ex-situ" process whereby the silver halide (AgX) grains are prepared and grown separately. With this technique, one has the possibility of controlling the grain size, grain size distribution, dopant levels, and composition much more precisely, so that one can impart more specific properties to both the silver halide grains and the photothermographic material. The preformed silver halide grains may be introduced prior to and be present during the formation of the source of reducible silver ions. Co-precipitation of the silver halide and the source of reducible silver ions provides a more intimate mixture of the two materials [see for example U.S. Pat. No. 3,839,049 (Simons)]. Alternatively, the preformed silver halide grains may be added to and physically mixed with the source of reducible silver ions.

The non-photosensitive source of reducible silver ions is a material that contains reducible silver ions. Typically, the preferred non-photosensitive source of reducible silver ions acting as a catalyst for the subsequent formation of a silver 30 is a silver salt of a long chain aliphatic carboxylic acid having from 10 to 30 carbon atoms, or mixtures of such salts. Such acids are also known as "fatty acids" or "fatty carboxylic acids." Silver salts of other organic acids or other organic compounds, such as silver imidazoles, silver tetrazoles, silver benzotriazoles, silver benzotetrazoles, silver benzothiazoles and silver acetylides have also been proposed. U.S. Pat. No. 4,260,677 (Winslow et al.) discloses the use of complexes of various inorganic or organic silver salts.

> In photothermographic materials, exposure of the photographic silver halide to light produces small clusters containing silver atoms $(Ag^0)_n$. The imagewise distribution of these clusters, known in the art as a latent image, is generally not visible by ordinary means. Thus, the photosensitive material must be further developed to produce a visible image. This is accomplished by the reduction of silver ions that are in catalytic proximity to silver halide grains bearing the silver-containing clusters of the latent image. This produces a black-and-white image. The non-photosensitive silver source in the exposed areas is catalytically reduced to form the visible black-and-white negative image while the silver halide and the non-photosensitive silver source in the unexposed areas are not reduced.

In photothermographic materials, the reducing agent for the reducible silver ions, often referred to as a "developer," may be any compound that, in the presence of the latent image, can reduce silver ion to metallic silver and is preferably of relatively low activity until it is heated to a temperature sufficient to cause the reaction. A wide variety of classes of compounds have been disclosed in the literature that function as developers for photothermographic materials. At elevated temperatures, the reducible silver ions are reduced by the reducing agent. In photothermographic materials, upon heating, this reaction occurs preferentially in the regions surrounding the latent image. This reaction produces a negative image of metallic silver having a color that ranges from yellow to deep black depending upon the

presence of toning agents and other components in the imaging layer(s).

Differences Between Photothermography and Photography
The imaging arts have long recognized that the field of

The imaging arts have long recognized that the field of photothermography is clearly distinct from that of photography. Photothermographic materials differ significantly from conventional silver halide photographic materials that require processing with aqueous processing solutions.

As noted above, in photothermographic imaging materials, a visible image is created by heat as a result of the 10 reaction of a developer incorporated within the material. Heating at 50° C. or more is essential for this dry development. In contrast, conventional photographic imaging materials require processing in aqueous processing baths at more moderate temperatures (from 30° C. to 50° C.) to provide a 15 visible image.

In photothermographic materials, only a small amount of silver halide is used to capture light and a nonphotosensitive source of reducible silver ions (for example a silver carboxylate) is used to generate the visible image 20 using thermal development. Thus, the imaged photosensitive silver halide serves as a catalyst for the physical development process involving the non-photosensitive source of reducible silver ions and the incorporated reducing agent. In contrast, conventional wet-processed, black-and- 25 white photographic materials use only one form of silver (that is, silver halide) that, upon chemical development, is itself at least partially converted into the silver image, or that upon physical development requires addition of an external silver source (or other reducible metal ions that form black 30 images upon reduction to the corresponding metal). Thus, photothermographic materials require an amount of silver halide per unit area that is only a fraction of that used in conventional wet-processed photographic materials.

In photothermographic materials, all of the "chemistry" 35 for imaging is incorporated within the material itself For example, such materials include a developer (that is, a reducing agent for the reducible silver ions) while conventional photographic materials usually do not. Even in so-called "instant photography," the developer chemistry is 40 physically separated from the photosensitive silver halide until development is desired. The incorporation of the developer into photothermographic materials can lead to increased formation of various types of "fog" or other undesirable sensitometric side effects. Therefore, much 45 effort has gone into the preparation and manufacture of photothermographic materials to minimize these problems during the preparation of the photothermographic emulsion as well as during coating, use, storage, and post-processing handling.

Moreover, in photothermographic materials, the unexposed silver halide generally remains intact after development and the material must be stabilized against further imaging and development. In contrast, silver halide is removed from conventional photographic materials after 55 solution development to prevent further imaging (that is in the aqueous fixing step).

In photothermographic materials, the binder is capable of wide variation and a number of binders (both hydrophilic and hydrophobic) are useful. In contrast, conventional photographic materials are limited almost exclusively to hydrophilic colloidal binders such as gelatin.

Because photothermographic materials require dry thermal processing, they present distinctly different problems and require different materials in manufacture and use, 65 compared to conventional, wet-processed silver halide photographic materials. Additives that have one effect in con-

4

ventional silver halide photographic materials may behave quite differently when incorporated in photothermographic materials where the chemistry is significantly more complex. The incorporation of such additives as, for example, stabilizers, antifoggants, speed enhancers, supersensitizers, and spectral and chemical sensitizers in conventional photographic materials is not predictive of whether such additives will prove beneficial or detrimental in photothermographic materials. For example, it is not uncommon for a photographic antifoggant useful in conventional photographic materials to cause various types of fog when incorporated into photothermographic materials, or for supersensitizers that are effective in photographic materials to be inactive in photothermographic materials.

These and other distinctions between photothermographic and photographic materials are described in *Imaging Processes and Materials (Neblette's Eighth Edition)*, noted above, *Unconventional Imaging Processes*, E. Brinckman et al. (Eds.), The Focal Press, London and New York, 1978, pp. 74–75, in Zou et al., *J. Imaging Sci. Technol.* 1996, 40, pp. 94–103, and in M. R. V. Sahyun, *J. Imaging Sci. Technol.* 1998, 42, 23.

Problem to be Solved

Historically, photographic films containing various silver halides have been used for various radiographic purposes. Such films have exhibited excellent sensitivity to X-radiation, high spatial resolution, low image noise, and archival storage properties. Desired sensitivity to imaging X-radiation has been achieved through amplification of a relatively small number of latent image centers without too much "noise" being added to the image. However, such films require the use of undesirable aqueous processing solutions and equipment.

In photothermographic materials, all of the "chemistry" ample, such materials include a developer (that is, a ducing agent for the reducible silver ions) while conventional photographic materials usually do not. Even in recalled "instant photography," the developer chemistry is a development is desired. The incorporation of the development is desired.

Wet-processed radiographic films have generally been used in combination with some other material to convert X-radiation to another radiation form that can be more readily detected by silver halide in the films. Generally, such radiation "converting" materials are metal plates or metal oxides that convert X-radiation to electrons, or inorganic phosphors that convert X-radiation to visible radiation. Such 50 "converting" materials are also usually provided in a separate element in what is known as "metal screens," "intensifying screens," or "phosphor panels" because if phosphors or metal oxides are included within the typical silver halide emulsion, very high image noise levels result. This is due to the fact that electrons or visible radiation from the "converting" materials will expose many silver halide grains at the same time, including those outside of the "image area." Upon development, the exposed silver halide grains are "correlated" (that is, all the grains in the vicinity of the phosphor particle are developed, giving rise to high image noise. Thus, metal or phosphor intensifying screens or panels have been commonly used in combination with radiographic films in what are known as cassettes or radiographic imaging assemblies.

Attempts to incorporate phosphors in wet silver halide to improve sensitivity to X-radiation have been not been favored. K. Becker and coworkers found that incorporation

of p-terphenyl into an wet silver halide emulsion gave a material with a flat energy response between 10 keV and 1000 keV but with an excessive amount of noise (K. Becker, E. Klein, and E. Zeitler, *Naturwissenschaften*, 1960, 47, 199, K. Becker, *Roentgenstr*, 1961a, 95, 694, and K. Becker, 5 *Roentgenstr*, 1961b, 95, 939).

Efforts have been made to achieve increased photographic speed in photothermographic materials because such materials offer a number of important advantages over the use of conventional wet-processed photographic materials. 10 However, a significant problem with photothermographic materials is the difficulty in achieving high speed without accompanying increases in fog (D_{min}) or a loss in image contrast.

Another problem arises in such materials because the 15 level of silver halide is relatively low compared to wet-processed photographic materials. Thus, direct exposure of such materials to X-radiation would require that a very high dosage be delivered to the film (through a patient) in order to produce a useful image. This would be unacceptable for 20 both human and animal subjects.

One method of achieving X-radiation sensitive photothermographic materials employing phosphors and photothermographic emulsions prepared and coated from organic solvents without a loss in photospeed or D_{max} or a significant 25 increase in fog (D_{min}) is addressed in copending and commonly assigned U.S. Ser. No. 09/867,984 (filed May 30, 2001 by Simpson and Moore).

It has been reported in the literature that the use of silver halide tabular grain emulsions provides certain advantages 30 over the use of cubic grain emulsions in photothermographic materials. However, the grain size requirement for tabular grain emulsions needed to achieve a reasonable aspect ratio has resulted in significant large grain volumes in comparison to cubic grain emulsions. These higher volumes generally 35 introduce undesirably high D_{min} and post-processing haze into the resulting images from the presence of undeveloped silver halide grains that cannot be removed.

Workers in the art have tried various approaches to solving this problem. One approach has been to reduce the 40 size or equivalent circular diameter (ECD) of the tabular grain emulsions. The other approach has been to use silver chloride emulsions, thereby reducing light scattering in the resulting photothermographic imaging layers by virtue of the more favorable index of refraction for such grains.

U.S. Pat. No. 4,435,499 (Reeves) teaches the use of silver halide tabular grain emulsions in photothermographic materials containing silver behenate as the source of reducible silver ions. U.S. Pat. No. 5,876,905 (Irving et al.) discloses a double-sided coated photothermographic imaging material 50 comprising high chloride {1,0,0} tabular grain emulsions, silver behenate as the source of reducible silver ions, and a hydrophobic binder. EP 0 844 514 A (Elst et al.) also describes a photothermographic material containing silver chloride tabular grains.

The use of small tabular grain emulsions, and particularly the use of silver chloride tabular grain emulsions, invariably reduces the photographic speed of the resulting imaging material. To obtain higher speed photothermographic materials, it is preferred to use silver iodobromide tabular 60 grain emulsions. Alternatively, one can use tabular grain emulsions with relatively large ECD to achieve higher photographic speed.

Photothermographic systems have not achieved wide use in X-radiography because of low speed, poor resolution, and 65 poor contrast. U.S. Pat. No. 4,480,024 (Lyons et al.) describes one attempt to overcome these problems by com-

6

bining a specialized photothermographic coating and a rareearth intensifying screen which are uniquely adapted to one another for the purpose of radiographic imaging.

One approach to reducing the amount of X-radiation exposure needed to produce an image in photothermographic materials is to place "double faced coatings" of photothermographic materials into contact with metal or phosphor intensifying screens.

EP 0 350 883 B1 (Pesce et al.) describes photothermographic materials having double-sided coatings that are sensitized to the wavelength of light emitted by an adjacent phosphor screen. Each adjacent phosphor screen emits at a different wavelength.

JP 2001109101 (Adachi) also describes a photothermographic material useful in X-radiography having photothermographic layers coated on both sides of the support. A coloring matter capable of being bleached by heat or light is included in the photosensitive layer or in at least one layer between the photothermographic layer and the support. The layer including the coloring matter is formed using >30% water as one of the coating solvents.

JP 2001-022027 (Adachi) also describes a double-sided photothermographic material useful in medical X-radiography having photothermographic layers coated on both sides of a polyethylene naphthalate support. The photosensitive silver halide is chemically sensitized by a chalcogen compound, and the reducing agent is included in a layer different from the layer including the photosensitive silver halide. The phosphor screen is laminated to the photothermographic coating.

There are imaging applications in which the use of such contact screens would be disadvantageous. For example, in the practice of intra-oral dental radiography, reuse of the expensive intensifying screens would require sterilization between uses. In addition, light spread and modulation transfer function (MTF) reducing characteristics associated with intensifying screens can reduce image sharpness to unacceptable levels.

Thus, there is a need for a method to render photother-mographic materials X-radiation sensitive without a loss in photospeed or D_{max} or a significant increase in fog (D_{min}) . There is also a need to achieve this X-radiation sensitivity in photothermographic materials without the use of heavy, bulky, and costly phosphor intensifying screens.

Moreover, it would also be desirable to prepare and coat photothermographic materials that provide images with low D_{min} and low post-processing haze using water as the solvent. Such photothermographic materials are particularly needed for radiographic imaging having increased sensitivity to X-radiation.

SUMMARY OF THE INVENTION

This invention provides an X-radiation sensitive photothermographic material comprising a support having on at least one side thereof, one or more imaging layers each comprising a hydrophilic binder, and in reactive association:

a. chemically sensitized photosensitive silver halide grains, at least 70% of the total photosensitive silver halide grain projected area being provided by tabular silver halide grains comprising at least 70 mol % bromide (based on total silver halide) with the remainder of the halide being iodide or chloride, the tabular grains having an average thickness of at least $0.02 \, \mu \text{m}$ and up to and including $0.10 \, \mu \text{m}$, an equivalent circular diameter of at least $0.5 \, \mu \text{m}$ and up to and including 8 μm , and an aspect ratio of at least 5:1,

b. a non-photosensitive source of reducible silver ions,

- c. a reducing agent composition for the reducible silver ions, and
- d. a phosphor that is sensitive to X-radiation and is present in an amount of at least 0.1 mole per mole of total 5 silver.

In preferred embodiments, the photothermographic materials of this invention (both those described above and those described below) further include a toner in one or more imaging layers. In more preferred embodiments, this toner is a triazole compound (such as a mercaptotriazole) as defined in more detail below.

This invention also provides embodiments that are "double-sided" photothermographic materials having one or more of the same or different photothermographic imaging 15 layers as described above on both sides of the support.

Thus, in another embodiment, this invention provides a black-and-white photothermographic material comprising a support having thereon one or more hydrophilic layers each layer comprising a hydrophilic binder, and the photother- 20 mographic material further comprising on both sides of the support, one or more imaging layers comprising, in reactive association:

- a. a non-photosensitive source of reducible silver ions,
- b. a reducing agent composition for the reducible silver ions,
- c. chemically sensitized photosensitive silver halide grains, at east 70% of the total photosensitive silver halide grain projected area being rovided by tabular silver halide grains comprising at least 70 mol % bromide (based on total silver halide) and the remainder of the halide being iodide or chloride, the tabular grains having an average thickness of at least $0.02 \, \mu \text{m}$ and up to and including $0.10 \, \mu \text{m}$, an equivalent circular diameter of at least $0.5 \, \mu \text{m}$ and up to and including 8 μm , and an aspect ratio of at least 5:1, and
- d. a phosphor that is sensitive to X-radiation and is present in an amount of at least 0.1 mole per mole of total silver,

the imaging layers on both sides of the support being the same or different.

In a preferred embodiment, the photothermographic material further includes a toner. In a more preferred embodiment, the toner is a triazole compound.

Further, this invention provides methods of forming a visible image comprising:

- A) imagewise exposing the photothermographic materials described above to electromagnetic radiation to form a latent image, and
- B) simultaneously or sequentially, heating the exposed photothermographic material to develop the latent image into a visible image.

In preferred embodiments, the method of forming a visible image comprises:

- A) imagewise exposing the photothermographic material described above to X-radiation to form a latent image, and
- B) simultaneously or sequentially, heating the exposed photothermographic material to develop the latent 60 image into a visible image.

This invention further provides an imaging assembly comprising any of the photothermographic materials described herein that is arranged in association with one or more phosphor intensifying screens.

Still again, the present invention provides an imaging precursor emulsion comprising the following component d

8

in combination with any two or more of the following components a, b, and c:

- a. chemically sensitized photosensitive silver halide grains, at least 70% of the total photosensitive silver halide grain projected area being provided by tabular silver halide grains comprising at least 70 mol % bromide (based on total silver halide) with the remainder of the halide being iodide or chloride, said tabular grains having an average thickness of at least $0.02 \, \mu m$ and up to and including $0.10 \, \mu m$, an equivalent circular diameter of at least $0.5 \, \mu m$ and up to and including 8 μm , and an aspect ratio of at least 5:1,
- b. a non-photosensitive source of reducible silver ions,
- c. a reducing agent composition for the reducible silver ions, and
- d. a phosphor that is sensitive to X-radiation.

In a preferred embodiment, the imaging precursor emulsion further includes a toner, such as a triazole compound.

The present invention provides a number of advantages. The use of inorganic phosphors in one or more imaging layers in combination with the use of very thin ("ultrathin") tabular grains as the predominant photosensitive silver halide provides unexpected increase in photographic speed (or sensitivity) to X-radiation. It was also discovered that the materials of this invention provide improved image sharpness, low fog, and a low level of noise. Such benefits are obtained using very small amounts of inorganic phosphors in the imaging layers.

These advantages are particularly noticeable in aqueous-based photothermographic imaging emulsions and materials including those that include silver benzotriazole or other heterocyclic silver salts as the non-photosensitive sources of reducible silver ions. Thus, the photothermographic materials of this invention are "aqueous-based" materials wherein the various imaging layers have been formulated in and coated out of predominantly (more than 50 volume %) water.

DETAILED DESCRIPTION OF THE INVENTION

The photothermographic materials of this invention can be used in black-and-white photothermography. They are particularly useful for medical imaging of human or animal subjects in response to X-radiation. Such applications include, but are not limited to, thoracic imaging, mammography, dental imaging, orthopedic imaging, general medical radiography, therapeutic radiography, veterinary radiography, and auto-radiography. The materials of this invention are also useful for non-medical uses of X-radiation such as in X-ray lithography and in industrial radiography.

For some applications it may be useful that the photothermographic materials of this invention are "doublesided," that is having photothermographic coatings layers on both sides of the support.

The photothermographic materials of this invention can be sensitized to different regions of the spectrum, such as ultraviolet, visible, and infrered radiation. The photosensitive silver halide used in these materials has intrinsic sensitivity to blue light and to X-radiation. Increased sensitivity to a particular region of the spectrum is imparted through the use of various sensitizing dyes adsorbed to the silver halide grains.

In the photothermographic materials of this invention, the components needed for imaging can be in one or more thermally developable layers. The layer(s) than contain the photosensitive silver halide or non-photosensitive source of

reducible silver ions, or both, are referred to herein as "thermally developable layer(s)," "imaging layers," or "photothermographic emulsion layer(s)." The photosensitive silver halide and the non-photosensitive source of reducible silver ions are in catalytic proximity (that is, in reactive association with each other) and preferably are in the same emulsion layer. "Catalytic proximity" or "reactive association" means that they should be in the same layer or in adjacent layers. In addition, the one or more phosphors described herein are also in catalytic proximity or reactive association with the photosensitive silver halide, and are preferably in the same imaging layer.

Where the materials contain imaging layers on one side of the support only, various non-imaging layers are usually disposed on the "backside" (non-emulsion side) of the materials, including antihalation layer(s), protective layers, antistatic layers, conducting layers, and transport enabling layers.

In such instances, various non-imaging layers can also be disposed on the "frontside" or emulsion side of the support, 20 including protective topcoat layers, primer layers, interlayers, opacifying layers, antistatic layers, conductive layers, antihalation layers, acutance layers, auxiliary layers, and other layers readily apparent to one skilled in the art.

If the photothermographic materials comprise one or 25 more thermally developable imaging layers on both sides of the support, each side can also include one or more protective topcoat layers, primer layers, interlayers, antistatic layers, acutance layers, auxiliary layers, crossover-control layers, and other layers readily apparent to one skilled in the 30 art.

When the photothermographic materials of this invention are thermally developed as described below in a substantially water-free condition after, or simultaneously with, imagewise exposure, a silver image (preferably a black-and-35 white silver image) is obtained.

Definitions

As used herein:

In the descriptions of the photothermographic materials of the present invention, "a" or "an" component refers to "at 40 least one" of that component (for example phosphors or toners).

Heating in a substantially water-free condition as used herein, means heating at a temperature of from about 50° C. to about 250° C. with little more than ambient water vapor 45 present. The term "substantially water-free condition" means that the reaction system is approximately in equilibrium with water in the air and water for inducing or promoting the reaction is not particularly or positively supplied from the exterior to the material. Such a condition 50 is described in T. H. James, *The Theory of the Photographic Process*, Fourth Edition, Eastman Kodak Company, Rochester, N.Y., 1977, p. 374.

"Photothermographic material(s)" means a construction comprising at least one photothermographic emulsion layer 55 or a photothermographic set of layers (wherein the silver halide and the source of reducible silver ions are in one layer and the other essential components, including the phosphor, or desirable additives are distributed, as desired, in the same layer or in an adjacent coating layer) and any supports, 60 topcoat layers, image-receiving layers, antistatic layers, conductive layers, blocking layers, antihalation layers, subbing or priming layers. These materials also include multilayer constructions in which one or more imaging components are in different layers, but are in "reactive association" so that 65 they readily come into contact with each other during imaging and/or development. For example, one layer can

10

include the non-photosensitive source of reducible silver ions and another layer can include the reducing agent composition, but the two reactive components are in reactive association with each other.

"Photocatalyst" means a photosensitive compound such as silver halide that, upon exposure to radiation, provides a compound that is capable of acting as a catalyst for the subsequent development of the image-forming material.

"Catalytic proximity" or "reactive association" means that the materials are in the same layer or in adjacent layers so that they readily come into contact with each other during thermal imaging and development.

"Emulsion layer," "imaging layer," "thermally developable imaging layer," or "photothermographic emulsion 15 layer," means a layer of a photothermographic material that contains the photosensitive silver halide and/or nonphotosensitive source of reducible silver ions. It can also mean a layer of the photothermographic material that contains, in addition to the photosensitive silver halide and/or non-photosensitive source of reducible ions, additional essential components (such as the phosphor) and/or desirable additives. These layers are usually on what is known as the "frontside" of the support, but in some embodiments, they are present on both sides of the support. Such embodiments are known as "double-sided" photothermographic materials. In such double-sided materials the layers can be of the same or different chemical composition, thickness, or sensitometric properties.

The four "essential imaging components" required in the photothermographic materials of this invention are a high aspect ratio tabular grain photosensitive silver halide, a non-photosensitive source of reducible silver ions, a reducing agent composition for the reducible silver ions, and a phosphor (all defined in more detail below). All of these essential "imaging components" are incorporated into one or more imaging layers of the photothermographic materials during manufacture. In other words, they are not incorporated from an external source such as from a laminated element or phosphor screen.

"Ultraviolet region of the spectrum" refers to that region of the spectrum less than or equal to 410 nm, and preferably from about 100 nm to about 410 nm, although parts of these ranges may be visible to the naked human eye. More preferably, the ultraviolet region of the spectrum is the region of from about 190 to about 405 nm.

"Visible region of the spectrum" refers to that region of the spectrum of from about 400 nm to about 700 nm.

"Short wavelength visible region of the spectrum" refers to that region of the spectrum of from about 400 nm to about 450 nm.

"Red region of the spectrum" refers to that region of the spectrum of from about 600 nm to about 700 nm.

"Infrared region of the spectrum" refers to that region of the spectrum of from about 700 nm to about 1400 nm.

"Non-photosensitive" means intentionally neither radiation nor light sensitive.

The term "rare earth" is used to indicate elements having an atomic number of 39 or 57 through 71.

A"phosphor" is an inorganic compound that is responsive to X-radiation and upon irradiation, emits radiation in the ultraviolet, visible, or infrared region of the spectrum. Most phosphors emit such radiation immediately upon exposure to stimulating radiation. However, some phosphors are known as "storage" phosphors because they have the capacity to store energy from the initial irradiation and to release the light at a later time when stimulated by still other radiation.

The sensitometric terms "speed," "photospeed" or "photographic speed" (also known as "sensitivity"), "absorbance," "contrast," D_{min} , and D_{max} have conventional definitions known in the imaging arts. Particularly, D_{min} is considered herein as image density achieved when the 5 photothermographic material is thermally developed without prior exposure to radiation.

The sensitometric term absorbance is another term for optical density (OD).

"Transparent" means capable of transmitting visible light 10 or imaging radiation without appreciable scattering or absorption.

The term "RAD" is used to indicate a unit dose of absorbed radiation, that is energy absorption of 100 ergs per gram of tissue.

The terms "kVp" and "MVp" stand for peak voltage applied to an X-ray tube times 10³ and 10⁶, respectively.

The term "equivalent circular diameter" (ECD) is used to define the diameter (μ m) of a circle having the same projected area as a silver halide grain.

The term "aspect ratio" is used to define the ratio of grain ECD to grain thickness.

The term "coefficient of variation" (COV) is defined as 100 times the standard deviation(s) of grain ECD divided by the mean grain ECD.

The term "tabular grain" is used to define a silver halide grain having two parallel crystal faces that are clearly larger than any remaining crystal faces and having an aspect ratio of at least 2. The term "tabular grain emulsion" herein refers to an imaging emulsion containing silver halide grains in 30 which the tabular grains account for more than 70% of the total photosensitive silver halide grain projected area.

The terms "double-sided" and "double-faced coating" are used to define photothermographic materials having one or more of the same or different thermally developable emul- 35 sion layers disposed on both sides (front and back) of the support.

In the compounds described herein, no particular double bond geometry (for example, cis or trans) is intended by the structures drawn. Similarly, alternating single and double 40 bonds and localized charges are drawn as a formalism. In reality, both electron and charge delocalization exists throughout the conjugated chain.

As is well understood in this art, for all organic compounds herein described, substitution is not only tolerated, 45 but is often advisable and various substituents are anticipated on the compounds used in the present invention unless otherwise stated. Thus, when a compound is referred to as "having the structure" of a given formula, any substitution that does not alter the bond structure of the formula or the 50 shown atoms within that structure is included within the formula, unless such substitution is specifically excluded by language (such as "free of carboxy-substituted alkyl"). For example, where a benzene ring structure is shown (including fused ring structures), substituent groups may be placed on 55 the benzene ring structure, but the atoms making up the benzene ring structure may not be replaced.

As a means of simplifying the discussion and recitation of certain substituent groups, the term "group" refers to chemical species that may be substituted as well as those that are 60 not so substituted. Thus, the term "group," such as "alkyl group" is intended to include not only pure hydrocarbon alkyl chains, such as methyl, ethyl, n-propyl, t-butyl, cyclohexyl, iso-octyl, and octadecyl, but also alkyl chains bearing substituents known in the art, such as hydroxyl, 65 alkoxy, phenyl, halogen atoms (F, Cl, Br, and I), cyano, nitro, amino, and carboxy. For example, alkyl group

12

includes ether and thioether groups (for example CH₃—CH₂—CH₂—O—CH₂— and CH₃—CH₂—CH₂—S—CH₂—), haloalkyl, nitroalkyl, alkylcarboxy, carboxyalkyl, carboxamido, hydroxyalkyl, sulfoalkyl, and other groups readily apparent to one skilled in the art. Substituents that adversely react with other active ingredients, such as very strongly electrophilic or oxidizing substituents, would, of course, be excluded by the ordinarily skilled artisan as not being inert or harmless.

Research Disclosure is a publication of Kenneth Mason Publications Ltd., Dudley House, 12 North Street, Emsworth, Hampshire PO10 7DQ England (also available from Emsworth Design Inc., 147 West 24th Street, New York, N.Y. 10011).

Other aspects, advantages, and benefits of the present invention are apparent from the detailed description, examples, and claims provided in this application.

The Photosensitive Silver Halide

As noted above, the photothermographic materials of the present invention include one or more silver halides that comprise at least 70 mol % (preferably at least 85 mol % and more preferably at least 90 mol %) bromide (based on total silver halide). The remainder of the halide is either iodide or chloride, or both. Preferably, the additional halide is iodide.

Such useful silver halides include pure silver bromoide and mixed silver halides such as silver bromoiodide, silver bromoiodochloride, and silver bromochloride as long as the bromide comprises at least 70 mol % of the total halide content. Mixtures of these silver halides can also be used in any suitable proportion as long as bromide comprises at least 70 mol % of the total halides in the mixtures. Silver bromide and silver bromoiodide are more preferred, with the latter silver halide having up to 15 mol % iodide (based on total silver halide) and ore preferably, up to 10 mol % iodide.

Moreover, at least 70% (preferably from about 85 to 100%) of the total photosensitive silver halide grain projected area in each emulsion used in the invention are tabular silver halide grains having an aspect ratio of at least 5. The remainder of the silver halide grains can have any suitable crystalline habit including, but not limited to, cubic, octahedral, tetrahedral, orthorhombic, rhombic, dodecahedral, other polyhedral; laminar, twinned, or platelet morphologies and may have epitaxial growth of crystals thereon. If desired, a mixture of these crystals can be employed. Most preferably, substantially all of the silver halide grains have tabular morphology.

The tabular silver halide grains used in the practice of this invention are advantageous because they are considered "ultrathin" and have an average thickness of at least $0.02 \,\mu m$ and up to and including $0.10 \,\mu m$. Preferably, they have an average thickness of at least $0.03 \,\mu m$ and more preferably of at least $0.04 \,\mu m$, and up to and including $0.08 \,\mu m$ and more preferably up to and including $0.07 \,\mu m$.

In addition, these tabular grains have an ECD of at least $0.5 \mu m$, preferably at least $0.75 \mu m$, and more preferably at least $1.0 \mu m$. The ECD can be up to and including $8 \mu m$, preferably up to and including $6 \mu m$, and more preferably up to and including $4 \mu m$.

The aspect ratio of the useful tabular grains is at least 5:1, preferably at least 10:1, and more preferably at least 15:1. For practical purposes, the tabular grain aspect ratio is generally up to 100:1. An aspect ratio of between about 30:1 and about 70:1 is particularly useful.

Grain size may be determined by any of the methods commonly employed in the art for particle size measurement. Representative methods are described, for example, in "Particle Size Analysis," ASTM Symposium on Light

Microscopy, R. P. Loveland, 1955, pp. 94–122, and in C. E. K. Mees and T. H. James, *The Theory of the Photographic Process*, Third Edition, Macmillan, New York, 1966, Chapter 2. Particle size measurements may be expressed in terms of the projected areas of grains or approximations of their 5 diameters. These will provide reasonably accurate results if the grains of interest are substantially uniform in shape. In the Examples below, the grain sizes referred to were determined using well-known electron microscopy techniques such as Transmission Electron Microscopy (TEM) or Scanning Electron Microscopy (SEM).

As noted above, the tabular silver halide grains useful in the present invention generally have a uniform ratio of halide throughout. However, they may have a graded halide content, with a continuously varying ratio of, for example, 15 silver bromide and silver iodide or they may be of the core-shell type, having a discrete core of one halide ratio, and one or more discrete shells of another halide ratio. For example, the central regions of the tabular grains may contain at least 1 mol % more iodide than outer or annular 20 regions of the grains. Core-shell silver halide grains useful in photothermographic materials and methods of preparing these materials are described for example in U.S. Pat. No. 5,382,504 (Shor et al.), incorporated herein by reference. Iridium and/or copper doped core-shell and non-core-shell 25 grains are described in U.S. Pat. No. 5,434,043 (Zou et al.) and U.S. Pat. No. 5,939,249 (Zou), both incorporated herein by reference.

The tabular photosensitive silver halide grains can also be doped using one or more of the conventional metal dopants 30 known for this purpose including those described in *Research Disclosure* Item 38957, September, 1996 and U.S. Pat. No. 5,503,970 (Olm et al.), incorporated herein by reference. Preferred dopants include iridium (3+ or 4+) and ruthenium (2+ or 3+) salts.

The tabular silver halide grains can be added to (or formed within) the emulsion layer(s) in any fashion as long as it is placed in catalytic proximity to the non-photosensitive source of reducible silver ions.

It is preferred that the tabular silver halide grains be 40 preformed and prepared by an ex-situ process. The silver halide grains prepared ex-situ may then be added to and physically mixed with the non-photosensitive source of reducible silver ions.

The source of reducible silver ions may also be formed in the presence of ex-situ-prepared tabular silver halide grains. In this process, the source of reducible silver ions, is formed in the presence of these preformed silver halide grains. Co-precipitation of the reducible source of silver ions in the presence of silver halide provides a more intimate mixture of the two materials [see, for example U.S. Pat. No. 3,839,049 (Simons)]. Materials of this type are often referred to as "preformed soaps."

Mixing of the tabular silver halide grains prepared ex-situ with the non-photosensitive sliver source can also be carried 55 out during the coating step using, for example, in-line mixing techniques.

Preformed tabular grain silver halide emulsions used in the material of this invention can be prepared by aqueous or organic processes and can be unwashed or washed to remove 60 soluble salts. In the latter case, the soluble salts can be removed by ultrafiltration, by chill setting and leaching, or by washing the coagulum [for example, by the procedures described in U.S. Pat. No. 2,618,556 (Hewitson et al.), U.S. Pat. No. 2,614,928 (Yutzy et al.), U.S. Pat. No. 2,565,418 65 (Yackel), U.S. Pat. No. 3,241,969 (Hart et al.), and U.S. Pat. No. 2,489,341 (Waller et al.)].

14

Additional methods of preparing these silver halide and organic silver salts and manners of blending them are described in *Research Disclosure*, June 1978, Item 17029, U.S. Pat. No. 3,700,458 (Lindholm) and U.S. Pat. No. 4,076,539 (Ikenoue et al.), and JP Applications 13224/74, 42529/76, and 17216/75.

In some instances, it may be helpful to prepare the tabular grain photosensitive silver halide in the presence of a hydroxytetrazindene (such as 4-hydroxy-6-methyl-1,3,3a,7-tetrazaindene) or a N-heterocyclic compound comprising at least one mercapto group (such as 1-phenyl-5-mercaptotetrazole) to provide increased photospeed. Details of this procedure are provided in copending and commonly assigned U.S. Ser. No. 09/833,533 (filed Apr. 12, 2001 by Shor, Zou, Ulrich, and Simpson), that is incorporated herein by reference.

A useful method of preparing the "ultrathin" silver halide grains useful in the practice of this invention are exemplified below just prior to the examples.

In addition to the preformed tabular silver halide grains, it is also effective to use an in-situ process in which a halide-containing compound is added to an organic silver salt to partially convert some of the silver of the organic silver salt to silver halide. The halogen-containing compound can be inorganic (such as zinc bromide or lithium bromide) or organic (such as N-bromosuccinimide).

The one or more tabular grain photosensitive silver halides used in the photothermographic materials of the present invention are preferably present in an amount of from about 0.005 to about 0.5 mole, more preferably from about 0.05 to about 0.30 mole, and most preferably from about 0.01 to about 0.25 mole, per mole of non-photosensitive source of reducible silver ions.

Chemical Sensitizers

The photosensitive silver halide used in the present invention may be employed without modification. However, it may be chemically sensitized with one or more chemical sensitizing agents such as compounds containing sulfur, selenium, or tellurium, a compound containing gold, platinum, palladium, iron, ruthenium, rhodium, or iridium, a reducing agent such as a tin halide. The details of these procedures are described in T. H. James, *The Theory of the* Photographic Process, Fourth Edition, Eastman Kodak Company, Rochester, N.Y., 1977, Chapter 5, pages 149 to 169, U.S. Pat. No. 1,623,499 (Sheppard et al.), U.S. Pat. No. 2,399,083 (Waller et al.), U.S. Pat. No. 3,297,447 (McVeigh), U.S. Pat. No. 3,297,446 (Dunn), U.S. Pat. No. 5,049,485 (Deaton), U.S. Pat. No. 5,252,455 (Deaton), U.S. Pat. No. 5,391,727 (Deaton), U.S. Pat. No. 5,912,111 (Lok et al.), U.S. Pat. No. 5,759,761 (Lushington et al.), U.S. Pat. No. 5,945,270 (Lok et al.), U.S. Pat. No. 6,159,676 (Lin et al), and U.S. Pat. No. 6,296,998 (Eikenberry et al).

In addition, tabular silver halide grains comprising sensitizing dye(s), silver salt epitaxial deposits, and addenda that include a mercaptotetrazole and a tetraazaindene may be chemically sensitized. Such emulsions are described in U.S. Pat. No. 5,691,127 (Daubendiek et al.), incorporated herein by reference, Sulfur sensitization is performed by adding a sulfur sensitizer and stirring the emulsion at a temperature as high as 40° C. or above for a predetermined time. In addition to the sulfur compound contained in gelatin, various sulfur compounds can be used. Some examples of sulfur sensitizers include thiosulfates (for example, hypo), thioureas (for example, diphenylthiourea, triethylthiourea, N-ethyl-N'-(4-methyl-2-thiazolyl)thiourea and certain tetrasubstituted thioureas known as "rapid sulfiding agents"), thioamides (for example, thioacetamide), rhodanines (for example,

diethylrhodanine and 5-benzylidene-N-ethylrhodanine), phosphine sulfides (for example, trimethylphosphine sulfide), thiohydantoins, 4-oxo-oxazolidine-2-thiones, dipolysulfides (fox example, dimorpholine disulfide, cystine and hexathiocane-thione), mercapto compounds (for 5 example, cysteine), polythionates, and elemental sulfur.

Rapid "sulfiding" agents are also useful in the present invention. Such compounds are described, for example in U.S. Pat. No. 6,296,998 (Eikenberry et al.), and U.S. Pat. No. 6,322,961 (Lam et al.), both noted above. Particularly 10 useful are the tetrasubstituted middle chalcogen thiourea compounds represented by the following Structure RS-1:

wherein each R_a , R_b , R_c , and R_d group independently represents an alkylene, cycloalkylene, carbocyclic arylene, heterocyclic arylene, alkarylene or aralkylene group, or taken together with the nitrogen atom to which they are attached, R_a and R_b or R_c and R_d can complete a 5- to 25 7-membered heterocyclic ring, and each of the B_a , B_b , B_c , and B_d groups independently is hydrogen or represents a carboxylic, sulfinic, sulfonic, hydroxamic, mercapto, sulfonamido or primary or secondary amino nucleophilic group, with the proviso that at least one of the R_aB_a through R_dB_d groups contains the nucleophilic group bonded to a urea nitrogen atom through a 1- or 2-membered chain. Tetrasubstituted middle chalcogen ureas of such formula are disclosed in U.S. Pat. No. 4,810,626 (Burgmaier et al.), the disclosure of which is here incorporated by reference.

Apreferred group of rapid sulfiding agents has the general structure RS-1 is that wherein each of the R_a, R_b, R_c, and R_d groups independently represents an alkylene group having 1 to 6 carbon atoms, and each of the B_a, B_b, B_c, and B_d groups independently is hydrogen or represents a carboxylic, ⁴⁰ sulfinic, sulfonic, hydroxamic group, with the proviso that at least one of the R_aB_a through R₄B₄ groups contains the nucleophilic group bonded to a urea nitrogen atom through a 1- or 2-membered chain. Especially preferred rapid sulfiding agents are represented by the following Structures ⁴⁵ RS-1a and RS-1b:

$$Na^{+-}O \underbrace{\hspace{1cm} N \\ O \\ CH_{3} \\ CH_{3} \\ O \\ CH_{3} \\ O \\ CH_{3} \\ O \\ (RS-1b)$$

These compounds have been shown to be very effective sensitizers under mild digestion conditions and to produce higher speeds than many other thiourea compounds that lack the specified nucleophilic substituents.

The amount of the sulfur sensitizer to be added varies 65 depending upon various conditions such as pH, temperature and grain size of silver halide at the time of chemical

16

ripening, it is preferably from 10^{-7} to 10^{-2} mole per mole of silver halide, and more preferably from 10^{-5} to 10^{-3} mole.

Selenium sensitization is performed by adding a selenium compound and stirring the emulsion at a temperature at least 40° C. for a predetermined time. Examples of the selenium sensitizers include colloidal selenium, selenoureas (for example, N, N-dimethylselenourea, trifluoromethylcarbonyl-trimethylselenourea and acetyltrimethylselenourea), selenoamides (for example, selenoacetamide and N,N-diethylphenylselenoamide), phosphine selenides (for example, triphenylphosphine selenide and pentafluorophenyl-triphenylphosphine selenide, and methylene-bis[diphenyl-phosphine selenide), selenophoshpates (for example, tri-p-tolyl-selenophosphate and tri-n-15 butyl selenophosphate), selenoketones (for example, selenobenzophenone), isoselenocyanates, selenocarboxylic acids, selenoesters and diacyl selenides. Other selenium compounds such as selenious acid, potassium selenocyanate, selenazoles, and selenides can also be used as 20 selenium sensitizers. Some specific examples of useful selenium compounds can be found in U.S. Pat. No. 5,158, 892 (Sasaki et al.), U.S. Pat. No. 5,238,807 (Sasaki et al.), and U.S. Pat. No. 5,942,384 (Arai et al.). Still other useful selenium sensitizers are those described in co-pending and commonly assigned U.S. Ser. No. 10/082,516 (filed Feb. 25, 2002 by Lynch, Opatz, Gysling, and Simpson), incorporated herein by reference.

Tellurium sensitizers for use in the present invention are compounds capable of producing silver telluride, which is presumed to serve as a sensitization nucleus on the surface or inside of silver halide grain. Examples of the tellurium sensitizers include telluroureas (for example, tetramethyltellurourea, N,N-dimethylethylene-tellurourea and N,N'-diphenylethylenetellurourea), phosphine tellurides 35 (for example, butyl-diisopropylphosphine telluride, tributylphosphine telluride, tributoxyphosphine telluride and ethoxy-diphenylphosphine telluride), diacyl ditellurides and diacyl tellurides [for example, bis(diphenylcarbamoyl ditelluride, bis(N-phenyl-N-methylcarbamoyl) ditelluride, bis(N-phenyl-N-methylcarbamoyl) telluride and bis (ethoxycarbonyl telluride)], isotellurocyanates, telluroamides, tellurohydrazides, telluroesters (such as butyl hexyl telluroester), telluroketones (such as telluroacetophenone), colloidal tellurium, (di)tellurides and other tellurium compounds (for example, potassium telluride and sodium telluropentathionate). Tellurium compounds for use as chemical sensitizers can be selected from those described in J. Chem. Soc,. Chem. Commun. 1980, 635, ibid., 1979, 1102, ibid., 1979, 645, J. Chem. Soc. 50 Perkin. Trans, 1980, 1, 2191, The Chemistry of Organic Selenium and Tellurium Compounds, S. Patai and Z. Rappoport, Eds., Vol. 1 (1986), and Vol. 2 (1987) and U.S. Pat. No. 5,677,120 (Lushington et al.). Preferred telluriumcontaining chemical sensitizers are those described in 55 copending and commonly assigned U.S. Ser. No. 09/975, 909 (filed Oct. 11, 2001 by Lynch, Opatz, Shor, Simpson, Willett, and Gysling) and in co-pending and commonly assigned U.S. Ser. No. 09/923,039 (filed Aug. 6, 2001 by Gysling, Dickinson, Lelental, and Boettcher), both incorpo-60 rated herein by reference.

Specific examples thereof include the compounds described in U.S. Pat. No. 1,623,499 (Sheppard et al.), U.S. Pat. No. 3,320,069 (Illingsworth), U.S. Pat. No. 3,772,031 (Berry et al.), U.S. Pat. No. 5,215,880 (Kojima et al.), U.S. Pat. No. 5,273,874 (Kojima et al.), U.S. Pat. No. 5,342,750 (Sasaki et al.), British Patent 235,211 (Sheppard), British Patent 1,121,496 (Halwig), British Patent 1,295,462 (Hilson

et al.) and British Patent 1,396,696 (Simons), and JP-04-271341 A (Morio et al.).

The amount of the selenium or tellurium sensitizer used in the present invention varies depending on silver halide grains used or chemical ripening conditions. However, it is 5 generally from 10^{-8} to 10^{-2} mole per mole of silver halide, preferably on the order of from 10^{-7} to 10^{-3} mole. The conditions for chemical sensitization in the present invention are not particularly restricted. However, in general, pH is from 5 to 8, pAg is from 6 to 11, preferably from 7 to 10, 10 and temperature is from 40 to 95° C., preferably from 45 to 85° C.

Noble metal sensitizers for use in the present invention include gold, platinum, palladium and iridium. Gold sensitization is particularly preferred.

The gold sensitizer used for the gold sensitization of the silver halide emulsion used in the present invention may have an oxidation number of 1 or 3, and may be a gold compound commonly used as a gold sensitizer. Examples thereof include chloroauric acid, potassium chloroaurate, 20 auric trichloride, potassium dithiocyanatoaurate, [AuS₂P(i- C_4H_9 ₂₂, bis-(1,4,5-trimethyl-1,2,4-triazolium-3-thiolate) gold (I) tetrafluoroborate, and pyridyltrichloro gold. U.S. Pat. No. 5,858,637 (Eshelman et al) describes various Au (I) compounds that can be used as chemical sensitizers. Other 25 useful gold compounds can be found in U.S. Pat. No. 5,759,761 (Lushington et al.).

Useful combinations of gold (I) complexes and rapid sulfiding agents are described in U.S. Pat. No. 6,322,961 (Lam et al.). Combinations of gold (III) compounds and 30 either sulfur or tellurium compounds are useful as chemical sensitizers and are described in co-pending and commonly assigned U.S. Ser. No. 09/768,094 (filed Jan. 23, 2001 by Simpson, Shor, and Whitcomb), incorporated herein by reference.

Production or physical ripening processes for the silver halide grains used in emulsions of the present invention may be performed under the presence of cadmium salts, sulfites, lead salts, or thallium salts.

Reduction sensitization may also be used. Specific 40 examples of compounds useful in reduction sensitization include, but are not limited to, stannous chloride, hydrazine ethanolamine, and thioureaoxide. Reduction sensitization may be performed by ripening the grains while keeping the emulsion at pH 7 or above, or at pAg 8.3 or less. Also, 45 reduction sensitization may be performed by introducing a single addition portion of silver ion during the formation of the grains.

Spectral Sensitizers

In general, it may also be desirable to add spectral 50 Non-Photosensitive Source of Reducible Silver Ions sensitizing dyes to enhance silver halide sensitivity to ultraviolet, visible, and/or infrared radiation. Thus, the photosensitive silver halides may be spectrally sensitized with various dyes that are known to spectrally sensitize silver halide. Non-limiting examples of sensitizing dyes that can 55 be employed include cyanine dyes, merocyanine dyes, complex cyanine dyes, complex merocyanine dyes, holopolar cyanine dyes, hemicyanine dyes, styryl dyes, and hemioxanol dyes. Cyanine dyes, merocyanine dyes and complex merocyanine dyes are particularly useful.

Suitable sensitizing dyes such as those described in U.S. Pat. No. 3,719,495 (Lea), U.S. Pat. No. 4,396,712 (Kinoshita et al.), U.S. Pat. No. 4,690,883 (Kubodera et al.), U.S. Pat. No. 4,840,882 (Iwagaki et al.), U.S. Pat. No. et al.), U.S. Pat. No. 5,393,654 (Burrows et al), U.S. Pat. No. 5,441,866 (Miller et al.), U.S. Pat. No. 5,508,162 (Dankosh), 18

U.S. Pat. No. 5,510,236 (Dankosh), U.S. Pat. No. 5,541,054 (Miller et al.), JP 2000-063690 (Tanaka et al.), JP 2000-112054 (Fukusaka et al.), JP 2000-273329 (Tanaka et al.), JP 2001-005145 (Arai), JP 2001-064527 (Oshiyama et al.), and JP 2001-154305 (Kita et al.), can be used in the practice of the invention. All of the publications noted above are incorporated herein by reference.

A summary of generally useful spectral sensitizing dyes is also contained in *Research Disclosure*, Item 308119, Section IV, December, 1989. Additional teaching relating to specific combinations of spectral sensitizing dyes also include U.S. Pat. No. 4,581,329 (Sugimoto et al.), U.S. Pat. No. 4,582, 786 (Ikeda et al.), U.S. Pat. No. 4,609,621 (Sugimoto et al.), U.S. Pat. No. 4,675,279 (Shuto et al.), U.S. Pat. No. 4,678, 15 741 (Yamada et al.), U.S. Pat. No. 4,720,451 (Shuto et al.), U.S. Pat. No. 4,818,675 (Miyasaka et al.), U.S. Pat. No. 4,945,036 (Arai et al.), and U.S. Pat. No. 4,952,491 (Nishikawa et al.). Additional classes of dyes useful for spectral sensitization, including sensitization at other wavelengths are described in Research Disclosure, 1994, Item 36544, section V. All of the above references and patents above are incorporated herein by reference.

Also useful are spectral sensitizing dyes that decolorize by the action of light or heat. Such dyes are described in U.S. Pat. No. 4,524,128 (Edwards et al.), JP 2001-109101 (Adacbi), JP 2001-154305 (Kita et al.), and JP 2001-183770 (Hanyu et al.).

Spectral sensitizing dyes are chosen for optimum photosensitivity, 10 stability, and synthetic ease. They may be added before, after, or during the chemical finishing of the photothermographic emulsion. One useful spectral sensitizing dye for the photothermographic materials of this invention is anhydro-5-chloro-3,3'-di-(3-sulfopropyl)naphtho[1, 2-d]thiazolothiacyanine hydroxide, triethylammonium salt.

Spectral sensitizing dyes may be used singly or in combination. When used singly or in combination, the dyes are selected for the purpose of adjusting the wavelength distribution of the spectral sensitivity, and for the purpose of supersensitization. When using a combination of dyes having a supersensitizing effect, it is possible to attain much higher sensitivity than the sum of sensitivities that can be achieved by using each dye alone. It is also possible to attain such supersensitizing action by the use of a dye having no spectral sensitizing action by itself, or a compound that does not substantially absorb visible light. Diaminostilbene compounds are often used as supersensitizers.

An appropriate amount of spectral sensitizing dye added is generally about 10^{-10} to 10^{-1} mole, and preferably, about 10^{-7} to 10^{-2} mole per mole of silver halide.

The non-photosensitive source of reducible silver ions used in photothermographic materials of this invention can be any organic compound that contains reducible silver (1+) ions. Preferably, it is a silver salt or coordination complex that is comparatively stable to light and forms a silver image when heated to 50° C. or higher in the presence of an exposed silver halide and a reducing agent composition.

Silver salts of nitrogen-containing heterocyclic compounds are preferred, and one or more silver salts of 60 compounds containing an imino group are particularly preferred. Representative compounds of this type include, but are not limited to, silver salts of benzotriazole and substituted derivatives thereof (for example, silver methylbenzotriazole and silver 5-chlorobenzotriazole), silver salts of 5,064,753 (Kohno et al.), U.S. Pat. No. 5,281,515 (Delprato 65 1,2,4-triazoles or 1-H-tetrazoles such as phenylmercaptotetrazole as described in U.S. Pat. No. 4,220,709 (deMauriac), and silver salts of imidazoles and imidazole derivatives as

described in U.S. Pat. No. 4,260,677 (Winslow et al.). Particularly useful silver salts of this type are the silver salts of benzotriazole, substituted derivatives thereof, or mixtures of two or more of these salts. A silver salt of benzotriazole is most preferred in the photothermographic emulsions and 5 materials of this invention.

Silver salts of compounds containing mercapto or thione groups and derivatives thereof can also be used. Preferred compounds of this type include a heterocyclic nucleus containing 5 or 6 atoms in the ring, at least one of which is 10 a nitrogen atom, and other atoms being carbon, oxygen, or sulfur atoms. Such heterocyclic nuclei include, but are not limited to, triazoles, oxazoles, thiazoles, thiazolines, imidazoles, diazoles, pyridines, and triazines. Representative examples of these silver salts include, but are not limited 15 to, a silver salt of 3-mercapto-4-phenyl-1,2,4-triazole, a silver salt of 2-mercaptobenzimidazole, a silver salt of 2-mercapto-5-aminothiadiazole, a silver salt of 2-(2ethylglycolamido)benzothiazole, a silver salt of 5-carboxylic-1-methyl-2-phenyl-4-thiopyridine, a silver salt 20 of mercaptotriazine, a silver salt of 2-mercaptobenzoxazole, silver salts as described in U.S. Pat. No. 4,123,274 (Knight et al.) (for example, a silver salt of a 1,2,4-mercaptothiazole derivative, such as a silver salt of 3-amino-5-benzylthio-1, 2,4-thiazole), and a silver salt of thione compounds [such as 25] a silver salt of 3-(2-carboxyethyl)-4-methyl-4-thiazoline-2thione as described in U.S. Pat. No. 3,785,830 (Sullivan et al.)]. Examples of other useful silver salts of mercapto or thione substituted compounds that do not contain a heterocyclic nucleus include but are not limited to, a silver salt of 30 thioglycolic acids such as a silver salt of an S-alkylthioglycolic acid (wherein the alkyl group has from 12 to 22) carbon atoms), a silver salt of a dithiocarboxylic acid such as a silver salt of a dithioacetic acid, and a silver salt of a thioamide.

Suitable organic silver salts including silver salts of organic compounds having a carboxylic acid group can also be used. Examples thereof include a silver salt of an aliphatic carboxylic acid (for example, having 10 to 30 carbon atoms in the fatty acid) or a silver salt of an aromatic 40 carboxylic acid. Preferred examples of the silver salts of aliphatic carboxylic acids include silver behenate, silver arachidate, silver stearate, silver oleate, silver laurate, silver caprate, silver myristate, silver palmitate, silver maleate, silver fumarate, silver tartarate, silver furoate, silver 45 linoleate, silver butyrate, silver camphorate, and mixtures thereof When silver carboxylates are used, silver behenate is used alone or in mixtures with other silver salts.

In some embodiments of this invention, a mixture of a silver carboxylate and a silver salt of a compound having an 50 imino group can be used.

Representative examples of the silver salts of aromatic carboxylic acid and other carboxylic acid group-containing compounds include, but are not limited to, silver benzoate, and silver substituted-benzoates, (such as silver 3,5-55 dihydroxy-benzoate, silver o-methylbenzoate, silver m-methylbenzoate, silver p-methylbenzoate, silver 2,4-dichlorobenzoate, silver acetamidobenzoate, silver p-phenylbenzoate, silver tannate, silver phthalate, silver terephthalate, silver salicylate, silver phenylacetate, and 60 silver pyromellitate).

Silver salts of aliphatic carboxylic acids containing a thioether group as described in U.S. Pat. No. 3,330,663 (Weyde et al.) are also useful. Soluble silver carboxylates comprising hydrocarbon chains incorporating ether or thio- 65 ether linkages, or sterically hindered substitution in the α - (on a hydrocarbon group) or ortho- (on an aromatic group)

20

position, and displaying increased solubility in coating solvents and affording coatings with less light scattering can also be used. Such silver carboxylates are described in U.S. Pat. No. 5,491,059 (Whitcomb). Mixtures of any of the silver salts described herein can also be used if desired.

Silver salts of sulfonates are also useful in the practice of this invention. Such materials are described for example in U.S. Pat. No. 4,504,575 (Lee). Silver salts of sulfosuccinates are also useful as described for example in EP 0 227 141 A (Leenders et al.).

Moreover, silver salts of acetylenes can also be used as described, for example in U.S. Pat. No. 4,761,361 (Ozaki et al.) and U.S. Pat. No. 4,775,613 (Hirai et al.).

The methods used for making silver soap emulsions are well known in the art and are disclosed in *Research Disclosure*, April 1983, Item 22812, *Research Disclosure*, *October* 1983, Item 23419, U.S. Pat. No. 3,985,565 (Gabrielsen et al.) and the references cited above.

Non-photosensitive sources of reducible silver ions can also be provided as core-shell silver salts such as those described in U.S. Pat. No. 6,355,408 (Whitcomb et al.), that is incorporated herein by reference. These silver salts include a core comprised of one or more silver salts and a shell having one or more different silver salts.

Still another useful source of non-photosensitive reducible silver ions in the practice of this invention are the silver dimer compounds that comprise two different silver salts as described in copending and commonly assigned U.S. Ser. No. 09/812,597 (filed Mar. 20, 2001 by Whitcomb), that is incorporated herein by reference. Such non-photosensitive silver dimer compounds comprise two different silver salts, provided that when the two different silver salts comprise straight-chain, saturated hydrocarbon groups as the silver coordinating ligands, those ligands differ by at least 6 carbon atoms.

As one skilled in the are would understand, the non-photosensitive source of reducible silver ions can include various mixtures of the various silver salt compounds described herein, in any desirable proportions.

The photosensitive silver halide and the non-photosensitive source of reducible silver ions must be in catalytic proximity (that is, reactive association). It is preferred that these reactive components be present in the same emulsion layer.

The one or more non-photosensitive sources of reducible silver ions are preferably present in an amount of about 5% by weight to about 70% by weight, and more preferably, about 10% to about 50% by weight, based on the total dry weight of the emulsion layers. Stated another way, the amount of the sources of reducible silver ions is generally present in an amount of from about 0.001 to about 0.2 mol/m² of the dry photothermographic material, and preferably from about 0.0 1 to about 0.05 mol/m² of that material.

The total amount of silver (from all silver sources) in the photothermographic materials is generally at least 0.002 mol/m² and preferably from about 0.01 to about 0.05 mol/m².

Reducing Agents

The reducing agent (or reducing agent composition comprising two or more components) for the source of reducible silver ions can be any material, preferably an organic material, that can reduce silver (1+) ion to metallic silver. Conventional photographic developing agents such as methyl gallate, hydroquinone, substituted hydroquinones, 3-pyrazolidinones, p-aminophenols, p-phenylenediamines, hindered phenols, amidoximes, azines, catechol, pyrogallol,

ascorbic acid (and derivatives thereof), leuco dyes and other materials readily apparent to one skilled in the art can be used in this manner as described for example in U.S. Pat. No. 6,020,117 (Bauer et al.).

An "ascorbic acid" reducing agent (also referred to as a 5 developer or developing agent) means ascorbic acid, and complexes and derivatives thereof Ascorbic acid developing agents are described in a considerable number of publications in photographic processes, including U.S. Pat. No. 5,236,816 (Purol et al.) and references cited therein. Useful 10 ascorbic acid developing agents include ascorbic acid and the analogues, isomers and derivatives thereof. Such compounds include, but are not limited to, D- or L-ascorbic acid, sugar-type derivatives thereof (such as sorboascorbic acid, γ-lactoascorbic acid, 6-desoxy-L-ascorbic acid, 15 L-rhamnoascorbic acid, imino-6-desoxy-L-ascorbic acid, glucoascorbic acid, fucoascorbic acid, glucoheptoascorbic acid, maltoascorbic acid, L-arabosascorbic acid), sodium ascorbate, potassium ascorbate, isoascorbic acid (or L-erythroascorbic acid), and salts thereof (such as alkali 20 metal, ammonium or others known in the art), endiol type ascorbic acid, an enaminol type ascorbic acid, a thioenol type ascorbic acid, and an enamin-thiol type ascorbic acid, as described for example in U.S. Pat. No. 5,498,511 (Yamashita et al.), EP 0 585 792 A (Passarella et al.), EP 0 25 573 700 A (Lingier et al.), EP 0 588 408 A (Hieronymus et al.), U.S. Pat. No. 5,089,819 (Knapp), U.S. Pat. No. 5,278, 035 (Knapp), U.S. Pat. No. 5,384,232 (Bishop et al.), U.S. Pat. No. 5,376,510 (Parker et al.), JP 7-56286 (Toyoda), U.S. Pat. No. 2,688,549 (James et al.), and Research Disclosure, 30 March 1995, Item 37152, D-, L-, or D,L-ascorbic acid (and alkali metal salts thereof) or isoascorbic acid (or alkali metal salts thereof) are preferred. Sodium ascorbate and sodium isoascorbate are preferred salts. Mixtures of these developing agents can be used if desired.

Hindered phenol reducing agents can also be used (alone or in combination with one or more high-contrast co-developing agents and co-developer contrast enhancing agents). Hindered phenols are compounds that contain only one hydroxy group on a given phenyl ring and have at least 40 one additional substituent located ortho to the hydroxy group. Hindered phenol developers may contain more than one hydroxy group as long as each hydroxy group is located on different phenyl rings. Hindered phenol developers include, for example, binaphthols (that is 45 dihydroxybinaphthyls), biphenols (that is dihydroxybiphenyls), bis(hydroxynaphthyl)methanes, bis (hydroxyphenyl)methanes, (that is, bisphenols), hindered phenols, and hindered naphthols, each of which may be variously substituted.

Representative binaphthols include, but are not limited, to 1,1'-bi-2-naphthol, 1,1'-bi-4-methyl-2-naphthol and 6,6'-dibromo-bi-2-naphthol. For additional compounds see U.S. Pat. No. 3,094,417 (Workman) and U.S. Pat. No. 5,262,295 (Tanaka et al.), both incorporated herein by reference.

Representative biphenols include, but are not limited, to 2,2'-dihydroxy-3,3'-di-t-butyl-5,5-dimethylbiphenyl, 2,2'-dihydroxy-3,3',5,5'-tetra-t-butylbiphenyl, 2,2'-dihydroxy-3, 3'-di-t-butyl-5,5'-dichlorobiphenyl, 2-(2-hydroxy-3-t-butyl-5-methylphenyl)-4-methyl-6-n-hexylphenol, 4,4'- 60 dihydroxy-3,3',5,5'-tetra-t-butylbiphenyl and 4,4'-dihydroxy-3,3',5,5'-tetramethylbiphenyl. For additional compounds, see U.S. Pat. No. 5,262,295 (noted above).

Representative bis(hydroxynaphthyl)methanes include, 5,981,151 (Leenders et al.). but are not limited to, 4,4'-methylenebis(2-methyl-1-65 porated herein by reference. naphthol). For additional compounds see U.S. Pat. No.

5,981,151 (Leenders et al.). porated herein by reference. In some instances, the red prises two or more components.

Representative bis(hydroxyphenyl)methanes include, but are not limited to, bis(2-hydroxy-3-t-butyl-5-methylphenyl) methane (CAO-5), 1,1'-bis(2-hydroxy-3,5-dimethylphenyl)-3,5,5-trimethylhexane (NONOX or PERMANAX WSO), 1,1'-bis(3,5-di-t-butyl-4-hydroxyphenyl)methane, 2,2'-bis (4-hydroxy-3-methylphenyl)propane, 4,4'-ethylidene-bis(2-t-butyl-6-methylphenol), 2,2'-isobutylidene-bis(4,6-dimethylphenol) (LOWINOX 221B46), and 2,2'-bis(3,5-dimethyl-4-hydroxyphenyl)propane. For additional compounds see U.S. Pat. No. 5,262,295 (noted above).

Representative hindered phenols include, but are not limited to, 2,6-di-t-butylphenol, 2,6-di-t-butyl-4-methylphenol, 2,4-di-t-butylphenol, 2,6-dichlorophenol, 2,6-dimethylphenol and 2-t-butyl-6-methylphenol.

Representative hindered naphthols include, but are not limited to, 1-naphthol, 4-methyl-1-naphthol, 4-methoxy-1-naphthol, 4-chloro-1-naphthol and 2-methyl-1-naphthol. For additional compounds, see U.S. Pat. No. 5,262,295 (noted above).

More specific alternative reducing agents that have been disclosed in dry silver systems including amidoximes such as phenylamidoxime, 2-thienylamidoxime and p-phenoxyphenylamidoxime, azines (for example, 4-hydroxy-3,5-dimethoxybenzaldehydrazine), a combination of aliphatic carboxylic acid aryl hydrazides and ascorbic acid, such as 2,2'-bis(hydroxymethyl)propionyl-β-phenyl hydrazide in combination with ascorbic acid, a combination of polyhydroxybenzene and hydroxylamine, a reductione and/or a hydrazine [for example, a combination of hydroquinone and bis(ethoxyethyl)hydroxylamine, piperidinohexose reductone or formyl-4-methylphenylhydrazine, hydroxamic acids (such as phenylhydroxamic acid, p-hydroxyphenylhydroxamic acid, and o-alaninehydroxamic acid), a combination of azines and sulfonamidophenols (for example, phenothiazine and 2,6-35 dichloro-4-benzenesulfonamidophenol), α-cyanophenylacetic acid derivatives (such as ethyl α-cyano-2-methylphenylacetate and ethyl α-cyanophenylacetate), bis-o-naphthols [such as 2,2'dihydroxyl-1-binaphthyl, 6,6'-dibromo-2,2'-dihydroxy-1,1'binaphthyl, and bis(2-hydroxy-1-naphthyl)methane, a combination of bis-o-naphthol and a 1,3-dihydroxybenzene derivative (for example, 2,4-dihydroxybenzophenone or 2,4-dihydroxyacetophenone), 5-pyrazolones such as 3-methyl-1-phenyl-5-pyrazolone, reductones (such as dimethylaminohexose reductone, anhydrodihydro-aminohexose reductone and anhydrodihydro-piperidone-hexose reductione), sulfonamidophenol reducing agents (such as 2,6-dichloro-4-benzenesulfonamido-phenol, and p-benzenesulfonamidophenol), 2-phenylindane-1,3-dione and similar compounds, chromans (such as 2,2-dimethyl-7t-butyl-6-hydroxychroman), 1,4-dihydropyridines (such as 2,6-dimethoxy-3,5-dicarbethoxy-1,4-dihydropyridine), ascorbic acid derivatives (such as 1-ascorbylpalmitate, ascorbylstearate and unsaturated aldehydes and ketones), 55 3-pyrazolidones, and certain indane-1,3-diones.

An additional class of reducing agents that can be used as developers are substituted hydrazines including the sulfonyl hydrazides described in U.S. Pat. No. 5,464,738 (Lynch et al.). Still other useful reducing agents are described, for example, in U.S. Pat. No. 3,074,809 (Owen), U.S. Pat. No. 3,094,417 (Workman), U.S. Pat. No. 3,080,254 (Grant, Jr.) and U.S. Pat. No. 3,887,417 (Klein et al.). Auxiliary reducing agents may be useful as described in U.S. Pat. No. 5,981,151 (Leenders et al.). All of these patents are incorporated herein by reference.

In some instances, the reducing agent composition comprises two or more components such as a hindered phenol

developer and a co-developer that can be chosen from the various classes of reducing agents described below. Ternary developer mixtures involving the further addition of contrast enhancing agents are also useful. Such contrast enhancing agents can be chosen from the various classes of reducing agents described below.

23

Additional classes of reducing agents that can be used as co-developers are trityl hydrazides and formyl phenyl hydrazides as described in U.S. Pat. No. 5,496,695 (Simpson et al.), incorporated herein by reference.

Various contrast enhancing agents can be used in some photothermographic materials with specific co-developers. Examples of useful contrast enhancers include, but are not limited to, hydroxylamines (including hydroxylamine and alkyl- and aryl-substituted derivatives thereof), alkanola- 15 mines and ammonium phthalamate compounds as described for example, in U.S. Pat. No. 5,545,505 (Simpson), hydrox-amic acid compounds as described for example, in U.S. Pat. No. 5,545,507 (Simpson et al.), N-acylhydrazine compounds as described for example, in U.S. Pat. No. 5,558,983 (Simpson et al.), and hydrogen atom donor compounds as described in U.S. Pat. No. 5,637,449 (Harring et al.). All of the patents above are incorporated herein by reference.

It is to be understood that not all combinations of developer and non-photosensitive source of reducible silver ions 25 work equally well. One preferred combination includes a silver salt of benzotriazole, substituted derivatives thereof, or mixtures of such silver salts as the non-photosensitive source of reducible silver ions and an ascorbic acid reducing agent.

Another combination includes a silver fatty acid carboxylate having 10 to 30 carbon atoms, or mixtures of said silver carboxylates as the on-photosensitive source of reducible silver ions and a hindered phenol as the reducing agent.

The reducing agent (or mixture thereof) described herein 35 is generally present as 1 to 10% (dry weight) of the emulsion layer. In multilayer constructions, if the reducing agent is added to a layer other than an emulsion layer, slightly higher proportions, of from about 2 to 15 weight % may be more desirable. Any co-developers may be present generally in an 40 amount of from about 0.001% to about 1.5% (dry weight) of the emulsion layer coating. Phosphors

Phosphors are materials that emit infrared, visible, or ultraviolet radiation upon excitation. An intrinsic phosphor 45 is a material that is naturally (that is, intrinsically) phosphorescent. An "activated" phosphor is one composed of a basic material that may or may not be an intrinsic phosphor, to which one or more dopant(s) has been intentionally added. These dopants "activate" the phosphor and cause it to emit 50 infrared, visible, or ultraviolet radiation. For example, in Gd_2O_2S :Tb, the Tb atoms (the dopant/activator) give rise to the optical emission of the phosphor. Some phosphors, such as BaFBr, are known as storage phosphors. In these materials, the dopants are involved in the storage as well as 55 the emission of radiation.

Any conventional or useful phosphor can be used, singly or in mixtures, in the practice of this invention. More specific details of useful phosphors are provided as follows.

For example, useful phosphors are described in numerous 60 references relating to fluorescent intensifying screens, including but not limited to, *Research Disclosure*, Vol. 184, August 1979, Item 18431, Section IX, X-ray Screens/Phosphors, and U.S. Pat. No. 2,303,942 (Wynd et a].), U.S. Pat. No. 3,778,615 (Luckey), U.S. Pat. No. 4,032,471 65 (Luckey), U.S. Pat. No. 4,225,653 (Brixner et al.), U.S. Pat. No. 3,418,246 (Royce), U.S. Pat. No. 3,428,247 (Yocon),

24

U.S. Pat. No. 3,725,704 (Buchanan et al.), U.S. Pat. No. 2,725,704 (Swindells), U.S. Pat. No. 3,617,743 (Rabatin), U.S. Pat. No. 3,974,389 (Ferri et al.), U.S. Pat. No. 3,591, 516 (Rabatin), U.S. Pat. No. 3,607,770 (Rabatin), U.S. Pat. No. 3,666,676 (Rabatin), U.S. Pat. No. 3,795,814 (Rabatin), U.S. Pat. No. 4,405,691 (Yale), U.S. Pat. No. 4,311,487 (Luckey et al.), U.S. Pat. No. 4,387,141 (Patten), U.S. Pat. No. 5,021,327 (Bunch et al.), U.S. Pat. No. 4,865,944 (Roberts et al.), U.S. Pat. No. 4,994,355 (Dickerson et al.), U.S. Pat. No. 5,064,729 (Zegarski), U.S. Pat. No. 5,108,881 (Dickerson et al.), U.S. Pat. No. 5,871,892 (Dickerson et al.), EP 0 491 116 A (Benzo et al.), the disclosures of all of which are incorporated herein by reference with respect to the phosphors.

Useful classes of phosphors include, but are not limited to, calcium tungstate (CaWO₄), activated or unactivated lithium stannates, niobium and/or rare earth activated or unactivated yttrium, lutetium, or gadolinium tantalates, rare earth (such as terbium, lanthanum, gadolinium, cerium, and lutetium)-activated or unactivated middle chalcogen phosphors such as rare earth oxychalcogenides and oxyhalides, and terbium-activated or unactivated lanthanum and lutetium middle chalcogen phosphors.

Still other useful phosphors are those containing hafnium as described for example in U.S. Pat. No. 4,988,880 (Bryan et al.), U.S. Pat. No. 4,988,881 (Bryan et al.), U.S. Pat. No. 4,994,205 (Bryan et al.), U.S. Pat. No. 5,095,218 (Bryan et al.), U.S. Pat. No. 5,112,700 (Lambert et al.), U.S. Pat. No. 5,124,072 (Dole et al.), and U.S. Pat. No. 5,336,893 (Smith et al.), the disclosures of which are all incorporated herein by reference.

Preferred rare earth oxychalcogenide and oxyhalide phosphors are represented by the following formula (1):

$$\mathbf{M'}_{(w-r)}\mathbf{M''}_{r}\mathbf{O}_{w}\mathbf{X'} \tag{1}$$

wherein M' is at least one of the metals yttrium (Y), lanthanum (La), gadolinium (Gd), or lutetium (Lu), M" is at least one of the rare earth metals, preferably dysprosium (Dy), erbium (Er), europium (Eu), holmium (Ho), neodymium (Nd), praseodymium (Pr), samarium (Sm), tantalum (Ta), terbium (Tb), thulium (Tm), or ytterbium (Yb), X' is a middle chalcogen (S, Se, or Te) or halogen, r is 0.002 to 0.2, and w is 1 when X' is halogen or 2 when X' is a middle chalcogen. These include rare earth-activated lanthanum oxybromides, and terbium-activated or thulium-activated gadolinium oxides such as Gd₂O₂S:Tb.

Other suitable phosphors are described in U.S. Pat. No. 4,835,397 (Arakawa et al.) and U.S. Pat. No. 5,381,015 (Dooms), both incorporated herein by reference, and including for example divalent europium and other rare earth activated alkaline earth metal halide phosphors and rare earth element activated rare earth oxyhalide phosphors. Of these types of phosphors, the more preferred phosphors include alkaline earth metal fluorohalide prompt emitting and/or storage phosphors [particularly those containing iodide such as alkaline earth metal fluorobromoiodide storage phosphors as described in U.S. Pat. No. 5,464,568 (Bringley et al.), incorporated herein by reference].

Another class of phosphors includes compounds having a rare earth host and are rare earth activated mixed alkaline earth metal sulfates such as europium-activated barium strontium sulfate.

Particularly useful phosphors are those containing doped or undoped tantalum such as YTaO₄, YTaO₄:Nb, Y(Sr)TaO₄, and Y(Sr)TaO₄:Nb. These phosphors are described in U.S. Pat. No. 4,226,653 (Brixner), U.S. Pat. No. 5,064,729

(Zegarski), U.S. Pat. No. 5,250,366 (Nakajima et al.), and U.S. Pat. No. 5,626,957 (Benso et al.), all incorporated herein by reference.

Other useful phosphors are alkaline earth metal phosphors that can be the products of firing starting materials comprising optional oxide and a combination of species characterized by the following formula (2):

$$MFX_{(1-z)}I_zuM^aX^a:yA:eQ:tD$$
(2)

wherein M is magnesium (Mg), calcium (Ca), strontium 10 (Sr), or barium (Ba), F is fluoride, X is chloride (Cl) or bromide (Br), I is iodide, M^a is sodium (Na), potassium (K), rubidium (Rb), or cesium (Cs), X^a is fluoride (F), chloride (Cl), bromide (Br), or iodide (I), A is europium (Eu), cerium (Ce), samarium (Sm), or terbium (Tb), Q is BeO, MgO, 15 CaO, SrO, BaO, ZnO, Al₂O₃, La₂O₃, In₂O₃, SiO₂, TiO₂, ZrO₂, GeO₂, SnO₂,:Nb₂O₅, Ta₂O, or Tho₂, D is vanadium (V), chromium (Cr), manganese (Mn), iron (Fe), cobalt (Co), or nickel (Ni). The numbers in the noted formula are the following: "z" is 0 to 1, "u" is from 0 to 1, "y" is from 20 1×10^{-4} to 0.1, "e" is from 0 to 1, and "t" is from 0 to 0.01. These definitions apply wherever they are found in this application unless specifically stated to the contrary. It is also contemplated that M, X, A, and D represent multiple elements in the groups identified above.

Storage phosphors can also be used in the practice of this invention. Various storage phosphors are described for example, in U.S. Pat. No. 5,464,568 (noted above), incorporated herein by reference. Such phosphors include divalent alkaline earth metal fluorohalide phosphors that may 30 contain iodide are the product of firing an intermediate, comprising oxide and a combination of species characterized by the following formula (3):

$$[Ba_{(1-a-b-c)}Mg_aCa_bSr_c]FX_{(1-z)}I_zrM^aX^a:yA$$
(3)

wherein X, M^a, X^a, A, z, and y have the same meanings as for formula (2) and the sum of a, b, and c is from 0 to 4, and r is from 10⁻⁶ to 0.1. Some embodiments of these phosphors are described in more detail in U.S. Pat. No. 5,464,568 (noted above). A particularly useful storage phosphor is 40 BaFBr:Eu.

Still other storage phosphors are described in U.S. Pat. No. 4,368,390 (Takahashi et al.), incorporated herein by reference, and include divalent europium and other rare earth activated alkaline earth metal halides and rare earth 45 element activated rare earth oxyhalides, as described in more detail above.

Examples of useful phosphors include: SrS:Ce,SM, SrS:Eu,Sm, ThO₂:Er, La₂O₂S:Eu,Sm, ZnS:Cu,Pb, and others described in U.S. Pat. No. 5,227,253 (Takasu et al.), 50 incorporated herein by reference.

The one or more phosphors used in the practice of this invention are present in the photothermographic materials in an amount of at least 0.1 mole per mole, and preferably from about 0.5 to about 20 mole, per mole of total silver in the 55 photothermographic material. Generally, the amount of total silver is at least 0.002 mol/m².

Because of the size of the phosphors used in the invention, generally the layers in which they are incorporated (usually one or more emulsion layers), have a dry coating weight of 60 at least 5 g/m², and preferably from about 5 g/m² to about 200 g/m². Most preferably, the one or more phosphors and the photosensitive silver halide are incorporated within the same imaging layer that has a dry coating weight within the noted preferred range.

Thus, one preferred embodiment of the present invention is an aqueous-based X-radiation sensitive photothermo-

26

graphic material comprising a support having on one or both sides thereof, the same or different photothermographic imaging layers each having a dry coating weight of from about 5 to about 200 g/m², and a surface protective layer over each imaging layer, each imaging layer comprising a hydrophilic binder and in reactive association:

- a. a photosensitive "ultrathin" tabular grain silver halide (as described above),
- b. a silver salt of a compound having an imino group,
- c. a reducing agent composition for the reducible silver ions,
- d. a triazole compound as a toner, and
- e. a phosphor that is sensitive to X-radiation and is present in an amount of from about 0.1 to about 20 mole per mole of total silver,

the phosphor being one or more of YTaO₄, YTaO₄:Nb, Y(Sr)TaO₄, Y(Sr)TaO₄:Nb, and BaFBr:Eu.

Other Addenda

The photothermographic materials of the invention can also contain other additives such as shelf-life stabilizers, antifoggants, contrast enhancing agents, toners, development accelerators, acutance dyes, post-processing stabilizers or stabilizer precursors, thermal solvents (also known as "melt formers"), and other image-modifying agents as would be readily apparent to one skilled in the art.

To further control the properties of photothermographic materials, (for example, contrast, D_{min} , speed, or fog), it may be preferable to add one or more heteroaromatic mercapto compounds or heteroaromatic disulfide compounds of the formulae Ar—S—M¹ and Ar—S—S—Ar, wherein M¹ represents a hydrogen atom or an alkali metal atom and Ar represents a heteroaromatic ring or fused heteroaromatic ring containing one or more of nitrogen, sulfur, oxygen, 35 selenium, or tellurium atoms. Preferably, the heteroaromatic ring comprises benzimidazole, naphthimidazole, benzothiazole, naphthothiazole, benzoxazole, naphthoxazole, benzoselenazole, benzotellurazole, imidazole, oxazole, pyrazole, triazole, thiazole, thiadiazole, tetrazole, triazine, pyrimidine, pyridazine, pyrazine, pyridine, purine, quinoline, or quinazolinone. Compounds having other heteroaromatic rings and compounds providing enhanced sensitization at other wavelengths are also envisioned to be suitable. For example, heteroaromatic mercapto compounds are described as supersensitizers for infrared photothermographic materials in EP 0 559 228 B1 (Philip Jr. et al.).

If used, a heteroaromatic mercapto compound is generally present in an emulsion layer in an amount of at least about 0.0001 mole per mole of total silver in the emulsion layer. More preferably, the heteroaromatic mercapto compound is present within a range of about 0.001 mole to about 1.0 mole, and most preferably, about 0.005 mole to about 0.2 mole, per mole of total silver.

The photothermographic materials of the present invention can be further protected against the production of fog and can be stabilized against loss of sensitivity during storage. While not necessary for the practice of the invention, it may be advantageous to add mercury (2+) salts to the emulsion layer(s) as an antifoggant. Preferred mercury (2+) salts for this purpose are mercuric acetate and mercuric bromide. Other useful mercury salts include those described in U.S. Pat. No. 2,728,663 (Allen).

Other suitable antifoggants and stabilizers that can be used alone or in combination include thiazolium salts as described in U.S. Pat. No. 2,131,038 (Staud) and U.S. Pat. No. 2,694,716 (Allen), azaindenes as described in U.S. Pat.

No. 2,886,437 (Piper), triazaindolizines as described in U.S. Pat. No. 2,444,605 (Heimbach), the urazoles described in U.S. Pat. No. 3,287,135 (Anderson), sulfocatechols as described in U.S. Pat. No. 3,235,652 (Kennard), the oximes described in GB 623,448 (Carrol et al.), polyvalent metal 5 salts as described in U.S. Pat. No. 2,839,405 (Jones), thiuronium salts as described in U.S. Pat. No. 3,220,839 (Herz), palladium, platinum, and gold salts as described in U.S. Pat. No. 2,566,263 (Trirelli) and U.S. Pat. No. 2,597, 915 (Damshroder), compounds having —SO₂CBr₃ groups 10 as described for example in U.S. Pat. No. 5,594,143 (Kirk et al.) and U.S. Pat. No. 5,374,514 (Kirk et al.), and 2-(tribromomethylsulfonyl)quinoline compounds as described in U.S. Pat. No. 5,460,938 (Kirk et al.).

Stabilizer precursor compounds capable of releasing stabilizers upon application of heat during development can also be used. Such precursor compounds are described in for example, U.S. Pat. No. 5,158,866 (Simpson et al.), U.S. Pat. No. 5,175,081 (Krepski et al.), U.S. Pat. No. 5,298,390 (Sakizadeh et al.), and U.S. Pat. No. 5,300,420 (Kenney et 20 al.).

In addition, certain substituted-sulfonyl derivatives of benzotriazoles (for example alkylsulfonylbenzotriazoles and arylsulfonylbenzotriazoles) have been found to be useful stabilizing compounds (such as for post-processing print 25 stabilizing), as described in U.S. Pat. No. 6,171,767 (Kong et al.).

Furthermore, other specific useful antifoggants/stabilizers are described in more detail in U.S. Pat. No. 6,083,681 (Lynch et al.), incorporated herein by reference.

The photothermographic materials may also include one or more polyhalo antifoggants that include one or more polyhalo substituents including but not limited to, dichloro, dibromo, trichloro, and tribromo groups. The antifoggants can be aliphatic, alicyclic, or aromatic compounds, including aromatic heterocyclic and carbocyclic compounds. Particularly useful antifoggants of this type are polyhalo antifoggants, such as those having a —SO₂C(X')₃ group wherein X' represents the same or different halogen atoms.

Another class of useful antifoggants includes compounds described in copending and commonly assigned U.S. Ser. No. 10/014,961 (filed Dec. 11, 2001 by Burgmaier and Klaus), incorporated herein by reference. These compounds are generally defined as compounds having a pKa of 8 or less and represented by the following Structure I:

$$R^{1}$$
— SO_{2} — $C(R^{2})R^{3}$ — $(CO)_{m}$ — $(L)_{n}$ — SG (I)

wherein R₁ is an aliphatic or cyclic group, R² and R³ are independently hydrogen or bromine as long as at least one of them is bromine, L is an aliphatic divalent linking group, m and n are independently 0 or 1, and SG is a solubilizing group having a pKa of 8 or less.

In some preferred embodiments, the antifoggants are defined using Structure I noted above wherein:

when m and n are both 0, SG is carboxy (or a salt thereof), sulfo (or a salt thereof), phospho (or a salt thereof), (—SO₂N⁻COR⁴)(M²)⁺, or (—N⁻SO₂R⁴)(M²)⁺,

when m is 1 and n is 0, SG is carboxy (or salt thereof), sulfo (or a salt thereof), phospho (or a salt thereof), or $(-N^-SO_2R^4)(M^2)^+$,

when m and n are both 1, SG is carboxy (or a salt thereof), sulfo (or a salt thereof), phospho (or a salt thereof), or (—SO₂N⁻COR⁴)(M²)⁺, and

R⁴ is an aliphatic or cyclic group, and (M²)⁺ is a cation other than a proton.

Advantageously, the photothermographic materials of this invention also include one or more "thermal solvents" also

called "beat solvents," thermosolvents," "melt formers," "melt modifiers," "eutectic formers," development modifiers," "waxes," or "plasticizers" for improving the reaction speed of the silver-developing redox-reaction at elevated temperature.

28

By the term "thermal solvent" in this invention is meant an organic material which becomes a plasticizer or liquid solvent for at least one of the imaging layers upon heating at a temperature above 60° C. Useful for that purpose are a polyethylene glycol having a mean molecular weight in the range of 1,500 to 20,000 described in U.S. Pat. No. 3,347, 675. Further are mentioned compounds such as urea, methyl sulfonamide and ethylene carbonate being thermal solvents described in U.S. Pat. No. 3,667,959, and compounds such as tetrahydro-thiophene-1,1-dioxide, methyl anisate and 1,10-decanediol being described as thermal solvents in Research Disclosure, December 1976, Item 15027, pp. 26–28. Other representative examples of such compounds include, but are not limited to, niacinamide, hydantoin, 5,5-dimethylhydantoin, salicylanilide, phthalimide, N-hydroxyphthalimide, N-potassium-phthalimide, succinimide, N-hydroxy-1,8-naphthalimide, phthalazine, 1-(2H)-phthalazinone, 2-acetylphthalazinone, benzanilide, 1,3-dimethylurea, 1,3-diethylurea, 1,3-diallylurea, mesoerythritol, D-sorbitol, tetrahydro-2-pyrimidone, glycouril, 2-imidazolidone, 2-imidazolidone-4-carboxylic acid, and benzenesulfonamide. Combinations of these compounds can also be used including, for example, a combination of succinimide and 1,3-dimethylurea. Known thermal solvents are disclosed, for example, in U.S. Pat. No. 3,438,776 (Yudelson), U.S. Pat. No. 5,250,386 (Aono et al.), U.S. Pat. No. 5,368,979 (Freedman et al.), U.S. Pat. No. 5,716,772 (Taguchi et al.), U.S. Pat. No. 6,013,420 (Windender), and in Research Disclosure, December 1976, Item 15022.

It is often advantageous to include a base-release agent or base precursor in the photothermographic materials according to the invention to provide improved and more effective image development. A base-release agent or base precursor as employed herein is intended to include compounds which upon heating in the photothermographic material provide a more effective reaction between the described photosensitive silver halide, and the image-forming combination comprising a silver salt and the silver halide developing agent. Representative base-release agents or base precursors 45 include guanidinium compounds, such as guanidinium trichloroacetate, and other compounds that are known to release a base moiety but do not adversely affect photographic silver halide materials, such as phenylsulfonyl acetates. Further details are provided in U.S. Pat. No. 50 4,123,274 (Knight et al.).

A range of concentration of the base-release agent or base precursor is useful in the described photothermographic materials. The optimum concentration of base-release agent or base precursor will depend upon such factors as the desired image, particular components in the photothermographic material, and processing conditions.

Toners

"Toners" are compounds that improve image color and increase the optical density of the developed image. For black and white photothermographic films, particularly useful toners are those that also contribute to the formation of a black image upon development. Thus, the use of "toners" or derivatives thereof is highly desirable and toners are preferably included in the photothermographic materials described herein. Such compounds are well known materials in the photothermographic art, as described in U.S. Pat. No. 3,074,809 (Owen), U.S. Pat. No. 3,080,254 (Grant, Jr.), U.S.

Pat. No. 3,446,648 (Workman), U.S. Pat. No. 3,832,186 (Masuda et al.), U.S. Pat. No. 3,844,797 (Willems et al.), U.S. Pat. No. 3,847,612 (Winslow), U.S. Pat. No. 3,881,938 (Masuda et al.), U.S. Pat. No. 3,951,660 (Hagemann et al.), U.S. Pat. No. 4,082,901 (Laridon et al.), U.S. Pat. No. 5 4,123,282 (Winslow), U.S. Pat. No. 4,201,582 (White et al.), U.S. Pat. No. 4,220,709 (deMauriac et al.), U.S. Pat. No. 4,451,561 (Hirabayashi et al.), U.S. Pat. No. 4,543,309 (Hirabayashi et al.), U.S. Pat. No. 5,599,647 (Defieuw et al.), and GB 1,439,478 (AGFA).

Examples of toners include, but are not limited to, phthalimide and N-hydroxyphthalimide, cyclic imides (such as succinimide), pyrazoline-5-ones, quinazolinone, 1-phenylurazole, 3-phenyl-2-pyrazoline-5-one, and 2,4thiazolidinedione, naphthalimides (such as N-hydroxy-1,8- 15 naphthalimide), cobalt complexes [such as hexaaminecobalt (3+)trifluoroacetate, mercaptans (such as mercaptotriazoles including 3-mercapto-1,2,4-triazole, 3-mercapto-4-phenyl-1,2,4-triazole, 4-phenyl-1,2,4-triazolidine-3,5-dithione, 4-allyl-3-amino-5-mercapto-1,2,4-triazole and 4-methyl-5- 20 thioxo-1,2,4-triazolidin-3-one, pyrimides including 2,4dimercaptopyrimidine, thiadiazoles including 2,5dimercapto-1,3,4-thiadiazole, 5-methyl-1,3,4-thiadiazolyl-2-thiol, mercaptotetrazoles including 1-phenyl-5mercaptotetrazole, and 5-acetylamino-1,3,4-thiadiazoline-2-25 thione, mercaptoimidazoles including 1,3-dihydro-1phenyl-2H-imidazole-2-thione,), N-(aminomethyl) aryldicarboximides [such as (N,N-dimethylaminomethyl) phthalimide, and N-(dimethylaminomethyl)naphthalene-2, 3-dicarboximide, a combination of blocked pyrazoles, 30 isothiuronium derivatives, and certain photobleach agents [such as a combination of N,N'-hexamethylene-bis(1carbamoyl-3,5-dimethylpyrazole), 1,8-(3,6-diazaoctane)bis (isothiuronium)trifluoroacetate, a n d 2-(tribromomethylsulfonyl benzothiazole), merocyanine 35 dyes {such as 3-ethyl-5-[(3-ethyl-2-benzothiazolinylidene)-1-methyl-ethylidene]-2-thio-2,4-oazolidinedione, phthalazine and derivatives thereof [such as those described in U.S. Pat. No. 6,146,822 (Asanuma et al.)], phthalazinone and phthalazinone derivatives, or metal 40 salts or these derivatives [such as 4-(1-naphthyl) phthalazinone, 6-chlorophthalazinone, 5,7dimethoxyphthalazinone, and 2,3-dihydro-1,4phthalazinedione, a combination of phthalazine (or derivative thereof) plus one or more phthalic acid deriva- 45 tives (such as phthalic acid, 4-methylphthalic acid, 4-nitrophthalic acid, and tetrachlorophthalic anhydride), quinazolinediones, benzoxazine or naphthoxazine derivatives, rhodium complexes functioning not only as tone modifiers but also as sources of halide ion for silver halide 50 formation in-situ [such as ammonium hexachlororhodate (III), rhodium bromide, rhodium nitrate, and potassium hexachlororhodate (III)], benzoxazine-2,4-diones (such as 1,3-benzoxazine-2,4-dione, 8-methyl-1,3-benzoxazine-2,4dione and 6-nitro-1,3-benzoxazine-2,4-dione), pyrimidines 55 and asym-triazines (such as 2,4-dihydroxypyrimidine, 2-hydroxy-4-aminopyrimidine and azauracil) and tetraazapentalene derivatives [such as 3,6-dimercapto-1,4-diphenyl-1H,4H-2,3a,5,6a-tetraazapentalene and 1,4-di-(ochlorophenyl)-3,6-dimercapto-1H,4H-2,3a,5,6a-60 tetraazapentalene].

Phthalazine and phthalazine derivatives [such as those] described in U.S. Pat. No. 6,146,822 (noted above), incorporated herein by reference] are particularly useful as toners in when using silver carboxylate compounds as the non- 65 photosensitive source of reducible silver and hindered phenols as developers. Phthalazine and derivatives thereof can

be used in any layer of the photothermo-graphic material on either side of the support

Compounds that are particularly useful as toners in the practice of this invention when using silver salts of nitrogencontaining heterocyclic compounds containing an imino group as the non-photosensitive source of reducible silver and ascorbic acid, an ascorbic acid complex or an ascorbic acid derivative as a reducing agent are mercaptotriazole compounds defined by the following Structure II

$$\begin{array}{c|c} & & & & \\ & & & & \\ & & & & \\ R_1 & & & \\ & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\$$

wherein R_1 and R_2 independently represent hydrogen, a substituted or unsubstituted alkyl group of from 1 to 7 carbon atoms (such as methyl, ethyl, isopropyl, t-butyl, n-hexyl, hydroxymethyl, and benzyl), a substituted or unsubstituted alkenyl group having 2 to 5 carbon atoms in the hydrocarbon chain (such as ethenyl, 1,2-propenyl, methallyl, and 3-buten-1-yl), a substituted or unsubstituted cycloalkyl group having 5 to 7 carbon atoms forming the ring (such as cyclopenyl, cyclohexyl, and 2,3dimethylcyclohexyl), a substituted or unsubstituted aromatic or non-aromatic heterocyclyl group having 5 or 6 carbon, nitrogen, oxygen, or sulfur atoms forming the aromatic or non-aromatic heterocyclyl group (such as pyridyl, furanyl, thiazolyl, and thienyl), an amino or amide group (such as amino or acetamido), and a substituted or unsubstituted aryl group having 6 to 10 carbon atoms forming the aromatic ring (such as phenyl, tolyl, naphthyl, and 4-ethoxyphenyl).

In addition, R₁ and R₂ can be a substituted or unsubstituted Y_1 — $(CH_2)_k$ — group wherein Y_1 is a substituted or unsubstituted aryl group having 6 to 10 carbon atoms as defined above for R_1 and R_2 , or a substituted or unsubstituted aromatic or non-aromatic heterocyclyl group as defined above for R_1 , Also, k is 1–3.

Alternatively, R_1 and R_2 taken together can form a substituted or unsubstituted, saturated or unsaturated 5- to 7-membered aromatic or non-aromatic nitrogen-containing heterocyclic ring comprising carbon, nitrogen, oxygen, or sulfur atoms in the ring (such as pyridyl, diazinyl, triazinyl, piperidine, morpholine, pyrrolidine, pyrazolidine, and thiomorpholine).

Still again, R₁ or R₂ can represent a divalent linking group (such as a phenylene, methylene, or ethylene group) linking two mercaptotriazole groups, and R₂ may further represent carboxy or its salts.

M₁ is hydrogen or a monovalent cation (such as an alkali metal cation, an ammonium ion, or a pyridinium ion).

The definition of mercaptotriazoles of Structure II also includes the following provisos:

- 1) R_1 and R_2 are not simultaneously hydrogen.
- 2) When R₁ is substituted or unsubstituted phenyl or benzyl, R₂ is not substituted or unsubstituted phenyl or benzyl.
- 3) When R_2 is hydrogen, R_1 is not allenyl, 2,2diphenylethyl, α -methylbenzyl, or a phenyl group having a cyano or a sulfonic acid substituent.
- 4) When R_1 is benzyl or phenyl, R_2 is not substituted 1,2-dihydroxyethyl, or 2-hydroxy-2-propyl.
- 5) When R_1 is hydrogen, R_2 is not 3-phenylthiopropyl. In one further optional embodiment, the photothermographic material is further defined wherein:

6) One or more thermally developable imaging layers has a pH less than 7.

Preferably, R₁ is methyl, t-butyl, a substituted phenyl or benzyl group. More preferably R₁ is benzyl. Also, R₁ can represent a divalent linking group (such as a phenylene, 5 methylene, or ethylene group) that links two mercaptotriazole groups.

Preferably, R₂ is hydrogen, acetamido, or hydroxymethyl. More preferably, R₂ is hydrogen. Also, R₂ can represent a divalent linking group (such as a phenylene, methylene, or ethylene group) that links two mercaptotriazole groups.

As noted above, in one embodiment, one or more thermally developable imaging layers has a pH less than 7. The pH of these layers may be conveniently controlled to be acidic by addition of ascorbic acid as the developer. Alternatively, the pH may be controlled by adjusting the pH of the silver salt dispersion prior to coating with mineral acids such as, for example, sulfuric acid or nitric acid or by addition of organic acids such as citric acid. It is preferred that the pH of the one or more imaging layers be less than 7 and preferably less than 6. This pH value can be determined using a surface pH electrode after placing a drop of KNO₃ solution on the sample surface. Such electrodes are available from Corning (Corning, N.Y.).

Many of the toners described herein are heterocyclic compounds. It is well known that heterocyclic compounds 25 exist in tautomeric forms. In addition both annular (ring) tautomerism and substituent tautomerism are often possible.

For example, in one preferred class of toners, 1,2,4-mercaptotriazole compounds, at least three tautomers (a 1H form, a 2H form and a 4H form) are possible.

H
N
N
N
N
N
N
N
N
N
N
N
SH
N
SH
SH
N
 N
 N

In addition, 1,2,4-mercaptotriazoles are also capable of thiol-thione substituent tautomerism.

Interconversion among these tautomers can occur rapidly and individual tautomers cannot be isolated, although one tautomeric form may predominate. For the 1,2,4-55 mercaptotriazoles described herein, the 4H -thiol structural formalism is used with the understanding that such tautomers do exist.

Mercaptotriazole compounds represented by Structure II are particularly preferred when used with silver benzotria- 60 zole as the non-photosensitive source of reducible silver and ascorbic acid as the reducing agent. When so used, compounds represented by Structure II have been found to give dense black images,

Representative compounds having Structure II and useful 65 as toners in the practice of the present invention include the following compounds T-1 through T-59:

32

T-10

T-11

T-12

T-13

50

30

35

-continued

-continued

40 HO
$$-CH_2$$
 N SH $-CH_3$ $-CH_3$

30

35

40

T-24 ₄₅

T-25

55

T-26 60

65

T-23

T-21

T-20

-continued

-continued

$$S$$
 N
 N
 N
 SH
 CH_3

T-28

N
N
N
SH

$$CH_3$$

T-29

10

15

20

45

T-36

CH₃

T-35

-continued

H SH

`SH

$$\begin{array}{c}
\text{T-39} \\
\text{Cl} \\
\text{N} \\
\text{N} \\
\text{N} \\
\text{SH}
\end{array}$$

$$T-40$$

N
N
SH
 H_3C
 CH_3
 $T-41$

$$N \longrightarrow N$$
 $N \longrightarrow N$
 $N \longrightarrow N$

T-52
$$5 \qquad HO - CH_2 \qquad N \qquad SH$$

Compounds T-1, T-2, T-3, T-1 1, T-12, T-16, T-37, T-41, and T-44, are preferred in the practice of this invention, and Compounds T-1, T-2, and T-3 are most preferred.

The mercaptotriazole toners described herein can be readily prepared using well known synthetic methods. For example, compound T-1 can be prepared as described in U.S. Pat. No. 4,628,059 (Finkelstein et al.) or in U.S. Pat. No. 4,120,864 (Seidel, et. al.). Additional preparations of various mercaptotraizoles are described in U.S. Pat. No. 3,769,411 (Greenfield et al.), U.S. Pat. No. 4,183,925 (Baxter et al.), U.S. Pat. No. 6,074,813 (Asanuma et al.), DE 1 670 604 (Korosi), and in *Chem. Abstr.* 1968, 69, 52114j. Some mercaptotriazole compounds are commercially available.

As would be understood by one skilled in the art, two or more mercaptotriazole toners as defined by Structure II can be used in the practice of this invention if desired, and the multiple toners can be located in the same or different layers of the photothermographic materials.

Additional conventional toners can also be included with the one or more mercaptotriazoles described above. Such compounds are well known materials in the photothermographic art, as shown in U.S. Pat. No. 3,080,254 (Grant, Jr.), U.S. Pat. No. 3,847,612 (Winslow), U.S. Pat. No. 4,123,282 (Winslow), U.S. Pat. No. 4,082,901 (Laridon et al.), U.S. Pat. No. 3,074,809 (Owen), U.S. Pat. No. 3,446,648 (Workman), U.S. Pat. No. 3,844,797 (Willems et al.), U.S. Pat. No. 3,951,660 (Hagemann et al.), U.S. Pat. No. 5,599, 647 (Defieuw et al.) and GB 1,439,478 (AGFA).

T-56 45 Mixtures of mercaptotriazoles with additional toners (for example, 3-mercapto-4-benzyl-1,2,4-triazole with phthalazine) are also useful in the practice of this invention.

Generally, one or more toners described herein are present in an amount of about 0.01% by weight to about 10%, and more preferably about 0.1% by weight to about 10% by weight, based on the total dry weight of the layer in which it is included. Toners may be incorporated in one or more of the thermally developable imaging layers as well as in adjacent layers such as a protective overcoat or underlying "carrier" layer. The toners can be located on both sides of the support if thermally developable imaging layers are present on both sides of the support.

T-57 Binders

T-55

The photosensitive tabular grain silver halide, the non-photosensitive source of reducible silver ions, the reducing agent composition, toner(s), and any other additives used in the present invention are generally added to one or more binders that are hydrophilic. Thus, predominantly aqueous formulations (at least 50 solvent volume % and preferably at least 70 solvent volume % is water) are used to prepare the photothermographic materials of this invention. Mixtures of such binders can also be used.

Examples of useful hydrophilic binders include, but are not limited to, proteins and protein derivatives, gelatin and gelatin derivatives (hardened or unhardened, including alkali- and acid-treated gelatins, acetylated gelatin, oxidized gelatin, phthalated gelatin, and deionized gelatin), cellulosic 5 materials such as hydroxymethyl cellulose and cellulosic esters, acrylamide/methacrylamide polymers, acrylic/ methacrylic polymers polyvinyl pyrrolidones, polyvinyl alcohols, poly(vinyl lactams), polymers of sulfoalkyl acrylate or methacrylates, hydrolyzed polyvinyl acetates, 10 polyacrylamides, polysaccharides (such as dextrans and starch ethers), and other synthetic or naturally occurring vehicles commonly known for use in aqueous-based photographic emulsions (see for example, Research Disclosure, Item 38957, noted above). Cationic starches can also be used 15 as a peptizer for tabular silver halide grains as described in U.S. Pat. No. 5,620,840 (Maskasky) and U.S. Pat. No. 5,667,955 (Maskasky).

"Minor" amounts of hydrophobic binders can also be present as long as more than 50% (by weight of total 20 binders) is composed of hydrophilic binders. Examples of typical hydrophobic binders include, but are not limited to, polyvinyl acetals, polyvinyl chloride, polyvinyl acetate, cellulose acetate, cellulose acetate butyrate, polyolefins, polyesters, polystyrenes, polyacrylonitrile, polycarbonates, 25 methacrylate copolymers, maleic anhydride ester copolymers, butadiene-styrene copolymers, and other materials readily apparent to one skilled in the art. Copolymers (including terpolymers) are also included in the definition of polymers. The polyvinyl acetals (such as polyvinyl butyral 30 and polyvinyl formal) and vinyl copolymers (such as polyvinyl acetate and polyvinyl chloride) are particularly preferred. Particularly suitable binders are polyvinyl butyral resins that are available as BUTVAR® B79 (Solutia, Inc.) and PIOLOFORM® BS-18 or PIOLOFORM® BL-16 35 (Wacker Chemical Company). Minor amounts of aqueous dispersions (such as latexes) of hydrophobic binders may also be used. Such latex binders are described, for example, in EP-0 911 691 A1 (Ishizaka et al.).

Hardeners for various binders may be present if desired 40 and the hydrophilic binders used in the photothermographic materials are generally partially or fully hardened using any conventional hardener. Useful hardeners are well known and include vinyl sulfone compounds described, U.S. Pat. No. 6,143,487 (Philip et al.), EP 0 460 589 (Gathmann et al.), 45 aldehydes, and various other hardeners described in U.S. Pat. No. 6,190,822 (Dickerson et al.), as well as those described in T. H. James, *The Theory of the Photographic Process*, Fourth Edition, Eastman Kodak Company, Rochester, N.Y., 1977, Chapter 2, pp. 77–8.

Where the proportions and activities of the photothermographic materials require a particular developing time and temperature, the binder(s) should be able to withstand those conditions. Generally, it is preferred that the binder does not decompose or lose its structural integrity at 120° C. for 60 seconds. It is more preferred that the binder does not decompose or lose its structural integrity at 177° C. for 60 seconds

The polymer binder(s) is used in an amount sufficient to carry the components dispersed therein. The effective range 60 can be appropriately determined by one skilled in the art. Preferably, a binder is used at a level of about 10% by weight to about 90% by weight, and more preferably at a level of about 20% by weight to about 70% by weight, based on the total dry weight of the layer in which it is included. The 65 amount of binders in double-sided photothermographic materials can be the same or different.

42

Support Materials

The photothermographic materials of this invention comprise a polymeric support that is preferably a flexible, transparent film that has any desired thickness and is composed of one or more polymeric materials, depending upon their use. The supports are generally transparent (especially if the material is used as a photomask) or at least translucent, but in some instances, opaque supports may be useful. They are required to exhibit dimensional stability during thermal development and to have suitable adhesive properties with overlying layers. Useful polymeric materials for making such supports include, but are not limited to, polyesters (such as polyethylene terephthalate and polyethylene naphthalate), cellulose acetate and other cellulose esters, polyvinyl acetal, polyolefins (such as polyethylene and polypropylene), polycarbonates, and polystyrenes (and polymers of styrene derivatives). Preferred supports are composed of polymers having good heat stability, such as polyesters and polycarbonates. Support materials may also be treated or annealed to reduce shrinkage and promote dimensional stability. Polyethylene terephthalate film is the most preferred support. Various support materials are described, for example, in Research Disclosure, August 1979, Item 18431. A method of making dimensionally stable polyester films is described in Research Disclosure, September 1999, Item 42536.

It is also useful to use supports comprising dichroic mirror layers wherein the dichroic mirror layer reflects radiation at least having the predetermined range of wavelengths to the emulsion layer and transmits radiation having wavelengths outside the predetermined range of wavelengths. Such dichroic supports are described in U.S. Pat. No. 5,795,708 (Boutet), incorporated herein by reference.

It is further possible useful to use transparent, multilayer, polymeric supports comprising numerous alternating layers of at least two different polymeric materials. Such multilayer polymeric supports preferably reflect at least 50% of actinic radiation in the range of wavelengths to which the photothermographic sensitive material is sensitive, and provide photothermographic materials having increased speed. Such transparent, multilayer, polymeric supports are described in WO 02/21208 A1 (Simpson et al.), incorporated herein by reference.

Opaque supports, such as dyed polymeric films and resin-coated papers that are stable to high temperatures, can also be used.

Support materials can contain various colorants, pigments, tinting dyes, antihalation or acutance dyes if desired. Support materials may be treated using conventional procedures (such as corona discharge) to improve adhesion of overlying layers, or subbing or other adhesion-promoting layers can be used. Useful subbing layer formulations include those conventionally used for photographic materials such as vinylidene halide polymers.

Photothermographic Formulations

An aqueous formulation for the photothermographic emulsion layer(s) can be prepared by dissolving or dispersing the hydrophilic binder (such as gelatin or a gelatin derivative), the photosensitive "ultrathin" tabular grain silver halide(s), the non-photosensitive source of reducible silver ions, the reducing agent composition, the phosphor, and optional addenda in water or water-organic solvent mixtures to provide aqueous-based coating formulations. Minor amounts (less than 50 volume %) of water-miscible organic solvents such as water-miscible alcohols, acetone, or methyl ethyl ketone, may also be present. Preferably, the solvent system used to provide these formulations is at least

80 volume % water and more preferably the solvent system is at least 90 volume % water).

Photothermographic materials of this invention can contain plasticizers and lubricants such as polyalcohols and diols of the type described in U.S. Pat. No. 2,960,404 5 (Milton et al.), fatty acids or esters such as those described in U.S. Pat. No. 2,588,765 (Robijns) and U.S. Pat. No. 3,121,060 (Duane), and silicone resins such as those described in GB 955,061 (DuPont). The materials can also contain matting agents such as starch, titanium dioxide, zinc 10 oxide, silica, and polymeric beads including beads of the type described in U.S. Pat. No. 2,992,101 (Jelley et al.) and U.S. Pat. No. 2,701,245 (Lynn). Polymeric fluorinated surfactants may also be useful in one or more layers of the photothermographic materials for various purposes, such as 15 improving coatability and optical density uniformity as described in U.S. Pat. No. 5,468,603 (Kub).

EP 0 792 476 B1 (Geisler et al.) describes various means of modifying photothermographic materials to reduce what is known as the "woodgrain" effect, or uneven optical 20 density. This effect can be reduced or eliminated by several means, including treatment of the support, adding matting agents to the topcoat, using acutance dyes in certain layers or other procedures described in the noted publication.

The photothermographic materials of this invention can 25 include antistatic or conducting layers. Such layers may contain soluble salts (for example, chlorides or nitrates), evaporated metal layers, or ionic polymers such as those described in U.S. Pat. No. 2,861,056 (Minsk) and U.S. Pat. No. 3,206,312 (Sterman et al.), or insoluble inorganic salts 30 such as those described in U.S. Pat. No. 3,428,451 (Trevoy), electroconductive underlayers such as those described in U.S. Pat. No. 5,310,640 (Markin et al.), electronically-conductive metal antimonate particles such as those described in U.S. Pat. No. 5,368,995 (Christian et al.), and 35 electrically-conductive metal-containing particles dispersed in a polymeric binder such as those described in EP 0 678 776 A (Melpolder et al.). Other antistatic agents are well known in the art.

Other conductive compositions include one or more 40 fluoro-chemicals each of which is a reaction product of R_f — CH_2CH_2 — SO_3H with an amine wherein R_f comprises 4 or more fully fluorinated carbon atoms. These antistatic compositions are described in more detail in copending and commonly assigned U.S. Ser. No. 10/107,551 (filed Mar. 27, 45 2002 by Sakizadeh, LaBelle, Orem, and Bhave) that is incorporated herein by reference.

The photothermographic materials of this invention can be constructed of one or more layers on a support. Single layer materials should contain the tabular grain photosensi- 50 tive silver halide, the non-photosensitive source of reducible silver ions, the reducing agent composition, the hydrophilic binder, the phosphor, as well as optional materials such as toners, acutance dyes, coating aids and other adjuvants.

Two-layer constructions comprising a single imaging 55 layer coating containing all the ingredients and a surface protective topcoat are generally found in the materials of this invention. However, two-layer constructions containing silver halide, phosphor, and non-photosensitive source of reducible silver ions in one imaging layer (usually the layer 60 adjacent to the support) and the reducing agent composition and other ingredients in the second imaging layer or distributed between both layers are also envisioned.

For double-sided photothermographic materials, each side of the support can include one or more of the same or 65 different imaging layers, interlayers, and protective topcoat layers. In such materials preferably a topcoat is present as

44

the outermost layer on both sides of the support. The photothermographic layers on opposite sides can have the same or different construction and can be overcoated with the same or different protective layers.

Layers to promote adhesion of one layer to another in photothermographic materials are also known, as described for example in U.S. Pat. No. 5,891,610 (Bauer et al.), U.S. Pat. No. 5,804,365 (Bauer et al.), and U.S. Pat. No. 4,741, 992 (Przezdziecki). Adhesion can also be promoted using specific polymeric adhesive materials as described for example in U.S. Pat. No. 5,928,857 (Geisler et al.).

Layers to reduce emissions from the film may also be present, including the polymeric barrier layers described in U.S. Pat. No. 6,352,819 (Kenney et al.), U.S. Pat. No. 6,352,820 (Bauer et al.), and in copending and commonly assigned U.S. Ser. No. 09/916,366 (filed Jul. 27, 2001 by Bauer, Horch, Miller, Teegarden, Hunt, and Sakizadeh), all incorporated herein by reference.

Photothermographic formulations described herein can be coated by various coating procedures including wire wound rod coating, dip coating, air knife coating, curtain coating, slide coating, or extrusion coating using hoppers of the type described in U.S. Pat. No. 2,681,294 (Beguin). Layers can be coated one at a time, or two or more layers can be coated simultaneously by the procedures described in U.S. Pat. No. 2,761,791 (Russell), U.S. Pat. No. 4,001,024 (Dittman et al.), U.S. Pat. No. 4,569,863 (Keopke et al.), U.S. Pat. No. 5,340,613 (Hanzalik et al.), U.S. Pat. No. 5,405,740 (LaBelle), U.S. Pat. No. 5,415,993 (Hanzalik et al.), U.S. Pat. No. 5,525,376 (Leonard), U.S. Pat. No. 5,733,608 (Kessel et al.), U.S. Pat. No. 5,849,363 (Yapel et al.), U.S. Pat. No. 5,843,530 (Jerry et al.), U.S. Pat. No. 5,861,195 (Bhave et al.), and GB 837,095 (Ilford). A typical coating gap for the emulsion layer can be from about 10 to about 750 μ m, and the layer can be dried in forced air at a temperature of from about 20° C. to about 100° C. It is preferred that the thickness of the layer be selected to provide maximum image densities greater than about 0.2, and more preferably, from about 0.5 to 5.0 or more, as measured by a MacBeth Color Densitometer Model TD 504.

When the layers are coated simultaneously using various coating techniques, a "carrier" layer formulation comprising a single-phase mixture of the two or more polymers described above may be used. Such formulations are described in U.S. Pat. No. 6,355,405 (Ludemann et al.), incorporated herein by reference.

Mottle and other surface anomalies can be reduced in the materials of this invention by incorporation of a fluorinated polymer as described for example in U.S. Pat. No. 5,532,121 (Yonkoski et al.) or by using particular drying techniques as described, for example in U.S. Pat. No. 5,621,983 (Ludemann et al.).

Preferably, two or more layers are applied to a film support using slide coating. The first layer can be coated on top of the second layer while the second layer is still wet. The first and second fluids used to coat these layers can be the same or different.

While the first and second layers can be coated on one side of the film support, manufacturing methods can also include forming on the opposing or backside of said polymeric support, one or more additional layers, including an antibalation layer, an antistatic layer, or a layer containing a matting agent (such as silica), an imaging layer, a protective topcoat layer, or a combination of such layers.

It is also contemplated that the photothermographic materials of this invention can include thermally developable imaging (or emulsion) layers on both sides of the support

and at least one infrared radiation absorbing heat-bleachable composition in an antihalation underlayer beneath other layers on one or both sides of the support.

Photothermographic materials having thermally developable layers disposed on both sides of the support often suffer from "crossover." Crossover results when radiation used to image one side of the photothermographic material is transmitted through the support and images the photothermographic layers on the opposite side of the support. Such radiation causes a lowering of image quality (especially sharpness). As crossover is reduced, the sharper becomes the image. Various methods are available for reducing crossover. Such "anti-crossover" materials can be materials specifically included for reducing crossover or they can be acutance or antihalation dyes. In either situation it is necessary that they be rendered colorless during processing.

To promote image sharpness, photothermographic materials according to the present invention can contain one or more layers containing acutance, filter, cross-over prevention (anti-crossover), anti-irradiation and/or antihalation 20 dyes. These dyes are chosen to have absorption close to the exposure wavelength and are designed to absorb scattered light. One or more antihalation dyes may be incorporated into one or more antihalation layers according to known techniques, as an antihalation backing layer, as an antihalation underlayer, or as an antihalation overcoat. Additionally, one or more acutance dyes may be incorporated into one or more layers such as a thermally developable imaging layer, primer layer, underlayer, or topcoat layer (particularly on the frontside) according to known techniques.

Dyes useful as antihalation, filter, cross-over prevention (anti-crossover), anti-irradiation and/or acutance dyes include squaraine dyes described in U.S. Pat. No. 5,380,635 (Gomez et al.), U.S. Pat. No. 6,063,560 (Suzuki et al.), and EP 1 083 459 Al (Kimura), the indolenine dyes described in 35 EP 0 342 810 A (Leichter), and the cyanine dyes described in U.S. Ser. No. 10/011,892 (filed Dec. 5, 2001 by Hunt, Kong, Ramsden, and LaBelle). All of the above references are incorporated herein by reference.

It is also useful in the present invention to employ 40 compositions including acutance, filter, cross-over prevention (anti-crossover), anti-irradiation and/or antihalation dyes that will decolorize or bleach with heat during processing. Dyes and constructions employing these types of dyes are described in, for example, U.S. Pat. No. 5,135,842 45 (Kitchin et al.), U.S. Pat. No. 5,266,452 (Kitchin et al.), U.S. Pat. No. 5,314,795 (Helland et al.), U.S. Pat. No. 6,306,566, (Sakurada et al.), U.S. Published Application 2001-0001704 (Sakurada et al.), JP 2001-142175 (Hanyu et al.), and JP 2001-183770 (Hanye et al.). Also useful are bleaching 50 compositions described in JP 11-302550 (Fujiwara), JP 2001-109101 (Adachi), JP 2001-51371 (Yabuki et al.), JP 2001-22027 (Adachi), JP 2000-029168 (Noro), and U.S. Pat. No. 6,376,163 (Goswami, et al.). All of the above references are incorporated herein by reference.

Particularly useful heat-bleachable acutance, filter, crossover prevention (anti-crossover), anti-irradiation and/or antibalation compositions include a radiation absorbing compound used in combination with a hexaaryl-biimidazole (also known as a "HABI"). Such HABI compounds are well 60 known in the art, such as U.S. Pat. No. 4,196,002 (Levinson et al.), U.S. Pat. No. 5,652,091 (Perry et al.), and U.S. Pat. No. 5,672,562 (Perry et al.), all incorporated herein by reference. Examples of such heat-bleachable compositions are described for example in copending and commonly 65 assigned U.S. Ser. No. 09/875,772 (filed Jun. 6, 2001 by Goswami, Ramsden, Zielinski, Baird, Weinstein, Helber,

46

and Lynch) and U.S. Ser. No. 09/944,573 (filed Aug. 31, 2001 by Ramsden and Baird) both incorporated herein by reference.

Under practical conditions of use, the compositions are heated to provide bleaching at a temperature of at least 90° C. for at least 0.5 seconds. Preferably, bleaching is carried out at a temperature of from about 100° C. to about 200° C. for from about 5 to about 20 seconds. Most preferred bleaching is carried out within 20 seconds at a temperature of from about 110° C. to about 130° C.

Imaging/Development

The photothermographic materials of the present invention can be imaged using any suitable X-radiation imaging source. Suitable exposure means are well known and include medical, mammographic, dental, industrial X-ray units, and other X-radiation generating equipment known to one skilled in the art. Also suitable are light-emitting screencassette systems of X-radiation units.

When storage phosphors are incorporated within the photothermographic materials, the initial exposure to X-radiation is "stored" within the phosphor particles. When the material is then later exposed a second time to stimulating electromagnetic radiation (usually to visible light or infrared radiation), the "stored" energy is then released as an emission of visible or infrared radiation. The photothermographic materials may then be developed by heating. BaFBr is such a storage phosphor.

Thermal development conditions will vary, depending on the construction used but will typically involve heating the imagewise exposed material at a suitably elevated temperature. Thus, the latent image can be developed by heating the exposed material at a moderately elevated temperature of, for example, from about 50° C. to about 250° C. (preferably from about 80° C. to about 200° C. and more preferably from about 100° C. to about 200° C.) for a sufficient period of time, generally from about 1 to about 120 seconds. Heating can be accomplished using any suitable heating means such as a hot plate, a steam iron, a hot roller or a heating bath.

In some methods, the development is carried out in two steps.

Thermal development takes place at a higher temperature for a shorter time (for example at about 150° C. for up to 10 seconds), followed by thermal diffusion at a lower temperature (for example at about 80° C.) in the presence of a transfer solvent.

Imaging Assemblies

To further increase photospeed, the X-radiation sensitive photothermographic materials of this invention may be used in association with one or more phosphor intensifying screens and/or metal screens in what is known as "imaging assemblies." An intensifying screen absorbs X-radiation and emits longer wavelength electromagnetic radiation that the photosensitive silver halide more readily absorbs. Double-side coated X-radiation sensitive photothermographic materials are preferably used in combination with two intensifying screens, one screen in the "front" and one screen in the "back" of the material.

Such imaging assemblies are composed of a photother-mographic material as defined herein (particularly one sensitive to X-radiation or visible light) and one or more phosphor intensifying screens adjacent the front and/or back of the material. These screens are typically designed to absorb X-rays and to emit electromagnetic radiation having a wavelength greater than 300 nm.

There are a wide variety of phosphors known in the art that can be formulated into phosphor intensifying screens,

including but not limited to, the phosphors described in Research Disclosure, Vol. 184, Aug. 1979, Item 18431, Section IX, X-ray Screens/Phosphors, U.S. Pat. No. 2,303, 942 (Wynd et al.), U.S. Pat. No. 3,778,615 (Luckey), U.S. Pat. No. 4,032,471 (Luckey), U.S. Pat. No. 4,225,653 (Brixner et al.), U.S. Pat. No. 3,418,246 (Royce), U.S. Pat. No. 3,428,247 (Yocon), U.S. Pat. No. 3,725,704 (Buchanan et al.), U.S. Pat. No. 2,725,704 (Swindells), U.S. Pat. No. 3,617,743 (Rabatin), U.S. Pat. No. 3,974,389 (Ferri et al.), U.S. Pat. No. 3,591,516 (Rabatin), U.S. Pat. No. 3,607,770 (Rabatin), U.S. Pat. No. 3,666,676 (Rabatin), U.S. Pat. No. 3,795,814 (Rabatin), U.S. Pat. No. 4,405,691 (Yale), U.S. Pat. No. 4,311,487 (Luckey et al.), U.S. Pat. No. 4,387,141 (Patten), U.S. Pat. No. 5,021,327 (Bunch et al.), U.S. Pat. No. 4,865,944 (Roberts et al.), U.S. Pat. No. 4,994,355 (Dickerson et al.), U.S. Pat. No. 4,997,750 (Dickerson et al.), U.S. Pat. No. 5,064,729 (Zegarski), U.S. Pat. No. 5,108,881 (Dickerson et al.), U.S. Pat. No. 5,250,366 (Nakajima et al.), U.S. Pat. No. 5,871,892 (Dickerson et al.), EP 0 491 116 A (Benzo et al.), U.S. Pat. No. 4,988,880 (Bryan et al.), U.S. Pat. No. 4,988,881 (Bryan et al.), U.S. 20 Pat. No. 4,994,205 (Bryan et al.), U.S. Pat. No. 5,095,218 (Bryan et al.), U.S. Pat. No. 5,112,700 (Lambert et al.), U.S. Pat. No. 5,124,072 (Dole et al.), U.S. Pat. No. 5,336,893 (Smith et al.), U.S. Pat. No. 4,835,397 (Arakawa et al.), U.S. Pat. No. 5,381,015 (Dooms), U.S. Pat. No. 5,464,568 25 (Bringley et al.), U.S. Pat. No. 4,226,653 (Brixner), U.S. Pat. No. 5,064,729 (Zegarski), U.S. Pat. No. 5,250,366 (Nakajima et al.), and U.S. Pat. No. 5,626,957 (Benso et al.), U.S. Pat. No. 4,368,390 (Takahashi et al.), U.S. Pat. No. 5,227,253 (Takasu et al.), the disclosures of which are all incorporated herein by reference for their teaching of phosphors and formulation of phosphor intensifying screens.

Phosphor intensifying screens can take any convenient form providing they meet all of the usual requirements for use in radiographic imaging, as described for example in ³⁵ U.S. Pat. No. 5,021,327 (Bunch et al.), incorporated herein by reference. A variety of such screens are commercially available from several sources including by not limited to, LANEX®, X-SIGHT® and InSight® Skeletal screens all available from Eastman Kodak Company. The front and ⁴⁰ back screens can be appropriately chosen depending upon the type of emissions desired, the photicity desired, emulsion speeds, and % crossover. A metal (such as copper or lead) screen can also be included if desired.

Imaging assemblies can be prepared by arranging a suitable photothermographic material in association with one or more phosphor intensifying screens, and one or more metal screens in a suitable holder (often known as a cassette), and appropriately packaging them for transport and imaging uses.

Constructions and assemblies useful in industrial radiography include, for example, U.S. Pat. No. 4,480,024 (Lyons et al), U.S. Pat. No. 5,900,357 (Feumi-Jantou et al.), and EP 1 350 883 (Pesce et al.).

The following examples are provided to illustrate the practice of the present invention and the invention is not meant to be limited thereby.

MATERIALS AND METHODS FOR THE EXAMPLES

All materials used in the following examples are readily available from standard commercial sources, such as Aldrich Chemical Co. (Milwaukee Wis.) unless otherwise specified. All percentages are by weight unless otherwise indicated.

Phosphors were obtained from Nichia America Corp. 65 (Mountville, Pa.). P-1 is a Gd₂O₂S,Tb green-emitting phosphor. P-2 is a Y(Sr)TaO₄ UV-emitting phosphor.

48

BZT is benzotriazole.

NaBZT is a 0.7M solution of the sodium salt of benzot-riazole. It is prepared from NaOH and BZT.

"PVP" is poly(vinyl pyrrolidone), average MW.=55,000. Determination of Grain Size

A sample of the emulsion was examined by scanning and transmission electron microscopy, and the projected areas of resulting grain images were measured to determine the mean area. The weighting was such that the diameters reported are the equivalent circular diameters of the mean areas for those grains which have an aspect ratio greater than five. Thickness was characterized from the spectral reflectivity of the grains using equations described in *Optics*, John Wiley & Sons, 1970, pp. 582–585, and the refractive dispersion of gelatin and silver bromide given in T. H. James, *The Theory of the Photographic Process*, Fourth Edition, Eastman Kodak Company, Rochester, N.Y., 1977, p.579.

Preparation of Ultra-thin Tabular Grain Photosensitive Silver Halide Emulsions Useful in the Invention

Emulsion A: A vessel equipped with a stirrer was charged with 6 liters of water containing 2.95 g of lime-processed bone gelatin, 5.14 g of sodium bromide, 65.6 mg of KI, a conventional antifoaming agent, and 1.06 g of 0.1M sulfuric acid held at 24° C. During nucleation, which was accomplished by balanced simultaneous 4-second addition of AgNO₃ and sodium bromide solutions (both at 2.5M) in sufficient quantity to form 0.03348 moles of silver iodobromide, the pBr and pH values remained approximately at the values initially set in the reaction mixture. Following nucleation, 24.5 g of a 4%-NaOCl aqueous solution was added, then 68.2 g of a 3.42 molar solution of sodium chloride was added. After a temperature increase to 45° C. over 12.5 minutes, there was a 3 minute hold, followed by a cool down to 35° C. over 9 minutes.

After 3 minutes at this temperature, 100 g of oxidized methionine lime-processed bone gelatin dissolved in 1.5 liter of water at 40° C. were added to the vessel. The excess bromide ion concentration was allowed to rise by addition of 62.53 g of a 3.0 molar sodium bromide solution added over 1 minute at a constant rate.

Thirty four minutes after nucleation, the growth stage was begun during which 1.49 molar (later 3.0 molar) AgNO₃, 1.49 molar (later 3.0 molar) sodium bromide, and a 0.45 molar suspension of silver iodide (Lippmann emulsion) were added in proportions to maintain a nominal uniform iodide level of (i) 1.5 mole % for the first 75% of the grain growth, (ii) 6 mole % for the 75%–87.25% portion of grain growth, and (iii) pure AgBr for the last portion of grain growth. The flow rates were 6.6 ml/min (initially of the 1.49) 50 molar reactants) and ramped in several accelerated flow segments up to 13.4 ml/min over 15 minutes, to 18.1 ml/min over the next 15 minutes, and then to 26.9 ml/min in the next 15 minutes. After a switch to 3.0 molar reactants, the flow rates were 13.4 ml/min ramped in several segments up to a rate of 64.0 ml/min. During this time the pBr was held in control and 0.01 mg of dipotassium hexachloroiridate (K₂IrCl₆) per mole of AgX was added. For the 6 mole % iodide addition the flow rate was held at a constant 44.5 ml/min and for the final pure bromide growth the pBr was raised to 1.74 and the flow rate held constant at 71.0 ml/min.

A total of 12.3 moles of silver iodobromide (1.87 mole % iodide) were formed. The resulting emulsion was washed by ultra-filtration and pH and pBr were adjusted to storage values of 6 and 2.5, respectively. The emulsion was also examined by Scanning Electron Microscopy to determine grain morphology. Tabular grains accounted for greater than 99% of total grain projected area and the mean ECD of the

grains was $0.848 \mu m$. The mean tabular thickness was 0.053 μ m. The aspect ratio was 16:1

Emulsion B: Emulsion B was prepared by a procedure similar to that for Emulsion A except that the grain size was altered by modifying the amount of sodium bromide added during the pBr shift step (just before the main growth steps) and by modifying the amount of silver halide precipitated during the nucleation step in a manner described, for example, in U.S. Pat. No. 5,494,789. The resulting emulsion contained 1.87 mole % iodide and had a grain size of 1.054 μ m×0.053 μ m. The aspect ratio was 19.9:1.

Emulsion B was evaluated after chemical sensitization at 60° C. for 30 minutes using a combination of a gold sensitizer (potassium tetrachloroaurate—KAuCl₄) and compound SS-1, a sulfur sensitizer described in U.S. Pat. No. 15 6,296,998 (Eikenberry et al.). Levels of up to 0.425 mmol of blue sensitizing dye SSD-B1 per mole of AgX were added at 50° C. before the chemical sensitizers.

$$(C_2H_5)_4N^+$$
- $O_3S(CH_2)_2CH_2$ $CH_2(CH_2)_2SO_3$ $CH_2(CH_2)_2SO$

Emulsion C: A vessel equipped with a stirrer was charged with 9 liters of water containing 14.1 g of lime-processed bone gelatin, 7.06 g NaBr, 4.96 g ammonium sulfate, an antifoamant, and 9.85 g 4.0M sulfuric acid plus sufficient 0.1M sulfuric acid to adjust pH to 2.5 (at 40° C.). The 35 mixture was held at 35° C. During nucleation, which followed the main acid addition by 8.5 minutes, and which was accomplished by balanced simultaneous 6 second addition of AgNO₃ and Na(Br, I) (at 1.5 mole % Iodide) solutions, both at 2.5M, in sufficient quantity to form 0.0339 moles of 40 silver iodobromide. pBr and pH remained approximately at the values initially set in the reactor solution. Following nucleation, the reactor gelatin was quickly oxidized by addition of 471 mg of OXONE (2KHSO₅.KHSO₄.K₂SO₄, purchased from Aldrich) in 90 ml H₂O and the mixture held 45 for ten minutes. Next, 61.0 g of a 2.5M aqueous solution of sodium hydroxide was added (pH to 10).

After 14 minutes at this pH, 100 g of oxidized methionine, deionized, lime-processed bone gelatin dissolved in 1.5 liter of water at 40° C. were added to the reactor and the pH was 50 dropped to 5.8 with 37.6 g of 1.0M sulfuric acid. Next the temperature was raised from 35° C. to 45° C. in 6 minutes. The excess Br concentration is then allowed to rise to a pBr of 1.74 by addition of a 4.0M NaBr solution over about 1.5 minutes at a constant rate of 25 ml/min. This pBr value was 55 maintained throughout the remainder of the precipitation by double jet addition of silver nitrate and salt solutions.

Thirty eight minutes after nucleation the growth stage was begun during which 2.5M (later 3.8M) AgNO₃, 4.0M NaBr, and a 0.25M suspension of AgI (Lippmann) were added in 60 proportions to maintain a uniform iodide level of 3.16 mole % for the first 95% of the grain growth, and (ii) pure AgBr for the last 5% of the growth. The silver flow rate was 7.6 ml/min (initially of the 2.5M AgNO₃ reactant) and ramped in several accelerated flow segments up to 15.2 ml/min over 65 50 minutes. After a switch to 3.8M AgNO₃ reactant, the silver flow rate was 10.0 ml/min ramped in several segments

50

up to a rate of 40.0 ml/min over 38 minutes. During this time (at a point of 70% of total silver addition) 0.01 mg/Ag mole of dipotassium iridium hexachloride dopant was added. The final 5% of growth involving pure AgBr was carried out with 3.8M AgNO₃ added at a constant rate of 30 cc/minute. A total of 9.0 moles of silver iodobromide (3.0% bulk-I) were formed. The resulting emulsion was washed by ultrafiltration and pH and pBr were adjusted to storage values of 6 and 2.5, respectively. The resulting emulsion was examined by Scanning Electron Microscopy. Tabular grains accounted for greater than 99% of total grain projective area, the mean ECD of the grains was $1.117 \mu m$. The mean tabular thickness was $0.056 \mu m$. The aspect ratio was 19.9:1.

Emulsion C was evaluated after chemical sensitization at 60° C. for 30 minutes using a combination of a gold sensitizer (potassium tetrachloroaurate—KAuCl₄) and compound SS-1, a sulfur sensitizer described in U.S. Pat. No. 6,296,998 (Eikenberry et al.). Levels of up to 0.567 mmol of blue sensitizing dye SSD-B1 per mole of AgX were added SSD-B1 20 at 50° C. before the chemical sensitizers.

Preparation of Silver Benzotriazole Dispersion

A stirred reaction kettle was charged with lime processed gelatin (85 g), phthalated gelatin (25 g), and deionized water (2000 g). Solution B containing benzotriazole (185 g), 25 deionized water (1405 g), and 2.5 molar sodium hydroxide (680 g) was prepared. The mixture in the reaction kettle was adjusted to a pAg of 7.25 and a pH of 8.0 by addition of Solution B, and 2.5 M sodium hydroxide solution as needed, and maintaining the temperature at 36° C. Solution C 30 containing silver nitrate (228.5 g) and deionized water (1222 g) was added to the kettle at the accelerated flow rate defined by the formula Flow Rate=16(1+0.002t²) ml/min, and the pAg was maintained at 7.25 by the simultaneous addition of Solution B. This process was terminated when Solution C was exhausted. At this point, a solution of phthalated gelatin (80 g) and deionized water (700 g) at 40° C. was added to the kettle. The resulting mixture was stirred and the pH was adjusted to 2.5 with 2M sulfuric acid to coagulate the silver salt emulsion. The coagulum was washed twice with 5 liters of deionized water, and re-dispersed by adjusting pH to 6.0 and pAg to 7.0 with 2.5 M sodium hydroxide solution and Solution B. The resulting silver salt dispersion contained fine particles of silver benzotriazole salt.

Preparation of Mercaptotriazole Dispersion

A mixture containing 4.0 g of mercaptotriazole compound T-1, 16 g of 10% poly(vinyl pyrrolidone) solution, and 18 g of deionized water were ball milled with a Brinkmann Instrument S100 grinder for three hours. To the resulting suspension was added 15 g of 30% lime processed gelatin solution. The mixture was heated to 50° C. on a water bath to give a fine dispersion of mercaptotriazole particles in gelatin solution.

Examples 1 to 6

Inventive aqueous photothermographic materials were prepared by mixing the following compounds in order as follows:

Silver benzotriazole (BZT) dispersion 8.08 g (4.68 mmol) Lime-processed gelatin 1.0 g (35% in water) Succinimide 1.0 g (10% in water)3-Methylbezothiazolium iodine 0.5 g (5% in water) NaBZT 0.4 g (0.7M)0.5 g (20% in water) Dimethylurea Silver Halide Emulsion B 1.0 g (1.18 mmol)

-continued

To this aqueous photothermographic formulation was added 5.8 g, 7.4 g or 9.0 g of phosphor particles P-1 or P-2 and mixed for 1 minute. Control formulations were prepared without phosphor particles.

The aqueous formulations were coated under safelight conditions onto a gelatin primed 178 μ m blue-tinted poly (ethylene terephthalate) support using a knife coater. Samples were dried at 51.7° C. for 5.6 minutes. The silver 15 coating weights of the samples were approximately 2.2 g/m². The phosphor-containing formulations were coated at approximate phosphor coating weights of 53, 50, 41, 37, 33, and 27 g/m² (as shown in TABLE I below). A control sample, Control A, was prepared in an identical manner but 20 containing no phosphor.

TABLE I

Example	Phosphor	Average Phosphor Size (μ m)	Amount of Phosphor (g/m²)	Moles of Phosphor per Mole of Silver
Control A	None		0	0
Example 1	P-2	7	53	3.7
Example 2	P-2	7	37	3.0
Example 3	P-2	7	33	2.4
Example 4	P-1	4	50	2.9
Example 5	P-1	4	41	2.4
Example 6	P-1	4	27	1.8

Imaging exposures were made using a 70 kVp, single-phase X-ray unit, filtered with 2.5 mm sheet of aluminum. The films were placed approximately 1.5 meters from the imaging source, and various "phantoms" were placed on the films. A resolution test target was also placed on the films. These "phantoms" are made of bone, plastic, and metal, and are very commonly used to evaluate imaging systems in radiography. The films were then exposed to a density of 1.4 above the base density of the film. The amount of radiation required to achieve this result was recorded for each film.

The imaged films were then developed by heating at 150° C. for 15 seconds on a heated drum processor. Visual assessments were made of the image resolution, in line pairs per millimeter.

Samples were compared to the speed (set at "100") of commercially available KODAK ULTRASPEED X-ray Film 4502. A control photothermographic material (Control A), coated without incorporating phosphor gave no image. A second sample of Control A exposed while in contact with commercially available DuPont Ultra Vision Rapid Screen that contained YTaO₄ phosphor in a "back screen" configuration, provided an image and allowed determination of speed.

The data, shown below in TABLE II, demonstrate that 60 incorporation of phosphors into aqueous-based photothermographic emulsions provide materials having speeds approaching that of commercially available materials requiring the use of external screens. Speed increased as coating weights of the incorporated phosphor were increased. Resolution was also comparable to that of commercially available KODAK ULTRASPEED X-ray Film 4502.

TABLE II

5	Example	External Screen	Relative Speed	Resolution line pairs/mm
	KODAK ULTRASPEED	No	100	>20
	X-ray Film 4502 Control A	No	Negligible	
	Control A	Yes	89	8
	Example 1	No	74	14
0		No	50	14
	Example 3	No	43	16
	Example 4	No	36	16
	Example 5	No	31	16
	Example 6	No	24	18

Examples 7 to 9

Samples of inventive aqueous photothermographic materials were prepared by mixing the following compounds in order as follows:

Silver benzotriazole (BZT) dispersion	8.32 g (4.68 mmol)
Lime-processed gelatin	1.0 g (35% in water)
Succinimide	1.0 g (10% in water)
3-Methylbezothiazolium iodine	0.5 g (5% in water)
NaBZT	0.4 g (0.7M)
Dimethylurea	0.5 g (20% in water)
Silver Halide Emulsion C	1.1 g (1.44 mmol)
Mercaptotriazole Dispersion	0.3 g
Ascorbic Acid	2.1 g (20% in water)

To these aqueous photothermographic formulations were added 9.0 g, 10.6 g, or 12.2 g of phosphor particles P-2 and mixed for 1 minute. A control formulation, Control B, was prepared without phosphor particles.

The photothermographic emulsion formulations were coated under safelight conditions onto a gelatin-primed 7 mil (178 μ m) blue-tinted poly(ethylene terephthalate) support using a knife coater. Samples were dried at 51.7° C. for 5.6 minutes. The silver coating weights were approximately 2.2 g/m². Various phosphor-containing coating weights were used as shown. The results, shown below in TABLE III, demonstrate that incorporation of phosphor particles into aqueous-based photothermographic materials increases photospeed.

TABLE III

Example	Phosphor	Average Phosphor Size (μ m)	Amount of Phosphor (g/m ²)	Moles of Phosphor per Mole of silver
Control B Example 7 Example 8 Example 9	None P-2 P-2 P-2		0 42 57 68	0 3.5 4.1 4.7

Imaging exposures were made using a 70 kVp, single-phase X-ray unit, filtered with 2.5 mm sheet of aluminum. The films were placed approximately 1.5 meters from the imaging source, and various "phantoms" were placed on the films. These "phantoms" are made of bone, plastic, and metal, and are very commonly used to evaluate imaging systems in radiography. A resolution test target was also placed on the films. The films were then exposed to a density of 1.4 above the base density of the film. The amount of radiation required to achieve this result was recorded for each film.

53

The imaged films were then developed by heating at 150° C. for 15 seconds on a heated drum processor. Visual assessments were made of the image resolution, in line pairs per millimeter.

The data, shown below in TABLE IV, demonstrate the increased speeds for aqueous photothermographic materials as coating weights of the incorporated phosphor were increased as compared to the speed (set at "100") of commercially available KODAK ULTRASPEED X-ray Film 4502. A control material (Control B), coated without incorporating phosphor gave no image. Speed and images could be determined when the Control B sample was imaged while in contact with commercially available DuPont Ultra Vision Rapid Screen that contained YTaO₄ phosphor in a "back screen" configuration. Without the addition of external 15 screens, speed was superior to the commercially available film while resolution was equal to the commercially available film.

TABLE IV

Material	External Screen	Relative Speed	Resolution line pairs/mm
KODAK ULTRASPEED X-ray Film 4502	No	100	>20
Control B	No	Negligible	
Control B	Yes	76	8
Example 7	No	100	16
Example 8	No	140	16
Example 9	No	109	16

The invention has been described in detail with particular reference to certain preferred embodiments thereof, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.

We claim:

- 1. An X-radiation sensitive photothermographic material comprising a support having on at least one side thereof, one or more imaging layers each comprising a hydrophilic binder, and in reactive association:
 - a. chemically sensitized photosensitive silver halide grains, at least 70% of the total photosensitive silver halide grain projected area being provided by tabular silver halide grains comprising at least 70 mol % bromide, based on total silver halide, with the remainder of the halide being iodide or chloride, said tabular grains having an average thickness of at least 0.02 μ m and up to and including 0.10 μ m, an equivalent circular diameter of at least 0.5 μ m and up to and including 8 μ m, and an aspect ratio of at least 5:1,
 - b. a non-photosensitive source of reducible silver ions,
 - c. a reducing agent composition for said reducible silver ions, and
 - d. a phosphor that is sensitive to X-radiation and is present in an amount of at least 0.1 mole per mole of total 55 silver.
- 2. An imaging assembly comprising the photothermographic material as claimed in claim 1 that is arranged in association with one or more phosphor intensifying screens.
- 3. An X-radiation sensitive photothermographic material 60 comprising a support having on at least one side thereof, one or more imaging layers each comprising a hydrophilic binder, and in reactive association:
 - a. chemically sensitized photosensitive silver halide grains, at least 70% of the total photosensitive silver 65 halide grain projected area being provided by tabular silver halide grains comprising at least 70 mol %

54

bromide, based on total silver halide, with the remainder of the halide being iodide or chloride, said tabular grains having an average thickness of at least $0.02 \mu m$ and up to and including $0.10 \mu m$, an equivalent circular diameter of at least $0.5 \mu m$ and up to and including 8 μm , and an aspect ratio of at least 5:1,

- b. a non-photosensitive source of reducible silver ions,
- c. a reducing agent composition for said reducible silver ions,
- d. a phosphor that is sensitive to X-radiation and is present in an amount of at least 0.1 mole per mole of total silver, and
- e. a toner.
- 4. The photothermographic material of claim 3 wherein said non-photosensitive source of reducible silver ions is a silver salt of a compound containing an imino group.
- 5. The photothermographic material of claim 3 wherein said non-photosensitive source of reducible silver ions is a silver salt of benzotriazole or a substituted derivatives thereof, or mixtures of such silver salts.
 - 6. The photothermographic material of claim 5 wherein said non-photosensitive source of reducible silver ions includes a silver salt of benzotriazole.
- 7. The photothermographic material of claim 3 wherein said non-photosensitive source of reducible silver ions is a silver fatty acid carboxylate having 10 to 30 carbon atoms in the fatty acid or a mixture of said silver carboxylates.
 - 8. The photothermographic material of claim 7 wherein at least one of said silver carboxylates is silver behenate.
 - 9. The photothermographic material of claim 3 wherein said hydrophilic binder is gelatin, a gelatin derivative, a cellulosic material, or poly(vinyl alcohol).
- 10. The photothermographic material of claim 3 wherein at least 85% of the silver halide grain projected area is projected by said tabular silver halide grains that comprise at least 85 mol % bromide, based on total silver halide, with the remainder of the halide being iodide or chloride, said tabular grains having an average thickness of at least 0.03 μ m and up to and including 0.08 μ m, an equivalent circular diameter of at least 0.75 μ m and up to and including 6 μ m, and an aspect ratio of at least 10:1.
 - 11. The photothermographic material of claim 3 wherein said tabular silver halide grains has been chemically sensitized with a sulfur-containing chemical sensitizing compound, a tellurium-containing chemical sensitizing compound, a selenium-containing chemical sensitizing compound, a gold-containing chemical sensitizing compound, or mixtures of any of these chemical sensitizing agents.
 - 12. The photothermographic material of claim 3 comprising one or more of the same or different imaging layers on both sides of said support.
 - 13. The photothermographic material of claim 12 further comprising a protective layer over said imaging layers on both sides of said support.
 - 14. The photothermographic material of claim 3 wherein said phosphor is present in said material in an amount of from about 0.5 to about 20 mole per mole of total silver and the total silver present in said material is at least 0.002 mol/m².
 - 15. The photothermographic material of claim 3 wherein said phosphor is calcium tungstate (CaWO₄), activated or unactivated lithium stannate, a niobium and/or rare earth activated or unactivated yttrium, lutetium, or gadolinium tantalates, a rare earth-activated or unactivated middle chalcogen phosphor, or a terbium-activated or unactivated lanthanum and lutetium middle chalcogen phosphor.

55

16. The photothermographic material of claim 15 wherein said phosphor is a rare earth oxychalcogenide and halide phosphor represented by the following formula (1):

$$\mathbf{M'}_{(w-r)}\mathbf{M''}_{r}\mathbf{O}_{w}\mathbf{X'} \tag{1} \quad 5$$

wherein M' is at least one of the metals yttrium (Y), lanthanum (La), gadolinium (Gd), or lutetium (Lm), M" is at least one of the rare earth metals dysprosium (Dy), erbium (Er), europium (Eu), holmium (Ho), neodymium (Nd), 10 praseodymium (Pr), samarium (Sm), tantalum (Ta), terbium (Tb), thulium (Tm), or ytterbium (Yb), X' is a middle chalcogen (S, Se, or Te) or halogen, r is 0.002 to 0.2, and w is 1 when X' is halogen or 2 when X' is a middle chalcogen.

- 17. The photothermographic material of claim 15 wherein said phosphor is YTaO₄, YTaO₄:Nb, Y(Sr)TaO₄, Y(Sr) TaO₄:Nb, or BaFBr:Eu.
- 18. The photothermographic material of claim 15 wherein said phosphor is the product of firing starting materials comprising optional oxide and a combination of species 20 characterized by the following formula (2):

$$MFX_{(1-z)}I_zuM^aX^a:yA:eQ:tD$$
 (2)

wherein "M" is magnesium (Mg), calcium (Ca), strontium (Sr), or barium (Ba), "F" is fluoride, "X" is chloride (Cl) or 25 bromide (Br), "I" is iodide, Ma is sodium (Na), potassium (K), rubidium (Rb), or cesium (Cs), X^a is fluoride (F), chloride (Cl), bromide (Br), or iodide (I), "A" is europium (Eu), cerium (Ce), samarium (Sm), or terbium (Th), "Q" is BeO, MgO, CaO, SrO, BaO, ZnO, Al₂O₃, La₂O₃, In₂O₃, 30 SiO₂, TiO₂, ZrO₂, GeO₂, SnO₂, Nb₂O₅, Ta₂O₅, or ThO₂, "D" is vanadium (V), chromium (Cr), manganese (Mn), iron (Fe), cobalt (Co), or nickel (Ni), "z" is 0 to 1, "u" is from 0 to 1, "y" is from 1×10^{-4} to 0.1, "e" is from 0 to 1, and "t" is from 0 to 0.01.

19. The photothermographic material of claim 15 wherein said phosphor is a divalent alkaline earth metal fluorohalide phosphors characterized by the following formula (3):

$$[Ba_{(1-a-b-c)}Mg_aCa_bSr_c]FX_{(1-z)}I_zrM^aX^a:yA$$
(3)

wherein "M" is magnesium (Mg), calcium (Ca), strontium (Sr), or barium (Ba), "F" is fluoride, "X" is chloride (Cl) or bromide (Br), "I" is iodide, Ma is sodium (Na), potassium (K), rubidium (Rb), or cesium (Cs), X^a is fluoride (F), 45 chloride (Cl), bromide (Br), or iodide (I), "A" is europium (Eu), cerium (Ce), samarium (Sm), or terbium (Th), "z" is 0 to 1, "y" is from 1×10^{-4} to 0.1, the sum of a, b and c is from 0 to 4, and r is from 10^{-6} to 0.1.

- 20. The photothermographic material of claim 15 wherein 50 said phosphor is SrS:Ce,Sm, SrS:Eu,Sm, ThO₂:Er, La₂O₂S:Eu,Sm, or ZnS:Cu,Pb.
- 21. The photothermographic material of claim 3 wherein said photosensitive silver halide and phosphor are in the same imaging layer.
- 22. The photothermographic material of claim 3 wherein said phosphor is present at a dry coating weight of at least 5 g/m².

56

- 23. The photothermographic material of claim 3 wherein said phosphor is a storage phosphor.
- 24. The photothermographic material of claim 3 wherein said toner is a triazole compound.
- 25. The photothermographic material of claim 24 wherein said triazole compound is a mercaptotriazole.
- 26. A black-and-white photothermographic material comprising a support having thereon one or more hydrophilic layers each layer comprising a hydrophilic binder, and said photothermographic material further comprising on both sides of the support, one or more imaging layers comprising, in reactive association:
 - a. a non-photosensitive source of reducible silver ions,
 - b. a reducing agent composition for said reducible silver ions,
 - c. chemically sensitized photosensitive silver halide grains, at least 70% of the total photosensitive silver halide grain projected area being provided by tabular silver halide grains comprising at least 70 mol % bromide, based on total silver halide, and the remainder of the halide being iodide or chloride, said tabular grains having an average thickness of at least 0.02 μ m and up to and including $0.10 \, \mu \text{m}$, an equivalent circular diameter of at least 0.5 μ m and up to and including 8 μ m, and an aspect ratio of at least 5:1, and
 - d. a phosphor that is sensitive to X-radiation and is present in an amount of at least 0.1 mole per mole of total silver,

said imaging layers on both sides of said support being the same or different.

- 27. A method of forming a visible image comprising:
- A) imagewise exposing the photothermographic material as claimed in claim 1 to electromagnetic radiation to form a latent image, and
- B) simultaneously or sequentially, heating said exposed photothermographic material to develop said latent image into a visible image.
- 28. The method of claim 27 wherein said imagewise exposing is carried out using visible or X-radiation.
- 29. The method of claim 27 wherein said photothermographic material is arranged in association with one or more phosphor intensifying screens.
 - **30**. A method for forming a visible image comprising:
 - A) imagewise exposing the photothermographic material of claim 3 to visible or X-radiation to form a latent image, and
 - B) simultaneously or sequentially, heating said exposed photothermographic material to develop said latent image into a visible image.
- 31. The method of claim 30 wherein said photothermographic material comprises a storage phosphor, and after step A, said photothermographic material is exposed to electromagnetic radiation to stimulate said storage phosphor to an emission of visible or infrared radiation.