



US006589070B1

(12) **United States Patent**
Lias et al.

(10) **Patent No.:** **US 6,589,070 B1**
(45) **Date of Patent:** **Jul. 8, 2003**

(54) **CIRCUIT BREAKER JUMPER ASSEMBLY WITH PHASE ISOLATION**

(75) Inventors: **Edward Ethber Lias**, Aliquippa, PA (US); **Michael Jerome Whipple**, Rochester, PA (US)

(73) Assignee: **Eaton Corporation**, Cleveland, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/067,193**

(22) Filed: **Feb. 4, 2002**

(51) **Int. Cl.**⁷ **H01R 31/08**

(52) **U.S. Cl.** **439/507; 439/715; 439/724**

(58) **Field of Search** 439/507, 715, 439/724, 514, 709, 722, 212, 213, 710, 711, 712, 713, 714, 717, 721, 716, 718, 719, 720, 47, 48, 44; 361/637, 638, 639, 640, 822, 823, 824

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,909,097	A	9/1975	Roth et al.	
3,941,443	A	3/1976	Reimer	
4,603,376	A	* 7/1986	Maier	361/426
4,785,378	A	11/1988	Hinckley et al.	
5,064,384	A	11/1991	Weaver	
5,403,210	A	* 4/1995	Hasegawa	439/723
6,036,554	A	3/2000	Koeda et al.	

OTHER PUBLICATIONS

OEM, "Commercial and Industrial Circuit Breakers for OEM Applications," pp. 1-16, Square D Groupe Schneider (1998) USA.

* cited by examiner


Primary Examiner—Ross Gushi

(74) *Attorney, Agent, or Firm*—Martin J. Moran

(57) **ABSTRACT**

A jumper assembly that includes a housing assembly and at least two bus assemblies. The housing assembly has a planar member and a plurality of upper and lower side walls extending generally perpendicular from opposite sides of the planar member. The housing assembly planar member has an upper side and a lower side with one or more openings passing therethrough. The at least two or more bus assemblies each have a planar bus member and one or more collar assemblies coupled to each planar bus members. The upper side walls form two or more separate upper raceways. The lower side walls form two or more lower raceways. The bus planar members are disposed in the lower raceways. The collars disposed in the upper raceways and coupled to the bus planar members through the housing assembly planar member openings. Thus, a first power line may pass through a first upper raceway to be coupled to a first collar assembly attached to a first bus assembly; and a second power line may pass through a second upper raceway to be coupled to a second collar assembly attached to a second bus assembly. Therefore the first and second power lines are isolated from each other.

3 Claims, 33 Drawing Sheets






FIG. 1
PRIOR ART




FIG. 4




FIG. 5




FIG. 6







FIG. 7E



166 FIG. 7C



187 185 FIG. 7B




FIG. 7D





FIG. 7F






FIG. 8A






FIG. 8E






FIG. 8F





FIG. 8D






FIG. 9A




FIG. 9B




FIG. 9C






FIG. 9D






FIG. 9G




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18




FIG. 19

CIRCUIT BREAKER JUMPER ASSEMBLY WITH PHASE ISOLATION

CROSS REFERENCE TO RELATED APPLICATION

This application is related to the applications CIRCUIT BREAKER JUMPER ASSEMBLY WITH SNAP-FIT BUS MOUNTING Ser. No. 10/066,896, CIRCUIT BREAKER JUMPER ASSEMBLY WITH COVER ASSEMBLY ACCESS KNOCKOUTS Ser. No. 10/067,022, CIRCUIT BREAKER JUMPER ASSEMBLY WITH A SNAP-FIT COVER ASSEMBLY Ser. No. 10/066,924, CIRCUIT BREAKER JUMPER ASSEMBLY HAVING BUSSES IN A SINGLE PLANE Ser. No. 10/066,878, CIRCUIT BREAKER JUMPER ASSEMBLY HAVING A MODULAR DESIGN STRUCTURED FOR SINGLE AND THREE PHASE OPERATION Ser. No. 10/066,919, and MULTI-UNIT CIRCUIT BREAKER JUMPER ASSEMBLY Ser. No. 10/067,066.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a jumper assembly used in conjunction with two circuit breakers, more specifically to a jumper assembly where the power lines and bus assemblies having different phases are isolated from each other.

2. Background Information

A jumper assembly is a device for dividing a current from a power line so that the current may be directed to two or more circuit breakers. The jumper assembly includes a non-conductive housing and two conductive buses. The current is divided by coupling the power line to a single input point, typically a collar assembly, on a bus having two or more output terminals. The output terminals are then coupled to two different circuits, each of which has its own circuit breaker. The circuit breakers on the different circuits typically have different ratings. At typical jumper assembly is disclosed in U.S. Pat. No. 5,064,384.

As shown in FIG. 1, which is the same as FIG. 9 in the U.S. Pat. No. 5,064,384, the prior art jumper included a first bus bar, a second bus bar and a non-conductive housing. Each bus bar had a collar that is structured to be coupled to a power line. Each bus bar has multiple output terminals. The bus bars are not isolated from each other. That is, as shown on FIG. 6 of the U.S. Pat. No. 5,064,384, both bus bars are exposed to the interior of the housing. When power lines are coupled to the bus bars as shown on FIG. 9 of the U.S. Pat. No. 5,064,384, great care must be taken to ensure that the insulation on the power line coupled to the upper bus bar is intact as this power line lies directly over top of the lower bus bar. It would be better to have a jumper assembly where the bus assemblies are isolated from each other to reduce the risk of creating a short between a power line and a non-associated bus.

There is, therefore, a need for a jumper assembly having separate raceways for each power line.

There is a further need for a assembly having separate raceways for each bus assembly.

SUMMARY OF THE INVENTION

These needs, and others, are satisfied by the invention which provides a jumper assembly that includes a housing assembly and at least to bus assemblies. The housing assembly has a planar member and a plurality of upper and lower side walls extending generally perpendicular from opposite

sides of the planar member. The housing assembly planar member has an upper side and a lower side with one or more openings passing therethrough. The at least two or more bus assemblies each have a planar bus member and one or more collar assemblies coupled to each planar bus members. The upper side walls form two or more separate upper raceways. The lower side walls form two or more lower raceways. The bus planar members are disposed in the lower raceways. The collars disposed in the upper raceways and coupled to the bus planar members through the housing assembly planar member openings. Thus, a first power line may pass through a first upper raceway to be coupled to a first collar assembly attached to a first bus assembly; and a second power line may pass through a second upper raceway to be coupled to a second collar assembly attached to a second bus assembly. Therefore the first and second power lines are isolated from each other. Additionally, the lower raceways are separate from each other, thus, the bus assemblies are also isolated from each other.

BRIEF DESCRIPTION OF THE DRAWINGS

A full understanding of the invention can be gained from the following description of the preferred embodiments when read in conjunction with the accompanying drawings in which:

FIG. 1 is an isometric view of a six-terminal prior art jumper assembly.

FIG. 2 is an isometric view of the modular jumper assembly.

FIG. 3 is a top plan view of the modular jumper assembly.

FIG. 4 is a bottom plan view of the modular jumper assembly.

FIG. 5 is a front elevational view of the modular jumper assembly.

FIG. 6 is an exploded top view of the modular jumper assembly showing three modules.

FIG. 7A is a top view of the first size module. FIG. 7B is a bottom view of the first size module. FIG. 7C is a front view of the first size module. FIG. 7D is a left side view of the first size module. FIG. 7E is a back side view of the first size module. FIG. 7F is a right side view of the first size module. FIG. 7G is an exploded isometric view of the first size module.

FIG. 8A is a top view of the second size module. FIG. 8B is a bottom view of the second size module. FIG. 8C is a front view of the second size module. FIG. 8D is a left side view of the second size module. FIG. 8E is a back side view of the second size module. FIG. 8F is a right side view of the second size module. FIG. 8G is an exploded isometric view of the second size module.

FIG. 9A is a top view of the third sized module. FIG. 9B is a bottom view of the third sized module. FIG. 9C is a front view of the third sized module. FIG. 9D is a left side view of the third sized module. FIG. 9E is a back side view of the third sized module. FIG. 9F is a right side view of the third sized module. FIG. 9G is an exploded isometric view of the third sized module.

FIG. 10 is a detail view of a bus assembly clip.

FIG. 11 is a detail view of a bus assembly mounting boss.

FIG. 12 is an isometric view of the tongue-and-groove connector.

FIG. 13 is an isometric view of the first sized module cover assembly.

FIG. 14A is an isometric view of the back side of the second sized module cover assembly.

FIG. 14B is an isometric view of the front side of the second sized module cover assembly.

FIG. 15 is an isometric view of the third sized module cover assembly.

FIG. 16A is a top view of the fourth sized module. FIG. 16B is a bottom view of the fourth sized module. FIG. 14C is an exploded isometric view of the fourth sized module.

FIG. 17A is a top view of the full sized module. FIG. 17B is a bottom view of the full sized module. FIG. 17C is an exploded isometric view of the full sized module.

FIG. 18 is a top view of an alternate configuration of the jumper assembly.

FIG. 19 is a top view of linked jumper assemblies.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in FIGS. 2–6, a modular jumper assembly 100 includes one or more jumper modules, a first sized module 102, (FIGS. 7A–7G) a second sized module 104 (FIGS. 8A–8G), and a third sized module 106 (FIGS. 9A–9G) which are coupled together in a nested configuration. As will be detailed below, each module 102, 104, 106 includes a housing assembly 130, 330, 500 and a bus assembly 180, 440, 640. The combined module housing assemblies 130, 330, 500, when joined as described below, form the jumper assembly. Each bus assembly 180, 440, 640 includes two terminal ends 110, 112 that extend beyond the housing assemblies 130, 330, 500. All terminal ends 110, 112 extend from one side of the modular jumper assembly 100. As used herein, the side of the modular jumper assembly 100 or the modules 102, 104, 106 from which the terminal ends 110, 112 extend is the “front side”. As used herein, the side of the modular jumper assembly 100 or the modules 102, 104, 106 opposite the front side is the “back side.” Accordingly, as viewed from the front side, the side of the modular jumper assembly 100 or the modules 102, 104, 106 to the left is the “left side” and the side to the right is the “right side.” Additionally, as used herein, the bus assemblies will be said to extend in a generally horizontal direction. Accordingly, a plane perpendicular to the horizontal directions shall be identified as the vertical direction.

As shown best in FIG. 6, the first size module 102 includes a generally linear or rectangular housing assembly 130 (described below). The second size module 104 has a generally U-shaped housing assembly 330 having a base portion 334, a left extension 336 and a right extension 338 (described below). The second size module 104 is sized so that the first size module 102 can fit between, i.e., be nested between, the second module left and right extensions 336, 338. The third size module 106 also has a generally U-shaped housing assembly 500, having a base portion 504, a left extension 506 and a right extension 508. The third sized module 106 is sized such that the second sized module 104 fits between, or is nested between, the third size module left and right extensions 506, 508. The modular jumper assembly 100 is generally symmetrical about a centerline 101 extending through the middle of the first sized module 102 and perpendicular to the front side.

The terminal ends 110, 112 of the bus assemblies 180, 440, 640 are structured to engage two circuit breakers 1, 2 (FIG. 3). That is, the terminal ends 110 on one side of a centerline 101 engage a first circuit breaker 90, while the terminal ends 112 on the other side of the centerline 101 engage a second circuit breaker 92. If the jumper assembly 100 includes three modules 102, 104, 106, the jumper assembly 100 can engage two separate three-phase circuit

breakers 1A, 2A. Alternatively, the jumper assembly may only include two modules, typically the first sized module 102 and the second sized module 104, and engage two separate two-line circuit breakers 1B, 2B.

As shown in FIGS. 7A–7G, the first size module 102 has a housing assembly 130, and a bus assembly 180 (FIGS. 7B, 7G). The first sized module housing assembly 130 is made from a non-conductive material. The first sized module housing assembly 130 includes a horizontal generally rectangular planar member 132 having a medial opening 134. The first sized module planar member 132 has an upper side 136 and a lower side 138. A plurality of side walls 140 extend upwards from the perimeter of the first sized module housing planar member upper side 136 and downward from the first sized module planar member lower side 138. The side walls 140 have, generally, either a uniform height or depth. The height of the first sized module housing upper side walls is between about ½ to 2.0 inches and preferably about 1.0 inch. The depth of the first sized module housing lower side walls is between about ⅛ to 1⅝ inches and preferably about ⅝ inches. The first sized module housing upper side walls include a front side wall 142, a left-back side wall 144, and a right-back side wall 146. The first sized module upper front side wall 142 extends left to right across the front side of the first sized module housing planar member 132. The first sized module upper left-back side wall 144 extends left to right along the left most portion of the first sized module housing planar member 132 back side. The first sized module upper right-back side wall 146 extends right to left along the right most portion of the first sized module housing planar member 132 back side. Between the first sized module upper left-back side wall 144 and the first sized module upper right-back side wall 146 is a first sized module back side upper medial opening 148. A tab 150 extends generally perpendicularly to the right side of the first sized module upper right back side wall 146. The tab 150 on the first sized module upper right back side wall 146 extends toward the front side. Thus, the first sized module front side wall 142 and the left back side wall 144 and the first sized module front side wall 142 and the tab 150 define a first sized module left side opening 152 and a first sized module right side opening 154, respectively.

As shown best on FIG. 7B, the first sized module housing lower side walls include a first sized module lower left side wall 160, a first sized module lower back side wall 162, a first sized module lower right side wall 164, and a first sized module lower front medial side wall 166. The first sized module lower left side wall 160, the first sized module lower back side wall 162, and the first sized module lower right side wall 164 extend along the entire perimeter of the of the first sized module housing planar member 132 left side, back side and right side, respectively. The first sized module lower front medial side wall 166, however, only extends left to right along the central portion of the first sized module housing planar member 132 front side. Thus, there is a first sized module lower left front opening 168 between the first sized module lower front medial side wall 166 and the first sized module lower left side wall 160 and a first sized module lower right front opening 169 between the first sized module lower medial front side wall 166 and the lower right side wall 164. The first sized module lower side walls 160, 162, 164, 166 define a first sized module lower bus raceway 170.

Two bus assembly clips 171, as detailed in FIG. 10, are located along the lower front side of the first sized module planar member 132, one clip 171 in each opening 168, 169. Each clip 171 extends from the first sized module housing

planar member lower surface **138** and include an elongated flexible stem **172**, a perpendicular latching surface **173**, and an angled lower surface **174**. The first size module lower back side wall **162** includes a bus assembly mounting boss **175**. The mounting boss **175**, as detailed in FIG. **11**, is a protuberance extending from the front fact of the first sized module lower back side wall **162** and having a flat surface **176** parallel to the first sized module housing planar member **132**. The flat surface **176** is spaced, about the height of the first sized module bus assembly planar member **182** (described below), apart from the first sized module housing planar member **132**. There may also be a bus assembly alignment guide **177** extending from the planar member lower side **138**. The bus assembly alignment guide **177** is a protuberance having a angled lower surface.

Additionally, there are two first sized module front spacers **178**, **179**. One spacer **178** extends toward the front from the first sized module upper front side wall **142** and the first sized module lower front medial side wall **166**. The other spacer **179** extends toward the front from the upper front side wall **142** at the front right corner and is an extension of the first sized module lower right side wall **164**. The spacers **178**, **179** run vertically and protrude from the first sized module front side walls **142**, **166** less distance than the first sized module bus assembly terminals **184**, **186** (described below).

As shown best in FIG. **7G**, the first sized module bus assembly **180** includes a generally rectangular and planar member **182**, two terminals **184**, **186**, and a collar assembly **190**. The first sized module bus assembly planar member **182** includes a medial opening **183**. The two terminals **184**, **186** are joined at one end to the first sized module bus assembly planar member **182** and each has a planar distal end **185**, **187**. The terminals **184**, **186** may have a bent portion **188** that shifts the planar distal ends **185**, **187** out of the plane of the first sized module bus assembly planar member **182**. The collar assembly **190** includes a collar assembly body **192**, a mounting device **194** and a fastening device **196**. The collar assembly body **192** is generally cube shaped having a top surface **198**, a bottom surface **200** and four sides **202**. The collar assembly body **192** has a side opening **204** on at least one of the four sides **202**. The collar body top surface **198** includes a threaded opening **201**. The collar assembly fastening device **196** has threads corresponding to the top surface threaded opening and is disposed therein. The collar assembly fastening device **196** is structured to move into and out of the collar assembly body **192** so as to engage a power line **810** (described below). The collar assembly bottom surface **200** also includes a threaded opening (not shown). The collar assembly mounting device **194** is structured to engage the collar assembly bottom surface **200** threaded opening.

To assemble the first sized module **102**, the back side of the first sized module bus planar member **182** is inserted between the mounting boss **175** and the first sized module housing planar member **132**. Thus, the terminals **184**, **186** pass through the first sized module lower left front opening **168** and first sized module lower right front opening **169**. As the first sized module bus assembly planar member **182** contacts the angled lower surface of the bus assembly alignment guide **177**, the bus assembly alignment guide **177** acts to centrally position the first sized module bus assembly **180** within the lower bus raceway **170**. The first sized module bus assembly planar member **182** is then brought into face-to-face contact with the first sized module housing planar member lower side **138**. As the first sized module bus assembly planar member **182** is brought into contact with

the first sized module housing planar member lower side **138**, each terminal **184**, **186** contacts a bus assembly clip angled lower surface **174** causing the clip stem **172** to flex and allow the terminal **184**, **186** to pass. Once the first sized module bus assembly planar member **182** in generally parallel to the first sized module housing planar member **132**, the clip stem **172** will return to its original position. At this point, a clip latching surface **173** is adjacent to each terminal **184**, **186**. The first sized module bus planar member **182** is secured to the first sized module housing assembly **130** by positioning the collar assembly **190** over the upper side of the first sized module housing medial opening **134** while passing the collar assembly mounting device **194** through the first sized module bus planar member medial opening **183** and the first sized module housing medial opening **134** to engage the collar assembly bottom surface **200** threaded opening. Thus, the first sized module bus assembly **180** is coupled to the first sized module housing assembly **130** with the terminal ends **110**, **112** extending beyond the first sized module housing assembly **130** front side.

As shown in FIGS. **8A–8G**, the second size module **104** has a housing assembly **330**, and a bus assembly **440**. The second sized module housing assembly **330** is made from a non-conductive material and is generally symmetrical about a second sized module centerline **331**. The second sized module housing assembly **330** includes a horizontal, generally U-shaped planar member **332** having a base portion **334**, a left extension **336** and a right extension **338**. Both the second sized module housing planar member left extension **336** and the second sized module housing planar member right extension **338** extend from the front side of the second sized module housing planar member base portion **334**. A first opening **340** and a second opening **342** extend through the second sized module housing planar member base portion **334**. The second sized module housing planar member first opening **340** is disposed adjacent to the second sized module housing planar member base portion **334** left side. The second sized module housing planar member second opening **342** is disposed adjacent to the second sized module housing planar member base portion **334** right side. The second sized module housing planar member has an upper side **350** and a lower side **352**. A plurality of side walls **360** extend upwards from the perimeter of, and across, the second sized module housing planar member upper side **350** and downward from the second sized module housing planar member lower side **352**. The side walls **360** have, generally, either a uniform height or depth. The height of the second sized module housing upper side walls is between about $\frac{1}{2}$ to 2.0 inches and preferably about 1.0 inch. The depth of the second sized module housing lower side walls is between about $\frac{1}{8}$ to $1\frac{5}{8}$ inches and preferably about $\frac{5}{8}$ inches.

As shown best in FIG. **8A**, the second sized module housing upper side walls include a left front side wall **362** extending left to right and disposed at the front side of the second sized module housing planar member left extension **336**, a right front side wall **364** extending left to right and disposed at the front side of the second sized module housing planar member right extension **338**, a left extension medial side wall **366** extending left to right and disposed between the second sized module housing planar member base portion **334** and the second sized module housing planar member left extension **336**, a right extension medial side wall **368** extending left to right and disposed between the second sized module housing planar member base portion **334** and the second sized module housing planar member right extension **338**, a left back side wall **370**

extending left to right disposed at the left back side of the second sized module housing planar member base portion **334**, and a right back side wall **372** extending right to left disposed at the right back side of the second sized module housing planar member base portion **334**. A base portion upper left medial side wall **374** and a base portion upper right medial side wall **376** extend front to back between the front side and the back side of the second sized module housing planar member base portion **334**. The second sized module housing base portion left medial wall **374** is disposed to the left side of the second sized module centerline **331**. The base second sized module housing base portion upper right medial wall **376** is disposed to the right side of the second sized module centerline **231**. As with the first sized module housing side walls **140**, the second sized module upper side walls include tabs **380** which extend generally perpendicularly to the second sized module upper side walls **362, 364, 366, 368, 370, 372, 374, 376**. Thus, there are tabs **380** extending towards the back from the left and right ends of both the left front side wall **362** and the right front side wall **364**. Both the left and right second sized module housing base portion upper medial side walls **374, 376** have tabs **380** extending left to right along the perimeter of the second sized module housing base portion **334**. The tabs **380** extend to both the left and the right of left second sized module housing base portion upper left medial side wall **374** as well as to both the left and the right of right second sized module housing base portion upper right medial side wall **376**. The tab **380** on the front side of left second sized module housing base portion upper left medial side wall **374** extends leftward to become contiguous with left extension medial side wall **366**. The tab **380** on the front side of right base portion upper left medial side wall **374** extends rightward to become contiguous with right extension medial side wall **368**.

Thus, upper side walls define a plurality of openings. On the second sized module housing left extension **336** there is a left side opening **390** and a right side opening **392**. On the second sized module housing planar member right extension **338** there is a left side opening **394** and a right side opening **396**. On the second sized module housing planar member base portion **334** there is a left side opening **398**, a right side opening **400**, a back side left opening **402**, a back side right opening **404**, a back side medial opening **406**, and a front side medial opening **408**.

As shown best in FIG. 8B, the second sized module housing lower side walls generally extend along the perimeter of the U-shaped planar member **332**, except for the front side of both the left and right extensions **336, 338**. Thus, there is a second sized module housing base portion lower back side wall **410**, a second sized module housing base portion lower front side wall **411**, a second sized module housing base portion lower left side wall **412**, a second sized module housing base portion lower right side wall **414**, a second sized module housing left extension lower left side wall **416**, a second sized module housing left extension lower right side wall **418**, a second sized module housing right extension lower left side wall **420**, and a second sized module housing right extension lower right side wall **422**. The second sized module lower side wall therefore define a U-shaped second sized module lower raceway **424**. As with the first sized module **102**, the front side of both the left and right extensions **336, 338** each include one or more bus assembly clips **171** used to secure the second sized module bus assembly **440**. Additionally, there are two bus assembly mounting bosses **426, 428** located on the front face of the second sized module housing base portion lower back side

wall **410**. The second sized module bus assembly mounting bosses **426, 428** are substantially similar to the first sized module bus assembly mounting bus **175**.

There are two second sized module front spacers **430, 432**. One spacer **430** extends from the second sized module housing right side of the left extension upper front side wall **362** and is an extension of the second sized module housing left extension lower right side wall **418**. The other spacer **432** extends from the right side of the second sized module housing right extension upper front side wall **364** and is an extension of the second sized module housing right extension lower right side wall **418**. The second sized module front spacers **430, 432** run vertically and protrude from the second sized module housing front side walls **362, 364** less distance than the second sized module bus terminals **448, 450** (described below).

The second sized module bus assembly **440** includes a generally U-shaped planar member **441** having a base portion **442**, a left extension **444**, and a right extension **446**. The second sized module bus planar member left and right extensions **444, 446** end in two terminals **448, 450**. The two terminals **448, 450** each have a planar distal end **456, 458**. The terminals **448, 450** may have a bent portion **460** that shifts the planar distal ends **456, 458** out of the plane of the second sized module bus planar member **441**. The second sized module bus assembly **440** further includes one or more collar assemblies **190**. The second sized module bus planar member base portion **442** includes two openings **452, 454**, one each disposed adjacent to either the right or left sides.

To assemble the second sized module **104**, the back side of the second sized module bus planar member **441** is inserted between the mounting bosses **426, 428** and the second sized module housing planar member lower side **352**. The second sized module bus planar member **441** is then brought into face-to-face contact with the second sized module housing planar member lower side **352**. As the bus planar member **441** is brought into contact with the second sized module housing planar member lower side **352**, each terminal **448, 450** contacts a bus assembly clip angled lower surface **174** causing the clip stem **172** to flex and allow the terminals **448, 450** to pass. Once the second sized module bus planar member **441** is generally parallel to the second sized module planar member lower side **352**, the clip stem **172** will return to its original position. At this point, the clip latching surface **173** is located below, and parallel to, the second sized module bus terminals **448, 450**. The second sized module bus planar member **441** is secured to the second sized module housing assembly **330** by positioning a collar assembly **190** over the upper side of one of the second sized module housing planar member openings **340, 342** and passing, from the lower side, the collar assembly mounting device **194** through a corresponding second sized module bus planar member opening **454, 456** and the second sized module planar member openings **340, 342** to engage the collar assembly bottom surface **200** threaded opening. Thus, the second sized module bus assembly **440** is coupled to the second sized module housing assembly **330** with the terminals **448, 450** extending beyond the second sized module left and right extension front side walls **362, 364**.

As shown in FIGS. 9A-9G, the third sized module **106** also includes a housing assembly **500** and a bus assembly **640**. The third sized module housing assembly **500** is made from a non-conductive material. The third sized module housing assembly **500** includes a U-shaped, generally planar member **502** having a base portion **504**, a left extension **506** and a right extension **508**. The third sized module housing

planar member **502** has an upper side **510** and a lower side **512**. There are two opening **514**, **516** extending through the third sized module housing planar member **502**. The third sized module housing planar member first opening **514** is disposed adjacent to the third sized module housing assembly base portion **504** left side. The third sized module housing planar member second opening **516** is disposed adjacent to the third sized module housing assembly base portion **504** right side. A plurality of side walls **520** extend upwards from the perimeter of the third sized module housing planar member upper side **510** and downward from the third sized module housing planar member lower side **512**. The side walls **520** have, generally, either a uniform height or depth. The height of the third sized module housing upper side walls is between about $\frac{1}{2}$ to 2.0 inches and preferably about 1.0 inch. The depth of the third sized module housing lower side walls is between about $\frac{1}{8}$ to $1\frac{5}{8}$ inches and preferably about $\frac{5}{8}$ inches.

As shown best in FIG. 9A, the third sized module housing upper walls include a third sized module left side extension upper front side wall **522**, a third sized module right side extension upper front side wall **524**, a third sized module left side extension upper front medial side wall **526**, a third sized module right side extension upper front medial side wall **528**, a third sized module left side extension upper back medial side wall **530**, a third sized module right side extension upper back medial side wall **532**, a third sized module base portion upper back left side wall **534**, and a third sized module base portion upper back right side wall **536**. The third sized module upper walls further include four base portion upper side walls **538**, **540**, **542**, **544** which extend front to back. A third sized module base portion upper left outer side wall **538** is disposed adjacent to the right side of the third sized module left extension **506**. A third sized module base portion upper left inner side wall **540** is disposed on a generally medial line between the third sized module base portion upper left outer side wall **538** and the third sized module centerline **501**. A third sized module base portion upper right outer side wall **544** is disposed adjacent to the right side of the third sized module housing planar member right extension **508**. A third sized module base portion upper right inner side wall **542** is disposed on a generally medial line between the third sized module base portion upper right outer side wall **544** and the third sized module centerline **501**. As with the first sized module housing side walls **140** and the second sized module side walls **360**, the third sized module upper side walls may include tabs **550** which extend generally perpendicularly to selected third sized module upper side walls. The tabs **550** extend front to back at the left and right ends of the third sized module left side extension upper front medial side wall **526**, the third sized module right side extension upper front medial side wall **528**, the third sized module left side extension upper back medial side wall **530**, and the third sized module right side extension upper back medial side wall **532**. Additionally, tabs **550** also extend left-to-right at the front and back ends of the four base portion upper side walls **538**, **540**, **542**, **544**. The tab **550** on the front side of the third sized module base portion upper left outer side wall **538** extends leftward to become contiguous with third sized module left side extension upper back medial side wall **530**. The tab **550** on the front side of the third sized module base portion upper right outer side wall **544** extends rightward to become contiguous with third sized module right side extension upper back medial side wall **532**.

Thus, the third sized module upper side walls define a plurality of openings. On the third sized module housing

planar member left extension **506** there is an upper front left side opening **560**, an upper front right side opening **562**, an upper back left side opening **564**, and an upper back right side opening **566**. On the third sized module housing planar member right extension **508** there is an upper front left side opening **570**, an upper front right side opening **572**, an upper back left side opening **574**, and an upper back right side opening **576**. On the third sized module housing assembly base portion **504** there is an upper left side opening **580**, an upper right side opening **582**, an upper back left side opening **584**, and an upper back side right opening **586**. Adjacent to the upper back left side opening **584** is a back side left medial opening **587**. On the front side of the third sized module housing assembly base portion **504**, opposite the third sized module base portion upper back side left medial opening **587** is a front side left medial opening **588**. Adjacent to the third sized module base portion upper back side right opening **586** is a back side medial right opening **590**. On the front side of the third sized module housing assembly base portion **504**, opposite the back side medial right opening **590** is a front side right medial opening **592**. Also on the third sized module housing assembly base portion **504**, at or about the centerline **501**, are a back side medial opening **594** and a front side medial opening **596**.

As shown best in FIG. 9G, the third sized module housing lower side walls generally extend along the perimeter of the U-shaped planar member **502**, except for the front side of both the left and right extensions **506**, **508**. Thus, there is a third sized module housing base portion lower back side wall **600**, a third sized module housing base portion lower front side wall **601**, a third sized module base portion lower left side wall **602**, a third sized module base portion lower right side wall **604**, a third sized module left extension lower left side wall **606**, a third sized module left extension lower right side wall **608**, a third sized module right extension lower left side wall **610**, and a third sized module right extension lower right side wall **612**. The third sized module lower side walls, therefore, defined a third sized module lower raceway **614**. As with the second sized module **104**, the front side of both the left and right extensions **506**, **508** each include one or more bus assembly clips **171** used to secure the third sized module bus assembly **640**. Additionally, there are two bus assembly mounting bosses **616**, **618** located on the front face of the third sized module housing base portion lower back side wall **600**. The third sized module bus assembly mounting bosses **616**, **618** are substantially similar to the first sized module bus assembly mounting bus **175**.

There are two third sized module front spacers **620**, **622**. One spacer **620** extends forward from the right side of the third sized module left extension upper front side wall **522** and is an extension of the third sized module left extension lower right side wall **608**. The other spacer **622** extends from the right side of the right extension upper front side wall **524** and is an extension of the third sized module right extension lower right side wall **612**. The third sized module spacers **620**, **622** run vertically and protrude from the third sized module front side walls **522**, **524** less distance than the third sized module bus terminals **648**, **650** (described below).

The third sized module bus assembly **640** includes a generally U-shaped planar member **641** having a base portion **642**, a left extension **644**, and a right extension **646**. The third sized module bus planar member left and right extensions **644**, **646** end in two terminals **648**, and **650**. The two terminals **648**, **650** each have a planar distal end **656**, **658**. The terminals **648**, **650** may have a bent portion **660** that shifts the planar distal ends **656**, **658** out of the plane of the

third sized module bus planar member **641**. The third sized module bus assembly **640** further includes one or more collar assemblies **190**. The third sized module bus planar member base portion **642** includes two openings **652, 654**, one each disposed adjacent to either the right or left sides.

To assemble the third sized module **106**, the back side of the third sized module bus planar member **641** is inserted between the third sized module bus assembly mounting bosses **616, 618** and the third sized module housing planar member lower side **512**. The third sized module bus planar member **641** is then brought into face-to-face contact with the third sized module housing planar member lower side **512**. As the third sized module bus planar member **641** is brought into contact with the third sized module planar member lower side **512**, each terminal **648, 650** contacts a bus assembly clip angled lower surface **174** causing the clip stem **172** to flex and allow the terminals **648, 650** to pass. Once the third sized module bus planar member **641** is generally parallel to the third sized module housing planar member **502**, the clip stem **172** will return to its original position. At this point, the clip latching surface **173** is located below, and parallel to, each third sized module housing bus terminal **648, 650**. The third sized module bus planar member **541** is secured to the third sized module housing assembly **500** by positioning a collar assembly **190** over one of the third sized module housing planar member openings **514, 516** while passing, from the lower side, the collar assembly mounting device **194** through a corresponding third sized module bus planar member opening **652, 654** and the third sized module planar member openings **516, 518** to engage the collar assembly bottom surface **200** threaded opening. Thus, the third sized module bus assembly **640** is coupled to the third sized module housing assembly **500** with the terminals **648, 650** extending beyond the third sized module left and right extension front side walls **522, 524**.

The first sized module **102**, the second sized module **104** and the third sized module **106** are coupled together by a plurality of bisected tongue-and-groove connectors **700**. As shown in FIG. **12**, the bisected tongue-and-groove connectors **700** include an upper tongue portion **702**, a lower tongue portion **704**, an upper groove portion **706** and a lower groove portion **708**. Each of the upper tongue portion **702**, lower tongue portion **704**, upper groove portion **706** and lower groove portion **708** extend in a horizontal direction beyond the side walls **140, 360, 520** of the first sized module **102**, second sized module **104**, and third sized module **106**. As shown in FIGS. **7A, 7G, 8A, 8G, 9A** and **9G**, generally, the tongue-and-groove connectors **700** are disposed adjacent to the left and right openings **152, 154, 390, 392, 394, 396, 398, 400, 560, 562, 564, 566, 570, 572, 574, 576, 580, 582**. More specifically, each upper tongue portion **702** and lower tongue portion **704** is disposed to the left side of one of the left openings **152, 390, 394, 398, 560, 564, 570, 574, 580**. Each upper tongue portion **702** is disposed on an upper left side wall. Each lower tongue portion **704** is disposed on a lower side wall below a left opening **152, 390, 394, 398, 560, 564, 570, 574, 580**. Additionally, each lower tongue portion **704** has an upper surface **705**. The lower tongue upper surface **705** is contiguous with, and in the same plane as, either the first sized module housing planar member upper side **136**, the second sized module housing planar member upper side **350**, or the third sized module housing planar member upper side **510**. Each upper groove portion **706** and lower groove portion **708** is disposed to the right of one of the right openings **154, 392, 396, 400, 562, 566, 572, 576, 582**. Each upper groove portion **706** is disposed on a right upper side

wall. Each lower groove portion **708** is disposed on a right lower side wall below a right side opening **154, 392, 396, 400, 562, 566, 572, 576, 582**.

When the first sized module **102**, second sized module **104**, and third sized module **106** are assembled into the modular jumper assembly **100**, each upper tongue portion **702**, except those tongue portions on the left side and the groove portions on the right side of the third sized module **106**, will engage a corresponding upper groove portion **706** on an adjacent module **102, 104, 106**. Additionally, because the third sized module **106** includes tongue-and-groove connectors **700** on the outer left and right sides, two or more modular jumper assemblies **100** may be joined together as shown in FIG. **19**, this multi-jumper assembly configuration **1248** is discussed further below. Additionally, when the modular jumper assembly **100** is assembled, each bus assembly **180, 440, 640** are generally co-planar, and the housing planar members **132, 332, 502** are generally co-planar.

The lower side raceways **170, 424, 614** are shown clearly on FIG. **4**. As discussed above, the lower side raceways **170, 424, 614** have the same general shape as the first, second, and third sized module housing planar members **132, 332, 502**. In addition to the lower raceways **170, 424, 614**, the modular jumper assembly **100** includes a plurality of upper raceways **800**, as shown in FIGS. **2** and **3**. The plurality of upper raceways **800** are only formed when two or more modules **102, 104, 106** are joined together to form the modular jumper assembly **100**. The plurality of upper raceways **800** provide a path for one or more power lines **810, 812, 814, 816, 818, 820, 822, 824, 826, 828, 829** to access and be coupled to the collar assemblies **190** attached to the first sized module bus assembly **180**, the second sized module bus assembly **440**, and the third sized module bus assembly **640**. Each upper race way **800** is separated from an adjacent upper raceway **800** by one or more upper side walls.

For example, there are three upper first sized module upper raceways **830, 832, 834** to access the first sized module collar assembly **190** coupled to the first sized module bus assembly. Each first sized module upper raceway **830, 832, 834** extends across all three modules **102, 104, 106**. That is, there is a first sized module upper left raceway **830**, a first sized module upper right raceway **832**, and a first sized module upper medial raceway **834**. The first sized module upper left raceway **830** provides a path extending left to right, from the left side of the modular jumper assembly **100** to the center of the first sized module **102**. The first sized module upper left raceway **830** is formed by the third sized module left extension upper front left side opening **560**, the third sized module left extension upper front right side opening **562**, the second sized module left extension upper left side opening **390**, the second sized module left extension upper right side opening **392**, and the first sized module upper left side opening **152**. The first sized module upper right raceway **832** is formed by the third sized module right extension upper front right side opening **572**, the third sized module right extension upper front left side opening **570**, the second sized module right extension upper right side opening **396**, the second sized module right extension upper left side opening **394**, and the first sized module upper right side opening **154**. The first sized module upper medial raceway **834** is formed by the third sized module base portion upper back side medial opening **594**, the third sized module base portion upper front side medial opening **596**, the second sized module base portion upper back side medial opening **406**, the second sized module base

portion upper front side medial opening **408**, and the first sized module upper back side medial opening **148**. Accordingly, there may be a first sized module left side power line **810**, shown in ghost, extending through the first sized module upper left raceway **830** and coupled to the collar assembly **190** disposed above the first sized module bus planar member medial opening **183**, a first sized module right side power line **812** extending through the first sized module upper right raceway **832** and coupled to the collar assembly **190** disposed above the first sized module bus planar member medial opening **183**, and/or a first sized module medial power line **814** extending through the first sized module upper medial raceway **834** and coupled to the collar assembly **190** disposed above the first sized module bus planar member medial opening **183**.

When single power line, for example the left side power line **810**, is used, the power line **810** is passed through a collar assembly side opening **204** and secured with the collar fastening device **196**. If two or more power lines **810**, **812**, **814** coupled to the collar assembly **190** disposed above the first sized module bus planar member medial opening **183**, a flat power line terminal end **809** may be used so as to provide sufficient space within the collar assembly **190**.

There are four second sized module upper raceways **840**, **842**, **844**, **846**. More specifically, there is a second sized module upper left raceway **840**, a second sized module upper back side left raceway **842**, a second sized module upper back side right raceway **844**, and a second sized module upper right raceway **846**. The second sized module left raceway **840** is formed by the third sized module left extension upper back left side opening **564**, third sized module left extension upper back right side opening **566**, and the second sized module base portion upper left side opening **398**. The second sized module upper back side left raceway **842** is formed by the third sized module base portion upper back side left medial opening **587**, the third sized module base portion upper front side left medial opening **588** and the second sized module base portion upper back side left opening **402**. The second sized module upper back side right raceway **844** is formed by the third sized module base portion upper back side right medial opening **590**, the third sized module base portion upper front side right medial opening **592** and the second sized module base portion upper portion back side right opening **404**. The second sized module right raceway **846** is formed by the third sized module right extension upper back right side opening **576**, third sized module right extension upper back left side opening **574**, and the second sized module base portion upper right side opening **400**. Accordingly, there may be a second sized module left power line **816** extending through the second sized module left raceway **840**, and/or a second sized module left back power line **818** extending through the second sized module left back raceway **842**, coupled to the collar assembly **190** disposed above the second sized module planar member first opening **340**. Additionally, there may be a second sized module right power line **822** extending through the second sized module right raceway **846**, and/or a second sized module right back power line **820** extending through the second sized module upper back side right raceway **844**, coupled to the collar assembly **190** disposed above the second sized module planar member second opening **342**.

There are four third sized module upper raceways **850**, **852**, **854**, **856**. More specifically, there is a third sized module upper left raceway **850**, a third sized module upper back left raceway **852**, a third sized module upper back right raceway **854**, and a third sized module upper right raceway

856. The third sized module upper left raceway **850** is formed by the third sized module base portion upper left side opening **580**. The third sized module back left raceway **852** is formed by the third sized module base portion upper back left side opening **584**. The third sized module upper back right raceway **854** is formed by the third sized module base portion upper back right side opening **586**. The third sized module upper right raceway **856** is formed by the third sized module base portion upper right side opening **582**. Accordingly, there may be a third sized module left power line **824** extending through the third sized module left raceway **850**, and/or a third sized module left back power line **826** extending through the third sized module left back raceway **852**, coupled to the collar assembly **190** disposed above the third sized module planar member first opening **514**. Additionally, there may be a third sized module right power line **829** extending through the third sized module right raceway **856**, and/or a third sized module right back power line **828** extending through the third sized module right back raceway **854**, coupled to the collar assembly **190** disposed above the third sized module planar member second opening **516**.

As shown in FIGS. **13–15**, the modular jumper assembly **100** also includes a snap-fit cover assembly **230**, **280**, **290**. The cover assembly **230**, **280**, **290** is sized to fit the largest module **102**, **104**, **106** used to create the modular jumper assembly **100**. For example, the first sized module cover assembly **230**, shown in FIG. **13**, is structured to fit a modular jumper assembly **100** formed from a single first sized module **102**. The first sized module cover assembly **230** includes a planar member **232** having an upper side **234** and a lower side **236**. One or more latching members **238**, **240** extend downwardly from the first sized module cover planar member **232** back side. Each latching members **238**, **240** include an elongated flexible stem **244**, a perpendicular latching surface **246**, and an angled lower surface **248**. The first sized module cover assembly **230** also includes a plurality of raceway covers **250**. Each raceway cover **250** includes a base portion **252**, which extends downwardly from the first sized module cover planar member **232**, and a break-away portion **254** coupled to the base portion **252** by a frangible seam **253**. The raceway covers **250** are positioned to be disposed in the upper, outer openings on a housing assembly. Thus, the first sized module cover assembly **230** includes three raceway covers **250** that are structured to fit with the first sized module left opening **152**, the first sized module back medial opening **148** and the first sized module right opening **154**. The break-away portion **254** of the raceway cover **250** may be removed by fracturing the coupling between the raceway cover base portion **252** and the break-away portion **254**. The break-away portion **254** is removed at the raceway where the power line(s), e.g. first sized module power line **810**, will be disposed.

The first sized module cover assembly planar member **232** also includes a knockout access assembly **258**. The knockout access assembly **258** is a removable portion of the first sized module cover assembly planar member **232**. The knockout access assembly **258** includes a generally circular opening **260** in the first sized module cover assembly planar member **232** and a removable member **262** sized to fit within the opening **260** and attached to the first sized module cover assembly planar member **232** by frangible tabs **263**. The opening **260** in the cover assembly planar member is positioned so as to be located over the collar assembly fastening device **196** when the cover assembly **230** is coupled to the first sized module housing assembly.

The cover assembly latching members **238**, **240** are structured to cooperate with latch channels **264**, **266** dis-

posed on back side of each module **102**, (FIG. 7E) **104** (FIG. 8E), **106** (FIG. 9E). Again with reference to the first sized module **102**, the latch channels **264**, **266** are disposed on the back side of the first sized module upper left back side wall **144** and the first sized module upper right back side wall **146**. The latch channels **264**, **266** include a latch protuberance **268** extending into the channel **264**, **266**. The latch protuberance **268** includes an angled upper surface **270** and a latch surface **271**. The protuberance latch surface **271** extends generally perpendicular to the latch channel **264**, **266** side wall, that is, in a generally horizontal direction.

To install the first sized module cover assembly **230**, an operator initially removes the raceway break-away portion **254** that would be disposed in the first sized module upper opening where the power line, **810** e.g. is disposed. The first sized module cover assembly **230** is then placed over the top of the first sized module **102** with the latching members **238**, **240** disposed in the top portion of the latch channels **264**, **266**. The operator then pushes the first sized module cover assembly **230** towards the first sized module housing planar member **132**. As the latching member angled lower surface **248** contacts the latch protuberance angled upper surface **270**, the latching member flexible stem **244** flexes to allow the latching member perpendicular latching surface **246** to pass the latch protuberance **268**. Once the latching member perpendicular latching surface **246** passes the protuberance latch surface **271**, the latching member flexible stem **244** snaps back to its original position. At this point, the latching member perpendicular latching surface **246** is adjacent to the protuberance latch surface **271**, thereby latching the first sized module cover assembly **230** to the first sized module housing assembly **130**. Should the operator need to access the first sized module collar assembly fastening device **196**, for example, to remove the power line **810**, the operator needs only to remove the first sized module cover assembly knockout access assembly **258**.

A second sized module cover assembly **280** is shown in FIGS. 14A and 14B. The second sized module cover assembly **280** includes a planar member **282** sized to fit over top of a combination of the first sized module **102** and the second sized module **104**. The second sized module cover assembly **280** also includes one or more latching members **238**, **240** extending downwards from the back side of the second sized module cover assembly planar member **282**. The second sized module cover assembly **280** also includes a plurality of raceway covers **250**. The raceway covers **250** on the second sized module cover assembly **280** are positioned to be disposed within the second sized module left extension upper left side opening **390**, the second sized module right extension upper right side opening **396**, the second sized module base portion upper left side opening **398**, second sized module upper right side opening **400**, second sized module upper back side left opening **402**, second sized module upper back side right opening **404**, and the second sized module upper back side medial opening **406**. As shown in FIG. 8E, the latch channels **264**, **266** on the second sized module housing assembly **330** are disposed on the back face of the tabs **380** on the back side of the second sized module housing base portion upper left medial side wall **374** and the second sized module housing base portion upper right medial side wall **376**. The second sized module cover assembly **280** also may have one or more front side clips **284** each having an elongated flexible stem **285**, a perpendicular latching surface **286**, and an angled lower surface **287**. The second sized module cover assembly front side clips **284** are structured to engage a block shaped front side latch protuberance **287** (FIG. 8G) disposed on the front

side of the second sized module housing assembly **330**. The second sized module front side latch protuberance **287** may have an angled upper surface **288**. Additionally, as with the first sized module cover assembly **230**, the second sized module cover assembly **280** includes a knockout access assembly **258** disposed at a location corresponding to each location of a collar assembly **190** that is attached to either the first sized module bus assembly **180** or the second sized module bus assembly **440**.

The cover assembly **290** for the third sized module **106** may be a larger version of the second sized module cover assembly **280** having additional knockout access assemblies **258** and raceway covers **250**. That is, the third sized module cover assembly may have a rectangular planar member (not shown) having, in addition to the knockout access assemblies **258** at the locations on the second sized module cover assembly **280**, knockout access assemblies **258** disposed at a location corresponding to each location of a collar assembly **190** that is attached to the third sized module bus assembly **640**. Additionally, the third sized module cover assembly **290** would have raceway covers **250** located at locations corresponding to the third sized module housing assembly left extension upper front left side opening **560** and upper back left side opening **564**, the third sized module right extension upper front right side opening **572** and an upper back right side opening **576**, the third sized module housing planar member base portion **334** upper left side opening **580**, an upper right side opening **582**, an upper back left side opening **584**, and an upper back side right opening **586**, upper back side left medial opening **587**, upper back side medial right opening **590**, and upper back side medial opening **594**.

Alternatively, as shown in FIG. 15, the third sized module cover assembly **290** may be structured to cooperate with the second sized module cover assembly **280**. That is, the third sized module cover assembly **290** may have a U-shaped planar member **291** sized to correspond to the third sized module housing assembly **500**. The third sized module cover assembly planar member **291** includes knockout access assemblies **258** disposed at a location corresponding to each location of a collar assembly **190** that is attached to the third sized module bus assembly **640**. Additionally, the third sized module cover assembly **290** includes a plurality of raceway covers **250** extending downwards from the third sized module cover assembly planar member **291**. The third sized module cover assembly raceway covers **250** are located at locations corresponding to the third sized module left extension upper front left side opening **560** and upper back left side opening **564**, the third sized module right extension upper front right side opening **572** and an upper back right side opening **576**, the third sized module housing planar member base portion **334**, upper left side opening **580**, an upper right side opening **582**, an upper back left side opening **584**, and an upper back side right opening **586**, upper back side left medial opening **587**, upper back side medial right opening **590**, and upper back side medial opening **594**. The third sized module cover assembly **290** may have one or more front side clips **294** each having an elongated flexible stem **295**, a perpendicular latching surface **296**, and an angled lower surface **297**. The third sized module cover assembly front side clips **294** are structured to engage a block shaped front side latch protuberance **298** (FIG. 9G) disposed on the front side of the third sized module housing assembly **500**. The third sized module front side latch protuberance **298** may have an angled upper surface **299**.

The third sized module cover assembly **290** also includes one or more latching members **238**, **240** extending down-

wards from the back side of the third sized module cover assembly planar member 291. Like the latching members 238, 240 on the second sized module cover assembly 280, the latching members 238, 240 on the third sized module cover assembly 290 cooperate with latch channels 264, 266 located on the third sized module housing assembly 500. As shown in FIG. 9E, the latch channels 264, 266 on the third sized module housing assembly 500 are disposed on the back face of the tabs 550 on the back side of the third sized module base portion upper left inner side wall 540 and the third sized module base portion upper right inner side wall 542.

In the embodiment described above, the jumper assembly 100 is formed from three modules 102, 104, 106. A first alternate modular jumper assembly 900 is shown in FIGS. 14A–14C. The first alternate jumper assembly 900, hereinafter the fourth sized module, is, essentially, a single module that combines the features of the first sized module 102 and second sized module 104. The fourth sized module includes a housing assembly 902, a first sized module bus assembly 180, and a second sized module bus assembly 440. The fourth sized module is generally symmetric about a centerline 901. The fourth sized module housing assembly 902 includes a planar member 904 having an upper side 906 and a lower side 908. There are three openings 910, 912, 914 extending through the fourth sized module housing planar member 904. The fourth sized module housing planar member first opening 910 is disposed along front side at about the centerline 901. The fourth sized module housing planar member second opening 912 is disposed adjacent to the left side and the backside. The fourth sized module housing planar member third opening 914 is disposed adjacent to the right side and the back side. A plurality of side walls 916 extend upwards from the fourth sized module housing planar member upper side 906 and downward from the fourth sized module housing planar member lower side 908. The side walls 916 have, generally, either a uniform height or depth. The height of the fourth sized module upper side walls is between about ½ to 2.0 inches and preferably about 1.0 inch. The depth of the fourth sized module lower side walls is between about ⅓ to 1⅝ inches and preferably about ⅝ inches.

As shown in FIGS. 16A, 16C, the fourth sized module upper walls include a front side wall 920, a left L-shaped side wall 922, a right L-shaped side wall 924, a left back side wall 926 and a right back side wall 928. The fourth sized module upper front side wall 920 extends left to right along the front side of the fourth sized module housing planar member 904. The fourth sized module left L-shaped side wall 922 includes a first portion 922A, which extends left to right, and a second portion 922B which extends front to back. The fourth sized module left L-shaped side wall first portion 922A extends from a medial point on, and perpendicular to, the left side of the fourth sized module planar member 904 to a point generally between the fourth sized module housing planar member first opening 910 and the fourth sized module housing planar member second opening 912. The fourth sized module left L-shaped side wall second portion 922B extends from the point generally between the fourth sized module housing planar member first opening 910 and the fourth sized module housing planar member second opening 912 to the back side of the fourth sized module housing planar member 904. The fourth sized module right L-shaped side wall 924 includes a first portion 924A, which extends left to right, and a second portion 924B which extends front to back. The fourth sized module right L-shaped side wall first portion 924A extends from a medial

point on, and perpendicular to, the right side of the fourth sized module planar member 904 to a point generally between the fourth sized module planar member first opening 910 and the fourth sized module planar member third opening 914. The right L-shaped side wall second portion 924B extends from the point generally between the fourth sized module planar member first opening 910 and the fourth sized module planar member third opening 914 to the back side of the fourth sized module planar member 904. The left back side wall 926 is disposed along the back side of fourth sized module planar member 904 and extends from the left side of the fourth sized module planar member 904. The fourth sized module right back side wall 928 is disposed along the back side of fourth sized module planar member 904 and extends from the right side of the fourth sized module planar member 904. Perpendicular tabs 929 may be disposed at the ends of the fourth sized module left L-shaped side wall 922 and fourth sized module right L-shaped side wall 924.

Thus, the fourth sized module upper side walls define a plurality of openings and raceways. There is a left side front opening 930 between the front side wall 920 and the fourth sized module left L-shaped side wall first portion 922A, a left side back opening 932 between the fourth sized module left L-shaped side wall first portion 922A and the left back side wall 926, a back side left opening 934 between the left back side wall 926 and the fourth sized module left L-shaped side wall second portion 922B, a medial back side opening 936 between the fourth sized module left L-shaped side wall second portion 922B and the fourth sized module right L-shaped side wall second portion 924B, a back side right opening 938 between the fourth sized module right L-shaped side wall second portion 924B and the right back side wall 928, a right side back opening 940 between the right back side wall 928 and the fourth sized module right L-shaped side wall first portion 924A, and a right side front opening 942 between the fourth sized module right L-shaped side wall first portion 924A and the front side wall 920. Additionally, the front side wall 920 and the fourth sized module left L-shaped side wall first portion 922A define a fourth sized module first raceway 944, the fourth sized module left L-shaped side wall second portion 922B and the fourth sized module right L-shaped side wall second portion 924B define a fourth sized module second raceway 946, the fourth sized module right L-shaped side wall first portion 924A and the front side wall 920 define a fourth sized module third raceway 948. Each of the fourth sized module raceways 944, 946, 948 provide an access path to the fourth sized module planar member first opening 910.

As shown in FIG. 16B, the fourth sized module lower side walls include lower left side wall 950, a lower back side wall 952, a lower right side wall 954, a lower front medial side wall 956, and a lower medial U-shaped side wall 958. The lower left side wall 950, lower back side wall 952, and lower right side wall 954 are disposed along, and extend the length of, the fourth sized module planar member 904 left side, back side, and right side, respectively. The lower front medial side wall 956 is disposed at about the centerline 901 and extends a short distance to the left and right of the centerline 901. The fourth sized module lower medial U-shaped side wall 958 includes a left extension 958A, a base portion 958B and a right extension 958C. The fourth sized module lower medial U-shaped wall left extension 958A begins at a point between the lower left side wall 950 and the lower front medial side wall 956 and extends perpendicular to the front side of the fourth sized module planar member 904 to a medial point on the fourth sized

module planar member **904**. The fourth sized module lower medial U-shaped wall right extension **958C** begins at a point between the lower right side wall **954** and the lower front medial side wall **956** and extends perpendicular to the front side of the fourth sized module planar member **904** to a medial point on the fourth sized module planar member **904**. The fourth sized module lower medial U-shaped wall base portion **958B** extends left to right between the ends of the fourth sized module lower medial U-shaped side wall left extension **958A** and fourth sized module lower medial U-shaped side wall right extension **958C**. Thus, lower front medial side wall **956** and the fourth sized module lower medial U-shaped side wall **958** defines a first lower raceway **960**, and the fourth sized module lower medial U-shaped wall **958** with the fourth sized module lower left side wall **950**, fourth sized module lower back side wall **952**, and fourth sized module lower right side wall **954** define a second lower raceway **962**.

Bus assembly mounting bosses **964**, **966**, similar to those described above, are disposed on the front side of the fourth sized module lower back side wall **952**. Another bus assembly mounting boss **970** is disposed on the front side of the fourth sized module lower medial U-shaped side wall base portion **958B**. Additionally, bus assembly bus clips **171** are disposed at the front side of the fourth sized module first and second lower raceways **960**, **962** and bus assembly alignment guides **963** are disposed within the fourth sized module first and second lower raceways **960**, **962**. A first sized module bus assembly is disposed in the fourth sized module first lower raceway **960** and is coupled to a collar assembly **190** being disposed through the fourth sized module planar member first opening **910**. A second sized module bus assembly is disposed in the fourth sized module second lower raceway **962** and is coupled to a collar assembly **190** being disposed through the fourth sized module planar member second and/or third opening **912**, **914**.

A plurality of spacers **980** extend from the front side of the fourth sized module upper front side wall **920** and the lower front medial side wall **956** or as extensions of the lower side walls. The left and right sides of the fourth sized module housing assembly **902** have a tongue and groove connector **700** as described above. As such, the fourth sized module may be coupled to a third sized module **106**. When coupled to a third sized module **106**, the upper raceways are formed as described above.

A second alternate jumper assembly is shown in FIGS. **17A–17C**. The second alternate jumper assembly, hereinafter the full sized module **1000**, is essentially, a single module that combines the features of the first sized module **102**, the second sized module **104**, and the third sized module **106**. The full sized module **1000** includes a housing assembly **1002**, a first sized module bus assembly **180**, a second sized module bus assembly **440**, and a third sized module bus assembly **640**. The full sized module **1000** is generally symmetric about a centerline **1001**. The full sized module housing assembly **1002** includes a planar member **1004** having an upper side **1006** and a lower side **1008**. There are five openings **1010**, **1012**, **1014**, **1016**, **1018** extending through the full sized module housing planar member **1004**. The full sized module planar member first opening **1010** is disposed along front side at about the centerline **1001**. The full sized module planar member fourth opening **1016** is disposed adjacent to the left side and the backside. The full sized module planar member fifth opening **1018** is disposed adjacent to the right side and the backside. The full sized module planar member second opening **1012** is disposed at about the medial point between the full sized module planar

member first opening **1010** and the full sized module planar member fourth opening **1016**. The full sized module planar member third opening **1014** is disposed at about the medial point between the full sized module planar member first opening **1010** and the full sized module planar member fifth opening **1018**. A plurality of side walls **1020** extend upwards from the full sized module planar member upper side **1006** and downward from the full sized module planar member lower side **1008**. The side walls **1020** have, generally, either a uniform height or depth. The height of the full sized module upper side walls is between about $\frac{1}{2}$ to 2.0 inches and preferably about 1.0 inch. The depth of the full sized module lower side walls is between about $\frac{1}{8}$ to $1\frac{5}{8}$ inches and preferably about $\frac{5}{8}$ inches.

As shown in FIGS. **17A** and **15C**, the full sized module upper walls include a front side wall **1022**, a front left L-shaped side wall **1024**, a back left L-shaped side wall **1026**, a front right L-shaped side wall **1028**, a back right L-shaped side wall **1030**, a left back side wall **1032** and a right back side wall **1034**. The full sized module upper front side wall **1022** extends left to right along the front side of the full sized module planar member **1004**. The full sized module front left L-shaped side wall **1024** includes a first portion **1024A**, which extends left to right, and a second portion **1024B** which extends front to back. The full sized module front left L-shaped side wall first portion **1024A** extends from a point about one third of the distance between the front side and the back side of the full sized module housing planar member **1004** along, and perpendicular to, the left side of the full sized module planar member **1004** to a point generally between the full sized module planar member first opening **1010** and the full sized module planar member second opening **1012**. The full sized module front left L-shaped side wall second portion **1024B** extends from the point generally between the full sized module planar member first opening **1010** and the full sized module planar member second opening **1012** to the back side of the full sized module planar member **1004**. The full sized module back left L-shaped side wall **1026** includes a first portion **1026A**, which extends left to right, and a second portion **1026B** which extends front to back. The full sized module back left L-shaped side wall first portion **1026A** extends from a point about two-thirds of the distance between the front side and the back side of the full sized module housing planar member **1004** along, and perpendicular to, the left side of the full sized module planar member **1004** to a point generally between the full sized module planar member second opening **1012** and the full sized module planar member fourth opening **1016**. The full sized module back left L-shaped side wall second portion **1026B** extends from the point generally between the full sized module planar member second opening **1012** and the full sized module planar member fourth opening **1016** to the back side of the full sized module planar member **1004**.

The full sized module front right L-shaped side wall **1028** includes a first portion **1028A**, which extends left to right, and a second portion **1028B** which extends front to back. The full sized module front right L-shaped side wall first portion **1028A** extends from a point about one third of the distance between the front side and the back side of the full sized module housing planar member **1004** along, and perpendicular to, the right side of the full sized module planar member **1004** to a point generally between the full sized module planar member first opening **1010** and the full sized module planar member third opening **1014**. The front right L-shaped side wall second portion **1028B** extends from the point generally between the full sized module planar

member first opening **1010** and the full sized module planar member third opening **1014** to the back side of the full sized module planar member **1004**. The full sized module back right L-shaped side wall **1030** includes a first portion **1030A**, which extends right to right, and a second portion **1030B** which extends front to back. The full sized module back right L-shaped side wall first portion **1030A** extends from a point about two-thirds of the distance between the front side and the back side of the full sized module housing planar member **1004** along, and perpendicular to, the right side of the full sized module planar member **1004** to a point generally between the full sized module planar member third opening **1014** and the full sized module planar member fifth opening **1018**. The back right L-shaped side wall second portion **1030B** extends from the point generally between the full sized module planar member third opening **1014** and the full sized module planar member fifth opening **1018** to the back side of the full sized module planar member **1004**.

The left back side wall **1032** is disposed along the back side of full sized module planar member **1004** and extends from the left side of the full sized module planar member **1004**. The right back side wall **1034** is disposed along the back side of full sized module planar member **1004** and extends from the right side of the full sized module planar member **1004**. Perpendicular tabs **1033** may be disposed at the ends of the full sized module front left L-shaped side wall **1024**, the full sized module back left L-shaped side wall **1026**, the full sized module front right L-shaped side wall **1028**, and the full sized module back right L-shaped side wall **1030**.

Thus, the full sized module upper side walls define a plurality of openings and raceways. There is a front left side opening **1040** between the full sized module front side wall **1022** and the full sized module front left L-shaped side wall first portion **1024A**, a left side medial opening **1042** between the full sized module front left L-shaped side wall first portion **1024A** and the back left L-shaped side wall first portion **1026A**, a back left side opening **1044** between the back left L-shaped side wall first portion **1026A** and the left back side wall **1032**, a back side left opening **1045** between the left back side wall **1032** and the back left L-shaped side wall second portion **1026B**, a back side left medial opening **1046** between the back left L-shaped side wall second portion **1026B** and the front left L-shaped side wall second portion **1024B**, a back side medial opening **1048** between the front left L-shaped side wall second portion **1024B** and the front right L-shaped side wall second portion **1028B**, a back side right medial opening **1050** between the front right L-shaped side wall second portion **1028B** and the back right L-shaped side wall second portion **1030B**, a back side right opening **1052** between the back right L-shaped side wall second portion **1030B** and the right back side wall **1034**, a right side back opening **1054** between the right back side wall **1034** and the back right L-shaped side wall first portion **1030A**, a right side medial opening **1056** between the back right L-shaped side wall first portion **1030A** and the front right L-shaped side wall first portion **1028A**, and a right side front opening **1058** between the front right L-shaped side wall first portion **1028A** and the full sized module front side wall **1022**.

Additionally, the full sized module front side wall **1022** and the full sized module front left L-shaped side wall first portion **1024A** define a full sized module first upper raceway **1060**. The front left L-shaped side wall second portion **1024B** and the front right L-shaped side wall second portion **1028B** define a full sized module second upper raceway **1062**. The full sized module front side wall **1022** and the

front right L-shaped side wall first portion **1028A** define a full sized module third upper raceway **1064**. The full sized module front left L-shaped side wall first portion **1024A** and the full sized module back left L-shaped side wall first portion **1026A** define a full sized module fourth upper raceway **1066**. The full sized module front left L-shaped side wall second portion **1024B** and the full sized module back left L-shaped side wall second portion **1026B** define a full sized module fifth upper raceway **1068**. The full sized module front right L-shaped side wall first portion **1028A** and the full sized module back right L-shaped side wall first portion **1030A** define a full sized module sixth upper raceway **1070**. The full sized module front right L-shaped side wall second portion **1028B** and the full sized module back right L-shaped side wall second portion **1030B** define a full sized module seventh upper raceway **1072**. The full sized module first, second and third upper raceways **1060**, **1062**, **1064** provide an access path to the full sized module planar member first opening **1010**. The full sized module fourth and fifth upper raceways **1066**, **1068** provide an access path to the full sized module planar member second opening **1012**. The full sized module sixth and seventh upper raceways **1070**, **1072** provide an access path to the full sized module planar member third opening **1014**.

As shown in FIG. 17B, the full sized module lower side walls include lower left side wall **1100**, a lower back side wall **1102**, a lower right side wall **1104**, a lower front medial side wall **1106**, lower outer medial U-shaped side wall **1108**, and a lower inner medial U-shaped side wall **1110**. The lower left side wall **1100**, lower back side wall **1102**, and lower right side wall **1104** are disposed along, and extend the length of, the full sized module planar member **1004** left side, back side, and right side, respectively. The lower front medial side wall **1106** is disposed at about the centerline **1001** and extends a short distance to the left and right of the centerline **1001**. The full sized module lower outer medial U-shaped side wall **1108** includes a left extension **1108A**, a base portion **1108B** and a right extension **1108C**. The full sized module lower outer medial U-shaped side wall left extension **1108A** is spaced from the full sized module lower left side wall **1100** by about twice the width of the third sized module bus planar member left extension **644**. The full sized module lower outer medial U-shaped wall left extension **1108A** begins at the front side and extends toward the back to a point spaced about the width of the third sized module bus planar member base portion **642** from the full sized module lower back side wall **1102**. The full sized module lower outer medial U-shaped wall right extension **1108C** is spaced from the lower right side wall **1104** by about twice the width of the third sized module bus planar member right extension **646**. The full sized module lower outer medial U-shaped wall right extension **1108C** begins at the front side and extends toward the back to a point spaced about the width of the third sized module bus planar member base portion **642** from the full sized module lower back side wall **1102**. The full sized module lower outer medial U-shaped wall base portion **1108B** extends left to right between the back side ends of the full sized module lower outer medial U-shaped wall left extension **1108A** and full sized module lower outer medial U-shaped wall right extension **1108C**.

The full sized module lower inner medial U-shaped side wall **1110** includes a left extension **1110A**, a base portion **1110B** and a right extension **1110C**. The full sized module lower inner medial U-shaped wall left extension **1110A** is spaced from the lower outer medial left extension side wall **1108A** by about twice the width of the second sized module bus planar member left extension **444**. The full sized module

lower inner medial U-shaped wall left extension **1110A** begins at the front side and extends toward the back to a point spaced about the width of the second sized module bus planar member base portion **442** from full sized module lower outer medial U-shaped side wall base portion **1108B**. The full sized module lower inner medial U-shaped side wall right extension **1110C** is spaced from the lower outer medial U-shaped side wall right extension **1108C** by about twice the width of the second sized module bus planar member left extension **446**. The full sized module lower inner medial U-shaped wall right extension **1110C** begins at the front side and extends toward the back to a point spaced about the width of the second sized module bus planar member base portion **442** from full sized module lower outer medial U-shaped wall base portion **1108B**. The full sized module lower inner medial U-shaped wall base portion **1110B** extends left to right between the back side ends of the full sized module lower inner medial U-shaped wall left extension **1110A** and full sized module lower inner medial U-shaped wall right extension **1110C**.

Thus, lower front medial side wall **1106** and the full sized module lower inner medial U-shaped side wall **1110** define a first lower raceway **1180**, the full sized module lower inner medial U-shaped side wall **1110** with the full sized module lower outer medial U-shaped side wall **1108** define a second lower raceway **1182**, and the full sized module lower outer medial U-shaped side wall **1108** along with the full sized module lower left side wall **1100**, full sized module lower back side wall **1102**, and full sized module lower right side wall **1104** define a third lower raceway **1184**.

Bus assembly mounting bosses **1090**, **1092**, similar to those described above, are disposed on the front side of the full sized module lower back side wall **1102**. Two more bus assembly mounting bosses **1094**, **1096** are disposed on the front side of the lower outer medial U-shaped side wall base portion **1108B**, and one bus assembly mounting boss **1098** is disposed on the front side of the full sized module lower inner medial U-shaped wall base portion **1110B**. Additionally, bus assembly bus clips **171** are disposed at the front side of the full sized module first, second, and third lower raceways **1180**, **1182**, **1184** and bus assembly alignment guides **1200** are disposed within the full sized module first, second, and third lower raceways **1180**, **1182**, **1184**.

A first sized module bus assembly **180** is disposed in the full sized module first lower raceway **1180** and is coupled to a collar assembly **190** being disposed through the full sized module planar member first opening **1010**. A second sized module bus assembly **440** is disposed in the full sized module second lower raceway **1182** and is coupled to a collar assembly **190** being disposed through the full sized module planar member second and/or third opening **1012**, **1014**. A third sized module bus assembly **640** is disposed in the full sized module third lower raceway **1184** and is coupled to a collar assembly **190** being disposed through the full sized module planar member fourth and/or fifth opening **1016**, **1018**. A plurality of spacers **1202** extend from the front side of the full sized module upper front side wall **1022** and the lower front medial side wall **1106** or as extensions of the lower side walls. The left and right sides of the full sized module housing assembly **1002** have a tongue and groove connector **700** as described above. As such, the full sized module may be coupled to another full sized jumper module **1000** or to a modular jumper assembly **100**.

The modular design allows for jumper assemblies of various sizes to be constructed. For example, the third sized module **106** may be omitted when the modular jumper assembly **100** is to be used with a two power line system in

conjunction with two adjacent circuit breakers. Alternatively, if the circuit breakers are spaced from each other, the jumper assembly **100** may be configured using a second sized module **104** and a third sized module **106**, as shown in FIG. **18**.

Additionally, the modular jumper assemblies **100** may be linked together in a multi-jumper assembly configuration **1248**. That is, as shown in FIG. **19**, a first modular jumper assembly **100A**, disposed on the left, may be coupled, both mechanically and electrically, to a second modular jumper assembly **100B**, or to full sized jumper module **1000**, disposed to the right. The modular jumper assemblies **100A**, **100B** are linked mechanically by the tongue-and-groove connector **700** disposed on the right side of the first modular jumper assembly **100A** and the left side of the second modular jumper assembly **100B**. That is, as described above, the right side of the first modular jumper assembly **100A** has the bisected groove portion of the tongue-and-groove connector **700** while the left side of the second modular jumper assembly **100B** incorporates the bisected tongue portion of the tongue-and-groove connector **700**.

The first and second modular jumper assemblies **100A**, **100B** are further coupled together by conductive bus straps **1250A**, **1250B**, **1250C**. The bus straps **1250A**, **1250B**, **1250C** are coupled to the collar assemblies **190** of each bus assembly **180**, **440**, **640**. On the second sized module and third sized module bus assemblies **440**, **640**, the bus straps **1250**, preferably, are coupled to a collar assembly **190** that is not coupled to a power line, e.g., power line **1260**. That is, as shown, power lines **1260**, **1262**, **1264** are coupled to the first modular jumper assembly **100A** first sized module bus assembly **180**, the second sized module bus assembly **440**, and the third sized module bus assembly **640**, respectively. Both the second sized module bus assembly **440** and the third sized module bus assembly **640** include a left side collar assembly **190** and a right side collar assembly **190**. The power line **1264** extends through the third sized module upper left raceway **850** and is coupled to the left collar assembly **190** on the third sized module bus assembly **640**. A third sized module bus strap **1250C** is coupled to the right collar assembly **190** on the first modular jumper assembly **100A** third sized module bus assembly **640** and to the left collar on the second modular jumper assembly **100A** third sized module bus assembly **640**. The third sized module bus strap **1250C** extends through the first modular jumper assembly **100A** third sized module upper right raceway **856** and through the second modular jumper assembly **100B** third sized module upper left raceway **850**. Similarly, the power line **1262** extends through the second sized module upper left raceway **840** and is coupled to the left collar assembly **190** on the second sized module bus assembly **440**. A second sized module bus strap **1250B** is coupled to the right collar assembly **190** on the first modular jumper assembly **100A** second sized module bus assembly **440** and to the left collar assembly **190** on the second modular jumper assembly **100A** second sized module bus assembly **440**. The second sized module bus strap **1250B** extends through the first modular jumper assembly **100A** second sized module upper right raceway **846** and through the second modular jumper assembly **100B** second sized module upper left raceway **840**.

Because the first sized module bus assembly **180** has only one collar assembly **190**, the power line **1260** and a first sized module bus strap **1250A** require a generally flat terminal end **1249** so that the single first sized module bus assembly collar **190** may accommodate both. The power line **1260** extends through the first modular jumper assembly

100A first sized module bus assembly upper left raceway **830**. The first sized module bus strap **1250A** extends through the first modular jumper assembly **100A** first sized module bus assembly upper right raceway **832** and through the second modular jumper assembly **100B** first sized module bus assembly upper left raceway **830**. Additional modular jumper assemblies **100** may be coupled to the first and second jumper assemblies **100A**, **100B** in a similar manner. Thus, one set of power lines may be couple to an infinite number of modular jumper assemblies **100**.

While specific embodiments of the invention have been described in detail, it will be appreciated by those skilled in the art that various modifications and alternatives to those details could be developed in light of the overall teachings of the disclosure. Accordingly, the particular arrangements disclosed are meant to be illustrative only and not limiting as to the scope of invention which is to be given the full breadth of the claims appended and any and all equivalents thereof.

What is claimed is:

1. A modular jumper assembly comprising:

- a first sized module having a housing assembly and a bus assembly;
- a second sized module having a housing assembly and a bus assembly;
- said first sized module and said second sized module structured to be coupled together;
- said first sized module housing assembly having a planar member and plurality of side walls, said planar member having at least one opening therethrough;
- said second sized module housing assembly having a planar member and a plurality of side walls, said planar member having at least one opening therethrough;
- said first sized module lower side walls forming a first sized module lower raceway;
- said second sized module lower side walls forming a second sized module lower raceway;
- said first sized module upper side walls and said second sized module upper side walls cooperating to form a plurality of upper access raceways;
- wherein said lower raceways are separated from said upper raceways by each said housing assembly planar member;
- whereby separate power lines may pass through a said separate upper raceways to be coupled to each bus assembly;
- wherein each bus assembly includes a planar member, and a collar assembly;
- each said planar bus planar member disposed in a lower raceway;
- each said collar assembly disposed in an upper raceway and coupled to said bus assembly planar member through said housing assembly planar member opening;
- wherein one or more upper raceways provide access to the first sized module bus assembly collar;
- one or more upper raceways provide access to the second sized module bus assembly collar;
- said first sized module upper raceways are separate from said second sized module upper raceways;
- wherein said first sized module raceways include a first sized module left access raceway, a first sized module right access raceway, and a first sized module back medial access raceway;

- said second sized module raceways include a left access raceway, a back side left access raceway, a back side right access raceway, and a right access raceway;
 - wherein said first sized module housing planar member has a generally rectangular shape;
 - said first sized module lower side walls include a first sized module lower left side wall, a first sized module lower back side wall, a first sized module lower right side wall and a first sized module lower front medial side wall;
 - said first sized module lower left side wall, first sized module lower back side wall and first sized module lower right side wall extending generally along the entire perimeter of said first sized module housing planar member;
 - said first sized module lower front side wall extending over the medial portion of said first sized module planar member front side;
 - whereby said first sized module lower side walls form a first sized module lower raceway;
 - said first sized module bus assembly planar member is disposed within said first sized module lower raceway;
 - wherein said second sized module housing planar member has a U- shape with a base portion, a left extension and a right extension;
 - said second sized module lower side walls include a second sized module left extension lower left side wall, a second sized module left extension lower right side wall, a second sized module right extension lower right side wall, a second sized module right extension lower left side wall, a second sized module base portion lower left side wall, a second sized module base portion lower right side wall, and a second sized module base portion lower back side wall;
 - whereby said second sized module lower side walls form a second sized module lower raceway; and
 - said second sized module bus assembly planar member is disposed within said second sized module lower raceway.
- 2.** The jumper assembly of claim **1**, wherein
- said first sized module upper side walls include a front side wall, a left back side wall and a right back side wall;
 - said first sized module upper side walls defining a left side opening between the front side wall and the left back side wall, a medial back opening between the left back side wall and the right back side wall, and a right side opening between the front side wall and the right back side wall.
- 3.** The jumper assembly of claim **2**, wherein
- said second sized module upper side walls include a left front side wall disposed at the front side of the left extension, a right front side wall disposed at the front of the right extension, a left medial side wall disposed between the base portion and the left extension, a right medial side wall disposed between the base portion and the right extension, a left back side wall disposed along the left back side of the base portion, a right back side wall disposed along the right back side of the base portion, a base portion left medial side wall extending front to back and a base portion right medial side wall extending front to back; and
 - said second sized module upper side walls defining a second sized module left extension left opening and a second sized module left extension right opening

27

between the left front side wall and the left medial wall, a second sized module right extension left and right openings between the right front side wall and the right medial wall, a second sized module base portion left side opening between the left medial side wall and the left back side wall, a left back opening between the left back side wall and the base portion left medial side wall, a medial back side opening and a medial front

5

28

side opening each between the base portion left medial side wall and the base portion right medial side wall, a right back opening between the base portion right medial side wall and the right back side wall, and a base portion right side opening between the right back side wall and the right medial side wall.

* * * * *