



US006618965B1

(12) **United States Patent**
Schultz et al.

(10) **Patent No.:** **US 6,618,965 B1**
(45) **Date of Patent:** **Sep. 16, 2003**

(54) **CUSHION STOP AND METHOD FOR ABSORBING BIDIRECTIONAL IMPACT OF SNOW PLOW BLADE TRIPPING**

(75) Inventors: **Lynn W. Schultz**, Campbellsport, WI (US); **Timothy G. Koch**, Theresa, WI (US); **Terry C. Wendorff**, Cedarburg, WI (US)

(73) Assignee: **Sno-Way International, Inc.**, Hartford, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/192,224**

(22) Filed: **Jul. 10, 2002**

(51) **Int. Cl.**⁷ **E01H 5/04**

(52) **U.S. Cl.** **37/232**

(58) **Field of Search** 37/232, 233, 264, 37/266, 268, 270, 235; 172/811, 815, 817, 684.5, 772, 772.5

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,014,289 A * 10/1961 Torrey 37/233
- 3,987,562 A 10/1976 Deen et al.
- 4,096,652 A * 6/1978 Raines et al. 37/231
- 4,304,057 A 12/1981 Watson et al.
- 4,307,523 A * 12/1981 Reissinger et al. 37/233
- 4,619,060 A 10/1986 Knowlton
- 4,658,519 A 4/1987 Quenzi
- 4,747,612 A 5/1988 Kuhn
- 4,962,599 A 10/1990 Harris
- 4,976,053 A 12/1990 Caley
- 5,036,608 A 8/1991 Ciula
- 5,044,098 A * 9/1991 Berghefer 37/232
- 5,050,321 A 9/1991 Evans
- 5,075,988 A 12/1991 Ciula
- 5,082,065 A 1/1992 Fletcher
- 5,111,603 A 5/1992 Knowlton et al.
- 5,191,729 A * 3/1993 Verseef 37/232

- 5,193,296 A 3/1993 Reilley
- 5,353,530 A 10/1994 Pieper
- 5,568,694 A 10/1996 Capra et al.
- 5,603,172 A * 2/1997 Maher 37/233
- 5,647,153 A 7/1997 Gervais
- RE35,700 E 12/1997 Watson et al.
- 5,697,172 A * 12/1997 Verseef 37/232
- 5,706,591 A 1/1998 Wissmiller
- 5,806,213 A 9/1998 Doornek et al.
- 5,806,214 A 9/1998 Behrens et al.
- 5,815,956 A * 10/1998 Lavin et al. 37/241
- 5,870,839 A 2/1999 Wissmiller
- 5,921,010 A * 7/1999 Schulte et al. 37/232
- 6,012,240 A 1/2000 Klug et al.
- 6,050,008 A 4/2000 Doornek et al.
- 6,073,371 A * 6/2000 Goos et al. 37/232
- 6,074,120 A 6/2000 Williams

(List continued on next page.)

OTHER PUBLICATIONS

Webpage from www.tocata.com, "Cut Your Plow Time in Half!", Back-Drage Plow Images, pp. 1-6, Dec. 27, 2000.


Primary Examiner—Victor Batson

(74) *Attorney, Agent, or Firm*—Reinhart Boerner Van Deuren S.C.

(57) **ABSTRACT**

An improved snow plow for use with light and medium duty trucks is disclosed which has an impact-absorbing mechanism which absorbs the shocks of both the tripping of the snow plow blade upon striking an object and the spring-biased return of the snow plow blade to its original position. Impact-absorbing members made of a polymeric material are mounted in pockets contained in the pivot support structure of the snow plow blade support structure, and portions of the snow plow blade frame impact the impact-absorbing members prior to the snow plow blade reaching either a tripped position or a trip return position. The impact-absorbing members are highly resistant to damage even when absorbing large shocks caused by substantial impacts, and are easily replaceable when their lifetime has been expended.

22 Claims, 19 Drawing Sheets





US 6,618,965 B1

Page 2

U.S. PATENT DOCUMENTS

6,134,813 A *	10/2000	Vickers	37/196	6,276,075 B1	8/2001	Kost et al.	
6,145,222 A	11/2000	Curtis		6,276,076 B1	8/2001	Quenzi et al.	
6,151,808 A	11/2000	Curtis		6,354,024 B1	3/2002	Kost et al.	
6,170,178 B1	1/2001	Christy		6,363,629 B1	4/2002	Curtis	
6,178,669 B1	1/2001	Quenzi et al.		6,381,880 B1	5/2002	Curtis	
6,209,231 B1	4/2001	Curtis		6,393,737 B2	5/2002	Quenzi et al.	
6,219,943 B1	4/2001	Kitchell		6,408,546 B2	6/2002	Curtis	
6,240,659 B1	6/2001	Curtis et al.		6,408,547 B1 *	6/2002	Jones et al.	37/232

* cited by examiner






FIG. 3




FIG. 4




FIG. 5




FIG. 6







FIG. 7








FIG. 12




FIG. 13

FIG. 15





FIG. 14






FIG. 23

FIG. 24







FIG. 16






FIG. 20

FIG. 21






FIG. 22






FIG. 27





FIG. 28






FIG. 33




FIG. 32




FIG. 31





FIG. 35

FIG. 34






FIG. 37




FIG. 38

**CUSHION STOP AND METHOD FOR
ABSORBING BIDIRECTIONAL IMPACT OF
SNOW PLOW BLADE TRIPPING**

**IDENTIFICATION OF RELATED PATENT
APPLICATIONS**

This application is related to four other concurrently filed patent applications, namely U.S. patent application Ser. No. 10/192336, entitled "Snow Plow Quick Connect/Disconnect Hitch Mechanism and Method," U.S. patent application Ser. No. 10/192225, entitled "Snow Plow Having an In-Line Frame Design and Method of Making the Same," U.S. patent application Ser. No. 10/192577, entitled "Spring Bracket Design and Method for Snow Plow Blade Trip Mechanism," U.S. patent application Ser. No. 10/192230, entitled "Back Blade Wearstrip for Efficient Backward Operation of Snow Plows and Method for Facilitating the Same," all assigned to the assignee of the present patent application, which four patent applications are hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to snow plows for use with light and medium duty trucks, and more particularly to an improved snow plow having an impact-absorbing mechanism which absorbs the shocks of both the tripping of the snow plow blade upon striking an object and the spring-biased return of the snow plow blade to its original position.

Once the exclusive domain of municipality-operated heavy trucks, snow plows have been used with light and medium duty trucks for decades. As would be expected in any area of technology which has been developed for that period of time, snow plows for light and medium duty trucks have undergone tremendous improvement in a wide variety of ways over time, evolving to increase both the usefulness of the snow plows as well as to enhance the ease of using them. The business of manufacturing snow plows for light and medium duty trucks has been highly competitive, with manufacturers of competing snow plows differentiating themselves based on the features and enhanced technology that they design into their products.

When plowing snow, a not infrequent occurrence is striking an object which is concealed beneath the snow. This occurs particularly often when plowing roads which are not paved, such as, for example, gravel roads or dirt roads. Since roads being plowed are typically frozen, it is common for an object of significant size to become frozen into the road. For example, medium size rocks or sticks which would not present a significant obstacle were they loose on the surface of the road can present a problem when they are frozen into the surface of the road and concealed beneath a layer of snow. In addition, when significant snow depth covers the area being plowed, the operator may miscalculate and drive the snow plow into a fixed obstacle such as a curb.

For this reason, snow plow blades have for some time been manufactured with a blade trip mechanism which allows the bottom of the blade to yield upon substantial impact. This is typically accomplished through the mounting of the snow plow blade on its support structure using a pivoting mechanism. The snow plow blade is mounted onto the support structure at a position between eight and sixteen inches above the ground in a manner which permits the bottom of the snow plow blade to pivot back when an object is struck. Simultaneously as the bottom of the snow plow blade pivots back, the top of the snow plow blade will pivot forward.

This movement between the normal plowing position of the snow plow blade to the position in which the bottom of the snow plow blade pivots fully backward is referred to as blade tripping. The movement of the snow plow blade from the normal plowing position to the tripped position is resisted by two or more strong trip springs which are mounted behind the snow plow blade, typically running from positions near the top of the snow plow blade to the snow plow blade support structure. Even when the snow plow blade is in its normal plowing position, the trip springs are under tension. Accordingly, it will be appreciated that when the bottom of the snow plow blade is forced backward, the trip springs will provide a strong resistance to the movement, tending to absorb some of the force of the impact of the snow plow blade with the object which has been struck.

When the force which has caused the snow plow blade to trip is removed, the trip springs will cause the snow plow blade to return to the normal plowing position, also referred to as the "trip return" position. Since it will be appreciated that it is highly undesirable for the snow plow blade to move from the normal plowing position when plowing snow, the trip springs are quite strong. This strength will result in a significant impact between the snow plow blade and its support structure when it is returned to the trip return position. This impact is typically metal on metal, and can over time result in damage to the snow plow blade and/or the supporting structure. In addition, if the snow plow blade strikes a fixed obstacle with sufficient force, the movement of the snow plow blade from the normal plowing position to the tripped position can also result in a metal on metal impact which can, over time, result in damage to the snow plow blade and/or the support structure.

It is accordingly the primary objective of the present invention that it provide a mechanism for absorbing a substantial part of the impact of the snow plow blade as it reaches its fully tripped position when the snow plow blade strikes an object with sufficient force to drive it to the fully tripped position. It is a closely related objective of the snow plow blade trip impact absorber of the present invention that it also provide a mechanism for absorbing a substantial part of the impact of the snow plow blade as it is returned to its trip return position by the force of the trip springs. It is a further related objective of the snow plow blade trip impact absorber of the present invention that it minimize or eliminate the metal-on-metal impact which would otherwise occur both at the fully tripped position of the snow plow blade and at the trip return position of the snow plow blade.

It is another objective of the snow plow blade trip impact absorber of the present invention that it not interfere with the tripping movement, either as the snow plow blade is tripping, or as it is returning to its normal plowing position, except as the snow plow blade approaches its extreme positions. It is yet another objective of the snow plow blade trip impact absorber of the present invention that the impact-absorbing members be made of a material which is highly resistant to damage even when absorbing large shocks caused by substantial impacts. It is a still further objective of the snow plow blade trip impact absorber of the present invention that the impact-absorbing members be easily replaceable when their lifetime has been expended.

The snow plow blade trip impact absorber of the present invention must also be of a construction which is both durable and long lasting, and it should also require little or no maintenance to be provided by the user throughout its operating lifetime. In order to enhance the market appeal of the snow plow blade trip impact absorber of the present

invention, it should also be of inexpensive construction to thereby afford it the broadest possible market. Finally, it is also an objective that all of the aforesaid advantages and objectives of the snow plow blade trip impact absorber of the present invention be achieved without incurring any substantial relative disadvantage.

SUMMARY OF THE INVENTION

The disadvantages and limitations of the background art discussed above are overcome by the present invention. With this invention, an impact-absorbing member is mounted at each pivot point used to support the snow plow blade from its support structure. The impact-absorbing member is mounted on the support structure, and is shaped such that it will be contacted by a part of the snow plow blade as the snow plow blade moves toward either its fully tripped position or its trip return position. The impact-absorbing member is made of a high density polymeric material such as polyurethane, which will absorb the impact to prevent or minimize metal-to-metal impact which would otherwise cause significant wear on the snow plow blade and/or its support structure.

In a typical embodiment, the snow plow blade is supported at two pivot points on the right and left sides of the snow plow blade by a swing frame. Trip springs mounted between the snow plow blade and the swing frame provide the tripping resistance force. The snow plow blade has a plurality of vertically oriented curved ribs which are connected between top and bottom plow frame members, and two of these ribs have apertures located between approximately eight and sixteen inches from the bottom of the snow plow blade. The swing frame has a pair of parallel blade pivot mounts located at each end thereof, which blade pivot mounts extend forwardly from a swing frame tube on which they are mounted.

Located near the front of each of the blade pivot mounts are apertures which are aligned in each pair of blade pivot mounts. Each pair of blade pivot mounts will receive a portion of one of the ribs on the snow plow frame which have the apertures therein, with one of the blade pivot mounts in each pair being located on either side of the rib to which that side of the swing frame is being mounted. A pin extends through the aligned apertures on each side of the snow plow blade to pivotally mount it on the swing frame.

Located between each pair of blade pivot mounts behind the rib of the snow plow blade received therein and in front of the swing frame tube is a pocket into which a cushion block will be placed. In the preferred embodiment, these pockets are further defined by additional support members which will prevent the cushion blocks from moving upwardly, downwardly, or rearwardly. Each cushion block is retained in its pocket between the pair of blade pivot mounts by a bolt which extends through apertures in the blade pivot mounts and the cushion block.

As mentioned above, the cushion blocks are made of a high density polymeric material such as polyurethane. The cushion blocks are configured so as to contact the ribs mounted to the blade pivot mounts before the snow plow blade reaches either the tripped position or the trip return position. The cushion blocks resemble a brick mounted in a vertical orientation, with the lower front having a corner removed therefrom. The polymeric material of which they are made is capable of absorbing a considerable impact, and is resilient and wear-resistant as well.

It may therefore be seen that the present invention teaches a mechanism for absorbing a substantial part of the impact

of the snow plow blade as it reaches its fully tripped position when the snow plow blade strikes an object with sufficient force to drive it to the fully tripped position. The snow plow blade trip impact absorber of the present invention also provides a mechanism for absorbing a substantial part of the impact of the snow plow blade as it is returned to its trip return position by the force of the trip springs. In doing so, the snow plow blade trip impact absorber of the present invention minimizes or eliminates the metal-on-metal impact which would otherwise occur both at the fully tripped position of the snow plow blade and at the trip return position of the snow plow blade.

The snow plow blade trip impact absorber of the present invention does not interfere with the tripping movement, either as the snow plow blade is tripping, or as it is returning to its normal plowing position, except as the snow plow blade approaches its extreme positions. The impact-absorbing members of the snow plow blade trip impact absorber of the present invention are made of a material which is highly resistant to damage even when absorbing large shocks caused by substantial impacts. In addition, the impact-absorbing members of the snow plow blade trip impact absorber of the present invention are easily replaceable when their lifetime has been expended.

The snow plow blade trip impact absorber of the present invention is of a construction which is both durable and long lasting, and which will require little or no maintenance to be provided by the user throughout its operating lifetime. The snow plow blade trip impact absorber of the present invention is also of inexpensive construction to enhance its market appeal and to thereby afford it the broadest possible market. Finally, all of the aforesaid advantages and objectives are achieved by the snow plow blade trip impact absorber of the present invention without incurring any substantial relative disadvantage.

DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention are best understood with reference to the drawings, in which:

FIG. 1 is a perspective view of a plow A-frame;

FIG. 2 is a partial cross-sectional view of the plow A-frame illustrated in FIG. 1;

FIG. 3 is a perspective view of a plow swing frame which will be pivotally mounted on the front end of the plow A-frame illustrated in FIGS. 1 and 2 and which will support a plow blade therefrom;

FIG. 4 is a cross-sectional view of the plow swing frame illustrated in FIG. 3;

FIG. 5 is a bottom plan view of the plow swing frame illustrated in FIGS. 3 and 4;

FIG. 6 is a perspective view of a pivoting lift bar which will be pivotally mounted at the rear end of the plow A-frame illustrated in FIGS. 1 and 2;

FIG. 7 is a perspective view of a hitch frame nose piece which will be mounted on a truck under the front bumper thereof;

FIG. 8 is a perspective view of a bellcrank which is used to operate the pivoting lift bar illustrated in FIG. 6;

FIG. 9 is a perspective view of a lift link which connects the bellcrank illustrated in FIG. 8 to the pivoting lift bar illustrated in FIG. 6;

FIG. 10 is a cutaway view of the various components of the snow plow frame assembled together, showing the hydraulic cylinder used to pivot the lift bar;

FIG. 11 is a perspective view of a plow blade from the rear side which will be mounted onto the plow swing frame illustrated in FIGS. 3 through 5;

FIG. 12 is an exploded view of the plow blade illustrated in FIG. 11, showing the assembly of a moldboard made of man-made material onto the plow blade frame;

FIG. 13 is a partial cross-sectional view of the top of the plow blade illustrated in FIG. 11, showing how the top of the moldboard is retained by the plow blade frame;

FIG. 14 is a partial cross-sectional view of the bottom of the plow blade illustrated in FIG. 11, showing how the bottom of the moldboard is retained by the plow blade frame and the plow cutting edge;

FIG. 15 is a partial cross-sectional view of a side edge of the plow blade illustrated in FIG. 11, showing how the side of the moldboard is retained by the plow blade frame;

FIG. 16 is a partial perspective view of the rear of the plow blade illustrated in FIG. 11, showing the installation of a wear strip onto the rear of the plow blade;

FIG. 17 is an exploded, partial cross-sectional view showing the assembly of the plow swing frame illustrated in FIGS. 3 through 5 onto the plow A-frame illustrated in FIGS. 1 and 2;

FIG. 18 is a partial cross-sectional view showing the plow swing frame and the plow A-frame illustrated in FIG. 17 assembled together;

FIG. 19 is a perspective view of a blade stop cushion;

FIG. 20 is a cross-sectional view from the side showing the installation of the blade stop cushion illustrated in FIG. 19 onto the plow swing frame, with the plow blade in its normal position as stopped by the blade stop cushion;

FIG. 21 is a cross-sectional view of the components illustrated in FIG. 20, from the top side thereof;

FIG. 22 is a cross-sectional view from the side similar to the view of FIG. 20, but with the plow blade in a rotated position as stopped by the blade stop cushion;

FIG. 23 is a perspective view of portions of the plow blade and the plow swing frame, showing the spring mounts on one side of the plow blade and the plow swing frame, and also showing two springs in phantom lines;

FIG. 24 is a partial rear plan view of the plow blade, the plow swing frame, and the spring mounts illustrated in FIG. 23;

FIG. 25 is a perspective view of an alternate embodiment similar to the view shown in FIG. 23, but with a single spring mount on one side of the plow blade and the plow swing frame, and also showing a spring in phantom lines;

FIG. 26 is a partial rear plan view of plow blade, the plow swing frame, and the spring mount illustrated in FIG. 25;

FIG. 27 is a cross-sectional view from the side of the assembled plow blade and the plow swing frame, showing the plow blade in its normal position;

FIG. 28 is a cross-sectional view from the side of the assembled plow blade and the plow swing frame, showing the plow blade in its rotated position;

FIG. 29 is a perspective view of the assembled snow plow of the present invention;

FIG. 30 is a top view of the assembled snow plow illustrated in FIG. 29;

FIG. 31 is a partial view from the top showing the hitch mounting mechanism on one side of the snow plow illustrated in FIGS. 29 and 30 prior to installation;

FIG. 32 is a partial view from the top showing the components illustrated in FIG. 31 in a mounted position;

FIG. 33 is a partial cross-sectional view from the front showing the components illustrated in FIGS. 28 and 29 in a mounted position with the retaining pin inserted;

FIG. 34 is a side view of the snow plow illustrated in FIGS. 29 and 30 as the hitch frame nose piece is brought into engagement with a mounting pin on the pivoting lift bar;

FIG. 35 is a schematic depiction of the engagement of the mounting pin with a slot in the hitch frame nose piece;

FIG. 36 is a side view similar to that of FIG. 34, with the pivoting lift bar beginning to pivot to bring the mounting pin into engagement with the slot in the hitch frame nose piece;

FIG. 37 is a side view similar to that of FIGS. 34 and 36, with the pivoting lift bar pivoted to bring the mounting holes in the pivoting lift bar into alignment with the mounting holes in the hitch frame nose piece; and

FIG. 38 is a perspective view of an alternate embodiment snow plow having blade shoes mounted thereupon.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The preferred embodiment of the present invention is illustrated in a series of figures, of which the FIGS. 1 through 9 and 11 are components of the snow plow which embodies the present invention. FIGS. 10, 12 through 24, and 27 through 29 illustrate the assembly of the snow plow embodying the present invention, and FIGS. 30 through 37 illustrate the manner in which the snow plow is attached to the hitch. Finally, FIGS. 25, 26, and 38 illustrate two alternate embodiments. The snow plow of the present invention includes five novel aspects: a novel frame design which has a lower profile and an enhanced linear strength which is attained by that design; a novel hitch quick connect, quick release design; a novel plow blade trip spring placement; a novel plow blade stop design which uses replaceable cushion stop blocks to absorb the impact of plow blade movement between extreme positions; and a novel back blade wearstrip which allows the plow blade to be used to plow backward as well as forward.

The first of these five novel aspects of the snow plow of the present invention resides in the innovative design of its two-piece frame. Referring first to FIGS. 1 and 2, the first of these two pieces, a plow A-frame 50, is illustrated. The plow A-frame 50 as illustrated in FIG. 2 has its front end shown at the left of FIG. 2 and its rear end shown at the right of FIG. 2, and is symmetric around an axis running from the front to the rear thereof. The plow A-frame 50 tapers from a narrower width at the front thereof to a wider width at the rear thereof.

The basic shape of the plow A-frame 50 is formed by a top plate 52 and a bottom plate 54, which are essentially parallel and are spaced apart from each other. The configurations of the top plate 52 and the bottom plate 54 as viewed from the top (or from the bottom) resemble a portion of the capital letter "A," with the portions of the sides of the "A" above the crossbar of the "A" being absent. There is a large aperture extending through each of the top plate 52 and the bottom plate 54 above the crossbar of the "A," which apertures resemble an isosceles trapezoid. The top plate 52 and the bottom plate 54 are preferably made of steel plate.

Mounted between the sides of the top plate 52 and the bottom plate 54 at the location of the crossbar of the "A" and extending rearwardly so as to resemble abbreviated legs of the "A" below the crossbar are two lugs 56 and 58 made of flat bar stock. The lugs 56 and 58 are also preferably made of steel, and are welded onto the sides of the top plate 52 and the bottom plate 54. The portion of the lug 56 which extends rearwardly from the top plate 52 and the bottom plate 54 has an aperture 60 extending therethrough, and the portion of the lug 58 which extends rearwardly from the top plate 52 and the bottom plate 54 has an aperture 62 extending there-through.

Portions of three sides of the top plate 52 are bent downwardly at a ninety degree angle to extend to the top of the bottom plate 54. Only one of these sides, a left side 64, is visible in FIGS. 1 and 2. The left side 64 of the top plate 52 extends from just in front of the lug 58, and extends approximately two-thirds of the way toward the front end of the plow A-frame 50. A right side of the top plate 52 (which is the mirror image of the left side 64 of the top plate 52) and a rear side of the top plate 52 extending between the lugs 56 and 58 are also bent downwardly at ninety degree angles to extend to the top of the bottom plate 54. These three sides are all welded to the bottom plate 54 to create a box-like structure. A rectangular plate 66 is located just in front of the isosceles trapezoid-shaped apertures in the top plate 52 and the bottom plate 54, and extends between the sides of the top plate 52 and the bottom plate 54. The rectangular plate 66 is also preferably made of steel, and all four sides of the rectangular plate 66 are welded onto the top plate 52 (including the left side 64 and right side thereof) and the bottom plate 54 to provide the fourth side of the box-like structure.

Extending from the sides of the lugs 56 and 58 are U-shaped swing cylinder mounts 76 and 78, respectively. The swing cylinder mounts 76 and 78 are also preferably made of steel, and are welded onto the lugs 56 and 58, respectively, with the legs of the U's of the swing cylinder mounts 76 and 78 being located on the top and the bottom of the plow A-frame 50. An aperture 80 is located in each leg of the U in the swing cylinder mount 76, and an aperture 82 is similarly located in each leg of the U in the swing cylinder mount 78.

Located between the rear of the top plate 52 at the location of the crossbar of the "A" and the rear of the bottom plate 54 at the location of the crossbar of the "A" are two lift cylinder mounts 84 and 86. The cylinder mounts 84 and 86 are parallel both to each other and to the plane which divides the plow A-frame 50 into left and right sides thereof. The cylinder mounts 84 and 86 each extend from slots 88 and 90, respectively, located in the crossbar of the "A" of the top plate 52 and slots 92 and 94, respectively, located in the crossbar of the "A" of the bottom plate 54. The cylinder mounts 84 and 86 are also preferably made of steel, and their ends are welded into the slots 88 and 90, respectively, in the top plate 52 and the slots 92 and 94, respectively, in the bottom plate 54. The cylinder mounts 84 and 86 each have an aperture 96 or 98, respectively, located therein which apertures 96 and 98 are coaxial.

Located at the top of the aperture in the "A" in the plow A-frame 50 are two parallel, spaced-apart, pivot mount plates 100 and 102. The pivot mount plates 100 and 102 are also preferably made of steel, and are welded onto the rectangular plate 66, the portion of the top plate 52 adjacent thereto, and the portion of the bottom plate 54 adjacent thereto. The pivot mount plates 100 and 102 are mounted on opposite sides of the centerline of the plow A-frame 50, and extend rearwardly and upwardly from the rectangular plate 66, and are beneath a portion of the bottom plate 54. Located near the rearmost and uppermost ends of the pivot mount plates 100 and 102 are apertures 104 and 106, respectively, which are coaxial.

Mounted near the front of the plow A-frame 50 are two hollow cylindrical swing frame pivots 108 and 110. The swing frame pivots 108 and 110 are centrally mounted near the front end of the plow A-frame 50 in apertures 112 and 114, respectively, which are located in the top plate 52 and the bottom plate 54, respectively. The swing frame pivots 108 and 110 are also preferably made of steel, and are

welded into the apertures 112 and 114, respectively. The swing frame pivots 108 and 110 are coaxial and are orthogonal to the top plate 52 and the bottom plate 54.

Located on the inside of each of the legs of the "A" of the plow A-frame 50 near to the top of the "A" are two support sides 116 and 118. The support sides 116 and 118 extend perhaps one-fourth of the way from the top of the opening of the "A" toward the crossbar of the "A." The ends of the support sides 116 and 118 oriented closest to the crossbar of the "A" extend between the top side of the top plate 52 and the bottom side of the bottom plate 54, and the support sides 116 and 118 increase in height above the top plate 52 and below the bottom plate 54 as the support sides 116 and 118 extend towards the front of the plow A-frame 50. The support sides 116 and 118 are preferably made of steel, and are welded to the top plate 52, the bottom plate 54, and the rectangular plate 66.

Four U-shaped ribs 120, 122, 124, and 126 extend between the support sides 116 and 118 and the swing frame pivots 108 and 110. The bases of the "U" of each of the U-shaped ribs 120, 122, 124, and 126 are much wider than the legs of the "U" are tall. The U-shaped ribs 120 and 122 are mounted on top of the top plate 52, and the bases of the "U's" of the U-shaped ribs 120 and 122 are located close adjacent the right and left sides, respectively, of the top plate 52. The U-shaped rib 124 and 126 are mounted on the bottom of the bottom plate 54, and the bases of the "U's" of the U-shaped ribs 124 and 126 are located close adjacent the right and left sides, respectively, of the bottom plate 54. In the preferred embodiment, the U-shaped rib 120, the support side 116, and the U-shaped rib 124 are manufactured as a single component, and likewise the U-shaped rib 122, the support side 118, and the U-shaped rib 126 are also manufactured as a single component.

One leg of the U-shaped rib 120 extends between the base of the "U" and the support side 116, and the other leg of the U-shaped rib 120 extends between the base of the "U" and the swing frame pivot 108. One leg of the U-shaped rib 122 extends between the base of the "U" and the support side 118, and the other leg of the U-shaped rib 122 extends between the base of the "U" and the swing frame pivot 108. One leg of the U-shaped rib 124 extends between the base of the "U" and the support side 116, and the other leg of the U-shaped rib 124 extends between the base of the "U" and the swing frame pivot 110. One leg of the U-shaped rib 126 extends between the base of the "U" and the support side 118, and the other leg of the U-shaped rib 126 extends between the base of the "U" and the swing frame pivot 110.

The U-shaped ribs 120, 122, 124, and 126 are preferably made of steel, and the U-shaped ribs 120 and 122 are welded onto the top plate 52, while the U-shaped ribs 124 and 126 are welded onto the bottom of the bottom plate 54. As mentioned above, the U-shaped ribs 120 and 124 may be made integrally with the support side 116, while the U-shaped rib 122 and 126 may be made integrally with the support side 118. The swing frame pivots 108 and 110 define an axis upon which a swing frame which will be described below in conjunction with FIGS. 3 through 5 will be mounted, and the area between the top plate 52 and the bottom plate 54 and in front of the rectangular plate 66 is the area in which the swing frame will be mounted.

Referring next to FIGS. 3 through 5, a swing frame 140 is illustrated which will be mounted as described above on the plow A-frame 50 (illustrated in FIGS. 1 and 2). The swing frame 140 is based upon a rectangular swing frame tube 142 having a hollow cylindrical pivot 144 extending

through the thinner cross section thereof at the midpoint of the length of the rectangular swing frame tube 142. The rectangular swing frame tube 142 has an aperture 146 located in the top side thereof and another aperture 148 located in the bottom side thereof. The apertures are closer to the rear side of the rectangular swing frame tube 142 than they are to the front side thereof. Both the rectangular swing frame tube 142 and the pivot 144 are preferably made of steel, and the pivot 144 is welded to the rectangular swing frame tube 142. The pivot 144 extends slightly above and below the top and bottom, respectively, of the rectangular swing frame tube 142.

A guide plate 150 extends from the rear of the rectangular swing frame tube 142. The guide plate 150 is shaped like an isosceles trapezoid with a low triangle mounted on the top thereof, with the base of the isosceles trapezoid mounted onto the rectangular swing frame tube 142. The width of the guide plate 150 is perhaps half of the length of the rectangular swing frame tube 142, and the guide plate 150 is centrally mounted both as to the length of the rectangular swing frame tube 142 and as to its height as well. The guide plate 150 is preferably also steel, and is welded onto the rectangular swing frame tube 142.

Mounted on the rear edge of the guide plate 150 is a guide/stop bar 152 which is made of a segment of flat stock which is wider than the height of the rectangular swing frame tube 142. The guide/stop bar 152 is bent to conform to the guide plate 150, and its ends contact the rear side of the rectangular swing frame tube 142. The guide plate 150 and the guide/stop bar 152 together form a T-shaped configuration in cross-section, as best shown in FIG. 4. The guide/stop bar 152 thus extends both slightly above and slightly below the rectangular swing frame tube 142, as is also best shown in FIG. 4. The guide/stop bar 152 is preferably made of steel, and is welded onto the guide plate 150, with the ends of the guide/stop bar 152 being welded onto the rear of the rectangular swing frame tube 142. When the swing frame 140 is mounted onto the plow A-frame 50 (illustrated in FIGS. 1 and 2), the guide/stop bar 152 will contact the rectangular plate 66 when the swing frame 140 is rotated between its extreme positions, with the guide/stop bar 152 thus acting to prevent rotation of the swing frame 140 in either direction beyond these positions.

Four triangular swing cylinder mounting plates 154, 156, 158, and 160 are mounted onto the rectangular swing frame tube 142 at positions approximately halfway between the center and the ends of the rectangular swing frame tube 142, and project rearwardly. The swing cylinder mounting plates 154 and 156 are mounted on the top of the rectangular swing frame tube 142 near the rear edge thereof and the right and left sides thereof, respectively. The swing cylinder mounting plates 158 and 160 are mounted on the bottom of the rectangular swing frame tube 142 near the rear edge thereof and the right and left sides thereof, respectively. The swing cylinder mounting plates 154, 156, 158, and 160 are preferably made of steel, and are welded onto the rectangular swing frame tube 142.

The swing cylinder mounting plates 154, 156, 158, and 160 each have a slot 162, 164, 166, or 168, respectively, cut therein to receive an end of the guide/stop bar 152. The ends of the guide/stop bar 152 fit into these slots 162, 164, 166, or 168 and are welded therein. Located in each of the swing cylinder mounting plates 154, 156, 158, and 160 near the rearmost corner thereof is an aperture 170, 172, 174, or 176, respectively. The apertures 170 and 174 are coaxial, and the apertures 172 and 176 are coaxial.

Four blade pivot mounts 178, 180, 182, and 184 are mounted on the rectangular swing frame tube 142 in spaced-

apart pairs located at each end thereof. The blade pivot mounts 178, 180, 182, and 184 have rectangular apertures 186, 188, 190, and 192, respectively, extending therethrough to receive therein the rectangular swing frame tube 142. The blade pivot mount 178 is mounted at the end of the rectangular swing frame tube 142 which will be on the right when the swing frame 140 is mounted on the plow A-frame 50 (illustrated in FIGS. 1 and 2), and the blade pivot mount 180 is spaced away from the blade pivot mount 178 on the rectangular swing frame tube 142.

Similarly, the blade pivot mount 184 is mounted at the end of the rectangular swing frame tube 142 which will be on the left when the swing frame 140 is mounted on the plow A-frame 50, and the blade pivot mount 182 is spaced away from the blade pivot mount 184 on the rectangular swing frame tube 142. The spacing between the blade pivot mount 178 and the blade pivot mount 180, and between the blade pivot mount 182 and the blade pivot mount 184 is sufficient to admit cushion stops which will be discussed below in conjunction with FIG. 19. The blade pivot mounts 178, 180, 182, and 184 are preferably also made of steel, and are welded onto the rectangular swing frame tube 142.

It should be noted that the blade pivot mounts 178, 180, 182, and 184 are identical in construction, with each extending forwardly in front of the rectangular swing frame tube 142 (as best shown in FIG. 4) and rearwardly and upwardly behind the rectangular swing frame tube 142. Located near the front of the blade pivot mounts 178, 180, 182, and 184 are apertures 194, 196, 198, and 200, respectively, which will be used to pivotally mount the snow plow blade (illustrated below in FIG. 11). The apertures 194, 196, 198, and 200 are coaxial. Located in the blade pivot mounts 178, 180, 182, and 184 intermediate the apertures 194, 196, 198, and 200, respectively, and the front of the rectangular swing frame tube 142 are apertures 202, 204, 206, and 208, respectively, which will be used to retain cushion stops which will be discussed below in conjunction with FIG. 19. The pairs of apertures 202 and 204, and 206 and 208 are coaxial.

As mentioned above, each of the blade pivot mounts 178, 180, 182, and 184 also extends rearwardly of the rectangular swing frame tube 142, resembling the profile of a vertical tail fin of a plane as best shown in FIG. 4. Mounted to each pair of each pair of the blade pivot mounts 178 and 180, and 182 and 184, are two trip spring brackets 210 and 212. The trip spring brackets 210 and 212 are preferably also made of steel, are generally oval in configuration, and are mounted with the wider sides being oriented between the left and right sides of the swing frame 140. The trip spring bracket 210 is welded onto the blade pivot mounts 178 and 180, and the trip spring bracket 212 is welded onto the blade pivot mounts 182 and 184. The trip spring bracket 210 has apertures 214 and 216 disposed near opposite ends thereof, and similarly the trip spring bracket 212 has apertures 218 and 220 disposed near opposite ends thereof.

Completing the swing frame 140 are two additional components which are used both to act as a stop for rotational movement of the plow blade (which will be discussed below in conjunction with FIG. 11) as well as to help define an enclosure for the cushion stops (which will be discussed below in conjunction with FIG. 18). A stop 222 is mounted at the top of, intermediate, and at the bottom of the blade pivot mounts 178 and 180. The stop 222 extends rearwardly from a point above the apertures 202 and 204, drops down in front of the rectangular swing frame tube 142, and extends rearwardly below the rectangular swing frame tube 142 to a point halfway between the front edge of the rectangular swing frame tube 142 and the pivot 144.

Similarly, a stop **224** is mounted at the top of, intermediate, and at the bottom of the blade pivot mounts **182** and **184**. The stop **224** extends rearwardly from a point above the apertures **206** and **208**, drops down in front of the rectangular swing frame tube **142**, and extends rearwardly below the rectangular swing frame tube **142** to a point halfway between the front edge of the rectangular swing frame tube **142** and the pivot **144**. The stops **222** and **224** are both preferably also made of steel, and are welded to the blade pivot mount pairs **178** and **180**, and **182** and **184**, respectively.

Referring next to FIG. 6, a lift bar **230** is illustrated which forms part of the hitch mechanism of the snow plow. The lift bar **230** has two lift bar support members **232** and **234**, which are located on the right and left sides, respectively, of the lift bar **230**. Each of the lift bar support members **232** and **234** has a configuration consisting of three segments: rear mounting supports **236** and **238**, respectively, which extend upward vertically; central support arms **240** and **242**, respectively, which extend forwardly and upwardly from the top of the rear mounting supports **236** and **238**, respectively; and front light bar supports **244** and **246**, respectively, which extend upwardly from the forwardmost and upwardmost ends of the central support arms **240** and **242**, respectively. The lift bar support members **232** and **234** are preferably made of steel plate.

Extending inwardly from the rear sides of rear mounting supports **236** and **238** are segments of angled stock **248** and **250**, respectively. It should be noted that the angle defined by each of the segments of angled stock **248** and **250** is less than ninety degrees, as, for example, approximately seventy degrees. The reason for this angle will become apparent below in conjunction with the discussion of FIGS. 31 and 32. The angled stock segments **248** and **250** are also preferably made of steel, and are welded onto rear mounting supports **236** and **238**, respectively, so that the rear mounting supports **236** and **238** and the angled stock segments **248** and **250** together form vertically-oriented channels which are essentially U-shaped. Referring for the moment to FIG. 1 in addition to FIG. 6, the space between the rear mounting support **236** and the angled stock segment **248** of the lift bar **230** is designed to admit the lug **56** of the plow A-frame **50** with space between the lug **56** and the inside of the angled stock segment **248**, and similarly the space between the angled stock segment **250**, and the rear mounting support **238** of the lift bar **230** is designed to admit the lug **58** of the plow A-frame **50** with space between the lug **58** and the inside of the angled stock segment **250**.

Referring again solely to FIG. 6, a rectangular reinforcing segment **252** (preferably also made of steel) is located at the bottom of the U-shaped channel formed by the rear mounting support **236** and the angled stock segment **248**, and is welded to the bottoms of the rear mounting support **236** and the angled stock segment **248**. Similarly, a rectangular reinforcing segment **254** (preferably also made of steel) is located at the bottom of the U-shaped channel formed by the rear mounting support **238** and the angled stock segment **250**, and is welded to the bottoms of the rear mounting support **238** and the angled stock segment **250**.

Not illustrated in the figures but used to reinforce the construction of the lift bar **230** are two additional rectangular reinforcing segments which are respectively located above the reinforcing segments **252** and **254**. On the right side of the lift bar **230**, the first of these additional reinforcing segments (preferably also made of steel) is located near the top of the U-shaped channel formed by the rear mounting support **236** and the angled stock segment **248**, and is

welded to the tops of the rear mounting support **236** and the angled stock segment **248**. Similarly, the other of these reinforcing segments (preferably also made of steel) is located at near the top of the U-shaped channel formed by the rear mounting support **238** and the angled stock segment **250**, and is welded to the tops of the rear mounting support **238** and the angled stock segment **250**.

Extending between the lift bar support members **232** and **234** are a larger diameter hollow round upper pin support tube **256** and a smaller diameter round light bar brace **258**. The upper pin support tube **256** and the light bar brace **258** are both also preferably made of steel. One end of the upper pin support tube **256** extends through an aperture **260** located in an intermediate position in the central support arm **240** of the lift bar support member **232**, and the other end of the upper pin support tube **256** extends through an aperture **262** located in an intermediate position in the central support arm **242** of the lift bar support member **234**. The ends of the upper pin support tube **256** are welded onto the central support arms **240** and **242**. One end of the light bar brace **258** is welded onto the lift bar support member **232** at the intersection of the central support arm **240** and the light bar support **244**, and the other end of the light bar brace **258** is welded onto the lift bar support member **234** at the intersection of the central support arm **242** and the light bar support **246**.

Two upper pin hanger plates **264** and **266** are mounted on the upper pin support tube **256** in spaced-apart fashion near the middle of the upper pin support tube **256**. The upper pin hanger plates **264** and **266** have apertures **268** and **270**, respectively, extending therethrough near one end thereof, and the upper pin support tube **256** extends through these apertures **268** and **270**. The upper pin hanger plates **264** and **266** are both also preferably made of steel, and are welded onto the upper pin support tube **256** in a manner whereby they are projecting forwardly. A tubular upper pin **272** extends through apertures **274** and **276** in the upper pin hanger plates **264** and **266**, respectively, near the other end thereof. The upper pin **272** is also preferably made of steel, and is welded onto the upper pin hanger plates **264** and **266**.

Located in the rear mounting support **236**, the angled stock segment **248**, the angled stock segment **250**, and the rear mounting support **238** near the bottoms thereof are apertures **278**, **280**, **282**, and **284**, respectively, which are aligned with each other and which together define a pivot axis about which the lift bar **230** will pivot when it is mounted onto the plow A-frame **50** (Illustrated in FIG. 1). Located in the rear mounting support **236**, the angled stock segment **248**, the angled stock segment **250**, and the rear mounting support **238** nearer the tops thereof than the bottoms thereof are apertures **286**, **288**, **290** (not shown in FIG. 6), and **292**, which are aligned with each other.

The apertures **286** and **288** define a first location into which a retaining pin (not shown in FIG. 6) will be placed to mount the snow plow of the present invention onto a truck, and the apertures **290** and **292** define a second location into which another retaining pin (not shown in FIG. 6) will be placed to mount the snow plow of the present invention onto the truck. Located in the light bar support **244** are three apertures **294**, and located in the light bar support **246** are three apertures **296**. The apertures **294** and **296** will be used to mount a light bar (not illustrated in FIG. 6) onto the lift bar **230**.

Referring now to FIG. 7, a hitch frame nose piece **300** which will be mounted onto a truck under the front bumper (not illustrated in FIG. 7) thereof is illustrated. The hitch

frame nose piece **300** has a square hitch frame tube **302** which is horizontally oriented. Four-hitch brackets **304**, **306**, **308**, and **310** are mounted on the square hitch frame tube **302** in spaced-apart pairs located nearer the ends of the square hitch frame tube **302** than the center thereof. The hitch brackets **304**, **306**, **308**, and **310** have square apertures **312**, **314**, **316**, and **318**, respectively, extending therethrough to receive therein the square hitch frame tube **302**. Both the square hitch frame tube **302** and the hitch brackets **304**, **306**, **308**, and **310** are preferably made of steel, and the hitch brackets **304**, **306**, **308**, and **310** are welded onto the square hitch frame tube **302**.

Referring for the moment to FIG. 6 in addition to FIG. 7, the space between the hitch bracket **304** and the hitch bracket **306** of the hitch frame nose piece **300** is designed to admit the rear mounting support **236** and the angled stock segment **248** of the lift bar **230**, and similarly the space between the hitch bracket **308** and the hitch bracket **310** of the hitch frame nose piece **300** is designed to admit the angled stock segment **250** and the rear mounting support **238** of the lift bar **230**. The hitch brackets **304**, **306**, **308**, and **310** have rectangular notches **320**, **322**, **324**, and **326**, respectively, cut into the front sides thereof.

Located in the hitch brackets **304**, **306**, **308**, and **310** in the bottoms of the rectangular notches **320**, **322**, **324**, and **326**, respectively, are slots **328**, **330**, **332**, and **334**, respectively. The slots **328**, **330**, **332**, and **334** have rounded bottoms, and are axially aligned. Also located in the hitch brackets **304**, **306**, **308**, and **310** above the tops of the rectangular notches **320**, **322**, **324**, and **326**, respectively, are apertures **336**, **338**, **340**, and **342**, respectively. The apertures **336**, **338**, **340**, and **342** are also axially aligned.

Unlike the hitch brackets **306** and **308** which are flat, the hitch brackets **304** and **310** have their forward-most portions flanged outwardly to act as guides to direct the lift bar **230** into engagement with the hitch frame nose piece **300**. Thus, the portions of the hitch brackets **304** and **310** at the front of the rectangular notches **320** and **326**, respectively, extend outwardly, both on the top of the rectangular notches **320** and **326** and on the bottom of the rectangular notches **320** and **326**. It should be noted that, if desired, the hitch brackets **304** and **310** may also be flat. The ramifications of having them flat instead of flanged will eliminate the utility of the right and left sides of the lift bar **230**.

The respective ends of the square hitch frame tube **302** are mounted onto mounting plates **344** and **346**. The mounting plates **344** and **346** are also preferably made of steel, and the ends of the square hitch frame tube **302** are welded onto the mounting plates **344** and **346**. Located in the mounting plates **344** and **346** are a plurality of apertures **348** and **350**, respectively, which will be used to mount the hitch frame nose piece **300** onto the frame of a truck (not shown in FIG. 7) using mounting brackets (not shown in FIG. 7) in a manner which is conventional.

Referring next to FIG. 8, a bellcrank **360** is illustrated. The bellcrank **360** has parallel, spaced apart triangular pivot plates **362** and **364**. One of the sides of the triangle is shorter than the other two in each of the pivot plates **362** and **364**. A gusset plate **366** is mounted between the pivot plates **362** and **364** with one side thereof near the shortest side of the triangle to support the pivot plates **362** and **364** in their spaced-apart configuration. In the preferred embodiment, both the pivot plates **362** and **364** and the gusset plate **366** are made of steel, and are welded together.

The pivot plates **362** and **364** have apertures **370** and **372**, respectively, located therein near a first corner of the triangle

which will be used to mount the bellcrank **360** for pivotal movement from the apertures **104** and **106** of the pivot mount plates **100** and **102**, respectively (illustrated in FIG. 1). The pivot plates **362** and **364** have apertures **374** and **376**, respectively, located therein near a second corner of the triangle which will be connected via the element to be discussed in FIG. 9 below to drive the upper pin **272** of the lift bar **230** (illustrated in FIG. 6). The pivot plates **362** and **364** have apertures **378** and **380**, respectively, located therein near the third corner of the triangle will be connected to a hydraulic cylinder (not shown in FIG. 9). The short side of the triangle is between the first and third corners of the triangle. The side of the gusset plate **366** adjacent this short side will act as a lift stop to limit pivotal movement of the gusset plate **366** when this side of the gusset plate **366** contacts the pivot mount plates **100** and **102** (illustrated in FIG. 1).

Referring now to FIG. 9, a lift link **390** is illustrated. The lift link **390** has parallel, spaced apart arms **392** and **394**. A gusset plate **396** is mounted between the arms **392** and **394** in their spaced-apart configuration. The side of the gusset plate **396** which is oriented toward one end of the arms **392** and **394** has a notch **398** cut therein. In the preferred embodiment, both the arms **392** and **394** and the gusset plate **396** are made of steel, and are welded together. The one end of the arms **392** and **394** have apertures **400** and **402**, respectively, located therein, and the other ends of arms **392** and **394** have apertures **404** and **406**, respectively, located therein.

Referring next to FIG. 10, the linkage used to attach the snow plow of the present invention to the hitch frame nose piece **300** is illustrated. The components which are linked together are the plow A-frame **50**, the lift bar **230**, the bellcrank **360**, and the lift link **390**. Accordingly, reference may also be had to FIGS. 1, 6, 8, and 9 as well as to FIGS. 31 and 32 in the following description of the interconnection of these components. The lift bar **230** is pivotally mounted on the plow A-frame **50** using two pins **408** and **410** (the pin **410** is not shown in FIG. 10) which are each of a length longer than distance between the opposite-facing sides of the pairs of the hitch brackets **304** and **306**, or **308** and **310** (illustrated in FIG. 7). The pins **408** and **410** are preferably made of steel.

In the preferred embodiment, a hollow cylindrical collar **409** (shown in FIGS. 31 and 32) having a setscrew **411** (also shown in FIGS. 31 and 32) is used with the pin **410** as a spacer. A similar collar which a setscrew (not shown in the drawings) is used with the pin **408** as a spacer. The collar **409** will be located intermediate the lug **58** on the plow A-frame **50** and the angled stock segment **250** on the lift bar **230**. The setscrew **411** on the collar **409** may be used to lock the collar **409** in place on the pin **410**. The other collar will be located intermediate the lug **56** on the plow A-frame **50** and the angled stock segment **248** on the lift bar **230**, with a setscrew in that collar being used to lock that collar in place on the pin **408**.

The pin **408** will thus extend sequentially through the aperture **278** in the rear mounting support **236** of the lift bar **230**, the aperture **60** in the lug **56** of the plow A-frame **50**, the collar, and the aperture **280** in the rear mounting support **238** of the lift bar **230**. The pin **408** will be retained in place by the setscrew on the collar, which will contact the pin **408** when it is screwed into the collar. Approximately equal lengths of the pin **408** extend outwardly beyond the rear mounting support **236** and the angled stock segment **248** at each end of the pin **408**. Alternately, the pin **408** may be welded in place on the rear mounting support **236** and the

angled stock segment **248** of the lift bar **230**, or C-clips (not shown herein) could be installed in annular groves (not shown herein) in the pin **408** at locations which correspond to the ends of the collar.

The pin **410** will thus extend sequentially through the aperture **282** in the angled stock segment **250** of the lift bar **230**, the collar **409**, the aperture **62** in the lug **58** of the plow A-frame **50**, and the aperture **284** in the rear mounting support **238** of the lift bar **230**. The pin **410** will be retained in place by the setscrew **411** on the collar **409**, which will contact the pin **410** when it is screwed into the collar **409**. Equal lengths of the pin **410** extend outwardly beyond the angled stock segment **250** and the rear mounting support **238** at each end of the pin **410**. Alternately, the pin **410** may be welded in place on the angled stock segment **250** and the rear mounting support **238** of the lift bar **230**, or C-clips (not shown herein) could be installed in annular groves (not shown herein) in the pin **410** at locations which correspond to the ends of the collar **409**.

It will thus be appreciated by those skilled in the art that the lift bar **230** is pivotally mounted onto the plow A-frame **50** using the pins **408** and **410**. When the snow plow of the present invention is mounted onto a vehicle using the hitch frame nose piece **300**, the ends of the pins **408** and **410** will be received in the pairs of slots **328** and **330**, and **332** and **334** in the hitch frame nose piece **300** (illustrated in FIG. 7). Thus, the pins **408** and **410** function both to pivotally mount the lift bar **230** onto the plow A-frame **50**, and to help to mount the snow plow onto the hitch frame nose piece **300**.

The bellcrank **360** is pivotally mounted on the plow A-frame **50** using two bolts **412** and two nuts **414**. The pivot plates **362** and **364** of the bellcrank **360** will fit outside of the pivot mount plates **100** and **102**, respectively. One of the bolts **412** will extend through the aperture **104** in the pivot mount plate **100** of the plow A-frame **50** and the aperture **370** in the pivot plate **362** of the bellcrank **360**, and one of the nuts **414** will be mounted on that bolt **412** to retain it in place. The other one of the bolts **412** will extend through the aperture **106** in the pivot mount plate **102** of the plow A-frame **50** and the aperture **372** in the pivot plate **364** of the bellcrank **360**, and the other one of the nuts **414** will be mounted on that bolt **412** to retain it in place.

The bolts **412** allow the bellcrank **360** to pivot on the plow A-frame **50**. In the preferred embodiment, a spacer and two washers (not shown) may be used with each of the bolts **412**, the spacer going through the apertures in the parts being pivotally joined and being longer than the combined thickness of the apertures in the parts, and a washer being located on either end of the spacer to facilitate free rotation of parts, here movement of the bellcrank **360** with reference to the plow A-frame **50**. It will be understood by those skilled in the art that a spacer and two washers will preferably be used at other points of relative movement between two elements of linkage of the snow plow described herein, although the spacer and two washers will not be specifically mentioned in conjunction with each of these pivoting connections made between two elements using a bolt. In addition, it will be understood by those skilled in the art that a pin retained by a cotter pin (not shown herein) could be used instead of a bolt and nut in many of the applications for a fastener used in the linkage discussed herein.

A hydraulic cylinder **416** is mounted at one end to the cylinder mounts **84** and **86** of the plow A-frame **50** using a bolt **418** which extends through the aperture **96** in the cylinder mount **84** and the aperture **98** in the cylinder mount **86**, with a nut **420** being used to retain the bolt **418** in place.

The other end of the hydraulic cylinder **416** drives the third corner of the triangular pivot plates **362** and **364** of the bellcrank **360**, with a bolt **422** extending between the aperture **378** in the pivot plate **362** of the bellcrank **360** and the aperture **380** in the pivot plate **364** of the bellcrank **360**. A nut **424** is used to retain the bolt **422** in place. The bolts **418** and **422** allow the hydraulic cylinder **416** to move as it drives the bellcrank **360**. Spacers (not shown herein) may be used on each side of the other end of the hydraulic cylinder **416** on the insides of the pivot plates **362** and **364** to center the hydraulic cylinder **416**.

The lift link **390** is used to connect the bellcrank **360** to pivot the lift bar **230**. A bolt **426** is used to connect the lift link **390** to the lift bar **230**, with the bolt **426** extending sequentially through the aperture **404** in the arm **392** of the lift link **390**, the upper pin **272** from the end extending through the upper pin hanger plate **264** to the end extending through the upper pin hanger plate **266** of the lift bar **230**, and the aperture **406** in the arm **394** of the lift link **390**. A nut **428** is used to retain the bolt **426** in place. The bolt **426** allows the lift link **390** to pivot on the lift bar **230**, and a spacer and two washers may also be used as mentioned hereinabove.

The second corner of the triangle formed by the pivot plates **362** and **364** of the bellcrank **360** drives the ends of the arms **392** and **394** of the lift link **390** which are not connected to the lift bar **230**. Two bolts **430** are used to connect the bellcrank **360** to the lift link **390**, with one of the bolts **430** also being used to mount a stand **432**. The stand **432** is described in U.S. Pat. No. 5,894,688, to Struck et al., which patent is assigned to the assignee of the inventions described herein. U.S. Pat. No. 5,894,688 is hereby incorporated herein by reference.

One bolt **430** (not shown) extends through the aperture **400** in the arm **392** of the lift link **390** and the aperture **374** of the pivot plate **362** of the bellcrank **360**, with a nut **434** being used to retain the first bolt **430** in place, and a spacer and two washers may also be used as mentioned hereinabove. The other bolt **430** extends sequentially through an aperture (not shown) in the upper portion of the stand **432**, the aperture **376** of the pivot plate **364** of the bellcrank **360**, and the aperture **402** in the arm **394** of the lift link **390**, with a nut **434** being used to retain the second bolt **430** in place. The second bolt **430** allows the lift link **390** to pivot on the bellcrank **360**, and a spacer and two washers may again be used as mentioned hereinabove. A removable pin (not shown) extending through an aperture near the top of the stand **432** and apertures located in the lift link **390** is used to link the stand **432** with the lift link **390**.

The hydraulic cylinder **416** is shown in FIG. 10 nearly in its fully retracted position. When the hydraulic cylinder **416** is fully extended, it will be appreciated by those skilled in the art that the lift bar **230** will rotate counterclockwise from the position in which it is shown in FIG. 10, and the stand **432** will be lowered to engage the ground (not shown) and thereby tend to lift the rear end of the plow A-frame **50** upwardly. It will also be appreciated that once the pins **408** and **410** are in engagement with the slots **328**, **330**, **332**, and **334** in the hitch brackets **304**, **306**, **308**, and **310**, respectively, of the hitch frame nose piece **300**, the hydraulic cylinder **416** may be used to align the apertures **286**, **288**, **290**, and **292** on the lift bar **230** with the apertures **336**, **338**, **340**, and **342**, respectively, in the hitch brackets **304**, **306**, **308**, and **310**, respectively, of the hitch frame nose piece **300**.

Turning next to FIGS. 11 through 16, a plow blade **440** and various aspects thereof are illustrated. The plow blade

440 has a frame which may be fundamentally thought of as a horizontal top plow frame member 442, a bottom plow frame member 444, and a plurality of vertical ribs 446, 448, 450 452, 454, 456, and 458 extending between the top plow frame member 442 and the bottom plow frame member 444. The top plow frame member 442 is made of a triangular tube as best shown in FIG. 13. The bottom plow frame member 444 is made of a three sided channel resembling a wide, inverted "U" with the tops of the legs of the "U" angling outwardly as best shown in FIG. 14.

The right side rib 446 is located on the right side of the plow blade 440, and the left side rib 458 is located on the left side of the plow blade 440. The ribs 448, 450, 452, 454, and 456 are located at evenly spaced intervals intermediate the right side rib 446 and the left side rib 458. Note that all of the ribs 446, 448, 450 452, 454, 456, and 458 have an arcuate shape when viewed from the side. The ribs 448, 450, 452, 454, and 456 all extend between the back side of the top plow frame member 442 and the top side of the bottom plow frame member 444, while the right side rib 446 and the left side rib 458 are mounted on the ends of the top plow frame member 442 and the bottom plow frame member 444, thereby overlying them as best shown in FIGS. 11 through 14. The top plow frame member 442, the bottom plow frame member 444, and the ribs 446, 448, 450 452, 454, 456, and 458 are all preferably made of steel, and are welded together.

Located in front of the ribs 450 and 454 are curved reinforcing plates 460 and 462 which serve to strengthen the ribs 450 and 454, which will be used to mount the plow blade 440 to the swing frame 140 (shown in FIGS. 3 through 5). The rib 450 has a mounting aperture 464 which extends therethrough and which is located near to the bottom end of the rib 450. Similarly, the rib 454 has a mounting aperture 466 which extends therethrough and which is located near to the bottom end of the rib 454. The curved reinforcing plates 460 and 462 are welded to the ribs 450 and 454, respectively, and to the top plow frame member 442 and the bottom plow frame member 444.

Four arcuate torsional stiffeners 468, 470, 472, and 474 are used to provide stiffness to the configuration of the plow blade 440. The torsional stiffener 468 extends from the bottom of the rib 448 to a position near the top of the right side rib 446. The torsional stiffener 470 extends from the bottom of the rib 450 to a position near the top of the rib 448. The torsional stiffener 472 extends from the bottom of the rib 454 to a position near the top of the rib 456. The torsional stiffener 474 extends from the bottom of the rib 456 to a position near the top of the left side rib 458. The torsional stiffeners 468, 470, 472, and 474 are also preferably made of steel, and are welded to other components in the plow blade 440.

Located on the left side of the right side rib 446 and on the right side of the left side rib 458 are curved support plates 476 and 478, respectively. The curved support plates 476 and 478 are recessed back from the front edges of the right side rib 446 and the left side rib 458, respectively, as best shown in FIG. 15 for the curved support plate 478. The curved support plates 476 and 478 are preferably also made of steel, and are welded to other components in the plow blade 440. The frontmost portions of the top plow frame member 442, the curved support plate 476, the rib 448, the curved reinforcing plate 460, the rib 452, the curved reinforcing plate 462, the rib 456, and the curved support plate 478 together define a curved support surface which will support a moldboard 480 thereupon. The right side rib 446 and the left side rib 458 extend slightly forward of the top plow frame member 442, the bottom plow frame member

444, and the ribs 448, 450, 452, 454, and 456, to thereby prevent the moldboard 480 from moving laterally. The moldboard 480 may be made of a man-made material such as polycarbonate, which may be clear, or other man-made materials such as ultra-high molecular weight (UHMW) polyethylene, or steel.

Extending across the front side of the top plow frame member 442 is a moldboard retainer strip 482 (best shown in FIG. 13), into which the top edge of the moldboard 480 fits and is retained. The moldboard retainer strip 482 is bent slightly toward the top plow frame member 442, which ensures that the top edge of the moldboard 480 fits snugly therein. Thus, it will be appreciated that the top, right, and left sides of the moldboard 480 are retained in position on the plow blade 440. The front of the bottom plow frame member 444 extends forwardly with respect to the curved moldboard support surface defined by the frontmost portions of the top plow frame member 442, the curved support plate 476, the rib 448, the curved reinforcing plate 460, the rib 452, the curved reinforcing plate 462, the rib 456, and the curved support plate 478. The bottom edge of the moldboard 480 comes just to the top of the bottom plow frame member 444, as best shown in FIG. 14.

The front of the bottom plow frame member 444 has a plurality of tapped apertures 484 located therein across the entire width thereof. A wearstrip 486 which is approximately the same width as the bottom plow frame member 444 has a matching plurality of apertures 488 located therein. The wearstrip 486 is preferably made of a high carbon steel such as AISI 1080 high carbon steel. The wearstrip 486 is bolted onto the bottom plow frame member 444 with a plurality of bolts 490. Alternately, if the apertures 484 are not tapped, bolts and nuts could be used to mount the wearstrip 486 onto the bottom plow frame member 444. optionally, the apertures 488 in the wearstrip 486 may be countersunk to recess the heads of the bolts 490 to the level of surface of the wearstrip 486. The front of the bottom plow frame member 444 is arranged and configured such that the wearstrip 486 will be mounted with its bottom edge angled forwardly with respect to the ground at angle of between approximately zero and forty-five degrees, with between approximately fifteen and thirty degrees being preferred, and an angle of approximately twenty-five degrees being most preferred.

The wearstrip 486 retains the bottom of the moldboard 480 in place, and it will at once be appreciated that the moldboard 480 may be replaced by merely removing the wearstrip 486, making the replacement substantially easier than in earlier snow plow blade designs. When the wearstrip 486 is bolted to the bottom plow frame member 444, it will be appreciated by those skilled in the art that it extends well below the bottom of the bottom plow frame member 444, so that as it is worn down, the bottom plow frame member 444 will not be damaged by contact with the ground.

Mounted on the back of the ribs 450 and 454, respectively, are two trip spring brackets 492 and 494. The trip spring brackets 492 and 494 are mounted approximately three-quarters of the way up the ribs 450 and 454, and are bent at a ninety degree angle, the bends being on an axis parallel to the lateral axis of the plow blade 440. The portions of the trip spring brackets 492 and 494 facing forward have notches 496 and 498, respectively, cut into them from the forwardmost edges thereof to the bends therein. The rear edges of the ribs 450 and 454 fit into the notches 496 and 498, respectively, and the portions of the spring brackets 492 and 494 facing rearwardly fit against the ribs 450 and 454, respectively. The spring brackets 492 and 494 are also preferably made of steel, and are welded onto the ribs 450

and 454, respectively. The rear-facing portion of the trip spring bracket 492 has two apertures 500 and 502 located therein on which lie on opposite sides of the rib 450, and the rear-facing portion of the trip spring bracket 494 has two apertures 504 and 506 located therein on which lie on opposite sides of the rib 454.

Located on the right side of the plow blade 440 in the right side rib 446 near the top thereof are two apertures 512. Similarly, located on the left side of the plow blade 440 in the left side rib 458 near the top thereof are two apertures 514. The apertures 512 and 514 serve to allow a marker bar or the like (not shown in FIGS. 11 through 13) to be attached to the plow blade 440.

Located at the rear of the plow blade 440 at the bottom thereof is a back blade wearstrip 516, which is mounted onto the bottom plow frame member 444 and extends substantially across the width of the plow blade 440. The back blade wearstrip 516 has a plurality of apertures 518 therein, and the bottom plow frame member 444 has matching tapped apertures 520 located in the rear-facing side thereof. Bolts 522 are used in the back blade wearstrip 516 to mount it onto the bottom plow frame member 444. Alternately, if the apertures 520 are not tapped, bolts and nuts could be used to mount the back blade wearstrip 516 onto the bottom plow frame member 444. Optionally, the apertures 518 in the back blade wearstrip 516 may be countersunk to recess the heads of the bolts 522 to the level of surface of the back blade wearstrip 516.

The back blade wearstrip 516 is permanently mounted at an optimum angle with respect to the ground which is defined by the angle of the rear side of the bottom plow frame member 444. The rear of the bottom plow frame member 444 is arranged and configured such that the back blade wearstrip 516 will be mounted with its bottom edge angled rearwardly with respect to the ground at angle of between approximately zero and forty-five degrees, with between approximately fifteen and thirty degrees being preferred, and an angle of approximately twenty-five degrees being most preferred. In the preferred embodiment, the wearstrip 486 and the back blade wearstrip 516 will be mounted at the same angles, but with the wearstrip 486 being angled forwardly and the back blade wearstrip 516 being angled rearwardly.

In the preferred embodiment, the back blade wearstrip 516 is made of an UHMW polyethylene material which is used instead of steel to decrease the weight of the plow blade 440. Alternately, the back blade wearstrip 516 could be made of rubber, urethane, steel, aluminum, or any other suitable material. Also, if desired, the back blade wearstrip 516 can be manufactured as multiple identical narrower segments if desired.

Turning next to FIGS. 17 and 18, and making reference also to FIGS. 1 and 3 through 5, the installation of the swing frame 140 onto the plow A-frame 50 is illustrated. The rectangular swing frame tube 142 of the swing frame 140 is inserted between the top plate 52 and the bottom plate 54 of the plow A-frame 50, with the pivot 144 of the swing frame 140 being brought into alignment intermediate the swing frame pivot 108 and the swing frame pivot 110 of the plow A-frame 50. A pivot pin 524 having a threaded distal end 526 is inserted sequentially through the swing frame pivot 108 in the plow A-frame 50, the pivot 144 in the swing frame 140, and the swing frame pivot 110 in the plow A-frame 50, and is retained in place by a locking nut 528. Washers (not shown herein) may also be used if desired.

Thus, the swing frame 140 is pivotally mounted on the plow A-frame 50, and it will be appreciated by those skilled

in the art that the movement of the swing frame 140 is limited by the guide/stop bar 152 on the swing frame 140 which interacts with the rectangular plate 66 on the plow A-frame 50 to limit movement to approximately thirty degrees either to the right or to the left. The swing frame 140 will be pivoted by two hydraulic cylinders, the installation of which will be described later in conjunction with FIG. 30.

It will be appreciated by those skilled in the art that the design of the plow A-frame 50 and the swing frame 140 represents a substantial improvement over past snow plow frame designs since their centerlines are in the same horizontal plane. Thus, rather than having the swing frame 140 being located on top of the plow A-frame 50, the swing frame 140 is located in the same plane as is the plow A-frame 50. In the preferred embodiment, the apertures 60 and 62 in the lugs 56 and 58, respectively, as well as the pins 408 and 410, are also in the same horizontal plane.

Moving now to FIG. 19, a cushion block 530 is illustrated which will be used to absorb the impact of the plow blade 440 (shown in FIG. 11) as it moves between its limits. Such movement of the plow blade 440 is caused by the plow blade 440 striking an object, and is designed to prevent damage to the snow plow by allowing the plow blade 440 to "trip," that is, for the bottom of the plow blade 440 to move rearwardly and the top of the plow blade 440 to simultaneously move forward, resulting in a rotation of the plow blade 440 around a horizontal axis. Such a rotation is inhibited by springs, which act as a shock absorbing mechanism, and which return the plow blade 440 to a normal or "trip return" position. The springs are quite strong, since they must prevent the plow blade 440 from rotating when it is plowing snow, and the metal-to-metal impacts of both a blade trip and a blade trip return can be substantial. The cushion block 530 is designed to cushion the impacts on both the blade trip and the blade trip return.

The cushion block 530 is brick-shaped with a corner cut off to create a beveled face 532, and will be mounted with the beveled face 532 of the cushion block 530 facing both forwardly and downwardly. Above the beveled face 532 of the cushion block 530 and facing forwardly when the cushion block 530 is mounted is a front face 534. Extending laterally through the cushion block 530 at a central location is an aperture 536, which will be used to mount the cushion block 530 on the swing frame 140 (shown in FIGS. 3 through 5). A cushion block 530 will be mounted between each pair of the blade pivot mounts 178 and 180, and 182 and 184. The apertures 202 and 204 in the blade pivot mounts 178 and 180, respectively, will align with the aperture 536 in one cushion block 530, and the apertures 206 and 208 in the blade pivot mounts 182 and 184, respectively, will align with the aperture 536 in the other cushion block 530.

Turning next to FIGS. 20 through 22, and referring also to FIGS. 3, 11, and 19, the installation of both the cushion blocks 530 and the plow blade 440 onto the swing frame 140 is illustrated. One of the cushion blocks 530 is shown installed between the blade pivot mounts 182 and 184, with a bolt 538 extending sequentially through the aperture 208 in the blade pivot mount 184, the aperture 536 in the cushion block 530, and the aperture 206 in the blade pivot mount 182, and with a nut 540 being used to retain the bolt 538 in place. The top and the rearwardly facing side of the cushion block 530 are retained in position by the stop 222 in the swing frame 140. The other cushion block 530 would be similarly mounted between the blade pivot mounts 178 and 180. Alternately, silicone adhesive (or any other suitable type of adhesive) may be used instead of bolts to retain the cushion blocks 530 in place. Another alternate retaining

mechanism would be to have the cushion blocks 530 fit in place with an interference fit.

The plow blade 440 will pivot around an axis defined by the mounting apertures 464 and 466 located in the ribs 450 and 454, respectively, and is mounted onto the swing frame 140 using two pins 542. One of the pins 542 extends sequentially through the aperture 200 in the blade pivot mount 184, the mounting aperture 466 in the rib 454, and the aperture 198 in the blade pivot mount 182. The other one of the pins 542 extends sequentially through the aperture 196 in the blade pivot mount 180, the mounting aperture 464 in the rib 450, and the aperture 194 in the blade pivot mount 180. Retaining pins 544 are installed into diametrically extending apertures located in the distal ends of each of the pins 542, and retain the pins 542 in place, thereby pivotally mounting the plow blade 440 on the swing frame 140.

The plow blade 440 thus may pivot between the trip return position shown in FIG. 20 and the tripped position shown in FIG. 22. It will be appreciated by those skilled in the art that when the plow blade 440 hits an object on the ground sufficiently hard, it will be driven to the tripped position shown in FIG. 22, at which time the portion of the rib 454 and also the portion of the rib 450 (which is not shown in FIG. 22) below the pins 542 will contact the beveled faces 532 of the cushion blocks 530, which will absorb the impact. Similarly, when the plow blade 440 is driven back into the trip return position shown in FIG. 20, the portion of the rib 454 and also the portion of the rib 450 (which is not shown in FIG. 22) above the pins 542 will contact the front face 534 of the cushion blocks 530, which will absorb the impact. In the preferred embodiment, the cushion blocks 530 are made of polyurethane, such as, for example, Quazi formulated methylenebis(diphenyl diisocyanate (MDI) polyester-based 93 durometer (Shore A scale) polyurethane, available commercially from Kryptonics, Inc. under the trademark Kap-tane 93 black.

Referring now to FIGS. 23 and 24, portions of the left side of the swing frame 140 and the plow blade 440 are illustrated in the blade trip return position. In the principal design described herein and shown in the drawings, four trip springs 550, 552, 554, and 556 (the first two of which are not shown in FIGS. 23 or 24) will be used to bias the plow blade 440 into the trip return position, and to resist movement of the plow blade 440 into the tripped position. Two trip springs 550 and 552, or 554 and 556 will be located on each side of the swing frame 140 and the plow blade 440. The trip springs 554 and 556 are shown in phantom lines in FIG. 23, with the trip spring 554 being connected between the aperture 218 of the trip spring bracket 212 and the aperture 504 of the trip spring bracket 494, and the trip spring 556 being connected between the aperture 220 of the trip spring bracket 212 and the aperture 506 of the trip spring bracket 494.

It will at once be appreciated by those skilled in the art that the trip springs 554 and 556 are located immediately on either side of the pivoting connection between the plow blade 440 and the swing frame 140. The trip springs 554 and 556 exert a force in a plane which is parallel to the plane of rotation defined by the pivoting connection between the plow blade 440 and the swing frame 140. Thus, the trip springs 554 and 556 do not pull in a direction which is even in part at an angle to the plane of rotation. This represents a major advantage over previously known snow plow trip spring mounting designs, which without exception are located at an angle to the plane of rotation defined by the pivoting connection between the plow blade and the swing frame of such previously known snow plows. The design of

the snow plow described herein utilizes all of the trip spring force for the blade trip operation, and thus provides more consistent blade trip operation as well as eliminating lateral trip spring force being exerted on the frame of the plow blade 440.

Turning next to FIGS. 25 and 26, an alternate embodiment is illustrated in which two trip springs are used to bias the plow blade 440 into the trip return position, and to resist movement of the plow blade 440 into the tripped position. One trip spring will be located on each side of the swing frame 140 and the plow blade 440 (the trip spring 560 on the left side of the swing frame 140 and the plow blade 440 is illustrated in the blade trip return position in FIG. 25). In the alternate embodiment illustrated in FIGS. 25 and 26, the design of the trip spring brackets which are mounted on the back of the ribs 450 and 454 differs from the design of the trip spring brackets 210 and 212 (shown in FIGS. 3 through 5). A trip spring bracket 562 having a single aperture 564 located therein is mounted on the blade pivot mounts 182 and 184. The trip spring bracket 562 is also preferably made of steel, and is welded onto the blade pivot mounts 182 and 184 with the aperture 564 being located between the blade pivot mounts 182 and 184. An identical spring trip bracket (not shown) would also be used on the right side of the swing frame 140.

In the alternate embodiment illustrated in FIGS. 25 and 26, the design of the trip spring brackets which are mounted on the back of the ribs 450 and 454 also differs from the design of the trip spring brackets 492 and 494 (shown in FIGS. 11 and 12). A trip spring bracket 566 is mounted approximately three-quarters of the way up the rib 454, and is bent at a ninety degree angle, the bend being on an axis parallel to the lateral axis of the plow blade 440. The portion of the trip spring bracket 566 facing forward has a notch 568 cut into it from the forwardmost edge thereof to the bend therein. The rear edge of the rib 454 fits into the notch 568, and the portion of the spring bracket 566 facing rearwardly fits against the rib 454. The rear-facing portion of the trip spring bracket 566 has an aperture 570 located therein which lies in the same plane as the rib 454. The spring bracket 566 is also preferably made of steel, and is welded onto the rib 454. An identical spring trip bracket (not shown) would also be used on the right side of the plow blade 440.

It will be appreciated by those skilled in the art that the trip spring 560 is located, and exerts a force, in the plane of rotation defined by the pivoting connection between the plow blade 440 and the swing frame 140. Thus, the trip spring 560 does not pull in a direction which is even in part at an angle to the plane of rotation (unlike previously known snow plow trip spring mounting designs). The alternate embodiment design of the snow plow of FIGS. 25 and 26 utilizes all of the trip spring force for the blade trip operation and provides more consistent blade trip operation as well as eliminating lateral trip spring force being exerted on the frame of the plow blade 440.

Referring next to FIGS. 27 and 28, the movement of the plow blade 440 between the trip return position shown in FIG. 27 and the fully tripped position shown in FIG. 28 is illustrated. From these figures (and also by looking at the orientation of the trip springs 550, 552, 554, and 556 in the top plan view of FIG. 30), it will be appreciated that the trip springs 550, 552, 554, and 556 (which are already under tension even in the trip return position) are all further stretched as the plow blade 440 moves from the trip return position to the tripped position, and thus serve to return the plow blade 440 to the trip return position when the force which caused the plow blade 440 to be tripped is removed.

Turning next to FIGS. 29 and 30, the assembly of several additional components is illustrated. First, all four of the trip springs 550, 552, 554, and 556 are illustrated as mounted onto the swing frame 140 and the plow blade 440. In addition, right and left light support towers 572 and 574, respectively, are mounted on the light bar supports 244 and 246, respectively, of the lift bar 230, and a light support bar 576 is mounted on the top ends of the right and left light support towers 572 and 574. Lights (not shown herein) would be mounted on the light support bar 576, in a manner well known to one skilled in the art.

In addition, right and left swing cylinders 578 and 580, respectively, are mounted between the plow A-frame 50 and the swing frame 140. The right swing cylinder 578 extends between the swing cylinder mount 76 on the plow A-frame 50 (where it is secured with a pin 582) and the swing cylinder mounting plates 154 and 158 on the swing frame 140 (where it is secured with a pin 584), and the left swing cylinder 580 extends between the swing cylinder mount 78 on the plow A-frame 50 (where it is secured with a pin 586) and the swing cylinder mounting plates 156 and 160 on the swing frame 140 (where it is secured with a pin 588). It will be understood that the pins 582, 584, 586, and 588 are all retained in place with cotter pins (not shown) as is well known to those skilled in the art.

Also not shown or discussed herein is the hydraulic system to operate the snow plow, the construction and operation of which is also well known to those skilled in the art. The right and left swing cylinders 578 and 580 are used to pivot the swing frame 140 and the plow blade 440 on the plow A-frame 50. The hydraulic cylinder 416 (shown in FIG. 10) is used to operate the stand 432 (also shown in FIG. 10) prior to the snow plow being mounted onto a truck, to facilitate the mounting of the snow plow onto the truck (as will become apparent below in conjunction with the discussion of FIGS. 31 through 37), and to raise and lower the plow A-frame 50, the swing frame 140, and the plow blade 440 after the snow plow has been mounted onto the truck. The hydraulic system for the snow plow may be mounted on the plow A-frame 50 at the front thereof, and if so mounted would have a hydraulic system cover 590 mounted thereupon to protect it, as shown in phantom lines.

Referring now to FIGS. 31 through 37, the operation of the mounting system used to mount the snow plow on the hitch frame nose piece 300 is shown. Referring first to FIGS. 31 through 33, in conjunction with FIGS. 1, 6, 7, and 10, the mechanism used to connect the snow plow to the hitch frame nose piece 300 is shown. In the discussion herein, all references are to the left side of the snow plow and the hitch frame nose piece 300, but those skilled in the art will understand that the principles thereof are equally applicable to the right side of the snow plow and the hitch frame nose piece 300.

The snow plow is mounted onto the hitch frame nose piece 300 with the plow standing on the stand 432 (shown in FIG. 10). In this position, the pin 410 which extends laterally at the rear of the snow plow on the left side will be at a height such than when the truck having the hitch frame nose piece 300 mounted thereon moves forward, the pin 410 will fit into the rectangular notches 324 and 326 at the front of the hitch brackets 308 and 310, respectively. The pin 410 is brought fully into the rectangular notches 324 and 326 by moving the truck forward. It will be noted that the flange at the front of the hitch bracket 310 as well as the approximately seventy degree bend in the angled stock segment 250 will assist in guiding the rear mounting support 238 and the angled stock segment 250 of the lift bar 230 into position intermediate the hitch bracket 308 and 310.

A this point, the hydraulic cylinder 416 (shown in FIG. 10) is actuated to begin to retract it to raise the stand 432 (also shown in FIG. 10), causing the pin 410 to drop into the slots 332 and 334 in the hitch brackets 308 and 310, respectively. By continuing to actuate the hydraulic cylinder 416 to retract it, the lift bar 230 is pivoted to bring the apertures 290 and 292 in the angled stock segment 250 and the rear mounting support 238, respectively, of the lift bar 230 into alignment with the apertures 340 and 342 in the hitch brackets 308 and 310, respectively, of the hitch frame nose piece 300. At this point, a retaining pin 592 having a handle 594 may be inserted sequentially through the aperture 342 in the hitch bracket 310, the aperture 292 in the rear mounting support 238, the aperture 290 in the angled stock segment 250, and the aperture 340 in the hitch bracket 308. The retaining pin 592 has an aperture 596 extending through near the distal end thereof, and a retaining spring pin 598 is used to retain the retaining pin 592 in place.

Referring next to FIGS. 34 through 37, the installation of the snow plow onto the hitch frame nose piece 300 mounted on a truck 600 (shown in phantom lines in FIG. 37) is illustrated. In FIG. 34, the snow plow is shown in its stored position, supported on the stand 432. In this position, the hydraulic cylinder 416 is in its fully extended position, and the rear end of the snow plow is raised. In this position, the pin 408 (not shown in FIGS. 34 through 37) at the right rear of the snow plow will be received by the rectangular notches 320 and 322 (not shown in FIGS. 34 through 37) at the front of the hitch brackets 304 and 306 (not shown in FIGS. 34 through 37), respectively, at the right side of the hitch frame nose piece 300. Similarly, the pin 410 at the left rear of the snow plow will be received by the rectangular notches 324 (not shown in FIGS. 34 through 37) and 326 at the front of the hitch brackets 308 (not shown in FIGS. 34 through 37) and 310, respectively, at the left side of the hitch frame nose piece 300. The truck 600 may be driven forward to fully engage the pins 408 and 410 with the hitch frame nose piece 300 as shown in FIG. 34.

Next, as shown in FIG. 36, as the hydraulic cylinder 416 begins to retract, the plow A-frame 50 will lower at the rear end thereof as the stand 432 begins to move upwardly relative to the plow A-frame 50. This causes the pin 408 (not shown in FIGS. 34 through 37) to drop into the slots 328 and 330 (not shown in FIG. 36) in the hitch brackets 304 and 306 (not shown in FIG. 36), respectively, at the right side of the hitch frame nose piece 300. Similarly, the pin 410 drops into the slots 332 (not shown in FIG. 36) and 334 in the hitch brackets 308 (not shown in FIG. 36) and 310, respectively, at the left side of the hitch frame nose piece 300. This initial retraction of the hydraulic cylinder 416 also causes the lift bar 230 to begin to rotate clockwise as viewed from the left side of the snow plow, as is evident from the movement of the right light support towers 572 and 576 and the light support bar 576.

As shown in FIG. 37, as the hydraulic cylinder 416 continues to retract, the lift bar 230 rotates clockwise until the light support towers 572 and 576 are oriented nearly vertically. As this further rotation occurs, the pin 408 (not shown in FIG. 37) remains in the slots 328 and 330 in the hitch brackets 304 and 306, respectively (none of which are shown in FIG. 37). Similarly, the pin 410 remains in the slots 332 (not shown in FIG. 37) and 334 in the hitch brackets 308 (not shown in FIG. 37) and 310, respectively. On the right side of the lift bar 230 and the hitch frame nose piece 300 (best shown in FIGS. 6 and 7), the apertures 286 and 288 in the rear mounting support 236 and the angled stock segment 248, respectively, of the lift bar 230 move into engagement

with the apertures **336** and **338** in the hitch brackets **304** and **306**, respectively, of the hitch frame nose piece **300**. Likewise, on the left side of the lift bar **230** and the hitch frame nose piece **300** (portions of which are also best shown in FIGS. **6** and **7**, respectively), the apertures **290** and **292** in the angled stock segment **250** and the rear mounting support **238**, respectively, of the lift bar **230** move into alignment with the apertures **340** and **342** in the hitch brackets **308** and **310**, respectively, of the hitch frame nose piece **300**.

At this point, one of the retaining pins **592** is inserted sequentially through the aperture **336** in the hitch bracket **304**, the aperture **286** in the rear mounting support **236**, the aperture **288** in the angled stock segment **248**, and the aperture **338** in the hitch bracket **306** (all of which are best shown in FIGS. **6** and **7**). The other one of the retaining pins **592** is inserted sequentially through the aperture **342** in the hitch bracket **310**, the aperture **292** in the rear mounting support **238**, the aperture **290** in the angled stock segment **250**, and the aperture **340** in the hitch bracket **308** (many of which are also best shown in FIGS. **6** and **7**). The retaining spring pins **598** are then inserted into the apertures **596** near the distal ends of the retaining pins **592** to retain the retaining pins **592** in place. At this point, the stand **432** may also be moved to a stowed position by disconnecting it from the lift link **390** (by removal of the pin (not shown)) and rotating it to the stowed position as is taught in U.S. Pat. No. 5,894,688, which was incorporated by reference above.

Also shown in FIG. **37** is a marker bar **602**, one of which may be mounted on each side of the plow blade **440** at the top thereof using the apertures **512** and **514** (not shown in FIG. **37**) on the right and left sides of the plow blade **440**, respectively, using bolts **604** and nuts (not shown herein). The marker bars **602** are used to allow the driver of the truck **600** to see where the front of the plow blade **440** is at any given time (since the driver may not be able to see the plow blade **440** over the hood of the truck **600** from the cab of the truck **600**).

Referring finally to FIG. **38**, a snow plow having an alternate embodiment is illustrated in which shoes **610** and **612** are installed on the plow blade **440**. The shoes **610** and **612** are designed to ride in sliding contact with the surface to be plowed, and are particular useful on gravel or during the spring when the ground may not be fully frozen. The shoes **610** and **612** are mounted to the plow blade **440** using shoe mounts **614** and **616**, respectively. The shoe mount **614** is mounted on the bottom plow frame member **444** near the right side thereof, and the shoe mount **616** is mounted on the bottom plow frame member **444** near the left side thereof. The shoe mounts **614** and **616** are preferably made of steel and are welded onto the bottom plow frame member **444**.

The shoes **610** and **612** are mounted on posts **618** and **620**, respectively, which posts **618** and **620** are received by the shoe mounts **614** and **616**, respectively. The shoes **610** and **612** are adjusted using a combination of washers and tubular spacers, which are placed on the posts **618** and **620** either below or above the shoe mounts **614** and **616** to adjust the height of the shoes **610** and **612**. The position of the shoes **610** and **612** relative to the plow blade **440** may be adjusted to adjust the height of the plow blade **440** relative to the surface to be plowed. This allows the degree to which the wearstrip **486** scrapes the surface to be plowed to be controlled. Retaining pins **622** and **624** are used on the posts **618** and **620**, respectively, to retain them in the shoe mounts **614** and **616**.

The shoes **610** and **612** are typically made out of cast iron. It should be noted that although the back blade wearstrip **516**

is not shown in the embodiment illustrated in FIG. **38**, it can in fact be used with the shoes **610** and **612**, so long as the shoe mounts **614** and **616** extend sufficiently back to clear the back blade wearstrip **516**. The shoes **610** and **612** have feet which are adapted to ride in sliding contact with the surface to be plowed. The position of the feet relative to the plow blade may be adjusted to adjust the height of the plow blade relative to the surface to be plowed. In this way, the degree to which the blade edge scrapes the surface to be plowed may be controlled.

It may therefore be appreciated from the above detailed description of the preferred embodiment of the present invention that it teaches a mechanism for absorbing a substantial part of the impact of the snow plow blade as it reaches its fully tripped position when the snow plow blade strikes an object with sufficient force to drive it to the fully tripped position. The snow plow blade trip impact absorber of the present invention also provides a mechanism for absorbing a substantial part of the impact of the snow plow blade as it is returned to its trip return position by the force of the trip springs. In doing so, the snow plow blade trip impact absorber of the present invention minimizes or eliminates the metal-on-metal impact which would otherwise occur both at the fully tripped position of the snow plow blade and at the trip return position of the snow plow blade.

The snow plow blade trip impact absorber of the present invention does not interfere with the tripping movement, either as the snow plow blade is tripping, or as it is returning to its normal plowing position, except as the snow plow blade approaches its extreme positions. The impact-absorbing members of the snow plow blade trip impact absorber of the present invention are made of a material which is highly resistant to damage even when absorbing large shocks caused by substantial impacts. In addition, the impact-absorbing members of the snow plow blade trip impact absorber of the present invention are easily replaceable when their lifetime has been expended.

The snow plow blade trip impact absorber of the present invention is of a construction which is both durable and long lasting, and which will require little or no maintenance to be provided by the user throughout its operating lifetime. The snow plow blade trip impact absorber of the present invention is also of inexpensive construction to enhance its market appeal and to thereby afford it the broadest possible market. Finally, all of the aforesaid advantages and objectives are achieved by the snow plow blade trip impact absorber of the present invention without incurring any substantial relative disadvantage.

Although an exemplary embodiment of the snow plow blade trip impact absorber of the present invention has been shown and described with reference to particular embodiments and applications thereof, it will be apparent to those having ordinary skill in the art that a number of changes, modifications, or alterations to the invention as described herein may be made, none of which depart from the spirit or scope of the present invention. All such changes, modifications, and alterations should therefore be seen as being within the scope of the present invention.

What is claimed is:

1. In a snow plow having a snow plow frame for detachable installation at the front of a vehicle, a blade mounting structure which is mounted on the snow plow frame and which supports a snow plow blade therefrom, said blade mounting structure comprising:

a blade support frame member having right and left ends, said blade support frame member being supported by

the snow plow frame which is detachably mounted at the front of the vehicle;

said blade support frame member including right and left blade mounting members which are fixedly mounted adjacent said right and left ends of said blade support frame member, respectively, said right and left blade mounting members each defining a pivot point;

a snow plow blade having a frame comprising vertically oriented right and left mounting ribs, each of said right and left mounting ribs defining a pivot point;

connecting members used to pivotally connect said right mounting rib to said right blade mounting member and said left mounting rib to said left blade mounting member, said snow plow blade being pivotable between a blade return position and a blade tripped position;

blade biasing members which urge said snow plow blade from said blade tripped position to said blade return position; and

a cushion stop mounted on each of said right and left blade mounting members, said cushion stops being contacted by said mounting ribs as they pivot prior to said snow plow blade reaching either said blade tripped position or said blade return position, said cushion stops thus absorbing a substantial portion of the impact force which would otherwise be transferred to said blade support frame member.

2. A blade mounting structure as defined in claim 1, wherein said blade support frame member is pivotally mounted from said snow plow frame.

3. A blade mounting structure as defined in claim 1, wherein said frame of said snow plow blade comprises:

- a top plow frame member;
- a bottom plow frame member; and
- a plurality of ribs extending between said top and bottom plow frame members, said right and left mounting ribs being two of said plurality of ribs.

4. A blade mounting structure as defined in claim 3, wherein said top and bottom plow frame members and said plurality of ribs are all made of steel and are welded together to form said frame of said snow plow blade.

5. A blade mounting structure as defined in claim 3, additionally comprising:

- a curved reinforcing plate mounted in front of each of said right and left mounting ribs, each of said right and left mounting ribs and its associated curved reinforcing plate together presenting a "T"-shaped cross section, said curved reinforcing plates being respectively welded to said right and left mounting ribs.

6. A blade mounting structure as defined in claim 1, wherein said pivot point in each of said right and left mounting ribs is defined by an aperture extending through each of said right and left mounting ribs.

7. A blade mounting structure as defined in claim 6, wherein said right and left blade mounting members each comprise:

- a first blade pivot mount which is mounted on said blade support frame member near an end thereof, said first blade pivot mount extending forwardly from said blade support frame member; and
- an aperture extending through said first blade pivot mount in the portion thereof which extends forwardly from said blade support frame member; wherein said aperture in said right mounting rib is connected to said aperture in said first blade pivot mount which is

mounted on said right end of said blade support frame member with one of said connecting members, and wherein said aperture in said left mounting rib is connected to said aperture in said first blade pivot mount which is mounted on said left end of said blade support frame member with another of said connecting members.

8. A blade mounting structure as defined in claim 7, wherein said right and left blade mounting members each additionally comprise:

- a second blade pivot mount which is mounted on said blade support frame member at a location which is adjacent said first blade pivot mount but is spaced away from said first blade pivot mount sufficiently far to admit one of said mounting ribs therebetween, said second blade pivot mount extending forwardly from said blade support frame member; and

- an aperture extending through said second blade pivot mount in the portion thereof which extends forwardly from said blade support frame member, said apertures in said first and second blade pivot mount members being aligned;

wherein said one of said connecting members extends sequentially through said aperture in said first blade pivot mount which is mounted near said right end of said blade support frame member, said aperture in said right mounting rib, and said aperture in said second blade pivot mount which is close adjacent said first blade pivot mount which is mounted near said right end of said blade support frame member, and wherein said other of said connecting members extends sequentially through said aperture in said first blade pivot mount which is mounted near said left end of said blade support frame member, said aperture in said left mounting rib, and said aperture in said second blade pivot mount which is close adjacent said first blade pivot mount which is mounted near said left end of said blade support frame member.

9. A blade mounting structure as defined in claim 8, wherein said connecting members each comprise:

- a pin; and
- a retaining member secured to said pin to retain said pin in place.

10. A blade mounting structure as defined in claim 8, wherein said first and second blade pivot mounts and said blade support frame member are all made of steel, and are welded together.

11. A blade mounting structure as defined in claim 8, additionally comprising;

- cushion stop pocket members located between said first and second blade pivot mounts, said first and second blade pivot mounts and said cushion stop pocket members together defining pockets for receiving and supporting said cushion stops therein.

12. A blade mounting structure as defined in claim 11, additionally comprising:

- retaining members for removably retaining said cushion stops in said pockets.

13. A blade mounting structure as defined in claim 12, wherein said cushion stops each have an aperture located therein, and wherein said first and second blade pivot mounts each have an additional aperture located therein, said apertures in said cushion stops and said additional apertures in said first and second blade pivot mounts being aligned when said cushion stops are located in said pockets, and wherein said retaining members comprise:

- a bolt which extends through said additional apertures in each pair of said first and second blade pivot mounts

and said aperture in said cushion stop to retain said cushion stop in said pocket; and

a nut threaded onto said bolt to retain said bolt in position.

14. A blade mounting structure as defined in claim 11, wherein said cushion stops are retained in said pockets with an adhesive.

15. A blade mounting structure as defined in claim 11, wherein said cushion stops are retained in said pockets in an interference fit.

16. A blade mounting structure as defined in claim 1, wherein said cushion stops each have two faces which will contact said mounting ribs, one of said faces of said cushion stops being contacted by said mounting ribs as said snow plow blade approaches said blade return position, the other of said faces of said cushion stops being contacted by said mounting ribs as said snow plow blade approaches said blade tripped position.

17. A blade mounting structure as defined in claim 1, wherein said cushion stops are made of polyurethane.

18. A blade mounting structure as defined in claim 15, wherein said cushion stops are made of Quazi formulated methylenebis(diphenyl diisocyanate (MDI) polyester-based polyurethane.

19. A blade mounting structure as defined in claim 1, wherein said cushion stops are made of a material having a hardness of approximately 93 durometer on the Shore A scale.

20. In a snow plow having a snow plow frame for detachable installation at the front of a vehicle, a blade mounting structure which is mounted on the snow plow frame and which supports a snow plow blade therefrom, said blade mounting structure comprising:

a blade support frame member having right and left ends, said blade support frame member being supported by the snow plow frame which is detachably mounted at the front of the vehicle;

a first pair of blade pivot mounts which is mounted on said blade support frame member near said right end thereof, said first pair of blade pivot mounts being spaced away from each other and extending forwardly from said blade support frame member, said first pair of blade pivot mounts each having an aperture extending therethrough in the portion thereof which extends forwardly from said blade support frame member;

a second pair of blade pivot mounts which is mounted on said blade support frame member near said left end thereof, said second pair of blade pivot mounts being spaced away from each other and extending forwardly from said blade support frame member, said second pair of blade pivot mounts each having an aperture extending therethrough in the portion thereof which extends forwardly from said blade support frame member;

a snow plow blade having a frame comprising a top plow frame member, a bottom plow frame member, and a plurality of vertically oriented curved ribs extending between said top and bottom plow frame members, said plurality of vertically oriented curved ribs including right and left mounting ribs which each have an aperture extending therethrough, which apertures in said right and left mounting ribs define a pivot point for said snow plow blade;

a first connecting member used to pivotally connect said right mounting rib intermediate said first pair of blade pivot mounts, and a second connecting member used to pivotally connect said left mounting rib intermediate

said second pair of blade pivot mounts, said snow plow blade thereby being pivotable between a blade return position and a blade tripped position;

blade biasing members which urge said snow plow blade from said blade tripped position to said blade return position; and

a cushion stop mounted on each of said first and second pairs of blade pivot mounts, said cushion stops being contacted by said mounting ribs as they pivot prior to said snow plow blade reaching either said blade tripped position or said blade return position, said cushion stops being made of a hard, resilient, durable man-made material to absorb a substantial portion of the impact force which would otherwise be transferred to said blade support frame member.

21. A blade mounting structure for supporting a snow plow blade, said blade mounting structure being mounted on a snow plow frame which may be installed at the front of a vehicle, said blade mounting structure comprising:

a blade support frame member with right and left ends which is supported from the snow plow frame which may be installed at the front of the vehicle;

right and left blade mounting members which are fixedly mounted adjacent said right and left ends of said blade support frame member, respectively;

right and left mounting ribs contained in a frame of a snow plow blade which are pivotally mounted to said right and left blade mounting members, respectively, said snow plow blade thereby being pivotable between a blade return position and a blade tripped position;

blade biasing members which urge said snow plow blade from said blade tripped position to said blade return position; and

cushion stops mounted on each of said right and left blade mounting members, said cushion stops being contacted by said mounting ribs and absorbing a substantial portion of the impact force from said mounting ribs as said snow plow blade pivots prior to reaching either said blade tripped position or said blade return position.

22. A method of supporting a snow plow blade on a blade mounting structure which is mounted on a snow plow frame which may be installed at the front of a vehicle, said method comprising:

supporting a blade support frame member having right and left ends from the snow plow frame which is installed at the front of the vehicle;

fixedly mounting right and left blade mounting members adjacent to said right and left ends of said blade support frame member, respectively;

pivotally mounting right and left mounting ribs contained in a frame of a snow plow blade to said right and left blade mounting members, respectively, said snow plow blade thereby being pivotable between a blade return position and a blade tripped position;

biasing said snow plow blade from said blade tripped position to said blade return position; and

mounting a cushion stop on each of said right and left blade mounting members, said cushion stops being contacted by said mounting ribs and absorbing a substantial portion of the impact force from said mounting ribs as said snow plow blade pivots prior to reaching either said blade tripped position or said blade return position.