



US006623056B1

(12) **United States Patent**
Wickson

(10) **Patent No.:** **US 6,623,056 B1**
(45) **Date of Patent:** **Sep. 23, 2003**

(54) **BAG HOLDER**

(76) **Inventor:** **Arthur L. Wickson**, 200 E. Fillmore
#223, Phoenix, AZ (US) 85004

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** **10/175,772**

(22) **Filed:** **Jun. 20, 2002**

Related U.S. Application Data

(60) **Provisional application No.** 60/303,747, filed on Jul. 6,
2001.

(51) **Int. Cl.⁷** **B65D 33/06**

(52) **U.S. Cl.** **294/158; 294/137; 294/142;**
383/13

(58) **Field of Search** 294/137, 142,
294/158, 159, 170, 171; 16/406, 422, 425;
383/6, 13, 25, 26

(56) **References Cited**

U.S. PATENT DOCUMENTS

D352,902 S * 11/1994 Halverson D9/455

D359,235 S * 6/1995 Kennedy et al. D9/434
5,697,661 A * 12/1997 Robinson et al. 294/142
5,904,388 A * 5/1999 Seibel 294/163
6,347,822 B1 * 2/2002 Miller, Jr. 294/158

FOREIGN PATENT DOCUMENTS

BE 505660 * 1/1953 294/137
FR 2632-933 * 12/1989 294/137
FR 2652-563 * 4/1991 294/137


* cited by examiner

Primary Examiner—Dean J. Kramer
(74) *Attorney, Agent, or Firm*—Parsons & Goltry; Michael
W. Goltry; Robert A. Parsons

(57) **ABSTRACT**

A bag holder includes a handle having ends and a bag catch
having ends. The ends of the bag catch are attached to the
ends of the handle. The handle and the catch define an
opening of the bag holder, and the handle is severed between
its ends defining opposing free ends and an end gap ther-
ebetween.

12 Claims, 2 Drawing Sheets






FIGURE 1




FIGURE 2





FIGURE 4

1

BAG HOLDER**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the benefit of U.S. Provisional Application Ser. No. 60/303,747, filed Jul. 6, 2001.

FIELD OF THE INVENTION

This invention relates to apparatus and methods for holding and transporting handled objects.

BACKGROUND OF THE INVENTION

Carrying multiple handled objects such as bags is difficult, especially for the elderly and those having weak or injured hands. One of the most common situations in which people usually carry multiple bags by hand is when shopping for groceries, where it is common to see people carrying multiple plastic grocery bags by hand to and from their vehicles. Although carrying multiple grocery bags is a persistent problem for many, the art is want of a simple and inexpensive device that is capable of aiding people in comfortably and safely carrying multiple grocery bags. Given this deficiency in the art, the need for certain new and useful improvements is evident.

SUMMARY OF THE INVENTION

The above problems and others are at least partially solved and the above purposes and others realized in a new and improved bag holding that includes a handle having ends and a bag catch having ends. The ends of the bag catch are attached to the ends of the handle. The handle and the catch define an opening of the bag holder, and the handle is severed between its ends defining opposing free ends and an end gap therebetween. The handle has an outer edge and an opposing inner edge facing the opening. The end gap severs the outer and inner edges of the handle. The catch is inwardly flexed maintaining the free ends of the handle in an engaged or abutting state. Preferably, a first recess is disposed at one of the free ends of the handle between the outer and inner edges of the handle, and an opposing second recess is disposed at the other of the free ends of the handle between the outer and inner edges of the handle. A support is capable of being disposed between the free ends of the handle and secured by and between the opposing first and second recesses. In another embodiment, the invention incorporates a support disposed between the free ends of the handle and secured by and between the first and second recesses. An outwardly facing first beveled edge is carried by one of the free ends of the handle at the outer edge of the handle, and an opposing outwardly facing second beveled edge is carried by the other of the free ends of the handle at the outer edge of the handle. The second beveled edge is the mirror image of the first beveled edge.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring to the drawings:

FIG. 1 is a side elevation of a bag holder constructed in accordance with the teachings of the invention, the bag holding including a catch and an attached handle, which is severed defining free ends and an end gap therebetween;

FIG. 2 is a perspective view of the bag holder of FIG. 1;

FIG. 3 illustrates the bag holder of FIG. 1 shown as it would appear in use securing handles of bags for transport; and

2

FIG. 4 is a perspective view of another embodiment of a bag holder constructed in accordance with the teachings of the invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Turning now to the drawings, in which like reference characters indicate corresponding elements throughout the several views, attention is first directed to FIG. 1 in which is seen a bag holder, embodying the principle of the instant invention, generally indicated by the reference character **10** including a handle **11** having ends **12,13** and a bag catch **14** having ends **15,16**. Ends **15,16** of catch **14** are attached to ends **12,13**, respectively, of handle **11**. Handle **11** and catch **14** make up a semi-circular body, and catch **14** opposes and underlies handle **11**. Catch **14** is considered the lower member of bag holder **10**, and handle **11** is considered the upper member of bag holder **10**. Inner edges **21,22** of handle **11** and catch **14**, respectively, define an opening **20** of bag holder **10**. Handle **11** is severed between ends **12,13** defining opposing free ends **30,31** of handle **11** and an end gap **32** or channel therebetween. Handle **11** has an outer edge **33** opposing its inner edge **21**, which faces and partially defines opening **20**. End gap **32** severs outer and inner edges **33,21** of handle **11**.

In one embodiment, catch **14** is inwardly flexed maintaining free ends **30,31** of handle **11** in an engaged or abutting state. In another embodiment of the invention, the inwardly flexed nature of catch **14** is provided to maintain free ends **30,31** in close proximity to one another or otherwise in a confronting state, rather than engaged to one another. Preferably, a recess **40** is formed into and disposed at free end **30** of handle **11** between outer and inner edges **33,21**, and an opposing recess **41** is formed into and disposed at free end **31** handle **11** between outer and inner edges **33,21**. Recess **41** is the mirror image of recess **40**. Recesses **40,41** together define an engagement opening **42** of bag holder **10**.

Bag holder **10** is formed of a flexibly rigid material or combination of materials, whether plastic, a selected metal, a selected metal composite, etc., and although is preferably integrally formed such as through molding or machining can be formed as an assembly of two or more attached parts, if desired. Welding, adhesive, screws, rivets or other suitable fastening structure can be used for attaching together the various parts of bag holder **10** if so constructed. The flexibly rigid character of bag holder **10** permits free ends **30,31** to be moved apart in response to a forcible impulse applied to bag holder **10**, such as at handle **11**. By releasing such a forcible impulse, bag holder **10** will resume its original shape, and the material or materials used in the construction of bag holder **10** permit it to carry out this function.

A support, such as an elongate rod, is capable of being disposed between free ends **30,31** of the handle and secured by and between recesses **40,41**. In another embodiment, the invention incorporates a support, which is denoted in FIG. 2 at **50**. In this embodiment, support **50** is an elongate rod supported by and extending from wall or shelving structure. As illustrated, support **50** is disposed between free ends **30,31** of handle **11** and secured by and between recesses **40,41**, which arrangement causes bag holder **10** to be maintained and supported by support **50**. To engage bag holder **10** to support **50**, a free end of support **50** can be forcibly inserted through support opening **42**. Forcibly drawing bag holder **10** away from support **50** disengages bag holder **10** from support **50**. Another way to engage bag

3

holder **10** with support is to apply a forcible impulse to bag holder **10**, such as at handle **11**, spreading free ends **30,31** apart, positioning support **50** between free ends **30,31** disposing recesses **40,41** on either side of support **50** and then releasing the forcible impulse against bag holder **10** to cause ends **30,31** to come together disposing support **50** at support opening **42** and causing recesses **40,41** to engage and secure support **50**. Removal of bag holder **10** from support **50** can be accomplished by reversing this procedure. It will be appreciated that many such bag holders can be secured to support **50** for storage purposes, in which removal of each of the bag holders is easily accomplished as herein explained.

With continuing reference to FIG. 1, free end **30** is formed with an outwardly facing beveled edge **55**, which is disposed at outer edge **33** of handle **11**, and free end **31** is formed with an outwardly facing beveled **56**, which is also disposed at outer edge **33** of handle **11**. Beveled edge **56** is the mirror image of beveled edge **55**, and beveled edges **55,56** cooperate and form a pocket of funnel at and leading into end gap **32**.

Bag holder **10** has many uses. For example, end gap **32** can be used to pass therethrough the handles **61** of various and numerous types of bags **60** as shown in FIG. 3, which handles **61** then rest against and are secured by catch **14** or the lower member of bag holder **10**. Bags **60** are representative of plastic grocery bags, which are ubiquitous in modern society. A person can then take up handle **11** by hand and carry multiple bags at one time. The pocket formed by beveled edges **55,56** serves to guide the handles of bags **60** into end gap **32**. Bags **60** can be removed by passing the handles thereof through end gap **32**, removing bags **60** from bag holder **10**. Other uses not limited to carrying bags will readily occur to those skilled in the art. Finger gripping recesses can be included at inner edge **21** of handle **11** for increased comfort and gripping ability, if desired. An embodiment of the invention constitutes bag holder **10** and bags **60** having handles **61**, in which handles **61** of bags **60** are secured by catch **14**. So secured by catch **14**, a further advantage of the invention is that bags so held by bag holder **10** help prevent items contained within the bags from falling out, such in a car during transport home from the grocery store, etc.

Turning back to FIGS. 1 and 2, indicia **70** are imparted to handle **11**. Indicia **70** can be applied in any number of ways, such as by printing or etching. Indicia **70** can be adhesively attached or attached by means of lamination. Indicia **70** can also be embedded into handle **11**, in which handle **11** would, of course, need to be transparent or at least partially transparent to allow indicia **70** to be visually perceived. Indicia **70** can be imparted to an inserts disposed in slots formed into handle **70**. Those of ordinary skill will appreciate that indicia **70** can be applied in many ways. Indicia **70** are advertising or sensible indicia such as logo type indicia, logo wording, etc., for the purpose of conveying an advertising or other message or impression. Although indicia **70** are-disposed at handle **11** as illustrate, indicia can be imparted to bag holder **10** at other locations.

Reference is now made to FIG. 4, in which there is seen an alternate embodiment of a bag holder generally designated by the reference character **80**. In common with the previously described embodiment **10**, the immediate embodiment designated **80** shares handle **11** and catch **14** and the various structure components thereof, and differs only in the enlarged or cylindrical gripping portion **81** disposed at inner edge **21** of handle **11** providing enhanced hand-gripping comfort. The operation of bag holder **80** is

4

identical to bag holder **10**. Finger gripping recesses can be included at gripping portion **18** for increased comfort and gripping ability, if desired.

The present invention is described above with reference to preferred embodiments. However, those skilled in the art will recognize that changes and modifications may be made in the described embodiments without departing from the nature and scope of the present invention. Various changes and modifications to the embodiments herein chosen for purposes of illustration will readily occur to those skilled in the art. To the extent that such modifications and variations do not depart from the spirit of the invention, they are intended to be included within the scope thereof.

Having fully described the invention in such clear and concise terms as to enable those skilled in the art to understand and practice the same, the invention claimed is:

1. Apparatus comprising:

a handle having ends;

a catch having ends;

the ends of the catch attached to the ends of the handle;

an opening defined by the handle and the catch;

the handle severed between the ends defining opposing free ends and an end gap therebetween;

a first recess disposed at one of the free ends of the handle; and

an opposing second recess disposed at the other of the free ends of the handle.

2. Apparatus of claim 1, wherein the catch is inwardly flexed maintaining the free ends of the handle in an engaged state.

3. Apparatus of claim 1, further comprising:

the handle having an outer edge and an opposing inner edge facing the opening;

the end gap severing the outer and inner edges of the handle;

an outwardly facing first beveled edge carried by one of the free ends of the handle at the outer edge of the handle; and

an opposing outwardly facing second beveled edge carried by the other of the free ends of the handle at the outer edge of the handle;

wherein the second beveled edge is the mirror image of the first beveled edge.

4. Bags having handles secured by the catch of the apparatus of claim 1.

5. Assembly comprising:

an apparatus comprising:

a handle having ends;

a catch having ends;

the ends of the catch attached to the ends of the handle;

an opening defined by the handle and the catch;

the handle severed between the ends defining opposing free ends and an end gap therebetween;

a first recess disposed at one of the free ends of the handle;

an opposing second recess disposed at the other of the free ends of the handle; and

a support element disposed between the free ends of the handle secured by and between the first and second recesses.

6. Assembly of claim 5, wherein the catch is inwardly flexed maintaining the free ends of the handle in an engaged state.

7. Assembly of claim 5, further comprising:

the handle having an outer edge and an opposing inner edge facing the opening;

5

the end gap severing the outer and inner edges of the handle;
an outwardly facing first beveled edge carried by one of the free ends of the handle at the outer edge of the handle; and
an opposing outwardly facing second beveled edge carried by the other of the free ends of the handle at the outer edge of the handle;
wherein the second beveled edge is the mirror image of the first beveled edge.
8. Assembly of claim 5, further comprising:
bags having handles; and
the handles of the bags secured by the catch.
9. Assembly comprising:
an apparatus comprising:
a handle having ends, an outer edge and an opposing inner edge;
a catch having ends;
the ends of the catch attached to the ends of the handle;
an opening defined by the handle and the catch;
the handle severed defining opposing free ends and an end gap therebetween;
the end gap severing the outer and inner edges of the handle;

6

a first recess disposed at one of the free ends of the handle between the outer and inner edges of the handle;
an opposing second recess disposed at the other of the free ends of the handle between the outer and inner edges of the handle; and
a support element disposed between the free ends of the handle secured by and between the first and second recesses.
10. Assembly of claim 9, wherein the catch is inwardly flexed maintaining the free ends of the handle in an engaged state.
11. Assembly of claim 9, further comprising:
an outwardly facing first beveled edge carried by one of the free ends of the handle at the outer edge of the handle; and
an opposing outwardly facing second beveled edge carried by the other of the free ends of the handle at the outer edge of the handle;
wherein the second beveled edge is the mirror image of the first beveled edge.
12. Assembly of claim 9, further comprising:
bags having handles; and
the handles of the bags secured by the catch.

* * * * *