



US006625471B2

(12) **United States Patent**  
**Mori et al.**

(10) **Patent No.:** **US 6,625,471 B2**  
(45) **Date of Patent:** **\*Sep. 23, 2003**

(54) **MOBILE TELEPHONE SET AND DATA COMMUNICATION ADAPTOR**

(75) Inventors: **Shinichiro Mori**, Kawasaki (JP);  
**Masao Yamazawa**, Kawasaki (JP);  
**Akihide Nishiyama**, Kawasaki (JP);  
**Norishige Ihara**, Kawasaki (JP);  
**Hiroharu Seguchi**, Kawasaki (JP);  
**Toru Ogawa**, Kawasaki (JP); **Hitoshi Yamasaki**, Kawasaki (JP)

(73) Assignee: **Fujitsu Limited**, Kawasaki (JP)

(\* ) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/112,176**

(22) Filed: **Jul. 8, 1998**

(65) **Prior Publication Data**

US 2001/0053704 A1 Dec. 20, 2001

(30) **Foreign Application Priority Data**

Mar. 19, 1998 (JP) ..... 10-070773  
Feb. 10, 1998 (JP) ..... 10-028782

(51) **Int. Cl.**<sup>7</sup> ..... **H04B 1/38; H04M 1/00**

(52) **U.S. Cl.** ..... **455/557; 455/550; 379/433.13**

(58) **Field of Search** ..... 455/550, 556, 455/557, 566, 569, 575, 90, 347, 351, 568, 74.1; 379/430, 433, 433.13; 439/345, 347

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,946,010 A	*	8/1990	DiBono	.....	191/12.2 R
5,241,593 A	*	8/1993	Wagner	.....	379/438
5,409,394 A	*	4/1995	Astier	.....	439/347
D363,461 S	*	10/1995	Duckman et al.	.....	D13/140
5,544,836 A	*	8/1996	Pera	.....	242/372
5,600,719 A	*	2/1997	Lovecky et al.	.....	379/438
5,724,667 A	*	3/1998	Furuno	.....	455/90
6,028,930 A	*	2/2000	Chen	.....	379/446
6,073,034 A	*	6/2000	Jacobsen et al.	.....	455/90
2002/0137554 A1	*	9/2002	Hanna et al.	.....	455/568

**FOREIGN PATENT DOCUMENTS**

EP		0629071	*	12/1994	
JP		11234376 A	*	8/1999	..... H04M/1/02

\* cited by examiner

*Primary Examiner*—Charles Appiah  
(74) *Attorney, Agent, or Firm*—Katten Muchin Zavis Rosenman

(57) **ABSTRACT**

A portable telephone set includes a telephone set main body and a flipper. The telephone set main body is provided with a hinge mechanism and a flipper joint plate. The flipper joint plate is pivotally supported by hinge modules and has a connector at an end thereof. The flipper is joined to the flipper joint plate. The flipper is provided with a cable accommodating portion in which a short cable with a connector is accommodated. The cable includes a short cable main body as long as, for example, 10 cm and two connectors at respective ends of the cable. For mobile communication, one of the connectors of the cable is taken out from the flipper and connected to an information processing device.

**3 Claims, 22 Drawing Sheets**

140A




FIG. 1A PRIOR ART




FIG. 1B PRIOR ART






FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7






FIG. 8A

FIG. 8B





FIG. 9A




FIG. 9B




FIG. 10A

FIG. 10B




FIG. 11 140A





FIG. 12



# FIG. 13




FIG. 14B




FIG. 14A








FIG. 16




FIG. 17E

19D




FIG. 17D

19D




FIG. 17A

19D




FIG. 17C

19D



FIG. 17B




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 22B





FIG. 22A



## MOBILE TELEPHONE SET AND DATA COMMUNICATION ADAPTOR

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention generally relates to portable telephone sets and data communication adaptors and, more particularly to a portable telephone set and a data communication adaptor used to build a mobile communication system that includes an information processing device.

Recently, portable telephone sets are being used not only for telephone communication but also used in combination with an information processing device for mobile communication. Accordingly, it is required that a portable telephone set be useful to build a mobile communication system.

#### 2. Description of the Related Art

FIGS. 1A and 1B show a portable telephone set **10** according to the related art and how a mobile communication system is built using the portable telephone set **10**.

The portable telephone set **10** has a connector **10a** at the bottom thereof connectable to a connector of a cable.

FIG. 1A shows a mobile communication system **30** using an information processing device **20** not having a built-in data communication adaptor. The mobile communication system **30** is built using the information processing device **20**, a cable **40** with connectors and a data communication adaptor **50**. A connector **40a** at an end of the cable **40** is connected to the connector **10a** of the portable telephone set **10**. A connector **40b** at the other end of the cable **40** is connected to a connector **50a** at an end of the data communication adaptor **50**. The data communication adaptor **50** is inserted into a data communication adaptor accommodating unit **20a** of the information processing device **20**. A connector **50b** at the other end of the data communication adaptor **50** is connected to a connector **20b** at the rear end of the data communication adaptor accommodating unit **20a**.

Normally, the data communication adaptor **50** is inserted into the data communication adaptor **20a** of the information processing device **20**.

FIG. 1B shows how a mobile communication system **30A** is built using an information processing device **20A** having a built-in data communication adaptor. The information processing device **20A** has a built-in data communication adaptor **60**. The mobile communication system **30A** is built using the information processing device **20A**, the cable **40** with the connectors. The connector **40a** at an end of the cable **40** is connected to the connector **10a** of the portable telephone set **10** and the connector **40b** at the other end is connected to a connector **60a** of the data communication adaptor **60** built into the information processing device **20A**.

A user who intends to perform mobile communication carries the portable telephone set **10** with himself or herself. In addition, the user carries the information processing device **20 (20A)** and the cable **40** in, for example, a bag. If the cable **40** connected to the information processing device **20 (20A)** is accommodated in the bag, a intensive force is applied to the joint between the cable **40** and the information processing device **20 (20A)**, causing the joint to be damaged. For this reason, the cable **40** is disconnected from the information processing device **20 (20A)** while being carried.

Therefore, the user may leave the cable **40** behind at home since it is comparatively small. If the cable **40** is lost, mobile communication is impossible.

Another inconvenience is that, since the cable **40** should be connected to the portable telephone set **10** as well as to

the information processing device **20 (20A)**, it takes time to build a mobile communication system.

### SUMMARY OF THE INVENTION

5 Accordingly, an object of the present invention is to provide a portable telephone set and a data communication adaptor in which the aforementioned problems are eliminated.

Another and more specific object of the present invention is to provide a portable telephone set and a data communication adaptor whereby a data communication system is more readily built than according to the related art.

The aforementioned objects can be achieved by a portable telephone set comprising: a telephone set main body; and a cable accommodating portion for accommodating a cable with a connector connectable with a mobile information processing device, wherein the cable is accommodated in the cable accommodating portion such that an end of the cable is electrically connected to the telephone set main body.

Since the cable with the connector is accommodated such that an end of the cable is electrically connected to the portable telephone set, it is not necessary for a user to carry the cable with him or her. The cable is not lost by any chance. For mobile communication, the user has only to take the cable out of the cable accommodating unit and is not required to connect the cable to the portable telephone set.

The aforementioned objects can also be achieved by a portable telephone set comprising: a telephone set main body; and a flipper attached to the telephone set main body, wherein the flipper includes a cable accommodating portion for accommodating a cable with a connector connectable with a mobile information processing device, and the cable is accommodated in the cable accommodating portion such that an end of the cable is electrically connected to the telephone set main body.

It is to be appreciated that it is easier to provide the cable accommodating unit in the flipper than in telephone set main body.

The aforementioned objects can also be achieved by a portable telephone set comprising: a telephone set main body; and a flipper detachably attached to the telephone set main body, wherein the telephone set main body includes a telephone set main body connector, the flipper includes a cable accommodating portion for accommodating a cable having a first connector connectable with a mobile information processing device at one end thereof and having a second connector connectable with the telephone set main body connector, the cable is accommodated in the cable accommodating portion such that the second connector is fixedly secured to the cable accommodating portion, and the flipper is mechanically joined to the telephone set main body in a state where the second connector is connected to the telephone set main body connector.

Since the flipper is independent of the telephone set main body and detachably coupled thereto, the telephone set main body may be used for a plurality of types of portable telephone sets for users who intend to perform mobile communication using a portable information processing device.

The aforementioned objects can also be achieved by a portable telephone set comprising: a telephone set main body; and a connector to which a data communication adaptor for use in data communication when the portable telephone set is connected to a mobile information processing device is electrically connected.



By directly connecting the data communication adaptor to the portable telephone set, it is possible to perform mobile communication using a portable information processing device not having a built-in data communication adaptor.

The aforementioned objects can also be achieved by a portable telephone set comprising: a telephone set main body; and a flipper detachably attached to the telephone set main body, wherein a portion of the telephone set main body connected to the flipper is provided with a connector electrically connected to a data communication adaptor used for data communication when the portable telephone set is connected to a mobile information processing device.

By removing the flipper and connecting the data communication adaptor to the portable telephone, it is possible to perform mobile communication using a portable information processing device not having a data communication adaptor

The aforementioned objects can also be achieved by a card-like data communication adaptor used for data communication when a portable telephone set is connected to a mobile information processing device, comprising: a portable telephone set connector connectable to one of a portable telephone set and a connection adaptor connected to the portable telephone set; a mobile information processing device connector connectable with a mobile information processing device; and a mechanical supporting mechanism for mechanically maintaining a state where the portable telephone set connector is connected to one of the portable telephone set and the connection adaptor.

By providing a mechanical supporting mechanism, the moment caused by the weight of the portable telephone set is born by the mechanical supporting mechanism while mobile communication using the mobile communication system is proceeding so that a bending force is prevented from being exerted on the joint between the connectors.

The mechanical supporting mechanism may be embodied by holes to which arm portions projecting from the portable telephone set and the connection adaptor.

According to this aspect of the invention, it is easy to construct the mechanical supporting mechanism.

Each of the holes may be provided on an inner surface thereof with a rib portion engageable with a groove on a side of each of the arm portions.

By engaging the rib portion with the groove on the side of the arm portion, the mechanical support is reinforced.

The aforementioned objects can also be achieved by a card-like data communication adaptor used for data communication when a portable telephone set is connected to a mobile information processing device, comprising: an adaptor main body; a top shield plate formed of a metal and covering an upper major surface of the adaptor main body; and a bottom shield plate formed of a metal and covering a lower major surface of the adaptor main body, wherein the adaptor main body comprises: a portable telephone set connector electrically connectable to one of the portable telephone set and a connection adaptor connected to the portable telephone set; and a mobile information processing device connector connectable to a mobile information processing device, and wherein the card-like data communication adaptor further comprises: a mechanical supporting mechanism to which arm portions projecting from one of the portable telephone set and the connection adaptor are inserted and which mechanically supports the data communication adaptor with respect to one of the portable telephone set and connection adaptor, the mechanical supporting mechanism being embodied by holes formed by

incisions provided in the adaptor main body and by portions of the top shield plate and the bottom shield covering the incisions.

Since the shield plate is a formed of metal, the shield plate is not easily deformed. Accordingly, the mechanical support is reinforced.

Each of the incisions in the adaptor main body may be provided at an inner surface thereof with a rib portion engageable with a groove provided on a side of each of the arm portions.

By engaging the rib portion with the groove provided on the side of the arm portion, the mechanical support is reinforced.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and further features of the present invention will be apparent from the following detailed description when read in conjunction with the accompanying drawings, in which:

FIGS. 1A and 1B illustrate how a mobile communication system is built using a portable telephone set according to the related art;

FIG. 2 shows portable telephone sets according to first, second third and fourth embodiments of the present invention and mobile communication systems using such telephone sets;

FIG. 3 shows a portable telephone set according to the first embodiment;

FIG. 4 is an exploded perspective view of a telephone set main body of FIG. 3;

FIGS. 5A and 5B show the telephone set main body of FIG. 4 in detail;

FIG. 6 shows a flipper of FIG. 3 with parts broken away;

FIG. 7 shows the portable telephone set of FIG. 3 with the flipper being closed;

FIGS. 8A and 8B show how the portable telephone set of FIG. 3 is operated for mobile communication;

FIG. 9A shows an operation to be performed after the operation of FIGS. 8A and 8B;

FIG. 9B shows a mobile communication system;

FIGS. 10A and 10B shows a portable telephone set according to the second embodiment;

FIG. 11 is a mobile communication system using the portable telephone set of FIGS. 10A and 10B;

FIG. 12 shows a portable telephone set according to the third embodiment;

FIG. 13 is an exploded perspective view of a flipper of FIG. 12;

FIGS. 14A and 14B show a portable telephone set according to the fourth embodiment;

FIG. 15 shows a mobile communication system using the portable telephone set of FIG. 14A;

FIG. 16 shows a data communication adaptor;

FIGS. 17A–17E show a data communication adaptor;

FIG. 18 is an exploded perspective view of the data communication adaptor;

FIG. 19 is an exploded perspective view of a adaptor main body of FIG. 18;

FIG. 20A is an enlarged section taken along IXXA—IXXA of FIG. 16;

FIG. 20B is an enlarged section taken along IXXB—IXXB of FIG. 16;

FIG. 20C is an enlarged section taken along IXXC—IXXC of FIG. 16;

FIG. 21A is an enlarged section taken along XXA—XXA of FIG. 14B;

FIG. 21B is an enlarged section taken along XXB—XXB of FIG. 14B;

FIG. 21C is an enlarged section taken along XXC—XXC of FIG. 14B; and

FIGS. 22A and 22B show a variation of the telephone set main body.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 2 shows portable telephone sets 100, 100A, 100B and 100C according to first, second, third and fourth embodiments, respectively, of the present invention and mobile communication systems using the portable telephone sets 100, 100A, 100B and 100C.

A schematic description will first be given. The portable telephone set 100 according to the first embodiment includes a telephone set main body 110 and a flipper 111. The telephone set main body 110 is used in the other embodiments as well. The portable telephone set 100 is adapted for a user who intends to perform mobile communication using a portable information processing device 130 having a built-in data communication adaptor.

The telephone set main body 110 includes a liquid crystal display unit 112, a group of operation buttons 113, an antenna 114, a hinge mechanism 115 and a flipper joint plate 117. The hinge mechanism 115 is provided with hinge modules 116a and 116b. The flipper joint plate 117 is pivotally supported by the hinge modules 116a and 116b. The flipper joint plate 117 has a telephone set main body connector 118 at an end thereof. The flipper 111 may be sold by itself. The flipper 111 is joined with the telephone set main body 110 using the flipper joint plate 117. While the portable telephone set 100 is not used, the flipper 111 is closed so as to cover the group of operation buttons 113. When the user makes a telephone call or performs mobile communication, the flipper 111 is open.

The flipper 111 has a cable accommodating portion 119 having a short cable 120 with connectors accommodated therein. The short cable 120 comprises a short cable main body 121 as long as, for example, 10 cm, a connector 122 and a connector 123. The connector 122 of the short cable 120 is secured to the flipper 111. The short cable main body 121 in a bent state and the connector 123 are accommodated in the cable accommodating portion 119. The short cable main body 121 and the connector 123 of the short cable 120 are extractable from the cable accommodating portion 119 of the flipper 111. The connector 122 is connectable with the telephone set main body connector 118 and the connector 123 is connectable with a connector 131 of the mobile information processing device 130.

In a state in which the flipper 111 is connected to the flipper joint plate 117, the connector 122 is connected to the telephone set main body connector 118.

When the portable telephone set 100 is used for a telephone call, the short cable 120 remains accommodated in the flipper 111.

For mobile communication, a mobile communication system 140 is built by pulling out the connector 123 from the flipper 111 and connecting the same to the connector 131 of the information processing device 130 having a built-in data communication adaptor 132.

By providing the short cable main body 121, the flexibility of relative arrangement of the mobile information processing device 130 and the portable telephone set 100 is insured. By providing a distance between the mobile information processing device 130 and the portable telephone set 100, the operation is easy. No excessive stress is exerted on the joint between the connector 123 and the connector 131.

The portable telephone set 100A according to the second embodiment includes a telephone set main body 110 and a flipper 150 independent of the telephone set main body 110. The portable telephone set 100A is adapted for a user who intends to perform mobile communication using a portable information processing device 170 not having a built-in data communication adaptor.

The flipper 150 is connected to the flipper joint plate 117. The flipper 150 has a cable accommodating portion 151 having a short cable 152 with connectors accommodated therein. The short cable 152 comprises the short cable main body 121 as long as, for example, 10 cm, the connector 122 and the connector 153. The connector 122 of the short cable 152 is secured to the flipper 150. The short cable main body 121 in a bent state and the connector 153 are accommodated in the cable accommodating portion 151. The short cable main body 121 and the connector 153 of the short cable 152 are pulled out of the cable accommodating portion 151 of the flipper 150. The connector 122 is connectable with the telephone set main body connector 118 and the connector 153 is connectable with a connector 161 of a data communication adaptor 160.

In a state in which the flipper 150 is connected to the flipper joint plate 117, the connector 122 is connected to the telephone set main body connector 118.

When the portable telephone set 100A is used for a telephone call, the short cable 152 remains accommodated in the flipper 150.

For mobile communication, the flipper 150 is opened. The connector 153 is pulled out from the flipper 150 and connected to the connector 161 of the data communication adaptor 160. The data communication adaptor 160 is inserted in a data communication adaptor accommodating unit 171 of the information processing device 170 not having a built-in data communication adaptor. A connector 162 at the other end of the data communication adaptor 160 is connected to a connector 172 at the rear end of the data communication adaptor accommodating unit 171. Thus, simply by pulling out the connector 153 from the flipper 150 and connecting the connector 153 to the connector 161 of the data communication adaptor 160 inserted into the information processing device 170 not having a built-in data communication adaptor, a mobile communication system 140A is built.

By providing the short cable main body 121, the flexibility of relative arrangement of the mobile information processing device 170 and the portable telephone set 100A is insured. By providing a distance between the mobile information processing device 170 and the portable telephone set 100A, the operation is easy. No excessive stress is exerted on the joint between the connector 153 and the connector 161.

The portable telephone set 100B according to a third embodiment comprises the telephone set main body 110 and a flipper 180 independent of the telephone set main body 110. The portable telephone set 100B is adapted for a user who does not intend to perform mobile communication.

The flipper 180 is not provided with a cable and connected to the flipper joint plate 117.

The portable telephone set 100C according to the fourth embodiment comprises the telephone set main body 110.

The telephone set main body **110** uses a data communication adaptor **190** dedicated to the telephone set main body **110**. A mobile communication system **140A** is built by using a mobile information processing device **170A** not having a built-in data communication adaptor and adapted for the data communication adaptor **190**.

The data communication adaptor **190** is connectable with the flipper joint plate **117** and includes connectors **122** and **162**. The mobile information processing device **170A** has a data communication adaptor accommodating unit **171A** having the connector **172** at the rear end thereof.

The data communication adaptor **190** is connected to the flipper joint plate **117** such that the connector **122** is connected to the telephone set main body connector **118**. The data communication adaptor **190** joined to the telephone set main body **110** is inserted into the data communication adaptor accommodating unit **171A**. The connector **162** is connected to the connector **172** so that the data communication adaptor **190** is connected to the information processing device **170A**. Thus, a mobile communication system **140B** is built.

As described above, the telephone set main body **100** is used to construct the portable telephone sets **100**, **100A**, **100B** and **100C**, thus providing an economical advantage in producing the portable telephone sets **100**, **100A**, **100B** and **100C**.

A description will now be given of the portable telephone sets **100**, **100A**, **100B** and **100C** according to the respective embodiments.

#### Portable Telephone Set **100** According to the First Embodiment

As shown in FIG. **3**, the portable telephone set **100** is constructed such that the flipper **111** is mechanically and electrically connected to the telephone set main body **110**.

A description will be given of the telephone set main body **110**.

As shown in FIGS. **4**, **5A** and **5B**, the telephone set main body **110** is constructed such that an upper housing module **200** and a lower housing module **210** sandwich a substrate module **220**. The flipper joint plate **117** is pivotally secured to an end of the upper housing module **200** using the hinge modules **116a** and **116b**. In FIG. **4**, the flipper joint plate **117** is shown in an enlarged view for clearer illustration.

The upper housing module **200** comprises an upper housing **201**, a panel **202** and an operation button plate **203**.

The substrate module **220** comprises a liquid crystal panel **221**, a speaker **222**, a microphone **223**, connectors **224** and **225**, and band-like flexible cables **226** and **227**. An end of the flexible cable **226** is connected to the connector **224** so that the flexible cable **226** extends from the connector **224**. The other end of the flexible cable **226** is provided with the telephone set main body connector **118**. An end of the flexible cable **227** is connected to the connector **225** so that the flexible cable **227** extends from the connector **225**. The other end of the flexible cable **227** is provided with the microphone **223**.

The flipper joint plate **117** comprises a flipper joint plate main body **230**, a cover **231** secured to the underside of the flipper joint plate main body **230** by screws, and the telephone set main body connector **118**. The telephone set main body connector **118** is fixed to the flipper joint plate main body **230** by the cover **231** so as to be exposed at the end of the flipper joint plate **117**.

The flipper joint plate main body **230** has integral therewith ring portions **230a** and **230b**, and a semi-cylindrical

portion **230c**. The upper housing **201** has ring portions **201a** and **201b**, and a semi-cylindrical portion **201c** that match the ring portions **230a** and **230b**, and the semi-cylindrical portion **230c**, respectively. The flipper joint plate main body **230** and the upper housing **201** are joined to each other such that the ring portions **230a** and **230b**, the semi-cylindrical portion **230c**, the ring portions **201a** and **201b**, and the semi-cylindrical portion **201c** are aligned with each other. The hinge module **116a** engaged with the ring portion **230a** and the ring portion **201a** adjacent to each other, and the hinge module **116b** engaged with the ring portion **230b** and the ring portion **201b** adjacent to each other pivotally support the flipper joint plate **117**. An  $\alpha$ -shaped loop **226a** is formed in the middle of the flexible cable **226**. The  $\alpha$ -shaped loop **226a** is accommodated in a portion between the semi-cylindrical portion **201c** and the semi-cylindrical portion **231a** that are adjacent to each other. The diameter of the  $\alpha$ -shaped loop **226a** is increased when the flipper **111** (**150**, **180**) is open and decreased when the flipper **111** (**150**, **180**) is closed so that the stress produced in the flexible cable **226** is restrained.

The flipper joint plate main body **230** is provided with arm portions **230d** and **230e**. The arm portions **230d** and **230e** are provided at respective ends that are opposite to the pivotally supported side of the flipper **230** so as to extend away from the pivotally supported side. A recess **230f** is formed between the arm portions **230d** and **230e**. The telephone set main body connector **118** is exposed at a bottom **230f1** of the recess **230f**.

The arm portions **230d** and **230e** are provided with longitudinally extending slits **230d1** and **230e1**, respectively, at the periphery thereof.

Adjacent to the arms **230d** and **230e** are provided locking pawls **232** and **233** for locking the flipper **111** (**150**, **180**), respectively, and operation buttons **234** and **235**, respectively.

A description will now be given of the flipper **111**.

As shown in FIG. **6**, the flipper **111** comprises a flipper main body **240**, an openable and closable cover **241** pivotally secured to the flipper main body **240**, the short cable **120** and a holder member **242**. When the cover **241** is closed, the cable accommodating portion **119** is formed. The flipper **111** is connected to the flipper joint plate **117** at a joint end **243**. Numeral **244** indicates an end opposite to the end **243**.

The flipper main body **240** is provided on the joint end **243** with guide passages **240a** and **240b** extending along the interior surface thereof, a notch **240c** engageable with the operation button **234**, and an engaging hole **240d** engageable with the locking pawl **232**. A notch and an engaging hole on the other side are not shown.

A holder member **242** secured to the interior of the flipper main body **240** holds the connector **122** of the short cable **120** and a joint portion **121a** of the short cable main body **121** adjacent to the connector **122** in their places. A shaft portion **241a** of the cover **241** is also secured in its place by the holder member **242**. As shown in FIG. **8B**, the short cable main body **121** and the connector **123** of the short cable **120** are accommodated in the interior of the flipper main body **240**. The short cable main body **121** is appropriately bent such that it is guided under a cable holding portion **240e** projecting toward the interior of the flipper main body **240**. The connector **123** is held between a rib **240f** provided to extend along the periphery of the connector **123** and the inner wall of the flipper main body **240** such that the terminals faces the interior of the flipper main body **240**.

The cover **241** is rotatable around the shaft portion **241a**. When the cover **241** covers the cable accommodating por-

tion **119** locking pawls **241b** are engaged with recesses **240g** at the respective surfaces of the inner wall of the flipper main body **240**. The cover **241** covers the short cable **121** and the connector **123** when it is closed. Since the cover **241** is provided with side plates **241c** immediately adjacent to the locking pawls **241b**, it is unlikely that a finger of a user is caught on the locking pawl **241b**. Thus the locking pawl **241b** is prevented from being broken.

The cover **241** is also provided with notches **241d** and **241e** for pulling the short cable **121**. The flipper main body **240** is provided with a notch **240h** at a position that corresponds to the notch **241d**.

The guide passages **240a** and **240b** of the flipper **111** are engaged with the arm portions **230d** and **230e** of the flipper joint plate **117**, respectively. The flipper **111** is mechanically coupled to the flipper joint plate **117** (telephone set main body **110**) by the engaging holes **240d** being engaged with the locking pawls **232** and **233** and is electrically connected to the flipper joint plate **117** (the telephone set main body **110**) by the connector **122** being connected to the telephone set main body connector **118**. Thus, the portable telephone set **100** is constructed.

As shown in FIG. 7, the flipper **111** is normally closed so as to cover the operation buttons **113** of the telephone set main body **110**. A portion of the flipper **111** that corresponds to the microphone **223** is provided with an opening **226**.

A description will now be given of how the portable telephone set **100** is used.

When a telephone call is to be made, the flipper **111** is opened so that an appropriate operation is performed.

When mobile communication is to be performed, the mobile information processing device **130** having a built-in data communication adaptor as shown in FIG. 9B is taken out of the bag. The flipper **111** of the portable telephone set **100** is opened. The user applies a finger to the end of the cover **241** so as to open the cover **241** as indicated by the solid line in FIG. 8A and takes out the short cable **120** from the cable accommodating portion **119** and closes the cover **241** as indicated by the broken line in FIG. 8A. The short cable **120** may be guided through the notches **241d** and **240h** so as to extend from the end of the flipper **111**. As indicated by the alternate long and two short dashes line in FIG. 9A, the short cable **120** may alternatively be led out from the side of the flipper **111** via the notch **241e**.

As shown in FIG. 9b, the connector **123** at the end of the short cable **120** is connected to the connector **131** of the mobile information processing device **130**.

Thus, the mobile communication system **140** enabling mobile communication is built.

#### Portable Telephone Set **100A** According to the Second Embodiment

FIGS. 10A and 10B show the portable telephone set **100A**. Like the flipper **111** already described, the flipper **150** is mechanically and electrically connected to the telephone set main body **110**. As shown in FIG. 10B, the short cable **152** is accommodated in the flipper **150**.

When a telephone call is to be performed, the flipper **150** is opened so that an appropriate operation is performed.

When mobile communication is to be performed, the mobile information processing device **170** as shown in FIG. 11 not having a built-in data communication adaptor is taken out of the bag. The data communication adaptor **160** is inserted into the mobile information processing device **170**. As shown in FIGS. 10A and 10B, the flipper **150** of the

portable telephone set **100A** is opened so as to open the cover **241**. The short cable **152** is taken out of the cable accommodating portion **151**, whereupon the cover **241** is closed. The short cable **152** may be taken out in either of the two directions.

Subsequently, as shown in FIG. 11, the connector **153** at the end of the short cable **152** is connected to the connector **161** of the data communication adaptor **160** inserted into the mobile information processing device **170** not having a built-in data communication adaptor.

Thus, the mobile communication system **140A** enabling mobile communication is built.

#### Portable Telephone Set **100B** According to the Third Embodiment

The portable telephone set **100B** comprises the telephone set main body **110** and the flipper **180**. As shown in FIG. 12, the flipper **180** comprises a flipper main body **250**, an operation button member **251** fixed to the interior of the flipper main body **250**, and a cover **252** fixed to the interior of the flipper main body **250** and covering the operation button member **251**. The operation button member **251** is formed of rubber and is provided with three arm portions **251a** parallel with each other. A button portion **251b** is provided on the underside of each of the arm portions **251a**, and a projection **251c** is provided on each of the arm portions **251a**. The flipper main body **250** is provided with openings **250a** corresponding to the button portions **251b**. The cover **252** is provided with openings **252a** corresponding to the projections **251c**. The button portion **251b** is engaged with the opening **250a** and the projection **251c** is located in the opening **252a**.

Like the flipper **111** already described, the flipper **180** is mechanically joined to the telephone set main body **110**.

By pressing the button portion **251b** while the flipper **180** is being closed, three main buttons **113a**, **113b** and **113c** of the operation buttons **113** are pressed.

#### Portable Telephone Set **100C** According to the Fourth Embodiment

The portable telephone set **100C** according to the fourth embodiment includes the telephone set main body **110** as shown in FIG. 14A.

As shown in FIGS. 14A, 14B and 15, when mobile communication is to be performed, the data communication adaptor **190** is mechanically joined to the flipper joint plate **117** of the telephone set main body **110**. The connector **122** is connected to the telephone set main body connector **118** for electrical connection.

Subsequently, as shown in FIG. 15, the data communication adaptor **190** joined to the telephone set main body **110** is inserted into the data communication adaptor accommodating unit **171A**. The connector **162** is connected to the connector **172** so that the data communication adaptor **190** is connected to the information processing device **170A**. Thus, the mobile communication system **140B** is built.

The data communication adaptor **190** is provided with holes **190a** and **190b** at respective sides thereof. The holes **190a** and **190b** are engaged with the arm portions **230d** and **230e** so that connection between the flipper joint plate **117** and the data communication adaptor **190** is reinforced.

#### Variations

In the above-described embodiments, the telephone set main body **110** is provided with a removable flipper.

However, the flipper may be permanently attached to the telephone set main body 110. In a portable telephone set in which a flipper is removable, the telephone set main body connector 118 is provided at the end of the flipper. In a portable telephone set in which a flipper is not removable, the telephone set main body connector 118 may be provided in the telephone set main body. That is, the connector 118 may constitute a part of the portable telephone set.

#### Data Communication Adaptor 190 According to the Fifth Embodiment

The data communication adaptor 190 shown in FIG. 14A has a construction as shown in FIGS. 16-20C.

The data communication adaptor 190 functions as a PCMCIA card. As shown in FIG. 18, the data communication adaptor 190 comprises a main body 191 and metal shield covers 192 and 193 that cover the upper and lower surfaces of the main body 191, respectively.

As shown in FIG. 19, the main body 191 is constructed such that a printed circuit module 195 is combined with a frame 194. The printed circuit module 195 is constructed such that a plurality of electronic parts 195b are mounted on the upper and lower surfaces of a printed circuit board 195a. The connector 122 connected to a portable telephone set is attached to the X2 end of the printed circuit board 195a and the connector 162 connected to the mobile information processing device is attached to the X1 end of the printed circuit board 195a. The frame 194 is configured to adapt for the printed circuit module 195. At the X2 end, the frame 194 is provided with arm portions 194a and 194b projecting in the X2 direction at the Y1 end and the Y2 end, respectively. A connector accommodating portion 194c accommodating the connector 122 is formed between the arm portions 194a and 194b. A incision 194d extending in the Z1-Z2 direction is provided between the arm portion 194a and the connector accommodating portion 194c, and a incision 194e also extending in the Z1-Z2 direction is provided between the arm portion 194b and the connector accommodating portion 194c.

As shown in FIG. 20A, the shield cover 192 is provided with bent portions 192a and 192b at the Y1 and Y2 ends, respectively. The bent portions 192a and 192b are configured to be engageable with grooves 194f and 194g, respectively, provided at the Y1 and Y2 ends of the frame 194, respectively. The shield cover 193 is provided with bent portions 193a and 193b at the Y1 and Y2 ends, respectively. The bent portions 193a and 193b are also configured to be engageable with the grooves 194f and 194g, respectively, provided at the Y1 and Y2 ends of the frame 194, respectively. The shield covers 192 and 193 are electrically connected to the ground of the printed circuit module 195 and hermetically seal the printed circuit module 195.

The Z1 and Z2 ends of the incisions 194d and 194e are covered by respective portions of the shield covers 192 and 193. As shown in FIGS. 20A and 20B, the incision 194d and the shield covers 192 and 193 form the hole 190a. As shown in FIGS. 20A and 20C, the incision 194e and the shield covers 192 and 193 form the hole 190b. Each of the holes 190a and 190b has a relatively large depth A. The Z1 and Z2 end walls of the holes 190a and 190b have a relatively high mechanical strength since they are formed by respective portions of the shield covers 192 and 193. The holes 190a and 190b constitute a mechanical supporting mechanism as claimed.

To insure locking of the data communication adaptor 190, the arm portions 194a and 194b for locking of the data

communication adaptor 190 are provided with recesses 194a1 and 194b1, respectively, at the inner surfaces thereof and also provided with rib portions 194a2 and 194b2, respectively, extending in the X1-X2 direction.

The data communication adaptor 190 is provided with the connector 122 at the X2 end thereof and the connector 162 at the X1 end thereof.

In order to perform mobile communication, the data communication adaptor 190 is connected to the flipper joint plate 117 of the telephone set main body 110 such that the connector 122 is connected to the telephone set main body connector 118. Subsequently, the data communication adaptor 190 connected to the telephone set main body 110 is inserted into the data communication adaptor accommodating unit 171A such that the connector 162 is connected to the connector 172 for connection with the mobile information processing device 170A. Thus, the mobile communication system 140B is built. The end of each of the shield covers 192 and 193 is electrically connected to the ground terminal (not shown) exposed in the data communication adaptor accommodating unit 171A of the mobile information processing device 170A.

As shown in FIG. 15, while mobile communication is being performed by the mobile communication system 140B, the telephone set main body 110 is located adjacent to the mobile information processing device 170A so that a predetermined moment M that acts to bend a joint between the connector 122 and the telephone set main body connector 118 is exerted on the joint. The moment M is given by  $(W, \text{ which is a sum of the weight of the telephone set main body } 110, \text{ the force exerted on the telephone set main body } 110 \text{ for operation thereof, an external force exerted on the telephone set main body } 110) \times (L \text{ which is the length of an arm extending from the joint between the connector } 122 \text{ and the telephone set main body } 118 \text{ to the center of gravity of the telephone set main body } 110)$ . The mechanical supporting mechanism as mentioned above bears the moment M so that a bending force is prevented from being exerted on the joint between the connector 122 and the telephone set main body connector 118.

A description will now be given of how the holes 190a and 190b provide a mechanical support.

When the mobile communication system 140B has been built as shown in FIG. 14B, the arm portion 230d is inserted into the hole 190a by the distance A so as to come into contact with the rear end thereof, and the arm portion 230e is inserted into the hole 190b by the distance A so as to come into contact with the rear end thereof, as shown in FIGS. 21A, 21B and 21C. FIGS. 21A, 21B and 21C also show that the rib portion 194a2 is engaged with the slit 230d1, the rib portion 194b2 is engaged with the slit 230e1, the recess 194a1 is engaged with the locking pawl 232, and the recess 194b1 is engaged with the locking pawl 233.

The moment M is born such that, as shown in FIG. 21C, an edge 193c of the shield cover 193 facing an exit of the hole 190a bears a base 230d2 of the arm portion 230d and an edge 192c of the shield cover 192 facing a rear end of the hole 190a bears an end 230d3 of the arm portion 230d, and, as shown in FIG. 21B, an edge 193d facing an exit of the hole 190b bears a base 230e2 of the arm portion 230e and an edge 192d facing a rear end of the hole 190b bears an end 230e3 of the arm portion 230e. In this way, the arm portions 230d and 230e are supported at two locations at the Y1 and Y2 ends, respectively.

As shown in FIG. 21A, the moment M is also born by the engagement of the rib portions 194a2 and 194b2 with the slits 230d1 and 230e1, respectively.

## 13

The metal shield covers **192** and **193** with which the arm portions **230d** and **230e** come into contact are known to have a relatively large rigidity. The distance B in the Z1-Z2 direction of the holes **190a** and **190b** is substantially identical to the thickness C of the data communication adaptor **190**. Thus, the thickness of the arm portions **230d** and **230e** is relatively large. Accordingly, the mechanical support provided by the holes **190a** and **190b** is sufficient to bear the moment M. Thus, the joint between the connector **122** and the telephone set main body connector **118** is free from a bending force. Thus, the connection between the connector **122** and the telephone set main body connector **118** is prevented from being loosened. It is unlikely that the connector **122** and the telephone set main body connector **118** are bent while the connection is established or that terminals of the connector **122** or the telephone set main body connector **118** are damaged. Thus, the life of the connectors **122** and **118** is prevented from being excessively reduced.

## Variation of the Telephone Set Main Body

FIG. 22A shows a telephone set main body **110A** which is a variation of the telephone set main body **110** of FIG. 3. The telephone set main body **110A** comprises the liquid crystal display unit **112**, the operation buttons **113** and the antenna **114**. A connector **350** is provided at the lower end of the telephone set main body **110A**.

A connection adaptor **351** is used for the telephone set main body **110A**. The connection adaptor **351** comprises the hinge mechanism **115** and the flipper joint plate **117**. A connector **352** is provided on the upper end of the connection adaptor **351**.

The connection adaptor **351** is used to connect the data communication adaptor **190** to the telephone set main body **110A**.

The data communication adaptor **190** is connected to the telephone set main body **110A** such that the connector **352** is connected to the connector **350** so that the connection adaptor **351** is electrically and mechanically connected to the lower end of the telephone set main body **110A**. The data communication adaptor **190** is then connected to the flipper joint plate **117** of the connection adaptor **351**. Thus, a data communication system as shown in FIG. 22B results. The mechanical supporting mechanism is operated as described already.

## 14

The present invention is not limited to the above described embodiments, and variations and modifications may be made without departing from the scope of the present invention.

What is claimed is:

1. A portable telephone set comprising:
  - a telephone set main body; and
  - a flipper attached to said telephone set main body, wherein said flipper includes a cable accommodating portion for accommodating a cable with a connector connectable with a mobile information processing device, and the cable is accommodated in the cable accommodating portion such that an end of the cable is electrically connected to the telephone set main body.
2. A portable telephone set comprising:
  - a telephone set main body; and
  - a flipper detachably attached to said telephone set main body, wherein said telephone set main body includes a telephone set main body connector, said flipper includes a cable accommodating portion for accommodating a cable having a first connector connectable with a mobile information processing device at one end thereof and having a second connector connectable with said telephone set main body connector, said cable is accommodated in said cable accommodating portion such that said second connector is fixedly secured to said cable accommodating portion, and said flipper is mechanically joined to said telephone set main body in a state where said second connector is connected to said telephone set main body connector.
3. A portable telephone set comprising:
  - a telephone set main body; and
  - a flipper detachably attached to said telephone set main body, wherein a portion of said telephone set main body connected to said flipper is provided with a connector electrically connected to a data communication adaptor used for data communication when the portable telephone set is connected to a mobile information processing device.

\* \* \* \* \*