



US006629533B1

(12) **United States Patent**  
**Webb et al.**

(10) **Patent No.:** **US 6,629,533 B1**  
(45) **Date of Patent:** **\*Oct. 7, 2003**

(54) **PUNCTUM PLUG WITH AT LEAST ONE ANCHORING ARM**

(75) Inventors: **Nicholas J. Webb**, Redding, CA (US);  
**Richard W. Mendius**, Collierville, TN (US)

(73) Assignee: **Eagle Vision, Inc.**, Memphis, TN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/608,463**

(22) Filed: **Jun. 30, 2000**

(51) Int. Cl.<sup>7</sup> ..... **A61B 17/00**

(52) U.S. Cl. .... **128/887**; 604/8

(58) Field of Search ..... 128/846, 848,  
128/887; 604/8-10, 294

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,949,750 A	4/1976	Freeman	128/260
4,056,496 A	11/1977	Mancini et al.	260/29.6
4,461,295 A	7/1984	Herrick	128/303
4,660,546 A	4/1987	Herrick et al.	128/1 R
4,886,488 A	12/1989	White	604/9
4,915,684 A	4/1990	MacKeen et al.	604/8
4,959,048 A	9/1990	Seder et al.	604/9
5,049,142 A	9/1991	Herrick et al.	604/294
5,171,270 A	12/1992	Herrick	623/11
5,283,063 A	2/1994	Freeman	424/427
5,334,137 A	8/1994	Freeman	604/8
5,417,651 A	5/1995	Guena et al.	604/8

5,423,777 A	6/1995	Tajiri et al.	604/294
5,522,837 A	6/1996	Latina	606/201
5,601,553 A	2/1997	Trebing et al.	606/61
5,626,559 A	5/1997	Solomon	604/9
5,645,565 A	7/1997	Rudd et al.	606/213
5,723,005 A	3/1998	Herrick	623/4
5,766,243 A	6/1998	Christensen	623/4
5,830,171 A	11/1998	Wallace	604/8

**FOREIGN PATENT DOCUMENTS**


GB	2069339 A	8/1981
GB	2160778 A	1/1986


*Primary Examiner*—Michael A. Brown  
(74) *Attorney, Agent, or Firm*—Gordon & Jacobson, P.C.

(57) **ABSTRACT**

A punctum plug generally includes a shaft and a head at a proximal end of the shaft. The shaft is provided with at least one circumferentially radiating flexible anchoring arm of varying radial extension at at least two locations along its length which is adapted to secure the punctum plug within the punctum of a wearer. The head has a concave proximal surface and a distal surface which tapers toward the shaft. A diameter of the head is substantially larger than a diameter of the shaft. According to a first embodiment of the invention, a plurality of anchoring arms in the form of symmetric circumferential rings are spaced a distance apart along a length of the shaft and define spaces therebetween. One or more of the rings has a diameter equal to or larger than the diameter of the head of the plug, and different rings preferably have different diameters. According to a second embodiment of the invention, a plurality of anchoring arms in the form of longitudinally offset flanges are spaced a distance apart along a length of the shaft. The offset flanges are offset relative to a plane extending axially through the shaft.

**37 Claims, 6 Drawing Sheets**





**FIG. 1**  
PRIOR ART




FIG. 2b




FIG. 2a




FIG. 3a





FIG. 3b








FIG. 5a







FIG. 5b





## PUNCTUM PLUG WITH AT LEAST ONE ANCHORING ARM

This application is related to U.S. Pat. No. 6,041,785, and is a continuation-in-part of U.S. Ser. No. 09/305,599 filed May 5, 1999, which in turn is a continuation-in-part of Ser. No. 08/826,216 filed Mar. 27, 1997; all three of which are hereby incorporated by reference herein in their entireties.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

This invention relates broadly to medical canalicular inserts. More particularly, this invention relates to canalicular plugs which are placed into the punctal opening of the lacrimal duct to prevent lacrimal fluid from flowing through the lacrimal duct.

#### 2. State of the Art

A variety of eye problems are related to an insufficient volume of tears on the surface of the eyes. The most common is keratoconjunctivitis sicca, also known as dry eyes. Contact lens problems are also often provoked by a lack of tear volume. A common cause for the insufficient tear volume is the drainage of tear fluid through the punctal opening of the lacrimal duct and into the nasal passage, thereby removing the fluid from where it is needed at the eye surface. Furthermore, drainage of tear fluid through the lacrimal duct into the nasal passage is believed to be the cause of or associated with several additional problems such as post nasal drip, sinusitis, allergies, headaches, and snoring.

A number of methods for closing the punctal opening have been used to prevent drainage of tears through the lacrimal duct, including suturing, laser sealing, and plugging. Plugging with a canalicular plug, such as a punctum plug or a lacrimal plug, is the least severe solution, is relatively inexpensive, and is being performed with increasing frequency.

Referring to prior art FIG. 1, a punctum plug **10** typically includes an elongate member or shaft **12** having a proximal end **14** and a distal end **16**, a head **18** at the proximal end **14** of the shaft **12**, and a relatively larger body **20** at the distal end **16** of the shaft **12** for occluding a lacrimal duct **22**. The plug **10** is usually provided with a proximal axial bore **24** for receiving an insertion tool. In the punctum plug insertion procedure, the insertion tool is positioned into the bore **24** of the plug **10**, the body **20** of the plug **10** is directed at a punctal opening **26** of the lacrimal duct **22**, and force is applied to the insertion tool to move the body **20** of the plug **10** through the punctal opening **26**, the muscles of the punctal ring **27**, and into the vertical punctum **28** of the lacrimal duct **22**. Once the plug **10** is fully inserted in the punctum **28**, the insertion tool is removed. The plug **10** is fully inserted when the head **18** seats against the tissue at the punctal opening **26** and the body **20** seats within the lacrimal duct **22** so as to block the passage of tear fluid into the duct **22** and thereby retain tear fluid at the surface of the eye. Similarly, lacrimal plugs (not shown) which seat entirely within the lacrimal duct (completely below the punctal opening) are also known.

It has been found that prior art punctum and lacrimal plugs, while providing some benefit, often do not provide satisfactory occlusion of the lacrimal duct. Tear fluid tends to flow through the interstices **30** between the body of the plug and the tissue of the vertical punctum of the lacrimal duct. One proposed prior art solution of this problem has been to provide the plug **10** with an enlarged distal body **20**.

However, the punctum plug having the larger distal body is difficult to insert through the relatively small punctal opening and may inadvertently cause damage to the delicate punctal tissue.

Another problem with prior art punctum plugs is that the puncta of different individuals tend to be different in size. Thus, a physician is required to have available a plurality of differently sized punctum plugs. The physician must carefully measure or estimate the size of the punctum and punctal opening of each patient to select the proper sized plug to insert. If the physician misjudges the size required, the punctum plug will not effectively block the lacrimal fluid flow and the patient will not realize the full benefit of the device.

### SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide a punctum plug which occludes the flow of tears through the lacrimal duct.

It is another object of the invention to provide a punctum plug which is not easily unintentionally dislodged from the lacrimal duct.

It is also an object of the invention to provide a punctum plug which is designed to facilitate insertion into the lacrimal duct.

It is a further object of the invention to provide a punctum plug which can easily be extricated by a physician when desired.

It is yet another object of the invention to provide a single sized punctum plug which is adaptable to fit within substantially all sized puncta.

In accord with these objects, which will be discussed in detail below, a punctum plug generally includes a shaft and a head at a proximal end of the shaft. The distal end of the shaft terminates at a tip. The shaft is provided with at least one circumferentially radiating flexible anchoring arm of varying radial extension at at least two locations along its length which is adapted to secure the punctum plug within the punctum of a wearer.

The punctum plug of the invention is preferably made from a highly flexible, resilient biocompatible material. According to the invention, the head has a concave proximal surface and a distal surface which tapers toward the shaft. A diameter of the head of the plug is substantially larger than a diameter of the shaft. Preferably, the at least one flexible anchoring arm radially extends a distance greater than a radial width of the head. In accord with a first preferred aspect of the invention, the tip is no greater in diameter than the diameter of the shaft. An axial insertion bore is optionally defined through the proximal head of the plug extending a distance through the shaft.

According to a first embodiment of the invention, a plurality of anchoring arms in the form of symmetric circumferential rings are spaced a distance apart along a length of the shaft and define spaces therebetween. One or more of the rings has a diameter equal to or larger than the diameter of the head of the plug, and different rings preferably have different diameters.

According to a second embodiment of the invention, a plurality of anchoring arms in the form of longitudinally offset flanges are spaced a distance apart along a length of the shaft. The offset flanges are offset relative to a plane extending axially through the shaft providing an asymmetric cross-section to the plug at the shaft. Preferably, the flanges radially extend different lengths away from the shaft.



3

According to a third embodiment of the invention, the anchoring arm is a single flange helically wound about the shaft, and optionally the tip of the punctum plug. The radial length of the helical flange changes as it moves up or down the shaft. In addition, the pitch of the helical flange may

According to a fourth embodiment of the invention, two preferably arcuate anchoring arms are provided at a distal portion of the shaft and extend outward and towards the head. The anchoring arms thereby function as barbs which retain the plug within the punctum.

According to a fifth embodiment of the invention, a single anchoring arm extends from the tip of the plug outward and upward toward the head of the plug. In addition, the arm is preferably relatively small adjacent the tip, to aid in insertion, and generally becomes relatively larger with its distance from the tip. The anchoring arm is flexible, and adapted to engage the underside of the punctal ring to secure the plug within the punctum.

In all embodiments, it is preferred that the arm or arm portion which extends the furthest radially be located at or along a middle portion of the shaft.

According to the invention, prior to insertion of the punctum plug into the punctum of a wearer, the punctal opening of the eye is optionally dilated. The plug is advanced into the punctum until the head of the plug rests adjacent the punctal opening. When the punctal opening returns to its predilated size, the anchoring arm or arms retain the punctum plug within the punctum and the head occludes the opening preventing lacrimal fluid flow. The anchoring arm or arms and the head surround the punctal ring to create a secure fit.

Additional objects and advantages of the invention will become apparent to those skilled in the art upon reference to the detailed description taken in conjunction with the provided figures.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a broken perspective view of a prior art punctum plug inserted within a punctum of a patient;

FIG. 2a is a perspective view of a first embodiment of a punctum plug according to the invention;

FIG. 2b is an enlarged cross-sectional view of the first embodiment of the punctum plug according to the invention taken along line 2b—2b of FIG. 2a;

FIG. 3a is a perspective view of a second embodiment of a punctum plug according to the invention;

FIG. 3b is an enlarged cross-sectional view of the second embodiment of the punctum plug according to the invention taken along line 3b—3b of FIG. 3a;

FIG. 4a is a perspective view of a third embodiment of a punctum plug according to the invention;

FIG. 4b is an enlarged cross-sectional view of the third embodiment of the punctum plug according to the invention taken along line 4b—4b of FIG. 4a;

FIG. 5a is a perspective view of a fourth embodiment of a punctum plug according to the invention;

FIG. 5b is a cross-sectional view of the fourth embodiment of the punctum plug according to the invention taken across line 5b—5b in FIG. 5a;

FIG. 6a is a side elevation view of a fifth embodiment of the punctum plug according to the invention;

FIG. 6b is a cross-sectional view of the fifth embodiment of the punctum plug according to the invention taken across line 6b—6b in FIG. 6a; and

4

FIG. 7 illustrates the fifth embodiment of the punctum plug inserted within a punctum.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Turning now to FIGS. 2a and 2b, a punctum plug 110 according to the a first embodiment of the invention is provided which generally includes a shaft 112 having a proximal end 114 and a distal end 116, and a head 118 at the proximal end 114 of the shaft 112. The shaft 112 terminates in a tip 132 at its distal end 116. According to the invention, the shaft 112 is preferably substantially cylindrical. The head 118 preferably has a concave proximal surface 134, a distal surface 136 which tapers toward the shaft 112, and a diameter greater than a diameter of the shaft 112. An optional axial insertion bore 124, adapted to receive an insertion tool (not shown), is defined through the head 118 of the plug 110 extending a distance through the shaft 112. The punctum plug 110 of the invention is preferably molded from a resilient biocompatible material such as silicone or another soft, low Durometer biocompatible material which is highly flexible and permits the head 118 to conform to the shape of a variety of sized and shaped punctal openings.

In accord with the first embodiment of the invention, the shaft 112 is provided at at least two locations along its length a circumferentially radiating anchoring arm 138. The anchoring arms 138 are flexible yet are adapted to frictionally or mechanically engage punctal tissue to secure the plug 110 within a punctum of a wearer. By providing anchoring arms of different radial lengths, differently sized puncta are accommodated. Preferably, at least one of the flexible anchoring arms 138c extends radially from the shaft 112 a distance greater than a radially extended distance of the head 118. The largest anchoring arm 138c aids in retention of the plug 110 within even the largest punctum, yet is adapted to fold to fit smaller punctum. Although the anchoring arms can act to restrict some of the lacrimal fluid flow within the punctum, according to the invention, punctal lacrimal flow occlusion mainly occurs as a result of tissue at the punctal opening seating about the distal surface 136 of the head 118. The punctum plug of the invention properly fits within a variety of sized puncta resulting in the ability to use a punctum plug of one size to achieve improved lacrimal flow occlusion in a variety of sized puncta.

In accord with a preferred aspect of the invention, the tip portion 132 of the shaft 112, which may be rounded, truncated, or pointed, is no larger in diameter than a diameter of the shaft 112 resulting in a reduced distal surface area relative to prior art plugs 10. The reduced distal surface area aids in insertion and prevents build-up of pressure behind the plug 110 reducing the likelihood of inadvertently dislodging the plug 110. In addition, the smaller tip results in reduced tissue damage during insertion and greater comfort for the patient.

Particularly with respect to the first embodiment 110 of the invention, the anchoring arms 138 constitute a plurality of circumferential rings 138 spaced a distance apart along a length 140 of the shaft 112 defining spaces 142 therebetween. The rings 138 are symmetric about a plane extending axially through the shaft 112. Preferably, four rings 138a—138d are positioned substantially equidistance apart along the shaft 112. The rings 138a—138d differ in radially extension, i.e., the diameter of each ring is different. As stated above, preferably, at least one of the anchoring rings (138c) has a diameter greater than the diameter of the head 118 of the plug 110. It should be appreciated that each of the



## 5

arms is sufficiently flexible such that the arms will fold upward toward the head during insertion and will accommodate even unusually narrow punctal openings.

Referring to FIGS. 3a and 3b, a second embodiment of a punctum plug **210**, substantially similar to the first embodiment **110** (with like parts having numbers incremented by 100) is shown. According to the second embodiment **210**, the anchoring arms **238a–238g** are a plurality of longitudinally offset flanges, at least some of which have different radial lengths spaced a distance apart along a length of the shaft **212**. The flanges **238a–238g** are all substantially semicircular with two groups of three flanges being offset relative to each other with respect to a plane of the plug **210** extending axially through the shaft **212**. Thus, the flanges provide an asymmetric cross-section along a plane of the plug **210**. As with the first embodiment, it is preferable that at least one of the flanges **238** (e.g. **238d** and **238e**) extends radially outward a distance greater than the radial extension of the head **218**.

Referring to FIGS. 4a and 4b, a third embodiment of a punctum plug **310**, substantially similar to the first embodiment **110** (with like parts having numbers incremented by 200) is shown. According to a third embodiment of the invention **310**, the anchoring arm **338** is a single flange helically wound about (and integral with) the shaft **312** and preferably terminating distally at the tip **332** of the shaft **312**. The helical flange **338** changes in radial length as it extends along the shaft, (e.g. compare portions **338b** and **338c** with portions **338a** and **338d**) with the helical flange **338** preferably extending the furthest radially at a midsection of the shaft **312**. In addition, the helical flange preferably changes in pitch along the length of the shaft, with a longer pitch (steeper angle to the flange) nearer the tip **332**, and a shorter pitch (with the flange more perpendicular relative to the shaft **312**) nearer the head **318**. The longer pitch at the tip **332** facilitates initial insertion of the plug **310** into the punctal opening, and the shorter pitch nearer the head **318** facilitates anchoring along the punctum. Slits (not shown) may be provided in the flange to facilitate folding of the flange within the punctum to accommodate insertion and varying punctal sizes. In addition, the spiralling flange **338** guides the punctum plug **310** into the punctal opening and aids in insertion by allowing the device to be inserted and positioned with a rotational (or screw-like) motion. To that end, the bore **324** is preferably provided with a non-circular cross-section (as taught in parent application U.S. Ser. No. 09/305,599) to receive an insertion tool having an interfering cross-section. As such, during insertion, rotation of the insertion tool results in corresponding rotation of the plug **310** to guide the plug **310** into the punctal opening. As with the previous two embodiments, at least a portion of the anchoring arm **338** (at **338b** and **338c**) extends radially a distance greater than the radial extension of the head **318**.

Referring to FIGS. 5a and 5b, a fourth embodiment of a punctum plug **410** is shown. According to the fourth embodiment of the invention, two preferably radially arcuate (relative to the shaft) anchoring arms **438** are provided at a distal portion of the shaft **412** and extend outward and upwards towards the head **418**. The anchoring arms **438** thereby function as barbs which operate to mechanically retain the plug within the punctum by engaging the punctal ring.

Referring to FIGS. 6a, 6b and 7, a fifth embodiment of a punctum plug **510** is shown. According to the fifth embodiment of the invention, a single anchoring arm **538** extends at an angle from the lower shaft **512** or tip **532** of the plug upward and outward, generally toward the periphery of the

## 6

head **518** of the plug **510**. In addition, the arm **538** is preferably relatively small adjacent the tip **532**, to aid in insertion through the punctal opening, and generally becomes relatively larger with its distance from the tip. Referring to FIG. 7, the anchoring arm **538** is flexible, and adapted to bend upward **538a** to facilitate insertion, and bend downward **538b** once provided within the vertical punctum to engage the underside of the punctal ring **527** to secure the plug within the vertical punctum **528** via both frictional and mechanical engagement (FIG. 7).

The punctum, plugs of the invention are inserted into the punctum of a patient by optionally first dilating the punctal opening of the patient, inserting an insertion tool into the bore **124** (**224**, **324**, **424**, **524**) of the plug, and positioning the tip **132** (**232**, **332**, **432**, **532**) of the shaft **112** (**212**, **312**, **412**, **512**) at the punctal opening. The plug is then moved either axially (in the case of plugs **110**, **210**, **310**, **410**, **510**) or optionally axially with rotation (in the case of plug **310**) through the punctal opening until the distal surface **136** (**236**, **336**, **436**, **536**) of the head **118** (**218**, **318**, **418**, **518**) of the plug rests against tissue at the punctal opening. The insertion tool is then removed from within the axial bore. The anchoring arms **138** (**238**, **338**, **438**, **538**) frictionally or mechanically engage the punctal tissue and/or the punctal ring. As the punctal opening returns to its predilated state, the punctal tissue encloses about the shaft **112** (**212**, **312**, **412**, **512**) and seats between the distal surface **136** (**236**, **336**, **436**, **536**) of the tapered head **118** (**218**, **318**, **418**, **518**) and the anchoring arms to secure the plug within the punctal opening and substantially completely blocking lacrimal fluid flow from entering the punctum.

According to the invention, the punctum plug is preferably designed to fit within a wide range of differently sized puncta. To this end, the punctum plug is preferably 1.5 mm to 2.5 mm long from head to tip. The shaft is preferably 1.4 mm to 2.4 mm long, and 0.4 mm to 0.6 mm in diameter. The head is preferably 1.5 mm to 2.5 mm in diameter (i.e. a diameter which is larger than a diameter of the largest punctal opening of a wearer). The radially extending anchoring arms preferably extend between 1.0 mm to 2.0 mm from the shaft with at least a portion of at least one of the anchoring arms extending beyond the radius of the head.

There have been described and illustrated herein several embodiments of a lacrimal flow occluder (punctum plug) and a method of inserting the occluder. While particular embodiments of the invention have been described, it is not intended that the invention be limited thereto, as it is intended that the invention be as broad in scope as the art will allow and that the specification be read likewise. Thus, while particular arrangements of anchoring arms have been disclosed, it will be appreciated that other arrangements may be used as well. For example and not by way of limitation, a punctum plug may have three or more offset flanges extending radially from the shaft. Furthermore, while particular shapes, sizes, and numbers of the anchoring arms have been disclosed, it will be understood that punctum plugs having more or fewer anchoring arms formed about the shaft in a variety of shapes and sizes can be similarly used. Also, it will be appreciated that any of the embodiments may be formed having any style or shape tip. Further, while it is preferable that the anchoring bodies be spaced equidistance apart, it will be appreciated that the spacing can vary. In particular, in certain circumstances it may be desirable to provide additional distance between the largest arms and the arms adjacently above the largest arms. In addition, while particular types of materials have been disclosed, it will be understood other materials can be used.



Further, while it is preferred that the entire plug be formed from a flexible material, it will be understood that only portions of the plug (preferably the head and the anchoring arms) need be formed from a flexible material. It will therefore be appreciated by those skilled in the art that yet other modifications could be made to the provided invention without deviating from its spirit and scope as claimed.

What is claimed is:

1. A punctum plug for insertion into a punctum of a wearer, comprising:

- a) a shaft having a proximal end, a distal end, and a length;
- b) a plurality of circumferential rings radially extending from said shaft and spaced apart along said length of said shaft and defining spaces therebetween, at least one of said plurality of circumferential rings has a diameter larger than a diameter of said head; and
- c) a head at said proximal end of said shaft.

2. A punctum plug according to claim 1, wherein: said head and said shaft at least partially define an axial bore, said axial bore adapted to receive an insertion tool.

3. A punctum plug according to claim 1, wherein: at least one of said plurality of circumferential rings has a diameter larger than a diameter of said head.

4. A punctum plug according to claim 1, wherein: said plurality of circumferential rings include at least one proximal ring, one distal ring and an intermediate ring, at least two of said plurality of circumferential rings having different diameters.

5. A punctum plug according to claim 1, wherein: said head tapers distally toward said shaft.

6. A punctum plug according to claim 1, wherein: a tip is provided at said distal end of said shaft, said tip having a diameter no greater than a diameter of said shaft.

7. A punctum plug according to claim 6, wherein: said tip is one of pointed, rounded and truncated in shape.

8. A punctum plug according to claim 1, wherein: said shaft, said circumferential rings, and said head are flexible.

9. A punctum plug for insertion into a punctum of a wearer comprising:

- a) a shaft having a proximal end, a distal end, and a length;
- b) a plurality of circumferential rings radially extending from said shaft and spaced apart along said length of said shaft and defining spaces therebetween, said plurality of circumferential rings including at least one proximal ring, one distal ring and an intermediate ring, said intermediate ring having a larger diameter than said proximal ring and said distal ring; and
- c) a head at said proximal end of said shaft.

10. A punctum plug for insertion into a punctum of a wearer comprising:

- a) a shaft having a proximal end, a distal end, and a length;
- b) a plurality of circumferential rings radially extending from said shaft and spaced apart along said length of said shaft and defining spaces therebetween; and
- c) a head at said proximal end of said shaft, said head: said head having a concave proximal surface.

11. A punctum plug for insertion into a punctum of a wearer, comprising:

- a) a shaft having a proximal end, a distal end, a circumference, and a length;
- b) a plurality of flanges which extending less than 360 degrees about the circumference and are spaced apart along said length of said shaft; and

c) a head at said proximal end of said shaft.

12. A punctum plug according to claim 11, wherein: said head and said shaft at least partially define an axial bore adapted to receive an insertion tool.

13. A punctum plug according to claim 11, wherein: said head has a radial extension and at least one of said flanges has a radial extension greater than said radial extension of said head.

14. A punctum plug according to claim 11, wherein: said plurality of flanges include at least a proximal flange, a distal flange and an intermediate flange, at least two of the flanges having different diameters.

15. A punctum plug according to claim 14, wherein: said intermediate flange is of a larger diameter than said proximal flange and said distal flange.

16. A punctum plug according to claim 11, wherein: said head tapers distally toward said shaft.

17. A punctum plug according to claim 11, wherein: a tip is provided at a distal end of said shaft, said tip having a diameter no greater than a diameter of said shaft.

18. A punctum plug according to claim 17, wherein: said tip is one of pointed, rounded and truncated in shape.

19. A punctum plug according to claim 11, wherein: said shaft, said plurality of flanges, and said head are flexible.

20. A punctum plug according to claim 11, wherein: said flanges are substantially semicircular.

21. A punctum plug for insertion into a punctum of a wearer comprising:

- a) a shaft having a proximal end, a distal end, a circumference, and a length;
- b) a plurality of flanges which are circumferentially offset and spaced apart along said length of said shaft; and
- c) a head at said proximal end of said shaft, said head: said head having a concave proximal surface.

22. A punctum plug for insertion into a punctum of a wearer, comprising:

- a) a longitudinally extending shaft having a proximal end, a distal end, and a length;
- b) a flexible flange radially extending from and helically coiled about said longitudinally extending shaft; and
- c) a head at said proximal end of said shaft.

23. A punctum plug according to claim 22, wherein: said head and said shaft at least partially define an axial bore adapted to receive an insertion tool.

24. A punctum plug according to claim 22, wherein: said flange has a portion which radially extends from said shaft greater than a maximum radial extension of said head.

25. A punctum plug according to claim 24, wherein: said flange has a proximal portion, a distal portion, and an intermediate portion, said intermediate portion being of larger radial extension than said proximal and distal portions.

26. A punctum plug according to claim 22, wherein: said head tapers distally toward said shaft.

27. A punctum plug according to claim 22, wherein: a tip is provided at a distal end of said shaft, said tip having a diameter which does not exceed a diameter of said shaft.



9

28. A punctum plug according to claim 27, wherein:  
said tip is one of pointed, rounded and truncated in shape.
29. A punctum plug according to claim 22, wherein:  
said shaft, said plurality of said flanges, and said head are  
flexible. 5
30. A punctum plug for insertion into a punctum of a  
wearer comprising:  
a) a shaft having a proximal end, a distal end, a length;  
b) a flange extending from and helically coiled about said  
shaft; and 10  
c) a head at said proximal end of said shaft,  
said head having a concave proximal surface.
31. A punctum plug for insertion into a punctum of a  
wearer, comprising: 15  
a) a shaft;  
b) anchoring means for anchoring said plug within the  
punctum, said anchoring means including at least one  
arm extending from said shaft at at least two axial  
locations along said shaft; and 20  
c) a head at a proximal end of said shaft.

10

32. A punctum plug according to claim 31, wherein:  
said at least one anchoring means is at least one arm  
radially extending from said shaft.
33. A punctum plug according to claim 31, wherein:  
said at least one anchoring means is at least one arm  
extending at an angle less than ninety degrees relative  
to said shaft.
34. A punctum plug according to claim 33, wherein:  
said at least one arm forms a barb.
35. A punctum plug according to claim 34, wherein:  
said barb is adapted to bend both toward said shaft and  
away from said shaft.
36. A punctum plug according to claim 34, wherein:  
said at least one barb is curved.
37. A punctum plug according to claim 34, wherein:  
said at least one arm include a portion which expands in  
size as said portion extends further from said shaft.

\* \* \* \* \*