



US006644504B2

(12) **United States Patent**
Yuyama et al.

(10) **Patent No.:** US 6,644,504 B2
(45) **Date of Patent:** Nov. 11, 2003

(54) **TABLET PACKING APPARATUS**
(75) Inventors: **Shoji Yuyama**, Toyonaka (JP);
Hiroyuki Yuyama, Toyonaka (JP);
Tsuyoshi Kodama, Toyonaka (JP);
Hidenori Murakami, Toyonaka (JP)

(73) Assignee: **Yuyama Mfg. Co., Ltd.**, Toyonaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/828,896**

(22) Filed: **Apr. 10, 2001**

(65) **Prior Publication Data**

US 2002/0162850 A1 Nov. 7, 2002

(30) **Foreign Application Priority Data**

Apr. 11, 2000 (JP) 2000-109302

(51) **Int. Cl.**⁷ **B65G 59/00**

(52) **U.S. Cl.** **221/265; 221/264; 221/130; 221/131; 221/92**

(58) **Field of Search** 221/92, 264, 265, 221/289, 123, 124, 130, 131

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,709,063 A * 1/1998 Yuyama et al. 53/154

5,787,678 A * 8/1998 Koike et al. 53/154
5,852,911 A * 12/1998 Yuyama et al. 53/168
5,901,876 A * 5/1999 Yuyama et al. 221/133
6,012,602 A * 1/2000 Yuyama et al. 221/130
6,145,700 A * 11/2000 Takahashi et al. 221/133
6,202,385 B1 * 3/2001 Kim 53/154
6,349,848 B1 * 2/2002 Uema et al. 221/6
6,508,045 B2 * 1/2003 Kim 53/154

* cited by examiner

Primary Examiner—Donald P. Walsh

Assistant Examiner—Jonathan R Miller

(74) *Attorney, Agent, or Firm*—Wenderoth, Lind & Ponack, L.L.P.

(57) **ABSTRACT**

The present invention provides a tablet packing apparatus which is possible to feed specially administrative tablets separately from general tablets. Specially administrative tablets are contained in a feeder vessel. A tablet reserving member 200 is disposed below the feeder vessel 36. A shutter 203 which is movable to open and close the lower opening of the tablet reserving member 200 is provided. When setting the tablet vessel beneath the tablet reserving member 200 and moving the shutter 203 to open the lower opening of the tablet reserving member 200, the specially administrative tablets are fed into the tablet vessel without passing through the common passage.

10 Claims, 30 Drawing Sheets




Fig. 1




Fig. 2A




Fig. 2B




Fig. 3




Fig. 4




Fig. 5 A




Fig. 5 B




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15 A




Fig. 15 B




Fig. 16 A




Fig. 16 B




Fig. 16 C




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23






Fig. 24




F i g . 2 5 A




12

F i g . 2 5 B



12

F i g . 2 6 A



F i g . 2 6 B




Fig. 27 A




Fig. 27 B




Fig. 27 C





Fig. 28



TABLET PACKING APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a tablet packing apparatus and more particularly to a tablet packing apparatus which is suited to feed specially administrative tablets (for example, pyrine medicine) to a tablet vessel.

2. Description of Related Art

Conventionally, there has been known a tablet packing apparatus in which tablets stored in a tablet feed section are fed through a common passage and contained in a tablet vessel fed from a tablet vessel feed section.

However, in the tablet packing apparatus, even specially administrative tablets such as pyrine medicines and histamine tablets which cause allergy or so to some patients are conveyed through the common passage. Thus, dust from the specially administrative tablets remain on the common passage, allowing the dust to adhere to the surface of other general tablets which are conveyed through the common passage.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a tablet packing apparatus in which it is possible to feed specially administrative tablets separately from general tablets.

The present invention provides, as a solution to the above-described problems with the prior art, a tablet packing apparatus in which tablets fed from a plurality of feeder vessels in a tablet feed section through a common passage are contained in a tablet vessel fed from a tablet vessel feed section. The apparatus includes:

a tablet reserving member disposed below the feeder vessel which stores specially administrative tablets, the tablet reserving member having a lower opening, the tablet reserving member receiving the specially administrative tablets fed from the feeder vessel; and

a shutter which is movable to open and close the lower opening of the tablet reserving member, whereby when setting the tablet vessel beneath the tablet reserving member and moving the shutter to open the lower opening of the tablet reserving member, the specially administrative tablets are fed into the tablet vessel without passing through the common passage.

According to the present invention, the specially administrative tablets such as pyrine medicines and histamine tablets are contained in the tablet reserving member and then fed into the tablet vessel without passing through the common passage. Thus, dust generated during conveyance of the specially administrative tablets do not adhere to the other general tablets which pass through the common passage.

It is preferable that the tablet reserving member is separated from the feeder vessel and connected to the feeder vessel by means of a tube. Thus, it is possible to select a place where the specially administrative tablets are fed from the tablet reserving member. It is also possible to dispose the tablet reserving member at a desired place, resulting in effective dispensing work of the specially administrative tablets.

It is preferable that the tablet reserving member includes a biasing member for biasing the shutter so as to close the lower opening of the tablet reserving member and the shutter is formed with a cutout portion with which the tablet vessel

engages, whereby when engaging the tablet vessel with the cutout portion to push the shutter, the shutter opens the lower opening of the tablet reserving member. Thus, it is possible to easily position the tablet vessel beneath the tablet reserving member and smoothly open the shutter, enhancing workability.

It is preferable that the tablet reserving member includes an indicator for indicating that the specially administrative tablets have been fed into the tablet reserving member, thereby preventing mis-operations.

It is also preferable that the tablet reserving member includes a sensor for detecting opening or closing of the lower opening of the tablet reserving member by the shutter, whereby the specially administrative tablets can be fed from the tablet vessel only when the sensor detects closing of the lower opening of the tablet reserving member. Thus, it is possible to prevent mis-operation and feed a desired number of tablets.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and features of the present invention will become clear from the following detailed description with reference to the accompanying drawings in which:

FIG. 1 is a perspective overall view illustrating a tablet packing apparatus in accordance with the invention;

FIG. 2A is a perspective view illustrating a container chamber held in storage shelves in FIG. 1;

FIG. 2B is a fragmentary perspective view in FIG. 2A;

FIG. 3 is a perspective view illustrating an arm member in FIG. 1;

FIG. 4 is a sectional view illustrating a tablet container section in FIG. 1;

FIG. 5A is an exploded perspective view illustrating a motor base and a feeder vessel in FIG. 4;

FIG. 5B is a bottom view illustrating the feeder vessel in FIG. 5A;

FIG. 6A is a sectional view illustrating the motor base and the feeder vessel in FIG. 4;

FIG. 6B is a fragmentary view illustrating a dividing fin in FIG. 6A;

FIG. 7A is a front view illustrating a rotor provided in a feeder vessel in FIG. 4;

FIG. 7B is a bottom view illustrating the rotor in FIG. 7A;

FIG. 8 is a perspective view illustrating a stock container in FIG. 1;

FIG. 9 is a sectional view of FIG. 8;

FIG. 10 is a perspective view illustrating a vessel taking out portion in FIG. 8;

FIG. 11 is a fragmentary perspective view illustrating the vicinity of a tablet packing section in FIG. 1;

FIG. 12 is a plan view illustrating a vessel support portion and a label fitting apparatus in FIG. 11;

FIG. 13 is a partly enlarged perspective view of FIG. 12;

FIG. 14 is a front view illustrating a vessel support portion and a filling hopper in FIG. 11;

FIGS. 15A and 15B are front views illustrating the operation of a tablet weighing section in FIG. 11;

FIGS. 16A, 16B and 16C are front views illustrating the operation of the tablet weighing section in FIG. 11;

FIG. 17 is a block diagram on the tablet packing apparatus in accordance with the invention;

FIG. 18 is a main flow chart illustrating the tablet packing control;

FIG. 19 is a flow chart illustrating an empty vessel feeding process in FIG. 18;

FIG. 20 a flow chart illustrating a tablet feeding process in FIG. 18;

FIG. 21 is a flow chart continued from FIG. 20;

FIG. 22 is a flow chart illustrating a vessel delivering process in FIG. 18;

FIG. 23 is a flow chart illustrating a recovery process;

FIG. 24 is a flow chart illustrating the tablet recovering process in FIG. 23;

FIGS. 25A and 25B are views illustrating a main menu displayed on a touch panel;

FIGS. 26A and 26B are front views illustrating contents displayed on the touch panel in the case of power-off;

FIG. 27A is a perspective view, in part section, illustrating a particular dispensing apparatus for specially administrative tablets;

FIG. 27B is a sectional view illustrating an example of a tablet container section in FIG. 1 provided the particular dispensing apparatus of FIG. 27A;

FIG. 27C is a sectional view illustrating the motor base and the feeder vessel of the particular dispensing apparatus of FIG. 27A; and

FIG. 28 is a plan view illustrating a tablet feed section provided with a particular dispensing apparatus according to an another embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a tablet packing apparatus in accordance with the invention. The apparatus generally comprises storage shelves 1 provided on one end side of the apparatus, a tablet feeding section 2 provided in the upper part of the apparatus, tablet vessel feeding sections 3 provided under the tablet feeding section 2, a tablet packing section 4 provided between the storage shelves 1 and the tablet vessel feeding sections 3, and a controlling section 5 (see FIG. 17).

The storage shelves 1 have a generally semi-cylindrical shape and includes a plurality of container chambers 6. As shown in FIG. 2A, each container chamber 6 has a rectangular frame body in which at least the surfaces opposed in the direction shown by an arrow in FIG. 2A have openings. The openings are closed with doors 6a biased by means of unshown springs or so. The doors 6a can be opened toward the front surface side, preventing one's hand from being inserted into a packed vessel conveyor 13 that will be explained hereinafter. The doors 6a can be pivoted within a range that does not interfere with a tablet vessel 11 held by a vessel holder 8 that will be explained hereinafter. A display 7 is provided on the upper part of the front side of the container chamber 6. In the embodiment, the feeder vessel number and the tablet count number are displayed on the display 7. The container chamber 6 is also provided with a vessel holder 8. In the vessel holder 8, a pair of holding plates 9 are opposed to each other in a horizontal direction. The holding plates 9 are biased by a spring 9a in the direction in which the holding plates 9 come close to each other. At the lower ends of the holding plates 9 are formed holding lugs 10 which extend in the direction in which the holding plates 9 are opposed. As shown in FIG. 2B, on opposed edges of the holding lugs 10 are formed recesses 10a which have a generally elliptic shape so as to hold a tablet vessel 11. At the back side corners of the holding lugs 10 are formed cutouts 10b which are spread out toward the inside. The cutouts 10b are provided to facilitate the inser-

tion of the tablet vessel 11 into the recesses 10a. A vessel sensor 8a is capable of detecting whether the tablet vessel 11 is held by the vessel holder 8 in the container chamber 6 or not.

As shown in FIG. 1, in the center part of the outer circumference of the storage shelves 1 is provided a touch panel 12, instead of the container chamber 6. The touch panel 12 is provided to allow instruction data on the prescription to be inputted directly.

Inside the storage shelves 1 is provided a conveyor 13 for packed vessel. In the conveyor 13 for packed vessel, as shown in FIG. 3, an arm member 15 is pivotally mounted to a rectangular frame 14 which is capable of traveling vertically.

A bearing recess 16 is provided at each of the upper and lower ends of both outside surfaces of the rectangular frame 14. The bearing recesses 16 are in sliding contact with guide shafts 17 standing at a given interval behind the storage shelves 1. The conveyor 13 for packed vessel can be moved vertically through the medium of a belt (not shown) by the driving of a motor (not shown). A first driving gear 18 is fixed to the center of the lower horizontal plate 14a of the rectangular frame 14. Instead of the bearing recess 16, a roller or a bearing that comes into slide contact with the guide shaft 17 can be used.

The arm member 15 comprises an arm body 19 mounted rotatably on the center shaft of the first driving gear 18. A first driving motor 20 is provided on one end portion of the arm body 19. To the rotating shaft of the first driving motor 20 which protrudes from the bottom surface of the arm body 19 are fixed position detection plates 21 and a second driving gear (not shown) engaged with the first driving gear 18. A rotational position of the second driving gear can be determined by the detection of the position detection plates 21 by a sensor (not shown). With this arrangement, the arm member 15 is rotated in forward or reverse direction in the range of 180° by the drive of the first driving motor 20. On the top surface of the arm body 19 is provided a sliding member 22 which is driven by a built-in, second driving motor (not shown) and thereby reciprocates in the longitudinal direction. On one end portion of the sliding member 22 (on the side opposite to the first driving motor 20) is provided a gripping member 23. The gripping member 23 comprises a pair of gripping pieces 25 which are driven through a gear not shown by a third driving motor 24 provided on the sliding member 22 and thereby open and close.

The third driving motor 24 is driven and stopped based on an electric current value that fluctuates due to a difference of load applied on the gripping pieces 25. Concretely, when the load of the third driving motor 24 increases at the time of gripping and releasing the tablet vessel 11 and then the electric current value exceeds a threshold value (obtained by adding a margin electric current to an electric current value at the normal operation), the third driving motor 24 is stopped. The increase of the load at the time of releasing the tablet vessel 11 is caused by allowing the gripping pieces 25 to come into contact with a stopper (not shown) at a predetermined open position. The gripping pieces 25 are urged toward the open position by an unshown spring or so in order to absorb the backlash of the gear.

The tablet feeding section 2 comprises a tablet container section 26 and a tablet conveyor section 27.

In the tablet container section 26, as partly shown in FIG. 4, grooves 29 extending vertically are provided on both sides of a vertical wall 28. Each groove 29 is covered with a shelf

member **30** provided pivotably about a pivot **30a** so that common guide paths **31** are formed. A plurality of openings **30b** for discharging tablets are provided in a vertical line on each shelf member **30**. A plurality of motor bases **32** corresponding to the openings **30b** for discharging tablets are mounted to the outer surface of each shelf member **30**.

As shown in FIGS. **5A** and **6A**, each motor base **32** has a built-in driving motor **32a**. A driving gear **33** to which the power from the driving motor **32a** is transferred is exposed on the top surface of the motor base **32**. A fall guide path **34** is formed on one end side of the motor base **32**. A tablet detecting sensor **35** is provided on the inner wall of the fall guide path **34**, so that the tablets discharged through the fall guide path **34** can be detected (counted).

A feeder vessel **36** is detachably mounted to the motor base **32**. The feeder vessel **36** is generally in the shape of a rectangle which opens upward and which can be covered with a cover **37**. In the feeder vessel **36** is stored tablets. At the bottom of the feeder vessel **36** is provided a rotor **39** having a gear **38** at the lower end thereof.

As shown in FIGS. **7A** and **7B**, the rotor **39** has conical surfaces on its upper and lower parts. The attachment of the feeder vessel **36** to the motor base **32** engages the gear **38** with the gear **33** on the motor base **32**. On the lower conical surface of the rotor **39** are formed tablet guiding grooves **40** extending spirally toward the center of the surface, and are formed dividing grooves **41** dividing each tablet guiding groove **40** into two parts in the middle thereof. The spiral direction of the tablet guiding grooves **40** toward the center of rotation of the rotor **39** is opposite to the direction of rotation of the rotor **39** (opposite to the direction shown in the arrow in FIG. **7B**). In the dividing grooves **41** is provided a dividing fin **42**. With the rotation of the rotor **39** as shown in FIG. **6B**, the dividing fin **42** divides the line of tablets that pass through the tablet guiding grooves **40**.

As shown in FIG. **5B**, a gear stopper **43** is capable of engaging with the gear **38** in the feeder vessel **36** when the feeder vessel **36** is detached from the motor base **32** and disengaged to the gear **38** when the feeder vessel **36** is mounted. The gear stopper **43** is biased against the gear **38** by a stopper spring **44**. Even though the feeder vessel **36** is detached from the motor base **32**, the above arrangement allows the gear stopper **43** to engage with the gear **38** and prevents the rotor **39** from rotating, so that tablets cannot fall out of the feeder vessel **36**.

In the tablet feeding section **2**, when the driving motor **32a** in the motor base **32** is driven with the feeder vessel **36** attached to the motor base **32**, the rotor **39** is rotated through the medium of the gear **33** and of the driving gear **38**, thereby tablets move in a line toward the center of rotation, forming a line for each tablet guiding groove **40**. As mentioned above, the tablet guiding grooves **40** are formed so as to extend spirally toward the center of rotation of the rotor **39** in the direction opposite to the direction of rotation of the rotor **39**. Tablets are therefore forced to move toward the center of rotation regardless of the centrifugal forces exerted on the tablets by the rotation of the rotor **39**. The line of tablets is divided by the dividing fin **42** before each tablet guiding grooves **40** communicates with the fall guide path **34**, and then fall one by one into the common guide path **31** through the fall guide path **34**.

As shown in FIG. **4**, at the lower ends of the common guide paths **31** are provided a shutter **43** for temporarily retaining the tablets which have fallen from the fall guide path **34**. The shutter **43** comprises a single plate which can horizontally slide across the common guide paths **31**. At the

both end portions of the shutter **43**, openings **43a**, **43b** are formed. When the shutter **43** slides toward the left side, the right common guide path **31** is opened by the right opening **43a**. When the shutter **43** slides toward the right side, the left common guide path **31** is opened by the left opening **43b**. When the shutter stops at the middle point of the slide stroke, the both of the common guide paths **31** are closed.

Beneath the shutter **43**, a hopper **44** is slidably and detachably disposed. Along with the slide operation of the shutter **43**, the hopper **44** can slide to a position where the hopper **44** can receive the tablets. Thus, the tablets received through the common guide paths **31** can be fed to respective conveyor vessels **46** in the tablet conveyor section **27** disposed beneath the hopper **44**.

The tablet conveyor section **27**, as shown in FIG. **11**, comprises two lines of conveyor belts **48** and conveyor vessels **46**. The conveyor belts **48** are looped between a pair of pulleys **47**. The conveyor vessels **46** are supported on the conveyor belts **48** by a support frame **46a** so as to be reciprocated. Rectangular apertures **46c** are provided in a line on a bottom plate **46b** of the support frame **46a** (see FIGS. **11** and **15**). The conveyor belt **48** has continual guide projections **48a**, which engage with the rectangular apertures **46c** to allow the conveyor vessel **46** to be moved. The bottom of the conveyor vessel **46** comprises a shutter **49** which can be opened and closed. The shutter **49** is biased, as shown in FIG. **15**, by a spring **50** provided at one end of the shutter **49** so as to shut the bottom of the conveyor vessel **46**. A protrusion **49a** is formed at one end on the downside surface of the shutter **49**.

As shown in FIGS. **8** and **9**, each tablet vessel feeding section **3** comprises a stock container **51** for storing empty tablet vessels **11**, a vessel takeout section **52** for taking out tablet vessels **11** one by one from the stock container **51**, and an empty vessel conveyor **53** for conveying the tablet vessel **11** taken out from the stock container **51** by the vessel takeout section **52**. The tablet vessel feeding sections **3** are disposed in a line as shown in FIG. **1**. The sizes (outside diameters or lengths) of empty tablet vessels **11** stored in the stock containers **51** are different for each stock container **51**.

The bottom wall **54** of the stock container **51** is inclined downwardly toward the vessel takeout section **52** and is provided with a rotation plate **55** in the vicinity of the vessel takeout section **52**. The rotation plate **55** slightly protrudes from the bottom wall **54**. The rotation plate **55** is periodically rotated both forward and backward by a motor **56** so that the inclined direction of the tablet vessels **11** with respect to the vessel takeout section **52** can be changed. On the upper surface of the rotation plate **55**, a semi-spherical shape of protrusion **55a** is formed. The protrusion **55a** allows the tablet vessel **11** to change its position lateral and assists in taking out of the tablet vessel **11** by the vessel takeout section **52**. Transmission types of photo sensors **54a** are provided above the inclined bottom wall **54**. Indication lamps (not shown) provided on the stock container **51** indicate the remaining quantity of the tablet vessels **11** based on the detected signal of the photo sensors **54a**. Namely, "F" lamp is ON when light between the photo sensors **54a** is intercepted, while "L" lamp is ON when light between the photo sensors **54a** is not intercepted. Moreover, "E" lamp is ON when a sensor provided on a conveyor **61** or a delivery table **62** which will be described hereinafter does not detect the tablet vessel **11** for a predetermined time. Alternatively, the remaining quantity of the tablet vessels **11** may be indicated on the touch panel **12** as shown in FIG. **12**.

The vessel takeout section **52**, as shown in FIG. **10**, comprises rollers **57** juxtaposed vertically and a belt **58**

running between the rollers 57. On the belt 58, lateral vessel holding portions 59 are provided at a predetermined distance along the running direction. Between the lateral vessel holding portions 59, two vertical vessel eliminating portions 60 are provided. Each lateral vessel holding portion 59 comprises a plurality of holding fingers 59a protruding with a predetermined distance. Each vertical vessel eliminating portion 60 comprises a plurality of projections 60a protruding with a predetermined distance. The distance between the lateral vessel holding portions 59 is smaller than the height of the tablet vessel 11 and larger than the outside diameter of the tablet vessel 11. The distance between the holding fingers 59a is larger than the outside diameter of the tablet vessel 11. Thus, the lateral vessel holding portions 59 can surely hold the tablet vessel 11 laterally without engaging the open edge of the tablet vessel 11 with the holding fingers 59a.

The vessel takeout section 52 further comprises a conveyor 61 and a delivery table 62 for conveying the tablet vessels 11 taken out by the vessel takeout section 52 to the empty vessel conveyor 53. The conveyor 61 comprises a pair of rollers 68 and four conveyor ropes 69 running between the rollers 68. The roller 68 is driven to rotate both forward and backward by a motor not shown. The distance between the conveyor ropes 69 is smaller than the outside diameter of the tablet vessel 11. The delivery table 62 has a substantially L shaped section and is pivotable between positions as shown in solid line and two dots chain line respectively in FIG. 9 to deliver the tablet vessels 11 conveyed by the conveyor 61 to the empty vessel conveyor 53. The vessel takeout section 52 is operated when no tablet vessel 11 is detected on the conveyor 61 or delivery table 62 by a sensor not shown for a predetermined time. The empty vessel conveyor 53 is operated in a reverse conveying direction for a predetermined time at the time of power ON initially and after emergency stop. If the empty tablet vessel 11 is present on the way of the empty vessel conveyor 53, the empty tablet vessel 11 is recovered into a recovery box not shown disposed on one end of the empty vessel conveyor 53, namely on the end opposite to the tablet packing section 4.

The empty vessel conveyor 53 is provided below the delivery table 62 along the stock containers 51 arranged in line. In the same manner as the conveyor 66, the empty vessel conveyor 53 comprises a pair of pulleys 71 and a pair of conveyor ropes 72 looped between the pair of pulleys 71.

As shown in FIG. 11, the tablet packing section 4 comprises a fork-like vessel holder section 76 and a tablet weighing section 77.

The vessel holder section 76 has a plurality of support pieces 78 between which the tablet vessel 11 can be supported. The distance between the support pieces 78 corresponds to the size of the tablet vessels 11. In the present embodiment, the vessel holder section 76 can hold S, M and L sizes of the tablet vessels 11. The vessel holder section 76 can reciprocate between a vessel receiving position and a tablet receiving position by means of drive unit not shown.

In the vicinity of the vessel receiving position, first, second and third guide plates 79, 80 and 81 are disposed. The first guide plate 79 has a substantially V-shape so that the tablet vessel 11 conveyed by the empty vessel conveyor 53 can be delivered to the second guide plate 80. The second guide plate 80 is inclined so that the tablet vessel can roll on the second guide plate 80 toward the vessel holder section 76. The third guide plate 81 can pivot above the second guide plate 80 for allowing or disallowing the tablet vessel

11 to be passed to the vessel holder section 76. The third guide plate 81 may be provided with a delivery guide plate which allows the tablet vessel 11 to surely roll.

Under the vessel holder section 76, a vessel aligning plate 82 is disposed. The vessel aligning plate 82 allows the tablet vessels 11 held by the support pieces 78 to align when the vessel holder section 76 is horizontally moved. Thus, it is possible to reduce push quantity by push rollers 92 which will be described hereinafter, resulting in effective operation.

In the vicinity of the tablet receiving position, there are provided a labeler 83 and a lifter 84.

The labeler 83 is arranged to print a medicine name or so on labels 85 and fix the labels 85 to the tablet vessels 11. The labels 85 are in advance stuck to a sheet 87 wound on one roller 86a and released from the sheet 87 when the sheet 87 is turned at a guide tip 88. The sheet 87 with the labels 85 released is rewound on the other roller 86b. Printing to the labels 85 is carried out before releasing the labels 85 from the sheet 87 in such a manner that printing information is heat transferred through a ribbon 90 by means of printing head 89 as the sheet 87 is supported with a backing roller 86c. The ribbon 90 is fed from one roller 91a and rewound on the other roller 91b.

Under the vessel holder section 76, a pair of push rollers 92 and a guide roller 93 are disposed. A size detecting sensor (not shown) for detecting the size of the tablet vessels 11 is provided between the push rollers 92. The push rollers 92 are arranged to push the tablet vessel 11 aligned by the vessel aligning plate 82 in a protruding direction of the support pieces 78, whereby holding the tablet vessel 11 together with the guide roller 93 positioned on the other side. Beneath the tablet vessel 11 held by the push rollers 92 and the guide roller 93, a rotation bearing table 110 is disposed. The rotation bearing table 110 can be raised up to a height corresponding to the size of the tablet vessel 11 detected by the size detecting sensor. The guide roller 93 is urged toward the push roller 92 and rotates the tablet vessel 11 due to drive of a motor 93a.

The lifter 84 can lift up the tablet vessel 11 up to a rotation position where a flange portion of the tablet vessel 11 is positioned slightly above the support pieces 78 and a tablet receiving position where the tablet vessel 11 receive the tablets from a packing hopper 97 which will be described hereinafter.

The tablet weighing section 77 comprises an input hopper 94, a weighing section 95, a measuring hopper 96, a packing hopper 97, and a discharging hopper 98.

As shown in FIG. 15, the approach of the conveyor vessel 46 to the input hopper 94 brings the protrusion 49a of the shutter 49 into contact with an edge of the input hopper 94, causing the shutter 49 to open against the bias exerted by the spring 50. This operation allows the tablets accommodated in the conveyor vessel 46 to fall into the input hopper 94.

As shown in FIGS. 11 and 15, the weighing section 95 comprises a weighing vessel 99 for accommodating tablets which have fallen from the input hopper 94, a weighing device 100 for weighing the weighing vessel 99 along with the accommodated tablets, and a pair of arms 101 for supporting the weighing vessel 99. Two projections 99a, 99b, as shown in FIG. 16A, are formed on each outside surface on both sides of the weighing vessel 99. At the distal end of each arm 101 is formed an engaging recess 101a which engages with the projection 99a at one end. The engaging recess 101a is so shaped that the projections 99a on the weighing vessel 99 are prevented from falling out when tablets in the weighing vessel 99 are fed into the

packing hopper 97 with the pivotal motion of the arms 101. When tablets are fed from the input hopper 94 into the weighing vessel 99, the arms 101 suspend the weighing vessel 99 above the weighing device 100 so that the impulsive force caused by the feeding cannot act directly on the weighing device 100. After the feeding, the arms 101 pivot to load the weighing vessel 99 on the weighing device 100. With this arrangement, the measuring time by the weighing device 100 is shortened.

The bottom surface of the measuring hopper 96 comprises a shutter 96a as shown in FIG. 11. Packing amount detecting sensors 102 are provided on the side surfaces facing each other of the measuring hopper 96, so that the amount of the tablets stocked in the measuring hopper 96 can be determined.

The upper openings of the packing hopper 97 and of the discharging hopper 98 are closed and opened by a closing/opening door 103 provided pivotably. The lower end of the packing hopper 97, as shown in FIG. 14, extends so as to gradually reducing its diameter and connects to a lower cylindrical portion 110 to form a step like shape. In the lower cylindrical portion 110, an internal cylinder 111 is disposed so as to move vertically. A hood 112 is fixed on the upper end of the internal cylinder 111 so that the hood 112 can open and close the internal opening 110a of the lower cylindrical portion 110. Thus, when the tablet vessel 11 is raised by the lifter 84 to push up the internal cylinder 111, tablets sustained by the hood 112 are discharged into the tablet vessel 11.

As shown in FIG. 17, the controlling section 5 receives an input of prescription data from a host computer 105 (or only an input signal from the touch panel 12). The controlling section 5 also receives a signal from or actuates and controls the storage shelves 1 (e.g., the vessel sensors 8a, the touch panel 12, motors 14a, the first driving motor 20, and the third driving motor 24), the tablet feeding section 2 (e.g., the driving motors 32a, and the tablet detecting sensors 35), the tablet vessel feeding sections 3, and the tablet packing section 4 (e.g., the weighing device 100, the packing amount detecting sensors 102) and an emergency stop switch 106 and so on.

The operation of the tablet packing apparatus as arranged above will be described below.

As shown in the flow chart of FIG. 18, first, prescription specifying data based on prescription data is received from the host computer 105 (step S1). A empty tablet vessel feeding process (step S2) and a tablet feeding process (step S3) are then performed simultaneously in parallel on the basis of the prescription specifying data. Subsequently, a tablet packing process (step S4) is performed, and a vessel delivering process (step S5) is then performed for delivering the tablet vessel 11 to the container chamber 6 in the storage shelves 1. The prescription specifying data may be received in multiple according to the processing capacity.

In the empty vessel feeding process, as shown in the flow charts of FIG. 19, in accordance with the above prescription data, the vessel takeout section 52 in the stock container 51 in which the tablet vessels 11 corresponding to the prescription data are contained is operated (step S11). In the vessel takeout section 52, the tablet vessels 11 are conveyed upward in laterally held condition by the lateral vessel holding portions 59. At this time, the vertical vessel eliminating portions 60 prevent the tablet vessels 11 from being held by the lateral vessel holding portions 59 in a vertical condition or in a laterally overlaid condition. Feeding of the next tablet vessel 11 is carried out by operating the vessel

takeout section 52 in the stock container 51 when use of the tablet vessel 11 held on the vessel holder section 76 is decided, i.e., when the next prescription data is inputted.

When the tablet vessel 11 is conveyed upward by the vessel takeout section 52, operation of the conveyor 61 is commenced to move the tablet vessel 11 to the delivery table 62 (step S12). Then, activation of the solenoid not shown causes the delivery table 62 to pivot, whereby the tablet vessel 11 is delivered to the empty vessel conveyor 53 (step S13).

In the empty vessel conveyor 53, after the tablet vessel 11 is delivered from the stock container 51, the motor not shown is driven to convey the tablet vessel 11 to the tablet packing section 4 by the conveyor ropes 72 (step S14).

In the tablet packing section 4, the tablet vessel 11 is delivered to the second guide plate 80 through the first guide plate 79 and then guided by the third guide plate 81 (step S15). The vessel holder section 76 is horizontally moved to position the pair of the support pieces 78 corresponding to the size of the tablet vessel 11 to be conveyed at the lower end edge portion of the second guide plate 80 (step S16). Then, the third guide plate 82 is pivoted so that the tablet vessel 11 is supported by the support pieces 78 of the vessel holder section 76 (step S17). As a result, the flange portion of the tablet vessel 11 is supported, whereby the tablet vessel 11 necessarily becomes to be an upwardly opened condition.

The support positions of the tablet vessels 11 on the support pieces 78 are different in accordance with the sizes and the delivery directions of the tablet vessels 11. Therefore, the vessel holder section 76 is horizontally moved, whereby the tablet vessels 11 are aligned by the vessel aligning plate 82 (step S18). If the tablet vessel 11 reaches the tablet receiving position (step S19), then the movement of the vessel holder section 76 is stopped (step S20). Consequently, the lifter 84 is driven to slightly lift the tablet vessel 11 from the vessel holder section 76 (step S21). In this condition, the push rollers 92 are moved forward (step S22), thereby the tablet vessel 11 is held by the push rollers 92 and the guide roller 93. Then, the motor 93a is driven to rotate the guide roller 93 so that the label 85 on which a predetermined information is printed is fixed on the outer surface of the tablet vessel 11 (step S23).

In the tablet feeding process, as shown in the flow chart of FIGS. 20 and 21, a relevant tablet container section 26 is actuated and controlled on the basis of the prescription specifying data. That is, the built-in motor in the relevant motor base 32 is driven to rotate the rotor 39 to discharge a given number of the tablets stored in the feeder vessel 36 (step S41). The number of the discharged tablets is counted by the tablet detecting sensor 35 provided in the fall guide path 34 (step S42). After the given number of tablets are discharged from the feeder vessel 36 through the fall guide path 34 into a common guide path 31 (step S43), the rotation of the rotor 39 is halted to suspend the discharge of tablets (step S44).

The tablet conveyor section 27 is then actuated and controlled; that is, the pulleys 47 are driven and rotated so that the conveyor vessel 46 is moved by the conveyor belt 48 and positioned under the common guide path 31 (step S45). The hopper 44 is then rotated to direct the opening thereof to the conveyor vessel 46 (step S46), and the shutter 49 is opened to allow the tablets to be stored into the conveyor vessel 46 (step S47).

After the given number of the relevant tablets are stored in the conveyor vessel 46, the conveyor vessel 46 is moved to the input hopper 94 by the actuation and control of the

tablet conveyor section 27 (step S48). At this time, the protrusion 49a of the shutter 49 comes into contact with an edge of the input hopper 94, and the movement of the conveyor vessel 46 thereby causes the shutter 49 to open gradually, so that the stored tablets are inputted into the weighing vessel 99 through the input hopper 94. The weighing vessel 99 is then suspended slightly above the weighing device 100 by the pivotal motion of the arms 101, so that the impulsive force caused by the input of the tablets cannot act directly on the weighing device 100. Subsequently, the weighing vessel 99 is loaded on the weighing device 100 by the pivotal motion of the arms 101 and the weight of the weighing vessel 99 is measured (step S49).

It is then judged whether the weight is as large as a given weight or not (step S50). The tablets are then fed into the measuring hopper 96 by the pivotal motion of the arms 101 (step S51). Whether the amount of the tablets is within the capacity of the tablet vessel 11 or not is then judged on the basis of detection signals from the packing amount detecting sensors 102 in the measuring hopper 96 (step S52).

In the case that the weight is as large as the given value and that the amount of the fed tablets is not more than the given amount, it is judged that the relevant tablets could be packed by the given amount. Then, the tablet vessel 11 is further lifted by the lifter 84 so that the internal cylinder 111 of the packing hopper 97 is raised (step S53). As a result, the internal opening 110a is opened by the hood 112, whereby the tablets are packed in the tablet vessel.

In the case that the weight is larger or smaller than the given value or that the amount of the fed tablets is larger than the given amount, it is judged that the tablets are irrelevant or that the amount of the tablets exceeds the capacity of the tablet vessel 11. The opening of the packing hopper 97 is then closed (step S54), and the shutter 96a is opened (step S55). The tablets are thus discharged through the discharging hopper 98. In this case, returning to step S41, the tablet feeding process is performed afresh.

After the tablets are packed into the tablet vessel 11, the process for delivering the vessel to the storage shelves 1 is performed. At this time, a using condition of the container chamber 6 is confirmed by referring to a storage shelves data table and a vacant container chambers 6 are specified. The storage shelves data table is established based on detected signal of the vessel sensor 8a provided in each container chamber 6 of the storage shelves 1. Among the vacant container chambers 6, the order of the container chambers 6 in which the tablet vessel 11 is to be delivered is decided. In the present embodiment, the order of positions of the container chambers 6 that an operator can easily take out the tablet vessel 11 is decided.

After the container chamber 6 to which the tablet vessel 11 is to be delivered is decided, as shown in FIG. 22, the arm member 15 is caused to pivot (step S61), the sliding member 22 is moved forward relative to the arm body 19 (step S62), and the tablet vessel 11 is gripped by the gripping pieces 25 (step S63). The sliding member 22 is then retracted (step S64), and the arm member 15 is caused to pivot and elevated (step S65). The position where the arm member 15 is to reach with the pivotal motion and elevation is such a position as determined as described above, i.e., the container chamber 6 from which the operator can easily take out the tablet vessel 11.

Once the arm member 15 reaches the determined position to reach with the pivotal motion and elevation (step S66), a using condition of the container chamber 6 is confirmed again based on the detected signal of the vessel sensor 8a

provided in the corresponding container chamber 6. If the tablet vessel 11 is not contained, the sliding member 22 is moved forward to open the door 6a and deliver the gripped tablet vessel 11 to the container chamber 6 in the storage shelves 1 (step S67). The tablet vessel 11 then travels to the recesses 10a while pushing aside the holding plates 9 in the container chamber 6 through the medium of the cutouts 10b formed in the holding lugs 10, and is held with the bias exerted by the spring 9a. The gripping pieces 25 are then released (step S68); the sliding member 22 is retracted (step S69); and the arm member 15 is subsequently lowered (step S70) for the delivery of the next tablet vessel 11. Just before the tablet vessel 11 is contained in the container chamber 6, if a tablet vessel 11 is detected in the container chamber 6, another container chamber 6 in which the tablet vessel 11 can be contained is retrieved and then the tablet vessel 11 is contained in the retrieved container chamber 6.

In the selection of the aimed container chamber 6, the container chambers 6 may be numbered so that the number increases with increase in the period of time required for the delivery of a tablet vessel 11 to the container chamber 6 by the arm member 15, and the vacant container chamber 6 which has the smallest number may be selected as the aimed chamber.

Once the tablet vessel 11 packed with the given amount of the specified tablets is thus delivered to the container chamber 6 in the storage shelves 1, the numbers assigned to the feeder vessels and the counts of the tablets are displayed on the display 7 of the relevant container chamber 6 in response to a detection signal from the vessel sensor 8a (step S71).

In the aforementioned tablet packing apparatus, when an emergency stop button which is provided in both the lower middle portion of the storage shelves 1 and the middle portion of the tablet vessel feeding sections 3 is pressed down, or power supply is cut off due to power failure or the like during the operation, the apparatus is shut down. In this case, the power supply to the motor base 32 which operates the tablet container section 26 is stopped, preventing mis-feeding of the tablets. Whereas, the power supply to the controlling section 5 is not stopped and it is communicated to the controlling section 3 that it is an emergency stop condition. At the normal stop of the power supply, without simultaneously stopping the power supply to both the motor base 32 and the controlling section 5, the power supply to the motor base 32 is stopped first and then the power supply to the controlling section 5 is stopped. The controlling section 5 is possible to receive power supply from a secondary power source not shown, the operating condition is maintained. However, there may arise a case that an information on the tablet vessel 11 and the tablet which had been under conveyance can not be perfectly controlled. Thus, it is required to execute a restoring process in which the tablet vessel 11 and the tablet which had been under conveyance is recovered to reset the information.

In the restoring process which will be explained in detail hereinafter, the tablet vessel 11 and the tablet which had been under conveyance is recovered into the container chambers 6 of the storage shelves 1. Therefore, in the case that there is no room or few room for the container chambers 6, the tablet vessels 11 should be removed from the container chambers 6 so that the restoring process can be executed. Moreover, in the conveyance path of the tablet vessels 11 (the empty vessel conveyor 53, the vessel holder section 76 and so on), the empty vessel conveyor 53 is reversed for a predetermined time to remove the tablet vessel 11 on the empty vessel conveyor 53. In the vessel holder section 76, the size data of the tablet vessel 11 is memorized again by

means of the size detecting sensor for detecting the size of the tablet vessel **11** provided between the push rollers **92**.

It is preferable to make an indication on the touch panel **12** that the tablet is removed. Since an error that either the feeder vessels **36** or the stock vessel **51** is empty does not show abnormality, the restoring process is not executed in such case.

The restoring process will be explained in accordance with the flow chart as shown in FIG. **23**.

The controlling section **5** is once powered off (step **S81**). This is because of the deletion of the processing data temporarily stored in the memory of the controlling section **5**. When an area displayed on the touch panel **12** by "CLOSE" as shown in FIG. **25A** is touched, the indications of "DO YOU WANT TO POWER OFF?", "YES" and "NO" are displayed as shown in FIG. **26A**. If the "YES" is selected, the indication that "IT'S SAFETY EVEN IF POWER IS POWERED OFF" is displayed as shown in FIG. **26B** to power off.

If the emergency stop button is pressed down (step **S82**), then the emergency stop button is reset (step **S83**) and the controlling section **5** is powered on again (step **S84**). Thus, the menu is displayed on the touch panel **12** as shown in FIG. **25A**.

Among the items as shown in FIG. **25A**, if the "RECALL" is touched (step **S85**), then the recovering process of the tablet which had been under conveyance is commenced (step **S86**). At this time, the indication that "RECALL UNDER PROCESS . . ." is displayed on the touch panel **12** as shown in FIG. **25B** to indicate that restoring process is going on (step **S87**).

In the tablet recovering process, the tablets remaining in the conveyor vessels **46** and the hoppers **44** are recovered as shown in flow chart of FIG. **24**. At first, the vessel holder section **76** is moved to position the tablet vessel **11** having the largest capacity at the packing position, i.e., beneath the packing hopper **97** (step **S91**). Normally, since the tablet vessel **11** having the largest capacity is ready on the vessel holder section **76**, such tablet vessel **11** is used. If such tablet vessel is not ready, it is replenished from the stock vessel **51**. On the other hand, the tablets are recovered from any one of the common guide paths by means of the conveyor vessel **46** (step **S92**). Then, the tablets are packed into the largest tablet vessel **11** through the input hopper **94** and the packing hopper and so on (step **S93**). Consequently, the tablet vessel **11** packed with the tablets is transferred to the container chamber **6** of the storage shelves **1** by the arm member **15**. At the same time, a tablet vessel **11** having the same size as the tablet vessel transferred to the storage shelves **1** is replenished to the vessel holder section **76** (step **S95**). In addition, the indication of "P000" is displayed on the display **7** (step **S96**) to enable an operator to distinguish at a glance that the recovered tablets are packed in the tablet vessel **11** transferred to the container chamber **6**.

In the same manner as explained above, a tablet vessel **11** having the largest capacity is replenished to the vessel holder section **76** from the stock vessel **51** to recover the tablets remaining in the another common guide paths **31**. Although there may be no tablet in the common guide paths **31**, the recovery process of tablets should be executed from all of the common guide paths **31** in order to perfectly grasp which tablets had been under conveyance.

If the tablets remaining in all common paths **31** (step **S97**) is recovered, then other size of the tablet vessels **11** held on the vessel holder section **76** are recovered to the storage shelves **1** (step **S98**). In this case, the tablet vessels **11** having

the same size as that of the tablet vessels **11** which are recovered and transferred to the container chamber **6** of the storage shelves **1** are replenished to the vessel holder section **76** from the corresponding stock vessel **51** (step **S99**).

If the recovery of the tablet vessels is finished (step **S100**), then main menu is displayed on the touch panel **12**. The touch with "AUTO" enables the restoration to the normal operation, i.e., the tablet vessel feeding process (step **S2**), the tablet feeding process (step **S3**) and the tablet packing process (step **S4**) in the same manner as described before.

In the above explained restoring process, in the case that the tablet packing apparatus is stopped due to the abnormality, the controlling section **5** is always powered off to clear the processing data stored in the memory. However, it may be also possible to have the operator select whether such processing data is utilized or not. For example, when the indication of "RECALL" displayed on the touch panel **12**, the processing data which are stored before the apparatus is stopped may be utilized to continue the process. In this case, the tablet vessels **11** remaining in the empty vessel conveyor **53**, the vessel holder section **76** and so on, or the tablets remaining in the common guide paths **31** and the like are not necessary to be recovered.

Moreover, in the above explained restoring process, the indication of "P000" indicating recovery is displayed on the display **7** of the container chamber **6**. Instead of this, it is also possible to indicate which feeder vessel **36** the tablets were discharged from. In this case, it is necessary to memorize the common guide path from which the tablets were recovered based on the position of the conveyor vessel **46**. Thus, according to both the memorized common guide path and the processing data, it is possible to specify the feeder vessel **36** from which the tablets were discharged.

Oftentimes the tablets to be contained in the tablet feeding section **2** include specially administrative tablets (for example, pyrine medicines and histamine tablets which cause allergy). Therefore, if a packing operation is carried out through a common passage, there would be a risk that the drug forming the specially administrative tablets would intermingle or mix with the other tablets due to the troubles and so on of the apparatus. Therefore, it is preferable to provide a particular dispensing apparatus, in the tablet feeding section **2**, containing the specially administrative tablets.

As shown in FIG. **27A** and FIG. **27C**, the particular dispensing apparatus comprises a tablet reserving member **200** for temporarily reserving the tablets fed from the motor base **32'**. An upper opening **208** of the tablet reserving member **200** communicates with a fall guide path **207** in the motor base **32'**. An LED **201** is provided on the front surface of the motor base **32'**. The LED **201** is ON when the tablets are received in the tablet reserving member **200** from the motor base **32'**. The lower opening of the tablet reserving member **200** can be closed by a shutter **203** which is rotatably supported around a support shaft **203a** on a support member **202**. The shutter **203** is formed with an arc-like cutout **204** on its front edge and also provided with a detection piece **205** on its side edge. The cutout **204** is arranged so as to engage the flange of the tablet vessel with the internal edge of the cutout **204** in order to position the tablet vessel **11** to push the shutter **203**. The detection piece **205** is detected by a sensor **206** provided on the support member **202** when the lower opening of the tablet reserving member **200** is closed by the shutter **203**. The shutter **203** is urged by urging means such as a spring or the like (not shown) so that the lower opening of the tablet reserving member **200** can be closed.

In the tablet feeding section **2** with the particular dispensing apparatus having the above-described construction, when the motor base **32'** is driven and the specially administrative tablets are received in the tablet reserving member **200**, the LED **201** is ON. Thus, an operator can recognize at a glance from which tablet feeding section **2** the specially administrative tablets were discharged. Then, the operator sets the tablet vessel **11** on the particular dispensing apparatus of the tablet feeding section **2** in which the LED **201** is ON. Consequently, with the tablet vessel **11** engaged with the cutout **204**, the operator pushes the shutter **203**. As a result, the shutter **203** is pivoted around the support shaft **203a** against the force of the urging means. Thus, the upper opening of the tablet vessel **11** can communicate with the lower opening of the tablet reserving member **200**, and thereby the specially administrative tablets in the tablet reserving member **200** are packed or received in the tablet vessel **11**. At this time, as the sensor **206** does not detect the detection piece **205** of the shutter **203**, the LED **201** is OFF.

Instead of the tablet reserving member **200** shown in FIGS. **27A–27C**, a tablet reserving member having such a construction as shown in FIG. **28** with a shutter **300** and sensors **301a**, **301b** can be adopted.

The shutter **300** has a fan-shape. On the front edge thereof the shutter **300** is formed with a guide portion **302** comprising an arc-like cutout, while on the rear edge thereof the shutter **300** is formed with a protrusion **303** which is detected by sensors **301a**, **301b**. The shutter **300** is urged in a counterclockwise direction in FIG. **28** around a support shaft **301a** by a spring **304** provided around the support shaft **301a**. Therefore, if no load is applied, the shutter **300** closes the lower opening **305** of the tablet reserving member. The guide portion **302** is directed toward the front side, allowing the upper opening of the tablet vessel **11** to position easily in place. The protrusion **303** is detected by the sensor **301a**, i.e., the closes condition of the shutter **300** is detected by the sensor **301a**, whereby the tablets can be fed from the motor base **32**. However, after the tablets are discharged in the tablet reserving member, the tablets can not be fed from the motor base **32** unless the opened condition of the shutter **300** is detected. Thus, the feed of the tablets are controlled based on the signals from the sensors **301a**, **301b** and the motor base **32**, whereby the feed of the tablets can be constantly properly conducted.

In the aforementioned embodiment, to the tablet feeding section **2** with the specially administrative tablets contained, the tablet reserving member **200** of the particular dispensing apparatus is directly fixed. However, the tablet reserving member **200** may be connected to the tablet feeding section **2** via a tube or so. Thus, it is possible that the tablet reserving member **200** have a mounting and dismounting construction and is disposed at a proper position to dispense the specially administrative tablets.

Although the present invention has been fully described by way of the examples with reference to the accompanying drawing, it is to be noted that here that various changes and modifications will be apparent to those skilled in the art. Therefore, unless such changes and modifications otherwise depart from the spirit and scope of the present invention, they should be construed as being included therein.

What is claimed is:

1. A tablet packing apparatus in which tablets fed from a plurality of feeder vessels in a tablet feed section through a common guide path are packaged in a tablet vessel fed from a tablet vessel feed section, the apparatus comprising:

a fall guide path formed in a motor base on which a feeder vessel, which stores specially administrative tablets, is

mounted, wherein the fall guide path does not communicate with the common guide path;

a tablet reserving member disposed below the motor base on which the feeder vessel which stores specially administrative tablets is mounted, the tablet reserving member having an upper opening which communicates with the fall guide path of the motor base and a lower opening, the tablet reserving member receiving the specially administrative tablets fed from the feeder vessel through the fall guide path of the motor base; and a shutter which is movable to open and close the lower opening of the tablet reserving member, wherein when setting the tablet vessel beneath the tablet reserving member and moving the shutter to open the lower opening of the tablet reserving member, the specially administrative tablets are fed into the tablet vessel without passing through the common guide path.

2. The tablet packing apparatus as in claim 1, wherein the tablet reserving member is separated from the feeder vessel and connected to the feeder vessel by means of a tube.

3. The tablet packing apparatus as in claim 1, wherein the tablet reserving member includes a biasing member for biasing the shutter so as to close the lower opening of the tablet reserving member and the shutter is formed with a cutout portion with which the tablet vessel engages, whereby when engaging the tablet vessel with the cutout portion to push the shutter, the shutter open the lower opening of the tablet reserving member.

4. The tablet packing apparatus as in claim 1, wherein the tablet reserving member includes an indicator for indicating that the specially administrative tablets are fed into the tablet reserving member.

5. The tablet packing apparatus as in claim 1, wherein the tablet reserving member includes a sensor for detecting opening or closing of the lower opening of the tablet reserving member by the shutter, whereby the specially administrative tablets can be fed from the tablet vessel only when the sensor detects closing of the lower opening of the tablet reserving member.

6. A tablet packing apparatus including a tablet feed section comprising a plurality of tablet feeder vessels for feeding tablets through a common guide path to a tablet vessel, said tablet feed section further comprising:

at least one motor base defining a tablet fall guide path that does not communicate with the common guide path;

a feeder vessel, mounted on said motor base, for storing specially administrative tablets;

a tablet reserving member disposed below said motor base, said tablet reserving member having a lower opening and an upper opening communicating with the fall guide path of said motor base such that said tablet reserving member receives the special administrative tablets fed from said feeder vessel; and

a shutter for opening and closing the lower opening of said tablet reserving member, wherein said shutter can be moved from a closed position to an open position by moving a tablet vessel beneath said tablet reserving member and engaging said shutter to open the lower opening and feed the specially administrative tablets into the tablet vessel without passing through the common guide path.

7. The tablet packing apparatus as claimed in claim 6, wherein said tablet reserving member is connected to said feeder vessel by means of a tube.

8. The tablet packing apparatus as claimed in claim 6, wherein said tablet reserving member includes a biasing member for biasing said shutter into a position closing the

17

lower opening of said tablet reserving member, and said shutter is formed with a cutout portion for engaging a tablet vessel such that when the cutout portion is engaged with the tablet vessel, said shutter is moved so as to open the lower opening of said tablet reserving member.

9. The tablet packing apparatus as claimed in claim 6, wherein said tablet reserving member includes an indicator for indicating that the specially administrative tablets have been fed into said tablet reserving member.

18

10. The tablet packing apparatus as claimed in claim 6, wherein said tablet reserving member includes a sensor for detecting whether the lower opening of said tablet reserving member is open or closed by said shutter so that the specially administrative tablets can be fed from said feeder vessel only when said sensor detects that the lower opening of said tablet reserving member is closed.

* * * * *