



US006684580B1

(12) **United States Patent**  
**Hull**

(10) **Patent No.:** **US 6,684,580 B1**  
(45) **Date of Patent:** **Feb. 3, 2004**

(54) **POST STABILIZATION SUPPORT**

(76) Inventor: **David Hull**, 262 Blueberry Dr.,  
Columbiana, OH (US) 44408

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/265,382**

(22) Filed: **Oct. 7, 2002**

(51) **Int. Cl.**<sup>7</sup> ..... **F16M 13/00**; E02D 27/42

(52) **U.S. Cl.** ..... **52/170**; 52/149; 52/152;  
52/127.2; 256/19; 256/64; 33/379

(58) **Field of Search** ..... 52/146, 149, 152,  
52/170, 127.2, 126.1, 749.1; 256/19, 30,  
31, 63, 64; 248/519, 163.1, 166, 412, 188.5,  
180.1, 177.1; 33/379, 404

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

877,268 A *	1/1908	Buren	52/165
882,870 A *	3/1908	Cary	135/140
1,217,606 A *	2/1917	Kane	384/24
1,722,352 A *	7/1929	Rawley	52/152
2,903,856 A *	9/1959	Dean	405/225
3,051,425 A *	8/1962	Homrighausen	248/168

3,239,176 A *	3/1966	Johnson	248/166
3,809,346 A	5/1974	Jackson	
4,099,354 A *	7/1978	DePirro	52/146
4,202,108 A *	5/1980	Adams et al.	33/379
5,104,074 A	4/1992	Malloy	
5,192,055 A	3/1993	Griggs et al.	
5,207,004 A *	5/1993	Gruetzmacher	33/379
5,255,443 A *	10/1993	Schmidt	33/373
5,460,344 A	10/1995	Malloy	
5,685,522 A	11/1997	Randolph, Jr.	
6,155,529 A *	12/2000	De Carlo	248/523
6,254,043 B1 *	7/2001	Schwarzler	248/163.1

\* cited by examiner


*Primary Examiner*—Brian E. Glessner



(74) *Attorney, Agent, or Firm*—Harpman & Harpman

(57) **ABSTRACT**

An adjustable post stabilization support device that includes a multiple sided post receiving sleeve having oppositely disposed pairs of extensible ground engagement leg assemblies thereon. Locking cam levers securing the sleeves on said posts with the extensible leg assemblies being hinged to the bottom of the sleeve. Each of the leg assemblies is independently adjustable and has a ground engagement foot on its extensible portion. Vertical orientation provided for alignment of the sleeve and associated post by two horizontal planes.

**16 Claims, 5 Drawing Sheets**








Fig. 4




Fig. 3






Fig. 6




Fig. 5




Fig. 9

Fig. 8

Fig. 7




Fig. 10




Fig. 11




Fig. 12




Fig. 13



## POST STABILIZATION SUPPORT

### BACKGROUND OF THE INVENTION

#### 1. Technical Field

This invention relates to post supporting devices that are used to temporarily hold a fence post or the like and vertical alignment in the ground during installation.

#### 2. Description of Prior Art

Prior art devices have been directed to fence posts and the like that are inserted into the ground by digging a hole, placing the post within and filling around the post with concrete and allowing it to set. The installation of such a post is difficult and time consuming requiring a temporary support to be used to hold the post in an upright vertical position (plum) while the cement hardens. Typically, such temporary supports are made on site by the use of scrap lumber nailed to the post and to a stake driven into the ground on two vertical planes. Such temporary supports are required in two directions to assume proper vertical alignment.

Prior art is directed to permanent brace systems that can be reused and require less time to set up. More specifically, most prior art is directed to semi-permanent fence post supports used to brace and hold metal fence post that are driven directly into the ground. Such fence bracing is used on corner support posts or where high lateral loads would be encountered, such as gate supports and the like.

In U.S. Pat. No. 3,809,346, a fence post support is disclosed having a post engagement socket extending from a ground engagement base plate extending under the socket. Pairs of angularly apertured brackets receive drift pins that are driven into the ground at angles to hold the socket base in vertical position.

Prior art patents directed towards fence post supports for fence posts driven into the ground can also be seen in U.S. Pat. Nos. 5,104,074, 5,192,055, and 5,460,344.

In U.S. Pat. No. 5,104,074 a fence post support can be seen having a pair of tubular braces that are held on the fence post by a collar that slips over the post and bearing elements which are pivotally secured to the ends of the respective tubular braces.

In U.S. Pat. No. 5,192,055, a portable brace assembly for fence posts having a pair of interengaging posts brackets as disclosed. Multiple adjustable legs extend from the upper bracket while the lower post engagement bracket have ground engagement members which are adjusted to correspond to ground surface variations.

A fence support can be seen in U.S. Pat. No. 5,460,344 wherein a pair of legs are temporarily secured to a metal fence post by an engagement collar. Each leg has a ground engagement pin sleeve for guiding a pin within aligned configuration utilizing a secondary leg assembly so multiple legs can extend from a single post engagement fitting or interengage with a second post in spaced relation thereto.

Finally, in U.S. Pat. No. 5,685,522, a fence post trim collar is claimed having a collar with hinge sections to be placed around the base of the post to prevent the growth of vegetations thereabout.

### SUMMARY OF THE INVENTION

The present invention is directed to a post alignment and support device that includes an adjustable post engagement sleeve removably secured to the post. Pairs of multiple leg assemblies extend from the sleeve to provide a four-point

support for the post. Each leg assembly has an extensible ground engagement leg portion that can be extended or retracted to the required length to maintain the post in a true vertical upright alignment until a foundation material about the post is set. Leveling devices are integrated within the sleeve for ease of vertical alignment by corresponding horizontal planes.

### DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view of the invention in use on a post set in the ground;

FIG. 2 is a partial perspective view of the post engagement portion of the invention;

FIG. 3 is an enlarged partial cross-sectional view illustrating the cam locking assembly of the invention;

FIG. 4 is a left side elevational view of the invention with portions broken away;

FIG. 5 is a right side elevational view of the invention with portions broken away;

FIG. 6 is a top plan view of the invention;

FIG. 7 is an enlarged partial front elevational view of an adjustable leg assembly;

FIG. 8 is an enlarged partial side elevational view of the leg assembly as seen in FIG. 7;

FIG. 9 is a section on lines 9—9 of FIG. 8;

FIG. 10 is a front elevational view of an alternate form of the invention showing a removable portion of the engagement sleeve;

FIG. 11 is an enlarged section of the alternate form of the invention illustrating the engagement of the removable panel to the main sleeve;

FIG. 12 is a second alternate form of the invention illustrating a hinge configuration for a removable panel of the sleeve; and

FIG. 13 is a partial side elevational view of the hinged removable panel illustrating an engagement locking latching mechanism thereto.

### DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 1, 2 and 3 of the drawings, a post support 10 can be seen having a post engagement portion 11 and multiple ground stabilization portions 12. The post engagement portion 11 is comprised of a generally rectangular retaining sleeve 13 having multiple sides 14, 15, 16 and 17. Each of the respective sides 14—17 is of a generally rectangular configuration and of equal height and width and defines a post engagement area 18 within. A locking post engagement assembly 19 is centered within the respective sides 14 and 17 having a pair of spaced parallel mounting lugs 20 extending therefrom. An opening at 21 is defined between the upstanding lugs 20 which are apertured at 22 for receiving a pivot pin 23 on which is positioned a movable cam arm 24. The cam arm 24, best seen in FIGS. 2 and 3 of the drawings has a cam portion 25 with a corresponding contoured cam engagement surface 25A thereon. A handle extension 26 extends integrally from the cam portion 25 which has an off center mounting aperture for the pivot pin 23, noted above.

Referring now to FIGS. 3 and 6 of the drawings, it will be seen that the retaining sleeve 13 when positioned on a post 27 can be locked thereto by rotation of the respective cam arms 24 indicated by directional arrows A engaging the post 27 forcing the respective sleeve sides 15 and 16 against the



post. The cam arms **26** so engage as indicated by the broken lines in FIG. **3** of the drawings will lock in a deployed position due to the respective cam surfaces **25A** as will be evident to those skilled in the art.

The multiple ground stabilizer portions **12** are each defined by adjustable leg assemblies **28**, best seen in FIGS. **1, 4, 6, 7, 8** and **9** of the drawings. Each leg assembly **28** has three tubular leg elements **29, 30,** and **31**. The leg elements **29** and **31** are secured at the respective upper ends to a hinge mounting fitting **32** which has a pair of leg engagement plates **32A** and **32B** and sleeve engagement plate **33**. A hinge pin **34** interconnects the respective hinge plate portions as in a typical hinge configuration. The leg elements **28** and **31** are tapered on their hinge engagement ends **35** and have respective effacing registration channels **36** that extend longitudinally their entire length. The channels **36** are keyed to registerably accept corresponding ribs **37 & 38** on oppositely disposed longitudinal sides of the center leg **30** as seen in FIG. **7** of the drawings. A leg locking clamp assembly **39** is used to lock the center leg **30** when extended. The clamp assembly **39** has a front and back leg engagement plates **40A** and **40B** interconnected by an adjustment bolt **41** that extends through said respective plates and the central leg **30**. An adjustment knob **42** is threadably secured on the free end of the adjustment bolt **41** allowing for compression of the hereinbefore described engagement plates **40A** and **40B** against the abutting legs **29, 30** and **31** frictionally locking and holding the center leg **30** in position when extended as best seen in FIGS. **7** and **8** of the drawings.

In use, the post support **10** is positioned on the post **27** that has been inserted within a hole **43** in the ground indicated at **44** and filled thereabout by foundation material such as concrete **45** as best seen in FIG. **1** of the drawings. The retaining sleeve **13** is temporarily secured in place by the activation rotation of the respective cam arms **24** of the locking engagement assemblies **19** as hereinbefore described.

The leg assemblies **28** are then deployed and the post **27** is vertically aligned (plum) by using a pair of horizontally oriented bevel levels **46** that are mounted on the outside surface of respective sleeve sides **15** and **16** in oppositely disposed relation to the locking engagement cam assemblies **19** as best seen in FIGS. **5** and **6** of the drawings. As required, the center legs **30** are extended from the respective leg assemblies at an appropriate support angle illustrated in FIG. **1** of the drawings required to hold the post **27** in the vertically aligned position until the cement **45** is set. Each of the center ground engaging legs **30** has earth engagement stake **47** extending from its free end. A small footpad **48** extends from each of the center legs **30** adjacent the ground engagement stake for insertion of same by applying pressure thereto as will be understood by those skilled in the art. The leg assemblies **28** are then locked in their extended adjusted position by rotation of the adjustment knob **42** drawing the respective engagement plates **40A** and **40B** together as noted above.

Referring now to FIG. **10** of the drawings, an alternate form of the invention can be seen wherein a post support **50** is illustrated having a removable side panel **51**. The removable panel **51** will allow the post support **50** to be used in situation where it is impractical to slip a post engagement sleeve **52** over the end of the post for removal once it has been secured in the ground due to the height of the post which may occur in certain applications. Removable side panel **51** has oppositely disposed engagement edge beads **53** thereon for sliding engagement within corresponding edge channels **54** formed on respective adjacent sleeve panels **55**

and **56** of the engagement sleeve. The respective edge channels **54** have closed ends at **57** to prevent the removable panel **51** from sliding therethrough.

Referring now to FIGS. **12** and **13** of the drawings, a second alternate form of the invention can be seen in which a hinged panel **58** is hinged to its respective adjacent side panel **59** on an alternate sleeve assembly **60**. The panel **58** can then be hinged outwardly from an adjacent side support panel **61**. The side support panel **59** is formed with a plurality of longitudinally spaced hinge elements **62**. The hinged panel **58** has corresponding registered hinge elements **63** and a quick release latch **64** illustrated in FIG. **13** of the drawings. The quick release latch has flexible hasp element **65** that frictionally engages an upstanding ridge **66** to secure same when in secured position.

In the preferred form and the alternate form, the panels are preferably made of molded synthetic resin material and is important to note that in all of the alternate forms discussed, the removable hinged panel would preferably have the bubble levels **46A** thereon maintaining the fixed panel for locking engagement assembly.

It will be evident from the above description that the leg assemblies **28** will be used with the alternate post engagement sleeves to provide the post stabilization and support needed to effect the proper setting of the post **27** as hereinbefore described.

It will thus be seen that a new and novel post-supporting device has been illustrated and described and it will be apparent to those skilled in the art that various changes and modifications may be made therein without departing from the spirit of the invention, therefore I claim:

1. A post stabilization support to temporarily support a post during installation, said post support comprising, a post engagement sleeve having a plurality of oppositely disposed interengaging side panels, locking post engagement assemblies extending through some of said side panels, adjustable leg assemblies pivotally secured and extending from each of said side panels, means for vertically aligning said sleeve portion on said post in two horizontal planes and means for adjustably extending and locking each of said leg assemblies for ground engagement independently from one another.

2. The post stabilization device set forth in claim 1 wherein said post engagement sleeve is of a rectangular cross section, a pair of adjacent side panels engaging the post opposite said locking post engagement assemblies.

3. The post stabilization support device set forth in claim 1 wherein said locking post assemblies comprise, a cam arm pivotally positioned from a first non-post engagement position to a second post engagement position.

4. The post stabilization support device set forth in claim 1 wherein said adjustable leg assemblies comprises multiple tubular legs, interengaged with one another.

5. The post stabilization support device as set forth in claim 1 wherein said means for vertically aligning said post with said sleeve comprises a bubble level on respective interconnected adjacent side panels of said sleeve.

6. The post stabilization support device set forth in claim 1 wherein said means for adjusting each of said leg assemblies comprises, a central movable leg, a clamp secured to said central movable leg and engageable on said adjacent legs.

7. The post stabilization support device set forth in claim 1 wherein said post engagement sleeve is preferably made of synthetic resin material.

8. The post stabilization support set forth in claim 1 wherein said leg assemblies are preferably made of metallic material.



5

9. A post stabilization support for temporarily supporting a post in vertical alignment position during installation comprising a post engagement sleeve, a pair of posts registration assemblies on said sleeve arranged for direct contact with the post, a pair of levels on said sleeve for vertical alignment of said stabilization support, multiple leg assemblies pivotally secured to said post engagement sleeve, each of said leg assemblies being longitudinally adjustable, and means for removing a portion of said post engagement sleeve for mounting and removal of said sleeve on said post.

10. The post stabilization support set forth in claim 9 wherein said post engagement sleeve is of a square cross section.

11. The post stabilization support set forth in claim 9 wherein said post registration assemblies comprises, a pivoted cam arm extending through an opening in said sleeve, said arm movable from a first non-engagement position to a second post engagement position.

12. The post stabilization support set forth in claim 9 wherein each of said leg assemblies comprises, a pair of

6

fixed tubular legs having a movable leg registerably therebetween, a clamp secured to said movable leg and registerable on said adjacent legs.

13. The post stabilization support set forth in claim 9 wherein said post engagement sleeve is preferably made of synthetic resin material.

14. The post stabilization support set forth in claim 9 wherein said means for removing one of said post engagement sleeves comprises, a movable sleeve panel.

15. The post stabilization support set forth in claim 9 wherein said post engagement sleeve is comprised of multiple interconnected panels.

16. The post stabilization support set forth in claim 9 wherein said means for removing one of said post engagement sleeves further comprises, a hinged sleeve panel and latch retaining assembly thereon.

\* \* \* \* \*