



US006684894B2

(12) **United States Patent**  
**Zheng**

(10) **Patent No.:** **US 6,684,894 B2**  
(45) **Date of Patent:** **\*Feb. 3, 2004**

(54) **COLLAPSIBLE STRUCTURES HAVING OVERLAPPING SUPPORT LOOPS**

(75) Inventor: **Yu Zheng**, Covina, CA (US)

(73) Assignee: **Patent Category Corp.**, Walnut, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/962,041**

(22) Filed: **Sep. 24, 2001**

(65) **Prior Publication Data**

US 2002/0078989 A1 Jun. 27, 2002

**Related U.S. Application Data**

(60) Division of application No. 09/696,909, filed on Oct. 26, 2000, now Pat. No. 6,499,498, which is a continuation-in-part of application No. 09/183,528, filed on Oct. 30, 1998, now Pat. No. 6,138,701, which is a continuation-in-part of application No. 09/056,729, filed on Apr. 7, 1998, now Pat. No. 6,032,685, which is a continuation-in-part of application No. 09/004,829, filed on Jan. 9, 1998, now Pat. No. 5,975,101, which is a continuation-in-part of application No. 08/717,408, filed on Sep. 20, 1996, now Pat. No. 5,941,265.

(51) **Int. Cl.<sup>7</sup>** ..... **E04H 15/40**

(52) **U.S. Cl.** ..... **135/126; 135/117; 135/143; 135/128; 160/377; 446/478; 446/487; 473/197**

(58) **Field of Search** ..... 135/125, 126, 135/128, 143, 147, 117, 136; 160/370.21, 135, 377; 296/97.7, 97.8; 220/9.3; 446/478, 487; 473/197; 273/400

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,675,667 A 7/1972 Miller  
3,960,161 A 6/1976 Norman  
3,990,463 A 11/1976 Norman

4,815,784 A 3/1989 Zheng  
4,825,892 A 5/1989 Norman  
4,858,634 A 8/1989 McLeese  
5,038,812 A 8/1991 Norman  
5,137,044 A 8/1992 Brady  
5,163,461 A 11/1992 Ivanovich et al.  
5,249,592 A 10/1993 Springer et al.  
5,301,705 A 4/1994 Zheng  
5,337,772 A 8/1994 Habchi  
5,385,165 A 1/1995 Hazinski et al.  
5,439,017 A 8/1995 Brown  
5,439,018 A 8/1995 Tsai  
5,452,934 A 9/1995 Zheng  
5,560,385 A 10/1996 Zheng  
5,592,961 A 1/1997 Chin  
5,601,105 A 2/1997 Blen et al.  
5,645,096 A 7/1997 Hazinski et al.  
5,676,168 A 10/1997 Price  
5,800,067 A 9/1998 Easter  
5,816,278 A 10/1998 Kim

**FOREIGN PATENT DOCUMENTS**

DE 3013178 11/1981  
FR 2635136 2/1990  
FR 2699459 6/1994  
WO WO9416178 7/1994

**OTHER PUBLICATIONS**


Frontgate Summer 1995 Catalog VELCRO Product Instruction Sheet (3/97).

*Primary Examiner*—Winnie S. Vir  
(74) *Attorney, Agent, or Firm*—Raymond Sun

(57) **ABSTRACT**

Collapsible structures are provided having at least two panels, with each of the panels having a flexible loop member defining a closed loop and adapted to assume an expanded position and a collapsed position, and a fabric for partially covering the loop member. The loop members of two adjacent first and second panels overlap each other at a first overlapping point along first edges of the loop members, and at a second overlapping point along second edges of the loop members, with the overlapping loop members defining a hinge portion about which the two loop members of the first and second panels are pivotable.

**12 Claims, 39 Drawing Sheets**






FIG. 2






FIG. 1A

FIG. 1B








FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C



FIG. 5D




FIG. 5E




FIG. 5F






FIG. 7




FIG. 6




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10




FIG. 11




FIG. 11A






FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13






FIG. 14




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23A





FIG. 23B






FIG. 24



## COLLAPSIBLE STRUCTURES HAVING OVERLAPPING SUPPORT LOOPS

### RELATED CASES

This is a division of Ser. No. 09/696,909, entitled “Collapsible Structures Having Overlapping Support Loops”, filed Oct. 26, 2000, now U.S. Pat. No. 6,499,498, which is a continuation-in-part of Ser. No. 09/183,528, entitled “Collapsible Structures Having Overlapping Support Loops”, filed Oct. 30, 1998, now U.S. Pat. No. 6,138,701, which is a continuation-in-part of Ser. No. 09/056,729, entitled “Collapsible Structures Having Overlapping Support Loops”, filed Apr. 7, 1998, now U.S. Pat. No. 6,032,685, which is a continuation-in-part of Ser. No. 09/004,829, entitled “Collapsible Structures Having Overlapping Support Loops”, filed Jan. 9, 1998, now U.S. Pat. No. 5,975,101, which is in turn a continuation-in-part of Ser. No. 08/717,408, entitled “Collapsible Sunshields, Partitions and Shade Structures Having Overlapping Support Loops”, filed Sep. 20, 1996, now U.S. Pat. No. 5,941,265, whose disclosures are incorporated by this reference as though fully set forth herein.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to sunshields, partitions and structures, and in particular, to collapsible sunshields, partitions, shade structures and other structures supported by resilient loop members maintained in overlapping relationship with each other. These sunshields, partitions, and structures may be twisted and folded to reduce the overall size of the sunshield, partition or structure.

#### 2. Background Art

A number of prior art sunshields are well-known for use, for example, in shielding the interior of an automobile from unwanted heat and sunlight. These sunshields may be positioned against an interior window surface, but are typically positioned against the windshield because of the difficulty of retaining these sunshields against the other window surfaces. Examples of these sunshields are illustrated in U.S. Pat. Nos. 4,815,784 to Zheng, 5,024,262 to Huang, and 5,452,934 to Zheng. In each of these sunshields, one or more resilient loop members are used to support the sunshield in an expanded configuration. These sunshields may be twisted and folded to reduce the overall size of the sunshield.

A number of prior art shade or tent structures have also been provided for a wide variety of uses, such as for camping, for shade, or for play by children. Examples of these shade structures are illustrated in U.S. Pat. Nos. 3,990,463 to Norman, 4,825,892 to Norman, 5,038,812 to Norman, and 5,467,794 and 5,560,385 both to the present inventor. Each of these shade structures also use one or more resilient loop members to support the structure in an expanded configuration. These shade structures may be twisted and folded to reduce the overall size of the shade structure.

In addition to sunshields and shade structures, there are also other structures that are provided for amusement purposes. Examples of such structures are illustrated in the present inventor’s U.S. Pat. No. 5,722,446. Each of these structures also use one or more resilient loop members to support the structure in an expanded configuration. These structures may also be twisted and folded to reduce the overall size of the structure.

### SUMMARY OF THE INVENTION

The present invention provides basic principles which are effective in constructing a wide variety of collapsible

structures, such as but not limited to sunshields, partitions, shade structures, amusement structures, container structures and other structures that can be twisted and folded to reduce the overall size of the structure for convenient transportation and storage. These collapsible structures have simple constructions, are easy to use, and provide the user with much variety in use and play. In addition, these collapsible structures allow for the stability and support of the structure and portions thereof to be varied and adjusted to accommodate different shapes and sizes for the structure, and to accommodate use in different applications. It is also possible to combine a plurality of the structures to provide structures having different sizes and configurations, thereby increasing the variety of use and play.

The collapsible structures according to the present invention have at least two panels, each of the panels having a flexible loop member defining a closed loop and adapted to assume an expanded position and a collapsed position, and a fabric for partially covering the loop member. The loop members of two adjacent first and second panels overlap each other at a first overlapping point along first edges of the loop members, and at a second overlapping point along second edges of the loop members, with the overlapping loop members defining a hinge portion about which the two loop members of the first and second panels are pivotable.

The panels are foldable on top of each other about their respective hinge portions to have the loop members overlapping each other, and the overlaying loop members are then collapsible to the collapsed positions by twisting and folding to form a plurality of concentric rings to substantially reduce the size of the structure in the collapsed position.

In some embodiments of the present invention, the bottom edges of the panels are adapted to contact a support surface.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a perspective view of a sunshield according to an embodiment of the present invention illustrated in an expanded configuration;

FIG. 1B is a top plan view of the sunshield of FIG. 1A;

FIG. 2 is a perspective cut-away sectional view of the sunshield of FIG. 1A taken along section 2—2 thereof;

FIG. 2A is perspective exploded view illustrating one embodiment of how the fabric pieces are deployed in the resilient loop members of FIG. 1A;

FIG. 2B a perspective cut-away sectional view of the loop member and fabric of FIG. 2A taken along section B—B thereof;

FIG. 2C is perspective exploded view illustrating another embodiment of how the fabric pieces are deployed in the resilient loop members of FIG. 1A;

FIG. 3 is a perspective view of the resilient loop members that can be used to support the sunshield of FIG. 1A;

FIG. 4 is a side elevational view of the sunshield of FIG. 1A positioned behind an automobile windshield;

FIGS. 5A through 5E illustrate how the sunshield of FIG. 1A may be twisted and folded for compact storage;

FIG. 5F illustrates the resilient loop members of FIG. 3 in a folded position illustrating how the loop members are folded to provide for two sets of three loop portions to thereby substantially reduce the size thereof;

FIG. 6 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 7 is a perspective view of a structure according to yet another embodiment of the present invention illustrated in an expanded configuration;

FIG. 8 is a perspective view of a structure according to a further embodiment of the present invention illustrated in an expanded configuration;

FIGS. 9A–9C illustrate how the different panels of the structure of FIG. 8 may be folded upon each other prior to twisting and folding for compact storage;

FIG. 10 is a perspective view of a structure according to yet a further embodiment of the present invention illustrated in an expanded configuration;

FIG. 11 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 8;

FIG. 11A is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 11;

FIG. 11B illustrates the section of the structure of FIG. 11A at the overlapping points and the stitch line;

FIG. 11C illustrates an alternative embodiment of the section of the structure of FIG. 11A at the overlapping points and the stitch line;

FIG. 11D illustrates a canopy deployed with the structure of FIG. 11A;

FIG. 12A is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIGS. 12B–12D illustrate how the different panels of the structure of FIG. 12A may be folded upon each other prior to twisting and folding for compact storage;

FIG. 13 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 12A;

FIG. 14 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 14A is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 14;

FIG. 14B is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 14A;

FIG. 14C is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration, which represents a modification to the structure of FIG. 14B;

FIG. 15 is a perspective view of a structure according to a further embodiment of the present invention illustrated in an expanded configuration;

FIGS. 16A and 16B are cross-sectional views of two preferred connections between two adjacent panels of the structure of FIG. 12A taken along line 16—16 thereof;

FIG. 17 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 18 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 19 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 20 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 21 is a top plan view of the structure of FIG. 20;

FIG. 22 is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIG. 23A is a perspective view of a structure according to another embodiment of the present invention illustrated in an expanded configuration;

FIGS. 23B–23C illustrate how the different panels of the structure of FIG. 23A can be may be folded upon each other prior to twisting and folding for compact storage; and

FIG. 24 is a perspective view of a structure according to yet another embodiment of the present invention illustrated in an expanded configuration.

#### BEST MODES FOR CARRYING OUT THE INVENTION

The following detailed description is of the best presently contemplated modes of carrying out the invention. This description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating general principles of embodiments of the invention. The scope of the invention is best defined by the appended claims.

The principles of the present invention are applicable to sunshields, partition structures and other structures, including shade structures, container structures, and amusement structures, and shall be described herein in connection with such structures. However, it will be appreciated by those skilled in the art that the principles of the present invention are not so limited and can be applied to other structures for many different uses.

FIGS. 1–3 illustrate a structure 20 according to one embodiment of the present invention, which may be used as a sunshield. The sunshield 20 is formed by two resilient loop members 22 and 24 that together define the outer boundary of the sunshield 20. Referring to FIG. 3, each loop member 22 and 24 is provided as a closed resilient loop, either as a closed continuous loop or as a strip of material with both ends held together by a retaining connector or other conventional attachment mechanism to form a closed loop. The resilient loop members 22 and 24 are preferably made from a relatively strong springy material which is flexible enough to allow it to be coiled. The preferred material for the loop members 22 and 24 includes flat spring steel stock, and in particular, stainless steel, although plastic may also be used. Each closed loop member 22 and 24 is preferably substantially equal in size and symmetrically disposed, but it will be appreciated by those skilled in the art that the resilient loop members 22 and 24 may assume any variety of shapes and sizes, including but not limited to circular or oval. Both resilient loop members 22 and 24 can even be provided in different sizes.

As illustrated in FIGS. 1–3, the two loop members 22 and 24 are fitted within each other, and overlap or cross-over each other at overlapping points 26 and 28. The overlapping point 26 is defined by the intersection or crossing of the upper edges 30 and 34 of loop members 22 and 24, respectively, and the overlapping point 28 is defined by the intersection or crossing of the lower edges 32 and 36 of loop members 22 and 24, respectively. The overlapping points 26 and 28 can be positioned anywhere along the upper edge 30 or lower edge 32 of the loop member 22, and anywhere along the upper edge 34 or lower edge 36 of the loop

member 24. FIG. 1A illustrates the overlapping points 26 and 28 provided near the adjacent side edges of the two loop members 22 and 24. The two overlapping loop members 22 and 24 are pivotable about their overlapping points 26 and 28 between two positions, a first completely open position (see FIG. 1E) in which both loop members 22 and 24 lie flat in the same plane and extend to the widest longitudinal length of the sunshield 22, and a second folded position in which the loop members 22 and 24 are folded towards each other (such as in the direction of arrows 70a and 70b in FIG. 1) to overlies each other. The sunshield 20 is normally deployed at the windshield of an automobile when in the first completely open position, and the sunshield 20 is deployed to the second folded position as a first step towards folding and collapsing the sunshield 20 into a smaller size, as described in greater detail hereinbelow.

Each loop member 22 and 24 is retained in a loop retaining portion of one or more fabric pieces. For example, as shown in FIG. 1A, two fabric pieces 40 and 42 are provided, one for each loop member 22 and 24, respectively. Each fabric piece 40 and 42 completely covers, and forms a panel 52 or 54 within, the respective loop member 22 or 24, and is preferably held in tension with the loop member 22 or 24. One side of each fabric 40, 42 may be used as the window-facing side of the sunshield.

The fabric pieces 40 and 42 are preferably made from a sheet material which is effective in reflecting and blocking light and heat from entering the interior of the automobile, and may be made from sheet fabric, woven fabric, PVC, metal foil, and even films. A layer of metallized fabric or other reflective material may be added to the window-facing sides of the fabric 40, 42 to further aid in reflecting and blocking light and heat. A less expensive, though less effective, alternative is to choose a white fabric as the reflective surface. In addition, the window-facing sides may be provided with a different color so that the user can easily recognize it.

The loop retaining portions are preferably provided in the form of a sleeve for retaining the loop members 22 and 24. The loop members 22 and 24 may be retained at the loop retaining portions by a number of different methods. In a first preferred method, which is illustrated in FIGS. 1-3, a sleeve 44 may be formed by folding a peripheral edge of the fabric 40 or 42 over the loop member 22 or 24 and then applying a stitching (such as designated by numeral 46), or by providing a separately-formed tubular sleeve that is stitched along the same stitch line 46 to the fabric 40, 42. Under this first method, the loop members 22 and 24 may be left free and unsecured within the sleeves 44. In a second preferred method, the loop members 22 and 24 may be mechanically fastened, glued or fused to the sleeve 44 or the fabric 40, 42. Other conventional methods may be used without departing from the spirit and scope of the present invention.

The loop members 22 and 24 should not be connected or attached at the overlapping points 26 and 28 so as to allow the loop members 22 and 24 to pivot about these points. The structure of the sleeve 44 at the overlapping points 26 and 28 can be provided in one of several ways. In a first alternative illustrated in an exaggerated sense in FIG. 3, a small portion of the sleeves 44 for both loop members 22 and 24 may be interrupted or disconnected adjacent the overlapping points 26 and 28 so as to expose the loop members 22 and 24 at these overlapping points 26 and 28. As a second alternative, the sleeves 44 for both panels 52 and 54 can be connected to each other to form a "+" or cross-shaped sleeve portion at the overlapping points 26 and 28 (see FIG. 2). As a third

example, the respective sleeves 44 for both panels 52 and 54 can run uninterrupted throughout the closed loop of the loop members 22 and 24. Thus, the loop members 22 and 24 pivot about the overlapping points 26 and 28 in the two directions illustrated by arrow 48 in FIG. 2, with the overlapping points 26 and 28 together acting as a hinge mechanism when the loop members 22 and 24 are pivoted about these points 26 and 28 at the same time. To better define the overall hinge mechanism created by the overlapping portions 26 and 28, this hinge mechanism may optionally include a stitch line 50 along which the two fabric pieces 40 and 42 are stitched together. The stitch line 50 extends from one overlapping point 26 to the other overlapping point 28, and assists in maintaining the loop members 22 and 24 at about the same overlapping points 26 and 28 even though the loop members 22 and 24 are not connected or attached to each other. Thus, the two side panels 52 and 54 defined by the loop members 22 and 24, respectively, may also be hinged and pivoted about the stitch or pivot line 50.

Referring now to FIG. 2A, the first fabric piece 40 can be provided in the form of a single piece of fabric that spans the space between the loop member 22. The second fabric piece 42 can be provided in the form of two separate portions of fabric, 42a and 42b. Each separate portion 42a, 42b has an inner edge 43a, 43b, respectively, that does not have, or is not attached to, a sleeve 44, but is instead stitched or otherwise attached to the first fabric 40 to form the stitch line 50. This is illustrated in greater detail in FIG. 2B, where a small strip 45 of the inner edge 43b is folded and stitched to the first fabric 40. It should be noted that although FIGS. 2A and 2B appear to show that the loop member 24 has been separated, this is not true since the loop member 24 is illustrated in this manner because of the exploded nature of these illustrations. Only the fabric portions 42a and 42b are separated, and as shown in greater detail in FIG. 2B, the loop member 24 extends over the overlapping points 26 and 28.

FIG. 2C illustrates another technique of attaching the fabric pieces 40, 42 to the loop members 22, 24. In this embodiment, only two fabric pieces 40x, 42x are provided, and each is adapted to span across and cover portions of both loop members 22, 24 (the loop members 22, 24 are not shown in FIG. 2C). Specifically, the first fabric piece 40x has a first portion 41a that covers or spans the majority of the first loop member 22 and is folded along a fold line 49a to form a second portion 47a that covers or spans a small portion of the second loop member 24. Similarly, the second fabric piece 42x has a first portion 41b that covers or spans the majority of the second loop member 24 and is folded along a fold line 49b to form a second portion 47b that covers or spans a small portion of the first loop member 22. The fold lines 49a, 49b can be stitched together to form the stitch line 50.

It will also be appreciated that the loop retaining portion or sleeve 44 can be provided either at the periphery of the fabric 40 and 42, as shown in FIGS. 1-3, or at a portion of the fabric 40 and 42 interior from the periphery. The only requirement is that the loop members 22 and 24 be positioned so that they can sufficiently support the sunshield 20 to effectively cover the automobile window or sunshield.

It will be appreciated that suction cups 56 can be optionally positioned anywhere on the window-facing sides of the fabric 40 and 42. Further, it will be appreciated by those skilled in the art that other conventional attachment devices, such as snaps or VELCRO™, may be used in place of the suction cups 56 without departing from the spirit and scope of the present invention.

FIG. 4 illustrates the sunshield 20 in position against a windshield 58. Although the operation of the sunshield 20 is

shown in connection with a windshield, it is understood that the sunshield **20** can also be used effectively in the same manner with side and rear windows. The windshield **58** is held in position by a frame **60** and the sunshield **20** is positioned between a dashboard **62** and a ceiling **64** of the automobile. Visors **66** and the rear view mirror **68** may be used to provide support for the sunshield **20** against the windshield **58**, although it is understood that the visors **66** are not necessary if the suction cups **56** are used. In most cases, suction cups **56** alone are sufficient for retaining the sunshield **20** against the windshield **58** or any side window or rear window where there are no overhanging visors. However, when used to cover a windshield **58**, the visors **66** may also be flipped down to assist in retaining the sunshield **20** against the windshield **58**. When the sunshield **20** is to be stored, the sunshield **20** can be easily removed from the windshield **58** by pulling the suction cups **56** from the windshield **58**. These suction cups **56** can also be removably attached to the fabric pieces **40** and **42** so that worn-out or defective suction cups **56** can be replaced after a period of use.

The shape of the loop members **22** and **24**, and of the resulting sunshield **20**, is not important as long as they are sized and shaped so that they sufficiently support the sunshield **20** to effectively cover the entire windshield **58**. Any shape may be used, and a few examples are illustrated in my previous U.S. Pat. No. 4,815,784 to Zheng, the entire disclosure of which is incorporated by this reference as though fully set forth herein. For example, the loop members **22** and **24** may be circular, oval, truncated circular, truncated oval, substantially rectangular, or any other variety of shapes.

FIGS. **5(A)** through **5(E)** describe the various steps for folding and collapsing the structure **20** of FIG. **1** for storage. The first step consists of folding the two loop members **22** and **24** toward each other (as shown by arrows **70a** and **70b** in FIG. **1**) about the hinge mechanism of the overlapping points **26** and **28**, and the optional stitch line **50**. When the two loop members **22** and **24** are folded together, the second step, shown in FIG. **5A**, is to twist and fold the combined structure to initially collapse the loop members and fabric into a smaller diameter. As shown in FIG. **5B**, the third step is to fold in the opposite side of the combined structure upon the previous fold to further collapse the combined loop members. As shown in FIG. **5C**, the fourth step is to continue the collapsing so that the size of the structure is a fraction of the diameter of the initial structure. FIG. **5D** shows the fifth step with the loop members **22**, **24** and fabric panels **52**, **54** collapsed on each other to provide for a small essentially compact configuration having a plurality of concentric closed loop rings and layers of fabric so that the collapsed structure has a size which is a fraction of the original size of the structure.

In addition, referring to FIGS. **1** and **5E**, a retaining member **72** may be attached to one end of the sunshield **20**, and may be used to tie or hold the collapsed sunshield **20** in the collapsed position. Alternatively, a bag (not shown) may be used to store the collapsed sunshield **20**.

FIG. **5F** illustrates loop members **22** and **24** in the collapsed position. The structure of each loop member **22** and **24** essentially consists of two sets of three loop rings intertwined to lie flat. In the collapsed position, the structure would have a diameter of less than twelve inches, which makes it easy to store the sunshield inside an automobile.

Although the structure **20** is illustrated as being a sunshield **20**, the same structure can be provided in larger sizes

and used as a partition or for other uses. For example, the structure **20**, as shown in FIG. **1** with the lower edges **32** and **36** of the loop members **22** and **24**, respectively, resting on a flat surface, such as the ground, can be used as a partition. The panels **52** and **54** would act as the walls of the partition, with the interconnecting hinge mechanism acting as a pivotable corner of the partition. This interconnecting hinge mechanism would be disposed substantially vertically, or perpendicular to the ground. When used as a partition, the size and configuration of the loop members **22** and **24**, and therefore the panels **52** and **54**, respectively, are not limited to the size and shape of a windshield and can therefore be varied. In addition, the overlapping points **26** and **28** can be positioned along different parts of the upper and lower edges **30**, **32**, **34** and **36** of the loop members **22** and **24**. These variations and modifications can be made to suit the user's needs. As a non-limiting example, a substantially "+" or cross-shaped partition can be defined by positioning the overlapping points **26** and **28** at substantially the centers of the upper and lower edges **30**, **32**, **34** and **36** of the loop members **22** and **24**, or at points between the center and the side edges of the upper and lower edges **30**, **32**, **34** and **36**, as shown in FIG. **3**. This will provide a partition which defines four separate non-enclosed spaces. In addition, the angle A (see FIG. **2**) between the panels **52** and **54** can be varied between 1 degree and 180 degrees to vary the configuration of the partition and the size of the space defined between the panels **52** and **54**. Other alternatives can be provided and modifications made without departing from the spirit and scope of the present invention.

Partitions and sunshields having more than two loop members and panels can also be provided according to the present invention. Referring to another embodiment of the present invention illustrated in FIG. **6**, a partition or sunshield **100** has three separate panels **102**, **104** and **106**, each defined by a loop member (not shown) and having the same construction as panels **52** and **54** and loop members **22** and **24** described above. Panels **102** and **104** are interconnected at the overlapping points **108**, **110** and stitch line **112** by overlapping their respective loop members in the manner described above. Similarly, panels **104** and **106** are interconnected at the overlapping points **114**, **116** and stitch line **118** by overlapping their respective loop members, also in the manner described above.

FIG. **6** shows the structure **100** in use as a partition, with the lower edges **124**, **126** and **128** of the panels **102**, **104** and **106**, respectively, resting on the ground, and the interconnecting hinge mechanisms (i.e., the optional stitch line **112** and the overlapping points **108** and **110**, and the optional stitch line **118** and the overlapping points **114** and **116**) disposed vertically. The angle B between the panels **102** and **104**, and the angle C between the panels **104** and **106**, can be varied by pivoting the interconnecting hinge mechanisms. When the structure **100** is to be used as a sunshield, the panels **106** and **102** are folded in the directions indicated by arrows **120** and **122**, respectively, so that the three panels **102**, **104** and **106** lie flat in the same plane. To fold and collapse the three panels **102**, **104** and **106**, the panels **106** and **102** are folded toward the panel **104** in the directions indicated by arrows **130** and **132**, respectively, so that the three panels **102**, **104** and **106** overlies each other to form one stack of panels. The folding and collapsing steps illustrated in FIGS. **5A**–**5E** can be used to fold and collapse the structure **100** into a size which is a fraction of the original size of the structure.

FIG. **7** is a modification **100a** of the partition or sunshield **100** of FIG. **6**. The structure **100a** is essentially the same as

the structure **100**, except that the panels **102a** and **104a** are interconnected at overlapping points **108a**, **110a** and stitch line **112a** which are at a different position along the edge **124a** of panel **102a**. FIG. 7 shows the structure **100a** in use as a partition, with the lower edges **124a**, **126a** and **128a** of the panels **102a**, **104a** and **106a**, respectively, resting on the ground, and the interconnecting hinge mechanisms disposed vertically. When the structure **100a** is to be used as a sunshield, the panels **106a** and **102a** are folded in the directions indicated by arrows **120a** and **122a**, respectively, so that the three panels **102a**, **104a** and **106a** lie flat in the same plane. To fold and collapse the three panels **102a**, **104a** and **106a**, the panels **106a** and **102a** are folded toward the panel **104a** in the directions indicated by arrows **130a** and **132a**, respectively, so that the three panels **102a**, **104a** and **106a** overlie each other to form one stack of panels. The folding and collapsing steps illustrated in FIGS. 5A–5E can be used to fold and collapse the structure **100a** into a size which is a fraction of the original size of the structure.

It is noted that the structures **20**, **100** and **100a** in FIGS. 1, 6 and 7, respectively, can be used as mats or panels that are laid flat on the ground. For example, the loops **22**, **24** and their respective fabrics **40**, **42** of the structure **20** can be opened until both the loops **22**, **24** are generally parallel to each other, and then placed flat on a surface to operate as a mat, carpet, or similar object. As another example, one loop **22** and its fabric **40** can be placed flat on the ground and the other loop **24** and its fabric **42** supported at an angle to operate as an inclined back rest. These same principles can be applied to the structures **100**, **100a**.

FIG. 8 illustrates another embodiment in which a structure **140** has four separate panels **142**, **144**, **146** and **148**, each defined by a loop member (not shown) and having the same construction as panels **52** and **54** and loop members **22** and **24** described above. Panels **142** and **144** are interconnected at the overlapping points **150**, **152** and stitch line **154** by overlapping their respective loop members in the manner described above. Similarly, panels **144** and **146** are interconnected at the overlapping points **156**, **158** and stitch line **160**, panels **146** and **148** are interconnected at the overlapping point **162** and stitch line **166**, and panels **142** and **148** are interconnected at the overlapping points **168**, **170** and stitch line **172**. FIG. 8 shows the structure **140** in use as a partition, with the lower edges **174**, **176**, **178** and **180** of the panels **142**, **144**, **146** and **148**, respectively, resting on the ground, and the four interconnecting hinge mechanisms disposed vertically. The angles between adjacent panels of the partition **140** can be varied by pivoting the interconnecting hinge mechanisms. Openings **196** can be provided in one or more of the panels **142**, **144**, **146**, **148** to provide ingress and egress.

To fold and collapse the four panels **142**, **144**, **146** and **148**, panels **142** and **144** are pushed against panels **148** and **146**, respectively, in the direction of arrow **182** shown in FIG. 9A so that the four panels **142**, **144**, **146** and **148** take the configuration shown in FIG. 9B, with panels **142** and **148** overlying each other and panels **144** and **146** overlying each other. During this first pushing step, the respective interconnecting hinge mechanisms (which include the optional hinge stitches **154**, **160**, **166** and **172** and their respective overlapping points) are pivoted. One pair of overlaying panels **142**, **148** or **144**, **146** is then folded over the interconnecting hinge mechanisms defined in part by hinge stitches **154** and **166** in the direction of arrow **184** in FIG. 9B, so that the four panels **142**, **144**, **146** and **148** overlie each other to form one stack of panels as shown in FIG. 9C. The folding and collapsing steps illustrated in FIGS. 5A–5E can be used to fold and

collapse the structure **140** into a size which is a fraction of the original size of the structure.

The partition **140** can also be provided with a roof **198** (shown in FIG. 11) so that it can be used as a collapsible shade structure or tent **202**. For example, a fabric panel can be stitched or otherwise connected by known methods to the upper edges **188a**, **190a**, **192a** and **194a** of the panels **142a**, **144a**, **146a** and **148a**, respectively, so that the four panels **142a**, **144a**, **146a** and **148a** and the fabric roof **198** define an enclosed interior space. Openings **196a** can be provided in one or more of the panels **142a**, **144a**, **146a** and **148a** to provide ingress and egress. In addition, another fabric or other material can be stitched or otherwise connected by known methods to the lower edges **174a**, **176a**, **178a** and **180a** of the panels **142a**, **144a**, **146a** and **148a**, respectively, to define a floor **200a** for the shade structure. The shade structure **202** is folded and collapsed in the same manner described above for partition **140**. Even though the structures **140** and **202** are shown as having four panels, it is possible to provide the structures **140** or **202** (used as a partition, shade structure, or other use) with three panels interconnected to each other according to the principles of the present invention.

FIGS. 11A–11D illustrate additional modifications and benefits of the structures according to the present invention. FIG. 11A illustrates a structure **202b** that is similar to the structure **202** of FIG. 11, except that the panels **142a**, **144a**, **146a** and **148a** are shaped differently from panels **142b**, **144b**, **146b** and **148b** in FIG. 11A. The elements of the structure **202** that are the same as the elements of the structure **202b** are provided with the same numeral designations except that a “b” has been added to the numeral designations in FIGS. 11A–11D. Each of the panels **142b**, **144b**, **146b** and **148b** has a curved outer configuration and overlap adjacent panels at opposing ends. The curved nature of the sides of these panels **142b**, **144b**, **146b** and **148b** allows the overlapping points (such as **150b** and **152b** shown in FIGS. 11B and 11C) to be configured slightly differently from the overlapping configurations illustrated hereinabove.

FIG. 11B illustrates the section of structure **202b** at the overlapping points **150b**, **152b** and the stitch line **154b**. Loop member **143** is the loop member that supports panel **142b**, and loop member **145** is the loop member that supports panel **144b**. The curved nature of the sides of these panels **142b**, **144b**, **146b** and **148b** also allows the overlapping loop members (such as **143** and **145**) to cross or overlap each other more naturally at the overlapping points (such as **150b** and **152b**). Fabric portions **147** and **149** for panels **142b** and **144b**, respectively, are still defined between the sides of the panels **142b**, **144b** and the stitch line **154b**.

The configuration illustrated in FIG. 11B can be modified to the configuration shown in FIG. 11C. In FIG. 11C, the fabric portions **147**, **149** are omitted so that the sleeves **151** and **153** of the panels **142b** and **144b**, respectively, can be stitched together by the stitch line **154b**.

As explained throughout the disclosure, the overlapping or crossing of a pair of loop members provides added stability and structural support to the structure at the overlapping points. The configurations illustrated in FIGS. 11B and 11C allow the degree and nature of the stability and support to be varied and adjusted. In addition, the distance or degree to which the fabric portions **147**, **149** extend from the stitch line **154b** can be varied for many different purposes. For example, if the overlapping points of the structure **202b** is used to provide external support for a canopy or roof **155**, as shown in FIG. 11D, then the fabric portions **147**, **149**

can be made to extend a greater distance from the stitch line **154b** to provide a larger shaded area under the canopy **155** outside of the structure **202b**. The canopy **155** can be a piece of fabric or other material having water-proof and/or heat-repelling properties.

The structure **202b** can be folded and collapsed, as well as re-deployed to the fully expanded configuration, according to the same methods utilized for the structure **140** described above in FIGS. **9A–9C**.

In addition, it is possible to combine a plurality of the structures to provide structures with different sizes and configurations, thereby increasing the variety of use and play. As a non-limiting example, FIG. **10** illustrates a structure **210** that is made up of two separate substantially “+” or cross-shaped structures **212** and **214** connected to each other along adjacent side edges **216** and **220** of panels **226** and **224**, respectively, and adjacent side edges **218** and **222** of panels **230** and **228**, respectively. The connection along the side edges may be made permanent by applying stitching, or may be made detachable by using conventional detachable attachment devices, such as snaps, hooks or VELCRO™. Each structure **212** and **214** has two separate panels **224**, **228** and **226**, **230** respectively, each connected by one interconnecting hinge mechanism which includes the overlapping points **232**, **234**, **238** and **240** and the optional hinge stitches **236** and **242**, according to the principles described hereinabove. The overall structure **210** may be a partition structure having one enclosed space and a plurality of other non-enclosed spaces. Alternatively, fabric roofs may be stitched or otherwise connected to all portions, or certain specific portions, of the structures **212** and **214** to provide either a full or a partial shade structure.

The principles of the present invention can also be used to extend the length of a panel for a larger structure. For example, the individual module shown and illustrated in U.S. Pat. No. 5,560,385 can be elongated by providing one of the side panels with a pair of overlapping panels according to the present invention. Referring to FIG. **12A**, a structure **300** has a first end panel **302** and a second end panel **304** opposite to the first end panel **302**. The structure further includes first and second left panels **306** and **308**, and first and second right panels **310** and **312**.

The first end panel **302** has a left side **314**, a bottom side **316**, a right side **318** and a top side **320**. The second end panel **304** has a left side **322**, a bottom side **324** (not shown), a right side **326** and a top side **328**. The first left panel **306** has a left side **330**, a bottom side **332**, a right side **334** and a top side **336**. The second left panel **308** has a left side **338**, a bottom side **340**, a right side **342** and a top side **344**. The first right panel **310** has a left side **346**, a bottom side **348** (not shown), a right side **350** and a top side **352**. The second right panel **312** has a left side **354**, a bottom side **356** (not shown), a right side **358** and a top side **360**.

Each end panel **302** and **304** has a continuous loop retaining sleeve **380** provided along and traversing the four edges of its four sides. See FIG. **16A**. A continuous loop member **382**, which can be the same as the loop member **22** described above in connection with FIGS. **1–3**, is retained or held within each retaining sleeve **380** to support each end panel **302** and **304**. Fabric or sheet material extends across each end panel **302**, **304** and is held taut by the respective loop member **382** when in its open or expanded position. The loop members **382** may be merely retained within the respective retaining sleeves **380** without being connected thereto. Alternatively, the retaining sleeves **380** may be mechanically fastened, stitched, fused, or glued to the loop members **382** to retain them in position.

Each pair of the left panels **306** and **308**, and the right panels **310** and **312**, is connected in the same overlapping manner as the pair of panels **52** and **54** described above in connection with FIGS. **1–3**. Specifically, the left panels **306** and **308** are overlapped adjacent the left side **330** of the first left panel **306** and the right side **342** of the second left panel **308** along stitch or pivot line **370**, and the right panels **310** and **312** are overlapped adjacent the left side **354** of the second right panel **312** and the right side **350** of the first right panel **310** along stitch or pivot line **372**. In addition, the left side **314** of the first end panel **302** is hingedly connected to the right side **334** of the first left panel **306**, and the right side **318** of the first end panel **302** is hingedly connected to the left side **346** of the first right panel **310**. Similarly, the left side **322** of the second end panel **304** is hingedly connected to the right side **358** of the second right panel **312**, and the right side **326** of the second end panel **304** is hingedly connected to the left side **338** of the second left panel **308**.

FIG. **16A** illustrates one structure and method for hingedly connecting the left side **314** of end panel **302** and the right side **334** of the first left panel **306**. The fabric pieces for each panel **302** and **306** are stitched at their edges by a stitching **384** to the respective sleeves **380a** for panel **302** and **380b** for panel **306**. In FIGS. **16A** and **16B**, loop member **382a** represents the loop member for panel **302** and loop member **382b** represents the loop member for panel **306**. Each sleeve **380a**, **380b** may be formed by folding a piece of fabric. The stitching **384** also acts as a hinge for the panels **302** and **306** to be folded upon each other, as explained below. At the top side **320**, **328** and the bottom side **316**, **324** of each end panel **302**, **304**, respectively, where there is no hinge connection to an adjacent panel, the retaining sleeve **380** may be formed by merely folding over the corresponding fabric piece and applying a stitching. The fabric piece for the corresponding end panel **302**, **304** may then be stitched to the sleeve **380**.

FIG. **16B** illustrates another structure and method for hingedly connecting the left side **314** of end panel **302** and the right side **334** of the first left panel **306**. As in the connection of FIG. **16A**, the fabric pieces are folded over at their edges at bottom sides **316** and **332**, and at top sides **320** and **336**, to define the respective sleeves **380**. However, the retaining sleeves **380** for each panel **302**, **306** converge at, or are connected to, one sleeve portion which interconnects panels **302**, **306** to form a singular retaining sleeve **386** which retains the loop members **382a** and **382b**. Sleeve **386** may be formed by providing a tubular fabric, or by folding a piece of fabric, and applying a stitching **388** to its edges to connect the sleeve **386** to the fabric pieces of the panels **302**, **306**. Stitching **388** acts as a hinge for the panels **302**, **306**. The other hinged connections of adjacent sides may be identical to those illustrated in either FIG. **16A** or FIG. **16B**.

FIGS. **12A–12D** illustrate how the structure **300** can be folded and collapsed into a smaller size. In the first step, the hinged connection between the left side **314** of end panel **302** and the right side **334** of the first left panel **306** is pushed in (see arrow **400** in FIG. **12A**) about the hinged connection so that end panel **302** collapses upon the first right panel **310** and the first left panel **306** is disposed generally parallel to the second end panel **304** (see FIG. **12B**). In the second step, the panels **302** and **310** are then pivoted about the hinges defined by the stitch line **372** and the hinged connection between the left side **314** of end panel **302** and the right side **334** of the first left panel **306** (see arrow **402** in FIG. **12B**) so that the panels **302** and **310** are collapsed onto the first left panel **306** (see FIG. **12C**). At this point, the structure **300** has been reduced to a structure that is about half the size of the

original structure **300**. In the third step, panels **304** and **312** are pushed in about their hinged connection (see arrow **404** in FIG. 12D) such that end panel **304** collapses upon second left panel **308** and second right panel **312** collapses upon first left panel **306**. Then, in the fourth step, the two combined panels **304** and **308** are pivoted about the hinges defined by the stitch line **370** and the hinged connection between the left side **322** of end panel **304** and the right side **358** of the second right panel **312** so as to be collapsed upon the stack of the other panels **312**, **306**, **302** and **310** (in that order). This creates a single stack of the six panels **308**, **304**, **312**, **306**, **302** and **310** (in that order). The folding and collapsing steps illustrated in FIGS. 5A–5E can then be used to fold and collapse this stack of panels into a size which is a fraction of the original size of the structure **300**.

To deploy the structure **300** back to the expanded, fully deployed position, the panels **302**, **304**, **306**, **308**, **310**, **312** and their associated loop members **382** are unfolded. The resiliency and spring force of the loop members **382** will cause the loop members **382**, and their associated panels **302**, **304**, **306**, **308**, **310**, **312**, to spring open to the expanded configuration. The different panels **302**, **304**, **306**, **308**, **310**, **312** can then be pivoted about their hinges to deploy the structure **300** in its original expanded configuration. The other structures described herein can also be deployed to their respective expanded, fully deployed positions by the resiliency and spring force of their respective loop members, which cause the loop members and their associated panels to spring open to the expanded configuration when the collapsed panels are unfolded.

As a result, the panels **302**, **304**, **306**, **308**, **310** and **312** are connected to each other to define an enclosed space surrounded by four walls. Two of the shorter walls are defined by the end panels **302** and **304**, while each of the other two, longer, walls is defined by a pair of overlapped panels **306** and **308**, or **310** and **312**. Thus, the overlapped panels **306**, **308** and **310**, **312** operate to extend the length of the left and right sides of structure **300**. This is advantageous over providing elongated left and right panels, since elongated panels can be difficult to grip, and to fold and collapse. By providing overlapping panels, the panels can be folded on to each other to initially reduce the overall size of the elongated sides, and the overlapped stack of panels can then be further folded and collapsed to reduce the size of the structure **300**. In addition, the overlapping portions of the overlapped panels provide structural stability to the extended sides formed by these overlapped panels. In this regard, it is also possible to provide an elongated side that is comprised of three or more panels, such as illustrated in connection with FIGS. 6 and 7. Further, the lengths, sizes and shapes of the overlapped panels can be varied. For example, the left panels **306**, **308** can have different sizes, with one being longer or larger than the other.

FIG. 13 illustrates the structure **300** modified for use as a container (e.g., a box). A floor **410** is provided in the form of a fabric that is stitched or otherwise connected to the bottom sides **316**, **324**, **332**, **340**, **348** and **356** of the panels **302**, **304**, **306**, **308**, **310** and **312**, respectively. In addition, a first lid **412** and a second lid **414** are provided. Each lid **412** and **414** can take the form of a panel having a structure that is the same as the end panels **302** and **304**. One side **416** and **418** of the lids **412**, **414** is hingedly attached (using one of the structures and methods illustrated in FIGS. 16A and 16B) to the top sides **352** and **360** of the right panels **310** and **312**, respectively. Each lid **412**, **414** is preferably sized and configured to cover the top of the space between opposing right and left panels. In addition, latching, attachment or

locking mechanisms can be provided to secure the lids **412**, **414** against the top sides **336**, **344** of the left panels **306**, **308**, respectively. Thus, the enclosed space can be used to hold or store any desired object(s). To fold and collapse the structure **300** in FIG. 13, the lids **412** and **414** are additionally folded over their hinged connections with the right panels **310** and **312**, respectively, to create a stack of eight panels that is folded and collapsed according to the method described above in connection with FIGS. 12A–12D and 5A–5E.

The principles of the structure **300** can be further utilized to provide collapsible structures for a wide variety of applications. One such example is illustrated by the shade structure **430** of FIG. 14, which is similar to the structure **300**, and has a first end panel **432**, a second end panel **434** opposite to the first end panel **432**, first and second left panels **436** and **438**, and first and second right panels **440** and **442**. The panels **432**, **434**, **436**, **438**, **440** and **442** may be provided in slightly different shapes and sizes when compared to the corresponding panels **302**, **304**, **306**, **308**, **310**, **312** in structure **300**, but these panels **432**, **434**, **436**, **438**, **440** and **442** are otherwise structured and connected in the same manner as the panels **302**, **304**, **306**, **308**, **310**, **312**, respectively, in structure **300**. In this regard, the first and second left panels **436** and **438** are connected in an overlapping manner, and the first and second right panels **440** and **442** are also connected in an overlapping manner. In addition, the end panels **432** and **434** are hingedly connected to their adjacent left and right panels **436**, **438**, **440** and **442**.

The shade structure **430** additionally includes a raised roof **444** which is made from a fabric material connected to the top sides of the panels **432**, **434**, **436**, **438**, **440** and **442**. Since the left side **446** of the first left panel **436** and the right side **448** of the second left panel **438** are longer than the right side **450** of the first left panel **436** and the left side **452** of the second left panel **438**, the center of the structure **300** is higher so that the roof **444** becomes raised as it extends from the end panels **432**, **434** towards the center of the structure **300**. An opening **454** can be provided in one or both end panels **432**, **434** to provide ingress and egress to the interior of the shade structure **300**. An optional floor **456**, which can be made from a fabric material, can also be connected to the bottom sides of the panels **432**, **434**, **436**, **438**, **440** and **442**.

FIG. 14A illustrates a modification to the structure **430**, in which all of the adjacent sides of all the panels **432a**, **434a**, **436a**, **438a**, **440a** and **442a** are connected in an overlapping manner. The elements of the structure **430a** that are the same as the elements of the structure **430** are provided with the same numeral designations except that an “a” has been added to the numeral designations in FIG. 14A. Thus, the end panels **432a** and **434a** are not hingedly connected to their adjacent left and right panels **436a**, **438a**, **440a** and **442a**, but are instead connected in an overlapping manner.

FIG. 14B illustrates a modification to the structure **430a**, in which the roof **444a** has been removed, and the end panels **432b** and **434b** provided with a different shape having a higher top edge and receiving a netting **433** in the form of a basket on the inner sides of the end panels **432b**, **434b**. The elements of the structure **430b** that are the same as the elements of the structure **430a** are provided with the same numeral designations except that a “b” has been added to the numeral designations in FIG. 14B. Thus, the structure **430b** has been converted into an enclosed basketball court. A large door **435** can be provided in (e.g., cut from) the fabric of one of the side panels (e.g., **438b**) to allow ingress and egress to and from the basketball court.

FIG. 14C illustrates a modification to the structure **430b** that combines the principles of structures **430** and **430b**. The

elements of the structure **430c** that are the same as the elements of the structure **430b** are provided with the same numeral designations except that a “c” has been added to the numeral designations in FIG. 14C. Thus, the structure **430c** is still an enclosed basketball court, as for structure **430b**, but the end panels **432c** and **434c** are now hingedly connected to their adjacent left and right panels **436c**, **438c**, **440c** and **442c**. In addition, nettings **437** in the form of soccer or hockey goals can also be provided at both end panels **432c**, **434c** so that the structure **430c** can also be used as an enclosed soccer or hockey arena. These nettings **437** can be made out of a meshed netting-type material that extend outwardly through openings **439** cut at the bottom of the end panels **432c**, **434c**.

The structures **430**, **430a**, **430b** and **430c** can be folded and collapsed, as well as re-deployed to the fully expanded configuration, according to the same methods utilized for the structure **300** described above.

As an additional example of how the principles of the structure **300** can be further utilized to provide collapsible structures for a wide variety of applications, FIG. 15 illustrates a collapsible arcade-like or amusement structure **500** which is similar to those described in the present inventor’s U.S. Pat. No. 5,722,446. However, the structure **500** provides two elongated side walls which are made up of two overlapping panels. In particular, the structure **500** is similar to the structure **300**, and has a front panel **502**, a rear panel **504**, first and second left panels **506** and **508**, and first and second right panels **510** and **512**. The panels **502**, **504**, **506**, **508**, **510** and **512** may be provided in slightly different shapes and sizes when compared to the corresponding panels **302**, **304**, **306**, **308**, **310**, **312** in structure **300**, but these panels **502**, **504**, **506**, **508**, **510** and **512** are otherwise structured and connected in the same manner as the panels **302**, **304**, **306**, **308**, **310**, **312**, respectively, in structure **300**. In this regard, the first and second left panels **506** and **508** are connected in an overlapping manner, and the first and second right panels **510** and **512** are also connected in an overlapping manner. In addition, the front and rear panels **502** and **504** are hingedly connected to their adjacent left and right panels **506**, **508**, **510** and **512**.

In addition, the left and right panels **506**, **508**, **510** and **512** are configured so that they slope or angle upwardly from the front panel **502** towards the rear panel **504**, so that the right side **516** of the first left panel **506** has a smaller vertical height than the left side **518** of the second left panel **508**. The rear panel **504** is significantly higher than the other panels **502**, **506**, **508**, **510**, **512**, and forms a backboard for a basket **520**. The shade structure **500** additionally includes a top fabric **522** which is connected adjacent to, but offset from and below, the top sides of the panels **502**, **504**, **506**, **508**, **510** and **512**, so that it also slopes upwardly from the front panel **502** towards the rear panel **504**. An optional floor **524**, which can be made from a fabric material, can also be connected to the bottom sides of the panels **502**, **504**, **506**, **508**, **510** and **512**.

The structure **500** can be folded and collapsed, as well as re-deployed to the fully expanded configuration, according to the same methods utilized for the structure **300** described above.

In using the amusement structure **500**, the user may toss a ball (not shown) at the basket **520**. All balls passing through the basket, or bounced off the backboard (i.e., the rear panel **504**), will be returned to the user at the front panel **502** because the sloping or angled nature of the top fabric **522** will cause the ball to roll towards the front panel **502**.

Since the top fabric **522** is offset from and below the top sides of the panels **502**, **504**, **506**, **508**, **510** and **512**, the ball will be retained on top of the top fabric **522**, but inside the confines of the panels **502**, **504**, **506**, **508**, **510** and **512**. Additional modifications and amusement features that can be used for the amusement structure **500** are illustrated and described in the present inventor’s U.S. Pat. No. 5,722,446, whose entire disclosure is hereby incorporated by this reference as though fully set forth herein.

The principles of the present invention can further be applied to a variety of amusement structures. FIG. 17 illustrates a structure **600** that has a first panel **610** and a second panel **612**, each defined by a separate loop member **602**, **604**, respectively, and having the same construction as panels **52** and **54** and loop members **22** and **24** described above. Panels **610** and **612** are interconnected at overlapping points **606**, **608** and stitch line **614** by overlapping their respective loop members **602**, **604** in the manner described above.

The structure **600** further includes a left supporting fabric piece **616** that is connected, such as by stitching, to most of the left side of the first panel **610** and the upper left side of the second panel **612**, and a right supporting fabric piece **618** that is connected, such as by stitching, to most of the right side of the first panel **610** and the upper right side of the second panel **612**. The fabric pieces **616** and **618** define the limits to which the two panels **610**, **612** can be pivoted away from each other (i.e., pivoted away in the directions of arrows **620**, **622**). An opening **624** is provided in the second panel **612** adjacent the stitch line **614**. A pocket **626** is stitched or otherwise provided at the lower end of first panel **610**. The pocket **626** can be made of a mesh or fabric material, and is adapted to receive a ball **628** that has passed through the opening **624**. Specifically, a ball **628** that is tossed at the first panel **610** (e.g., at the “bulls-eye” **630**) will hit the first panel **610** and roll down the first panel **610** since the first panel **610** is angled. If the ball **628** rolls through the opening **624**, it will continue to roll down the first panel **610** and be collected in the pocket **626**. Otherwise, the ball **628** will be collected between the panels **610**, **612** at the stitch line **614**.

FIG. 18 illustrates another amusement structure **700** that utilizes the principles of the present invention. The structure **700** has a first panel **710** and a second panel **712**, each defined by a separate loop member **702**, **704**, respectively, and having the same construction as panels **52** and **54** and loop members **22** and **24** described above. Panels **710** and **712** are interconnected at overlapping points **706**, **708** and stitch line **714** by overlapping their respective loop members **702**, **704** in the manner described above.

The structure **700** further includes a first end fabric piece **716** that is connected, such as by stitching, to most of the left sides of the first panel **710** and the second panel **712**, and a second end fabric piece **718** that is connected, such as by stitching, to most of the right sides of the first panel **710** and the second panel **712**. Each end fabric piece **716**, **718** extends or spans across the space defined by the extremities of the left and right sides of the panels **710**, **712** when the structure **700** is in the fully deployed position with the panels **710**, **712** fully expanded and pivoted about the overlapping points **706**, **708**. Each end fabric piece **716**, **718** can be provided in a one piece, or in four separate pieces. For example, the end fabric piece **716** can be made up of four separate pieces **716a**, **716b**, **716c** and **716d**. The piece **716a** extends between the two panels **710**, **712** below the overlapping point **706**. The piece **716c** extends between the two panels **710**, **712** above the overlapping point **706**. Pieces



716b and 716d extend along opposite exteriors of the left sides of the panels 710, 712. The fabric pieces 716 and 718 define the limits to which the two panels 710, 712 can be pivoted away from each other (i.e., pivoted away in the directions of arrows 720, 722).

In the structure 700, the overlapping points 706 and 708 are not situated at the center of the left and right sides of the loop members 702, 704. Instead, these overlapping points 706 and 708 are situated between the center and the top of the left and right sides of the loop members 702, 704 so as to provide the structure 700 with a wider base and a narrower top.

As a result, the panels 710, 712 and the fabric pieces 716 and 718 define both an interior space below the stitch line 714, and a top receiving well 726 above the stitch line 714. An opening 724 can be provided in one or both end fabric pieces 716, 718 to allow ingress and egress to the interior of the structure 700. An optional floor 730, which can be made of fabric, can be stitched or otherwise connected to the bottom sides of the panels 710, 712. In addition, the receiving well 726 can be adapted to receive light objects 728 that can be tossed at the receiving well 726. Thus, the structure 700 actually provides several play opportunities: the structure 700 can be used as a shade structure, or as an amusement structure 700 with the user tossing light objects 728 into the receiving well 726.

FIG. 19 illustrates an amusement structure 700a that utilizes the basic principles embodied by the structure 700 in FIG. 18, but which includes certain modifications. The elements of the structure 700a that are the same as the elements of the structure 700 are provided with the same numeral designations except that an "a" has been added to the numeral designations in FIG. 19. The structure 700a includes a first panel 710a and a second panel 712a, each defined by a separate loop member 702a, 704a, respectively, that are configured and overlapped in the same manner as the panels 710, 712 and loop members 702, 704 of structure 700. The difference between the structures 700 and 700a is that the end fabric pieces 716 and 718 in structure 700 are not provided in structure 700a. Instead, a first upper fabric piece 717a is provided and extends between the two panels 710a, 712a above the overlapping point 706a, and a second upper fabric piece 717b is provided and extends between the two panels 710a, 712a above the overlapping point 708a. Each upper fabric piece 717a, 717b is similar to the fabric piece 716c in structure 700, and functions to define the limits to which the panels 702a, 704a can be pivoted away from each other. In other words, the upper fabric pieces 717a, 717b prevent the panels 702a, 704a from spreading outwardly so that the structure 700a can be supported in an upright configuration on a floor or other surface. Optional lower fabric pieces 719a and 719b (not shown) can also be provided to extend for a short distance between the two panels 710a, 712a below the overlapping points 706a and 708a, respectively, to accomplish the same function. As an alternative, the upper fabric pieces 717a and 717b can be omitted in lieu of the lower fabric pieces 719a and 719b. As yet another alternative, instead of the upper and lower fabric pieces 717a, 717b, 719a, 719b, strings or straps (not shown) can be provided to connect the panels 710a, 712a, either slightly above and/or below the overlapping points 706a, 708a, or between the bottom edges 721 and 723 of the panels 710a and 712a, respectively, to accomplish the same function.

When the structure 700a is supported in its upstanding fully deployed configuration with both panels 710a, 712a in their fully expanded configuration, the bottom edges 721

and 723 of the panels 710a and 712a, respectively, contact the ground or surface. One or a plurality of openings 725 are provided in one or both panels 710a, 712a so that a user can toss a ball or other object through a selected one of these openings 725. The ball or object that passes through an opening 725 will be deposited in the space between the panels 710a, 710b, from which the user can then retrieve the ball or object. The panels 710a, 712a and the upper fabric pieces 717a and 717b define a top receiving well 726a above the stitch line 714a.

Thus, while structure 700 is primarily a shade structure, the structure 700a provides a different type of amusement by allowing the user to toss objects through the openings 725. The structure 700a can also be used as a shade structure by a user who positions himself or herself in the enclosed space under the overlapping panels 710a, 710b.

The structures 600, 700 and 700a can be folded and collapsed, as well as re-deployed to the fully expanded configuration, according to the same methods utilized for the structure 20 described above. The fabric pieces 616, 618, 716, 718 and the pocket 626 are made from a flexible material that will fold and collapse together with the fabric of the panels 610, 612, 710, 712, 710a, 712a.

It is also possible to provide some of the connections of the adjacent sides of side panels with hinged connections and others with overlapping connections to vary the structural stability and strength of the structure at different parts of the structure. Referring to FIGS. 20 and 21, the structure 750 utilizes principles from the structures illustrated in FIGS. 11A and 14. Structure 750 is similar to structure 202b of FIG. 11A in that structure 750 has four side panels 752, 754, 756 and 758, but of the four connections between adjacent sides of side panels, two are hinged connections and two are overlapping. Specifically, the right side 760 of panel 752 is connected in overlapping manner to the left side 762 of panel 754, the right side 764 of panel 754 is connected in overlapping manner to the left side 766 of panel 756, the right side 768 of panel 756 is hingedly connected to the left side 770 of panel 758, and the right side 772 of panel 758 is hingedly connected to the left side 774 of panel 752. A roof fabric 776 may be attached to the top sides of the panels 752, 754, 756, 758.

Thus, the two overlapping connections between the sides 760 and 762, and sides 764 and 766, provides stronger structural support and stability to the structure 750 on both sides 762, 764 of the panel 754, since the overlapping connections tend to provide stronger support and stability than the hinged connections, as explained hereinabove. The provision of a combination of hinged and overlapping connections allows a larger structure to be provided, since a large structure supported entirely by hinged connections may not be structurally strong and stable for certain applications. On the other hand, hinged connections are less complex and less expensive to make, so it is desirable to provide hinged connections at certain side connections of structures in some applications where it is not necessary for all the connections to be overlapped. The result is that the present invention provides principles which can be utilized to provide structures that can be sized and configured to meet a wide variety of applications and needs. In this regard, although FIGS. 20 and 21 illustrate a particular arrangement for the hinged connections and overlapping connections, these hinged connections and overlapping connections can be provided and arranged between the adjacent sides of any of the panels 752, 754, 756, 758.

FIG. 22 illustrates another structure 140c that is similar to structure 140 of FIG. 8, except that portions of the fabric

materials for the panels **142**, **144**, **146** and **148** have been omitted from panels **142c**, **144c**, **146c** and **148c** in FIG. 11A, and a separate outer piece of enclosing fabric **141** is provided. The elements of the structure **140c** that are the same as the elements of the structure **140** are provided with the same numeral designations except that a “c” has been added to the numeral designations in FIG. 22. The panels **142c**, **144c**, **146c** and **148c** of structure **140c** are configured in the same manner as panels **142**, **144**, **146** and **148** of structure **140**, except that the openings **196** in structure **140** have been enlarged so that only small fabric corner pieces **161** remain at the corners of the top sides of the panels **142c**, **144c**, **146c** and **148c** and the respective overlapping points **150c**, **156c**, **162c** and **168c** adjacent the stitch lines **154c**, **160c**, **166c** and **172c**. Thus, the fabric in the panels **142c**, **144c**, **146c**, **148c** between the stitch lines **154c**, **160c**, **166c**, **172c** has been removed, except for the corner pieces **161** that are provided to support the overlapping connections together. The fabric in the panels **142c**, **144c**, **146c**, **148c** between the outer sides of the panels and the stitch lines **154c**, **160c**, **166c**, **172c** still remain, as indicated, for example, by the fabric **163** between the outer side **165** of panel **144c** and stitch line **154c**. The corner pieces **161** are optional, and can be triangular, as shown in FIG. 22, and can assume any other shape as desired, and can even be a strap or string.

A separate outer piece of enclosing fabric **141** extends around the periphery of the structure **140c**, and in particular, around the outer sides (such as **165**) of all the overlapped panels **142c**, **144c**, **146c**, **148c**. The fabric **141** can be attached (e.g., by stitching) to the outer sides of the panels **142c**, **144c**, **146c**, **148c**. Although the fabric **141** is illustrated as only extending along a middle section of the height of the panels **142c**, **144c**, **146c**, **148c**, it is possible for the fabric **141** to completely cover the panels **142c**, **144c**, **146c**, **148c**, as well as the top of the structure **140c**.

Thus, the structure **140c** provides an interior space that is greater than the interior space provided by structure **140** of FIG. 8. By essentially removing the fabric in the panels **142c**, **144c**, **146c**, **148c** between the stitch lines **154c**, **160c**, **166c**, **172c**, and providing an enclosing fabric **141**, the interior space of the structure **140c** is expanded to include the outer space defined by the fabric in the panels **142c**, **144c**, **146c**, **148c** between the outer sides (such as **165**) of the panels and the stitch lines **154c**, **160c**, **166c**, **172c**. Structure **140c** also provides an additional benefit in that the overlapping connections provide increased stability and support while not decreasing interior space. This can be contrasted to the situation if the structure **140** were to have its panels hingedly connected to each other. The hinged connections would result in greater interior space (when compared to structure **140** of FIG. 8), but may sacrifice some stability if the size of the structure is large. The structure **140c** is particularly well-suited for use as a large camping tent, and a partition for use at trade shows, among other uses.

As an alternative, the enclosing fabric **141** can extend around some but not all of the panels **142c**, **144c**, **146c**, **148c**, thereby providing a walled enclosure at some regions of the structure **140c** and an opened area at the other regions of the structure **140c**.

The structure **140c** can be folded and collapsed, as well as re-deployed to the fully expanded configuration, according to the same methods utilized for the structure **140** described above. The enclosing fabric **141** can be tucked between the panels **142c**, **144c**, **146c**, **148c** during the folding and collapsing steps, and folded and collapsed together.

FIGS. 23A–23C illustrate an amusement structure **600a** that is similar to the structure **600** of FIG. 17. The elements

of the structure **600** that are the same as the elements of the structure **600a** are provided with the same numeral designations except that an “a” has been added to the numeral designations in FIGS. 23A–23C. The structure **600a** also has the two overlapping panels **610a** and **612a** that are essentially the same in orientation and construction as the panels **610** and **612**, respectively. The first panel **610a** and the second panel **612a** are each defined by a separate loop member **602a**, **604a**, respectively, and are interconnected at overlapping points **606a**, **608a** and stitch line **614a** by overlapping their respective loop members **602a**, **604a** in the manner described above, so that each panel **610a**, **612a** is angled with respect to each other. On the other hand, the supporting fabric pieces **616** and **618**, and the pocket **626**, are not provided in the structure **600a**. The opening **624a** can be curved, and can be provided in the second panel **612a** adjacent the stitch line **614a**.

Instead of the supporting fabric pieces **616** and **618**, the structure **600a** provides a rear support panel **638** that is coupled to the panels **610a**, **612a**. The rear support panel **638** can be constructed in the same manner as any of the other singular panels (such as panel **302**) described herein. The lower edge **640** of the rear support panel **638** can be either removably attached (e.g., using removable attachment mechanisms such as hooks, loops, fasteners, Velcro™ pads) or hingedly attached (using one of the structures and methods illustrated in FIGS. 16A and 16B) to the lower edge **642** of the panel **612a**, and the upper edge **644** of the panel **610a** can be removably attached (e.g., using removable attachment mechanisms such as hooks, loops, fasteners, Velcro™ pads) to the fabric **646** of the rear support panel **638** at a pre-determined desired vertical level. The vertical position of the attachment of the upper edge **644** to the fabric **646** can be adjusted to define the limits to which the two panels **610a**, **612a** can be pivoted away from each other (i.e., pivoted away in the directions of arrows **620a**, **622a**). For example, positioning the upper edge **644** at a higher vertical level means that the lower edges **642** and **650** of the panels **612a** and **610a**, respectively, are spaced closer together, while positioning the upper edge **644** at a lower vertical level means that the lower edges **642** and **650** of the panels **612a** and **610a**, respectively, are spaced further apart from each other.

A basket or hoop **654** is suspended from the side of the fabric **646** that faces the panels **610a**, **612a**. In use, a ball **628a** can be tossed at the basket **654**. The ball **628a** will either go through the basket **654**, or hit the panel **610a**, and then roll down the panel **610a** since the panel **610a** is angled. If the ball **628** rolls through the opening **624**, it will continue to roll down the panel **610a** and pass through the opening **624a** to the ground.

The structure **600a** can be collapsed in the following manner. First, as shown in FIGS. 23A and 23B, the lower edge **650** of the panel **610a** and the rear support panel **638** are pushed towards each other as shown by the arrows **666** and **668**. This pushing action is facilitated by the pivoting of the panels **610a**, **612a** along the stitch line **614a**, and will cause the three panels **610a**, **612a**, **638** to overlies each other to form one stack of panels as shown in FIG. 23C. The folding and collapsing steps illustrated in FIGS. 5A–5E can be used to fold and collapse the structure **600a** into a size which is a fraction of the original size of the structure.

FIG. 24 illustrates the application of the principles of the present invention to providing three overlapping or crossing loop members. The basic structure **800** in FIG. 24 has two basic crossing loops **802** and **804** that define two panels **810** and **812**, respectively, in exactly the same manner that the

loop members **602** and **604** define the two panels **610** and **612**, respectively, in FIG. 17. In addition, the structure **800** provides a third loop member **806** that defines a third panel **814**. The three loop members **802**, **804**, **806** overlap each other, and their respective fabrics **818**, **820** and **822** are attached, using the same techniques described in connection with FIGS. 2, 2A, 2B, 2C and 3, with the same principles applied to three loop members and three panels instead of two loop members and two panels. The three loop members **802**, **804**, **806** overlap at two opposing overlapping points **826** and **828** that are positioned along opposing sides of each of the panels **810**, **812**, **814**. The position of the overlapping points **826** and **828** can be anywhere along the sides of the panels **810**, **812**, **814**.

The structure **800** can be collapsed by pushing all the panels **810**, **812**, **814** towards each other (see arrows **830** and **832**) to form one stack of three panels **810**, **812**, **814**. This pushing action is facilitated by the pivoting of the panels **810**, **812**, **814** along the stitch line **834**, and will cause the three panels **810**, **812**, **814** to overlie each other to form one stack of panels. The folding and collapsing steps illustrated in FIGS. 5A–5E can be used to fold and collapse the structure **800** into a size which is a fraction of the original size of the structure.

As illustrated in the non-limiting embodiments and examples above, the principles of the present invention can be applied to a large variety of objects, including but not limited to sunshields, partitions, shade structures (which include tents), containers, sports structures, game structures and amusement structures. These structures can also be used as play structures (partitions, tents, shade structures, amusement games, etc.) for children and infants. When used for partitions, shade structures and containers, the fabric is preferably made from strong, lightweight materials and may include woven fabrics, sheet fabrics or even films. The fabric should be water-resistant and durable to withstand the wear and tear associated with rough treatment by children. The loop members can be made from the same materials described above for loop members **22** and **24**.

While the description above refers to particular embodiments of the present invention, it will be understood that many modifications may be made without departing from the spirit thereof. The accompanying claims are intended to cover such modifications as would fall within the true scope and spirit of the present invention.

What is claimed is:

1. A structure comprising:

a first flexible loop member having a closed loop adapted to assume an expanded position and a collapsed position;

a first fabric that covers portions of the first flexible loop member;

a second flexible loop member having a closed loop adapted to assume an expanded position and a collapsed position;

a second fabric that covers portions of the second flexible loop member;

wherein the first and second loop members overlap each other at first and second overlapping points that are spaced apart along the first and second flexible loop members; and

wherein a portion of the first fabric crosses a portion of the second fabric to form an X-shaped configuration between the first fabric and the second fabric.

2. The structure of claim 1, wherein each of the first and second overlapping points defines a hinge portion about which the first and second flexible loop members are pivotable.

3. The structure of claim 1, wherein the first flexible loop member and the first fabric define a first panel, and the second flexible loop member and the second fabric define a second panel.

4. The structure of claim 3, wherein the second panel is positioned at an angle with respect to the first panel.

5. The structure of claim 2, wherein the loop members are foldable on top of each other about the hinge portion to have the loop members overlaying each other, and wherein the overlaying loop members are collapsible to the collapsed positions by twisting and folding to form a plurality of concentric rings to substantially reduce the size of the structure in the collapsed position.

6. The structure of claim 2, wherein the hinge portion is positioned generally horizontally with respect to a support surface.

7. The structure of claim 2, wherein the hinge portion further includes a stitch line connecting the first and second fabrics and extending from about the first overlapping point to about the second overlapping point.

8. The structure of claim 1, further including a loop retaining portion provided along the first and second fabrics for retaining the respective loop member.

9. The structure of claim 3, wherein the first panel lies completely in the same first plane.

10. The structure of claim 9, wherein the second panel lies completely in the same second plane.

11. The structure of claim 10, wherein the first and second planes intersect each other.

12. The structure of claim 10, wherein the first and second planes are perpendicular to each other.

\* \* \* \* \*