



US006691807B1

(12) **United States Patent**
Bhavsar et al.

(10) **Patent No.:** **US 6,691,807 B1**
(45) **Date of Patent:** **Feb. 17, 2004**

(54) **HYBRID ELECTRIC VEHICLE WITH VARIABLE DISPLACEMENT ENGINE**

(75) Inventors: **Chinu P. Bhavsar**, Ann Arbor, MI (US); **Joanne T. Woestman**, Dearborn, MI (US); **Prabhakar B. Patil**, Southfield, MI (US)

(73) Assignee: **Ford Global Technologies LLC**, Dearborn, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

5,713,426 A	2/1998	Okamura	
5,713,427 A	2/1998	Lutz	
5,755,302 A	5/1998	Lutz	
5,775,449 A	7/1998	Moroto	
5,788,006 A	8/1998	Yamaguchi	
5,791,427 A	8/1998	Yamaguchi	
5,799,744 A	9/1998	Yamaguchi	
5,806,617 A	9/1998	Yamaguchi	
5,813,383 A *	9/1998	Cummings	123/198 F
5,823,280 A	10/1998	Lateur et al.	
5,823,281 A	10/1998	Yamaguchi	
5,975,052 A *	11/1999	Moyer	123/198 F
5,984,034 A *	11/1999	Morisawa et al.	180/65.2
5,992,390 A *	11/1999	Moyer	123/198 F

(21) Appl. No.: **09/547,275**

(22) Filed: **Apr. 11, 2000**

(51) **Int. Cl.**⁷ **B60K 6/02**

(52) **U.S. Cl.** **180/65.2**

(58) **Field of Search** 180/65.2, 65.3, 180/65.4, 65.6; 701/22, 70; 123/198 F

FOREIGN PATENT DOCUMENTS

DE	43 24 010 A1	1/1995
DE	197 12 246 A1	11/1997
EP	0 781 680 A2	7/1997
EP	11182275	7/1999
EP	0 970 838 A2	1/2000
GB	2 340 463 A	2/2000
RU	2132784	7/1999
WO	WO 99/24280	5/1999

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,335,429 A *	6/1982	Kawakatsu	180/65.2
4,583,505 A *	4/1986	Frank et al.	123/198 F
4,770,137 A *	9/1988	Okabe et al.	123/198 F
5,368,000 A	11/1994	Koziara	
5,408,966 A	4/1995	Lipinski	
5,408,974 A	4/1995	Lipinski	
5,437,253 A	8/1995	Huffmaster	
5,490,486 A	2/1996	Diggs	
5,495,912 A *	3/1996	Gray, Jr. et al.	180/65.4
5,568,795 A *	10/1996	Robichaux et al.	123/198 F
5,667,029 A	9/1997	Urban	
5,678,646 A	10/1997	Fliege	
5,691,588 A	11/1997	Lutz et al.	
5,697,466 A	12/1997	Moroto	
5,698,905 A	12/1997	Ruthlein	
5,713,425 A	2/1998	Buschhaus	

OTHER PUBLICATIONS

US 6,032,738, 3/2000, Boncan et al. (withdrawn)

* cited by examiner


Primary Examiner—Frank Vanaman

(74) *Attorney, Agent, or Firm*—Carlos Hanze; Brooks Kushman P.C.

(57) **ABSTRACT**

A hybrid electric vehicle **10** having a propulsion system **12** which integrates a motor-generator **14** and a variable displacement internal combustion engine **16**. Motor-generator **14** and engine **16** are each operatively coupled to drive train **17** of vehicle **10**, and cooperatively power vehicle **10**.

17 Claims, 3 Drawing Sheets






Figure 1




Figure 2




Figure 3

HYBRID ELECTRIC VEHICLE WITH VARIABLE DISPLACEMENT ENGINE

FIELD OF THE INVENTION

This invention relates to a hybrid electric vehicle and more particularly, to a hybrid electric vehicle having a variable displacement engine which provides for improved fuel economy and load performance.

BACKGROUND OF THE INVENTION

Various types of automotive vehicles have been designed and manufactured for the purpose of improving fuel economy. One type of vehicle, commonly known as a hybrid electric vehicle (“HEV”), utilizes both an internal combustion engine and one or more electric motors to generate power and torque. The electric motor(s) within a hybrid electric vehicle provides the vehicle with additional degrees of freedom in delivering the driver-demanded torque. Particularly, hybrid electric vehicles may have the flexibility of using the electric motor(s) as the sole source of torque at low load operating conditions. Additionally, at relatively high loads, a hybrid electric vehicle can employ or activate both the internal combustion engine and the electric motor(s) to supply the driver-demanded torque. Due to the ability of the electric motor(s) to augment the engine generated torque at high load operating conditions, hybrid electric vehicles typically employ relatively small or “downsized” internal combustion engines, which provide for improved fuel economy.

One drawback associated with these hybrid electric type vehicles is that the electric motors used within these vehicles receive power from an electrical energy storage device (e.g., a battery) which becomes depleted over time. When the electrical energy storage device or battery becomes depleted, the motors are no longer able to supplement the engine to deliver relatively high amounts of torque. This especially presents a problem in steady state high load situations (e.g., when towing or hauling heavy cargo), as the propulsion system (e.g., the engine and electric motor) may not be able to deliver the desired or demanded torque consistently and/or over an extended period of time. Thus, when high load steady state performance is required within a vehicle (e.g., within large trucks, sport-utility vehicles, and other vehicles that are often used for towing or hauling), the vehicle’s engine cannot be “downsized” and the hybridization-related fuel economy benefits cannot realized to the maximum potential.

Another type of vehicle, known as a variable displacement engine (“VDE”) type vehicle, conserves fuel by selectively disabling or deactivating some of the engine’s cylinders under certain operating conditions. Particularly, during low engine load operation, a VDE type vehicle conserves fuel by operating on only some of the engine’s cylinders (e.g., on four, five, six, or seven of eight cylinders). During relatively high speeds and/or high load operation, a VDE type vehicle can meet the driver-demanded speed and/or torque by operating on all of the engine’s cylinders (e.g., on eight of eight cylinders). While these VDE type vehicles improve fuel economy and provide the torque required to satisfy relatively high load operation, they suffer from some drawbacks.

For example and without limitation, during relatively low and/or transient load operation (e.g., when the operating load varies significantly over a short period of time), the power train of a VDE type vehicle frequently shifts between

various cylinder operating modes (e.g., the engine shifts between four, six, eight and ten cylinder operation). This frequent shifting between cylinder operating modes results in noise and vibration harshness (“NVH”) problems which are perceivable by the driver and which give the vehicle a “rough”, “inconsistent” and/or “non-responsive” feel or ride.

There is therefore a need for a vehicle which provides an improved fuel economy, which provides steady state high load performance, and which operates smoothly and responsively under transient load conditions.

SUMMARY OF THE INVENTION

It is a first object of the invention to provide an automotive vehicle which overcomes at least some of the previously delineated drawbacks of prior automotive vehicles.

It is a second object of the invention to provide an automotive vehicle which delivers and/or generates torque by use of a variable displacement engine and by use of one or more electric motors.

It is a third object of the invention to provide a hybrid electric vehicle having a variable displacement engine which allows the vehicle to perform under steady state high load operating conditions, while maintaining an improved fuel economy under relatively low or moderate load operating conditions.

It is a fourth object of the invention to provide an automotive vehicle having a variable displacement engine and which utilizes an electric motor to generate torque when operating under transient loads, thereby reducing the frequency of cylinder activation and deactivation within the variable displacement engine.

According to a first aspect of the present invention, a hybrid electric vehicle is provided. The hybrid electric vehicle includes a drive line; a battery which stores an amount of electrical charge and which selectively provides electrical power; and a sensor which is coupled to the battery and which is effective to estimate the amount of electrical charge and to generate a first signal based upon the estimated amount of electrical charge. The vehicle further includes an electric motor which is operatively coupled to the battery and to the drive line, which receives the electrical power from the battery, and which selectively provides torque to the drive line, and a variable displacement engine which is operatively coupled to the drive line and which selectively provides torque to the drive line. A controller is communicatively coupled to the variable displacement engine, to the electric motor, and to the sensor. The controller is effective to determine a requested torque to be provided to the drive line, to receive the first signal, and to partition the requested torque into an engine torque and a motor torque, based upon the first signal. The controller is further effective to cause the electric motor to provide the motor torque to the drive line, and to cause the variable displacement engine to provide the engine torque to said drive line.

According to a second aspect of the present invention, a method of delivering torque to a vehicle drive train is provided. The method includes the steps of providing a variable displacement internal combustion engine which selectively delivers torque to the drive train; providing a motor which selectively delivers torque to the drive train; providing an electrical charge storage device which supplies electrical energy to the motor; estimating an amount of charge which is held within the electrical charge storage device; receiving at least one signal from a driver-operated control; calculating a torque value based upon the at least

one signal; partitioning the torque value into a desired motor torque and a desired engine torque based upon the estimated amount of charge and the torque value; causing the motor to deliver the desired motor torque to the drive train; and causing the variable displacement internal combustion engine to deliver the desired engine torque to the drive train, thereby powering the vehicle.

These and other features, aspects, and advantages of the invention will become apparent by reading the following specification and by reference to the following drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a vehicle including a propulsion system which is made in accordance with the teachings of a preferred embodiment of the present invention;

FIG. 2 is a block diagram illustrating the operational functionality of the propulsion system utilized within the vehicle shown in FIG. 1; and

FIG. 3 is a block diagram illustrating one non-limiting example of the partitioning function performed by the propulsion system shown in FIG. 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT OF THE INVENTION

Referring now to FIGS. 1 and 2, there is shown an automotive hybrid electric vehicle 10 having a propulsion system 12 which is made in accordance with the teachings of the preferred embodiment of the present invention. Propulsion system 12 includes an electric machine or motor 14, which is operatively coupled to a conventional electrical energy storage device 15 (e.g., a battery or other electrical energy storage device), and a variable displacement internal combustion engine 16. Electric motor 14 and engine 16 are each selectively and operatively coupled to the vehicle's driveline or drive train 17 (e.g., to the drive shaft of the vehicle) and cooperatively deliver power and torque to the drive train 17, thereby powering the vehicle 10. A control system or controller 18 is electrically and communicatively coupled to conventional user or driver operated controls or components 20 and to conventional vehicle operating condition sensors 22. As described more fully and completely below, controller 18 receives signals and/or commands generated by controls 20 and sensors 22, and processes and utilizes the received signals to determine the amount of torque which is to be provided to the vehicle's drive train 17 and to selectively cause motor 14 and engine 16 to cooperatively provide the desired torque to the drive train 17.

In the preferred embodiment of the invention, electric machine or motor 14 is a conventional electric motor-generator unit which is adapted for use in a hybrid electric vehicle. Electric motor-generator 14 is operatively coupled to the drive shaft (not shown) of the vehicle 10 in a known and conventional manner. In alternate embodiments, motor-generator 14 is operatively and conventionally coupled to other portions of the drive train or drive line 17 of the vehicle 10 (e.g., to one or more of the axles or differential gear units of vehicle 10), and to other mechanical components of vehicle 10. In other alternate embodiments, propulsion system 12 may include several motor-generators. Motor-generator 14 selectively provides torque to the drive shaft or drive train 17 of vehicle 10, thereby selectively powering vehicle 10. Electric motor-generator 14 also functions as a motor to convert drive train energy into electrical energy which is used to electrically power various electrical com-

ponents of vehicle 10. Electrical charge storage device 15 supplies power to motor-generator 14 and can further be used to recover and store during vehicle braking. While the following description is made with reference to the motor-generator 14, it should be appreciated that other types of electric machines or motor-generators may be used in combination with the variable displacement engine 16 to deliver torque to the drive train 17 of vehicle 10.

In alternate embodiments, motor 14 may comprise a pair of motor-generators arranged in a conventional "dual-split" or "power-split" type hybrid configuration. Particularly, in such alternate embodiments, the engine (e.g., engine 16) and the pair of motor-generators are interconnected by use of a conventional planetary gear set or system, which is operatively coupled to and transfers torque and power to the vehicle's drive train (e.g., to the vehicle's drive shaft).

Variable displacement engine 16 is a conventional multi-cylinder internal combustion variable displacement engine which includes several cylinders (e.g., four, six, eight, ten or more cylinders) and which is capable of operating on less than a full complement of cylinders. That is, engine 16 is able to selectively disable or deactivate one or more cylinders and operate on less than all of its cylinders to conserve fuel at relatively light or low load operating conditions. In one non-limiting embodiment, engine 16 comprises the variable displacement engine which is described in U.S. Pat. No. 5,490,486 of Diggs which has been assigned to the present assignee. Engine 16 is operatively coupled to the driveline or drive train 17 (e.g., to the drive shaft) of vehicle 10 in a known and conventional manner and selectively provides torque to the drive train 17 of vehicle 10, thereby powering vehicle 10.

In the preferred embodiment, control system 18 includes several microprocessors or controllers 24, 26 and 28 as well as other chips and integrated circuits which cooperatively control the operation of propulsion system 12. Controllers 24, 26 and 28 comprise commercially available, conventional, and disparate chips or devices, which are operatively and communicatively linked in a cooperative manner. Controllers 24, 26 and 28 each include permanent and temporary memory units, which are adapted to and do store at least a portion of the operating software which directs the operation of control system 18. In one non-limiting embodiment, controllers 24, 26 and 28 are embodied within a single controller, chip, microprocessor or device. Controller 26 is a conventional controller of the type which is used to control an HEV motor-generator, and controller 28 is a conventional controller of the type which is used to provide control to a variable displacement engine. As described more fully and completely below, controller 24 is effective to determine the total amount of torque which is to be provided or delivered to drive train 17 and to partition or divide the total amount of torque between motor 14 and engine 16. Controller 24 selectively stores information and data, including information associated with the operation of the invention such as data defining engine and cylinder operating conditions, engine loads, vehicle speeds, state-of-charge conditions of battery 15, and other data, which are used by controller 24 to determine the amount of torque which should be provided to drive train 17 by motor 14 and by engine 16.

Driver operated controls 20 comprise a plurality of conventional and commercially available switches, devices and other components which accept user or driver selected inputs, thereby allowing the user or driver to operate vehicle 10. In one non-limiting embodiment of the invention, controls 20 include without limitation a vehicle accelerator or

“gas pedal”, a vehicle shifter which allows the driver to select between one or more operating speeds or gear engagements, a brake pedal, and a speed control system. Controls **20** provide commands and/or operating data to control system **18** which utilizes these commands or data to determine the amount of torque which is to be delivered by vehicle **10** and to selectively cause motor **14** and engine **16** to cooperatively provide the desired torque.

Sensors **22** comprise a plurality of conventional and commercially available sensors which measure and/or acquire information pertaining to the motor **14**, electrical charge storage device **15**, engine **16** and vehicle **10** (e.g., vehicle operating condition data). In the preferred embodiment of the invention, sensors **22** include one or more conventional vehicle and/or engine speed sensors and one or more sensors adapted to estimate the amount of charge remaining within battery **15**. Sensors **22** generate one or more signals to controller **18** based upon these measured and/or estimated values. Particularly, sensors **22** provide vehicle operating data to control system **18** which utilizes this data to determine the amount of torque which is to be delivered to drive train **17** and to selectively cause motor **14** and engine **16** to cooperatively provide the desired torque.

In operation, control system **18** (i.e., propulsion controller **24**) receives commands, data, and/or signals from driver operated controls **20** and from vehicle sensors **22**. Based upon this received data, propulsion controller **24** calculates or determines the overall amount of torque which is being demanded or requested by the driver/user of the vehicle **10**, as illustrated in functional block or step **30**. In one non-limiting embodiment, this overall “desired” torque calculation or determination is made by use of conventional algorithms and/or by referencing conventional database tables or matrixes stored within controller **24**.

Once the overall “desired” or “demanded” torque has been calculated, controller **24** proceeds to functional block or step **32**, and determines the amount or percentage of the desired torque which is to be provided by motor **14** (e.g., the “desired motor torque”) and the amount or percentage of the desired torque which is to be provided by engine **16** (e.g., the “desired engine torque”). Particularly, controller **24** determines the most efficient use of the torque providing sources (i.e., motor **14** and engine **16**), and partitions or divides the demanded torque in a manner which balances fuel economy and vehicle performance. One non-limiting example of this “partition” function or strategy performed by controller **24** is illustrated by flow diagram **50** shown in FIG. **3**.

Referring now to FIG. **3**, controller **24** receives the desired or demanded torque in functional block or step **52**. Controller **24** then determines whether electrical power is available (e.g., within battery **15**) to allow motor **14** to provide torque to the drive train **17**, as illustrated in functional block or step **54**. In one non-limiting embodiment, controller **24** determines whether electrical power is available by estimating the amount of charge remaining within battery **15** and comparing the measured amount or value to a predetermined value stored within controller **18**. If electrical power is not available, controller **24** proceeds to functional block or step **56**, otherwise controller **24** proceeds to functional block or step **58**. In step **56**, controller **24** determines whether the requested torque exceeds a “VDE mode” threshold torque value. If the requested torque exceeds the “VDE mode” threshold value, controller **24** “partitions” or allocates all of the requested torque to engine **16** (e.g., the “desired motor torque” is set to zero), and causes engine **16** to run in “ICE mode”, as illustrated in functional block or step **60**. Particularly, controller **24** sends

a signal to engine **16** which is effective to activate all of the cylinders of the engine **16** and to deactivate the “variable displacement” function of engine **16**. Thus, when operating in “ICE mode”, engine **16** runs on a full complement of cylinders (e.g., on ten of ten cylinders).

If the requested torque does not exceed the “VDE mode” threshold value, controller **24** partitions or allocates all of the requested torque to engine **16**, and causes engine **16** to run in “VDE mode”, as illustrated in functional block or step **62**. When operating in “VDE mode”, engine controller **34** determines the number of cylinders (e.g., the cylinder operating mode) that is required to deliver the requested torque to drive train **17** and activates only that number of cylinders.

By use of the above-described partition strategy, system **10** causes engine **16** to operate on all cylinders and to provide a maximum amount or percentage of torque to drive train **17** during operating conditions in which the battery **15** has been “drained” or discharged. It should be appreciated that these types of operating conditions (e.g., where battery **15** has been drained) correspond to steady state high load operating conditions. System **12** thus provides all of the requested torque through engine **16** during relatively high load operating conditions where engine **16** is the most efficient torque providing source. Moreover, the strategy **50** used by system **12** further substantially prevents engine **16** from changing between cylinder operating modes unless necessary, thereby reducing the frequency that cylinders are activated and deactivated within engine **16**.

The value of the “VDE mode” threshold is stored within controller **24** and may be a dynamic value (e.g., a function of vehicle speed or engine speed). In one non-limiting embodiment, controller **24** compares the requested torque to several different “VDE mode” thresholds, which each corresponds to a unique cylinder operating mode of engine **16**.

If electrical power is available in step **54**, controller **24** proceeds to functional block or step **58**. In step **58**, controller **24** determines whether the requested torque exceeds an “EM mode” threshold value. If the requested torque does not exceed the “EM mode” threshold value, controller **24** “partitions” or allocates a maximum amount or percentage (e.g., **100%**) of the requested torque to motor **14** and causes system **12** to run solely in “EM mode”, as illustrated in functional block or step **64**. When only “EM mode” is activated (i.e., when neither “VDE mode” nor “ICE mode” is concurrently activated), torque is provided solely by motor **14** and engine **16** can be “shut off” or disabled. In this manner, propulsion system **12** utilizes motor **14** to provide all of the requested torque during “low load” operating conditions, where the engine **16** is most inefficient, thereby conserving fuel. The value of the “EM mode” threshold is stored within controller **24** and may be a dynamic value (e.g., a function of vehicle speed or engine speed).

If the requested torque does exceed the “EM mode” threshold value, controller **24** proceeds to functional block or step **66**, and determines whether the requested torque exceeds the “VDE mode” threshold value. If the requested torque exceeds the “VDE mode” threshold value, controller **24** causes propulsion system **12** to run in “ICE mode” and “EM mode”, as illustrated in functional block or step **68**, and “partitions” or allocates a maximum amount or percentage of the requested torque to engine **16**. When operating in “ICE mode” and “EM mode”, propulsion system **12** utilizes all cylinders of engine **16** as well as motor **14** to provide torque to the vehicle drive line **17**.

If the requested torque is not greater than the “VDE mode” threshold value (e.g., during moderate and/or tran-

sient load operating conditions), controller **24** proceeds to functional block or step **70**, and causes the propulsion system to operate in “EM mode” and “VDE mode”. When operating in “EM mode” and “VDE mode”, controller **24** partitions or allocates the requested torque between motor **14** (i.e., the desired motor torque) and engine **16** (i.e., the desired engine torque) based upon the value of the requested torque. In one non-limiting embodiment, the torque partition or allocation is computed or determined by use of one or more database tables or matrixes stored within controller **24**. When the requested torque changes relatively rapidly (e.g., during transient load operating conditions), controller **24** allocates the majority of the transient torque values or response to motor **14** and maintains the torque allocated to engine **16** relatively constant. In this manner, controller **18** substantially prevents engine **16** from frequently shifting between cylinder operating modes (i.e., the frequent activation and deactivation of the cylinders), and achieves a smoother and more responsive performance.

It should be appreciated that the above-described torque partitioning function does not limit the scope of the invention, and that in other alternate embodiments, controller **24** performs other steps and considers different and/or additional vehicle operating attributes, conditions and other factors when partitioning or allocated the demanded torque.

Once the demanded torque has been “partitioned”, controller **24** generates a signal representing the desired “motor torque” to motor controller **26**, and a signal representing the desired “engine torque” to engine controller **28**. Motor controller **26** receives the desired “motor torque” and generates a control signal to motor **14** which is effective to cause motor **14** to produce and/or deliver the desired torque to drive train **17**.

Engine controller **28** receives the desired “engine torque” and determines the number of cylinders which are required to provide the requested torque (e.g., the cylinder operating mode of engine **16**), as illustrated in functional block or step **34**. In functional block or step **36**, engine controller **28** selectively deactivates or disables any cylinders which are not “necessary” to provide the desired torque, or selectively activates or enables and cylinders which are “necessary” to provide the desired torque. In functional block or step **38**, controller **28** generates a control signal to engine **16** which is effective to control the timing and operation of engine **16** and to cause engine **16** to produce and/or deliver the desired torque to drive train **17**.

It should be appreciated that the combination of a hybrid electric vehicle and a variable displacement engine provides significant advantages over prior systems. For example and without limitation, prior hybrid electric vehicles require a “downsized” or relatively small engine to achieve improved fuel economy. This “downsized” or relatively small engine substantially prevents hybrid electric vehicles from performing under steady state high load operating conditions. The integration of a variable displacement engine within the present invention allows the hybrid electric vehicle **10** to perform under steady state high load operating conditions (e.g., by activating all of the engine’s cylinders), while still allowing the vehicle **10** to achieve improved fuel economy under low load operating conditions (e.g., by disabling one or more cylinders of the variable displacement engine). Hence, instead of “downsizing” a hybrid electric vehicle’s engine to realize fuel economy benefits, the present invention integrates a variable displacement engine to efficiently deliver low torque, while maintaining the ability to deliver high torque when necessary.

The present invention further solves the problems associated with variable displacement engines which relate to the

frequent shifting between cylinder operating modes during transient load operating conditions and NVH issues at low loads. Particularly, by allowing the electric motor to meet the transient torque demands in these types of operating conditions, the torque which is provided by engine **16** can be held relatively constant, thereby preventing the frequent shifting between cylinder operating modes within the engine **16** and giving vehicle **10** a “smoother” and more responsive “feel” and ride. Thus, the integration of a hybrid electric vehicle and a variable displacement engine provided by the present invention expands the range of operating loads in which the vehicle can operate efficiently without while maintaining the quality of vehicle performance.

It is understood that the invention is not limited by the exact construction or method illustrated and described above, but that various changes and/or modifications may be made without departing from the spirit and/or the scope of the inventions.

What is claimed is:

1. A control system for a vehicle having a variable displacement engine, a motor, an electrical storage device operatively connected to the motor, a driver operated control, and a sensor for detecting a vehicle operating condition, the control system comprising:

- a controller in communication with the engine, the motor, the driver operated control, and the sensor, the controller being configured to at least,
 - a) receive an input from at least one of the driver operated control and the sensor,
 - b) determine a demanded torque based on the input received,
 - c) compare the demanded torque to a first torque threshold,
 - d) partition the demanded torque into an engine torque and a motor torque based on the comparison of the demanded torque to the first torque threshold,
 - e) compare the demanded torque to a second torque threshold when the engine torque is non-zero, and
 - f) determine a number of operating cylinders for the engine based on the comparison of the demanded torque to the second torque threshold.

2. The control system of claim **1**, wherein the controller is further configured to allocate all of the demanded torque to the motor when the demanded torque is not above the first torque threshold.

3. The control system of claim **1**, wherein the sensor includes one of a battery state of charge sensor, a vehicle speed sensor, and an engine speed sensor.

4. The control system of claim **1**, wherein the electrical storage includes a battery in communication with the sensor, and the controller is further configured to receive an input from the sensor related to a state of charge of the battery, and to allocate all of the demanded torque to the engine when the battery state of charge is below a predetermined value.

5. The control system of claim **1**, wherein the driver operated control includes one of an accelerator pedal, a brake pedal, a vehicle shifter, and a speed control system.

6. The control system of claim **1**, wherein all of the engine cylinders are operated when the demanded torque is above the second torque threshold.

7. The control system of claim **1**, wherein the controller comprises a motor controller and an engine controller.

8. The control system of claim **7**, wherein the controller further comprises a propulsion controller in communication with the motor controller and the engine controller, the propulsion controller being configured to receive the input from at least one of the driver operated control and the

9

sensor, and to determine the demanded torque and partition the demanded torque.

9. A vehicle comprising:

- a variable displacement engine capable of selectively providing torque to drive the vehicle;
- a motor capable of selectively providing torque to drive the vehicle;
- an electrical storage device operatively connected to the motor and capable of providing electrical power to the motor;
- a driver operated control; and
- a controller in communication with the engine, the motor, and the driver operated control and configured to at least receive an input from the driver operated control, determine a demanded torque based on the input received, compare the demanded torque to a first torque threshold, partition the demanded torque into an engine torque and a motor torque based on the comparison of the demanded torque to the first torque threshold, compare the demanded torque to a second torque threshold when the engine torque is non-zero, and determine a number of operating cylinders for the engine based on the comparison of the demanded torque to the second torque threshold.

10. The vehicle of claim **9**, wherein the driver operated control includes one of an accelerator pedal, a brake pedal, a vehicle shifter, and a speed control system.

11. The vehicle of claim **9**, wherein the controller is further configured to allocate all of the demanded torque to

10

the motor when the demanded torque is not above the first torque threshold.

12. The vehicle of claim **9**, wherein all of the engine cylinders are operated when the demanded torque is above the second torque threshold.

13. The vehicle of claim **9**, further comprising a sensor operatively connected to the controller for providing an input to the controller related to a vehicle operating condition.

14. The vehicle of claim **13**, wherein the sensor includes one of a battery state of charge sensor, a vehicle speed sensor, and an engine speed sensor.

15. The vehicle of claim **14**, wherein the electrical storage device includes a battery in communication with the sensor, and the controller is further configured to receive an input from the sensor related to a state of charge of the battery, and to allocate all of the demanded torque to the engine when the battery state of charge is below a predetermined value.

16. The vehicle of claim **15**, wherein the controller comprises a motor controller and an engine controller.

17. The vehicle of claim **16**, wherein the controller further comprises a propulsion controller in communication with the motor controller and the engine controller, the propulsion controller being configured to receive inputs from the driver operated control and the sensor, and to determine the demanded torque and partition the demanded torque.

* * * * *