



US006692059B1

(12) **United States Patent Mills**

(10) **Patent No.: US 6,692,059 B1**  
(45) **Date of Patent: Feb. 17, 2004**

(54) **SUN VISOR WITH CLAM SHELL CORE ATTACHMENT SNAPS**

(75) **Inventor: Don Mills, Sandusky, MI (US)**

(73) **Assignee: Grupo Antolin Ingenieria, S.A., Burgos (ES)**

(\* ) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.: 10/262,738**

(22) **Filed: Oct. 2, 2002**

(51) **Int. Cl.<sup>7</sup> ..... B60J 3/00**

(52) **U.S. Cl. .... 296/97.1; 296/97.2; 296/97.8**

(58) **Field of Search ..... 296/97.1, 97.5, 296/97.8, 97.9, 97.12**

5,678,879 A	10/1997	Mailander et al. ....	296/97.1
5,695,237 A	12/1997	Erickson et al. ....	296/97.1
5,716,092 A *	2/1998	Dellinger et al. ....	296/97.1
5,871,252 A	2/1999	Gute .....	276/97.1
5,887,933 A	3/1999	Peterson .....	296/97.1
5,895,087 A	4/1999	Viertel et al. ....	296/97.1
5,924,748 A	7/1999	Zapinski .....	286/97.1
5,934,734 A	8/1999	Wilson .....	296/97.11
5,984,399 A	11/1999	Viertel et al. ....	296/97.1
6,021,986 A	2/2000	Murdock .....	248/289.11
6,033,005 A	3/2000	Crotty, III .....	296/97.1
6,042,172 A	3/2000	Murdock .....	296/97.12
6,120,086 A	9/2000	Miller .....	296/97.9
6,126,302 A	10/2000	Corn .....	362/492
6,131,985 A	10/2000	Twietmeyer et al. ....	296/97.12
6,139,083 A	10/2000	Fischer et al. ....	296/97.1
6,302,467 B1	10/2001	Crotty, III et al. ....	296/97.1
6,367,861 B1	4/2002	Crotty, III et al. ....	296/97.1
6,409,245 B1 *	6/2002	Crotty et al. ....	296/97.1
2001/0024048 A1 *	9/2001	Hobson et al. ....	296/97.1
2002/0113454 A1 *	8/2002	Crotty et al. ....	296/97.1

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,763,946 A *	8/1988	Robbins et al. ....	296/97.1
4,810,023 A *	3/1989	Kawada .....	296/97.8
4,858,983 A	8/1989	White et al. ....	296/97.13
4,890,875 A	1/1990	Takahashi .....	296/97.2
4,925,233 A	5/1990	Clark .....	296/97.11
4,988,140 A *	1/1991	Van Order .....	296/97.2
4,998,765 A	3/1991	Van Order et al. ....	296/97.11
4,998,767 A *	3/1991	Lawassani et al. ....	296/97.1
5,007,532 A	4/1991	Binish .....	296/97.1
5,031,950 A	7/1991	Miller .....	296/97.1
5,031,951 A	7/1991	Binish .....	296/97.1
5,054,839 A *	10/1991	White et al. ....	296/97.1
5,108,143 A	4/1992	Miwa .....	296/97.1
5,131,711 A *	7/1992	Laferle .....	296/97.1
5,205,639 A *	4/1993	White et al. ....	296/97.2
5,209,880 A	5/1993	Miwa .....	264/23
5,301,994 A	4/1994	Wilson .....	296/97.2
5,308,136 A *	5/1994	Schwarz et al. ....	296/97.1
5,338,082 A	8/1994	Miller .....	296/97.1
5,411,309 A	5/1995	Aymerich et al. ....	296/97.1
5,556,154 A *	9/1996	Vaxelaire .....	296/97.1
5,580,118 A *	12/1996	Crotty, III .....	296/97.1

**FOREIGN PATENT DOCUMENTS**

EP	0 562 085	*	9/1993
EP	0 826 533 A2		4/1998
JP	1 215617	*	8/1989
JP	1 226421	*	9/1989
JP	11 334361	*	12/1999

\* cited by examiner


*Primary Examiner*—Kiran Patel

(74) *Attorney, Agent, or Firm*—Young & Basile, PC

(57) **ABSTRACT**

A sun visor has a plurality of receivers and projections defining snap connections for securing first and second core halves in a folded over, closed position. The receivers are carried on one of the core halves and include angularly extending latch arms. The projections are carried on the other core half and have an enlarged head insertable through the spaced ends of the latched arms such that the latch arms snap underneath the head into engagement with a stem of each projection to lock the projection in the receiver.

**8 Claims, 10 Drawing Sheets**






FIG - 1




FIG - 2




FIG - 3





FIG - 4








FIG - 8




FIG - 9





FIG - 10



FIG - 11






FIG - 12

FIG - 14





FIG - 15



## SUN VISOR WITH CLAM SHELL CORE ATTACHMENT SNAPS

### BACKGROUND

The present invention relates, in general, to vehicle sun visors.

Sun visors are used in vehicles to provide front and side window protection from sunlight entry. Such sun visors are pivotal about a longitudinal axis between a stowed position adjacent the headliner and a deployed position angularly extending from the headliner. Most sun visors can also be unlocked from a headliner mounted clip or D-ring and pivoted to the side window about a support arm attached to the vehicle headliner. A biasing means is typically mounted within the visor to prevent movement and noise when the sun visor is in the stowed position.

Over the years, various enhancements or features have been added for sun visors to increase their versatility as well as to add other convenience factors to the vehicle occupants.

One such feature is the telescopic extension of the entire sun visor along the longitudinal axis of the support arm to enable the sun visor to be repositioned laterally across the windshield or the side window to block sun light entry in a particular direction for an occupant.

Another common feature is a mirror with or without a pivotal cover and with or without an illumination means which is mounted in one surface of the sun visor, typically the surface facing the headliner when the sun visor is in the stowed position. The sun visor need only be pivoted to the angular downward extending position to allow use of the mirror.

When an illumination means, such as lamps, are provided around the mirror, electrical conductors or wires extend through the A pillar of the vehicle body and the support arm to the individual lamps in the sun visor.

Various means have been provided to mount fabric or decorative covers over the plastic sun visor core. One such mount traps the ends of the fabric cover between the two clam shell core halves when the halves are moved to their closed, locked position. Another mount utilizes projections on the inner surfaces of the core halves over which the inner edges of the fabric cover are forced.

Heat stake projections have also been provided about the periphery of the core halves. In this mounting technique, the edges of the fabric cover are forced over the heat stake projections and then heat is applied to melt the stakes through the interstices of the fabric cover to fixedly retain the inner edges of the cover in a fixed position on the sun visor core.

### SUMMARY

The present invention is a sun visor having unique clam shell core attachment snap lock means.

In one aspect of the invention, the sun visor includes a core formed of first and second foldable core halves each pivotal about a common hinge edge. A plurality of receivers are mounted on the first core half, each receiver formed of at least a pair of latch arms extending angularly from the core halves toward each other.

A plurality of projections are formed on the second core half, each projection having a stem extending from the second core half and an enlarged head, the first and second latch arm having ends which are displacable when the head of the projection is inserted therethrough wherein the ends of

the latch arms snap underneath the head into engagement with the projection to lock the projection in the and to lock the first and second core halves in a fully assembled, closed position.

In one aspect, the head defines a pair of opposed edges extending laterally outward from the stem, the edges engageable with the latch arms.

In another aspect, the latch arms are disposed at an acute angle with respect to a plane through a major extent of the second core half.

Each of the latch arms is normally spaced apart by a distance less than the dimension of the outer periphery of the head of the projection.

The sun visor with attachment snaps provides a unique attachment for sun visors having foldable core halves which provides easy insertion of one part into the other part while providing a high level of pull-out or separation force resistance to prevent inadvertent opening of the folded over core halves of the sun visor core. The unique snap attachments of the present invention provide increasing separation force resistance when force is exerted in a direction to separate the snap portions from each other.

Other applications of the present invention will become apparent to those skilled in the art when the following description of the best mode contemplated for practicing the invention is read in conjunction with the accompanying drawings.

### BRIEF DESCRIPTION OF THE DRAWING

The various features, advantages and other uses of the present invention will become more apparent by referring to the following detailed description and drawing in which:

FIG. 1 is a perspective view of a completely assembled sun visor according to one aspect of the present invention;

FIG. 2 is an elevational view of an open clam shell core for the sun visor shown in FIG. 1, depicting the initial step of attaching the fabric cover to the core;

FIG. 3 is an enlarged, cross-sectional view of one corner of the clam shell core in the closed position showing the edge fold and edge material attached to the core;

FIG. 4 is an enlarged, perspective view of the corner of the core shown in FIG. 3;

FIG. 5 is an exploded, perspective view of the slide carrier, clip and large support rod according to one aspect of the present invention;

FIG. 6 is a cross sectional view showing the slider carrier, clip and support rod in a closed core position;

FIG. 7 is a perspective view of the sun visor of FIG. 1 depicting the slider means in the normal, retracted position;

FIG. 8 is a perspective view similar to FIG. 7, but showing the slide carrier in the fully extended sun visor position;

FIG. 9 is a perspective view of the sun visor of FIG. 1 having a short length, non-telescoping support arm;

FIG. 10 is a perspective view of another aspect of the sun visor according to the present invention shown in an open core position and depicting the mounting of a mirror to one core half;

FIG. 11 is a perspective view of a completed sun visor showing one aspect of a fully optioned mirror assembly with a cover deployed in a closed position;

FIG. 12 is a perspective view, similar to FIG. 11, but with the cover deployed in an open position;

FIG. 13 is a cross-sectional view through the sun visor of FIG. 11 depicting the mounting of the mirror assembly to the core and cover;

FIG. 14 is a perspective view of another aspect of a sun visor according to the present invention having a mirror assembly mounted therein; and

FIG. 15 is a cross-sectional view of an alternate aspect of the sun visor of the present invention.

#### DETAILED DESCRIPTION

Referring now to the drawings, and to FIGS. 1-14 in particular, there is depicted a sun visor denoted generally by reference number 10 which includes a number of features, all described hereafter, which may be used in various combinations as well as individually, separate from the other features.

In general, the sun visor 10 includes a core 12, a cover 14 typically made of fabric, including synthetics and natural fabrics, a support arm formed of either a long length support arm 16 allowing telescoping movement of the sun visor 10 as described hereafter and as shown in FIGS. 7 and 8 or a short length support arm 18 shown in FIG. 9 which does not provide telescoping extension of the sun visor 10. The sun visor 10 may also include a mirror assembly shown in various feature combinations in FIGS. 11-14.

Referring now to FIGS. 2-4, the core 12 is in the form of a clam shell having a first clam shell portion or half 20 and a second portion or half 22. The core 20 is formed of a suitable, light weight, easily formed material, such as plastic. A plastic useable to form the core 12 maybe polypropylene, by example only.

The first and second core halves 20 and 22 are integrally and pivotally joined together along a living hinge portion or edge 24 extending between one longitudinal edge of each of the core halves 20 and 22.

The core halves 20 and 22 have a substantially mirror image configuration formed of opposed longitudinal edges joined together to form the living hinge 24, outer longitudinal edges 26 and 28, adjacent side edges 30 and 32, and adjacent side edges 34 and 36. The side edges 26 and 28 may optionally be formed as part of a pivotal flap section pivotable about a second living hinge or weakened portion 38 formed adjacent from each side edge 26 and 28.

As shown in FIGS. 1 and 2, an intermediate portion between the side edges 30 and 32 and an intermediate portion 40 between the side edges 30 and 32 of the first and second core halves 20 and 22, respectively, is recessed to form a space for insertion of one support arm 16 or 18 into the core 12. An end portion of the living hinge 24 between the core halves 20 and 22 is formed with an aperture 42 which, when the core 12 is in the closed, fully assembled position shown in FIG. 1, defines an open ended recess adapted for receiving a D-ring 44 for securing one end of the sun visor 10 to a latch member mounted in a vehicle head liner, not shown. The D-ring 44 is mounted in the core 12 by suitable clips, not shown.

The core 12 of the present invention is provided with a unique cover mounting means which insures a quick and secure mounting of the cover 14 on the outer surface of the core 12.

The cover mounting means includes an elongated, elevated cover attachment surfaces 50 and 52 respectively formed in the core halves 20 and 22. Each surface 50 and 52 is formed as one elongated projection extending between the side edges 30 and 34 and the side edges 32 and 36 or in a discontinuous fashion formed of multiple segments or projections. Each surface 50 and 52 terminates in a suitably formed outer mounting surface 54 and 56, respectively. Each

surface 54 and 56 may be planar or have any other shape, such a smoothly curved concave or convex shape.

In the aspect of the surfaces 50 and 52 shown in FIGS. 2 and 3, each surface 50 and 52 has a generally C-shape, formed as a continuous member projecting outward from the main extent or plane of the core halves 20 and 22.

In attaching the cover 14 to the core 12, the core 12 and the cover 14 are juxtaposed as shown in FIG. 2 with cover 14 overlaying an outer surface of the core 12. In this arrangement, the outer peripheral edge of the cover 14 shown by reference number 58 projects outward beyond the periphery of the side edges 30, 32, 34 and 36 of the core 12. The outer peripheral edge 58 of the cover 14 is then folded over a peripheral lip 60 and 62 on each core half 20 and 22 and inward to a position in which the peripheral edge 58 of the cover 14 is in contact with and overlays each of the surfaces 54 and 56 on the surfaces 50 and 52. Sonic waves are then applied to the surfaces 50 and 52 to cause molecular vibration and melting of the surfaces 50 and 52 into the interstices of the cover thereby joining the cover 14 to the core halves 20 and 22, after cooling, in a secure connection or joint which extends substantially continuously about the entire periphery of the core 12.

As shown in FIGS. 2-4, alignment and stability enhancing members 70, 72, 74 and 76 are formed in complimentary positions in the core halves 20 and 22 so as to be disposed in close proximity with an opposed member, with contact also being possible, as shown in FIGS. 3 and 4, when the core halves 20 and 22 are folded into the closed, fully assembled position. The alignment members 70, 72, 74 and 76 may take any shape, with the generally angular, L-shape shown in FIG. 2 by way of example only.

Lock means are provided for securing locking the core halves 20 and 22 in a fully assembled, closed position shown in FIGS. 3 and 4. The lock means comprises a plurality of posts denoted generally by reference number 80 which are formed of a stem 82 and a head 84 having a radially outward extending periphery formed of at least two side arms 86 and 88. Rather than just two side arms 86 and 88, the entire periphery of the head 84 may be enlarged to a greater diameter or cross-section dimension than the diameter or cross-section of the stem 82 so as to provide an enlarged head which overhangs the outer periphery of the stem 82 as shown in FIG. 3. The posts 80 are deployed at a number of locations on one of the core halves 20 and 22, with the post 80 being shown by way of example only as being mounted on the core half 22.

A plurality of lock receivers 90 are formed in the other core half 20. The lock receivers 90 include an outer wall formed of at least two wall portions 92 and 94, with additional wall portions, including a third wall portion and even a fourth wall portion to form walls 92, 94, 95 and 97 as a completely closed, continuous wall may also be employed. Lock members are resiliently mounted on and extend from an end of at least two of the side walls 92 and 94. The lock members all denoted generally by reference number 96 include a leg 98 which terminates in an outer end 100. The legs 98 of the lock members 96 are disposed at an acute angle from the adjacent side wall 92 or 94 such that the outer end 100 is pivotal about the connection between the legs 98 and the adjacent side walls 92 and 94 of each receiver 90. This pivotal movement allows the head 84 of a complementarity positioned lock post 80 on the mating core half 22 to slide through the space normally existing between two adjacent lock legs 98 thereby urging the outer ends 100 outward until the head 84 snaps past the outer ends 100 of

the legs **98**. The legs **98** then snap back toward the nominal position and seat against a shoulder formed between the inner surface of the side arm **86** and **88** of the head **84** and the adjacent outer surface of the stem **82** thereby securely locking the lock post **80** in the receiver **90**. The same locking process occurs across the entire core **12** at every location of a matingly positioned receiver **90** and lock post **80**.

Referring again to FIGS. **1** and **2**, and in greater detail in FIGS. **5** and **6**, the support arm **16** is mounted within the core **12** prior to locking closure of the core halves **20** and **22** as described above. The support arm may take one of two configurations, including the telescoping, long length support arm **16** shown in FIGS. **7** and **8** and the shorter length support arm **18** shown in FIG. **9** for non-telescoping sun visors.

Regardless of the length of the support arm **16** or **18**, the end portion of each support arm **16** or **18** includes at least one and preferably a pair of flats **110** adjacent an outer end **112**, with only the support arm **16** being depicted in FIG. **5** by way of example only. The remainder of the support arm **16** may have a circular cross-section, by example only. A stop flange **114** is spaced from the outer end **112** of the support arm **18** to retain the support arm **18** in a slide carrier **120**. The carrier **120** defines an integral, one piece body, typically of a molded plastic, having a pair of side arms **122** and **124**, each with an aperture **126** and **128**, respectively, the apertures **126** and **128** being coaxially aligned for receiving the end portion of the support arm **18** with the flats **110** disposed between the side arms **122** and **124**.

A first pair of apertures **130** are formed in a central leg **132** of the slider **120**. A second pair of apertures **134** are also formed in the central leg **132** of the slider **120**. The pairs of apertures **130** and **134** receive bent edges **136** and **138** of a spring clip **140** to attach the spring clip **140** to the slider **120**. The spring clip **140** has an enlarged end portion denoted by reference number **142** which receives the end portion of the support arm **16**. A pair of bent portions **144** and **146** on the spring clip **140** resiliently engage the flats **110** on the end of the support arm **18** to exert a biasing force tending to retain the entire sun visor **10** in a fixed position, typically biased in a direction toward the vehicle headliner in a normal, stored sun visor position to minimize buzz, squeaks or rattles. This provides the necessary noise control features for the sun visor **10** of the present invention.

The sun visor **10** has a unique telescoping mount using the slide carrier **120** which may be used by itself or in combination with the heat stake cover attachment described above as well as with or without any of the additional unit features of the sun visor described hereafter.

The slide carrier **120** includes first and second, oppositely directed, open ended channels **150** and **152** which are integrally formed in the carrier **120**. The open end of the channel **150** extends oppositely from the open end of the channel **152**. The channels **150** and **152** are positioned to engage slide rails **154** and **156**, shown in FIGS. **2**, **6**, **7** and **8** which are integrally formed as part of the core halves **20** and **22**, respectively. The slide rails **154** and **156** extend along the length of each core half **20** and **22**, generally in parallel with the hinge **24**.

When the core halves **20** and **22** are locked in the fully assembled, closed position shown in FIG. **6**, the slide rail **154** engages the channel **150** and the opposed slide rail **156** engages the opposite channel **152** in the slider **120**. This dual, opposed slide rail and channel configuration securely retains the slider **120** in a constant orientation during all telescoping movement of the sun visor **10** relative to the

support arm **16** as described hereafter. The addition of the second channel **150** and the slide rail **154** provides added stability to insure a smooth, even bi-directional telescoping movement of the sun visor **10** along the support arm **16** while at the same time securely retaining the sun visor **10** to the support arm **16**.

FIG. **7** depicts the normal, non-telescope position of the sun visor **10** relative to the support arm **16**. In this position, the carrier **120** is disposed adjacent to the D-ring end of the sun visor **10**. When the vehicle occupant desires to laterally extend the position of the sun visor **10** relative to the support arm **16**, the occupant grasps the sun visor **10** and slides the sun visor **10** along the support arm **16** to any position up to a maximum extend position shown in FIG. **8**. In the maximum extended position, the carrier **120** is disposed adjacent to a support arm pivot support or clip **160**. The clip **160**, shown in FIGS. **7**, **8** and **9**, includes a wall integrally formed on one of the core halves, such as the second core half **22** having an aperture **162** for receiving the support arm **16** therethrough. The portion **164** of the wall **160** carrying the aperture **162** is spaced from a collar **166**, also formed on the core half **22**, which defines a generally circular cross-section bore through which the support arm **16** extends.

The sun visor **10** may also be provided with the short length support arm **18** for non-telescoping use without any modifications to the core **12**. By example only, the non-telescoping aspect of the present sun visor **10** also employs the carrier **120**, the support wall **160** and the sleeve **166**. However, the carrier **120** is non-laterally moveably disposed within the wall **160** as shown in FIG. **9**.

Referring now to FIGS. **10**–**14**, there is depicted several aspects of a mirror assembly which may be optionally employed with the sun visor **10** of the present invention. It will be understood that the various aspects of the mirror assembly described hereafter are useable independently or in combination with any of the telescoping, fabric cover mount or core lock means described above.

In one aspect of a mirror assembly shown in FIG. **10**, which preferably applies to all the mirror assemblies described hereafter, a shallow recess **170** is formed in the core half **22** projecting slightly out of the plane of the main extent of the core half **22**. The recess **170** is formed by a wall **172**.

At least one and preferably a plurality of spaced apertures **174** are formed in the wall **172**. Each aperture **174** is alignable with a corresponding lock receiver **90** on the mating core half **20**. Each aperture **174** is positioned to receive a lock post **80**, identical to the lock post **80** described above for locking the core halves **20** and **22** in the fully closed, assembled position, but now provided on a back plate **176** of a frame or mirror support. The lock posts **80** project from the back wall or plate **176** so as to extend through the apertures **174** and the wall **172** and into locking engagement with the mating receiver **90** when the core halves **20** and **22** are pivoted to the fully closed position. This enables the mirror assembly to be fixedly attached to the core **10** at the same time the core halves **20** and **22** are locked in the closed, fully assembled position.

FIGS. **11** and **12** depict an opposite surface of the core half **22** which has the recess **170** formed therein for receiving a mirror assembly **182**. In this aspect of the mirror assembly **182**, the mirror assembly **182** includes a moveable or pivotal cover **184** which is pivotally mounted to a frame **186** formed of a fixed frame member **188** attached to the back plate **176** shown in FIG. **10** and a mirror surround frame **190**, only a portion of which is shown in FIG. **11**. The cover **184** has a

generally planar extent, with depending side walls and a raised edge **192** to permit easy pivotal movement of the cover **184** between open and closed positions shown in FIGS. **12** and **11**, respectively. A hinge **189** is provided between a fixed frame element **188** and the cover **184**.

The mirror assembly **182**, as shown in FIG. **12**, also is provided with an illumination means in the form of one or more lamp means **196** and **198** mounted in the mirror surround frame **190** on at least one and preferably opposed sides of a reflective mirror **200**. The mirror **200** is typically adhesively joined to the back plate **176**. Conductors for conducting power to the light means **196** and **198** located below the bezzles or lenses **202** are routed between the closed core halves **20** and **22** and into an aperture formed in the support arm **16** or **18** whereby the wires exit the sun visor **10** and pass through the vehicle interior, typically through the vehicle A pillar to the accessory power vehicle circuit.

According to a unique aspect of the present invention, the mirror assembly **182** is mounted on the sun visor **10** after the core halves **20** and **22** of the sun visor **10** have been pivoted to the closed, latched position. As shown in FIG. **13**, the lock post **80** may be forced through the fabric cover **14** into the underlying receiver **90** to fixedly mount the mirror assembly **182** to the sun visor **10**. The layer of the cover fabric **14** disposed between the back wall **176** of the mirror assembly **182** and the core half **20** minimizes the generation of buzzes, squeaks and rattles.

It will be understood that the mirror assembly **182** may be provided without the lamp means **196** and **198** and with or without the pivotal cover **184**. Another mirror assembly **210** is depicted in FIG. **14**. In this aspect, the mirror apparatus is formed of a multi-sided frame **212** which surrounds a mirror **214** secured, typically by adhesive, to a back plate, not shown. The back plate can be identical to the back plate **176** so as to carry the lock posts **80** for secure attachment of the mirror assembly **210** to the core half **22** as described above.

As shown in FIG. **15**, the core **10** having the recess **172** formed in one of the core halves for receiving one of the mirror assemblies described above, may also be utilized without any mirror assemble. In this application, a filler member **220** has a peripheral shape complementary to the shape of the recess **170** in the core half **22** and a thickness substantially the same as the depth of the recess **170**.

In use, the filler member **220** is mounted within the recess **170** and covered by the cover **14** which holds the filler member **220** in the recess **170**. Alternately, the filler member **220** may be fixed in the recess **170** by means of adhesive, etc.

The use of the filler member **220** provides a flush surface with the surrounding surface of the core half **22** when a mirror assembly is not used in the sun visor **10**. At the same time, the filler member enables a single core **12** design to be employed with and without a mirror assembly without requiring any modification or additional manufacturing cost.

In summary, there has been disclosed a unique vehicle sun visor having improved fabric cover attachment, easy and reliable telescoping visor movement, the option to switch between a telescoping support arm and a fixed short support

arm without modification to the sun visor core so as to contribute to a reduced manufacturing cost, multiple mirror assembly mounts, unique and reliable core lock members, and a mirror attachment means which controls or minimizes the generation of noise between the contacting parts of the mirror and the sun visor core.

What is claimed is:

1. A sun visor comprising:

a core having first and second foldable halves;

a plurality of receivers mounted on the first core half, each receiver including spaced sidewalls projecting from the first core half, and at least a pair of latch arms, each invertingly angularly extending from an end of one sidewall into a space between the sidewalls;

a plurality of projections carried on the second core half, each projection having a stem extending from the second core half terminating in an enlarged head, the head engagable through the latch arms to fixedly join the projection to the receiver when the first and second core halves are folded over each other to hold the first and second core halves in a folded over, closed position; and

ends of the latch arms snappingly engaging the projection at an edge formed between the head and the stem to resist separation between of the projection from the receiver.

2. The sun visor of claim 1 wherein the head comprises: at least a pair of opposed edges extending radially outward from the stem, the edges engagable with the latch arms to deflect the latch arms away from each other during insertion of the projection between the latch arms.

3. The sun visor of claim 1 wherein:

the latch arms are disposed at an acute angle with respect to the first core half.

4. The sun visor of claim 1 wherein:

the ends of the latch arms are normally spaced apart a distance less than an outer peripheral dimension of the head of the projection.

5. The sun visor of claim 1 further comprising:

means for maintaining the sidewalls in a substantially stationary position.

6. The sun visor of claim 5 wherein the maintaining means comprises:

at least one wall portion connecting the spaced sidewalls to prevent substantial movement of the sidewalls relative to each other.

7. The sun visor of claim 6 wherein the at least one wall portion comprises:

a pair of wall portions interposed between and connected to the sidewalls and forming a continuous wall with the sidewalls.

8. The sun visor of claim 5 wherein:

the latch arms are disposed at an acute angle with respect to the first core half.