



US006741244B1

(12) **United States Patent**
Czuchry, Sr. et al.

(10) **Patent No.:** **US 6,741,244 B1**
(45) **Date of Patent:** **May 25, 2004**

(54) **IMAGE IMPROVEMENT APPARATUS AND METHOD**

6,373,970 B1 4/2002 Dong et al.

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Andrew J. Czuchry, Sr.**, Gray, TN (US); **Andrew J. Czuchry, Jr.**, Auburn, GA (US)

WO WO 02/17646 A1 2/2002

OTHER PUBLICATIONS

(73) Assignee: **Microporous Products, L.P.**, Piney Flats, TN (US)

Philips Research, Technical Information on 3D-LCD, Copyright 2002.

(* Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 44 days.

* cited by examiner

Primary Examiner—Mark Zimmerman

Assistant Examiner—Lance W. Sealey

(74) *Attorney, Agent, or Firm*—Luedeka, Neely & Graham PC

(21) Appl. No.: **10/193,425**

(22) Filed: **Jul. 11, 2002**

(51) **Int. Cl.**⁷ **G06T 15/00**

(52) **U.S. Cl.** **345/419; 345/441**

(58) **Field of Search** 345/419, 441

(57) **ABSTRACT**


A method and apparatus for converting a digital image of one or more objects to interpolated three-dimensional image data for producing substantially realistic three-dimensional images. The method includes providing a digital image file containing digital image pixels, wherein the pixels having a structural contour relationship to the one or more objects. The digital image pixels are converted to contour corrected pixels to provide a contoured image file. An output image file is built from the contoured image file so that the output image file may be projected on an image output device. The method and apparatus provide substantially improved three-dimensional images for viewing on a variety of image output devices.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,128,979 A	2/1915	Hess	
1,918,705 A	7/1933	Ives	
5,099,320 A	3/1992	Allio	
5,828,380 A	* 10/1998	Lin	345/441
6,064,424 A	5/2000	van Berkel et al.	
6,069,650 A	5/2000	Battersby	
6,118,584 A	9/2000	van Berkel et al.	
6,373,963 B1	4/2002	Demers et al.	

15 Claims, 4 Drawing Sheets






Fig. 1

Fig. 2




Fig. 3
Prior Art




Fig. 4




Fig. 5




Fig. 6




Fig. 7

IMAGE IMPROVEMENT APPARATUS AND METHOD

FIELD OF THE INVENTION

The invention relates to apparatus for forming and viewing improved three-dimensional images of objects.

BACKGROUND

Image processing is applicable to a wide variety of applications including entertainment, medical, scientific investigations, and the like. One problem with such image processing is that it often fails to provide realistic three-dimensional images using inexpensive imaging devices such as cathode ray tubes (CRT's), liquid crystal displays (LCD's), lenticular devices, and laser or ink jet printers. In conventional image processing techniques, redundant image information is combined to provide a simulated three-dimensional image suitable for display by a two-dimensional display device. The appearance of depth in such images is provided by combining multiple segments of planar image data. The actual contour of the image is often ignored or severely distorted. Accordingly, the further the segment of image data is from the ideal focal point, the less sharp the image. Many conventional three-dimensional imaging techniques are thus based on combining two or more offset planar images to provide a simulation of depth as perceived by the human eye.

There continues to be a need for a method and apparatus for providing realistic three-dimensional images without the need for elaborate or costly imaging devices. There is also a need for an image processing technique which more closely approximates image perception experienced by the human eye without the need for multiple image input devices.

SUMMARY OF THE INVENTION

In one embodiment, with regard to the foregoing and other needs, the invention provides a method for converting a digital image of one or more objects to interpolated three-dimensional image data for producing a substantially realistic three-dimensional image of the object or objects. The method includes providing a digital image file containing digital image pixels, wherein the pixels have a structural contour relationship to the one or more objects. The digital image pixels are converted to contour corrected pixels to provide a contoured image file. An output image file is built from the contoured image file so that the output image file may be projected on an image output device.

In another embodiment, the invention provides an improved imaging tool. The imaging tool includes:

- an image file input device for receiving one or more image data files;
- a conversion module for converting the one or more image data files to pixelated data having color, depth and positional parameters;
- a positional translation module for incrementally adjusting the pixelated data to provide incremental positional data;
- an image correction module for receiving the color, depth, positional parameters, and incremental positional data for the pixelated data and providing corrected pixels having updated depth and updated position; and
- an output image correlation module for providing corrected pixels to an image output device.

Advantages of the invention include the ability to provide more realistic three-dimensional images of one or more objects on a variety of output devices. The images may be corrected for any desired image resolution. The imaging tool enables closer correlation between the contours of the image and the pixel positions of the image on the output device. For example, conventional three-dimensional imaging techniques provide redundant overlapping planar images to give the perception of depth. However, planar images do not include sufficient contour parameters to provide realistic depth perception of the images. The present invention solves the problem by providing pixel by pixel correction based on pixel position and depth or distance from an ideal focal point to provide image interpolation while substantially decreasing redundant image data points. The method and apparatus of the invention is readily adaptable to a variety of image file formats and can be applied to produce more realistic three-dimensional images from three-dimensional or two-dimensional image data.

BRIEF DESCRIPTION OF THE DRAWINGS

Further advantages of the invention will become apparent by reference to the detailed description when considered in conjunction with the figures, wherein like reference numbers indicate like elements throughout, and wherein:

FIG. 1 is a schematic illustration of how an eye of a person views points on one or more objects;

FIG. 2 is a schematic illustration of how the invention provides pixels in a data file for one or more objects;

FIG. 3 is a schematic illustration of the projection of image data for one or more three-dimensional objects on a planar surface;

FIG. 4 is a schematic illustration of an ideal location of image data for one or more three-dimensional objects with respect to a planar surface provided by the invention;

FIG. 5 is a schematic illustration of a relationship between changes in x and z coordinates of a pixel and angular movement of the pixel of one or more objects as the one or more objects are rotated;

FIG. 6 is a schematic illustration of a method for calculating ideal image data locations for one or more three-dimensional objects to provide a perception of depth on a two dimensional image device; and

FIG. 7 is a block flow diagram of a method for converting image data to realistic three-dimensional image data.

DETAILED DESCRIPTION OF THE INVENTION

The invention provides a manner for simulating how an eye views one or more objects. For the purposes of simplicity, the aspects of the invention will be described with respect to the image of a single object. However, the invention is adaptable to an image or images of multiple objects. In one aspect, simulation is accomplished by combining pixel data from an object in a unique manner. For example, with reference to FIGS. 1 and 2, points 12 and 14 on an object represented by circle 10, may be viewed by an eye 16 of a person starting from an initial position having an initial view angle (θ_0), of zero degrees with respect to reference line C. As the eye 16 of a person moves around the object 10 in a counter-clockwise manner to view point 14, the view angle (θ_v) changes and becomes greater than zero as illustrated by the dotted lines in FIG. 1.

In order to simulate how an eye views an object 10, the invention provides a manner for placing pixels for the object

10 in a data file so as to build an image for the object **10** which simulates how the eye **16** would view such object in a three-dimensional world. According to the invention, as the object **10** is rotated counter-clockwise, as shown by arrow **15**, point **18** representing a pixel moves from position **A** to position **B**. The change in angle with respect to reference line **C** is referred to as the angular velocity (ω_{xz}) of the point **18**. Angular velocity is used to represent the angle because the rate at which the angle changes as the object is rotated is related to the positioning of the pixel relative to an actual point **18** on the object **10**. For highly curved or contoured objects, the rate of change of the angle is greater than for less curved or contoured objects. In order to provide pixel data point placement in a data file so that the reproduced image more closely simulates an actual three-dimensional image, the relationship between the view angle (θ_v) and the angular velocity (ω_{xz}) is provided as described in more detail below.

The differences between conventional imaging techniques and the imaging techniques of the invention using the relationship between the view angle (θ_v) and the angular velocity (ω_{xz}) are described now, in conjunction with FIGS. **3–6**. Using conventional imaging techniques, image data for an object **10** (FIG. **3**) are projected by vectors $V_1, V_2, V_3, V_4,$ and V_5 to a relatively planar or two-dimensional plane **20**. For simplification, only projection of image data in the x direction on plane **20** is illustrated, however, it is understood that the image data has both x and y components for projection on plane **20**. The length of the vectors $V_1, V_2, V_3, V_4,$ and V_5 is equal to the distances the image data representing the object are from the plane **20**. As shown in FIG. **3**, these distances vary for each data point such that (V_1 and V_5) \neq (V_2 and V_4) \neq (V_3). Hence, the positioning of data points on plane **20** in the x direction, represented by $M_1, M_2, M_3, M_4,$ and M_5 , respectively, is offset from an ideal position as discussed with reference to FIG. **4**, thus introducing error into the image data.

Another way of looking at the data for an image is that vector V_3 represents projection of image data to a focal point M_3 . Ideally, all of the image data is projected to corresponding points $M_1, M_2, M_4,$ and M_5 with the same size vectors as vector V_3 . However, in order for the data points to be visible, they must intersect plane **20**. For this to occur, the vectors for the image data $V_1, V_2, V_4,$ and V_5 do not have the same length as vector V_3 . Hence, the data points $M_1, M_2, M_4,$ and M_5 are not in focus when the image file is reproduced in visible form.

The invention provides a unique way to correct the image data so that all of the data points for the image will be substantially more in focus as compared to image data obtained using prior art techniques thereby improving image resolution. With reference to FIG. **4**, the ideal positions for pixels for an image is along an arcuate path **22** corresponding to the contours of an object providing pixel data **24, 26, 28, 30,** and **32**. However, in order to view the image, the pixel data are projected to a two-dimensional plane **20** such as paper or a video screen as described above. In contrast to conventional techniques, pixel data **24, 26, 28, 30,** and **32** lying on the arcuate path **22** are projected to the plane **20** to provide new data points $N_1, N_2, N_3, N_4,$ and N_5 , along the x direction of the two-dimension plane **20**. In this case, vectors $Y_1, Y_2, Y_3, Y_4,$ and Y_5 , representing the distance of the pixel data **24, 26, 28, 30,** and **32** from object **10** along an arcuate path **22** have substantially equal lengths. This results in the projected data points for the pixel data being substantially more in focus than if the pixel data was projected to data points $M_1, M_2, M_4,$ and M_5 .

Because the pixel placement provided by the invention is with respect to an arcuate path **22**, the ideal position for each pixel point placement is shifted by an angle ω_{xz} which represents movement of a pixel point along the arcuate path **22** as the object is rotated as described above with reference to FIG. **2**. The magnitude of the shift in the placement of the projected data point lying on the arcuate path **22** is represented by Δx (FIG. **5**). The distance the pixel points on the arcuate path **22** are from the two-dimensional plane **20** is represented by the term Δz in FIG. **5**. Accordingly, as the object **10** is rotated so that a pixel moves from pixel point **28** to pixel point **30** along the arcuate path **22**, the projected pixel data placement on the two-dimensional plane **20** moves from data point N_3 to data point N_4 as shown in FIG. **4**. The Δx and Δz dimensions for pixel placement are calculated from the angular velocity (ω_{xz}) by the following equations:

$$\cos(\omega_x)=\Delta x/1=\Delta x \quad (I)$$

$$\sin(\omega_z)=\Delta z/1=\Delta z \quad (II)$$

The relationship between the angular velocity (ω_{xz}) and the view angle θ_v may be determined by reference to FIGS. **4** and **6**. The difference between placement positions N_4 and M_4 for pixel point **30** projected to plane **20** is defined as $\delta\Delta x$ and represents an error in pixel positioning in the x direction using a traditional planar approach as compared to pixel placement provided by the invention.

With reference to FIGS. **3, 4,** and **6**, the difference between the length of vectors V_4 and Y_4 is $\delta\Delta z$. $\delta\Delta z$ represents an error in pixel positioning in the z direction. Referring to FIGS. **1** and **6**, the view angle θ_v can be used to determine the magnitude of the error $\delta\Delta z$ between placement of a pixel point on the two-dimensional plane **20** using conventional techniques and placement of a pixel point on the arcuate path **22**. The error $\delta\Delta_z$ and the error $\delta\Delta_x$ are related to the view angle θ_v according to the following equation,

$$\sin(\theta_v)=\delta\Delta x/(\delta\Delta z). \quad (III)$$

for each view angle used. For each incremental view angle ($\Delta\theta_v$) selected, the relative view angle (θ_v) is provided by the following equation:

$$\theta_v=n*\Delta\theta_v \quad (IV)$$

wherein n is the number of incremental view angles comprising the total view angle (θ_v).

By using data points **24, 26, 28, 30,** and **32** on arcuate path **22**, each of the vectors $Y_1 \dots Y_n$ have the same length. Hence, the errors $\delta\Delta x$ and $\delta\Delta z$ may be calculated from the formulas:

$$\delta\Delta x=\cos(\omega_{xz})*Y_n \text{ and} \quad (V)$$

$$\delta\Delta z=\sin(\omega_{xz})*Y_n. \quad (VI)$$

The foregoing relationships are used by the apparatus of the invention to build one or more objects from image data for the one or more objects. Accordingly, pixel data for the object or objects are modified for placement in a data file as described in more detail below. Each of the pixels P for the image have coordinates (i,j). The x and z positions for each pixel P_{ij} of the image generated by the invention are provided by the following equations:

$$x_v=i+\cos(n*\omega_{xij})*d_{ij} \text{ and} \quad (VII)$$

$$z_v=j+\sin(n*\omega_{zij})*d_{ij}, \quad (VIII)$$

wherein x_v and z_v are the x and z positions on the arcuate path **22** for pixels P_{ij} , n is number of incremental view angles selected, ω_{xij} and ω_{zij} are angular velocities for each pixel P_{ij} as the object is rotated, and d_{ij} is a depth shift factor in the z direction for each pixel relative to arcuate path **22** and plane **20**.

Starting at a view angle of zero degrees and rotating the object relative to an initial starting position to simulate changes in the view angle as described with reference to FIGS. **1** and **2** above, the x and z coordinates are given by the following equations:

$$x_v = x_0 + \cos(\omega_{x\theta v}) * d_{ij} \quad \text{(IX)}$$

$$z_v = z_0 + \sin(\omega_{z\theta v}) * d_{ij} \quad \text{(X)}$$

The Δx and Δz values are calculated by the following equations:

$$\Delta x_v = x_0 + \cos(\omega_{x\Delta\theta v}) * d_{ij} \quad \text{(XI)}$$

$$\Delta z_v = z_0 + \sin(\omega_{z\Delta\theta v}) * d_{ij}, \quad \text{(XII)}$$

wherein x_0 and z_0 are the coordinates for pixels lying on planar surface **20** at a relative view angle of zero degrees ($\theta_v = 0$). In the general case, the x and z coordinates for all pixels is given by the following equations:

$$x_v = i + \cos(n * \omega_{xij}) * d_{ij} \quad \text{(XIII)}$$

$$z_v = j + \sin(n * \omega_{zij}) * d_{ij}, \quad \text{(XIV)}$$

wherein ω_{xij} and ω_{zij} are the angles for pixel placement on plane **20** using the ideal positions of the pixels on arcuate path **22**.

Hence, the invention tends to capture the smooth flow of image pixels projected from arcuate path **22** to plane **20**. Accuracy of placement of the pixels on plane **20** can be improved by selecting smaller and smaller view angles θ_v , or an increased number of incremental view angles up to a practical limit of view angles. However, the processing time for pixel positioning is increased as the view angle size is decreased or number of incremental view angles is increased.

By using the above techniques, the invention provides a method and apparatus for manipulating image data from an image file to provide ideal locations for the pixel data on a two-dimensional viewing surface. Such pixel data are observed to be more in focus and thereby provide more realistic three-dimensional images. This improvement is believed to result primarily from a reduction of errors in pixel placement in the x and z directions.

Since the functions used by the invention are regular functions, i.e., (cos) and (sin), the Δx and Δz values do not have to have discrete values to provide pixel positioning data. Furthermore, the calculations can generally be performed on any pixel data provided in a wide variety of file formats to provide improved output resolution. A process **100** for application of the invention to an image data file to provide an improved three-dimensional image is provided in FIG. **7**.

Referring to the process **100**, an image **106** of one or more objects is captured and converted to an image data file **108**. Images may be captured by cameras or other input devices which provide image data in a wide variety of image data formats. The image **106** may be a two-dimensional or a three-dimensional image. For a two-dimensional image, additional depth simulation data may be manually inserted into the image data file **108** or interpolated from a series of image data files. Because the image data may be provided in

a variety of file formats, the image data file **108** is input to an image conversion tool **110** which converts the image data file **108** into a useable format for the invention. Image formats which are compatible with the system **100** include, but are not limited to jpeg, tiff, bmp, pcx, png, and the like. The image conversion tool **110** provides parameters for each pixel of data. The parameters provided by tool **110** include color **112**, depth/distance **114** from the object to a focal plane, and pixel position **116** relative to the object and to other pixels representing the object.

The color **112**, depth/distance **114** and position **116** data is then input to an image correction module **118**. The depth **114** and/or position **116** data input to the image correction module **118** are modified in the image correction module **118** based on the output from positional translation tool **120**. Positional translation tool **120** calculates the pixel positions using the above equations I to XIV, particularly equation IV to determining the number of incremental view angles for the object or objects in the image. Next, equations XI and XII are used by positional translation tool **120** to provide Δx and Δz , respectively for each pixel. Image correction module **118** integrates the positional translation data calculated by positional translation tool **120** to provide pixel position adjustments for each pixel in the image. More particularly, the pixel position adjustments calculated by equations XI and XII are used in equations XIII and XIV by module **118** to provide the x and z coordinates for each pixel in the pixel data file for the image. The output from the image correction module **118** includes updated depth **122** and updated position **124** parameters for each pixel.

The updated depth **122** and updated position **124** parameters and a desired output resolution **126** are then input into a image contour building tool **128** which actually builds image contours based on the updated image data provided by correction module **118**. Tool **128** combines the color component of each pixel to provide image contours by mapping the updated depth **122** and updated position **124** with the desired output resolution **126** for each given depth. The mapping is conducted pixel by pixel, i.e., the color is assigned for each output pixel's Δx and Δz adjustment. Higher desired output resolution **126** provides for finer levels of visual distinction for each Δx and Δz adjustment, whereas, lower resolution output **126** results in visually combining Δx and Δz adjustments to provide effectively the same pixel positions. Hence, the image contours achieved by tool **128** provide pixel by pixel placement for the improved three-dimensional image based on the resolution **126** desired using the placement of pixel data along arcuate path **22**, as set forth above.

After the image is built up, pixel by pixel, an image correlation module **130** correlates the improved image to a particular media. The correlation of the improved image is media dependent and thus the output from module **130** is highly dependant on the media selection **132** which is input to the module. The invention may be applied to a wide variety of media, hence, the media may be selected from planar print media, lenticular viewing systems, electronic media, and the like. Likewise, the image output module **134** provides an image **136** which is highly dependent on the media selected for the image.

Having described various aspects and embodiments of the invention and several advantages thereof, it will be recognized by those of ordinary skills that the invention is susceptible to various modifications, substitutions and revisions within the spirit and scope of the appended claims.

What is claimed is:

1. A method for converting a digital image of one or more objects to interpolated three-dimensional image data for

7

producing substantially realistic three-dimensional image of the object or objects, comprising the steps of:

providing a digital image file containing digital image pixels, the pixels having a structural contour relationship to the one or more objects;

converting the digital image pixels to contour corrected pixels relative to view angles external to the one or more objects to provide a contoured image file;

building an output image file from the contoured image file; and

projecting the output image file on an image output device.

2. The method of claim 1 wherein the digital image file comprises pixels having color, depth and positional components.

3. The method of claim 1 wherein the contour corrected pixels comprise color, corrected depth, and pixel path components.

4. The method of claim 3 wherein the output image comprises pixels having x and z coordinates, further comprising providing the x and z coordinates of the pixels in the output image as a function of the corrected depth and pixel path components.

5. The method of claim 1 further comprising selecting an image resolution for the output image file as an input parameter for the step of building the output image file.

6. An imaging tool comprising:

an image file input device for receiving one or more image data files;

a conversion module for converting the one or more image data files to pixelated data having color, depth and positional parameters;

a positional translation module for incrementally adjusting the pixelated data to provide incremental positional data;

8

an image correction module for receiving color, depth, positional parameters, and incremental positional data for the pixelated data and providing corrected pixels having updated depth and updated position information; and

an output image correlation module for providing corrected pixels to an image output device.

7. The imaging tool of claim 6 wherein the image input device is adapted to receive multiple image data file types.

8. The imaging tool of claim 6 wherein the image correction module comprises a depth conversion module for providing updated depth and updated positional parameters for the pixelated data.

9. The imaging tool of claim 8 wherein the image correction module further comprises a density filter module for building the output image from the corrected pixels having updated depth and updated position.

10. The imaging tool of claim 6 wherein the output image correlation module comprises an image projection module for building an output image suitable for the image output device.

11. The imaging tool of claim 6 further comprising an output image file module for converting the output image to a master image file.

12. A machine-readable software program containing the imaging tool of claim 11.

13. A machine-readable software program containing the imaging tool of claim 6.

14. A computer system comprising the machine-readable software program of claim 13.

15. A computer system comprising the imaging tool of claim 6.

* * * * *