

US006762746B2

(12) **United States Patent**
Fukuda

(10) **Patent No.:** **US 6,762,746 B2**
(45) **Date of Patent:** **Jul. 13, 2004**

(54) **ENTERTAINMENT APPARATUS, STORAGE MEDIUM AND OPERATION METHOD OF MANIPULATING OBJECT**

6,425,826 B1 7/2002 Nakanishi et al.
2001/0035906 A1 11/2001 Fukuda
2002/0021298 A1 2/2002 Fukuda
2002/0068628 A1 6/2002 Takatsuka et al.

(75) Inventor: **Izumi Fukuda**, Oomura (JP)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Sony Computer Entertainment Inc.**, Tokyo (JP)

JP 5-32237 4/1993
JP 6-190152 7/1994
JP 11-047449 A 2/1999
JP 11-342265 12/1999

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 148 days.

OTHER PUBLICATIONS

(21) Appl. No.: **09/765,871**

Nintendo, "Instruction Booklet", Star Fox 64, Jul. 1, 1997, pp. 1-5, XP-002267695, http://www.world-of-nintendo.com/manuals/nintendo_64/star_fox_64.shtml.

(22) Filed: **Jan. 19, 2001**

Nintendo, "Star Fox 64", Game Legacy, retrieved from internet Jan. 21, 2004, Jun. 1, 1997, 2 pages, XP-002267697, <http://www.nintendo.com/gamesini?gameid=m-Game-0000-242>.

(65) **Prior Publication Data**

US 2001/0020934 A1 Sep. 13, 2001

European Patent Office, "European Search Report", dated Feb. 27 2004, for Application No. 01101286.1-1241, 3 pages.

(30) **Foreign Application Priority Data**

Jan. 21, 2000 (JP) 2000-012811

Japanese Patent Office; Japanese "Notification of Reasons for Refusal"; Dispatch Date Sep. 10, 2002; pp. 1-4; English translation included.

(51) **Int. Cl.**⁷ **G09G 5/00**

(52) **U.S. Cl.** **345/156; 463/37; 463/38**

(58) **Field of Search** 345/156, 157, 345/159, 161, 170; 273/148 R; 463/37, 38, 47

* cited by examiner

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,820,462 A * 10/1998 Yokoi et al. 463/37
5,850,352 A 12/1998 Moezzi et al.
5,883,690 A * 3/1999 Meyers et al. 345/161
6,001,014 A * 12/1999 Ogata et al. 463/37
6,040,841 A 3/2000 Cohen et al.
6,072,504 A 6/2000 Segen
6,097,394 A 8/2000 Levoy et al.
6,231,444 B1 * 5/2001 Goto et al. 463/37
6,241,611 B1 * 6/2001 Takeda et al. 463/38
6,325,717 B1 12/2001 Kawagoe et al.
6,330,356 B1 12/2001 Sundareswaran et al.
6,332,840 B1 * 12/2001 Nishiumi et al. 463/38
6,342,009 B1 * 1/2002 Soma 463/38
6,402,616 B1 * 6/2002 Ogata et al. 463/37
6,409,601 B2 * 6/2002 Ogata et al. 463/37
6,421,056 B1 * 7/2002 Nishiumi et al. 345/474

Primary Examiner—Regina Liang

Assistant Examiner—Jennifer T. Nguyen

(74) *Attorney, Agent, or Firm*—Fitch, Even, Tabin & Flannery

(57) **ABSTRACT**

Disclosed is an entertainment apparatus in which even an unskilled player can enjoy a flight simulation, a drive simulation or the like satisfactorily. Based on a signal depending on coordinate values on X-Y coordinate decided by a manipulation applied to manipulation sticks **31a** and **32a**, the signal being outputted from the controller **20**, a moving direction of a controlled object **601** is determined. When the coordinate value is within specified ranges, the moving direction of the object **601** is determined so that the object **601** is allowed to make a sharp turn flight.

8 Claims, 14 Drawing Sheets




FIG. 1




FIG.2




FIG. 3




FIG.4




FIG.5

OPTICAL DISK 85




FIG.6




FIG. 7




FIG. 8





FIG. 9




FIG. 10




FIG. 11




FIG.12A




FIG.12B




FIG.12C




FIG.12D




FIG.12E




FIG. 13A




FIG. 13B




FIG. 13C





FIG. 14



ENTERTAINMENT APPARATUS, STORAGE MEDIUM AND OPERATION METHOD OF MANIPULATING OBJECT

This application claims a priority based on Japanese Patent Application No. 2000-12811 filed on Jan. 21, 2000, the entire contents of which are incorporated herein by reference for all purposes.

BACKGROUND OF INVENTION

The present invention relates to a technology to control a movement of an object in a virtual field displayed on a display device according to manipulation contents of a manipulator, which are received via a controller having manipulation sticks such as joysticks.

In recent years, an entertainment apparatus such as a TV game machine has been spread, which is capable of performing a flight simulation, a drive simulation or the like by the use of a three dimensional graphic animation.

In this kind of entertainment apparatus, the manipulator (player) uses a controller such as an analog joystick or a game controller having the manipulation sticks and manipulation buttons, and controls an object that represents an airplane, an automobile or the like. Thus, the manipulator can move the object in a virtual three dimensional field. The entertainment apparatus generates a moving picture obtained by photographing the object, which moves in the three dimensional field, by the use of a virtual camera, and displays the moving picture on a display screen of a display device connected to the entertainment apparatus.

In this kind of entertainment apparatus, a posture and a moving direction of the object moving in the virtual three dimensional field have heretofore been controlled according to the manipulation contents applied to the manipulation sticks of the controller. For example, in a flight simulation, the manipulation sticks are made to possess the same function as that of a control stick, and a bank of an airplane, and rise and drop of a nose of the airplane, which is represented by the object, are determined by manipulation applied to the manipulation sticks. Moreover, in the drive simulation, the manipulation sticks are made to possess the same function as that of a steering wheel, and a tire direction of an automobile, which is represented by the object, is determined by manipulation applied to the manipulation sticks.

SUMMARY OF THE INVENTION

Incidentally, in the actual world, an extremely high control technique is required for a motion to allow an airplane to shift to a complete circular flight by the use of a control stick or a motion to allow an automobile to make a sharp turn by the use of a steering wheel. For this reason, if the manipulation sticks of the controller are merely allowed to possess the same function as that of the manipulation stick similarly to a conventional entertainment apparatus, an operation of a controlled object becomes extremely difficult, and an unskilled player might not be able to enjoy the flight simulation, the drive simulation or the like satisfactorily.

Accordingly, the objective of the present invention is to make it possible for even the unskilled player to enjoy the flight simulation, the drive simulation or the like satisfactorily.

To achieve the foregoing objective, in the present invention, in an entertainment apparatus which displays an object (object representing, for example, an airplane or an

automobile) moving in a virtual field on a display device according to manipulation contents of a player, the manipulation contents being received via a controller having a manipulation stick, which is constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis passing through the specified fulcrum, a moving direction of the object is determined based on a signal in accordance with coordinate values on X-Y coordinate decided depending on a tilt direction and tilt angle of the manipulation stick relative to the specified axis of the manipulation stick, the signal being outputted from the controller, and when the coordinate value is within specified ranges, it is judged that the object is made to perform a specific motion, and the motion of the object in the virtual field is controlled.

For example, in the case where the entertainment apparatus is the one that displays on a display screen of a display device a moving picture obtained by photographing an object representing an airplane, which moves in the virtual three dimensional field according to the manipulation contents of the player received via the controller, by the use of a virtual camera, manipulation content reception means determines the moving direction of the object, (bank of the airplane and rise and drop of a nose of the airplane represented by the object) based on a signal according to coordinate values on X-Y coordinate, the signal being outputted from the controller, and when the coordinate values are within specified ranges, it is judged that the object is made to perform a specified motion (motion considered to be difficult for a player to operate in the actual world, for example, a sharp turn flight), and the moving direction of the object is determined so that the object can perform the specific motion.

With such constitution, it is possible to allow even an unskilled player to make the object perform a motion considered to be difficult to operate in the actual world with a relatively easy manipulation to the manipulation stick. Accordingly, even the unskilled player can enjoy the flight simulation, the drive simulation or the like satisfactorily, thus improving entertainingness.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 exemplifies an appearance of an entertainment apparatus **1** and a controller **20** to which an embodiment of the present invention is applied.

FIG. 2 is a perspective view showing the controller **20** in FIG. 1.

FIG. 3 is a diagram for explaining values that can be entered into the entertainment apparatus **1** by the use of manipulation sticks **31a** and **31b** of the controller **20** shown in FIG. 2.

FIG. 4 is a block diagram exemplifying a hardware structure of the entertainment apparatus **1** shown in FIG. 1.

FIG. 5 is a block diagram for explaining a data structure of an optical disk **85** inserted in a disk inserting portion **3** of the entertainment apparatus **1**.

FIG. 6 is a block diagram showing a software structure for realizing a flight simulation game, which is constructed on the entertainment apparatus **1** shown in FIG. 4.

FIG. 7 is an explanatory view for explaining a positional relation between an object **601** to be controlled (herein after referred to as a controlled object) and a virtual camera **609** disposed in a three dimensional field by a camera disposing section **805** shown in FIG. 6.

FIG. 8 is an explanatory view for explaining a positional relation between the controlled object **601** and the virtual

camera **609** disposed in the three dimensional field by the camera disposing section **805** shown in FIG. 6.

FIG. 9 is an explanatory view for explaining positional relation between the controlled object **601** and the virtual camera **609** disposed in the three dimensional field by the camera disposing section **805** shown in FIG. 6.

FIG. 10 is an explanatory view for explaining how the virtual camera **609**, which is disposed in the three dimensional field by the camera disposing section **805** shown in FIG. 6, behaves for a motion of the controlled object **601**.

FIG. 11 is an explanatory view for explaining how the virtual camera **609**, which is disposed in the three dimensional field by the camera disposing section **805** shown in FIG. 6, behaves for a motion of the controlled object **601**.

FIGS. 12A to 12E show examples of pictorial images obtained by photographing the controlled object **601** with the virtual camera **609** disposed as shown in FIG. 10.

FIGS. 13A to 13C show examples of pictorial images obtained by photographing the controlled object **601** with the virtual camera **609** disposed as shown in FIG. 11.

FIG. 14 is a flowchart for explaining an operation of a software structure to realize a flight simulation constructed on the entertainment apparatus **1** of FIG. 11.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the present invention will be hereinafter described.

A hardware structure of an entertainment apparatus according to an embodiment of the present invention will be described.

An appearance of the entertainment apparatus according to the embodiment of the present invention will be described in FIG. 1.

This entertainment apparatus reads out a game program stored in an optical disc and the like such as CD-ROMs and DVD-ROMs, and executes a game in response to an instruction from a player. An execution of the game mainly means that a controlled object such as an object representing, for example, an airplane and an automobile, which is being displayed on a display screen of a display device such as a TV connected to the entertainment apparatus, is allowed to move, and a display of a moving picture and sound are controlled in accordance with a motion of the object in response to an instruction from a player, thus proceeding the game.

As illustrated in FIG. 1, a main body **2** of the entertainment apparatus **1** comprises a disc inserting portion **3**, in the center of which an optical disc such as a CD-ROM and a DVD-ROM is inserted that are a recording medium for supplying an application program of a TV game and the like and multimedia data; a reset switch **4** for resetting the game; a power switch **5**; a disc manipulation switch **6** for manipulating an insertion of the optical disc; and, for example, two slot portions **7A** and **7B**.

Two controllers **20** can be connected to the slot portions **7A** and **7B**, and two players can perform a match game, a competition game and the like. The slot portions **7A** and **7B** can be equipped with a memory card device **26** that can store and read out game data, and a portable electronic appliance **100** that can execute the game in a state where it is detached from the main body **2**.

The controller **20** has first and second manipulation portions **21** and **22**, an L button **23L**, an R button **23R**, a start button **24** and a selection button **25**. A controller **20** further

has analog manipulation portions **31** and **32**, a mode selection switch **33** for selecting a manipulation mode of the manipulation portions **31** and **32**, and a display portion **34** for displaying the selected manipulation mode.

The respective manipulation portions **31** and **32** have manipulation sticks **31a** and **32a**, each of which is constituted so as to be pivotally tilted and to be rotatable in the tilted state using a specified fulcrum "a" relative to a specified axis "b" passing through the fulcrum "a", as shown in FIG. 2. The controller **20** detects a tilt of each of the manipulation sticks **31a** and **32a** relative to the axis "b" and a tilt direction thereof, and then outputs a signal in accordance with coordinate values on the X-Y coordinate decided based on the tilt and the tilt direction. As shown in FIG. 3, the coordinate value in the Y-direction (vertical) is represented by one of 256 stages ranging from "0" to "255" depending on the tilts of the manipulation sticks **31a** and **32a** in the upward and downward direction, and the coordinate value in the X-direction (horizontal) is represented by one of 256 stages ranging from "0" to "255" depending on the tilts of the manipulation sticks **31a** and **32a** in the right and left direction.

Next, a constitution of the entertainment apparatus **1** is shown in FIG. 4.

As shown in FIG. 4, the entertainment apparatus **1** comprises: a control system **50** including a central processing unit (CPU) **51**, peripheral units and the like; a graphic system **60** including a graphic processing unit (GPU) **62** allowing a frame buffer **63** to carry out drawing thereon, and the like; a sound system **70** including a sound processing unit (SPU) **71** generating an audio signal such as a musical sound and an effect sound, and the like; an optical disc control section **80** for controlling an optical disc on which an application program and multimedia data are stored; a communication control section **90** for controlling input/output of a signal from the controller **20** to which an instruction from the player is inputted and for controlling input/output of data from a portable electronic appliance **100** and a memory card **26** storing a setting of a game; a bus **BUS** connected to the above described sections and systems; and the like.

The control system **50** comprises the CPU **51**; a peripheral unit control section **52** for performing an interruption control and direct memory access (DMA) transfer control; a main memory **53** comprising a random access memory (RAM); and a read only memory (ROM) **54** storing a program such as so called an operating system, which controls the main memory **53**, the graphic system **60**, the sound system **70** and the like.

The CPU **51** executes the operating system stored in the ROM **54**, thus controlling the whole of the entertainment apparatus **1**, and the CPU **51** is composed of, for example, a RISC-CPU.

In the entertainment apparatus **1**, upon turning on a power, the CPU **51** of the control system **50** executes the operating system stored in the ROM **54**. Thus, the CPU **51** controls the graphic system **60**, the sound system **70** and the like.

When the operating system is executed, the CPU **51** performs an initialization such as an operation confirmation for the whole of the entertainment apparatus **1**. Thereafter, the CPU **51** controls the optical disc control section **80**, and executes an application program such as a game stored on the optical disc. By executing the program of the game, the CPU **51** controls the graphic system **60**, the sound system **70** and the like in response to an input from the player, and controls an image display and generation of the effect sound and the musical sound.

The graphic system **60** comprises a geometry transfer engine (GTE) **61** for performing a processing of a coordinate transformation and the like; the GPU **62** for carrying out the drawing in accordance with an instruction for the drawing from the CPU **51**; the frame buffer **63** for storing an image drawn by the GPU **62**; and an image decoder **64** for decoding image data, which has been compressed by an orthogonal transformation such as a discrete cosine transform and then coded.

The GTE **61** comprises a parallel operation mechanism for executing a plurality of operations parallelly, and performs calculations of a matrix, a vector and the like such as the coordinate transformation. To be concrete, the GTE **61** constitutes a virtual three dimensional object by gathering triangular polygons when an application program such as a game, stored in an optical disc, uses so called a 3D graphic. Then, the GTE **61** performs various calculations for generating an image obtained by photographing the three dimensional object with a virtual camera. Specifically, the various calculations include a perspective transformation (a calculation of the coordinate value when vertexes of the polygons constituting the three dimensional object are projected onto a virtual camera screen), which is adopted in performing rendering.

Next, the GPU **62** performs rendering of the three dimensional object for the frame buffer **63** in response to an instruction from the CPU **51** while using the GTE **61** if necessary, and then forms an image. Subsequently, the GPU **62** outputs a video signal representing the image formed. As a technique of erasing shadow lines and shadow planes used for rendering, a Z buffer method, a scan line method, a ray tracing method and the like are employed. As a shading technique for shading, a flat shading method, a glow shading method, a ray tracing method and the like are employed. As a technique for expressing a surface material and pattern of the three dimensional object, a texture mapping and the like are employed.

The frame buffer **63** is composed of, so called a dual port RAM, and constituted so as to be able to simultaneously perform rendering of the GPU **62**, or a transfer from the main memory and reading-out for a display. In the frame buffer **63**, in addition to an image area in which the rendering and the reading-out for a display are performed, a texture area in which a texture used for the texture mapping is stored is provided.

The CPU **51** controls the image decoder **64** so that the image decoder **64** decodes image data of either a still picture or a moving picture, which is stored in the main memory **53**, and allows the main memory **53** to store the decoded image data. The decoded image data is stored in the frame buffer **63** via the GPU **62**, whereby the decoded image data is used as a background of an image to be subjected to the rendering by the foregoing GPU **62**.

The sound system **70** comprises the SPU **71** for outputting an audio signal such as a musical sound and an effect sound based on an instruction from the CPU **51** and a sound buffer **72** in which waveform data and the like is stored by the SPU **71**.

The SPU **71** comprises: an ADPCM decoding function to reproduce sound data that has been subjected to adaptive differential PCM (ADPCM); a reproduction function to reproduce an audio signal such as the effect sound and output the audio signal, by reproducing the waveform data stored in the sound buffer **72**; and a modulation function to modulate the waveform data stored in the sound buffer **72**, thus reproducing the modulated waveform data. With the

provision of such functions, the sound system **70** is constituted so as to be used as so called a sampling sound source that generates an audio signal such as the musical sound and the effect sound based on the waveform data which is stored in the sound buffer **72** in response to an instruction from the CPU **51**.

The optical disc control section **80** comprises: an optical disc device **81** for reproducing a program, data and the like stored in the optical disc; a decoder **82** for decoding a program, data and the like to which, for example, an error correction code (ECC) is added, stored in the optical disc; and a buffer **83** for making reading-out of the data from the optical disc faster by temporarily storing the data from the optical disc device **81**. A sub CPU **84** is connected to the decoder **82**.

As the sound data stored in the optical disc, which is read out by the optical disc device **81**, there is so called PCM data obtained by an A/D conversion of the audio signal in addition to the foregoing ADPCM data. The ADPCM data is decoded by the decoder **82**, and then supplied to the foregoing SPU **71**. The ADPCM data is subjected to a D/A conversion by the SPU **71**, and then outputted as the musical sound, the effect sound and the like from a sound apparatus such as an audio device connected to the entertainment apparatus **1**. Furthermore, the PCM data is subjected to a processing such as a D/A conversion and the like by the SPU **71**, and then outputted as the musical sound, the effect sound and the like from the sound apparatus.

The communication control section **90** comprises a communication controlling device **91** to control a communication with the CPU **51** through the bus BUS. In the communication controlling device **91**, provided are: a controller connection portion **12** connected to the controller **20** for entering an instruction from the player; and memory card insertion portions **8A** and **8B** connected to the memory card **26** as an auxiliary memory device for storing game setting data and the like and the portable electronic appliance **100**.

In order to enter the instruction from the player, the controller **20** connected to the controller connection portion **12** transmits states of the foregoing buttons and the manipulation portion to the communication controlling device **91** by a synchronous communication, in response to an instruction from the communication controlling device **91**. Then, the communication controlling device **91** transmits the states of the foregoing buttons and the manipulation portion of the controller **20** to the CPU **51**.

Thus, the instruction from the player is entered to the CPU **51**, and the CPU **51** executes processings in accordance with the instruction from the player based on a game program that is being executed. To be concrete, the CPU **51** generates an image including a controlled object in cooperation with other portions of the control system **70** and the graphic system **60**, and allows the display screen of the display device to display the image. In accordance with the instruction from the player, which was entered to the controller **20**, the CPU **51** sequentially generates images in which a display position of the controlled object and a posture thereof are changed, and allows the display screen of the display device to display these images. Note that a background of the image is also changed if necessary. Thus, the CPU **51** generates a moving picture as if the controlled object is controlled in response to the manipulation contents of the player entered to the controller **20**. In addition, the CPU **51** controls a sound and music output from the sound apparatus in cooperation with the sound system **70** if needs arise.

Hereupon, the image data must be transferred at high speed among the main memory **53**, the GPU **62**, the image

decoder 64 and the decoder 82 when reading-out of the program, the display of the image and the drawing are carried out. Accordingly, in the entertainment apparatus 1, so called a DMA transfer can be performed, in which data is directly transferred among the main memory 53, the GPU 62, the image decoder 64 and the decoder 82 by a control of the peripheral unit control section 52 without intervention of the CPU 51 as described above. Thus, a load of the CPU 51 due to the data transfer can be reduced, and a high speed data transfer can be performed.

Furthermore, when the setting data of the game that is being executed must be stored, the CPU 51 transfers the data to be stored to the communication controlling device 91, and the communication controlling device 91 writes the data from the CPU 51 in the memory card 26 or the portable electronic appliance 100, which are inserted in the slot of either the memory card insertion portion 8A or the memory card insertion portion 8B.

Here, a protection circuit for preventing electrical destruction is incorporated in the communication controlling device 91. The memory card 26 and the portable electronic appliance 100 are separated from the bus BUS, and freely removable from the main body 2 in a state where the power is being supplied to the main body 2 of the entertainment apparatus 1. Accordingly, when the memory card 26 and the portable electronic appliance 100 lack in storage capacity, a new memory card, etc., can be inserted without breaking the power of the apparatus body. Thus, a new memory card is inserted and new data can be written therein, so that game data that must be backed up is never lost.

Note that a parallel I/O interface (PIO) 96 and a serial I/O interface (SIO) 97 serve as an interface for connecting the entertainment apparatus 1 to the memory card 26 or the portable electronic appliance 100.

The hardware structure of the entertainment apparatus 1 was described in the above.

Next, a flight simulation game will be described, which is realized in such a manner that in the entertainment apparatus 1 constituted as described above, the CPU 51 executes an application program read out from an optical disc inserted in the disc inserting portion 3.

The flight simulation game means a game executed in the following manner. By the use of the controller 20 connected to the entertainment apparatus 1, a player controls the controlled object, which represents an airplane, to allow the controlled object to move in the virtual three dimensional field, and thus the player can experience an operation of the airplane virtually. The entertainment apparatus 1 generates a CG animation image obtained by photographing the controlled object moving in the three dimensional field with the virtual camera, and displays the CG animation image on the display screen of the display device connected to the entertainment apparatus 1.

A data structure of the optical disc will be first described.

FIG. 5 is a block diagram for explaining the data structure of the optical disk 85 inserted in the disk inserting portion 3.

As shown in FIG. 5, an application program (PG) 501 for realizing a flight simulation game, and various kinds of data including object data (DA) 502 and a map database (DB) 503 are stored in the optical disc 85.

In the object data DA 502, stored is a variety of information necessary for specifying a three dimensional shape and a texture, etc., of the controlled object, which represents an airplane and which is controlled by the use of the controller 20 by the player in the flight simulation game. In

the map database DB503, stored is a variety of information concerning map constituent elements for specifying topography in the virtual three dimensional field in the flight simulation game, in which the controlled object moves.

Next, a software structure for realizing the flight simulation game, which is constructed on the entertainment apparatus 1, will be described.

FIG. 6 is a block diagram showing the software structure for realizing the flight simulation game, which is constructed on the entertainment apparatus 1. Constituent elements shown in FIG. 6 are realized as processes in such a manner that the CPU 51 executes the application PG 501 read out by the optical disc control section 50 from the optical disc 85 which is inserted in the disc inserting portion 3 and which is loaded on the main memory 53.

In FIG. 6, a manipulation content reception section 801 determines a moving speed of the controlled object and a moving direction thereof, which moves in the three dimensional field, in response to the instruction of the player entered in the controller 20. This processing is performed periodically.

Here, the moving speed of the controlled object is determined by allowing any one of the first and second manipulation portions 21 and 22, and the L button 23L, and the R button 23R of the controller 20 to possess a same function as that of a throttle.

Specifically, when a detection signal of the button possessing the same function as that of the throttle is being outputted from the manipulation apparatus 20, it is judged that the throttle is in the on-state. When the detection signal of the button is not being outputted, it is decided that the throttle is in the off-state. When it is judged that the throttle is in the on-state, a certain speed is added to the moving speed of the controlled object determined the last time, whereby the moving speed of the controlled object is determined. The certain speed is obtained from a predetermined acceleration in response to the throttle-on-state and from duration time after the moving speed was determined last time. For the duration, the throttle is in the on-state. On the other hand, when it is decided that the throttle is in the off-state, another certain speed is subtracted from the moving speed of the controlled object determined last time, whereby the moving speed of the controlled object is determined. Another certain speed is obtained from a predetermined deceleration in response to the throttle-off-state and from the duration time after the moving speed was determined last time. For the duration, the throttle is in the off-state.

Furthermore, the moving direction of the controlled object is determined, for example, by allowing the manipulation sticks 31a and 32a of the controller 20 to possess a same function as that of a control stick.

Specifically, by the manipulation performed for the manipulation sticks 31a and 32a, a bank of the airplane represented by the controlled object is determined depending on a value of the X coordinate component obtained from a signal, which corresponds to the coordinate value on the X-Y coordinate, the signal being outputted from the controller 20. A rise and drop of the nose of the airplane is determined depending on a value of the Y-coordinate component obtained therefrom.

To be concrete, in FIG. 3, when the value of the X-coordinate component ranges from 128 to 255, the airplane shall tilt greatly to the right as the value of the coordinate component is larger. When the value of the X-coordinate component ranges from 0 to 126, the airplane

shall tilt greatly to the left as the value of the coordinate component is smaller. When the value of the X-coordinate component is equal to 127, the airplane shall not bank. Furthermore, when the value of the Y-coordinate component ranges from 128 to 255, the nose of the airplane shall rise greatly as the value of the Y-coordinate component is larger. When the value of the Y-coordinate component ranges from 0 to 126, the nose of the airplane shall lower greatly as the value of the Y-coordinate component is smaller. Then, when the value of the Y-coordinate component is equal to 127, the nose of the airplane shall not rise and drop.

The manipulation content reception section **801** obtains a change amount of the relative moving direction to the moving direction of the controlled object determined last time. The change amount is obtained based on the bank of the airplane represented by the controlled object and the rise and drop of the nose of the airplane. The bank of the airplane and the rise and drop of the nose of the airplane are specified by a signal depending on the coordinate value on the X-Y coordinate, the signal being outputted from the controller **20**. The obtained change amount of the relative moving direction is added to the moving direction of the controlled object determined last time. Thus, the moving direction of the controlled object is determined.

By the way, in the actual world, a very high level operation is required to shift the airplane to a perfect circular flight by the use of the control stick. For this reason, if the manipulation sticks **31a** and **32a** of the controller **20** are merely allowed to possess the same function just as that of the control stick, it is too difficult for an unskilled player to control the controlled object, and the player might not enjoy the flight simulation game satisfactorily.

Accordingly, in this embodiment, when the coordinate value on the X-Y coordinate represented by the signal is within a predetermined range, the manipulation content reception section **801** judges that the controlled object is allowed to perform a predetermined motion, that is, a motion considered for a player to be difficult to operate in the actual world. Note that this signal is outputted from the controller **20** to the manipulation content reception section **801** by the manipulation performed to the manipulation sticks **31a** and **32a**. Then, the moving direction of the controlled object is determined to be a direction required for performing this motion. In the example shown in FIG. **3**, when the X-coordinate value on the X-Y coordinate is equal to 240 or more and Y-coordinate value on the X-Y coordinate is equal to 15 or less, the manipulation content reception section **801** judges that the controlled object shall be allowed to make a rapid circular flight to the upper right. When the X-coordinate value on the X-Y coordinate is equal to 15 or less and Y-coordinate value on the X-Y coordinate is equal to 15 or less, the manipulation content reception section **801** judges that the controlled object shall be allowed to make a rapid circular flight to the upper left. The moving direction of the controlled object is determined to be a direction required to perform the rapid circular flight.

For example, when the manipulation content reception section **801** judges that the controlled object is allowed to make the rapid circular flight to the upper right, the airplane represented by the controlled object shall tilt to the right by 45 degrees, and shall rise its nose by 45 degrees. Then, the manipulation content reception section **801** determines the moving direction of the controlled object based on the moving direction of the controlled object determined last time. When the manipulation content reception section **801** judges that the controlled object is allowed to make the rapid circular flight to the upper left, the airplane shall tilt to the

left by 45 degrees, and shall rise its nose by 45 degrees. Then, the manipulation content reception section **801** determines the moving direction of the controlled object based on the moving direction of the controlled object determined last time.

In FIG. **6**, the object position calculation section **802** performs periodically processings for calculating a position and posture of the controlled object in the virtual three dimensional field.

To be concrete, the object position calculation section **802** calculates the present position of the controlled object, based on the position and posture (moving direction) of the controlled object calculated last time and the latest moving speed thereof determined by the manipulation content reception section **801**. Furthermore, the object position calculation section **802** calculates the present posture of the controlled object in accordance with the latest moving direction thereof determined by the manipulation content reception section **801**.

Directly from the map database **DB503** stored in the optical disc **85**, a three dimensional map drawing section **803** reads out map constituent elements to be disposed around the position of the controlled object calculated by the object position calculation section **802**. Alternatively, the three dimensional map drawing section **803** reads out the map constituent elements from the map database **DB503** which are read out from the optical memory **85** and temporarily stored in the main memory **53**. Then, the three dimensional map drawing section **803** disposes the constituent elements in the three dimensional field. Thus, topography to be expanded around the position of the controlled object is generated.

Note that the three dimensional map drawing section **803** is not always required to perform the topography generation processing every time the position of the controlled object is calculated by the object position calculation section **802**. For example, the three dimensional map drawing section **803** may perform the topography generation processing every time position of the controlled object is calculated by the object position calculation section **802** plural times. In this case, a range where the controlled object can move is taken into consideration in the processing for calculating the position of the controlled object, which is performed by the object position calculation section **802** plural times. Note that this range can be estimated based on the maximum moving speed of the controlled object previously set. Then the map constituent elements to be disposed around this range are read out from the map database **DB503**, and disposed in the three dimensional field satisfactorily.

In the three dimensional field in which the topography is expanded by the three dimensional map drawing section **803**, an object disposing section **804** disposes the controlled object at the latest position thereof calculated by the object position calculation section **802**. A three dimensional shape and the like are specified by the object data **DA502** stored in the optical disc **85**. On this occasion, the controlled object is disposed so that the posture of the controlled object is identical to that of the latest controlled object calculated by the object position calculation section **802**.

Note that the three dimensional map drawing section **803** and the object disposing section **804** are realized in such a manner that the CPU **51** uses, for example, the GTE **61** in FIG. **4**.

The camera disposing section **805** performs a processing for settling a disposing position of the virtual camera, that is, a viewpoint of the virtual camera, and a direction thereof,

that is, a sight line direction and a tilt of the camera around the sight line direction as an axis. The disposing position and direction of the virtual camera are used for generating a two dimensional image from the three dimensional field in which the topography and the controlled object are disposed by the three dimensional map drawing section **803** and the object disposing section **804**. This processing is performed every time the position and posture of the controlled object are calculated by the object position calculation section **802**. An example of the concrete processing for settling the disposing position and direction of the virtual camera in the camera setting section **805** will be described below.

FIGS. 7 to 9 are drawings for explaining the positional relation between the controlled object **601** and the virtual camera **609** in this embodiment.

FIG. 7 shows a state in which the object **601** and the virtual camera **609** disposed in the three dimensional field are overlooked just from above (an infinitely long distance of the Z-axis), and FIG. 8 shows a state in which the object **601** and the virtual camera **609** disposed in the three dimensional field are viewed just from the side (an infinitely long distance of the X-axis). FIG. 9 shows a state in which the object **601** and the virtual camera **609** disposed in the three dimensional field are viewed just from the side (an infinitely long distance of the Y-axis). Note that in these drawings, illustrations of the map constituent elements disposed in the three dimensional field are omitted.

(1) Disposing Position of Virtual Camera (Camera Setup Point)

As shown in FIGS. 7 to 9, the camera disposing section **805** settles the camera setup point **606**, which is the disposition point of the virtual camera **609** at a position satisfying the following conditions ① to ③.

①: A camera chasing point **604** is settled at a position higher by a predetermined value H than that located to the rear of the position **602** by the distance K, the position **602** being on the line **603** along the moving direction of the controlled object **601** newly calculated by the manipulation content reception section **801**. The line **603** passes through the position **602** of the controlled object **601** newly calculated by the object position calculation section **802**.

②: A camera setup point **606** is settled at a position, which approaches to the camera chasing point **604** from the camera setup point **606** calculated last time by the distance L/M. The distance L/M is obtained by dividing the distance L between the camera chasing point **604** and the camera chasing point **606'** by the predetermined value M. Accordingly, the camera setup point **606**, the a camera setup point **606'** calculated last time and the camera chasing point **604** satisfy the following relations.

X coordinate value of point **606**=(X coordinate value of point **604**-X coordinate value of point **606'**)/M+X coordinate value of point **606'**

Y coordinate value of point **606**=(Y coordinate value of point **604**-Y coordinate value of point **606'**)/M+Y coordinate value of point **606'**

Z coordinate value of point **606**=(Z coordinate value of point **604**-Z coordinate value of point **606'**)/M+Z coordinate value of point **606'**

③: In the relation ①, the distance K is set so as to be shorter, as the moving speed of the controlled object newly calculated by the manipulation content reception section **801** is increased. In other words, the distance K is set so that the camera chasing point **604** approaches to the controlled object **601**. For example, the distance K is represented as k when the moving speed of the controlled object is equal to A, and the distance X is set to satisfy the following equation.

$$K=k-a(B-A)$$

where B is the moving speed of the controlled object newly calculated by the manipulation content reception section **801**, and a is a predetermined coefficient. The coefficient a is set so as to satisfy the following conditions in the above described relation with the predetermined value M expressed in the condition ②.

Specifically, though the camera chasing point **604** approaches nearer to the controlled object **601** as the moving speed of the controlled object **601** is increased, the coefficient a and the predetermined value M are set so that the camera setup point **606** goes far behind the controlled object **601**, that is, the camera setup point **606** moves backward relative to the moving direction of the controlled object **601** as the moving speed of the controlled object **601** is increased.

In the initial state (at the time of starting the game) the camera setup point **606** may be settled at a predetermined position determined fixedly based on the relative positional relation between the camera setup point **606** and the controlled object **601**.

(2) Direction of Camera (Direction of Sight Line of Camera)

As shown in FIGS. 7 to 9, the camera disposing section **805** settles the camera sight line direction **610** so that the virtual camera **609** set at the camera setup point **606** is pointed at a camera reference point **607**. The camera disposing section **805** settles the camera reference point **607** at a position satisfying the following conditions ① and ②.

①: The camera reference point **607** is settled at a position in front of the position **602** by the distance J, the position being on the line **603** along the moving direction of the controlled object newly calculated by the manipulation content reception section **801**. The line **603** passes through the position **602** of the controlled object **601** newly calculated by the object position calculation section **802**.

②: In the condition ①, the distance J is set so as to be longer, that is, so that the camera reference point **607** leaves the controlled object **601** far, as the moving speed of the controlled object, which is newly calculated by the manipulation content reception section **801**, is increased. For example, the distance J is represented as j when the moving speed of the controlled object is equal to A, and the distance J is set so as to satisfy the following equation.

$$J=j+b(B-A)$$

where B represents the moving speed of the controlled object newly calculated by the manipulation content reception section **801**, and b represents a predetermined coefficient.

(3) Direction of Camera (Tilt of Camera Around Camera Sight Line Direction as Axis)

As shown in FIG. 9, when the controlled object banks around the line **603** as an axis, that is, when the manipulation content reception section **801** receives the manipulation content to allow the airplane represented as the controlled object **601** to bank left and right, the virtual camera **609** is rotated around the camera sight line direction **610** as an axis in accordance with the bank thereof. When the controlled object **601** rotates around the line **603** as an axis, the virtual camera **609** is rotated around the camera sight line direction **610** as an axis.

FIGS. 10 and 11 are explanatory views for explaining how the virtual camera **609** behaves for a motion of the controlled object **601** in the present embodiment.

Here, FIG. 10 shows a relation between the controlled object **601** and the virtual camera **609** when the controlled

object **601** shifts from a straight advance state at a constant speed to a clockwise circular flight state. FIG. **11** shows a relation between the controlled object **601** and the virtual camera **609** when the controlled object **601** increases the moving speed gradually in the straight advance state. Note that FIGS. **10** and **11** show a state where the controlled object **601** and the virtual camera **609** are overlooked just from above (an infinitely long distance of the Z-axis), and illustrations of map constituent elements disposed in the three dimensional field are omitted in FIGS. **10** and **11**.

FIGS. **12A** to **12E** exemplify pictorial images obtained by photographing the controlled object **601** with the virtual camera **609** disposed as shown in FIG. **10**. FIG. **12A** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (a) of FIG. **10**, and FIG. **12B** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position, (b) of FIG. **10**. FIG. **12C** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (c) of FIG. **10**, and FIG. **12D** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (d) of FIG. **10**. FIG. **12E** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (e) of FIG. **10**.

FIGS. **13A** to **13C** exemplify pictorial images obtained by photographing the controlled object **601** with the virtual camera **609** disposed as shown in FIG. **11**. FIG. **13A** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (a) of FIG. **11**, and FIG. **13B** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (b) of FIG. **11**. FIG. **13C** shows a pictorial image photographed by the virtual camera **609** when the controlled object is at the position (c) of FIG. **11**.

As apparent from FIG. **10** and FIGS. **12A** to **12E**, the disposing position and direction of the virtual camera **609** are set so that the foregoing conditions (1) to (3) are satisfied whereby the camera setup point **606'** calculated last time is taken into consideration for the camera setup point **606**. Accordingly, the virtual camera **609** behaves so as to chase the controlled object **601** behind with little delay for the motion of the controlled object **601**. When the controlled object **601** rotates around its moving direction as an axis, that is, when the controlled object banks left and right, also the virtual camera **609** rotates around the camera sight line direction **610** as an axis depending on the rotation of the controlled object **601**.

As apparent from FIG. **11** and FIGS. **13A** to **13C**, the disposing position and direction of the virtual camera **609** are set so that the foregoing conditions (1) to (3) are satisfied, whereby the virtual camera **609** moves in a direction to leave the controlled object **601** farther as the moving speed of the controlled object **601** is increased. Furthermore, the camera sight line direction **610** is pointed at a position further in front than the controlled object **601** as the motion speed thereof is increased.

Descriptions will be continued returning to FIG. **6**.

An image generation section **806** generates a two dimensional image obtained by photographing the three dimensional field by the virtual camera in which a disposing position and sight line direction thereof are settled by the camera disposing section **805**. In the three dimensional field, the topography and the controlled object are respectively disposed by the three dimensional map drawing section **803** and the object disposing section **804**. To be concrete, the two dimensional image is generated by a processing (a

rendering) performed in such a manner that by setting a disposing position of the virtual camera as a viewpoint, a direction of the virtual camera as a sight line direction, and rotating the virtual camera **609** around the camera sight line direction **610** as an axis depending on a bank of the controlled object, thus the controlled object and map constituent elements in the three dimensional field are projected on a virtual camera screen.

A display control section **807** transforms the two dimensional image generated by the Image generation section **806** to a video signal, and outputs the video signal to a display device connected to the entertainment apparatus **1**.

Note that the image generation section **806** and the display control section **807** are realized in such a manner that the CPU **51** uses, for example, the GTE **61** and the GPU **62** in FIG. **4**.

Next, an operation of a software structure to realize a flight simulation constructed on the entertainment apparatus **1** will be described.

FIG. **14** is a flowchart for explaining an operation of the software structure to realize the flight simulation constructed on the entertainment apparatus **1**.

The manipulation content reception section **801** first calculates the moving speed of the controlled object **601** (step **S1001**). To be concrete, by detecting a detection signal of a button having a role of a throttle of the controller **20**, an ON/OFF time of the throttle after calculating the moving speed last time is measured. Then, a speed, which is obtained based on the measured time of the throttle ON and an acceleration previously determined, is added to the moving speed calculated last time. And/or, a speed, which is obtained based on the measured time of the throttle OFF and a deceleration previously determined, is subtracted from the moving speed calculated last time. Thus, the moving speed of the controlled object **601** is calculated.

Next, the manipulation content reception section **801** calculates the moving direction of the controlled object **601** (steps **S1002** to **S1004**).

To be concrete, it is checked whether the coordinate value on the X-Y coordinate represented by the signal outputted from the controller **20** is within a predetermined range (step **S1002**). Note that this signal is outputted from the controller **20** by a manipulation performed for the manipulation sticks **31a** and **32a** of the controller **20** possessing a role as a control stick. For example, in the example shown in FIG. **3**, it is checked whether the X coordinate value on the X-Y coordinate is equal to 240 or more and the Y coordinate value thereon is equal to 15 or less, and it is checked whether X coordinate value on the X-Y coordinate is equal to 15 or less and the Y coordinate value thereon is equal to 15 or less.

If the X coordinate value and Y coordinate value on the X-Y coordinate are within the predetermined ranges, the controlled object shall be allowed to perform a predetermined operation, and the moving direction of the controlled object **601** is determined to one required for the controlled object to perform this operation (step **S1003**). For example, in the example shown in FIG. **3**, when the X coordinate value on the X-Y coordinate is equal to 240 or more and the Y coordinate value thereon is equal to 15 or less, it is judged that the controlled object is allowed to make a rapid circular flight to the upper right. Thus, it is assumed that from the moving direction of the controlled object calculated last time, the airplane represented by the controlled object **601** is banked to the right by 45 degrees and the nose of the airplane is risen by 45 degrees, and the moving direction of the controlled object **601** is calculated. When the X coordinate value on the X-Y coordinate is equal to 15 or less and the Y

coordinate value thereon is equal to 15 or less, it is judged that the controlled object is allowed to make a rapid circular flight to the upper left. Thus, it is assumed that from the moving direction of the controlled object calculated last time, the airplane is banked to the left by 45 degrees and the nose of the airplane is risen by 45 degrees, and the moving direction of the controlled object **601** is determined.

On the other hand, if the X coordinate value and the Y coordinate value on the X-Y coordinate are not within the predetermined ranges, a bank of the airplane represented by the controlled object **601** and a rise and drop of the nose of the airplane are determined depending on the coordinate value on the X-Y coordinate shown by a signal outputted from the controller **20** by a manipulation performed for the manipulation sticks **31a** and **32a** thereof. Then, it is assumed that the airplane is made to bank and rise and drop its nose by the determined angles from the moving direction of the controlled object **601** calculated last time, and a moving direction of the controlled object **601** is determined (step **S1004**).

Next, the object position calculation section **802** calculates a position and posture of the controlled object **601** in the virtual three dimensional field (step **S1005**).

Specifically, the present position of the controlled object **601** is calculated based on the position and posture (moving direction) of the controlled object calculated last time and the newest moving speed of the controlled object **601** calculated by the manipulation content reception section **801**. The present posture of the controlled object **601** is calculated in accordance with the newest moving direction of the controlled object **601** determined by the manipulation content reception section **801**.

Next, the three dimensional map drawing section **803** checks whether a map must be updated (step **S1006**). For example, in the case where the map is updated every N times the calculation processing of the position of the controlled object **601** in the step **S1005** is performed, a counter is provided, and it is checked whether a counter value reaches N. If the counter value reaches N, it is judged that the map must be updated, and the counter value is reset. The process advances to step **S1007**. On the other hand, if the counter value does not reach N, the counter value is incremented by one, and the process advances to step **S1008**.

In the step **S1007**, the three dimensional map drawing section **803** reads out map constituent elements to be disposed around the position of the controlled object from the map database **DBS03**. The position of the controlled object was calculated by the object position calculation section **802** in the step **S1005**. Then, the three dimensional map drawing section **803** disposes the constituent elements in the three dimensional field. Thus, topography to be expanded around the position of the controlled object is expanded.

In the step **S1008**, in the three dimensional field in which the topography has been expanded by the three dimensional map drawing section **803** in the step **S1007**, the object disposing section **804** disposes the controlled object **601** at the position of the controlled object calculated by the object position calculation section **802** in the step **S1005**. Note that a three dimensional shape of this controlled object **601** is specified by the object data **DA502**. At this time, the controlled object is disposed so that a posture of the controlled object is identical to that of the controlled object calculated by the object position calculation section **802** in the step **S1005**.

Next, according to the way explained by the use of FIGS. **7** to **13**, the camera disposing section **805** settles the disposing position and direction of the virtual camera **609** used

for generating a two dimensional image from the three dimensional field in which the topography and the controlled object **601** are respectively disposed by the three dimensional map drawing section **803** and the object disposing section **804** in the steps **S1007** and **S1008** (step **S1009**).

In the manner described above, when the controlled object **601** and the topography surrounding the controlled object **601** are disposed in the three dimensional field, and when the disposing position and direction of the virtual camera **609**, which photographs the controlled object **601** and the topography surrounding the controlled object **601** disposed in this three dimensional field, are settled, the image generation section **806** allows the virtual camera **609** to rotate around the camera sight line direction **610**. Note that the virtual camera **609** rotates by setting the disposing position of the virtual camera **609** as a viewpoint and the direction of the camera **609** as a sight line direction and depending on a bank around the moving direction of the controlled object **601**. Then, the image generation section **806** performs a rendering processing in which the controlled object **601** and the topography surrounding the controlled object **601**, which are disposed in the three dimensional field, are projected on a virtual camera screen. Thus, the image generation section **806** generates the two dimensional image (step **S1010**).

Then, the display control section **807** transforms the two dimensional image generated by the image generation section **806** in the step **S1010** to a video signal, and outputs the video signal to the display device connected to the entertainment apparatus **1** (step **S1011**).

By iterating the above described flow shown in FIG. **14**, the entertainment apparatus **1** displays a moving picture on the display screen of the display device connected thereto. The moving picture is obtained by photographing the controlled object **601** with the virtual camera **609**, the object **610** moving in the virtual three dimensional field in accordance with manipulation contents of the player received via the controller **20**.

The embodiment of the present invention was described as above.

According to this embodiment, since the camera setup point **606'** calculated last time is taken into consideration for the camera setup point **606** that is the disposing position of the virtual camera **609**, the virtual camera **609** behaves so as to chase the controlled object **601** behind with little delay for the motion of the controlled object **601**. When the controlled object **601** rotates around its moving direction as an axis, also the virtual camera **609** rotates around the camera sight line direction as an axis depending on the rotation of the controlled object **601**.

Therefore, the player can easily grasp the behavior of the controlled object **601**, which is controlled by the use of the controller **20**, in the virtual three dimensional field through the display screen. Accordingly, the feeling of being at flight by the flight simulation game is enhanced, and the player can enjoy more the flight simulation game.

Furthermore, according to this embodiment, as the moving speed of the controlled object **601** is increased, the virtual camera **609** moves in a direction farther behind the controlled object **601**.

Therefore, when the player increases the moving speed of the controlled object **601** by the use of the controller **20**, a pictorial image surrounding the object taken by the virtual camera **609** broadens depending on an increase amount of the moving speed. In other words, the pictorial image surrounding the object displayed on the display screen of the

display device broadens. Consequently, it is possible to prevent the control of the object from being extremely difficult when the moving speed of the controlled object **601** is increased.

The moving speed of the controlled object **601** is reflected on the moving picture displayed on the display screen of the display device as a relative speed of the object **601** for the topography, which is disposed around the object **610**. Accordingly, though a pictorial image surrounding the object taken by the virtual camera **609** broadens depending on an increase amount of the moving speed of the controlled object **601**, a feeling of speed acquired from the moving picture is not lost.

Furthermore, in this embodiment, the camera sight line direction **610** of the virtual camera **609** is pointed at a position further ahead in front of the controlled object **601** as the motion speed thereof is increased.

For this reason, when the player increases the moving speed of the controlled object **601** by the use of the controller **20**, the pictorial image surrounding the object taken by the virtual camera **609** broadens farther in front than the object depending on the increase amount of the moving speed. Accordingly, when the moving speed of the controlled object **601** is increased, it is possible to further effectively prevent the control of the object from being extremely difficult for a player.

In addition, in this embodiment, the bank of the airplane, which is represented by the controlled object **609**, is determined depending on the coordinate value on the X-Y coordinate, which is outputted from the controller **20** by the manipulation performed for the manipulation sticks **31a** and **32a** of the controller **20**. Moreover, a rise and drop of the nose of the airplane is also determined depending on the coordinate value on the X-Y coordinate. When the X-Y coordinate values on the X-Y coordinate is within a predetermined range, it is judged that the controlled object **601** is allowed to perform a predetermined motion, that is, a motion such as a rapid circular flight considered to be difficult for a player to operate in the actual world. Then, the moving direction of the controlled object **601** is determined to be a direction required for performing this motion.

With such constitution, it is possible to make the control for the controlled object **601** simpler compared to the case where the manipulation sticks **31a** and **32a** of the controller **20** are allowed to possess quite the same function as that of the control stick. Accordingly, even an unskilled player can enjoy the flight simulation game satisfactorily.

Note that the present invention is not limited to the above described embodiment, and various changes, substitutions and alternations can be made therein without departing from spirit and scope of the invention.

In the foregoing embodiment, the camera setup point **606'** calculated last time is taken into consideration for settling the camera setup point **606** that is a disposing position of the virtual camera **609**. However, the present invention is not limited to this. The camera setup point **606** is satisfactorily settled as long as a camera setup point obtained at least one preceding calculation is taken into consideration,

For example, the camera setup point **606** may be settled at a position, which approaches to the camera chasing point **604** from a middle point between the camera setup point **606'** and the camera chasing point **604** by the distance L/M . The distance L/M is obtained by dividing the distance L between the camera setup point **606'** obtained in one preceding calculation and the camera chasing point **604** by a predetermined value M .

Alternatively, the camera setup point **606** maybe settled at a position approaching to the camera chasing point **604** from

a middle point by the distance L/M . The distance L/M is obtained by dividing the distance L between the camera chasing point **604** and the middle point by the predetermined value M . This middle point is located between the camera setup point **606'** obtained in one preceding calculation and the camera setup point **606'** obtained in two preceding calculation.

Although the above described embodiment was described using the example in which the flight simulation game is performed by the use of the entertainment apparatus **1**, the present invention is not limited to this. For example, the present invention can be applied to cases in which performed are various TV games such as a drive simulation game capable of moving a controlled object in a virtual three dimensional field according to manipulation contents of a player received via the controller **20** by the use of the entertainment apparatus **1**.

In the case where the drive simulation game is performed by the use of the entertainment apparatus **1**, when a coordinate value on the X-Y coordinate is within a predetermined range, the coordinate value being represented by a signal outputted from the controller **20** by a manipulation performed for the manipulation sticks **31a** and **32a**, the manipulation content reception section **801** judges that the controlled object is allowed to perform an operation such as a rapid rotation that is considered to be difficult for a player to perform in the actual world. Then, the moving direction of the controlled object maybe determined to be a direction required for performing this operation.

The method of settling the disposing position and direction of the virtual camera **609** in the present invention can be applied not only to the TV game but also to an apparatus which generates a moving picture by photographing a display object moving in a virtual three dimensional field with a virtual camera.

An appearance and hardware structure of the entertainment apparatus **1** are not limited to the ones shown in FIGS. **1**, **2** and **4**. The entertainment apparatus **1** having a constitution of a general computer may be adopted, which is composed of: a CPU; a memory; an external storage device such as a hard disc device; a reading device for reading out data from a recording medium such as a CD-ROM and a DVD-ROM having portability; an input device such as a keyboard and a mouse; a display device such as a display; a data communication device for communicating through a network of the Internet and the like; and an interface for data transmission/reception among the above described devices.

A program for constructing the software structure shown in FIG. **6** on the entertainment apparatus **1**, as well as various data for specifying map constituent elements disposed in the three dimensional field and the three dimensional shape of the controlled object, are read out from the storage medium having the portability via the reading device, and may be stored in the memory and the external storage device. Alternatively, they may be downloaded from the network via the data communication device, and stored in the memory and the external storage device.

As described above, according to the present invention, it is possible to allow even an unskilled player to enjoy the flight simulation, the drive simulation or the like satisfactorily.

What is claimed is:

1. An entertainment apparatus which displays an object moving in a virtual field depending on manipulation contents, which are received via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis passing through the specified fulcrum,

the entertainment apparatus comprising:

manipulation content reception means which determines a moving direction of said object based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to said specified axis of said manipulation stick, said signal being outputted from said controller, and determines said moving direction of said object so that said object is allowed to make a specified motion when the coordinate values are within specified ranges instead of performing motions according to said coordinate values;

wherein said manipulation content reception means determines a bank of an airplane represented by said object and a rise and drop of a nose thereof based on the signal depending on the coordinate values on the X-Y coordinate, said signal being outputted from said controller, and determines the bank of the airplane and the rise and drop of the nose of the airplane represented by said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

2. An entertainment apparatus which displays an object moving in a virtual field depending on manipulation contents, which are received via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis passing through the specified fulcrum,

the entertainment apparatus comprising:

manipulation content reception means which determines a moving direction of said object based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to said specified axis of said manipulation stick, said signal being outputted from said controller, and determines said moving direction of said object so that said object is allowed to make a specified motion when the coordinate values are Within specified ranges;

wherein,

the entertainment apparatus is the one which displays, on a display screen of said display device, a moving picture obtained by photographing the object moving in a virtual three dimensional field, according to manipulation contents of a player which are received via said controller, by the use of a virtual camera,

said object is the one which is displayed on the display screen of said display device as an airplane moving in said three dimensional field, and

said manipulation content reception means determines a bank of the airplane represented by said object and a rise and drop of a nose thereof based on the signal depending on the coordinate values on the X-Y coordinate, said signal being outputted from said controller, and determines the bank of the airplane and the rise and drop of the nose of the airplane represented by said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

3. The entertainment apparatus according to claim 2, wherein,

said specified motion is a circular flight motion.

4. A storage medium storing a program which is read out and executed by a computer, wherein,

said program, by being read out and executed by said computer, is the one which, on said computer, realizes

means for receiving manipulation contents of a player via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis, which passes through the specified fulcrum, the controller being connected to said computer, and for displaying an object on a display device, the object moving in a virtual field according to the manipulation contents, and

said means includes manipulation content reception means for determining a moving direction of said object based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to the specified axis of said manipulation stick, said signal being outputted from said controller, and determines the moving direction of said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges instead of performing motions according to said coordinate values;

wherein said manipulation content reception means determines a bank of an airplane represented by said object and a rise and drop of a nose thereof based on the signal depending on the coordinate values on the X-Y coordinate, said signal being outputted from said controller, and determines the bank of the airplane and the rise and drop of the nose of the airplane represented by said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

5. A storage medium storing a program which is read out and executed by a computer, wherein,

said program, by being read out and executed by said computer, is the one which, on said computer, realizes means for receiving manipulation contents of a player via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis, which passes through the specified fulcrum, the controller being connected to said computer, and for displaying an object on a display device, the object moving in a virtual field according to the manipulation contents, and

said means includes manipulation content reception means for determining a moving direction of said object based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to the specified axis of said manipulation stick, said signal being outputted from said controller, and determines the moving direction of said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges;

wherein,

said means is the one which displays, on a display screen of said display device, a moving picture obtained by photographing an object, moving in a virtual three dimensional field, according to manipulation contents of a player which are received via said controller, by the use of a virtual camera,

said object is the one which is displayed on the display screen of said display device as an airplane moving in said three dimensional field, and

said manipulation content reception means determines a bank of the airplane represented by said object and a rise and drop of a nose thereof based on the signal depending on the coordinate values on the X-Y coordinate, said signal being outputted from said

21

controller, and determines the bank of the airplane and the rise and drop of the nose of the airplane represented by said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

6. The storage medium saving the program according to claim 5, wherein,

said specified motion is a circular flight motion.

7. A program product which is read out and executed by a computer,

wherein said program product being executed by said computer, realizes means, on said computer, for receiving manipulation contents of a player via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis, which passes through the specified fulcrum, the controller being connected to said computer, and for displaying an object on a display device, the object moving in a virtual field according to the manipulation contents, and

said means includes manipulation content reception means for determining a moving direction of said object based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to the specified axis of said manipulation stick, said signal being outputted from said controller, and for determining the moving direction of said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges instead of performing motions according to said coordinate values;

wherein said manipulation content reception means determines a bank of an airplane represented by said object and a rise and drop of a nose thereof based on the signal

22

depending on the coordinate values on the X-Y coordinate, said signal being outputted from said controller, and determines the bank of the airplane and the rise and drop of the nose of the airplane represented by said object so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

8. A method of controlling a display object which controls a movement of an object in a virtual field displayed on a display device, according to manipulation contents of a manipulator received via a controller having a manipulation stick constituted so as to be pivotally tilted using a specified fulcrum relative to a specified axis passing through the specified fulcrum, wherein,

a moving direction of said object is determined, based on a signal depending on coordinate values on X-Y coordinate decided by a tilt direction of said manipulation stick and an angle thereof relative to the specified axis of said manipulation stick, said signal being outputted from said controller, and the moving direction of said object is determined so that said object is allowed to make a specified motion when the coordinate value is within specified ranges instead of performing motions according to said coordinate values;

wherein a bank of an airplane represented by said object and a rise and drop of a nose thereof is determined based on the signal depending on the coordinate values on the X-Y coordinate, said signal being outputted from said controller, and the bank of the airplane and the rise and drop of the nose of the airplane represented by said object is determined so that said object is allowed to make a specified motion when the coordinate value is within specified ranges.

* * * * *