



US006816505B1

(12) **United States Patent**
Sutardja et al.

(10) **Patent No.:** **US 6,816,505 B1**
(45) **Date of Patent:** **Nov. 9, 2004**

(54) **CHIP-TO-CHIP INTERFACE FOR 1000 BASE T GIGABIT PHYSICAL LAYER DEVICE**

(75) Inventors: **Sehat Sutardja**, Cupertino, CA (US);
William Lo, Cupertino, CA (US)

(73) Assignee: **Marvell International Ltd.**, Hamilton (BM)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/501,556**

(22) Filed: **Feb. 9, 2000**

(51) **Int. Cl.**⁷ **H04L 12/66**

(52) **U.S. Cl.** **370/463; 370/465**

(58) **Field of Search** 370/463, 465,
370/276, 278, 282, 285, 389

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,889,766	A	3/1999	Ohnishi et al.	370/307
5,889,776	A *	3/1999	Liang	370/389
5,892,926	A	4/1999	Witkowski et al.	395/280
5,933,427	A *	8/1999	Liang	370/359
5,991,303	A	11/1999	Mills	370/402
6,002,279	A	12/1999	Evans et al.	327/144
6,108,726	A *	8/2000	Runaldue et al.	710/62
6,201,796	B1 *	3/2001	Agazzi et al.	370/286
6,295,281	B1 *	9/2001	Itkowsky et al.	370/293
6,359,893	B1 *	3/2002	Mills	370/402
6,385,208	B1	5/2002	Findlater et al.	
6,516,352	B1 *	2/2003	Booth et al.	709/250
2002/0126684	A1	9/2002	Findlater et al.	

FOREIGN PATENT DOCUMENTS

WO	WO9946867	9/1999	H04B/3/20
----	-----------	--------	-------	-----------

WO	WO0027079	5/2000	H04L/12/413
WO	WO0028663	5/2000	H03H/17/06
WO	WO0028668	5/2000	H03M/13/15
WO	WO0028691	5/2000	H04L/1/00
WO	WO0028712	5/2000	H04L/29/00
WO	WO0035094	6/2000	H03L/7/183

OTHER PUBLICATIONS

RMII Consortium, RMII Specification, AMD Inc., Broadcom Corp., National Semiconductor Corp., and Texas Instruments Inc., 1997, pp. 1-14 and Rev. A.

IEEE Standard 802.3 1988 Edition 22.1 & 35.1.

IEEE Std 802.3, 1998 Edition, Part 3: Carrier Sense Multiple Access With Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications, New York, NY, pp. 1-1222.

IEEE Standards (IEEE Std. 802.3-2002), "Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, pp. 1-581".

* cited by examiner


Primary Examiner—Ajit Patel

Assistant Examiner—Chirag Shah

(57) **ABSTRACT**

A network device comprises a first integrated circuit having fabricated thereon a media access controller and a first serializer interface in communication with the media access controller. A second integrated circuit is provided comprising a physical layer interface in communication with an external device and a second serializer interface in communication with physical layer interface and the first serializer interface. The first and second serializer interfaces each comprise a fiber channel physical layer device implemented in accordance with 1000 BASE-X.

5 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2





FIG. 3



Switch 20

FIG. 4




FIG. 5

CHIP-TO-CHIP INTERFACE FOR 1000 BASE T GIGABIT PHYSICAL LAYER DEVICE

BACKGROUND OF THE INVENTION

Incorporation by Reference

The inventors incorporate IEEE Standard 802.3 in its entirety herein by reference.

1. Field of the Invention

This invention relates generally to an interface and switch for a high speed network, and more particularly to an interface and network switch capable of communicating at a nominal rate of up to 1 gigabit per second.

2. Description of the Related Art

Interconnections of and communications among computers, peripheral devices, Internet appliances (generally referred to as network clients hereinbelow) via computer networks are ubiquitous. Moreover as applications such as, multimedia, require higher data transfer rates there is a need for more robust and faster networks.

Network switches facilitate interconnections and communications among networks and network clients. Conventional networks may utilize twisted pair cable such as Category 5 and operate at a data rate of either 10 megabits per second which generally complies with IEEE Standard 802.3, section 14, commonly known as 10 BASE-T, and 100 megabits per second which generally complies with IEEE Standard 802.3, sections 24 and 25, commonly known as 100 BASE-TX, the contents of each of which are incorporated herein by reference. As the demand for increased data transfer rates is required, a newer networking standard has been proposed that utilizes twisted pair cable and operates at a nominal data transfer rate of 1 gigabit per second (1000 megabits per second). The 1 gigabit per second transfer rate complies with IEEE Standard 802.3, section 40, commonly known as 1000 BASE-T, the contents of which are incorporated herein by reference.

FIG. 1 is schematic diagram of a typical networking system. As shown therein, a computer 10 is connected to a first port of switch 20 via a communications channel, such as, twisted pair cable 30. Switch 20 may comprise 24 ports, to allow computer 10 to communicate with other computers, peripherals, network appliances and other networks.

Computer 10 comprises a media access controller or MAC 12 and physical layer interface (PHY) or transceiver 16, which are connected to each other by an interface defined by, for example, the Media Independent Interface (MII) for 10 BASE-T standard and for 100 BASE-TX standard or the Gigabit Media Independent Interface (GMII) for 1000 BASE-T standard. MII for 10. BASE-T standard and for 100 BASE-TX standard are discussed at IEEE standard 802.3 section 22, the contents of which are incorporated herein by reference. The Gigabit Media Independent Interface (GMII) is defined by IEEE 802.3 section 35, the contents of which are incorporated herein by reference.

Media access controller 12 controls media access of transmitting and receiving packets to and from computer 10. Typically for gigabit level products, MAC 12 and PHY 16 are implemented as individual integrated circuits.

Switch 20 comprises MAC 22_n and PHY 26_n, which are respectively connected to each other in accordance with an interface as defined above. MAC 22_n and PHY 26_n are functionally similar to MAC 12 and PHY 16 of computer 10. When the network is operated in accordance with 10

BASE-T or 100 BASE-TX the interface is defined in accordance with Media Independent Interface (MII). The MII passes data to and from the MAC 22_n in 4 bit wide nibbles. The nibbles are converted to and from 10BASE-T or 100BASE-TX on the network side. When the network is operated at a higher transmission rate in accordance with 1000 BASE-T, the interface is defined by the GMII. In accordance with GMII, data is passed to and from the MAC 22_n in 8 bit wide bytes. The bytes are converted to and from 1000BASE-T on the network side. Note that if fiber is used on the network side then the bytes are converted to and from 1000BASE-X on the network side. In other words, the MII/GMII provides a standard interface from a MAC to a transceiver regardless of the actual protocol used on the network side.

In a system that complies with 10 BASE-T, the MII requires 16 connection lines or pins connecting the integrated circuit embodying PHY 16 and PHY 26 to integrated circuit embodying MAC 12 and MAC 22, respectively. Similarly, in a system that complies with 100 BASE-TX 16 connection lines or pins are required. In a system that complies with 1000 BASE-T 24 connection lines or pins are required. The number of pins required for MAC 12 is not a problem because there is only one MAC and one PHY. On the other hand since there are n ports in switch 20, and since the n MAC 22₁-22_n are typically fabricated as a single integrated circuit 22, the number of pins are 24×n. For example if there are 24 ports then the n MAC 22 requires 24×24 or 576 pins. The higher number of pins result in a larger die, a larger package, a more complicated integrated circuit and higher costs, particularly at the higher data transfer rates.

Various attempts have been made to solve the above-mentioned problems. Two ad hoc standards, namely Reduced Media Independent Interface (RMII) and Serial Media Independent Interface (SMII) reduce the number of pins by serialization techniques for 10 BASE-T and 100 BASE-TX. The RMII technique requires 7 pins per port and the frequency doubles from 25 MHz to 50 MHz. Thus for a 24 port switch 7×24 or 168 pins are required. The SMII technique requires 2 pins per port plus 1 synchronizing pin and the frequency increases 5 fold from 25 MHz to 125 MHz. In this technique 2×24+1 or 49 pins are required for the SMII technique. As will be appreciated by one of ordinary skill in the art, these techniques operate at frequencies in which clock recovery between PHY 26 and MAC 22 is not required.

The GMII interface consists of 24 pins operating at 125 Megabits per second. However, design of such circuit is difficult as the length of the traces and impedances between the traces must match for good signal integrity at this higher frequency. This results in a more costly and complicated integrated circuit.

An additional requirement of a network circuit operating at 1 gigabit per second is to be backward compatible with 10 BASE-T and 100 BASE-TX networks. That is, the network circuit must detect the maximum data transmission rate capability and set the transmission rate to that rate. For example, if computer 10 is capable of a maximum transmission rate of 100 Mb per second, switch 20 having a capability of 1 gigabit per second, must detect the 100 Mb per second rate and set the transmission rate of the port of switch 20 connect to computer 10 to 100 Mb per second. This feature is commonly known as auto-negotiation. The auto-negotiation feature is typically implemented in PHY 16 and PHY 26_n. PHY 16 communicates the auto-negotiated data transmission rate to MAC 12 and PHY 26_n communicates the auto-negotiated data transmission rate to MAC 22_n.

Traditional techniques either requires higher pin counts and complicated board routing.

OBJECTS OF THE INVENTION

Therefore, it -is an object of the present invention to overcome the aforementioned problems.

It is another object of the present invention to provide an interface between physical layer devices having data rates up to 1 gigabit per second.

It is a further object of the present invention to provide an interface between which reduces the number of pins or connections.

It is an additional object of the present invention to provide a system to efficiently control the auto-negotiated data rate.

SUMMARY OF THE INVENTION

According to one aspect of the present invention, a network device is provided which comprises a first integrated circuit having fabricated thereon a media access controller and a first serializer interface in communication with said media access controller. A second integrated circuit is provided comprising a physical layer interface in communication with an external device and a second, serializer interface in communication with physical layer interface and said first serializer interface. The first and second serializer interfaces comprise a fiber channel physical layer device implemented in accordance with 1000 BASE-X.

According to a second aspect of the present invention, the first serializer interface comprises a first receiver/decoder and a first transmitter/encoder, the second serializer interface comprises a second receiver/decoder and a second transmitter/encoder, and the first transmitter/encoder being in communication with the second receiver/decoder and the second transmitter/encoder being in communication with the first receiver/decoder.

In accordance with a third aspect of the present invention, the physical layer interface communicates with the external device at a selected one of plural data transmissions rates in accordance with a negotiated data transmission rate negotiated with the external device. The first transmitter/encoder communicates with the second receiver/decoder at a predetermined data transmission rate regardless of the negotiated transmission rate, and the second transmitter/encoder communicates with the first receiver/decoder at the predetermined data transmission rate regardless of the negotiated transmission rate.

In accordance with a fourth aspect of the present invention, the second integrated circuit further comprises a transceiver to communicate with the external device and an auto-negotiation circuit in communication with the transceiver. The auto-negotiation circuit negotiates the negotiated data transmission rate with the external device and provides a first control signal indicative of the negotiated data transmission rate to the second receiver/decoder and the second transmitter/encoder. If first control signal indicates that the negotiated data transmission rate is less than a specified data transmission rate, the second transmitter/encoder replicates data transmitted to the first receiver/decoder. The first receiver/decoder determines if any data received from the second transmitter/encoder has been replicated and provides a second control signal indicative of a received data transmission rate to the first transmitter/decoder. If the second control signal indicates that the first received data transmission rate is less than the specified data transmission rate, the

first transmitter/encoder replicates data transmitted to the second receiver/decoder. The second receiver/decoder determines if any data received from the first transmitter/encoder has been replicated to determine the received data transmission rate and compares the received transmission rate with the first control signal. If the received data transmission rate is not equal to the negotiated data transmission rate, the second receiver/decoder provides a third control signal to the transceiver. The transceiver transmits idle data to the external device upon receipt of the third control signal.

In accordance with a fifth aspect of the present invention, the predetermined data transmission rate is 1.25 gigabits per second.

In accordance with a sixth aspect of the present invention, the physical, layer interface is capable of communicating with the external device at a nominal data transmission rate of 1 gigabit per second.

In accordance with a seventh aspect of the present invention, a network switch is provided and comprises a first integrated circuit having a plurality of media access controllers and a plurality of first serializer interfaces, each in communication with a respective one of the plurality of media access controllers. A plurality of second integrated circuits are provide, each comprising a physical layer interface in communication with an external device, and a second serializer interface in communication with the physical layer interface and a corresponding one the first serializer interfaces.

In accordance with a eighth aspect of the present invention the first and second serializer interfaces comprise a fiber channel physical layer device implemented in accordance with 1000 BASE-X.

In accordance with a ninth aspect-of the present invention, an integrated circuit comprises a media access controller and a serializer interface in communication with the media access controller and an external device. The serializer interface comprises a fiber channel physical layer device implemented in accordance with 1000 BASE-X.

In accordance with a tenth aspect of the present invention, an integrated circuit comprises a physical layer interface in communication with a first external device and a serializer interface in communication with the physical layer interface and a second external device. The serializer interface comprises a fiber channel physical layer device implemented in accordance with 1000 BASE-X.

Other objects and attainments together with a fuller understanding of the invention will become apparent and appreciated by referring to the following description and claims taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings wherein like reference symbols refer to like parts:

FIG. 1 is a schematic diagram of a conventional networking system;

FIG. 2 is a schematic diagram of a networking system in accordance with a first embodiment of the present invention;

FIG. 3 is a more detailed schematic diagram of a media access controller (MAC) and PHY in accordance with the first embodiment of the present invention;

FIG. 4 is a more detailed schematic diagram of a media access controller (MAC) and PHY in accordance with a second embodiment of the present invention; and

FIG. 5 is a more detailed schematic diagram illustrating auto-negotiation in accordance with the first embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 2, shown therein is a preferred embodiment of the present invention. As shown therein, a computer 10 is connected to a first port of switch 20 via a communications channel, such as, twisted pair cable 30. Switch 20' may comprise 24 ports, to allow computer 10 to communicate with other computers, peripherals, network appliances and other networks.

Computer 10 comprises a media access controller or (IMAC) 12 and physical layer interface (PHY) or transceiver 16, which are connected to each other in accordance with an interface, such as, MII or GMII discussed above. Media access controller 12, computer 10, and PHY 16 are similar to those described above, therefore no further discussion is provided herein. As will be appreciated by one of ordinary skill in the art, communication channel 30 may be implemented using a variety of techniques, for example wired, wireless, radio frequency, optical and the like.

Switch 20' comprises n ports. Each of the n ports comprises MAC 22'_n and PHY 26'_n. PHY 26'_n comprises serializer interface 27'_n, and MAC 22'_n comprises serializer interface 28'_n, which are connected to each other to facilitate communication between MAC 22'_n and PHY 26'_n. Serializer interfaces 28'₁-28'_n and MAC's 22'₁-22'_n are fabricated on a single integrated circuit. PHY 26'_n and serializer interface 27'_n are fabricated on another integrated circuit. Serializer interfaces 27'_n and 28'_n have high bandwidth that can be connected to each other using only a small number of wires, connections or pins for each transmit and receive link. In the preferred embodiment, serializer interfaces 27'_n and 28'_n are implemented in accordance with the fiber channel physical layer device standard as described in IEEE 802.3, section 36, commonly known as 1000 BASE-X. The contents of IEEE 802.3, section 36 are incorporated herein by reference.

Referring now to FIG. 3, serializer interface 28'_n comprises receive port 41'_n, transmit port 42'_n and interface 43'_n. Port 41'_n of serializer interface 28'_n is connected to the transmit port 46'_n of serializer interface 27'_n by a pair of differential wires, and transmit port 42'_n of serializer interface 28'_n is connected to receive port 47'_n of serializer interface 27'_n by a pair of differential wires. Port 43'_n is connected to MAC 22'_n, and port 48'_n is connected to PHY 26'_n.

In the preferred embodiment serializer interface 28'_n requires only 4 pins, 2 pairs of differential wires or interconnections are required for each port. For a 24 port switch only 96 pins are required instead of the 576 pins required using conventional techniques.

FIG. 4 is a schematic diagram of another embodiment of the present invention. The embodiment shown herein is similar to the embodiment shown in FIG. 2, however PHY 26''_n comprises a GMII standard interface 23''_n. In this configuration, PHY 26''_n can be connected to any GMII compliant device, which can facilitate communication between that device and either serializer interface 27'_n or twisted pair cable 30.

The auto-negotiation feature will now be described below with reference to FIG. 5.

In accordance with any of the embodiments above, while switch 20' has the capability of communicating at nominally 1 gigabit per second, switch 20 must also be able to communicate at data rates of 10 Mbits per second and 100 Mbits per second, dependent on the network client connected thereto.

FIG. 5 is a schematic diagram of an embodiment capable of communicating with a network client having a different data transmission rate. This embodiment generally comprises the same components as that of FIG. 2. More specifically, serializer interface 27'_n comprises transmitter/encoder 60'_n and receiver/decoder 61'_n and serializer interface 28'_n comprises transmitter/encoder 63'_n and receiver/decoder 62'_n. Very generally, the principal of operation is as follows. Firstly, the data transmission rate between serializer interface 27'_n and serializer interface 28'_n is maintained at 1.25 gigabit per second, regardless of the data transmission rate between the network client and PHY 26''_n. In operation, auto-negotiation circuit 70'_n negotiates the data transmission rate with the network client using known techniques such as, standard IEEE 802.3, sections 28 and 40, the contents of which are incorporated by reference. The negotiated transmission rate is communicated to transmitter/encoder 60'_n via control signal 110. If the data transmission rate is below the nominal 1 gigabit per second, transmitter/encoder 60'_n will replicate data transmitted to serializer interface 28'_n, as explained in detail below, while the data transmission rate between transmitter/encoder 60'_n and serializer interface 28'_n is maintained at 1.25 gigabit per second. In the serializer interface 28'_n, receiver/decoder 62'_n monitors the data transmission and determines if data has been replicated. If no data has been replicated, the data transmission rate is 1.25 gigabit per second and no special processing is performed and all data is communicated with MAC 22''_n. If receiver/decoder 62'_n determines that data is being replicated, then the replicated data is ignored and not communicated to MAC 22''_n. This feature allows switch 20' to communicate with network clients having a lower transmission rate without the need for costly and complicated circuits.

In a data communication system in accordance with 1000 BASE-X as described in IEEE 802.3, section 36, when there is no data to be transmitted, the transmitting component, for example PHY'_n, sends an idle ordered set of data which consists of two alternating 10 bit code groups which are denoted as /K28.5/D16.2/. This ordered set is abbreviated as /I/. It is noted that the ordered set /K28.5/D5.6/ is occasionally utilized to maintain correct disparity. Also in accordance with 1000 BASE-X, when a packet is transmitted, the packet is delimited by a start of packet and end of packet delimiters which are abbreviated /S/ and /T/R/, respectively.

Receiver/decoder 62'_n and receiver/decoder 61'_n perform alignment of the bits stream into code-groups by searching for a comma pattern, namely, is 1100000 or 0011111. The comma pattern cannot be found in any code-group or within a concatenation of any combination of code-groups except for the code-groups /K28.5/, /K28.1/, and /K28.7/. In the preferred embodiment the code groups /K28.1/ and /K28.7/ are not used. Hence alignment is performed during idles where the /K28.5/ code-group is present.

It is further noted that the /K28.5/ code-group is also used in other ordered sets to pass configuration information. For example /K28.5/D21.5/Dx.x/Dx.x/ is a valid configuration ordered set. In the preferred embodiment, receiver/decoder 62'_n and 61'_n ignore most of the ordered sets containing configuration information. This simplifies the design of receiver/decoders 62'_n and 61'_n.

As noted above, the ordered set /K28.5/D5.6/ is occasionally utilized to maintain correct disparity. In general, the purpose of disparity is twofold. First, disparity is used to ensure that there will be equal numbers of 0's and 1's are transmitted over a short period of time to maintain DC balance regardless of the actual data within the packet. Second, disparity allows the receiver to detect the presence

of errors that occurs over the transmission medium. Typically, for each code group there is two possible 10 bit sequences. One is transmitted when the disparity is positive, and the other when negative. (For some code-groups the same 10-bit sequence is used to for both positive and negative disparities.)

In the following discussion it is assumed that the signal flow is serializer interface 27_n to serializer interface 28_n . The reverse process is used from the serializer interface 28_n to serializer interface 27_n .

More specifically, in transmitter/encoder 60_n nibbles are replicated. Since the conversion into 1000BASE-X requires byte wide data while 10BASE-T/100BASE-TX passes data in nibble wide data, the upper four bits of the byte are padded with dummy bits by transmitter/encoder 60_n . In 100BASE-TX the data is replicated 5 times and five bytes are transmitted from the 1000BASE-X for each 100BASE-TX nibble. In 10BASE-T the data is replicated 50 times.

In accordance with an alternative implementation of transmitter/encoder 60_n , the upper bits are not padded but rather two nibbles are passed at a time. In this case the data is replicated 10 and 100 for 100 BASE-TX and 10 BASE-T times respectively. The advantage of this approach is that MAC $22'_n$ passes data in bytes regardless of the speed of operation.

Note that the /S/ code group must be transmitted 10 or 100 times for 100 BASE-TX and 10 BASE-T, respectively. In principle the /T/R/ and /I/ code-groups must be transmitted 10 or 100 times for 100 BASE-TX and 10 BASE-T, respectively. However in accordance with the present embodiment, latency can be shortened by transmitting the code groups 5 or 50 times, for 100 BASE-TX and 10 BASE-T, respectively.

In the present embodiment data is simply replicated as many times as needed and disparity is calculated once every 5 or 50 code groups for 100 BASE-TX and 10 BASE T, respectively. In an alternate embodiment, disparity can also be calculated once every code group. This will allow a better short-term DC balance, but may complicate serializer interface 28_n .

PHY $26'_n$ determines the data transmission rate of the network based on auto-negotiation. However the MAC $22'_n$ requires some time to receive the data from the. PHY 26_n before it can respond. More specifically, auto-negotiation circuit 70_n negotiates the transmission data rate with the network client and sends a control signal 110 to transmitter/encoder 60_n . As noted above, transmitter/encoder 60 , will either pass the data through or replicate bits in accordance with the detected data transmission rate. Receiver/decoder 62_n of serializer interface 28_n can sense the data transmission rate by counting the number of /K28.5/ it receives, as noted above. Receiver/decoder 62_n sends a control signal 212 to transmitter/encoder 63_n . Receiver/decoder 61_n of serializer interface 27_n can sense the data transmission rate as noted above. Receiver/decoder 61_n then compares the data transmission rate it senses to the auto-negotiated data transmission rate from control signal 110 . If the data transmission rates are different, then receiver/decoder 61_n sends control signal 112 to transceiver 80 to transmit idle bits. When the data transmission rates become the same, the control 112 then permits transceiver 80 to transmit data.

While the invention has been described in conjunction with several specific embodiments, it is evident to those skilled in the art that many further alternatives, modifications and variations will be apparent in light of the foregoing description. Moreover, it is contemplated that the present

invention is not limited to the nominal 1 gigabit-per second data transmission rate and above-described protocols, and may be implemented with other appropriate data transmission rates and protocols. Thus, the invention described herein is intended to embrace all such alternatives, modifications, applications and variations as may fall within the spirit and scope of the appended claims.

What is claimed is:

1. A network device comprising:

a first integrated circuit comprising:

a media access controller, and

a first serializer interface in communication with said media access controller; and

a second integrated circuit comprising:

a physical layer interface in communication with an external device, and

a second serializer interface in communication with physical layer interface and said first serializer interface,

wherein said first serializer interface comprises a first receiver/decoder and a first transmitter/encoder,

wherein said second serializer interface comprises a second receiver/decoder and a second transmitter/encoder,

wherein said first transmitter/encoder is in communication with said second receiver/decoder, and

wherein said second transmitter/encoder is in communication with said first receiver/decoder,

wherein said physical layer interface communicates with the external device at a selected one of plural data transmissions rates in accordance with a negotiated data transmission rate negotiated with the external device,

wherein said first transmitter/encoder communicates with said second receiver/decoder at a predetermined data transmission rate regardless of the negotiated transmission rate,

wherein said second transmitter/encoder communicates with said first receiver/decoder at the predetermined data transmission rate regardless of the negotiated transmission rate, and wherein said second integrated circuit further comprises:

a transceiver to communicate with the external device; and

an auto-negotiation circuit in communication with said transceiver,

wherein said auto-negotiation circuit negotiates the negotiated data transmission rate with the external device,

wherein said auto-negotiation circuit provides a first control signal indicative of the negotiated data transmission rate to said second receiver/decoder and said second transmitter/encoder,

wherein if first control signal indicates that the negotiated data transmission rate is less than a specified data transmission rate, said second transmitter/encoder replicates data transmitted to said first receiver/decoder;

wherein said first receiver/decoder determines if any data received from said second transmitter/encoder has been replicated to provide a second control signal indicative of a received data transmission rate to said first transmitter/decoder;

wherein if the second control signal indicates that the first received data transmission rate is less than the specified data transmission rate, said first transmitter/encoder replicates data transmitted to said second receiver/decoder,

9

wherein said second receiver/decoder determines if any data received from said first transmitter/encoder has been replicated to determine the received data transmission rate,

wherein said second receiver/decoder compares the received transmission rate with the first control signal, wherein if the received data transmission rate is not equal to the negotiated data transmission rate, said second receiver/decoder provides a third control signal to said transceiver, and

wherein said transceiver transmits idle data to the external device upon receipt of the third control signal.

2. A network switch comprising:

a first integrated circuit comprising:

- a plurality of media access controllers, and
- a plurality of first serializer interfaces, each in communication with a respective one of said plurality of media access controllers; and

a plurality of second integrated circuits, each comprising:

- a physical layer interface in communication with an external device,
- a second serializer interface in communication with said physical layer interface and a corresponding one said first serializer interfaces, wherein each of said plurality of first serializer interfaces comprises a first receiver/decoder and a first transmitter/encoder,

wherein said second serializer interface comprises a second receiver/decoder and a second transmitter/encoder, wherein said first transmitter/encoder is in communication with said second receiver/decoder, and wherein said second transmitter/encoder is in communication with said first receiver/decoder,

wherein said physical layer interface communicates with the external device at a selected one of plural data transmissions rates in accordance with a negotiated data transmission rate negotiated with the external device,

wherein said first transmitter/encoder communicates with said second receiver/decoder at a predetermined data transmission rate regardless of the negotiated transmission rate, and

wherein said second transmitter/encoder communicates with said first receiver/decoder at the predetermined data transmission rate regardless of the negotiated transmission rate,

wherein each of said plurality of second integrated circuits further comprises:

- a transceiver to communicate with the external device; and
- an auto-negotiation circuit in communication with said transceiver,

wherein said auto-negotiation circuit negotiates the negotiated data transmission rate with the external device, wherein said auto-negotiation circuit provides a first control signal indicative of the negotiated data transmission rate to said second receiver/decoder and said second transmitter/encoder,

wherein if first control signal indicates that the negotiated data transmission rate is less than a specified data transmission rate, said second transmitter/encoder replicates data transmitted to said first receiver/decoder;

wherein said first receiver/decoder determines if any data received from said second transmitter/encoder has been replicated to provide a second control signal indicative

10

of a received data transmission rate to said first transmitter/decoder;

wherein if the second control signal indicates that the first received data transmission rate is less than the specified data transmission rate, said first transmitter/encoder replicates data transmitted to said second receiver/decoder,

wherein said second receiver/decoder determines if any data received from said first transmitter/encoder has been replicated to determine the received data transmission rate,

wherein said second receiver/decoder compares the received transmission rate with the first control signal, wherein if the received data transmission rate is not equal to the negotiated data transmission rate, said second receiver/decoder provides a third control signal to said transceiver, and

wherein said transceiver transmits idle data to the external device upon receipt of the third control signal.

3. An integrated circuit comprising:

- a physical layer interface in communication with a first external device; and
- a serializer interface in communication with said physical layer interface and a second external device, wherein said serializer interface comprises a fiber channel physical layer device,

wherein said integrated circuit further comprises:

- a transceiver to communicate with the external device; and
- an auto-negotiation circuit in communication with said transceiver,

wherein said serializer interface comprises a receiver/decoder and a transmitter/encoder,

wherein said auto-negotiation circuit negotiates a negotiated data transmission rate with the external device, wherein said auto-negotiation circuit provides a first control signal indicative of the negotiated data transmission rate to said receiver/decoder and said transmitter/encoder,

wherein if first control signal indicates that the negotiated data transmission rate is less than a specified data transmission rate, said transmitter/encoder replicates data to be transmitted;

wherein said receiver/decoder determines if any data received has been replicated to determine the received data transmission rate,

wherein said receiver/decoder compares the received transmission rate with the first control signal, wherein if the received data transmission rate is not equal to the negotiated data transmission rate, said receiver/decoder provides a second control signal to said transceiver, and

wherein said transceiver transmits idle data to the external device upon receipt of the second control signal.

4. A method of forming a network device comprising the steps of:

- fabricating on a first integrated circuit a media access controller and a first serializer interface;
- fabricating on a second integrated circuit a physical layer interface and a second serializer interface;
- implementing the first and second serializer interfaces as fiber channel physical layer devices;
- providing the first serializer with a first receiver/decoder and a first transmitter/encoder;

11

providing the second serializer with a second receiver/
 decoder and a second transmitter/encoder;
 transmitting data by the first transmitter/encoder to the
 second receiver/decoder;
 transmitting data by the second transmitter/encoder to the
 first receiver/decoder;
 communicating between the physical layer interface and
 the external device at a selected one of plural data
 transmissions rates in accordance with a negotiated
 data transmission rate negotiated with the external
 device;
 transmitting data by the first transmitter/encoder to the
 second receiver/decoder at a predetermined data trans-
 mission rate regardless of the negotiated transmission
 rate;
 transmitting data by the second transmitter/encoder to the
 first receiver/decoder at the predetermined data trans-
 mission rate regardless of the negotiated transmission
 rate;
 negotiating the negotiated data transmission rate with the
 external device,
 providing a first control signal indicative of the negotiated
 data transmission rate to the second receiver/decoder
 and the second transmitter/encoder,
 if the first control signal indicates that the negotiated data
 transmission rate is less than a specified data transmis-
 sion rate, replicating data transmitted to the first
 receiver/decoder;
 determining by the first receiver/decoder if any data
 received has been replicated to provide a second con-
 trol signal indicative of a received data transmission
 rate to the first transmitter/decoder;
 if the second control signal indicates that the first received
 data transmission rate is less than the specified data
 transmission rate, replicating data transmitted by the
 first transmitter/encoder,
 determining if any data received from the first transmitter/
 encoder has been replicated to determine the received
 data transmission rate,

12

comparing the received transmission rate with the first
 control signal,
 if the received data transmission rate is not equal to the
 negotiated data transmission rate, providing a third
 control signal, and
 transmitting idle data to the external device upon receipt
 of the third control signal.
5. An integrated circuit comprising:
 a physical layer interface in communication with a first
 external device; and
 a serializer interface in communication with said physical
 layer interface and a second external device, wherein
 said serializer interface comprises a fiber channel
 physical layer device,
 wherein said integrated circuit further comprises:
 a transceiver to communicate with the external device;
 and
 an auto-negotiation circuit in communication with said
 transceiver,
 wherein said serializer interface comprises a receiver/
 decoder,
 wherein said auto-negotiation circuit negotiates a negoti-
 ated data transmission rate with the external device,
 wherein said auto-negotiation circuit provides a first con-
 trol signal indicative of the negotiated data transmis-
 sion rate to said receiver/decoder,
 wherein said receiver/decoder determines if any data
 received has been replicated to determine the received
 data transmission rate,
 wherein said receiver/decoder compares the received
 transmission rate with the first control signal,
 wherein if the received data transmission rate is not equal
 to the negotiated data transmission rate, said receiver/
 decoder provides a second control signal to said
 transceiver, and
 wherein said transceiver transmits idle data to the external
 device upon receipt of the second control signal.

* * * * *