

US006857686B2

(12) **United States Patent**
Willard

(10) **Patent No.:** **US 6,857,686 B2**
(45) **Date of Patent:** **Feb. 22, 2005**

(54) **TWO-WAY OPENING DECKLID FOR A CONVERTIBLE ROOF VEHICLE**

(75) Inventor: **Michael Willard**, Harrison Township, MI (US)

(73) Assignee: **ASC Incorporated**, Southgate, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,973,097 A	11/1990	Hosan et al.
5,533,777 A	7/1996	Kleemann et al.
5,551,743 A	9/1996	Klein et al.
5,823,606 A	10/1998	Schenk et al.
5,904,395 A	5/1999	Wedin
5,944,378 A	8/1999	Mather et al.
5,967,590 A	10/1999	Beierl et al.
5,975,619 A	11/1999	Dettling et al.
6,010,178 A	1/2000	Hahn et al.
6,019,417 A	2/2000	Haberl

(List continued on next page.)

(21) Appl. No.: **10/361,163**

(22) Filed: **Feb. 6, 2003**

(65) **Prior Publication Data**

US 2004/0155480 A1 Aug. 12, 2004

(51) Int. Cl.⁷ **B60J 7/00**

(52) U.S. Cl. **296/107.08; 296/76**

(58) Field of Search 296/107.08, 76,
296/107.17, 136

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,774,199 A	8/1930	Good
1,933,623 A	11/1933	Gordon
1,990,848 A	2/1935	Velo
2,800,361 A	7/1957	Kubacka
3,211,494 A	10/1965	Husko
3,304,117 A	2/1967	Harris et al.
3,525,687 A	8/1970	Ross et al.
4,776,626 A	10/1988	Seyler
4,966,403 A	10/1990	Nordstrom

FOREIGN PATENT DOCUMENTS

DE	4136895 C1	11/1992
DE	4445580 C1	12/1995
DE	4445941 C1	3/1996
DE	4445944 C1	4/1996
DE	4446483 A1	6/1996
DE	4445920 A1	7/1996
DE	19514022 C1	9/1996


Primary Examiner—Lori L. Coletta

(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce, P.L.C.


(57) **ABSTRACT**

A two-way opening modular decklid assembly is disclosed. The modular decklid assembly includes a frame and a decklid that are installed in a vehicle as a modular unit. The decklid assembly uses a simple at least four-bar non-scissor linkage assembly to attach a frame to the vehicle. The linkage assembly is operable to move the frame between open and closed positions.

48 Claims, 12 Drawing Sheets



U.S. PATENT DOCUMENTS					
6,030,023	A	2/2000	Guillez	6,325,445	B1 12/2001 Schenk
6,039,382	A	3/2000	Mather et al.	6,352,298	B1 3/2002 Hayashi et al.
6,062,628	A	5/2000	Guillez	6,357,815	B1 3/2002 Queveau et al.
6,070,929	A	6/2000	Barkley	6,361,097	B1 3/2002 Lechkun
6,092,335	A	7/2000	Queveau et al.	6,386,615	B2 5/2002 Neubrand et al.
6,142,555	A	11/2000	Huber	6,419,294	B2 * 7/2002 Neubrand 296/76
6,145,915	A	11/2000	Queveau et al.	6,572,175	B2 * 6/2003 Schutt et al. 296/107.17
6,164,713	A	12/2000	Graf et al.	2001/0042991	A1 11/2001 Schuler et al.
6,186,577	B1	2/2001	Guckel et al.	2001/0048231	A1 12/2001 Ellermann et al.
6,193,300	B1	2/2001	Nakatomi et al.	2002/0011739	A1 1/2002 Nicastrì
6,217,104	B1	4/2001	Neubrand	2002/0014782	A1 2/2002 Neubrand
6,217,105	B1	4/2001	Hollerbach	2002/0036413	A1 3/2002 Neubrand et al.
6,250,707	B1	6/2001	Dintner et al.	2002/0041109	A1 4/2002 Wagner et al.
6,254,165	B1	7/2001	Neubrand	2002/0093218	A1 7/2002 Weissmueller et al.
6,293,605	B2	9/2001	Neubrand	2003/0071479	A1 * 4/2003 Schaller et al. 296/136
			* cited by examiner		






Fig-1B




Fig-2





Fig-3






Fig-5





Fig-6A






Fig-6C




Fig-7A




Fig-7B




Fig-7C

1

TWO-WAY OPENING DECKLID FOR A CONVERTIBLE ROOF VEHICLE**BACKGROUND AND SUMMARY OF THE INVENTION**

The present invention is generally related to decklids for a convertible roof vehicle, and more particularly to a two-way opening decklid for a convertible roof vehicle.

Automotive vehicles having a convertible roof typically stow the convertible roof (when retracted) in a stowage compartment that is behind or aft of the passenger seating area. To provide a desired appearance, the retracted convertible roof can be covered by a tonneau panel. The tonneau panel can be designed to cover the entirety of the stowed convertible roof or a portion thereof. The tonneau panel can also be used to cover the stowage compartment when the convertible roof is in the raised or extended position. To accommodate the movement of the convertible roof from the stowed to the raised position and vice versa, the tonneau panel is operated between open and closed positions to allow access to the stowage compartment.

In some convertible roof vehicles, the convertible roof does not occupy an entire storage area aft of the passenger seating area. For example, the area aft of the passenger seating area can include a stowage compartment for the convertible roof along with a general storage area or trunk behind or aft of the stowage area. The general storage area is covered by a trunk lid, known as a decklid, that moves between open and closed positions to allow access to the general storage area. Accordingly, combination decklids and tonneau panels have been devised that open in opposite directions to allow access to the general storage area from a rear of a vehicle and access to the stowage compartment from a forward position on the vehicle. Thus, two-way opening decklids and tonneau panels are known. However, the conventional mechanisms used to provide the two-way opening functionality can be complex and employ a large number of complicated links to provide the two-way opening functionality. Additionally, the installation of such two-way opening decklids can be difficult, involve multiple steps and be time consuming.

In accordance with the present invention, a two-way opening decklid assembly includes a frame and a decklid that are installed in a vehicle as a modular unit. In another aspect of the present invention, the decklid assembly uses at least a four-bar non-scissor linkage assembly to attach a frame to the vehicle and is operable to move the frame between open and closed positions.

The present invention is advantageous over traditional two-way opening decklid assemblies in that the two-way opening decklid assembly can be installed in a vehicle as a modular unit. This increases quality while reducing assembly line space, customer part count and difficult assembly ergonomics. Furthermore, the present invention is advantageous because the decklid assembly utilizes a simple linkage assembly that causes the frame to move between open and closed positions which allows the convertible roof to move between retracted and extended positions. The decklid assembly of the present invention can be utilized in an automotive vehicle having a hardtop convertible roof or a soft-top convertible roof. Additional advantages and features of the present invention will become apparent from the following description and appended claims taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

2

FIG. 1A is a perspective view of the preferred embodiment of a modular decklid assembly according to the principles of the present invention;

FIG. 1B is a perspective view of an alternate embodiment of a modular decklid assembly with an integral powered actuator according to the principles of the present invention;

FIG. 2 is a fragmented perspective view of a convertible roof vehicle with the decklid assembly according to the principles of the present invention;

FIG. 3 is a fragmented elevation view of the vehicle of FIG. 2 showing the decklid assembly in a closed position;

FIG. 4 is a fragmented elevation view of the vehicle of FIG. 2 with the decklid assembly open to allow retraction and extension of the convertible roof;

FIG. 5 is a fragmented elevation view of the vehicle of FIG. 2 with the decklid assembly in an open position allowing access to a rear storage area of the vehicle;

FIG. 6A is a fragmented perspective view of a hardtop convertible roof vehicle with a decklid assembly according to the principles of the present invention;

FIG. 6B is a fragmented elevation view of the vehicle of FIG. 6A with the hardtop convertible roof in an intermediate position and the decklid assembly open to allow retraction and extension of the hardtop convertible roof;

FIG. 6C is a fragmented elevation view of the vehicle of FIG. 6A with the hardtop convertible roof in a fully retracted position and the decklid assembly closed;

FIG. 7A is a fragmented elevation view of a soft-top convertible roof vehicle with a decklid assembly according to the principles of the present invention;

FIG. 7B is a fragmented elevation view of the vehicle of FIG. 7A with the rearmost roof bow of the soft-top convertible roof in an upright position and the decklid assembly closed; and

FIG. 7C is a fragmented elevation view of the vehicle of FIG. 7A with the soft-top convertible roof in a fully retracted position and the decklid assembly closed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following description of the preferred embodiment is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

Referring to FIG. 1A, the preferred embodiment of a modular decklid assembly 20 according to the principles of the present invention is shown. Modular decklid assembly 20 is used in an automotive vehicle 22 having a passenger compartment 24, a convertible roof system 26, a stowage compartment 28 for the convertible roof system, and a storage area or trunk 30. Stowage compartment 28 and storage area 30 can be a combined area that is not differentiated by a physical barrier or can be two separate areas separated by a physical barrier. Stowage compartment 28 and storage area 30 are both located behind passenger compartment 24. Stowage compartment 28 retains convertible roof system 26 when the convertible roof is in the retracted position, as described below. Attachment points, in this case in the form of brackets 32, are located in the rear portion of storage area 30 and allow modular decklid assembly 20 to be installed in vehicle 22, as described below.

Modular decklid assembly 20 includes a frame 34, rear linkage assemblies 36, a decklid 38, and front linkage assemblies 40. Frame 34 includes two longitudinal members

3

42 and two transverse members 44 that space longitudinal members 42 apart and are attached to respective front and rear portions of longitudinal members 42.

A front portion of decklid 38 is pivotally pivotally coupled to a front portion of frame 34 by front linkage assemblies 40. Front linkage assemblies 40 allow decklid 38 to move between open and closed positions to allow access to storage area 30 independent of movement of frame 34, as described below. Rear linkage assemblies 36 are attached to a rear portion of frame 34 and are adapted to be attached to brackets 32 on vehicle 22. Rear linkage assemblies 36 are operable to cause frame 34 to move between open and closed positions to allow retraction and extension of convertible roof system 26, as described below.

Modular decklid assembly 20 is installed in vehicle 22 as a modular unit. That is, frame 34, decklid 38, and rear and front linkage assemblies 36 and 40 are preassembled in a separate facility or in a static station, preferably with the external surface of the decklid facing down. Then modular decklid assembly 20 is installed in storage area 30 of vehicle 22 as a modular unit on the assembly line, which may be a moving one, prior to the painting process. To install modular decklid assembly 20, one of the links in each of the two rear linkage assemblies 36 is aligned with brackets 32 in storage area 30 of vehicle 22. The one link of each rear linkage assembly 36 is preferably attached to brackets 32 with bolts. However, it should be understood that other means of attaching a link in each of the rear linkage assemblies 36 to brackets 32 can alternately be employed. For example, a link in each rear linkage assembly 36 can be welded to brackets 32 if desired.

After installing modular decklid assembly 20 in vehicle 22, a powered actuator 46 (shown in FIGS. 2-4) is attached to a rear portion of storage area 30 and to one of the links in each rear linkage assembly 36. Powered actuator 46 is operable to move rear linkage assemblies 36 and cause frame 34 to move between the opened and closed positions. Powered actuator 46 can take a variety of forms. Preferably, powered actuator 46 is a hydraulic cylinder that moves between extended and retracted positions to operate rear linkage assemblies 36. Alternatively, powered actuator 46 could be in the form of an electric motor that drives rear linkage assemblies 36.

In an alternate embodiment, as shown in FIG. 1B, each end of powered actuator 46 is attached to two links of each rear linkage assembly 36. Operation of the powered actuators 46 between extended and retracted positions then causes rear linkage assemblies 36 to move which in turn causes frame 34 to move between its open and closed positions. In this alternate embodiment, powered actuators 46 are part of modular decklid assembly 20. That is, frame 34, decklid 38, rear and front linkage assemblies 36 and 40, and powered actuators 46 are all installed in vehicle 22 as a modular unit. A power source is later connected to powered actuators 46 to drive powered actuators 46 as desired.

Referring now to FIGS. 2 and 3, modular decklid assembly 20 is shown installed in vehicle 22 with rear linkage assemblies 36 attached to brackets 32 in storage area 30. A front portion of frame 34 rests on stops 48 of vehicle 22. Because each rear linkage assembly 36 is substantially an identical mirror image of the other and because each front linkage assembly 40 is also substantially an identical mirror image of the other, only the passenger side rear and front linkage assemblies 36 and 40 will be described in greater detail.

FIGS. 3 and 4 illustrate rear linkage assembly 36 which includes a first link 50 that fixedly attaches rear linkage

4

assembly 36 to bracket 32 of vehicle 22. First link 50 thereby is a fixed link that remains stationary regardless of movement of rear linkage assembly 36. One end of a second link 52 is pivotally attached to first link 50 at pivot 54 while the other end of second link 52 is pivotally attached to a rear portion of longitudinal member 42 of frame 34 at pivot 56. One end of a third link 58 is pivotally attached to a rear portion of longitudinal member 42 of frame 34 at pivot 60 while the other end of third link 58 is pivotally attached to first link 50 at pivot 62. Thus, rear linkage assembly 36 forms a four-bar non-scissor linkage assembly which includes first link 50, second link 52, longitudinal member 42, and third link 58 and is defined by pivots 54, 56, 60, and 62. In other words, rear linkage assembly 36 is a four-bar linkage assembly wherein each link of the linkage assembly is attached to two or less other links of the linkage assembly, thus being a non-scissor linkage assembly. In the preferred embodiment, second and third links 52 and 58 may overlap when frame 34 is moved between its open and closed positions, however, second and third links 52 and 58 do not cross over one another when frame 34 is moved between its open and closed positions.

One end of powered actuator 46 is pivotally attached to second link 52 at pivot 64 while the other end of powered actuator 46 is attached to vehicle 22. As can be seen in FIG. 3, when powered actuator 46 is in a retracted position, frame 34 is in the closed position and decklid 38 covers stowage compartment 28 along with storage area 30. As powered actuator 46 moves between its retracted position to its extended position, as shown in FIG. 4, second link 52 is pushed by powered actuator 46 and causes frame 34 to rotate clockwise (as shown in FIG. 4) and move to its open position. When frame 34 is in its open position, decklid 38 is no longer covering stowage compartment 28 and convertible roof system 26 can be operated to move between its extended and retracted positions. It is preferred that decklid 38 remain in its closed position when frame 34 is moved from between its open and closed positions. In other words, it is preferred that decklid 38 remain stationary relative to frame 34 as frame 34 moves between its open and closed positions. Thus, powered actuator 46 pushes or pulls second link 52 away from or toward powered actuator 46 which causes frame 34 to pivot and allows access to stowage compartment 28 so that convertible roof system 26 can move between extended and retracted positions.

Referring now to FIGS. 3 and 5, it can be seen that front linkage assembly 40 is operable to allow decklid 38 to move between its closed position, as shown in FIG. 3, and its open position, as shown in FIG. 5, which allows access to storage area 30. Front linkage assembly 40 includes a first link 66 which is fixedly attached to a front portion of decklid 38. One end of a second link 68 is pivotally attached to first link 66 at pivot 70 while the other end of second link 68 is pivotally attached to a front portion of longitudinal member 42 of frame 34 at pivot 72. One end of a third link 74 is pivotally attached to the front portion of longitudinal member 42 at pivot 76 further forward of pivot 72 while the other end of third link 74 is pivotally attached to first link 66 at pivot 78. First link 66, second link 68, longitudinal member 42, and third link 74 thereby form a four-bar linkage assembly defined by pivots 70, 72, 76 and 78 which allows decklid 38 to move between open and closed positions. A biasing member 80, in this case in the form of gas strut, is attached to longitudinal member 42 and first link 66. Gas strut 80 helps retain decklid 38 in the open position. Preferably, gas strut 80 is installed after the vehicle body and modular decklid assembly 20 have gone through the paint-

5

ing process. Alternatively, other biasing mechanisms can be used, such as springs, without departing from the scope of the present invention. Decklid **38** is capable of moving between its open and closed positions independently of movement of frame **34**. Thus, frame **34** can remain stationary and/or in its closed position while decklid **38** moves between its open and closed positions.

Modular decklid assembly **20** can be used on a vehicle **22** having a convertible roof system **26** that is a hardtop convertible roof system **26'**, such as that shown in FIGS. **6A–C** or, alternatively, a soft-top convertible roof system **26"**, such as that shown in FIGS. **7A–C** which will be further described hereinafter. Referring to FIGS. **6A–C**, modular decklid assembly **20** is shown being used with a hardtop convertible roof system **26'**. Hardtop convertible roof system **26'** is the same as that disclosed in U.S. Ser. No. 10/245,973 filed on Sep. 18, 2002, entitled "Vehicle Retractable Hardtop Roof" by Willard and assigned to the assignee of this Application, the disclosure of which is incorporated by reference herein.

Hardtop convertible roof system **26'** is moveable between an extended or raised position, shown in FIG. **6A**, wherein the passenger compartment **24** is covered by the hardtop convertible roof system **26'** and a retracted or stowed position, as shown in FIG. **6C**, wherein the hardtop convertible roof system **26'** is stored in stowage compartment **28** and covered by decklid **38**. Hardtop convertible roof system **26'** includes a convertible roof **88**. Convertible roof **88** includes a first roof section **90**, a second roof section **92**, a third roof section **94**, and a retraction mechanism **96**. Each of the first, second and third roof sections are substantially rigid members interconnected to one another by a retraction mechanism **96**. Retraction mechanism **96** is mounted in a cavity of stowage compartment **28**. Retraction mechanism **96** includes a pair of actuation assemblies **98** mounted near each outboard edge of vehicle **22**. Each of the actuation assemblies **98** are substantially identical mirror images to one another and only the driver side actuation assembly is depicted.

Actuation assembly **98** includes a linkage assembly **100** coupled to an actuator **102**. Actuator **102** is depicted as a hydraulic cylinder coupled to linkage assembly **100**. It should be appreciated that actuator **102** may alternately be constructed as an electric motor, a pneumatic cylinder or any suitable power source for driving linkage assembly **100**. Preferably, actuator **102** is the same type of actuator as powered actuator **46**.

Modular decklid assembly **20** is controlled to coordinate the movement of modular decklid assembly **20** with that of convertible roof **88** such that stowage compartment **28** is accessible when moving convertible roof **88** between the raised and stowed positions. As depicted in FIG. **6B**, first roof section **90** pivots relative to second roof section **92** in a clamshell manner such that an inner surface of first roof section **90** approaches an inner surface of second roof section **92** while third roof section **94** begins to enter stowage compartment **28**.

With reference to FIG. **6C**, convertible roof **88** is shown in the stowed position. In the stowed position, first roof section **90** and second roof section **92** are each positioned in a substantially horizontal manner within roof stowage compartment **28**. Once in the stowed position, modular decklid assembly **20** is operated to cause frame **34** to move from its open position to its closed position and cover convertible roof **88** with decklid **38**.

Referring now to FIGS. **7A–C**, modular decklid assembly **20** is shown on a vehicle **22** having a soft-top convertible

6

roof system **26"**. Soft-top convertible roof system **26"** includes a linkage assembly or top stack mechanism **118** covered by a pliable fabric top covering **120**. More specifically, the linkage assembly includes a number one roof bow **122**, a number two roof bow **124**, a number three roof bow **126**, a number four roof bow **128**, and a number five or rearmost bow **130**. The top stack mechanism **118** also includes a front roof rail **132**, a center roof rail **134**, and a rear roof rail **136** (shown in FIG. **7C**).

As can be seen in FIG. **7C**, front roof rail **132** is pivotally coupled to center roof rail **134** and is controlled by a linkage assembly. Center roof rail **134** is pivotally coupled to rear roof rail **136** and is controlled by a different linkage assembly. Soft-top convertible roof system **26"** is operable to move between a raised or extended position covering passenger compartment **24**, as shown in FIG. **7A**, through intermediate positions, such as that shown in FIG. **7B**, to a fully retracted or stowed position within stowage compartment **28**, as shown in FIG. **7C**.

In operation, when it is desired to move soft-top convertible roof system **26"** from the raised position to the stowed position, number five roof bow **130** is rotated upwardly and forwardly, as shown in FIG. **7B**, an amount sufficient to allow frame **34** of modular decklid assembly **20** to be moved from its closed to its open position. Once number five roof bow **130** has moved a sufficient distance, modular decklid assembly **20** is operated to cause frame **34** to move from its closed to its open position to allow access to stowage compartment **28**. Soft-top convertible roof system **26"** is then retracted into stowage compartment **28**, as shown in FIG. **7C**. As can be seen, the roof rails **132**, **134** and **136** rotate relative to one another and are stacked on top of one another when in the stowed position. Modular decklid assembly **20** is then operated to cause frame **34** to move to its closed position thereby causing decklid **38** to cover at least a portion of soft-top convertible roof system **26"**. While soft-top convertible roof system **26"** is shown as being a manually operated soft-top convertible roof system, it should be appreciated that movement of soft-top convertible roof system **26"** between its extended and stowed positions can be automated through the use of powered actuators such as hydraulic cylinders, electric motors, pneumatic cylinders or any suitable power source for driving top stack mechanism **118**.

Thus, modular decklid assembly **20** provides a decklid assembly that covers and conceals stowage compartment **28** and storage area **30**. Modular decklid assembly **20** can be opened to allow access to stowage compartment **28** so that a convertible roof system **26** can move between extended and retracted positions. Modular decklid assembly **20** can also be operated to cause decklid **38** to open to allow access to storage area **30**. Thus, modular decklid assembly **20** provides a two-way opening decklid assembly that can be used with a convertible roof vehicle that employs either a soft-top convertible roof system or a hardtop convertible roof system.

While modular decklid assembly **20** has been shown as being powered by actuator **46**, it should be appreciated that modular decklid assembly **20** can be a completely manually operated assembly. When modular decklid assembly **20** is manually operated, it is preferred that a biasing member, such as a spring or gas strut be employed to assist in moving frame **34** from its closed to its open position. It should be appreciated that front linkage assemblies **40** can include a powered actuator, such as those discussed above, to cause front linkage assemblies **40** to move decklid **38** between its open and closed positions. Thus, movement of decklid **38**

between its open and closed positions can be power actuated and be within the scope of the present invention.

Moreover, modular decklid assembly **20** can be used with other convertible roof systems beyond the specific hardtop and soft-top convertible roof systems disclosed. For example, decklid assembly **20** can be used with a vehicle having an outfolding convertible roof such as that disclosed in U.S. Pat. No. 4,828,317 entitled "Convertible Top Frame with Quarter Windows" by Muscat, and with a vehicle having a soft-top convertible roof system such as that disclosed in U.S. Pat. No. 6,288,511 entitled "Automotive Convertible Top System" by Porter et al. and assigned to the assignee of this Application, the disclosures of which are incorporated by reference herein.

It should be appreciated that a lock or latching mechanism (not shown) can be employed to retain decklid **38** in a closed position so that decklid **38** does not inadvertently open. Further, it should be appreciated that when frame **34** is manually operated a lock or latching mechanism (not shown) can be employed that locks or latches frame **34** in the closed position to avoid inadvertent opening or movement of frame **34**.

Furthermore, it should be appreciated that decklid assembly **20** can be put on a vehicle **22** as a non-modular unit although various advantages of the present invention may not be realized. That is, the individual components that comprise decklid assembly **20** can be installed individually or in different groupings and still be within the scope of the present invention. For example, frame **34** and rear and front linkage assemblies **36** and **40** can be preassembled in a separate facility or in a static station. The frame **34** and rear and front linkage assemblies **36** and **40** can then be installed in storage area **30** of vehicle **22** by aligning one of the links in each of the two rear linkage assemblies **36** with brackets **32** in storage area **30** of vehicle **22**. Decklid **38** can then be attached to front linkage assemblies **40** and adjusted into proper positioning relative to the body of vehicle **22**. Decklid **38** can be cycled into its open position and locked into the open position to hold in that position for the painting process. After the painting process has been completed, a latching mechanism can be installed on decklid **38** and gas struts **80** can be installed. Decklid **38** can then be moved to its closed position and frame **34** can be operated to its open position. Once in the open position, powered actuators **46** can be installed on vehicle **22** and on rear linkage assemblies **36**. If desired, powered actuators **46** can be installed as part of the installation of the convertible roof system **26**. Thus, it is not necessary for the decklid assembly to be a modular unit to be within the scope of the present invention. The description of the invention is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the invention. Such variations are not to be regarded as a departure from the spirit and scope of the invention.

What is claimed is:

1. A modular decklid assembly for a vehicle, the modular decklid assembly comprising:

a frame operable between open and closed positions;
a decklid pivotally coupled to said frame and operable between open and closed positions, said decklid capable of movement independent of said frame; and
wherein said frame and said decklid are adapted to be installed in the vehicle as a modular unit.

2. The modular decklid assembly of claim **1**, wherein said decklid is pivotally coupled to said frame by an at least four bar linkage assembly.

3. The modular decklid assembly of claim **2**, further comprising a gas strut having a first end attached to said decklid and a second end attach to said frame.

4. The modular decklid assembly of claim **1**, further comprising a powered actuator operable to cause said frame to move between said open and closed positions.

5. The modular decklid assembly of claim **4**, wherein said actuator, said frame and said decklid are installed in the vehicle as a modular unit.

6. The modular decklid assembly of claim **1**, wherein said frame remains stationary when said decklid moves between said open and closed positions to allow rear access.

7. The modular decklid assembly of claim **1**, further comprising:

a linkage assembly including at least a four bar linkage that couples said frame to the vehicle; and
said linkage assembly, said frame and said decklid being installed in the vehicle as a modular unit.

8. The modular decklid assembly of claim **1**, wherein said frame has a front portion and a rear portion, said rear portion of said frame is pivotally coupled to the vehicle and said decklid is pivotally coupled to said front portion of said frame.

9. A decklid assembly comprising:

a frame operable between open and closed positions;
an at least four bar, non-scissor linkage assembly attached to said frame and adapted to be attached to a vehicle, said linkage assembly being operable to move said frame between said open and closed positions; and
a decklid coupled to said frame and operable between open and closed positions independently of said frame, and said decklid moving with said frame when said frame moves between its open and closed positions.

10. The decklid assembly of claim **9**, further comprising a linkage assembly coupling said decklid to said frame.

11. The decklid assembly of claim **10**, wherein said linkage assembly coupling said decklid to said frame is an at least four bar linkage assembly.

12. The decklid assembly of claim **9**, further comprising a gas strut coupled to said decklid and coupled to said frame.

13. The decklid assembly of claim **9**, further comprising a powered actuator coupled to said linkage assembly and operable to cause said linkage assembly to move said frame between said open and closed positions.

14. The decklid assembly of claim **9**, wherein said at least four bar linkage assembly is a four bar linkage assembly.

15. The decklid assembly of claim **9**, wherein said frame has a front portion and a rear portion, said linkage assembly is attached to said rear portion of said frame and said decklid is coupled to said front portion of said frame.

16. An automotive vehicle system comprising:

a frame operable between first and second positions;
an at least four bar linkage assembly having at least two moving links that are free of crossing one another, said linkage assembly being coupled to said frame and operable to move said frame between said open and closed positions; and
a lid coupled to said frame and operable between open and closed positions independently of said frame.

17. The system of claim **16**, further comprising a convertible roof system including a convertible roof operable between extended and retracted positions.

18. The system of claim **17**, wherein said convertible roof system includes a hardtop convertible roof.

19. The system of claim **17**, wherein said convertible roof system includes a soft-top convertible roof.

9

20. The system of claim 17, wherein said frame opens to allow said convertible roof to move between said extended and retracted positions.

21. The system of claim 16, further comprising an at least four bar linkage assembly coupling said lid to said frame.

22. The system of claim 16, further comprising a strut having a first end coupled to said lid and a second end coupled to said frame.

23. The system of claim 16, further comprising a powered actuator coupled to said linkage assembly and operable to cause said linkage assembly to move said frame between said open and closed positions.

24. An automotive vehicle comprising:

a convertible roof system operable between extended and retracted positions; and

a decklid system including:

a frame operable between open and closed positions;
a linkage assembly including at least a four bar linkage, wherein each link of said linkage assembly is attached to two or less other links of said linkage assembly, said linkage assembly being attached to said frame and to the vehicle and said linkage assembly being operable to move said frame between said open and closed positions; and

a trunk cover coupled to said frame and operable between open and closed positions independently of said frame, and said trunk cover moving with said frame when said frame moves between said frame open and closed positions.

25. The automotive vehicle of claim 24, wherein said convertible roof system includes a hardtop convertible roof.

26. The automotive vehicle of claim 25, wherein said hardtop convertible roof has at least three substantially rigid panels.

27. The automotive vehicle of claim 26, wherein at least one of said panels is stowed substantially horizontally below said trunk cover when said convertible roof system is in said stowed position.

28. The automotive vehicle of claim 24, wherein said linkage assembly is a first linkage assembly and said decklid system further includes a second linkage assembly coupling said trunk cover to said frame.

29. The automotive vehicle of claim 28, wherein said second linkage assembly is an at least a four bar linkage assembly.

30. The automotive vehicle of claim 24, wherein said convertible roof system includes a soft-top convertible roof.

31. The automotive vehicle of claim 24, wherein said frame moves to said open position when said convertible roof system moves between said extended and retracted positions.

32. The automotive vehicle of claim 24, wherein said decklid system further includes a strut coupled to said trunk cover and coupled to said frame.

33. The automotive vehicle of claim 24, wherein said decklid system further includes a powered actuator coupled to said linkage assembly and operable to cause said linkage assembly to move said frame between said open and closed positions.

34. The automotive vehicle of claim 24, wherein said frame has a front portion and a rear portion, said linkage assembly is attached to said rear portion of said frame and said trunk cover is coupled to said front portion of said frame.

35. The automotive vehicle of claim 24, wherein said decklid system is installed in the automotive vehicle as a modular unit.

36. A method of installing a modular decklid system onto an automotive vehicle wherein the modular decklid system

10

includes a frame operable between open and closed positions and a decklid pivotally coupled to the frame and capable of movement independent of the frame, the method comprising:

(a) preassembling the decklid to the frame at a first station removed from the vehicle; and

(b) assembling the modular decklid system at a second station onto the vehicle.

37. The method of claim 36, wherein step (b) further includes coupling the frame to the vehicle.

38. The method of claim 37, wherein step (a) further includes preassembling a linkage assembly to the frame and step (b) further includes attaching said linkage assembly onto the vehicle.

39. The method of claim 38, wherein said linkage assembly is an at least four bar non-scissor linkage assembly and step (b) further includes attaching a link of said linkage assembly onto the vehicle.

40. The method of claim 36, wherein step (a) further includes preassembling a linkage assembly to the frame and coupling the decklid to the frame with said linkage assembly.

41. The method of claim 36, wherein the modular decklid system includes a powered actuator operable to move the frame between the open and closed positions, step (a) further includes preassembling said actuator to the modular decklid system, and further including the step of connecting a power source to said actuator.

42. The method of claim 36, further including the step of coupling a powered actuator to the vehicle and to the frame wherein said actuator is operable to cause the frame to move between the open and closed positions.

43. The method of claim 36, wherein step (b) further includes assembling the modular decklid system onto a rear portion of the vehicle.

44. A modular decklid assembly for a vehicle, the modular decklid assembly comprising:

a frame operable between open and closed positions; and
a decklid pivotally coupled to said frame and operable between open and closed positions,

wherein said frame and said decklid are adapted to be installed in the vehicle as a modular unit and said decklid is pivotally coupled to said frame by an at least four bar linkage assembly.

45. A modular decklid assembly for a vehicle, the modular decklid assembly comprising:

a frame operable between open and closed positions;
a decklid pivotally coupled to said frame and operable between open and closed positions; and

a powered actuator operable to cause said frame to move between said open and closed positions,

wherein said frame and said decklid are adapted to be installed in the vehicle as a modular unit.

46. A decklid assembly for a vehicle, the decklid assembly comprising:

a frame operable between open and closed positions; and
a decklid pivotally coupled to said frame and operable between open and closed positions, said decklid capable of movement independent of said frame.

47. The decklid assembly of claim 46, wherein said decklid is pivotally coupled to said frame by an at least four bar linkage assembly.

48. The decklid assembly of claim 46, further comprising a powered actuator operable to cause said frame to move between said open and closed positions.