



US006860427B1

(12) **United States Patent**
Schmidt et al.

(10) **Patent No.:** **US 6,860,427 B1**
(45) **Date of Patent:** ***Mar. 1, 2005**

(54) **AUTOMATIC OPTICAL PROJECTION
SCANNER FOR OMNI-DIRECTIONAL
READING OF BAR CODE SYMBOLS
WITHIN A CONFINED SCANNING VOLUME**

(58) **Field of Search** 235/462.01, 462.14,
235/462.17, 462.32, 462.35, 462.36, 462.37

(75) **Inventors:** **Mark C. Schmidt**, Williamstown, NJ
(US); **George B. Rockstein**, Audubon,
NJ (US); **David M. Wilz, Sr.**, Sewell,
NJ (US); **Carl H. Knowles**,
Moorestown, NJ (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,902,048 A 8/1975 Fleischer et al.

(List continued on next page.)

(73) **Assignee:** **Metrologic Instruments, Inc.**,
Blackwood, NJ (US)

FOREIGN PATENT DOCUMENTS

EP 424 097 B1 10/1990

(List continued on next page.)

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal dis-
claimer.

Microcomputer-Product Brochure of MS131 Microcom-
puter controller by Metrologic Instruments, Inc., 1984 (1
page).

(21) **Appl. No.:** **10/314,614**

(22) **Filed:** **Dec. 9, 2002**

(List continued on next page.)

Related U.S. Application Data

(63) Continuation of application No. 09/861,150, filed on May
18, 2001, now Pat. No. 6,604,684, which is a continuation
of application No. 08/615,054, filed on Mar. 12, 1996, now
Pat. No. 6,286,760, which is a continuation-in-part of appli-
cation No. 08/573,949, filed on Dec. 18, 1995, now aban-
doned, and a continuation-in-part of application No. 08/292,
237, filed on Aug. 17, 1994, now Pat. No. 5,808,285, and a
continuation-in-part of application No. 08/365,193, filed on
Dec. 28, 1994, now Pat. No. 5,557,093, and a continuation-
in-part of application No. 08/293,493, filed on Aug. 19,
1994, now Pat. No. 5,525,789, and a continuation-in-part of
application No. 08/561,479, filed on Nov. 20, 1995, now Pat.
No. 5,661,292, and a continuation-in-part of application No.
08/278,109, filed on Nov. 24, 1993, now Pat. No. 5,484,992,
and a continuation-in-part of application No. 08/489,305,
filed on Jun. 9, 1995, now abandoned, and a continuation-
in-part of application No. 08/476,069, filed on Jun. 7, 1995,
now Pat. No. 5,591,953, and a continuation-in-part of appli-
cation No. 08/584,135, filed on Jan. 11, 1996, now Pat. No.
5,616,908.

Primary Examiner—Daniel St. Cyr

(74) *Attorney, Agent, or Firm*—Morgan, Lewis & Bockius
LLP


(57) **ABSTRACT**

An automatic scanner which can be used at a point-of-sale
(POS) station. The scanner provides a confined scanning
volume, so as to avoid unintentional scanning of nearby
objects that are located outside of this confined scanning
volume. This scanner can be operated in an automatic
hands-on mode of operation, or also operated as a stationary
laser projection scanner in an automatic hands-free mode of
operation. A collimated scanning pattern is projected from
the hand-supportable device about a projection axis. The
collimated scanning pattern intersects the projection axis
within a narrowly confined scanning volume so that bar code
symbols disposed within this scanning volume can be read
omnidirectionally.

(51) **Int. Cl.**⁷ **G06K 7/10**

(52) **U.S. Cl.** **235/462.32; 235/462.14;**
235/462.33

47 Claims, 43 Drawing Sheets



U.S. PATENT DOCUMENTS

3,911,270 A 10/1975 Traub
 3,919,527 A 11/1975 Bowen et al.
 3,947,816 A 3/1976 Rabedeau
 3,978,317 A 8/1976 Yamaguchi et al.
 4,006,343 A 2/1977 Izura et al.
 4,026,630 A 5/1977 Wollenmann
 4,072,859 A 2/1978 McWaters
 4,086,476 A 4/1978 King
 4,093,865 A 6/1978 Nickl
 4,097,729 A 6/1978 Seligman et al.
 4,136,821 A 1/1979 Sugiura et al.
 4,387,297 A 6/1983 Swartz et al.
 4,409,470 A 10/1983 Shepard et al.
 4,431,912 A 2/1984 Dickson et al.
 4,460,120 A 7/1984 Shepard et al.
 4,496,831 A 1/1985 Swartz et al.
 4,521,678 A 6/1985 Winter
 4,570,057 A 2/1986 Chadima, Jr. et al.
 4,575,625 A 3/1986 Knowles
 4,603,262 A 7/1986 Eastman et al.
 4,639,070 A 1/1987 Ikeda et al.
 4,639,606 A 1/1987 Boles et al.
 4,647,143 A 3/1987 Yamazaki et al.
 4,652,732 A 3/1987 Nickl
 4,673,805 A 6/1987 Shepard et al.
 4,713,532 A 12/1987 Knowles
 4,736,095 A 4/1988 Shepard et al.
 4,737,702 A 4/1988 Koenck
 4,766,297 A 8/1988 McMillan
 4,766,298 A 8/1988 Meyers
 4,766,299 A 8/1988 Tierney et al.
 4,795,224 A 1/1989 Goto
 4,816,660 A 3/1989 Swartz et al.
 4,825,057 A 4/1989 Swartz et al.
 4,845,349 A 7/1989 Cherry
 4,861,973 A 8/1989 Hellekson et al.
 4,877,949 A 10/1989 Danielson et al.
 4,897,532 A 1/1990 Swartz et al.
 4,920,255 A 4/1990 Gabeler
 4,930,848 A 6/1990 Knowles
 4,933,538 A 6/1990 Heiman et al.
 4,939,356 A 7/1990 Rando et al.
 4,960,985 A 10/1990 Knowles
 4,962,980 A 10/1990 Knowles
 4,970,379 A 11/1990 Danstrom
 5,000,529 A 3/1991 Katoh et al.
 5,015,833 A 5/1991 Shepard et al.
 5,017,765 A 5/1991 Shepard et al.
 5,026,975 A 6/1991 Guber et al.
 5,039,184 A 8/1991 Murakawa et al.
 5,059,777 A 10/1991 Wittensoldner et al.
 5,086,215 A 2/1992 Carsner et al.
 5,107,100 A 4/1992 Shepard et al.
 5,115,333 A 5/1992 Mergenthaler et al.
 5,124,537 A 6/1992 Chandler et al.
 5,124,539 A 6/1992 Krichever et al.
 5,132,523 A 7/1992 Bassett
 5,153,417 A 10/1992 Sakai et al.
 5,180,904 A 1/1993 Shepard et al.
 5,196,696 A 3/1993 Lindacher
 5,198,650 A 3/1993 Wike, Jr.
 5,212,370 A 5/1993 Wittensoldner et al.
 5,216,231 A 6/1993 Ouchi
 5,221,832 A 6/1993 Collins, Jr. et al.

5,250,790 A 10/1993 Metlitsky et al.
 5,262,627 A 11/1993 Shepard
 5,280,162 A 1/1994 Marwin
 5,324,924 A 6/1994 Cai et al.
 5,420,411 A 5/1995 Salatto, Jr. et al.
 6,604,684 B1 * 8/2003 Schmidt et al. 235/462.32

FOREIGN PATENT DOCUMENTS

EP 460 669 B1 11/1991
 EP 0 517 958 B1 12/1992
 JP 54.819 1/1979
 JP 54.33740 3/1979
 JP 5412293 9/1979
 JP 6448017 2/1989

OTHER PUBLICATIONS

Enhanced Version of MS131 Controller–Product Brochure of MS132 Microcomputer Controller by Metrologic Instruments, Inc., 1984. (2 pages).
 Introduction to the Company, Metrologic Instruments, Inc. and some of its products–Product Brochure entitled “Metrologic Bar Code Scanning Systems” by Metrologic Instruments, Inc., 1995.
 Hand–Held Bar Code Symbol Scanner– “Hand–Held Holographic Scanner Having Highly Visible Locator Beam”, by R.T. Cato, IBM Technical Disclosure Bulletin, vol. 27, No. 4A, Sep. 1994.
 Laser Bar Code Symbol Scanner with hardware–Implemented Digital Count Data Filter–Product Brochure and Schematic Diagram entitled “Metrologic SS–200 Magazine Scanner”, Circa 1979.
 Hand–Held Laser Bar Code Symbol Scanner with Software Implemented Digital Count–Data Filter–Product Brochure and Schematic Diagram for MH290 Hand Held Laser Scanner by Metrologic Instruments, Inc., Nov. 1987.
 Stands and Holders for Hand–Held Bar Code Scanners–Sales Brochure Entitled “Stands, Holders and Accessories” by Symbol Technologies of Bohemia, New York; Dec. 1989.
 Omni–Directional Bar Code Symbol Scanner–Product Brochure for Omniscan OS–0712 by Micro Video, Inc. 1990, (2 pages).
 Omni–Directional Bar Code Symbol Scanner–Product Brochure for Omniscan OS–510 by Micro Video, Inc. 1990. (4 pages).
 Laser Projection Scanner–Product Brochure for Spectra–Physics Freedom™ Scanner, by Spectra Physics, Inc. (2 pages) Circa 1988.
 Holographic Laser Scanner “Hologram Scanner for Pos Bar Code Symbol Reader” by Hiroyuki Ikeda et al., published in Fujitsu Scientific & Technical Journal, vol. 15, No. 4, pp. 59–76, Dec. 1979.
 Holographic Laser Scanner–Product Brochure for Fujitsu Slimscan™ Holographic Scanner, by Fujitsu Systems of America 1989, (4 pages).
 Laser Scanner–NCR Technology Marketing Division Product Release for NCR 7852 Scanner, published by NCR Corporation. Circa 1988.

* cited by examiner







FIG. 1A








FIG. 1E







FIG. 1F








FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A1




FIG. 6B





FIG. 6A2



REFLECTING FACET FACE
(COMMON TO ALL OF FACETS)

FIG. 6D




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 8-1




FIG. 8-2




FIG. 8-3




FIG. 8-4




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F

$$\left. \begin{aligned} E_0 &= (B + A_0)(C_3 / C_2 - 1) \\ E_1 &= (C_3 / C_2 - 2) + B \\ E_2 &= (C_2 / C_1)(T_1) \end{aligned} \right\}$$

FIG. 8G




FIG. 8H




FIG. 8I




FIG. 8J




FIG. 8K

| R | $C_3 / C_2 - 1$ | $C_3 / C_2 - 2$ | E_3 | C_2 / C_1 |
|---|-----------------|-----------------|----------|-------------|
| 0 | X | X | A_{2L} | 0 |
| 1 | 0 | 0 | A_{2L} | 0 |
| 1 | 0 | 1 | A_{2S} | 0 |
| X | 1 | 1 | X | 1 |

X = DON'T CARE

FIG. 8M




FIG. 8L




FIG. 8N




FIG. 9




FIG. 10





FIG. 11



DATA PACKET NOTATION:
 TRANSMITTER #, GROUP #, TRANSMITTERS #
 xxxxxx DENOTES INTERFERENCE FROM MULTIPLE TRANSMITTERS
 DENOTES DATA THAT WILL PRODUCE ACKNOWLEDGE

FIG. 12




FIG. 13A




FIG. 13AA





FIG. 13B






FIG. 13CC




FIG. 14





FIG. 15B

FIG. 15A






FIG. 16A




FIG. 16B




FIG. 17




FIG. 17A




FIG. 18A




FIG. 18B

**AUTOMATIC OPTICAL PROJECTION
SCANNER FOR OMNI-DIRECTIONAL
READING OF BAR CODE SYMBOLS
WITHIN A CONFINED SCANNING VOLUME**

The present Application is a continuation of patent application Ser. No. 09/861,150, filed on May 18, 2001, now U.S. Pat. No. 6,604,684, which is a continuation of patent application Ser. No. 08/615,054, filed Mar. 12, 1996, now U.S. Pat. No. 6,286,760, which is a continuation-in-part of: application Ser. No. 08/573,949 filed Dec. 18, 1995, now abandoned; application Ser. No. 08/292,237 filed Aug. 17, 1994, now U.S. Pat. No. 5,808,285; application Ser. No. 08/365,193 filed Dec. 28, 1994, now U.S. Pat. No. 5,557,093; application Ser. No. 08/293,493 filed Aug. 19, 1994, now U.S. Pat. No. 5,525,789; application Ser. No. 08/561,479 filed Nov. 20, 1995, now U.S. Pat. No. 5,661,292; application Ser. No. 08/278,109 filed Nov. 24, 1993, now U.S. Pat. No. 5,484,992; application Ser. No. 08/489,305 filed Jun. 9, 1995, now abandoned; application Ser. No. 08/476,069 filed Jun. 7, 1995, now U.S. Pat. No. 5,591,953; and application Ser. No. 08/584,135 filed Jan. 11, 1996, now U.S. Pat. No. 5,616,908. Each of these patents and patent applications is assigned to, and commonly owned by, Metrologic Instruments, Inc. of Blackwood, N.J., and each is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to optical scanning systems and, more particularly, to automatic bar code symbol reading systems.

2. Brief Description of the Prior Art

Bar code symbols are widely utilized in many commercial environments such as point-of-sale (POS) stations in retail stores and supermarkets, inventory and document tracking, and various data control applications. To meet the growing demands of this technological innovation, bar code symbol readers of various types have been developed for scanning and decoding bar code symbol patterns and producing symbol character data for use as input in automated data processing systems.

In general, prior art hand-held bar code symbol readers using laser scanning mechanisms can be classified into two major categories.

The first category of hand-held laser-based bar code symbol readers includes manually-actuated, trigger-operated systems having lightweight laser scanners which can be supported in the hand of the user. The user positions the laser scanner at a specified distance from the object bearing the bar code symbol, manually activates the scanner to initiate reading and then moves the scanner over other objects bearing bar code symbols to be read. Prior art bar code symbol readers illustrative of this first category are disclosed in U.S. Pat. No. 4,387,297 to Swartz; U.S. Pat. No. 4,575,625 to Knowles; U.S. Pat. No. 4,845,349 to Cherry; U.S. Pat. No. 4,825,057 to Swartz, et al.; U.S. Pat. No. 4,903,848 to Knowles; U.S. Pat. No. 5,107,100 to Shepard, et al.; U.S. Pat. No. 5,080,456 to Katz, et al.; and U.S. Pat. No. 5,047,617 to Shepard, et al.

The second category of hand-held laser-based bar code symbol readers includes automatically actuated systems having lightweight triggerless laser scanners which can be supported in the hand of the user. The user positions the laser scanner at a specified distance from the object bearing the bar code, the presence of the object is automatically

detected, the presence of the bar code symbol on the object is detected, and thereafter the detected bar code symbol automatically read. Prior art illustrative of this second category of laser-based bar code symbol reading systems are disclosed in U.S. Pat. Nos. 4,639,606 to Boles, et al., and U.S. Pat. No. 4,933,538 to Heiman, et al.

While prior art hand-held and stationary laser scanners have played an important role in the development of the bar code symbol industry, these devices have suffered from a number of shortcomings and drawbacks. For example, hand-held laser scanners, although portable and lightweight, are not always convenient to use in assembly-line applications where the user processes bar coded objects over an extended period of time, or where the user requires the use of both hands in order to manipulate the objects. In some applications, hand-held laser scanners are difficult to manipulate while simultaneously moving objects or performing other tasks at a point-of-sale terminal. Stationary laser scanners, on the other hand, provide a desired degree of flexibility in many applications by allowing the user to manipulate bar coded objects with both hands. However, by their very nature, stationary laser scanners render scanning large, heavy objects a difficult task, as such objects must be manually moved into or through the laser scan field.

Attempting to eliminate the problems associated with the use of hand-held and stationary laser scanners, U.S. Pat. No. 4,766,297 to McMillan discloses a bar code symbol scanning system which combines the advantages of hand-held and stationary fixed laser scanners into a single scanning system which can be used in either a hands-on or hands-free mode of operation. The bar code symbol scanning system in U.S. Pat. No. 4,766,297 includes a portable hand-held laser scanning device for generating electrical signals descriptive of a scanned bar code symbol. In the "hands-on" mode of operation, a trigger on the hand-held laser scanning device is manually actuated each time a bar code symbol on an object is to be read. The system further includes a fixture having a head portion for receiving and supporting the hand-held laser scanning device, and a base portion above which the head portion is supported at a predetermined distance. In the hands-free mode of operation, the laser scanning device is supported by the fixture head portion above the fixture base portion in order to allow objects bearing bar code symbols to pass between the head and base portions of the fixture. In order to detect the presence of an object between the head and base portions of the fixture, the fixture also includes an object sensor operably connected to the hand-held laser scanning device. When the object sensor senses an object between the head portion and the base portion, the object sensor automatically initiates the hand-held laser scanning device supported in the fixture to read the bar code symbol on the detected object.

While the bar code symbol scanning system of U.S. Pat. No. 4,776,297 permits reading of printed bar code information using either a portable "hands-on" or stationary "hands-free" mode of operation, this system suffers from several significant shortcomings and drawbacks as well. In particular, in the hands-on mode of operation, scanning bar code symbols requires manually actuating a trigger each time a bar code symbol is to be read. In the hands-free mode of operation, scanning bar code symbols requires passing the object bearing the bar code between the head and base portions of the fixture. However, in many instances where both hands are required to manipulate a bar coded object, the object is too large to be passed between the head and base portions of the fixture and thus scanning of the bar code symbol is not possible.

In an attempt to address such problems, several hand-held projection laser scanners have been developed for omnidirectional code symbol scanning. Examples of such systems include the NCR 7890 presentation scanner from the NCR Corporation and the LS9100 omnidirectional laser scanner from Symbol Technologies, Inc. While each of these systems produces an omnidirectional laser scan pattern from a hand-supportable housing and have hands-free and hands-on modes of operation, each of these scanning devices suffer from a number of shortcomings and drawbacks. In particular, the spatial extent of the laser scan pattern produced from each of these scanners frequently results in the inadvertent scanning of code symbols on products placed near the scanner during its hands-free mode of operation. In the hands-on mode of operation, it is virtually impossible to use the scanners to read bar code symbol menus provided in diverse application environments. Moreover, in each of these scanner designs, the scanner is tethered to its base unit by a power/signal cord. In the hands-on operational mode, the user is required to handle the scanner housing in an awkward manner, resulting in strain and fatigue and thus a decrease in productivity. In addition, the control structure provided in each of these hand-held projection scanners operates the scanner components in a manner which involves inefficient consumption of electrical power, and prevents diverse modes of automatic code symbol reading which would be desired in portable scanning environments.

Thus, there is a great need in the bar code symbol reading art for a bar code symbol reading system which overcomes the above described shortcomings and drawbacks of prior art devices and techniques, while providing greater versatility in its use.

OBJECTS AND SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the invention to provide an automatic bar code symbol reading system, wherein a collimated scanning pattern is projected from the hand-supportable device about a projection axis, and intersects within a confined scanning volume so that bar code symbols disposed within the scanning volume can be read omnidirectionally, while preventing an inadvertent scanning of bar code symbols outside of the scanning volume.

It is another object of the present invention to provide such an automatic bar code symbol reading system, wherein the projection axis about which the confined scanning volume extends is substantially coplanar with the longitudinal axes of the head and handle portions of the hand-supportable housing.

It is another object of the present invention to provide such an automatic bar code symbol reading system, wherein the center-of-mass of the device is located within the hand-supportable portion to provide easy handling consistent with ergonomic design principles.

It is another object of the present invention to provide such an automatic bar code symbol reading system, in which one or more bar code symbols on an object can be automatically read in a consecutive manner.

A further object is to provide such an automatic bar code symbol reading device, in which the automatic hand-supportable bar code (symbol) reading device has an infrared light object detection field which spatially encompasses at least a portion of its visible laser light scan field along the operative scanning range of the device, thereby improving the laser beam pointing efficiency of the during the automatic bar code reading process of the present invention.

It is a further object of the invention to provide an automatic bar code symbol reading system having an automatic optical scanning device which can be used at a point-of-sale (POS) station as either a portable hand-supported scanner when operated in its automatic hands-on mode of operation, or as a stationary projection scanner when operated in its automatic hands-free mode of operation.

Another object of the invention is to provide such an automatic bar code reading system in which a support frame is provided for supporting the housing of the device in a selected mounting position, and permitting gripping of the handle portion of the hand-supportable housing prior to removing it from the support frame.

It is another object of the invention to provide an automatic bar code reading device which has both long and short-range modes of bar code symbol reading automatically selectable by placing the device within its support stand and removing it therefrom. With this particular embodiment of the present invention, the automatic bar code symbol reading system can be used in various bar code symbol reading applications, such as, for example, charge coupled device (CCD) scanner emulation and bar code "menu" reading in the hands-on short-range mode of operation, and counter-top projection scanning in the hands-free long-range mode of operation.

An even further object of the invention is to provide an automatic bar code reading device which prevents multiple reading of the same bar code symbol due to dwelling of the laser scanning beam upon a bar code symbol for an extended period of time.

A further object of the invention is to provide a point-of-sale station incorporating the automatic bar code symbol reading system of the invention.

It is a further object of the invention to provide an automatic bar code reading device having a control system which has a finite number of states through which the device may pass during its automatic operation, in response to diverse conditions automatically detected within the object detection and scan fields of the device.

Another object of the invention is to provide a portable, automatic bar code symbol reading device, wherein the laser beam scanning motor is operated at a lower angular velocity during its object detection state of operation in order to conserve power consumption and facilitate rapid steady-state response when the device is induced to its bar code symbol detection and bar code symbol reading states of operation.

Another object of the invention to provide a portable, automatic bar code symbol reading device, wherein the laser beam scanning motor is not energized during its object detection state of operation in order to conserve power consumption, and is momentarily overdriven to facilitate rapid steady-state response when the device undergoes a transition from the object detection state to the bar code symbol detection state of operation.

Another object of the invention to provide a novel mechanism for mounting a laser scanning platform within the head portion of an automatic hand-supportable projection laser scanning device.

Another object of the invention is to provide a novel laser scanning platform for use within an automatic portable projection laser scanning device.

Another object of the invention is to provide a bar code symbol reading system having at least one bar code symbol

5

reading device which, after each successful reading of a code symbol, automatically synthesizes and then transmits a data packet to a base unit positioned within the data transmission range of the bar code symbol reading device, and upon the successful receipt of the transmitted data packet and recovery of symbol character data therefrom, the base unit transmits an acoustical acknowledgement signal that is perceptible to the user of the bar code symbol reading device situated within the data transmission range.

A further object of the invention is to provide such a system with one or more automatic (i.e., triggerless) hand-supportable laser-based bar code symbol reading devices, each of which is capable of automatically transmitting data packets to its base unit after each successful reading of a bar code symbol.

A further object of the invention is to provide such a bar code symbol reading system in which the bar code symbol reading device can be used as either a portable hand-supported laser scanner in an automatic hands-on mode of operation, or as a stationary laser projection scanner in an automatic hands-free mode of operation.

A further object of the invention is to provide such a bar code symbol system in which the base unit contains a battery recharging device that automatically recharges batteries contained in the device when the device is supported within the base unit.

It is another object of the invention to provide such an automatic bar code symbol reading system with a mode of operation that permits the user to automatically read one or more bar code symbols on an object in a consecutive manner.

A further object of the invention is to provide such an automatic bar code symbol reading system, in which a plurality of automatic bar code symbol reading devices are used in conjunction with a plurality of base units, each of which is mated to a particular bar code symbol reading device.

A further object of the invention is to provide such an automatic bar code symbol reading system, in which radio frequency (RF) carrier signals of the same frequency are used by each bar code symbol reading device to transmit data packets to respective base units.

A further object of the invention is to provide such an automatic bar code symbol reading system, in which a novel data packet transmission and reception scheme is used to minimize the occurrence of data packet interference at each base unit during data packet reception.

A further object of the invention is to provide such an automatic bar code symbol reading system, in which the novel data packet transmission and reception scheme enables each base unit to distinguish data packets associated with consecutively different bar code symbols read by a particular bar code symbol reading device, without the transmission of electromagnetically-modulated data packet acknowledgment signals after receiving each data packet at the base unit.

A further object of the invention is to provide such an automatic bar code symbol reading device, in which the automatic bar code reading device has an infrared (IR) based object detection field which spatially encompasses at least a portion of its visible laser light scan field along the operative scanning range of the device, thereby improving the laser beam pointing efficiency of the device during the automatic bar code reading process of the invention.

Another object of the invention is to provide such an automatic bar code symbol reading system, in which the

6

base unit has a support frame that supports the housing of the device in a selected mounting position, wherein the device is also supportable in the hand of a user, and wherein the support frame permits hand gripping of the handle portion of the hand-supportable housing prior to removing it from the support frame.

An even further object of the invention is to provide an automatic bar code reading device which prevents multiple reading of the same bar code symbol due to dwelling of the laser scanning beam upon a bar code symbol for an extended period of time.

It is a further object of the invention to provide an automatic bar code reading device having a control system which has a finite number of states through which the device may pass during its automatic operation, in response to diverse conditions automatically detected within the object detection and scan fields of the device.

It is yet a further object of the invention to provide a portable, fully automatic bar code symbol reading system which is compact, simple to use and versatile.

Yet a further object of the invention is to provide a novel method of reading bar code symbols using an automatic laser scanning device.

A further object of the invention is to provide a point-of-sale station incorporating the automatic bar code symbol reading system of the present invention.

These and further objects of the invention may be realized in any of various forms, many of which are described below in conjunction with the Detailed Description of the Preferred Embodiments and set forth in the appended Claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the Objects of the Present Invention, the Detailed Description of the Illustrated Embodiments of the Present Invention should be read in conjunction with the accompanying drawings, wherein:

FIG. 1A is an elevated perspective view of an illustrative embodiment of the automatic bar code symbol reading system hereof, with its hand-supportable bar code symbol reading device shown supported within the scanner support stand portion of its matching base unit, and arranged for automatic hands-free operation;

FIG. 1B is an elevated perspective view of the illustrative embodiment of the automatic bar code symbol reading device hereof, shown being used in its automatic hands-on mode of operation;

FIG. 1C is an elevated side view of the illustrative embodiment of the automatic bar code symbol reading device hereof, illustrating that the mass balance of the hand-supportable bar code symbol reading device has been designed to minimize torques about the point of pivot of the housing about the user's index finger in order to maximize its ergonomic handling efficiency during automatic hands-on, omni-directional laser scanning operations;

FIG. 1D is an elevated side view of the illustrative embodiment of the automatic bar code symbol reading device hereof, illustrating the spatial alignment of the longitudinal axis of the head portion of the scanner and the projection axis of the laser scanning platform contained therein;

FIG. 1E is an elevated side view of the illustrative embodiment of the automatic bar code symbol reading device hereof, shown supported within the scanner support stand portion of its matching base unit, arranged for automatic hands-free operation in a first scanning position;

FIG. 1G is a diagrammatic representation of the structure of the base unit which may include a locking mechanism.

FIG. 1F is an elevated side view of the illustrative embodiment of the automatic bar code symbol reading device hereof, shown supported within the scanner support stand portion of its matching base unit, arranged for automatic hands-free operation in a second scanning position;

FIG. 2A is an elevated side view of the illustrative embodiment of the automatic bar code symbol reading device of the invention, illustrating the spatial relationship between the object detection and scan fields of the device, and the long and short-ranges of programmed object detection, bar code presence detection, and bar code symbol reading;

FIG. 2B is a plan view of the automatic bar code symbol reading device of FIG. 2A;

FIG. 3A is an elevated, cross-sectional side view of the automatic bar code symbol reading device of the invention, taken along its longitudinal axis, showing the various components contained therein;

FIG. 3B is an elevated, end view of the automatic bar code symbol reading device of FIG. 3A, showing the various components contained therein;

FIG. 4 is an elevated side view of the laser scanning platform of the present invention realized on its shock-mounted optical bench, removed from the housing of the hand-supportable bar code symbol reading device of the present invention;

FIG. 5A is a plan view of the optical bench of the laser scanning platform of FIG. 4, shown with the stationary array of mirrors, rotating polygonal mirror and motor removed therefrom for illustrative purposes;

FIG. 5B is another view of the laser scanning platform of FIG. 4;

FIG. 5C is an elevated side view of the optical bench of FIG. 5A, shown with the stationary mirror support bracket removed therefrom for illustrative purposes;

FIG. 5D is schematic diagram illustrating the physical layout of components on the analog signal processing board supported on the optical bench of the laser scanning platform of FIG. 4;

FIGS. 6A1 and 6A2 provide a geometrical optics model of the stationary mirror array of the laser scanning platform of the illustrative embodiment, graphically defining the various angles used to configure the stationary mirrors relative to the central reference plane thereof;

FIG. 6B is an inclination angle diagram and table showing the angle of the stationary mirror as referenced to the plane of the optical bench.

FIG. 6C is a geometrical optics model of the stationary mirror array of the laser scanning platform of the illustrative embodiment, graphically defining the various physical dimensions stationary mirrors relative to the central reference plane thereof;

FIG. 6D is a geometrical optics model of the stationary mirror array of the laser scanning platform of the illustrative embodiment, graphically defining the various physical dimensions stationary mirrors relative to the central reference plane thereof;

FIGS. 7A and 7B are cross-sectional views of the 3-D laser scanning volume of the illustrative embodiment, taken parallel to the light transmissive window at about 1.0" and 5.0" therefrom;

FIGS. 8-1 to 8-4 together comprise a system block functional diagram of the automatic bar code symbol read-

ing system of the present invention, illustrating the principal components integrated with the control (sub)system thereof;

FIG. 8A is a functional logic diagram of the system override signal detection circuit in the Application Specific Integrated Circuit (ASIC) chip in the automatic bar code symbol reading engine of the present invention;

FIG. 8B is a functional logic diagram of the oscillator circuit in the ASIC chip in the automatic bar code symbol reading engine of the present invention;

FIG. 8C is a timing diagram for the oscillator circuit of FIG. 8B;

FIG. 8D is a block functional diagram of the object detection circuit (i.e., system activation means) in the ASIC chip in the automatic bar code symbol reading engine of the present invention;

FIG. 8E is a functional logic diagram of the first control circuit (C_1) of the control system of the present invention;

FIG. 8F is a functional logic diagram of the clock divide circuit in the first control circuit C_1 of FIG. 8E;

FIG. 8G is table setting forth Boolean logic expressions for the enabling signals produced by the first control circuit C_1 ;

FIG. 8H is a functional block diagram of the analog to digital (A/D) signal conversion circuit in the ASIC chip in the bar code symbol reading engine of the present invention;

FIG. 8I is a functional logic diagram of the bar code symbol (Presence) detection circuit in the ASIC chip in the bar code symbol reading engine of the present invention;

FIG. 8J is a functional logic diagram of the clock divide circuit in the bar code symbol detection circuit of FIG. 8I;

FIG. 8K is a schematic representation of the time window and subintervals maintained by the bar code symbol detection circuit during the bar code symbol detection process;

FIG. 8L is a functional logic diagram of the second control circuit (C_2) in the ASIC chip in the automatic bar code symbol reading engine of the present invention;

FIG. 8M is Boolean logic table defining the functional relationships among the input and output signals into and out from the second control circuit C_2 of FIG. 8N;

FIG. 8N is a schematic representation of the format of each data packet transmitted from the data packet transmission circuit of FIG. 9.

FIG. 9 is a functional block diagram of the data packet transmission circuit of the bar code symbol reading system of the present invention;

FIG. 10 is a schematic representation illustrating several groups of data packets transmitted from the bar code symbol reading device hereof in accordance with the principles of data packet transmission and reception scheme of the present invention;

FIG. 11 is a schematic representation of an exemplary set of groups of data packet pseudo randomly transmitted from neighboring bar code symbol reading devices, and received at one base unit in physical proximity therewith;

FIG. 12 is a schematic representation of an exemplary set of data packets simultaneously transmitted from three neighboring bar code symbol reading devices of the present invention, and received at the associated base units assigned thereto;

FIGS. 13A to 13AA, 13B, 13C, and 13CC, taken together, show a high level flow chart of the control process performed by the control subsystem of the bar code symbol reading device, illustrating various modes of object detection, bar code presence detection and bar code symbol reading;

FIG. 14 is a state diagram illustrating the various states that the automatic hand-supportable bar code symbol reading device of the illustrative embodiment may undergo during the course of its programmed operation;

FIG. 15A is a perspective view of the scanner support stand housing of the countertop base unit of the present invention;

FIG. 15B is a perspective view of the base plate portion of the countertop base unit of the present invention;

FIG. 16 is a functional block diagram of the data packet receiving and processing circuitry and the acknowledgment signal generating circuitry of the present invention realized on the printed circuit board in the base unit shown in FIGS. 15A to 15C;

FIG. 16A is a functional block diagram of the radio receiver subcircuit of the data packet receiving circuit of FIG. 16;

FIG. 16B is a functional block diagram of the digitally controlled acoustical acknowledgment signal generating circuit of the present invention;

FIGS. 17 and 17A together comprise a flow chart illustrating the steps undertaken during the control process carried out in the base unit of FIG. 15A; and

FIG. 18A is perspective view of a point-of-sale (POS) station according to the present invention, showing the automatic hand-supportable bar code symbol reading device hereof being used in its automatic "hands-off" long-range mode of operation; and

FIG. 18B is a perspective view of the POS station of FIG. 18A, showing the symbol reading device hereof being used in its automatic "hands-on" short-range mode of operation.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in FIGS. 1 to 3B, automatic bar code symbol reading system 1 of an illustrative embodiment of the present invention comprises an automatic (i.e., triggerless) portable bar code symbol reading device 2 operably associated with a base unit 3 having a scanner support stand 4 pivotally connected thereto, for releasably supporting the automatic bar code symbol reading device 2 at any one of a number of positions above of a counter surface at a Point of Sale (POS) station. In the preferred embodiment, the bar code symbol reading device 2 is operably connected with its the base unit 3 by way of a one way electromagnetic link 5 that is momentarily created between bar code symbol reading device 2 and its mated base unit 3 after the successful reading of each bar code symbol by the bar code symbol reading-device. Operable interconnection between the base unit and a host system (e.g., electronic cash register system, data collection device, etc.) 6 is achieved by a flexible multiwire communications cable 7 extending from the base unit and plugged directly into the said data-input communications port of the host computer system 6. In the illustrative embodiment, electrical power from a low voltage direct current (DC) power supply (not shown) is provided to the base unit by way of a flexible power cable 8. Notably, this DC power supply can be realized in host computer system 6 or as a separate DC power supply adapter pluggable into a conventional 2- or 3-prong electrical socket. In other embodiments of the present invention, cables 7 and 8 can be integrated to provide a single flexible, multi-wire cable for transmission of power to the base unit and data to the host system. As will be described in greater detail hereinafter, a rechargeable battery power supply unit is

contained within the handle portion of the bar code symbol reading device 2 in order to energize the electrical and electro-optical components within the device.

As illustrated in FIGS. 1A through 1B, scanner support stand 4 is particularly adapted for receiving and supporting portable bar code symbol reading device 2 without user support, thus providing a stationary, automatic hands-free mode of operation. In general, portable bar code reading device 2 includes an ultra-light weight hand-supportable housing 9 having a head portion 9A and a contoured handle portion 9B. As will be described in greater detail hereinafter, head portion 9A encloses electro-optical components which are arranged in a novel scanning platform 10 of ultra compact construction which renders possible the production of a highly collimated scanning pattern 11 through light transmission window 12 for the purpose of scanning bar code symbols on objects within a narrowly confined scanning (i.e., 3-D scan field) volume 13, while preventing unintentional scanning of bar code symbols on objects located outside thereof at POS stations. Thus, by minimizing the amount of counter-space that must be clear (i.e. free) of bar coded items at point of sale (POS) stations, the laser scanner of the present invention provides retailers with greater counter-space availability for displaying merchandise and the like, yet without sacrificing the increase in check-out performance and worker productivity associated with the use of bar code symbol scanners at POS stations.

As illustrated in FIGS. 1 through 1C, the base unit 3 includes a base portion 14 which can be realized in a variety of different ways. For example, the base portion 14 can be realized as a compact stand for support upon a countertop surface as shown in FIG. 18, or it can be realized as a support mount for vertical wall-mounting. In either embodiment, the function of the scanner stand 4 is to support the device in any one of a plurality of positions above a workspace 19 which may be a counter surface in POS applications. With this arrangement, the highly collimated scanning pattern 11 can be projected about the projection axis 17 above the counter surface in any one of a plurality of orientations corresponding to the plurality of positions.

As shown in FIGS. 1A and 15A, base portion 14 contains electronic circuitry realized on a PC board 16 for carrying out various types of functions, namely: reception of electrical power from the host system and coupling electrical power to the rechargeable battery contained within the hand-supportable housing; reception of data packets transmitted from the automatic bar code symbol reading device, and processing the same for data recovery; generation of acoustical and/or optical acknowledgment signals; and transmission of symbol character data to the host system. Each of these functions will be described in greater detail hereinafter with reference to FIGS. 15A and 15B.

As illustrated in FIGS. 1B and 1C in particular, the head portion 9A continuously extends into contoured handle portion 9B at an obtuse angle α which, in the illustrative embodiment, is about 115 degrees. It is understood, however, that in other embodiments obtuse angle α may be in the range of about 100 to about 150 degrees. As illustrated in FIG. 1C, the mass balance of the device is particularly designed so that when the device is held within the user's hand, the index finger of the user is disposed beneath the head portion of the housing, and provides a pivot point about which there is a substantially zero torque acting upon the device, preventing it from rotating in either direction about the index finger. Instead, the resultant force distribution acting upon the user's hand is aligned in the direction of gravitational forces, as indicted in FIG. 1C. The effect of this

11

mass-balanced scanner design is to minimize the torque imposed on the user's wrists and forearms while using the bar code symbol reading device in the hands-on mode of operation. This, in turn, minimizes the amount of energy which the user must expend during hands-on scanning operations, thereby reducing wrist and arm fatigue and increasing worker productivity. In addition to the above advantages, the hand-supportable housing hereof is sculptured (i.e., form-fitted) to the human hand so that automatic hands-on scanning is rendered easy and effortless. Also, the ergonomic housing design eliminates the risks of musculoskeletal disorders, such as carpal tunnel syndrome, which can result from repeated biomechanical stress commonly associated with pointing prior art gun-shaped scanners at bar code symbols, squeezing a trigger to activate the laser scanning beam, and then releasing the trigger.

As best shown in FIGS. 1G, 15A and 15B, stand portion 4 of the base unit 3 is pivotally supported with respect to the base portion by way of pivot pins 22A and 22B. In order to releasably hold the stand portion of the base unit relative to the base portion thereof in any selected one of a large number of scanning positions, a releasable stand-locking mechanism 23 is provided. As shown in FIG. 1G, the locking mechanism is realized as a set of projections 24 formed on the inside surface of the support arms 4A of the stand portion of the base unit, and a projection-catch 25 formed on the adjacent surface of the base portion. These structure features of the base unit are shown in FIG. 1G. The function of the projection catch 25 is to releasably engage one of the projections 24 associated with the selected scanning position. Gentle rotation of the head portion of the scanner while supported in its stand causes the present projection caught in the projection-catch 25 to release therefrom, allowing the scanner to be repositioned as desired. At the resulting scanning position, the corresponding projection 24 automatically engages with the projection-catch 25 and locks the stand portion of the base unit relative to the base portion thereof. In addition, to allow the base unit to easily rotate relative to its support surface, the bottom of the base portion is realized as a turntable structure that allows its bottom section 26A to be stationary relative to the support surface (i.e. countertop) 27, while the upper section 26B is fixed relative to the balance of the base portion of the base unit. A pivot 26C is used to pivotally connect the upper and lower sections together for easy rotation of the base unit relative to the support surface.

In FIGS. 1E and 1F, the automatic bar code symbol reading system of the present invention is arranged in two extreme scanning configurations during the automatic hands-off mode of system operation. In these different scanning configurations, the stand portion of the base unit is arranged differently with respect to the base portion of the base unit. In FIG. 1E, the stand portion of the base unit is shown supporting the hand-supportable projection scanning device hereof so that its scanning volume is projected in a direction slightly off-parallel to the counter surface upon which the base unit is supported. In this hands-off scanning configuration, code symbols on large objects can be easily scanned by simply presenting the code symbol to the narrowly-confined scanning volume 13 projected along the "pointing direction" (i.e. longitudinal axis) of the head portion of the scanner housing. In FIG. 1F, the stand portion of the base unit is shown supporting the hand-supportable projection scanning device hereof so that its scanning volume is projected downwardly, in a direction passing through the counter surface upon which the base unit is supported. In this hands-off scanning configuration, code symbols on

12

small objects can be easily scanned by simply presenting to the code symbol to the narrowly-confined scanning volume 13 projected being projected beneath the head portion of the scanner housing.

As illustrated in FIGS. 2A through 3B, the head portion 9A of the hand-supportable housing has a light transmission aperture 12A formed in the front portion thereof. As shown, the light transmission window 12 is mounted over the entire light transmission aperture. In the preferred embodiment, the spectral transmission characteristics of the light transmission window are such that all wavelengths greater (i.e. longer) than slightly less than 670 nm (e.g. longer than 665 nm) are permitted to exit and enter the interior volume of the housing with minimum attenuation. As a result of such characteristics, the visible laser line at 670 nanometers and the infra-red (IR) spectral line at 870 nm (produced from the object sensing circuitry hereof) are allowed to propagate through the transmission window, out of the head portion of the housing, reflect from an object/bar code surface, and return through the transmission window. Notably, all other surfaces of the hand supportable housing are opaque to electromagnetic radiation in the visible band.

As illustrated in FIGS. 2, and 2A, in particular, the bar code symbol reading device 2 generates from its laser scanning platform 10, two different types of fields external to its hand-supportable housing. As explained below, these fields function to carry out a novel bar code symbol reading process according to the principles of the present invention. The first field, referred to as the "object detection field", indicated by broken and dotted lines 30, is provided external to the housing for detecting energy reflected off an object (bearing a bar code symbol) located in the object detection field. As shown in FIGS. 2A and 2B, the second field 30, referred to as the "scan field", has a multiplicity of laser beam scanning planes contained within narrowly confined scanning volume 13 projected external to the head portion of the housing. The function of the scanning volume is to scan a bar code symbol on an object automatically detected in the object detection field. In the preferred embodiment, bar code symbol scanning is achieved using a scanned visible laser beam which, after reflecting off the bar code symbol in the scan field, produces laser scan data that is collected for the purpose of automatically detecting the bar code symbol and subsequently reading (i.e., scanning and decoding) the same.

In general, detected energy reflected from an object during object detection can be optical radiation or acoustical energy, either sensible or non-sensible by the user, and may be either generated from the automatic bar code reading device or an external ambient source. However, as will be described in greater detail hereinafter, the provision of such energy is preferably achieved by transmitting a wide beam of pulsed infrared (IR) light away from transmission aperture 11, in a direction substantially parallel to longitudinal axis 16 of the hand-supportable housing. In the preferred embodiment, the object detection field, from which such reflected energy is collected, is designed to have a narrowly diverging pencil-like geometry of three-dimensional volumetric expanse, which is spatially coincident with at least a portion of the transmitted infrared light beam. This feature of the present invention ensures that an object residing within the object detection field will be illuminated by the infrared light beam, and that infrared light reflected therefrom will be directed generally towards the transmission aperture of the housing where it can be automatically detected to indicate the presence of the object within the object detection field. In response, a visible laser beam is automatically generated within the interior of the bar code

symbol reading engine, projected through the light transmission aperture of the housing and repeatedly scanned across the scan field, within which at least a portion of the detected object lies. At least a portion of the scanned laser light beam will be scattered and reflected off the object and directed back towards and through light transmissive window **11** for collection and detection within the interior of the bar code symbol reading engine, and subsequently processed in a manner which will be described in detail hereinafter.

To ensure that the user can quickly align the visible laser beam with the bar code symbol on the detected object, the object detection field of the preferred embodiment is designed to spatially encompass at a significant portion of the 3-D scanning volume along the operative scanning range of the device, as illustrated in FIGS. **2A** and **2B**, for the first illustrative embodiment of the present invention. This structural feature of the present invention improves the laser beam pointing efficiency of the device during the automatic bar code symbol reading process.

As best shown in FIGS. **3A** and **3B**, the laser scanning platform laser (i.e., scanning engine) **10** of the present invention is mounted within the head portion of the hand-supportable housing by way of a three-point shock-absorbing mounting mechanism, which will be described in greater detail hereinbelow. In the illustrative embodiment, the hand-supportable housing is realized as a five-piece split-housing construction comprising: a first housing portion **9C** carrying three spaced-apart mounting posts **29A**, **29B** and **29C**, and providing a battery storage bay **30** for storage of a (rechargeable) battery **32**; a second housing half **9D** providing posts **31A** and **31B** which engage with support posts **29A** and **29B** when the first and second housing halves are brought together, a battery cover **9E** for placement over the battery storage bay **30**; a housing end cap **9F** for placement over the ends of the first and second housing halves; and a housing bumper **9G** for supporting the light transmission window **12** and holding securely together the front ends of the first and second housing halves when the subcomponents of the housing are assembled together. Provided within the battery storage bay, is an electrical socket **33** designed to receive rechargeable battery **32** when it is installed within the bay when the bay cover **9E** is removed. An electrical wire harness **34** is used to connect the battery socket **33** to a printed circuit (PC) board **50** supported upon the laser scanning platform **10**, carrying digital scan data processing and control circuitry. Apertures **35A** and **35B** are formed in the end portion of the housing handle to allow electrodes **51A** and **51B** on the battery to establish electrical contact with charging electrodes **52A** and **52B** provided within the support bay **60** of the stand portion of the base unit when the scanning device is operated in its hands-free mode of operation. Preferably, the above-described housing subcomponents are made from a rugged, lightweight plastic material using injection-molding techniques well known in the art.

As will be described in greater detail hereinafter, the data packet transmission circuit of copending application Ser. No. 08/292,237 is realized on PC board **50**, along with the microprocessor used to implement symbol decoding, data formatting and system control functions. Electrical power supplied from rechargeable battery **32** is provided to the digital signal processing/control board **50** by way of flexible wire harness **34**. As shown, a transmitting antenna **53** is operably connected to the data packet transmission circuit on the digital signal processing board and is mounted within hand-supportable housing **9** for transmission of a data packet

modulated RF carrier signal. The structure and the functionalities of the automatic bar code symbol reading system hereof will be described in greater detail hereinafter with reference to FIGS. **8** to **14**.

In FIG. **4**, the laser scanning platform **10** is shown removed from its housing. As shown, the laser scanning platform comprises an assembly of subcomponents assembled upon an optical bench **34** with respect to a central longitudinal reference plane **35** referenced in FIGS. **5A** through **5B**, in particular. This subcomponent assembly comprises: a scanning polygon **36** having four light reflective surfaces **36A**, **36B**, **36C** and **36D**, each disposed at an tilt angle α with respect to the rotational axis of the polygon; an electrical motor **37** mounted on the optical bench, and having a rotatable shaft on which polygon **36** is mounted for rotationable movement therewith; an array of stationary mirrors **38A**, **38B**, **38C**, **38D** and **38E** fixedly mounted with respect to the optical bench; a laser beam production module **39**, fixedly mounted above the rotating polygon, for producing a laser beam having a circularized beam cross-section, and essentially free of astigmatism along its length of propagation; an analog signal processing board **40**, fixedly mounted over the rotating polygon, and carrying a photodetector **41** for detecting reflected laser light and producing analog scan data signals, and analog signal processing control circuits **42** for performing various functions, including analog scan data signal processing; a light collecting mirror **43**, disposed at a height above the central stationary mirror **38A**, for collecting light rays reflected off the rotating polygon and focusing the same onto the photodetector on the analog board; and a beam directing surface **44**, realized as a mirror chip mounted on the light collecting mirror **38A**, for directing the laser beam from the laser beam production module to the rotating polygon disposed therebeneath. As shown, these subcomponents are mounted relative to the optical bench **35** according to the Specifications set forth in FIGS. **6A** through **6B**.

In FIGS. **5A** through **5D**, the subcomponents of the laser scanning platform are shown in greater detail. In particular, optical bench **34** is shown in FIG. **5A** with the scanner motor **37** and stationary mirror elements **38A** through **38E** removed for illustration purposes. As shown, stationary mirror bracket **45** is mounted upon the optical bench **34** and has five mirror support elements **45A** through **45B**, disposed beneath the locations of their respective mirrors **38A**, **38B**, **38C**, **38D** and **38E**. As shown in FIG. **5B**, the analog signal processing board **40** is disposed above the polygonal mirror **36m** and extends at an acute angle with respect to the plane of the optical bench. This analog signal processing board **40** is supported in this position and orientation by a pair of support bracket **46A** and **46B**. These support brackets **46A** and **46B**, in turn, are supported by a pair of support brackets **47A** and **47B** mounted to the middle portion of the optical bench **34**, as shown in FIGS. **5A** and **5B**. As illustrated in FIG. **4**, the position of these support posts are slightly forward of the rotating axis of the polygon motor.

As best shown in FIG. **5A**, the transverse axis of the light collecting mirror **43** is perpendicular to the central transverse plane of the optical bench. The stationary light reflective surface has a transverse axis extending substantially perpendicularly with respect to the central reference plane **34**. Stationary light reflective surfaces **38B** and **38D** are symmetrically disposed on opposite sides of the central reference plane, respectively, and immediately adjacent stationary light reflective surface **38C**. Stationary light reflective surfaces **38A** and **38E** are symmetrically disposed on opposite sides of the central reference plane, and immedi-

ately adjacent stationary light reflective surfaces **38B** and **38D**, respectively, and adjacent rotating polygon **36**.

As best illustrated in FIG. 5C the angle of declination of the light collecting mirror is selected so that the incident laser beam thereon from the laser beam production module **38** is redirected towards the rotating polygon during laser beam scanning operations. The focal length of the light collecting mirror is selected so that collected light rays from the mirror are focused upon the photodetector **41**, centrally mounted upon the analog signal processing board **40**. In the illustrative embodiment, light focusing mirror **43** is realized from ground-polished glass or molded plastic coated with a mirror-finish provided by vapor deposition.

As shown in FIG. 5C, the photodetector **41** and light collecting mirror **43** are aligned along a common optical axis which is disposed within the central longitudinal plane. As shown in FIG. 5D, the photodetector **41** is mounted on the analog signal processing board **40** along with signal processing circuits and signal connector elements **300** and **301**, namely: optical filters **186A**; visible laser diode drive circuitry **178**; motor drive circuitry **181**; IR preamp circuitry **187**; IR transmit and receive circuitry **106**; signal processing circuitry **IC2**; scan signal preamplification circuitry **187**; microprocessor port connector **300**; and VLD/motor port connector **301**. The function of such components will be described in greater detail hereinafter.

The laser beam production module **39** of the laser scanning platform hereof may be realized in a variety of ways. Preferably, each embodiment thereof comprises a visible laser diode for producing a visible laser beam, and associated optics for circularizing the laser beam and eliminating astigmatism therefrom along its direction of propagation. In the illustrative embodiment, the associated optics comprises an aspheric collimating lens, a beam circularizing prism, and a holographic light diffractive grating configured in such a manner that the above-described functions are realized during laser beam production. The manner in which such a production module can be constructed without the use of aperture stops is taught in copending application Ser. No. 08/573,949, incorporated herein by reference.

The particular parameters used to configure the optical components of the laser scanning module are schematically represented in FIGS. 6A1 through 6D. In FIGS. 6A1 and 6A2, a geometrical optics model is provided for the illustrative embodiment of the laser beam scanning platform of the present invention. Within this geometrical optics model, stationary mirror surface **38A** through **38E** are designated by surface parameters **S1** through **S5**, respectively. Each of these mirror surfaces is located about the central longitudinal plane **35** of the system, which functions as a reference plane. In the illustrative embodiment, the distance between the rotational axis of the polygon and the base of the central mirror surface **S3** is 34 millimeters in the illustrative embodiment, whereas the base-to-base distance between mirror surfaces **S1** and **S5** is about 35 millimeters.

As shown in the generational optics model, the angles of inclination of the four mirrored surfaces on the polygon **36A**, **36B**, **36C**, **36D** are set forth in the Table of FIG. 6B. The angle of elevation ϕ (i.e. bend) of each of the stationary mirrors **38A**, **38B**, **38C**, **38D** and **38E** are listed in Table of FIG. 6A1. As shown in FIG. 6B, the angle of inclination of the stationary mirrors is referenced with respect to the plane of the optical bench. As shown in FIG. 6A1, the angle of twist α for each stationary mirror is referenced relative to the central longitudinal plane **35**. The twist angle for the stationary mirrors are set forth in the Table of FIG. 6A1.

Notably, as central stationary mirror **S3** is disposed transversely relative to the central longitudinal plane, the twist angle for this stationary mirror is 90° . The laterally disposed stationary mirrors **S2** and **S4** have the same twist angle of 43.75° , whereas stationary mirrors **S1** and **S5** have the same twist angle of 40.50° .

The heightwise and widthwise dimensions of the stationary reflective surfaces, in part, determine the scanline length of the scanlines within the scan field. These dimensions are indicated in FIG. 6C for the illustrative embodiment. Notably, the perimetrical dimensions of these stationary mirrors are irregular in order to form a tightly-nested stationary mirror array arranged about the rotating polygon **36**. The exact surface dimensions are indicated in FIG. 6C. The heightwise and widthwise dimensions of the mirrors on the rotating polygon are indicated in FIG. 6D. When constructed in accordance with the Specifications disclosed herein, the laser scanning platform of the illustrative embodiment will produce a highly collimated set of scanning planes which extend from the light transmission window and intersect about the projection axis **17** to form a highly collimated scanning pattern within a narrowly-confined 3-D scanning volume thereabout. Two-dimensional cross-section characteristics of the resulting laser scanning pattern at about 1.5 and 6 inches from the transmission window are shown in FIGS. 7A and 7B.

When assembled and configured as described above, the laser scanning platform **10** is mounted with the upper and lower halves of the hand-supportable housing **9A** and **9B**. Mounting is achieved by way of resiliently securing shock-mounting support posts **29A**, **29B** and **29C** to corresponding mounting holes formed within the optical bench **35** using rubber grommets and screws. As shown in FIG. 7, the assembled laser scanning platform (i.e. engine) is installed within the housing in a manner described above. As shown, a second printed circuit (PC) board **49** is mounted to the underside of the plastic optical bench by way of mechanical fasteners known in the art. The function of the second PC board **49** is to provide a substrate upon which the decode/control processor, RF data packet transmission circuitry and power distribution circuitry of the laser scanning engine hereof are realized. In order that the shock-absorbing mounting system can operate properly, it is important that sufficient clearance is provided between the outermost extensions of the scanning platform and the interior wall surface of upper portion of the housing. In this way, the scanning platform is permitted undergo gross displacements in the directions of the dominant oscillatory modes of system when the device is dropped onto the floor, knocked into solid objects and the like under normal or otherwise expected operating environments.

Having described the physical construction of the laser scanning engine **10** of the present invention, it is appropriate at this juncture to describe in greater detail the manner in which the laser scanning pattern is produced from the laser scanning platform hereof.

Upon detection of an object within the object detection field **30**, a laser beam is produced from the laser beam production module **39** and is directed towards beam directing surface **44** mounted on the light collecting mirror **43**. The laser beam reflects from the beam directing surface **44** towards the mirrored facets on the rotating scanning polygon **36**. As the polygon spins, the incident laser beam reflects off the rotating mirrors **36A** through **36D** and sweeps the laser beam about its rotational axis along a plurality of different paths which intersect the stationary array of mirrors **38A** through **38E** on the optical bench. During each revolution of

the polygon, the laser beam reflects off the rotating mirrors and therewith is repeatedly swept across the array of stationary mirrors thereby producing first, second, third, fourth and fifth groups of plural scan lines, respectively. These plural groups of scanlines shown in FIGS. 7A and 7B are projected out through the light transmission window and intersect about the projection axis 17 extending from the light transmission window, and within the narrowly confined scanning volume 13. In the illustrative embodiment, the intersection of the laser scanning planes extends from adjacent (e.g. about 9.5" from) the light transmission window to at least about 10.0 inches therefrom so as to produce a highly collimated projected scanning pattern within the narrowly confined 3-D scanning volume. Within this 3-D scanning volume, a bar code symbol can be scanned omnidirectionally, while preventing unintentional scanning of code symbols on objects located outside thereof.

As illustrated in the cross-sectional diagram of FIGS. 7A and 7B exists a particular relationship among the scanlines of the laser scanning pattern of the illustrative embodiment. In particular, each scan line in each group of scan lines is substantially parallel to each other scan line in that group of scan lines. As a result, when the code symbol is presented to the highly collimated projected scanning pattern within said narrowly confined scanning volume, the code symbol is scanned within said highly collimated projected scanning pattern independent of the orientation of the code symbol within the scanning volume. At least a portion of the laser light reflected from the scanned code symbol is directed through the light transmission window, reflected off the stationary light reflective surfaces, reflected off the rotating mirrors, collected by the light focusing mirror, and received by the photodetector 41, whereupon an electrical signal is produced for use in decode signal processing abound. The details of such signal processing operations, and the preferred means for achieving the same, can be best understood with a detailed description of the scan and control data processing circuitry embodied with the laser scanning engine of the present invention.

As shown in FIG. 8, automatic laser scanning engine of the illustrative embodiment cooperates with a number of system components to form the automatic bar code symbol reading system of the present invention. These additional system components include: a system override signal detection circuit 100 for detecting the production of a system override signal and producing in the presence thereof control activation signal $A_0=1$; a primary oscillator circuit 101 for producing a primary clock signal CLK for use by the system override signal detection circuit and object detection circuit 107; a first RC timing network 102 for setting the oscillation frequency of the primary oscillator circuit; means (e.g., Hall-effect sensor) 103 for producing a system override signal; first control means 104, realized as a first control circuit C_1 , for performing localized system control functions; a second RC timing network 105 for setting a timer T_1 in control circuit C_1 ; means (e.g., an object sensing circuit 106 and an object detection circuit 107) for producing a first activation control signal $A_1=1$ upon the detection of an object bearing a bar code in at least a portion of the object detection field; a laser beam scanning mechanism 108 for producing and scanning a visible laser beam across the bar code symbol on the detected object; photoreceiving circuit 109 for detecting laser light reflected off the scanned bar code symbol and producing an electrical signal D_1 indicative of the detected intensity; an analog-to-digital (A/D) conversion circuit 110 for converting analog scan data signal D_1 into a corresponding digital scan data signal D_2 ; a bar code

presence detection circuit 111 for processing digital scan data signal D_2 in order to automatically detect the digital data pattern of a bar code symbol on the detected object and produce control activation signal $A_2=1$; a third RC timing network 112 for setting a timer T_{BCD} in the bar code symbol detection circuit; second control means 113, realized as a second control circuit C_2 , for performing local system control operations in response to the detection of the bar code symbol; third control means 114, realized as third control module C_3 ; a range selection circuit 115 for supplying range selection signals to the object detection circuit; second control circuit C_2 and third control module C_3 ; timers T_2 , T_3 , and T_4 identified by reference numerals 116, 117 and 118, respectively; a symbol decoding module 119 for processing digital scan data signal D_2 so as to determine the data represented by the detected bar code symbol, generate symbol character data representative thereof, and produce activation control signal A_3 for use by third control module C_3 ; a data packet synthesis module 120 for synthesizing a group of formatted data packets for transmission to its mated base unit; and a data packet transmission circuit 121 for transmitting the group of data packets synthesized by the data packet synthesis module. As will be described in greater detail hereinafter, second control circuit C_2 is capable of "overriding" (i.e., inhibit and/or enable) first control circuit C_1 , whereas third control module C_3 is capable of overriding first and second control circuits C_1 and C_2 , respectively. As shown in FIG. 8, such control override functions are carried out by the generation of control override signals (i.e., C_2/C_1 , C_3/C_2 and C_3/C_1) transmitted between respective control structures. Owing to the unique architecture of the control subsystem hereof, the automatic bar code symbol reading device of the present invention is capable of versatile performance and ultra-low power operation. The structure, function and advantages of this control subsystem architecture will become apparent hereinafter.

As shown in the system diagram of FIG. 8, battery power supply unit (20) contained within the housing of the device provides electrical power to the components within the bar code reading. In the illustrative embodiment, this battery power supply unit is realized as a power supply distribution circuit 125 fed preferably by replaceable or rechargeable batteries 126. In the case of rechargeable batteries, a secondary inductive coil 127, bridge rectifier 128 and voltage regulation circuit 129 are contained within the hand-supportable housing, and configured as shown in FIG. 8. The function of second inductive coil 128 is to establish an electromagnetic coupling with the primary inductive coil contained in the base unit associated with the bar code reading device whenever the device is supported in the recharging portion of the base unit. In this configuration, electrical power is inductively transferred from the primary inductive coil in the base unit to secondary inductive coil 127, rectified by bridge rectifier 128, and filtered by voltage regulation circuit 129 to provide a regulated DC power supply for recharging rechargeable batteries 126. In addition, an externally accessible ON/OFF power switch 130 or functionally equivalent device is provided in series between battery supply unit 126 and power distribution circuitry 125 so as to permit the user to selectively energize and deenergize the device, as desired or required.

Range selection circuit 115 may include a manual switch externally accessible to the housing, which the user can depress to select long or short-range modes of object detection, bar code presence detection and/or bar code symbol reading. Alternatively, Range Selection Circuit 115 can be activated to a particular range setting by symbol

decoding module **119**. In this mode of operation, the range setting can be set by decoding a bar code symbol pre-designated to activate the long or short range modes of detection, as the case may be.

In the illustrative embodiment of the present invention, system override signal detection circuit **100**, primary oscillator circuit **101**, object detection circuit **107**, first control circuit C_1 , analog-to-digital conversion circuit **110**, bar code symbol detection circuit **111**, and second control circuit C_2 are all realized on a single Application Specific Integrated Circuit (ASIC) chip **133** using microelectronic circuit fabrication techniques known in the art. In the illustrative embodiment, the ASIC chip and associated circuits for laser scanning and light detection and processing functions are mounted on PC board **87**. Symbol decoding module **119**, data packet synthesis module **120**, timers T_2 , T_3 , T_4 , and T_5 and third control module C_3 are realized using a single programmable device, such as a microprocessor having accessible program and buffer memory, and external timing circuitry, collectively depicted by reference numeral **134** in FIG. **8**. In the illustrative embodiment, these components and devices are mounted on PC board **88**.

In the illustrative embodiment, when power switch **130** is engaged to its ON position, power from battery power unit **126** is provided to first control circuit C_1 , system override detection circuit **100**, primary oscillator circuit **101** and IR object sensing circuit **106** and object detection circuit **107** so as to enable their operation, while only biasing voltages are provided to all other system components so that they are each initially disabled from operation. In accordance with the principles of the present invention, the consumption of electrical power to all other system components occurs under the management of the control architecture formed by the interaction of distributed control centers C_1 , C_2 and C_3 .

In some embodiments, it is desired to override (i.e., disable) the entire system from operation, such as when a hand-supportable bar code symbol reading device is placed in a holster worn on the user's belt. In such instances, the bar code symbol reading device of the present invention can be simply disabled by activating the system override signal producing device (e.g., Hall-effect sensor in the presence of a magnetic field) **103** mounted within the hand-supportable housing. As shown in FIG. **8A**, system override signal detection circuit **100** comprises AND gates **136** and **137**, an inverter **138**, an S-R latch circuit **139** and a logical driver **140**, configured as shown. As illustrated in FIG. **8A**, the clock oscillator signal CLK (i.e., a periodic pulsed signal) is provided as one input of AND gate **136**, one input of AND gate **137**, and the input of logic driver **140**. The system override signal SO from Hall-effect sensor **103** is provided to the input of inverter **138** and the second input of AND gate **136**. The output of inverter **138** is provided to the input of AND gate **137**.

As shown, the output of AND gate **137** is provided to the RESET input of S-R latch **139**, whereas the output of AND gate **136** is provided to the SET input of S-R latch **139**. The output of S-R latch **139** is activation signal A_0 provided to first control circuit C_1 , whereas the output of logic driver **140** is the driver signal SO DR which is used to drive (i.e., provide the supply voltage for) the Hall-effect sensor **103** mounted within the hand-supportable housing.

As shown in FIG. **8**, primary clock oscillator circuit **101** supplies a periodic pulsed signal to both the system override signal detection circuit and the object detection circuit. In the illustrative embodiment, the primary oscillation circuit is designed to operate at a low frequency (e.g., about 1.0 KHz)

and a very low duty cycle (e.g., about 1.0%). The "ON" time for the system override signal producing means and the IR object sensing circuit is proportional to the duty cycle of the primary oscillation circuit. This feature allows for minimal operating current when the bar code symbol reading engine is in the object detection mode and also when the system override signal producing device is activated (i.e., produces a system override signal).

As shown in FIG. **8B**, primary oscillation circuit **101** comprises a Schmidt trigger **142**, invertors **143** and **144**, and a NMOS Field-Effect Transistor (FET) **145**. As shown, the output of trigger **142** is connected to the inputs of both invertors **143** and **144**. The output of inverter **143** produces clock signal CLK which is provided to system override signal detection circuit **100** and object detection circuit **107**. The primary oscillation circuit is connected to first RC network **102** which comprises resistors R_1 and R_2 , and capacitor C_1 configured as shown in FIG. **8B**. The function of the RC network **102** is to establish the duty cycle and the oscillation period of the primary oscillator circuit. As shown, two time constants (i.e., loads) are established by the network using capacitor C_1 and resistors R_1 and R_2 . The RC combination of R_1 and C_1 establishes the period of the oscillator. The ratio of the R_2 to R_1 provides the duty cycle of the oscillator. The value of R_2 is approximately 100 times smaller than R_1 to establish a 1.0% duty cycle. As shown in the timing diagram of FIG. **8C**, the clock signal CLK remains low while the V_{11} signal ramps up. This ramp up time is the time it takes for the capacitor C_1 to charge through R_1 . The clock signal CLK then goes HIGH for the shorter discharge time of the capacitor through R_2 . By adjusting the duty cycle (i.e., increasing or decreasing the value of resistor R_2), the sensitivity of the object detection circuit can be tuned such that it activates consistently at a specified distance from the light transmission window of the bar code symbol reading device.

In accordance with the present invention, the purpose of object detection circuit **107** is to produce a first control activation signal $A_1=1$ upon determining that an object (e.g., product, document, etc.) is present within the object detection field of the bar code symbol reading device, and thus at least a portion of the scan field thereof. As illustrated in FIG. **8**, the object detection circuit is activated (i.e., enabled) by enabling signal E_0 supplied from first control circuit C_1 , and the object detection circuit provides the first control circuit C_1 with first control activation signal $A_1=1$ when an object residing in the scan field is detected. In the illustrative embodiment, an "active" technique of automatic object detection is employed, although it is understood that "passive" techniques may be used with acceptable results. As shown in FIG. **8**, the object detection means of the system comprises two major subcomponents, namely object sensing circuit **106** and object detection circuit **107**, both of which are locally controlled by control circuit C_1 . In the illustrative embodiment, object sensing circuit comprises an IR LED **148** driven by an IR transmitter drive circuit **149**, and an IR phototransistor (or photodiode) **150** activated by an IR receive biasing circuit **151**. As shown in FIGS. **7D** and **7F**, these components are arranged and mounted on PC board **87** so as to provide an object detection field that spatially encompasses the laser scanning plane, as described above. As shown in FIG. **8**, the object detection circuit **107** produces an enable signal IR DR which is provided to the IR transmitter drive circuit **149**. The signal produced from IR phototransistor **151**, identified as IR REC, is provided as input signal to the object detection circuit **107** for signal processing in a manner which will be described in detail

below. In the illustrative embodiment, infrared LED **148** generates a 900 nanometer signal that is pulsed at the rate of the primary oscillation circuit **101** (e.g., 1.0 KHZ) when the object detection circuit is enabled by enable signal E_0 produced from the first control circuit C_1 . Preferably, the duty cycle of the primary oscillation circuit **101** is less than 1.0% in order to keep the average current consumption very low.

As shown in FIG. **3A**, in particular, this pulsed optical signal is transmitted from infrared LED **148** to broadly illuminate the scan field. When an object is present within the object detection portion of the scan field, a reflected optical pulse signal is produced and focussed through focusing lens **153** onto photodiode **150**. The function of photodiode **150** is to receive (i.e., sense) the reflected optical pulse signal and, in response thereto, produce a current signal IR REC.

As shown in FIG. **8D**, produced current signal IR REC is provided as input to the current-to-voltage amplifier (e.g., transconductance amplifier) **155** in the object detection circuit, and is converted into a voltage signal V_0 . Within the object detection circuit **107**, the infra-red LED drive signal IR DR is produced as the output of AND gate **157**, whose inputs are enabling signal E_0 supplied from the first control circuit C_1 and the pulsed clock signal CLK supplied from the primary oscillation circuit **101**.

As shown in FIG. **8D**, enabling signal E_0 is also provided to current-to-voltage amplifier circuit **155**, and the output voltage signal from AND gate **157** is provided as the second input to the synchronous transmitter/receiver circuit **156**. Notably, the output voltage signal from AND gate **157** and the output voltage signal V_0 from the current-to-voltage amplifier correspond to the IR pulse signal trains transmitted from and received by object sensing circuit **106**. The function of the synchronous transmitter/receiver circuit is to cyclically compare the output voltage signal from AND gate **157** and the output voltage signal V_0 from the current-to-voltage amplifier, and if these voltage signals synchronously match each other for a minimum of three (3) consecutive cycles of the primary oscillation circuit **101**, then synchronous transmitter/receiver circuit **156** produces as output, a first control activation signal $A_1=1$, indicative that an object is present in the scan field of the bar code symbol reading device. Conversely, whenever first control activation signal $A_1=0$ is produced, then this condition indicates that an object is not present in the scan field.

Alternatively, the automatic bar code reading device of the present invention can be readily adapted to sense ultrasonic energy reflected off an object present within the scan field. In such an alternative embodiment, object sensing circuit **106** is realized as an ultrasonic energy transmitting/receiving mechanism. In the housing of the bar code reading engine, ultrasonic energy is generated and transmitted forwardly into the scan field. Then, ultrasonic energy reflected off an object within the object detection field is detected adjacent to the transmission window using an ultrasonic energy detector that produces an analog electrical signal (i.e., UE REC) indicative of the detected intensity of received ultrasonic energy. Preferably, a focusing element is disposed in front of the energy detector in order to effectively maximize the collection of ultrasonic energy reflected off objects in the scan field. In such instances, the focusing element essentially determines the geometrical characteristics of the object detection field of the device. Consequently, the energy focusing (i.e., collecting) characteristics of the focusing element will be selected to provide an object detection field which spatially encompasses at least a portion

of the scan field. The electrical signal produced from the ultrasonic-energy based object sensing circuit is provided to object detection circuit **107** for processing in the manner described above.

In the illustrative embodiment, object detection circuit **107** is provided with two different modes of detection, namely, a long-range mode of object detection and a short-range mode of object detection. As shown in FIGS. **8** and **8D**, these modes are set by range selection circuit **115** using mode enable signal R_1 . When induced into the long-range mode of object detection, object detection circuit **107** will generate first control activation signal $A_1=1$ whenever an object has been detected within the operative range of the object detection field, independent of the particular distance at which the object resides from the transmissive window. When induced into the short-range mode of object detection, the object detection circuit will generate first activation control signal $A_1=1$ only when an object is detected at a distance within the short-range of the object detection field.

As schematically indicated in FIGS. **2** and **2A**, the long-range specification for object detection is preferably preselected to be the full or entire range of sensitivity provided by current-to-voltage amplifier (e.g., 0 to about 10 inches). Preferably, the short-range specification for object detection is preselected to be the reduced range of sensitivity provided by the IR sensing circuit when mode enable signal $E_{IRT}=1$ is provided to the desensitization port of amplifier **155**. In the illustrated embodiment, the short-range of object detection is about 0 to about 3 inches or so to provide CCD-like scanner emulation. As will become apparent hereinafter, the inherently limited depth and width of field associated with the short-range mode of object detection prevents laser scanning mechanism **108** from flooding the scan field with laser scanning light and thus inadvertently detecting undesired bar code symbols. Particular uses to which object detection range selection can be put, will be described in greater detail hereinafter.

As shown in FIG. **8D**, the sensitivity (i.e., gain) of current-to-voltage amplifier **155** is controlled by a sensitivity control signal E_{IRT} produced from range control signal generating circuit **158**. In the illustrative embodiment, the sensitivity control signal E_{IRT} **160** is produced by a resistance network whose values are selected using an analog switch that is responsive to a range select signal R_1 produced by range selection circuit **115**. As such, the sensitivity of the current-to-voltage amplifier is simply adjusted by selecting one of two resistance values within the resistance network used to realize range control signal generating circuit **158**. The short range mode of object detection is enabled by selecting a resistance value that produces an amplifier gain that is lower than that produced during the long-range mode of object detection where detectable objects can reside further away from the light transmission window of the bar code symbol reading device.

In general, first control logic block C_1 provides the first level of system control. This control circuit activates the object detection circuit **107** by generating enable signal $E_0=1$, it activates laser beam scanning circuit **108**, photoreceiving circuit **109** and A/D conversion circuit **110** by generating enable signal $E_1=1$, and it activates bar code symbol detection circuit **11** by generating enable signal $E_2=1$. In addition, the first control circuit C_1 provides control lines and signals in order to control these functions, and provides a system override function for the low power standby mode of the bar code symbol reading engine. In the illustrative embodiment, the specific operation of first control circuit C_1 is dependent on the state of several sets of

input signals (i.e., activation control signal A_0 and A_1 , and override signals C_2/C_1 , C_3/C_1-1 and C_3/C_1-2) and an internally generated digital timer signal B. A preferred logic implementation of the first control circuit C_1 is set forth in FIGS. 8E and 8F. The functional dependencies among the digital signals in this circuit are represented by the Boolean logic expressions set forth in the Table of FIG. 8G, and therefore are sufficient to uniquely characterize the operation of first control circuit C_1 .

As shown in FIG. 8E, first control circuit comprises a pair of logic invertors 161 and 162, an OR gate 163, a NAND gate 164, a NOR gate 165, an AND gate 166, and a digital timer circuit 167 which produces as output, a digital output signal B. As shown, digital timer circuit 167 comprises a flip-flop circuit 170, a NOR gate 171, a clock divide circuit 173, a comparator (i.e., differential) amplifier 172, and a NPN transistor 174. As illustrated, activation control signal A_1 is provided to the CLK input of flip-flop 170 by way of inverter 161. The QNOT output of the flip-flop is provided as one input to NOR gate 171, whereas the other input thereof is connected to the CLK input of clock divide circuit 173 and the output of comparator amplifier 172. The output of the NOR gate is connected to the base of transistor 174, while the emitter thereof is connected to electrical ground and the collector is connected to the negative input of comparator amplifier 172 as well as the second timing network 105, in a manner similar to the interconnection of first timing network 102 to primary oscillation circuit 101. Also, the divided clock output (i.e., CLK/2048) produced from clock divide circuit 173 is provided to the CL input of flip-flop 170. As shown, the Q output of flip-flop 170 is connected to the reset (RST) input of the clock divide circuit 173 as well as to one input of OR gate 163, one input of NOR gate 165, and one input of AND gate 166. Notably, the Q output of the flip-flop is the digital output signal B indicated in each of the Boolean expressions set forth in the Table of FIG. 8G.

As shown in FIG. 8E, enable signal A_0 from the system override signal detection circuit 100 is provided as the second input to OR gate 163, and the output thereof is provided as input to NAND gate 164. The override signal C_2/C_1 from second control circuit C_2 is provided as the input to inverter 162, whereas the output thereof is provided as the second input to AND gate 166. The override signal C_3/C_1-1 from third control module C_3 is provided as the second input to NAND gate 164, whereas the output thereof produces enable signal E_0 for activating the object detection circuit 107. The override signal C_3/C_1-2 is provided to the second input to NOR gate 165, whereas the output thereof produces enable signal E_1 for activating laser scanning and photoreceiving circuits 108 and 109 and A/D conversion circuit 110. The output of AND gate 166 produces enable signal E_2 for activating bar code symbol detection circuit 111.

Referring to FIG. 8E, the operation of digital timer circuit will be described. The output voltage of comparator amplifier 172 keeps transistor 174 in its non-conducting state (i.e., OFF), via NOR gate 171, thus allowing the external RC network 105 to charge to capacity. When comparator input voltage V_x exceeds reference voltage $VCC/2$, the comparator output voltage biases (i.e., switches ON) transistor 174 so as to begin discharging the RC timing network 105, until input voltage V_x falls below reference voltage $VCC/2$ upon which the process repeats, thus generating a digital clock oscillation at the comparator output. The timing cycle of digital output signal B is initiated by a transition on the activation control signal A_1 which toggles flip-flop 170. This toggling action sets the digital output signal B to its logical

HIGH state, resetting clock divide circuit 173 and starting the digital clock oscillator described above by toggling the Q output of flip-flop 170. As shown in FIG. 8F, clock divide circuit 173 is constructed by cascading eleven flip-flop circuits together in a conventional manner. Each stage of the clock divider circuit divides the input clock signal frequency by the factor 2. Thus the clock divider circuit provides an overall division factor of 2048. When the clock output CLK/2048 toggles, the flip-flop circuit is cleared thus setting the digital signal B to logical LOW until the next pulse of the activation control signal A_1 .

As reflected in the Boolean expressions of FIG. 8G, the state of each of the enable signals E_0 , E_1 and E_2 produced by the first control circuit C_1 is dependent on whether the bar code symbol reading system is in its override state of operation. To better understand the operation of control circuit C_1 , it is helpful to consider a few control strategies preformed thereby.

In the override state of operation of the system, enable signal E_0 can be unconditionally set to $E_0=0$ by the third control circuit C_3 setting override signal $C_3/C_1=0$. Under such conditions, the object detection circuit is enabled. Also, when the system override signal detection circuit is activated (i.e., $A_0=1$) or the laser scanning and photoreceiving circuits activated (i.e., $B=1$) and override signal $C_3/C_1-1=1$, then enable signal $E_0=1$ and therefore the object detection circuit is automatically deactivated. The advantage of this control strategy is that it is generally not desirable to have both the laser scanning circuit 108 and photoreceiving circuit 109 and the object sensing circuit 105 active at the same time, as the wavelength of the infrared LED 148 typically falls within the optical input spectrum of the photoreceiving circuit 109. In addition, less power is consumed when the object detection circuit 107 is inactive (i.e., disabled).

As illustrated in FIG. 8, laser scanning circuit 108 comprises a solid-state visible laser diode (VLD) 177 driven by a conventional driver circuit 178. In the illustrative embodiment, the wavelength of visible laser light produced from the laser diode is preferably about 670 nanometers. In order to repeatedly scan the produced laser beam over the scanning volume, the rotating polygon is rapidly accelerated to operating speed by motor 37 driven by a conventional driver circuit 181, as shown. Stationary mirror 44 directs the laser beam from the laser diode to the rotating polygon. To selectively activate both laser light source 38 and motor 37, a laser diode and scanning motor enable signal E_1 is provided as input to driver circuits 178 and 181. When enable signal E_1 is a logical "high" level (i.e., $E_1=1$) a laser beam is generated and projected through the light transmissive window, when the projected laser beam is repeatedly scanned through the scanning volume, and an optical scan data signal is thereby produced off the object (and bar code) residing within the scanning volume. When laser diode and scanning motor enable signal E_1 is a logical "low" (i.e., $E_1=0$), there is no laser beam produced, projected, or scanned across the scanning volume.

When a bar code symbol is present on the detected object at the time of scanning, the the visible laser beam is automatically scanned across the bar code symbol within the 3-D scanning volume, and incident laser light on the bar code symbol will be scattered and reflected. This scattering/reflection process produces a laser light return signal of variable intensity which represents a spatial variation of light reflectivity characteristic of the pattern of bars and spaces comprising the bar code symbol. Photoreceiving circuit 109 detects at least a portion of the reflected laser light of variable intensity and produces an analog scan data signal D_1 indicative of the detected light intensity.

In the illustrative embodiment, photoreceiving circuit **109** generally comprises a number of components, namely: laser light collection optics (i.e., stationary mirror array **38** and focusing mirror **43**) for focusing reflected laser light for subsequent detection; photoreceiver **41** (e.g., a silicon photosensor) mounted onto PC board **40**, as shown in FIG. **5D**, for detecting laser light focused by the light collection optics; and frequency selective filter **186A**, mounted in front of photoreceiver **41**, for transmitting thereto only optical radiation having wavelengths up to a small band above 670 nanometers.

In order to prevent optical radiation slightly below 670 nanometers from passing through light transmission aperture **12A** and entering the housing, the light transmissive window **68** realized as a plastic filter lens is installed over the light transmission aperture of the housing. This plastic filter lens has optical characteristics which transmit only optical radiation from slightly below 670 nanometers. In this way, the combination of plastic filter lens **12** at the transmission aperture and frequency selective filter **186A** before photoreceiver **41** cooperate to form a narrow band-pass optical filter having a center frequency $f_c=670$ nanometers. By permitting only optical radiation associated with the visible laser beam to enter the housing, this optical arrangement provides improved signal-to-noise ratio for detected scan data signals D_1 . This novel filtering optical arrangement is disclosed in greater detail in copending application Ser. No. 08/439,224, supra.

In response to reflected laser light focused onto photoreceiver **41**, photoreceiver **41** produces an analog electrical signal which is proportional to the intensity of the detected laser light. This analog signal is subsequently amplified by preamplifier **187** to produce analog scan data signal D_1 . In short, laser scanning circuit **108** and photoreceiving circuit **109** cooperate to generate analog scan data signals D_1 from the scan field, over time intervals specified by first control circuit C_1 during normal modes of operation, and by third control module C_3 during "control override" modes of operation.

As illustrated in FIG. **8**, analog scan data signal D_1 is provided as input to A/D conversion circuit **110**, shown in FIG. **8H**. In a manner well known in the art, A/D conversion circuit **110** processes analog scan data signal D_1 to provide a digital scan data signal D_2 which has a waveform that resembles a pulse width modulated signal where logical "1" signal levels represent spaces of the scanned bar code and logical "0" signal levels represent bars of the scanned bar code. A/D conversion circuit **110** can be realized using any conventional A/D conversion techniques well known in the art. Digitized scan data signal D_2 is then provided as input to bar code presence detection circuit **111** and symbol decoding module **119** for use in performing particular functions required during the bar code symbol reading process of the present invention.

The primary purpose of bar code presence detection circuit **111** is to determine whether a bar code is present in or absent from the scan field, over time intervals specified by first control circuit C_1 during normal modes of operation and by third control module C_3 during control override modes of operation. In the illustrative embodiment, bar code presence detection circuit **111** indirectly detects the presence of a bar code in the narrowly-confined scanning volume by detecting its bar code symbol "envelope". In the illustrative embodiment, a bar code symbol envelope is deemed present in the scanning volume upon detecting a corresponding digital pulse sequence in digital signal D_2 that A/D conversion circuit **110** produces when photoreceiving circuit **109**

detects laser light reflected off a bar code symbol scanned by the laser beam produced by laser beam scanning circuit **108**. This digital pulse sequence detection process is achieved by counting the number of digital pulse transitions (i.e., falling pulse edges) that occur in digital scan data signal D_2 within a predetermined time period T_1 clocked by the bar code symbol detection circuit. According to the laws of physics governing the laser scanning operation, the number of digital (pulse-width modulated) pulses detectable at photoreceiver **41** during time period T_1 is a function of the distance of the bar code from the light transmission window **111** at the time of scanning. Thus a bar code symbol scanned at 6" from the light transmission window will produce a larger number of digital pulses (i.e., digital count) at photoreceiver **41** during time period T_1 than will the same bar code symbol scanned at 3" from the light transmission window.

In the illustrative embodiment, the bar code symbol detection circuit **111** is provided with the capacity to detect the presence of a bar code symbol in either the long or short range portions of the scanning volume, as specified in FIGS. **3** and **3A**. This is achieved by counting the digital pulse transitions present in digital scan signal D_2 within predetermined time period T_1 and producing second control activation signal A_{2S} (i.e., $A_{2S}=1$) when the counted number of pulse transitions equals or exceeds a first prespecified digital pulse transition count corresponding to a bar code symbol scanned in the short range portion of the scan field, and producing second control activation signal A_{2L} (i.e., $A_{2L}=1$) when the counted number of pulse transitions equals or exceeds a second prespecified digital pulse transition count corresponding to a bar code symbol scanned in the long range portion of the scanning volume. As shown in FIG. **8**, both of these second control activation signals A_{2L} and A_{2S} are produced and provided as input to second control circuit C_2 . However, second control circuit C_2 selectively provides (e.g., gates) the second control activation signal that corresponds to range-mode of operation selected by the user. When the long range mode of operation has been selected by range selection circuit **115**, the device will automatically undergo a transition from bar code presence detection state to bar code symbol reading state upon receiving control activation signal $A_{2L}=1$. Similarly, when the short range mode of operation has been selected by the range selection circuit **115**, the device will automatically undergo a transition from bar code presence detection state to bar code symbol reading state upon receiving control activation signal $A_{2S}=1$.

In the illustrative embodiment, bar code symbol presence detection circuit **111** comprises a digital pulse transition counter **190** for counting digital pulse transitions during time period T_1 , and a digital clock circuit (i.e., T_{BCD} circuit) **191** for measuring (i.e., counting) time period T_{BCD} and producing a count reset signal CNT RESET at the end of each such time period, as shown in FIG. **8K**. As shown in FIG. **8K**, the function of digital clock circuit **191** is to provide a time period T_{BCD} (i.e., time window subdivision) within which the bar code symbol detection circuit attempts, repeatedly during time period T_1 , to detect a bar code symbol in the scan field. In the preferred embodiment, T_{BCD} is about 0.1 seconds, whereas T_1 is about 1.0 second. As shown in FIG. **8I**, in order to establish such "bar code search" time sub-intervals within time period T_1 , the digital clock circuit **191** generates the first count reset pulse signal CNT RESET upon the detection of the first pulse transition in digital scan data signal D_2 . The effect of this reset signal is to clear or reset the digital pulse transition (falling edge) counter. Then at the

end of each time subinterval T_{BCD} , digital clock signal **191** generates another count reset pulse CNT RESET to reset the digital pulse transition counter. If during time window T_1 , a sufficient number of pulse transitions in signal D_2 are counted over a subinterval T_{BDC} , then either control activation signal A_{2L} or A_{2S} will be set to "1". In response to the detection of this condition, second control circuit C_2 automatically enables control activation C_3 in order to initiate a transition from the bar code symbol detection state of operation to the bar code symbol reading state of operation.

As shown in FIG. **8I**, digital pulse transition counter **191** is formed by wiring together a series of four flip-flop circuits **192** to **195**, such that each flip flop divides the clock signal frequency of the previous stage by a factor of 2. As indicated in the drawing of FIG. **8I**, the Q output of flip flops **192** to **194** represent the binary digits **2**, **4**, **8**, and **16** respectively, of a binary number (i.e., counting) system. As shown, enable signal E_2 from first control circuit C_1 is provided as input to NOR gate **197**, while the second input thereto is the counter reset signal CNT RESET provided from the digital counter circuit **191**. In order to reset or clear the pulse transition counter circuit **190** upon the generation of each CNT RESET pulse, the output of the NOR gate **197** is connected to the clear line (CL) of each flip flop **192** to **195**, as shown.

As illustrated in FIG. **8I**, digital clock circuit **191** comprises a flip-flop circuit **198**, a NOR gate **199**, a clock divide circuit **200**, a comparator **201**, and a NPN transistor **202**. As illustrated, digital scan data signal D_2 is directly provided to the CLK input of flip-flop **198**. The QNOT output of the flip-flop is provided as one input to NOR gate **199**, whereas the Q output thereof is connected to the CLK input of clock divide circuit **200** and the second input of NOR gate **197**. The other input of NOR gate **199** is connected to the input line CLK of clock divide circuit **200** and to the output of comparator **201**, as shown. The output of the NOR gate is connected to the base of transistor **202**, while the emitter thereof is connected to electrical ground and the collector is connected to the negative input of comparator **201** as well as to the third timing network **112**, in a manner similar to the interconnection of the first timing network **102** to primary oscillation circuit **101**. As shown in FIG. **8J**, clock divide circuit **200** is realized as series of five flip-flops **200A** to **200E** wired together so as to divide digital clock input signal CLOCK by 32, and be resettable by pulsing reset line RESET in a conventional manner.

When an object is detected in the scan field, first control circuit C_1 produces enable signal $E_2=1$ so as to enable digital pulse transition counter **190** for a time duration of T_1 . As shown, the digital scan data signal D_2 (representing the bars and spaces of the scanned bar code) drives the clock line of first flip flop **192**, as well as the clock line of flip flop **198** in the T_{BCD} timer circuit. The first pulse transition in digital scan data signal D_2 starts digital timer circuit **191**. The production of each count reset pulse CNT RESET from digital timer circuit **191** automatically clears the digital pulse transition counter circuit **190**, resetting it once again to count the number of pulse transitions present in the incoming digital scan data signal D_2 over a new time subinterval T_{BCD} . The Q output corresponding to eight pulse transitions counted during time period T_{BCD} , provides control activation signal A_{2S} for use during the short range mode of operation. The Q output corresponding to sixteen pulse transitions counted during time period T_{BCD} , provides control activation signal A_{2L} for use during the long range mode of operation. When the presence of a bar code in the scan field is detected, second activation control signal A_{L2} or A_{2S} is generated, third control circuit C_3 is activated and second

control circuit C_2 is overridden by third control circuit C_3 through the transmission of control override signals (i.e., C_3/C_2 inhibit and C_3/C_1 enable signals) from the third control circuit C_3 .

As illustrated in FIG. **8L**, second control circuit C_2 is realized using logic circuitry consisting of NAND gates **205** to **208**, invertors **209** and **210**, NOR gates **211** to **213**, NAND gates **214** and **215**, AND gate **216**, configured together as shown. As shown, second control activation signals A_{2S} and A_{2L} are provided to the first inputs of NAND gates **214** and **215**, respectively, whereas the outputs of NOR gates **211** and **212** are provided to the second inputs of NAND gates **214** and **215** respectively. The outputs of NAND gates **214** and **215** are provided to the inputs of AND gate **216** and the output thereof provides enable signal E_3 for enabling third control module C_3 .

As shown in FIG. **8L**, the third control module C_3 provides override signals C_3/C_2-1 and C_3/C_2-2 to the first and second inputs of NAND gate **205** and to the first input of NAND gate **207** and the first input of NAND gate **208**, respectively. The range selection signal R produced from range selection circuit **115** is provided as input to NAND gate **206**. As shown, output of NAND gate **205** is provided as the second input to NAND gate **206**. The output of NAND gate **206** is provided as the second input to NAND gate **207** and the second input to NAND gate **208**. As shown in FIG. **8L**, the output of NAND gate **207** is provided as an input to NOR gate **211** and inverter **209**, whereas the output of NAND gate **208** is provided as inputs to NOR gates **211** and **212** and inverter **210**. The output of inverter **209** is provided as the other input to NOR gate **212** and one input to NOR gate **213**. The output of inverter **210** is provided as another input to NOR gate **213**, whereas the output thereof provides control override signal C_2/C_1 . So configured, the combinational logic of the second control circuit C_2 maps its input signals to its output signals in accordance with the logic table of FIG. **8M**.

Upon entering the bar code symbol reading state, third control module C_3 provides override control signal C_3/C_1 to first control circuit C_1 and second control circuit C_2 . In response to control signal C_3/C_1 , the first control circuit C_1 produces enable signal $E_1=1$ which enables scanning circuit, **109** photo-receiving circuit **109** and A/D conversion circuit **110**. In response to control signal C_3/C_2 , the second control circuit C_2 produces enable signal $E_2=0$, which disables bar code symbol detector circuit **111**. Thereafter, third control module C_3 produces enable signal E_4 to enable symbol decoding module **119**. In response to the production of such signals, the symbol decoding module decode processes, scan line by scan line, the stream of digitized scan data contained in signal D_2 in an attempt to decode the detected bar code symbol within the second predetermined time period T_2 established and monitored by the third control module C_3 . If the symbol decoding module **119** successfully decodes the detected bar code symbol within time period T_2 , then symbol character data D_3 (representative of the decoded bar code symbol and typically in ASCII code format) is produced. Thereupon symbol decoding module **119** produces and provides the third control activation signal A_3 to the third control module C_3 in order to induce a transition from the bar code symbol reading state to the data packet transmission state. In response thereto, a two distinct events occur. First the third control module C_3 produces and provides enable signal E_5 to data packet synthesis module **120**. Secondly, symbol decoding module **119** stores symbol character data D_3 in a memory buffer associated with data packet synthesis module **120**.

In the illustrative embodiment, symbol decoding module **119**, data packet synthesis module **120**, and timers T_2 , T_3 , T_4 and **T5** are each realized using programmed microprocessor and accessible memory **134**. Similarly, third control module C_3 and the control functions which it performs at Blocks I to GG in FIGS. **13A** and **13C**, are realized as a programming implementation using techniques well known in the art.

The function of data packet synthesis module **120** is to use the produced symbol character data to synthesize a group of data packets for subsequent transmission to its assigned base unit by way of data packet transmission circuit **121**.

In the illustrative embodiment, each synthesized data packet is formatted as shown in FIG. **8N**. In particular, each data packet in each data packet group comprises a number of data fields, namely: Start of Packet Field **220** for containing a digital code indicating the beginning of the transmitted data packet; Transmitter Identification Number Field **221** for containing a digital code representative of the Transmitting Bar Code Symbol Reader; Data Packet Group Number Field **222** for containing a digital code (i.e., a first module number) assigned to each particular data packet group being transmitted; Data Packet Transmission No. Field **223** for containing a digital code (i.e., a second module number) assigned to each data packet in each data packet group being transmitted; Symbol Character Data Field **224** for containing digital code representative of the symbol character data being transmitted to the base unit; Error Correction Code Field **225** for containing a digital error correction code for use by the receiving base unit to determine if error in data packet transmission has occurred; and End of Packet Field for **226** for containing a digital code indicating the end of the transmitted data packet.

After the data packet synthesis module synthesizes a group of data packets as described above, the third control module C_3 provides enable signal E_7 to data packet transmission circuit **121**. As illustrated in FIG. **9**, the data packet transmission circuit comprises a carrier signal generation circuit **230**, a carrier signal frequency modulation circuit **231**, a power amplifier **232**, a matching filter **233**, and a quarterwave ($\frac{1}{4}$) transmitting antenna element **234**. The function of the carrier signal generation circuit **230** is to generate a carrier signal having a frequency in the RF region of the electromagnetic spectrum. In the illustrative embodiment, the carrier frequency is about 912 Mhz, although it is understood that this frequency may vary from one embodiment of the present invention, to another embodiment thereof. As the carrier signal is being transmitted from transmitting antenna **234**, frequency modulation circuitry **231** modulates the instantaneous frequency of the carrier signal using the digital data sequence (i.e., digital data stream) **235** constituting the group of data packets synthesized by the data packet synthesis module **120**. The function of the power amplifier is to amplify the power of the transmitted modulated carrier signal so that it may be received by a base unit of the present invention located within a predetermined data transmission range (e.g., from about 0 to about 30 feet).

In general, each base unit of the present invention performs a number of functions. First, the base unit receives the modulated carrier signal transmitted from a hand-supportable bar code symbol reading device within the data reception range of the base unit. Secondly, the base unit demodulates the received carrier signal to recover the data packet modulated thereunto during signal transmission. Thirdly, the base unit analyzes each of the recovered data packets to determine whether the received carrier signal was transmitted from a hand-supportable bar code symbol read-

ing device preassigned to the receiving base unit. Fourthly, the base unit recovers the symbol character data from at least one data packet in a transmitted group of data packets, and ascertaining the reliability of the recovered symbol character data. Fifthly, the base unit generates an acoustical acknowledgement signal S_{ACK} that can be audibly perceived by the operator of the transmitting bar code symbol reading device while located in the data reception range of the base unit. Finally, the base unit transmits the received symbol character data to a host computer system or like device. Each of these functions will be described in greater detail during the detailed description of the Main System Control Routine set forth in FIGS. **13A** to **13C**.

In order to better understand the functions performed by the bar code symbol reading device and base unit of the present invention, it will be helpful to first describe the principles underlying the data communication method of the present invention, and thereafter discuss the role that the base unit plays in carrying out this communication method.

In general, one or more bar code symbol reading devices can be mated (i.e. registered or assigned) to operate with a single base unit **3**. In a first illustrative embodiment of the present invention, each bar code symbol reading device is a (resultant) system of bar code symbol reading subsystems installed in physical proximity with each other. Typically, each system is a point of sale (POS) station comprising (i) a host computer system interfaced with a base unit of the present invention and (ii) an automatic hand-supportable bar code symbol reading device preassigned to one of the base units. In such an illustrative arrangement, each bar code symbol reading device is mated (i.e. registered or associated) with a single base unit by storing a unique, preassigned "Transmitter Identification Code" in a memory device within the assigned base unit during a set-up procedure.

In the illustrative embodiment, the carrier frequency of the data packet transmitter in each bar code symbol reading device is substantially the same for all bar code symbol reading devices in the resultant system. Also, the data packet transmission range of each bar code symbol reading device will be substantially greater than the distance between each bar code symbol reading device and a neighboring base unit to which the bar code symbol reading unit is not assigned. Consequently, under such operating conditions, at any instance in time, any base station in the resultant system may simultaneously receive two or more packet modulated carrier signals which have been transmitted from two or more bar code symbol reading devices being used in the resultant system. These bar code symbol reading devices may include the bar code symbol reading device preassigned to the particular base unit as well as neighboring bar code symbol reading devices. Thus due to the principles of data packet transmission of present invention, there exists the possibility that any particular base unit may simultaneously receive two or more different data packets at any instant in time, thereby creating a "packet interference" situation.

In order to ensure that each base unit in the resultant system is capable of receiving at least one data packet from a data packet group transmitted by its preassigned bar code symbol reading device (i.e., without risk of interference from neighboring bar code symbol reading device transmitters), the unique "data packet group" transmission scheme shown in FIG. **10** is employed. As shown, upon the successful reading of a first bar code symbol and the production of its symbol character data D_3 , data packet synthesis module **120** aboard the bar code symbol reading device automatically produces a first (i.e., $N=1$) group of

(three) data packets, each having the packet format shown in FIG. 9. Thereafter, the data packet transmission circuit 121 uses the digital data bit stream, representative of the synthesized data packet group, to modulate a carrier signal transmitted from the hand-supportable bar code symbol reading device.

In the illustrative example shown FIG. 10, only the second and third data packets of the group sent over the modulated carrier signal are shown as being received by the preassigned base unit. As shown in this drawing, the base unit transmits the recovered symbol character data D_3 to its host computer system, upon receiving the second data packet in the transmitted group of data packets. Thereafter, the base unit produces an acoustical acknowledgement signal S_{ACK} of sufficient intensity that it can be easily heard by the operator of the bar code symbol reading device that transmitted the received data packet. The function of the acoustical acknowledgment signal is to provide the operator with an audible acknowledgement that the symbol character data D_3 (associated with the recently read bar code symbol) has been received by the base unit and transmitted to its host computer system for processing and or subsequent storage. Notably, while the third data packet N_3 is also received by the base unit, the available acknowledgement signal S_{ACK} and symbol character data transmission is not produced as packet N_3 contains redundant information already received by the second packet N_2 of the same group.

In the preferred embodiment, the pitch of the transmitted acoustical acknowledgement signal S_{ACK} is uniquely specified and assigned to a particular bar code symbol reading unit. This way the operator of each bar code symbol reading (sub)system can easily recognize (i.e., discern) the audible acoustical acknowledgement signal produced from the base unit preassigned to his or her bar code symbol reading device. At the same time, this pitch assignment scheme allows each operator to ignore audible acoustical acknowledgement signals produced from neighboring base units not mated with his or her portable bar code symbol reading device. If after reading a bar code symbol, the operator does not see the visual "good read" indication light on its device "flash" or "blink" and immediately thereafter hear its preassigned acoustical acknowledgement signal emanate from its base unit, then the operator is implicitly informed that the symbol character data of the read bar code symbol was not successfully received by the base unit. In response to such an event, the operator simply rereads the bar code symbol and awaits to hear the acoustical acknowledgment signal emanating from the base unit.

Notably, it may even be desirable in some operating environments to produce acoustical acknowledgement signals in the form of a unique series of notes preassigned to a bar code symbol reading device and its "mated" base unit. The pitch or note sequence assigned to each mated base unit and bar code symbol reading device can be stored in a memory (e.g., EPROM) realized in the base unit, and can be programmed at the time of system set-up and modified as required. Preferably, each pitch and each note sequence is selected so that it can be readily distinguished and recognized by the operator to which it is uniquely directed.

Also shown in FIG. 10 is the case where the bar code symbol reading device reads a second bar code symbol and then transmits a second ($N=2$) group of data packets. However, due to interference only the third data packet in the second transmitted group of data packets is received at the respective base unit. Despite such group transmission errors (e.g., due to channel corruption or non-radio transmissive obstructions), the base unit as shown is nevertheless

able to recover the transmitted symbol character data. Upon receiving the third data packet, recovering the packaged symbol character data and transmitting the same to the host computer system, the bar code symbol reading device generates an acoustical acknowledgement signal having a pitch or note sequence that the operator can hear and recognize as an indication that the data packet reception was successful.

In FIGS. 11 and 12, the data packet transmission and reception scheme of the present invention is shown for the case of three station system. In the best case scenario shown in FIG. 11, the group of data packets transmitted from each bar code symbol reading device is transmitted at a time when there are no neighboring bar code symbol reading devices transmitting data packets. This case will occur most frequently, as the total transmission times for each group of data packets is selected to be substantially smaller than the random time durations lapsing naturally between adjacent data packet transmissions from neighboring bar code symbol reading devices. This fact is illustrated in FIG. 11, in which (i) a group of data packets from bar code reading device No. 1 are transmitted between adjacent groups of data packet transmitted from bar code symbol reading devices Nos. 2, 3 and 4 without the occurrence of data packet interference (i.e., collision). In most instances, the time delay between consecutive groups of data packets transmitted from any particular bar code symbol reading device, will be sufficient to permit a neighboring bar code symbol reading device to transmit at least one data packet to its base unit without the occurrence of data packet interference.

In accordance with the data transmission scheme of the present invention, data packet interference is minimized by the random presence of interference-free time slots, during which a transmitted data packet can be received at its respective base unit without neighboring packet interference. However, the present invention employs additional measures to further reduce the likelihood of data packet interference. Such measures are best appreciated when considering a high-density data packet transmission environment, in which a number of closely situated neighboring bar code symbol readers are each attempting to transmit a group of data packets to its preassigned base unit. In general, such operating conditions would present a worst case scenario for the data packet transmission scheme of the present invention.

In the worst case scenario shown in FIG. 12, each of the four neighboring bar code symbol reading devices is assumed to consecutively read two bar code symbols and simultaneously begin the transmission of the first data packet in the first group of data packets corresponding to the first read bar code symbol. As mentioned above, each data packet is formatted essentially the same way, has substantially the same packet width, and is transmitted on a carrier signal having a frequency which is substantially the same as all other carrier signals transmitted throughout the system. In accordance with the principles of the present invention, the data packet transmission circuit 121 in each bar code symbol reading device is preprogrammed to transmit adjacent data packets with a different "time delay", as shown in FIG. 12. This condition is achieved throughout the resulting system by assigning a different Packet Time Delay to each having a different Transmitter Identification Number, and then programming the bar code symbol reading device with the preassigned Packet Time Delay parameter. As illustrated in FIG. 12, the value of the Packet Time Delay parameter programmed in each bar code symbol reading device is selected so that, when the neighboring bar code symbol reading devices simultaneously transmit groups of data

packets, each base unit in the resulting system is capable of receiving at least one data packet (in a group thereof) that has been transmitted from its preassigned bar code symbol reading device. In general, the data packet delay scheme of the present invention involves selecting and programming the Packet Time Delay parameter in each bar code symbol reading device so that each base unit is periodically provided a vacant time slot, during which one transmitted data packet in each group thereof can be received free of "data packet interference", as shown in FIG. 12. The advantage of providing a packet time delay among the data packets of each transmitted group thereof is that rereading and retransmission of bar code symbols is effectively minimized under the data packet transmission scheme of the present invention.

Having described the detailed structure and internal functions of automatic bar code symbol reading device of the present invention, the operation of the control system thereof will now be described while referring to the system block diagram shown in FIG. 8 and control Blocks A to GG in FIGS. 13A to 13C.

Beginning at the START block of Main System Control Routine and proceeding to Block A of FIG. 13A, the bar code symbol reading system is "initialized". This initialization step involves activating system override circuit 100, first control circuit C_1 and oscillator circuit 101. It also involves deactivating (i.e., disabling): (i) all external system components except the range selection circuit 115 and system override signal producing means 103 (i.e., infrared sensing circuit 105, laser scanning circuit 108, and photoreceiving circuit 109); (ii) all subcircuits aboard ASIC chip 133 not associated with the system override circuit 100, such as object detection circuit 107, A/D conversion circuitry 110, second control circuit C_2 and bar code presence detection circuit 111; and (iii) third control module 114, symbol decoding module 119 and data packet synthesis module 120. In addition, all timers T_1 , T_2 , T_3 , T_4 , and T_5 are reset to $t=0$.

Proceeding to Block B in FIG. 13A, the first control circuit C_1 checks to determine whether it has received control activation signal $A_0=1$ from system override detection circuit 100. If this signal is received, then the first control circuit C_1 returns to Block A. If control activation signal $A_0=1$ is not received, then at Block C the first control circuit C_1 activates (i.e., enables) the object detection circuit by producing E_0 . At Block D, the object detection circuit receives either the long range mode selection signal or the short range mode selection signal produced by the range selection circuit 115 and sets the appropriate sensitivity level of the circuit. At Block E, the first control circuit C_1 determines whether it has received control activation signal $A_1=1$, indicating that an object has been detected within the selected range of the scan field. If this control activation signal is not received, then at Block F the first control circuit C_1 determines whether it has received control activation signal $A_0=1$. If the first control circuit C_1 has received control activation signal $A_0=1$, then the control system returns to Block A in FIG. 13A, as shown. If the first control circuit C_1 has not received control activation signal $A_0=1$, then the control system returns to Block E, as shown.

If at Block E the first control circuit C_1 has received first control activation signal $A_1=1$, then at Block G the first control circuit C_1 (i) deactivates (i.e., disables) the object sensing circuit and the object detection circuit using disabling signal $E_0=0$, (ii) activates (i.e., enables) laser scanning circuit 108, photoreceiving circuit 109 and A/D signal conversion circuit 110 using enable signal $E_1=1$, (iii) activates bar code detection circuit 111 and second control

circuit C_2 using enable signal $E_2=1$, and (iv) starts timer T_1 maintained in the first control circuit C_1 . This permits the bar code symbol reading device to collect and analyze scan data signals for the purpose of determining whether or not a bar code is within the scan field. If at Block H the second control circuit C_2 does not receive control activation signal $A_{2S}=1$ or $A_{2L}=1$ from the bar code detection circuit within time period T_1 , indicating that a bar code symbol is detected in the selected range of the scan field, then the control system returns to Block A thereby returning system control to the first control unit C_1 , as shown in FIG. 13A. If at Block H the bar code symbol detection circuit 111 provides the second control circuit C_2 with control activation signal $A_{2S}=1$ or $A_{2L}=1$, as the case may be, then second control circuit C_2 activates (i.e., enables) third control module C_3 (i.e., microprocessor 134) using enable signal $E_3=1$.

At Block J, the third control module C_3 polls (i.e., reads) the parameter R set by range selection circuit 115 and sets a range limit flag in the symbol decoding module 119. At Block K third control module C_3 activates the symbol decoding module 119 using enable signal E_4 , resets and restarts timer T_2 permitting it to run for a second predetermined time period (e.g., $0 < T_2 < 1$ second), and resets and restarts timer T_3 permitting it to run for a third predetermined time period (e.g., $0 < T_3 < 5$ seconds). At Block L, the third control module checks to determine whether control activation signal $A_3=1$ is received from the symbol decoding module 119 within $T_2=1$ second, indicative that a bar code symbol has been successfully read (i.e., scanned and decoded) within the allotted time period. If control activation signal $A_3=1$ is not received within the time period $T_2=1$ second, then at Block M third control module C_3 checks to determine whether control activating signal $A_2=1$ is received. If a bar code symbol is not detected, then the control system returns to Block A, causing a state transition from bar code reading to object detection.

However, if at Block M the third control module C_3 receives control activation signal $A_2=1$, indicative that a bar code once again is within the scan field, then at Block N the third control module C_3 checks to determine whether time period T_3 has elapsed. If it has, then the control system returns to Block A. If, however, time period $0 < T_3 < 5$ seconds has not elapsed, then at Block K the third control module C_3 resets and restarts timer T_2 to run once again for a time period $0 < T_2 < 1$ second, while T_3 continues to run. In essence, this provides the device at least another opportunity to read a bar code present within the scan field when the control system is at control Block L. During typical bar code reading applications, the control system may progress through the control loop defined by Blocks K-L-M-N-K several times before a bar code symbol in the scan field is read within the time period allotted by timer T_3 .

Upon receiving control activation signal $A_3=1$ from symbol decoding module 119, indicative that a bar code symbol has been successfully read, the control system proceeds to Block O in FIG. 13B. At this stage of the system control process, the third control module C_3 continues activation of laser scanning circuit 108, photoreceiving circuit 109, and A/D conversion circuit 110, while deactivating symbol decoding module 119 and commencing activation of data packet synthesis module 120. While the laser beam is continuously scanned across the scan field, the operations at Blocks P to V described below, are carried out in a high speed manner under the orchestration of control module C_3 .

As indicated at Block P, data packet synthesis module 120 first sets the Packet Number to "1", and increments the Packet Group Number from the previous number.

Preferably, the data packet synthesis module keeps track of (i.e., manages) the "Packet Number" using a first modulo-N counter realized by programmable microprocessor 134, while it manages the "Packet Group Number" using a second modulo-M counter also realized by programmed microprocessor 134. In the illustrative embodiment, the first modulo counter has a cyclical count range of $N=2$ (i.e., 0,1,2,0,1,2, . . .), whereas the second modulo counter has a cyclical count range of $M=10$ (i.e., 0,1,2,3,4,5,6,7,8,9,0,1,2, . . .). At Block Q, the data packet synthesis module synthesizes or constructs a data packet having a packet format as shown in FIG. 9, i.e., consisting of symbol character data, a Transmitter Identification Number, a Packet Number, a Packet Group Number, check character, and Packet Start and End (i.e., framing) Characters. After the data packet has been formed and the digital data sequence constituting the same is buffered, the third control module C_3 activates at Block R the data packet transmission circuit. Thereafter at Block S, the data packet synthesis module outputs the buffered digital data sequence (of the first synthesized data packet of the group) to the data packet transmission circuit, which uses the digital data sequence to modulate the frequency of the carrier signal as it is being transmitted from the bar code symbol reading device, to its mated base unit, as described hereinabove, and then automatically deactivates itself to conserve power.

At Block T, the third control module C_3 determines whether the Packet Number counted by the first module counter is less than "3". If the Packet Number of the recently transmitted data packet is less than "3", indicative that at most only two data packets in a specific group have been transmitted, then at Block U the data packet synthesis module 120 increments the Packet Number by +1. At Block V, the third control module then waits for a time delay T_5 to lapse prior to the control system returning to Block Q, as shown in FIG. 13B. Notably, the occurrence of time delay T_5 causes a delay in transmission of the next data packet in the data packet group. As illustrated in FIG. 12, the duration of time delay T_5 is a function of the (last two digits of the) Transmitter Number of the current data packet group, and thus is a function of the bar code symbol reading device transmitting symbol character data to its mated base unit. For the case of three data packet groups, time delay T_5 will occur between the transmission of the first and second data packets in a packet group and between the transmission of the second and third data packets in the same packet group.

Returning to Block Q, the data packet synthesis module synthesizes or constructs the second data packet in the same data packet group. After the second data packet has been formed and the digital data sequence constituting the same is buffered, the third control module C_3 reactivates at Block R the data packet transmission circuit. Thereafter at Block S, the data packet synthesis module outputs the buffered digital data sequence (of the second synthesized data packet) to the data packet transmission circuit, which uses the digital data sequence to modulate the frequency of the carrier signal as it is being transmitted from the bar code symbol reading device, to its mated base unit, and thereafter automatically deactivates itself. When at Block T third control module C_3 determines that the Packet Number is equal to "3", the control system advances to Block W in FIG. 13C.

At Block W in FIG. 13C, the third control module C_3 continues activation of laser scanning circuit 108 photoreceiving circuit 109, and A/D conversion circuit 110 using control override signals C_3/C_1 , and deactivates symbol decoding module 119, data packet synthesis module 120 and the data packet transmission circuit 121 using disable signals

$E_4=0$, $E_5=0$ and $E_6=0$, respectively. Then at Block X the third control module C_3 determines whether control activation signal $A_1=1$, indicating that an object is present in the selected range of the scan field. If this control activation signal is not provided to the third control module C_3 , then the control system returns to Block A, as shown. If control activation signal $A_1=1$ is received, then at Block Y the third control module C_3 reactivates the bar code symbol detection circuit using override signal C_3/C_2 , and resets and restarts timer T_3 to start running over its predetermined time period, i.e., $0 < T_3 < 5$ seconds, and resets and restart timer T_4 for a predetermined time period $0 < T_4 < 3$ seconds.

At Block Z in FIG. 13C, the third control module C_3 then determines whether control activation signal $A_2=1$ is produced from the bar code symbol detection circuit 111 within time period T_4 , indicating that a bar code symbol is present in the selected range of the scan field during this time period. If this signal is not produced within time period T_4 , then at Block AA the third control module C_3 deactivates the bar code symbol detection circuit using override signal C_3/C_2 , and reactivates the bar code symbol decoding module 119 using enable signal $E_4=1$. At Block BB, the third control module C_3 resets and restarts timer T_2 to run over its predetermined time period, i.e., $0 < T_2 < 1$ second. At Block CC the third control module C_3 determines whether control activation signal $A_3=1$ is produced by the symbol decoding module within time period T_2 , indicating that the detected bar code symbol has been successfully decoded within this time period. If this control activation signal is not produced within time period T_2 , then at Block DD the third control module C_3 determines whether control activation signal $A_2=1$ is being produced from the bar code symbol detection circuit, indicating that either the same or another bar code symbol resides within the selected range of the scan field. If control activation signal $A_2=1$ is not being produced, then the control system returns to Block A, as shown. However, if this control signal is being produced, then at Block EE the third control module C_3 determines whether or not timer T_3 has lapsed, indicating that time window to read a bar code symbol without redetecting the object on which it is disposed, is closed. When this condition exists, the control system returns to Block A in FIG. 13A. However, if time remains on timer T_3 , then at Block BB the third control module C_3 resets and restarts timer T_2 and returns to Block CC. As mentioned above, the control system may flow through the control loop defined by Blocks BB-CC-DD-EE-BB a number of times prior to reading a bar code within time period T_3 .

When the symbol decoding module produces control activation signal $A_3=1$ within time period T_2 , the third control module C_3 determines at Block FF whether the decoded bar code symbol is different from the previously decoded bar code symbol. If the decoded bar code symbol is different than the previously decoded bar code symbol, then the control system returns to Block O in FIG. 13B. If the currently decoded bar code symbol is not different than the previously decoded bar code symbol, then the third control module C_3 determines whether timer T_3 has lapsed. If the timer T_3 has not lapsed, then the control system returns to Block BB and reenters the control flow defined at Blocks BB through GG, attempting once again to detect and read a bar code symbol on the detected object. However, if at Block GG timer T_3 has lapsed, then the control system returns to Block A in FIG. 13A.

Having described the operation of the illustrative embodiment of the automatic hand-supportable bar code reading device of the present invention, it will be helpful to describe

at this juncture the various conditions which cause state transitions to occur during its operation. In this regard, reference is made to FIG. 14 which provides a state transition diagram for the illustrative embodiment.

As illustrated in FIG. 14, the automatic hand-supportable bar code reading device of the present invention has four basic states of operation namely: object detection, bar code symbol presence detection, bar code symbol reading, and symbol character data transmission/storage. The nature of each of these states has been described above in great detail.

Transitions between the various states are indicated by directional arrows. Besides each set of directional arrows are transition conditions expressed in terms of control activation signals (e.g., A_1 , A_{2S} or A_{2L} and A_3 , and where appropriate, state time intervals (e.g., T_1 , T_2 , T_3 , T_4 , and T_5). Conveniently, the state diagram of FIG. 14 expresses most simply the four basic operations occurring during the control flow within the system control program of FIGS. 13A to 13C. Significantly, the control activation signals A_1 , A_{2S} , A_{2L} and A_3 in FIG. 14 indicate which events within the object detection and/or scan fields can operate to effect a state transition within the allotted time frame(s), where pre-

scribed. Referring now to FIGS. 15 to 15C, the base unit of the illustrative embodiment of the present invention will be described in greater detail.

In order to perform the data packet reception, processing, retransmission, and acknowledgement functions of base unit 3 described above, a circuit board 270 is mounted within the interior volume of support stand portion 14. In the illustrated embodiment, PC board 270 is populated with electronic circuitry and devices for realizing each of the functions represented by the block shown in the system diagram of FIG. 16. As shown in FIG. 15A, flexible communication and power supply cables 7 and 8 are routed through aperture 271 formed in the lower portion of side wall of the support frame, and connect to the electronic circuitry on PC board 270.

In FIG. 16, the system architecture of base unit 3 is schematically represented. As shown, base unit 3 comprises a number hardware and software components, namely: a power supply circuit 273; a receiving antenna element 274; an RF carrier signal receiver circuit 275 base unit identification number storage unit 276; a data packet storage buffer 277; a base unit system controller 278; a data packet frame check module 279; a transmitter number identification module 280; a data packet number identification module 281; a symbol character data extraction module 282; a data format conversion module 283; a serial data transmission circuit 284; and an acoustical acknowledgement signal generation circuit 285. In the illustrative embodiment, a programmed microprocessor and associated memory (i.e., ROM and RAM), indicated by reference numeral 286, are used to realize the base unit system controller 278 and each of the above-described data processing modules 277 to 283. The details of such a programming implementation are known by those with ordinary skill in the art to which the present invention pertains.

As shown in FIG. 16, receiving antenna element 274 is electrically coupled to an input signal port of radio receiver circuit 275 in a conventional manner. In general, the function of radio receiver circuit 275 is to receive and process the data-packet modulated carrier signal transmitted from a remote bar code symbol reader to its mated base unit. The radio receiver circuit of the illustrative embodiment can be realized by configuring several commercially available IC

chips together, although it is understood that there are certainly other ways in which to realize the basic functions of this circuit. As shown in FIG. 16A, receiving antenna 274 is connected to a matching filter circuit 287 realized using miniature inductive and capacitive components. The matching filter circuit is tuned to pass a 912 MHz RF carrier signal transmitted from the data packet transmission circuit 121 of the bar code symbol reading device. The output of matching filter circuit 287 is connected to the input of a first IC chip 288 which converts (i.e., translates) the frequency spectrum of the received modulated carrier signal down to an intermediate frequency band, for subsequent signal processing. In the illustrative embodiment, the first IC chip 288 is realized using the MAF2001 IC chip from Motorola, Inc., and provides a low noise amplifier 289, an double balanced mixer 290. A local oscillator 292 is needed to provide a local oscillator signal of about 922.7 MHz for use in frequency down-conversion in the double balanced mixer 290. Typically, a matching filter 291 is commonly required between local oscillator 292 and mixer 290. As shown in FIG. 16A, the output of the first IC chip is provided to a band-pass filter 293 tuned to about 10.7 MHz, the intermediate frequency band of each base unit. The intermediate signal is then provided as input to a second IC chip 294. In the illustrative embodiment, the second IC chip 294 is realized using the MC13156 IC chip commercially available from Motorola, and provides inter alia an amplification circuit, a quadrature demodulation circuit 295, a binary thresholding circuit 296, and carrier signal detection circuit 297. The function of the second IC chip is four-fold. The first function of the second IC chip is to filter and amplify the intermediate signal to produce in-phase and quadrature phase signal components for use in digital data recovery. The second function of the second IC chip is to recover an analog data signal at the base band portion of the spectrum, by providing the in-phase and quadrature-phase signal components to the quadrature demodulation circuit 295. Suitable quadrature demodulation circuitry for use in practicing the present invention is disclosed in U.S. Pat. No. 4,979,230 to Marz, which is incorporated herein by reference in its entirety. As illustrated in FIG. 16A, the third function of the second IC chip is to convert the analog data signal produced from quadrature demodulation circuit 295 into a digital data signal using a binary-level thresholding circuit 296. The fourth function of the second IC chip is to analyze the incoming signal from the output of band-pass filter 293 in order to detect the incoming carrier signal and produce a carrier detect signal A_7 to the base unit system controller 278. In order to produce a CMOS compatible signal, the recovered digital data signal produced from second IC chip 294 is amplified by a current amplification circuit 298 that is operative whenever a carrier signal is detected (i.e., $A_7=1$). As shown in FIG. 16, the output of current amplification circuit 298 is a serial data stream that is clocked into data packet storage buffer 277 under the control of base unit system controller 278. In general, the data packet storage buffer 277 can be realized using a commercially available Universal Asynchronous Receiver/Transmitter (UART) device. The primary function of data packet buffer memory 277 is to buffer bytes of digital data in the produced digital data stream.

In the illustrative embodiment, it necessary to provide a means within the base unit housing, to recharge the batteries contained within the hand-supportable housing of the portable bar code symbol reading device. Typically, DC electrical power will be available from the host computer system 6, to which the base unit is operably connected by way of

flexible cables **7** and **8**. An electrical arrangement for achieving this function is set forth in FIG. **16**. As shown, power supply circuit **273** aboard the base unit of the present invention comprises a conventional current chopper circuit **299**, a high-pass electrical filter **300** in parallel therewith, and a primary inductive coil **301** in parallel with the high-pass electrical filter. Low voltage DC electrical power provided from the host computer system by way of power cable **8** is provided to direct current (DC) chopper circuit **299**, which is realized on PC board **270** using high-speed current switching circuits. The function of current chopper circuit **299** is to convert the input DC voltage to the circuit into a high-frequency triangular-type (time-varying) waveform, consisting of various harmonic signal components. The function of the high-pass electrical filter is to filter out the lower frequency signal components and only pass the higher frequency signal components to the inductive coil **301**. As such, the high frequency electrical currents permitted to flow through inductive coil **301** induce a high voltage thereacross and produce time-varying magnetic flux (i.e., lines of force). In accordance with well known principles of electrical energy transfer, the produced magnetic flux transfers electrical power from the base unit to the rechargeable battery aboard the bar code symbol reading device, whenever the primary and secondary inductive coils aboard the base unit and the mated device are electromagnetically coupled by the magnetic flux. In order to maximize energy transfer between the base unit and its mated device during battery recharging operations, high permeability materials and well known principles of magnetic circuit design can be used to increase the amount of magnetic flux coupling the primary and secondary inductive coils of the battery recharging circuit.

Referring to FIG. **16**, the function of each of the data processing modules of base unit **3** will now be described in detail.

Upon reception of an incoming carrier signal and the recovery of the digital data stream therefrom, base unit system controller **278** orchestrates the processing of the recovered digital data stream. As shown in FIG. **16**, the operation of data processing modules **279**, **280**, **281**, **282** and **283** are enabled by the production of enable signals E_{PFC} , E_{TID} , E_{DPID} , E_{DE} , and E_{DFC} , respectively, from the base unit system controller.

The primary function of data packet frame check module **279** is to analyze all of the data bytes in the received data packet, including the Start and End of Packet Fields, and determine whether a complete frame (i.e., packet) of digital data bytes has been recovered from the incoming modulated carrier signal. If so, then data packet frame check module **279** produces activation control signal $A_{PFC}=1$, which is provided to the base unit system controller, as shown in FIG. **16**.

The primary function of the transmitter number identification module **280** is to analyze the data bytes in the Transmitter ID Field of the received data packet and determine the Transmitter ID Number preassigned to the bar code reading device that transmitted the data packet received by the base unit. If the Transmitter ID Number of the received data packet matches the preassigned Base Unit Identification No. stored in non-volatile memory (i.e., EPROM) **302** aboard the base unit, then the transmitter number identification module generates control activation signal $A_{TID}=1$, which is provided to the base unit system controller.

The primary function of the packet number identification module **281** is to analyze the data bytes in the Packet Number Field of the received data packet and determine the

Packet Number of the data packet received by the base unit. This module then advises the base unit system controller that a different packet number was received, representing a new group (e.g., now seen) by producing an encoded signal A_{DPID} during the system control process.

The primary function of the symbol character data extraction module **282** is to analyze the data bytes in the Symbol Character Data Field of the received data packet, determine the code represented by the symbol character data, and provided this symbol character data to the data format conversion module **283** under the control of the base unit system controller during the system control process.

The primary function of the data format conversion module **283** is to convert the format of the recovered symbol character data, into a data format that can be used by the host computer symbol **6** that is to ultimately receive and use the symbol character data. In the bar code symbol reading system of first illustrative embodiment, the data format conversion is from ASCII format to RS-232 format, although it is understood that other conversions may occur in alternative embodiment of the present invention. Typically, the data format conversion process is carried out using a data format conversion table which contains the appropriate data structure conversions.

The primary function of the serial data transmission circuit **284** is to accept the format-converted symbol character data from the data format conversion module **283**, and transmit the same as a serial data stream over data communication cable **7**, to the data input port of the host computer system **6** (e.g., cash register, data collection device, inventory computer). Preferably, an RS-232 data communication protocol is used to facilitate the data transfer process. Thus the construction of serial data transmission circuit **284** is conventional and the details thereof are well within the knowledge of those with ordinary skill in the art.

The primary function of acoustical acknowledgement signal generation circuit **285** is to produce an acoustical acknowledgement signal SA in response to the successful recovery of symbol character data from a transmitted data packet. The purpose of the acoustical acknowledgement signal is to notify the user that the transmitted data packet has been successfully received by its mated base unit. In the illustrative embodiment, the intensity of the acoustical acknowledgement signal is such that the remotely situated user of the portable bar code symbol reader can easily hear the acoustical acknowledgement signal in an expected work environment having an average noise floor of at least about 50 decibels. Preferably, the pitch of the acoustical acknowledgement signal is within the range of about 1 to about 10 kilohertz, in order to exploit the sensitivity characteristics of the human auditory apparatus of the user. In the exemplary embodiment, the pitch is about 2.5 kilohertz. Under such conditions, the intensity of such an acoustical acknowledgement signal at its point of generation will typically need to have an output signal power of about 70 decibels in order to be heard by the user in a working environment having an average noise floor of about 50 decibels and an average noise ceiling of about 100 decibels. Acoustical acknowledgement signals of such character can be produced from acoustical acknowledgement signal generation circuit **285**, shown in FIG. **16**.

As shown in FIG. **16B**, acoustical acknowledgement signal generation circuit **285** comprises a number of subcomponents, namely: a decoder circuit **305**; a voltage controlled oscillator (VCO) driver circuit **306**; a VCO circuit **307**; an output amplifier circuit **308**; and a piezo-electric

type electro-acoustic transducer **303** having an output signal bandwidth in the audible range. The operation (i.e., duration) of the acoustical acknowledgment signal generation circuit **285** is controlled by base unit system controller **278** using enable signal E_{AA} . In the illustrative embodiment, enable signal E_{AA} is a digital word encoded to represent one of a number of possible audible pitches or tones that are to be generated upon each successful reception of a transmitted data packet at a mated base station. The function of decoder circuit **305** is to decode the enable signal E_{AA} produced by the base unit system controller and produce a set of voltage signals $\{V_1, V_2, \dots, V_n\}$ which correspond to a specified pitch sequence to be produced by electro-acoustic transducer **309**. The function of VCO driver circuit **306** is to sequentially drive VCO circuit **307** with the produced set of voltages $\{V_1, V_2, \dots, V_n\}$ so that VCO circuit produces over a short time period (e.g., 0.5–1.5 seconds), a set of electrical signals having frequencies that correspond to the specified pitch sequence to be produced from the electro-acoustic transducer **309**. The function of amplifier circuit **308** is to amplify these electrical signals, whereas the function of electro-acoustical transducer **309** is to convert the amplified electrical signal set into the specified pitch sequence for the user to clearly hear in the expected operating environment. As shown in FIGS. **1** and **15A**, the base housing is preferably provided with an aperture or sound port **304** so as to permit the energy of the acoustical signal from transducer **309** to freely emanate to the ambient environment of the user. In particular application, it may be desired or necessary to produce acoustical acknowledgment signal of yet greater intensity levels than those specified above. In such instances, electro-acoustical transducer **309** may be used to excite one or more tuned resonant chamber(s) mounted within or formed as part of the base unit housing.

Having described the structure and general functional components of base unit **3**, it is appropriate at this juncture to now describe the overall operation thereof with reference to the control process shown in FIG. **17**.

As illustrated at Block **A** in FIG. **17**, radio receiving circuit **275** is the only system component that is normally active at this stage of the base unit system control process. All other system components are inactive (i.e., disabled), including base unit system controller **278**; data packet storage buffer **277**, data packet frame check module **279**, transmitter number identification module **280**, data packet number Identification module **281**, symbol character data extraction module **282**, data format conversion module **283**, serial data transmission circuit **284**, and acoustical acknowledgment signal generation circuit **285**. With the radio receiving circuit activated, the base unit is capable of receiving any modulated carrier signal transmitted from any of the bar code symbol reading devices within the data transmission range of the base unit.

At Block **B** in FIG. **17**, radio receiving circuit **275** determines whether it has received a transmitted carrier signal on its receiving antenna element **274**. If it has, then the radio receiving circuit generates a system controller activation signal A_7 , which activates base unit system controller **278** and signal amplifier **276** shown in FIG. **16** and **16A**, respectively. Then at Block C_1 the base unit system controller activates (i.e., enables) data packet storage buffer **277** and data packet frame check module **279** by producing activation control signals $ESB=1$ and $E_{PFC}=1$, respectively. At Block **D**, the base unit system controller determines whether it has received an acknowledgement (i.e., control activation signal $A_{PFC}=1$) from the data packet frame check

module, indicating that the received data packet is properly framed. If the received data packet is not properly framed, then the base unit returns to Block **A** in order to redetect an incoming carrier signal. However, if the received data packet is properly framed, then at Block **E** the base unit system controller enables the transmitter number identification module by generating enable signal $E_{TID}=1$.

At Block **F**, the base unit system controller determines whether it has received an acknowledgement (i.e., control activation signal $A_{TID}=1$) from the transmitter number identification module that the received data packet contains the correct transmitter identification number (i.e., the same number assigned to the base unit and stored in storage unit **276**). If the Transmitter Identification Number contained within the received data packet does not match the base unit identification number stored in storage unit **276**, then the base unit system controller returns to Block **A** whereupon it resumes carrier signal detection. If, however, the transmitter packet number contained within the received data packet matches the base unit identification number, then at Block **G** the base unit system controller enables the data packet number identification module **289** by generating enable signal $E_{DPID}=1$.

At Block **H**, the base unit system controller determines whether it has received an acknowledgement (i.e., control activation signal $A_{DPID}=1$) from the data packet identification module indicating that the received data packet is not a redundant data packet (i.e., from the same transmitted data packet group). If the received data packet is a redundant data packet, then the base unit system controller returns to Block **A**, whereupon carrier signal detection is resumed. If, however, the received data packet is not redundant, then at Block **I** the base unit system controller enables the symbol character data extraction module by generating enable signal $E_{DE}=1$. In response to the generation of this enable signal, the symbol data extraction module reads at Block **J** the symbol character data contained in the received data packet, checks the data for statistical reliability, and writes the extracted symbol character data bytes into a storage buffer (not explicitly shown).

As indicated at Block **K** in FIG. **17**, the base unit system controller then enables the data format conversion module by generating enable signal $E_{DFC}=1$. In response to this enable signal, the data format conversion module converts the data format of the recovered symbol character data and then buffers the format-converted symbol character data bytes in a data buffer (not explicitly shown). At Block **L** the base unit system controller enables the serial data transmission circuit **284** by generating enable signal $E_{DT}=1$. In response to this enable signal, the serial data transmission circuit transmits the format-converted symbol character data bytes over communication cable **7** using serial data transmission techniques well known in the art, as discussed above. When the serial data transmission process is successfully completed, the base unit system controller enables at Block **M** the acoustical acknowledgement signal generation circuit **285** by producing enable signal $E_{AA}=1$. In response to the production of this enable signal, acoustical acknowledgement signal generation circuit **285** generates a high intensity acoustical signal having characteristics of the type described above, thereby informing the user that a transmitted data packet has been received and that the symbol character data packaged therein has been successfully recovered and transmitted to the host computer system. Thereafter, the base unit system controller returns to the Block **A**, as shown.

It is appropriate at this juncture to illustrate the automatic hands-on and hands-free modes of operation of the system while utilized in different mounting installations.

A point-of-sale station is shown in FIGS. 18A and 18B, as comprising an electronic cash register 6 operably connected to the automatic bar code reading system of the first illustrative embodiment by way of flexible communication cable 7. Low voltage DC power is provided to base unit 3 by way of flexible power supply cable 8. In this particular mounting installation, base unit 3 is supported on a horizontal countertop surface. If necessary or desired in such mounting installations, the base plate of base unit 3 may be weighted by affixing one or more dense mass elements to the upper surface of the base plate.

With automatic bar code reading device 2 supported within scanner support stand portion of the base unit, the system is automatically induced into its automatic long-range hands-free mode of operation. However, owing to the positioning of both object detection and scan fields in this mounting installation, only bar code symbols located on small, very low profile objects can be easily read. In order to induce the system into its short-range hands-on mode of operation, the user simply encircles the handle portion of the hand-supportable device with his or her fingers, and then lifts the device out of the scanner support stand. Upon lifting the device out of its stand, the range selection circuit 115 (e.g., including a Halt-effect magnetic flux sensor (mounted in the handle of the housing) detects the absence of magnetic flux produced from a permanent magnet mounted in the support stand, and automatically generates the short-range control activation signal (i.e., $R_1=0$). The details of this range mode-selection mechanism can be found in copending application Ser. No. 07/761,123, supra.

With the automatic bar code reading device held in the user's hand, and a bar coded object 435 in the other hand, the object is moved into the short-range portion of the object detection field as shown in FIG. 18B, where the object is automatically detected, and bar code symbol 436 automatically scanned while the visible laser beam is repeatedly scanned within the scanning volume. After the bar code symbol has been successfully read (i.e., detected and decoded) and a transmitted data packet containing symbol character data has been received and processed at base unit 3 in a manner described hereinabove, a highly audible acoustical acknowledgement signal sack of a predetermined pitch is produced from the base unit. Thereafter, the bar code reading device is placed back within the scanner support stand, where it is once again induced into its long-range hands-free mode of operation.

Having described the preferred embodiments of the present invention, several modifications come to mind.

In the system control process of the illustrative embodiment, shown in FIG. 8, the polygon 36 is actively driven to its desired angular velocity only when the system is in its bar code symbol detection and read modes. In the illustrative embodiment, the moment of inertia of the polygon 36 is ultra-low so that it can instantly attain its desired angular velocity (from rest) in a very short time from when an object is detected within the 3-D scanning volume.

In an alternative embodiment of the present invention, the control system of the laser scanner hereof can be modified so that the scanning polygon 36 is actively driven to idle at angular velocity W_{OD} when the system is in its object detection mode, and actively driven to its desired angular velocity W_{BCD} (i.e., where $W_{BCD} > W_{OD}$) when the system is in the bar code detection mode. Using this control process, the scanning polygon is permitted to quickly attain its desired operating velocity W_{BCD} when an object is detected in the scanning volume, for subsequent scan data collection

operations. This control technique offers the advantage of using a polygon of a high moment of inertia, with the option of periodically imparting torque to the polygon motor shaft during the object detection state to maintain the idling velocity W_{ODS} in an electrically conservative manner. The motor control circuit hereof can be readily modified to realize such a pulsed-torque functionality in the system of the present invention.

In an alternative embodiment, where power consumption is not of critical concern, the scanning polygon can be continuously driven to the desired operating velocity at each state of system operation.

The automatic bar code reading system of the present invention is capable of performing a wide variety of complex decision-making operations in real-time, endowing the system with a level of intelligence hitherto unattained in the bar code symbol reading art. Within the spirit of the present invention, additional decision-making operations may be provided to further enhance the capabilities of the system.

While the various embodiments of the holographic laser scanner hereof have been described in connection with linear (1-D) code symbol scanning applications, it should be clear, however, that the projection laser scanner of the present invention is suitable for scanning 2-D code symbols as well as alphanumeric characters (e.g. textual information) in optical character recognition (OCR) applications.

While the particular illustrative embodiments shown and described above will be useful in many applications in code symbol reading, further modifications to the present invention herein disclosed will occur to persons with ordinary skill in the art. All such modifications are deemed to be within the scope and spirit of the present invention defined by the appended Claims of the Invention.

We claim:

1. A scanner for producing a confined scanning volume for scanning code symbols presented therein, while preventing unintentional scanning of code symbols on objects located outside of the confined scanning volume, the scanner comprising:

- (a) a housing having an optically admittance window through which optical energy can exit said housing and travel towards an object bearing a code symbol; at least a portion of the optical energy reflecting from the object, traveling back through the window, and entering the housing; whereby a central reference axis extends in a substantially longitudinal direction through the housing;
 - (b) an optical energy generation mechanism disposed within the housing for producing a beam of optical energy;
 - (c) a beam sweeping mechanism disposed within the housing for rotation about a rotational axis; the beam sweeping mechanism having at least first, second and third rotating optically reflective surfaces each being disposed at a different acute angle with respect to the rotational axis, for sweeping the beam about the rotational axis along a plurality of different paths, the rotational axis intersecting the central reference axis to thereby define a central reference plane;
 - (d) a stationary array of at least first, second, third, fourth, and fifth stationary optically reflective surfaces disposed within the housing and fixedly mounted with respect to the central reference axis;
- the first stationary optically reflective surface having a transverse axis extending substantially perpendicularly with respect to the central reference plane,

the second and third stationary optically reflective surfaces being substantially symmetrically disposed on opposite sides of the central reference plane, respectively, and adjacent the first optically reflective surface, and

the fourth and fifth stationary optically reflective surfaces being substantially symmetrically disposed on opposite sides of the central reference plane, and substantially adjacent to the second and third stationary optically reflective surfaces, respectively, and substantially adjacent to the beam sweeping mechanism;

(e) an optical energy collection mechanism disposed within the housing and substantially fixedly mounted with respect to the central reference axis, the collection mechanism including

(1) a collection mirror mounted along the central reference plane, so as to permit the beam produced by the optical energy generation mechanism to pass from the collection mirror, substantially along the central reference plane, to the beam sweeping mechanism, for sweeping the beam about the rotational axis thereof along the plurality of different paths, and

(2) an optical energy receiving mechanism for receiving optical energy from the collection mirror at a point substantially within the central reference plane, and detecting the received optical energy and producing an electrical signal indicative of the detected optical energy;

(f) a processing and control mechanism within the housing, for processing the electrical signal, and for controlling the operation of at least one of: (i) the optical energy generation mechanism, and (ii) the beam sweeping mechanism, so that, during scanner operation, optical energy produced by the optical energy generation mechanism passes from the collection mirror, substantially along the central reference plane, directly to the first, second and third rotating optically reflective surfaces of the beam sweeping mechanism, and as the beam reflects off said first, second and third rotating optically reflective surfaces, the beam is swept across the first, second, third, fourth and fifth stationary optically reflective surfaces, so as to produce first, second, third, fourth and fifth groups of plural scan lines, respectively, which are projected out through the window and intersect about a projection axis extending from the window, and within a confined scanning volume extending from substantially adjacent the window to at least about six inches from the window so as to produce a substantially collimated scanning pattern within the confined scanning volume, by which a code symbol can be scanned omnidirectionally while preventing unintentional scanning of code symbols on objects located outside of the confined scanning volume,

each scan line in the first group of scan lines being substantially parallel to each other scan line in the first group of scan lines,

each scan line in the second group of scan lines being substantially parallel to each other scan line in the second group of scan lines,

each scan line in the third group of scan lines being substantially parallel to each other scan line in the third group of scan lines,

each scan line in the fourth group of scan lines being substantially parallel to each other scan line in the fourth group of scan lines, and

each scan line in the fifth group of scan lines being substantially parallel to each other scan line in the fifth group of scan lines,

whereby, when a code symbol is presented to the collimated scanning pattern within the confined scanning volume, the code symbol is scanned within the collimated scanning pattern and at least a portion of the optical energy reflected from the scanned code symbol is directed through the window, reflected off the first, second, third, fourth and fifth stationary optically reflective surfaces, reflected off the first, second and third rotating optically reflective surfaces of the beam sweeping mechanism, collected by the collection mirror, and received by the receiving mechanism for detection, whereupon the electrical signal is produced.

2. The scanner of claim 1 wherein the processing and control mechanism is adapted to decode the electrical signal and produce, data representative of the scanned code symbol.

3. The scanner of claim 1, wherein the different acute angles are selected so that the scan lines within each group of scan lines are substantially equidistant from each other at a distance from the window.

4. The scanner of claim 1, wherein the optical energy generation mechanism includes a laser diode fixedly mounted with respect to the central reference axis, and wherein the first, second, third, fourth and fifth stationary reflective surfaces include first, second, third, fourth and fifth planar mirrors, respectively, each fixedly mounted with respect to the central reference axis.

5. The scanner of claim 1, wherein the first, second, third, fourth and fifth stationary reflective surfaces include first, second, third, fourth and fifth planar mirrors, respectively.

6. The scanner of claim 1 wherein the housing has a head portion and a handle portion.

7. The scanner of claim 1 further including a planar support structure upon which said first, second, third, fourth, fifth stationary reflective surfaces are mounted.

8. The scanner of claim 1, wherein the receiving mechanism comprises a photodetector.

9. The scanner of claim 8, wherein the photodetector is positioned so as to permit receipt of optical energy from the beam sweeping mechanism, and also positioned substantially within the central reference plane.

10. The scanner of claim 1, wherein the code symbol is a bar code symbol.

11. The scanner of claim 1 wherein the housing is adapted for use with a base mechanism for supporting the housing with respect to a counter surface so that at least a portion of the collimated scanning pattern is projected above the counter surface so as to permit scanning a code symbol presented to the collimated scanning pattern.

12. The scanner of claim 11 wherein the base mechanism is attached to the housing.

13. The scanner of claim 12 wherein the base mechanism is detachable from the housing.

14. The scanner of claim 11 wherein the collimated scanning pattern is oriented laterally outward above the counter surface at a point of sale station.

15. The scanner of claim 11, wherein the base mechanism further includes a mechanism for selectively supporting the housing in any one of a plurality of positions above the counter surface so that the collimated scanning pattern can be projected about the projection axis above the counter surface in any one of a plurality of orientations corresponding to the plurality of positions.

16. A scanner for producing a confined scanning volume for scanning code symbols presented therein, while prevent-

ing unintentional scanning of code symbols on objects located outside of the confined scanning volume, the scanner comprising:

- (a) a housing having an optically admissive window through which optical energy can exit said housing and travel towards an object bearing a code symbol; at least a portion of the optical energy reflecting from the object, traveling back through the window, and entering the housing; whereby a central reference axis extends, in a substantially longitudinal direction, through the housing;
- (b) an optical energy generation mechanism disposed within the housing for producing a beam of optical energy;
- (c) a beam sweeping mechanism disposed within the housing for rotation about a rotational axis; the beam sweeping mechanism having a plurality of rotating optically reflective surfaces each being disposed at a different acute angle with respect to the rotational axis, for sweeping the beam about the rotational axis along a plurality of different paths, the rotational axis intersecting the central reference axis to thereby define a central reference plane;
- (d) a stationary array of at least first, second, third, fourth, and fifth stationary optically reflective surfaces disposed within the housing and fixedly mounted with respect to the central reference axis;
 - the first stationary optically reflective surface having a transverse axis extending substantially perpendicularly with respect to the central reference plane,
 - the second and third stationary optically reflective surfaces being substantially symmetrically disposed on opposite sides of the central reference plane, respectively, and adjacent the first optically reflective surface, and
 - the fourth and fifth stationary optically reflective surfaces being substantially symmetrically disposed on opposite sides of the central reference plane, and substantially adjacent to the second and third stationary optically reflective surfaces, respectively, and substantially adjacent to the beam sweeping mechanism;
- (e) an optical energy collection mechanism disposed within the housing and fixedly mounted with respect to the central reference axis, the collection mechanism including
 - (1) a collection mirror substantially fixedly mounted along the central reference plane, so as to permit the beam produced by the optical energy generation mechanism to pass from the collection mirror, substantially along the central reference plane, to the beam sweeping mechanism, for sweeping the beam about the rotational axis along the plurality of different paths, and
 - (2) an optical energy receiving mechanism for receiving optical energy from the collection mirror at a point substantially within the central reference plane, and detecting the received optical energy and producing an electrical signal indicative of the detected optical energy;
- (f) a processing and control mechanism within the housing, for processing the electrical signal, and for controlling the operation of at least one of: (i) the optical energy generation mechanism, and (ii) the beam sweeping mechanism, so that, during scanner operation, optical energy produced by the optical energy generation mechanism passes from the collec-

tion mirror, substantially along the central reference plane, and in a sequential manner to each of a plurality of the rotating optically reflective surfaces of the beam sweeping mechanism, and as the beam sequentially reflects off each of the plurality of rotating optically reflective surfaces, the beam is swept across the first, second, third, fourth and fifth stationary optically reflective surfaces, so as to produce first, second, third, fourth and fifth groups of plural scan lines, respectively, which are projected out through the window and intersect about a projection axis extending from the window, and within a confined scanning volume extending from substantially adjacent the window to at least about six inches from the window so as to produce a substantially collimated scanning pattern within the confined scanning volume, by which a code symbol can be scanned omnidirectionally while preventing unintentional scanning of code symbols on objects located outside of the confined scanning volume,

each scan line in the first group of scan lines being substantially parallel to each other scan line in the first group of scan lines,

each scan line in the second group of scan lines being substantially parallel to each other scan line in the second group of scan lines,

each scan line in the third group of scan lines being substantially parallel to each other scan line in the third group of scan lines,

each scan line in the fourth group of scan lines being substantially parallel to each other scan line in the fourth group of scan lines, and

each scan line in the fifth group of scan lines being substantially parallel to each other scan line in the fifth group of scan lines,

whereby, when a code symbol is presented to the collimated projected scanning pattern within the confined scanning volume, the code symbol is scanned within the collimated scanning pattern and at least a portion of the optical energy reflected from the scanned code symbol is directed through the window, reflected off the first, second, third, fourth and fifth stationary optically reflective surfaces, sequentially reflected off the rotating optically reflective surfaces of the beam sweeping mechanism, collected by the collection mirror, and received by the receiving mechanism for detection, whereupon the electrical signal is produced.

17. The scanner of claim **16** wherein the housing is adapted for use with a base mechanism for supporting the housing with respect to a counter surface so that at least a portion of the collimated scanning pattern is projected above the counter surface so as to permit scanning a code symbol presented to the collimated scanning pattern.

18. The scanner of claim **17** wherein the base mechanism is attached to the housing.

19. The scanner of claim **18** wherein the base mechanism is detachable from the housing.

20. The scanner of claim **16** wherein the processing and control mechanism is adapted to decode the electrical signal and produce data representative of the scanned code symbol.

21. The scanner of claim **16**, wherein the different acute angles are selected so that the scan lines within each group of scan lines are substantially equidistant from each other at a distance from the window.

22. The scanner of claim **16**, wherein the optical energy generation mechanism includes a laser diode substantially fixedly mounted with respect to the central reference axis,

49

and wherein the first, second, third, fourth and fifth stationary reflective surfaces include first, second, third, fourth and fifth planar mirrors, respectively, each substantially fixedly mounted with respect to the central reference axis.

23. The scanner of claim 16, wherein the first, second, third, fourth and fifth stationary reflective surfaces include first, second, third, fourth and fifth planar mirrors, respectively.

24. The scanner of claim 16 wherein the housing has a head portion and a handle portion.

25. The scanner of claim 16 wherein the collimated scanning pattern is oriented laterally outward above the counter surface at a point of sale station.

26. The scanner of claim 16 wherein the base mechanism further includes a mechanism for selectively supporting the housing in any one of a plurality of positions above the counter surface so that the collimated scanning pattern can be projected about the projection axis above the counter surface in any one of a plurality of orientations corresponding to the plurality of positions.

27. The scanner of claim 16 further including a planar support structure upon which said first, second, third, fourth and fifth stationary reflective surfaces are mounted.

28. The scanner of claim 16 wherein the receiving mechanism comprises a photodetector.

29. The scanner of claim 28, wherein the photodetector is positioned so as to permit receipt of optical energy from the beam sweeping mechanism, and also positioned substantially within the central reference plane.

30. The scanner of claim 16, wherein the code symbol is a bar code symbol.

31. A scanner for producing a confined scanning volume for scanning code symbols presented therein, while preventing scanning of code symbols on objects located outside of the confined scanning volume, the scanner comprising:

(a) a housing having an optically admissive window through which optical energy can exit the housing and travel towards an object bearing a code symbol; at least a portion of the optical energy reflecting from the object, traveling back through the window, and entering the housing; whereby a central reference axis extends, in a substantially longitudinal direction, through the housing;

(b) an optical energy generation mechanism disposed within the housing for producing a beam of optical energy;

(c) a beam sweeping mechanism disposed within the housing for rotation about a rotational axis; the beam sweeping mechanism having a plurality of rotating optically reflective surfaces each disposed at a different acute angle with respect to the rotational axis, for sweeping the beam about the rotational axis along a plurality of different paths, the rotational axis intersecting the central reference axis to thereby define a central reference plane;

(d) a substantially stationary reflection mechanism including a plurality of stationary optically reflective surfaces disposed within the housing and fixedly mounted with respect to the central reference axis; wherein the plurality of stationary optically reflective surfaces includes at least a first stationary optically reflective surface having a transverse axis extending substantially perpendicularly with respect to the central reference plane;

(e) an optical energy collection mechanism disposed within the housing and substantially fixedly mounted with respect to the central reference axis, the collection mechanism including

50

(i) a collection mirror fixedly mounted along the central reference plane, so as to permit the beam produced by the optical energy generation mechanism to pass from the collection mirror, substantially along the central reference plane, to the beam sweeping mechanism, for sweeping the beam about the rotational axis thereof along the plurality of different paths, and

(ii) an optical energy receiving mechanism for receiving optical energy from the collection mirror at a point substantially within the central reference plane, and detecting the received optical energy and producing an electrical signal indicative of the detected optical energy;

(f) a processing and control mechanism within the housing, for processing the electrical signal, and for controlling the operation of at least one of: (i) the optical energy generation mechanism, and (ii) the beam sweeping mechanism, so that, during scanner operation, optical energy produced by the optical energy generation mechanism passes from the collection mirror, substantially along the central reference plane, and in a sequential manner to each of a plurality of the rotating optically reflective surfaces of the beam sweeping mechanism, and as the beam sequentially reflects off each of the plurality of rotating optically reflective surfaces, the beam is sequentially swept across each of the plurality of stationary optically reflective surfaces of the stationary reflection mechanism, so as to produce a corresponding plurality of plural scan line groups which are projected out through the window and intersect about a projection axis extending from the window, and within a confined scanning volume extending from substantially adjacent the window to at least about six inches from the window so as to produce a substantially collimated projected scanning pattern within the confined scanning volume, by which a code symbol can be scanned omni-directionally while preventing unintentional scanning of code symbols on objects located outside of the confined scanning volume,

the plural scan line groups including at least a first group of scan lines wherein each scan line in the first group is substantially parallel to each other scan line in the first group;

whereby, when a code symbol is presented to the collimated projected scanning pattern within the confined scanning volume, the code symbol is scanned within the collimated projected scanning pattern and at least a portion of the optical energy reflected from the scanned code symbol is directed through the window, sequentially reflected off each of the plurality of stationary optically reflective surfaces of the stationary reflection mechanism and sequentially reflected off the rotating optically reflective surfaces of the beam sweeping mechanism, collected by the collection mirror, and received by the receiving mechanism for detection, whereupon the electrical signal is produced.

32. The scanner of claim 31 wherein the housing is adapted for use with a base mechanism for supporting the housing with respect to a counter surface so that at least a portion of the collimated scanning pattern is projected above the counter surface so as to permit scanning a code symbol presented to the collimated scanning pattern.

33. The scanner of claim 32 wherein the base mechanism is attached to the housing.

34. The scanner of claim 33 wherein the base mechanism is detachable from the housing.

51

35. The scanner of claim 31 wherein the processing and control mechanism is adapted to decode the electrical signal and produce data representative of the scanned code symbol.

36. The scanner of claim 31, wherein the different acute angles are selected so that the plural scan lines within each scan line group are substantially equidistant from each other at a distance from the window.

37. The scanner of claim 31, wherein the optical energy generation mechanism includes a laser diode fixedly mounted with respect to the central reference axis, and wherein the stationary reflection mechanism includes a plurality of planar mirrors, each substantially fixedly mounted with respect to the central reference axis.

38. The scanner of claim 31, wherein the optical energy generation mechanism includes a laser diode substantially fixedly mounted with respect to the central reference axis, and wherein the stationary reflection mechanism includes an integrated mechanical member comprising plurality of planar reflective surfaces.

39. The scanner of claim 31, wherein the stationary reflection mechanism includes first, second, third, fourth and fifth planar mirrors.

40. The scanner of claim 31 wherein the housing has a head portion and a handle portion.

52

41. The scanner of claim 31 wherein the collimated scanning pattern is oriented laterally outward above the counter surface at a point of sale station.

42. The scanner of claim 32, wherein the base mechanism further includes a mechanism for selectively supporting the housing in any one of a plurality of positions above the counter surface so that the collimated scanning pattern can be projected about the projection axis above the counter surface in any one of a plurality of orientations corresponding to the plurality of positions.

43. The scanner of claim 31 further including a planar support structure upon which the stationary reflection mechanism is mounted.

44. The scanner of claim 31, wherein the receiving mechanism comprises a photodetector.

45. The scanner of claim 31, wherein the receiving mechanism comprises a light-sensitive semiconductor material.

46. The scanner of claim 44, wherein the photodetector is positioned so as to permit receipt of optical energy from the beam sweeping mechanism, and also positioned substantially within the central reference plane.

47. The scanner of claim 31, wherein the code symbol is a bar code symbol.

* * * * *