



US006860458B1

(12) **United States Patent**  
**Pagano**

(10) **Patent No.:** **US 6,860,458 B1**  
(45) **Date of Patent:** **Mar. 1, 2005**

(54) **BOOK HOLDER**

(76) Inventor: **Samuel Pagano**, 1632 Squaw Creek,  
Girard, OH (US) 44420

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/917,520**

(22) Filed: **Jul. 30, 2001**

(51) **Int. Cl.<sup>7</sup>** ..... **A47B 19/00**

(52) **U.S. Cl.** ..... **248/441.1; 248/451; 248/174**

(58) **Field of Search** ..... 248/451, 452,  
248/446, 448, 449, 149, 152, 174, 441.1,  
455, 457

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

456,089 A *	7/1891	Harrison	190/10
1,899,404 A	2/1933	White	
2,156,225 A	4/1939	O'Meara	
2,441,932 A	5/1948	Curry	
3,043,047 A *	7/1962	La Fleur	248/220.41
D219,757 S *	1/1971	Pagano	D19/91
3,813,075 A *	5/1974	Capper	248/451
4,116,414 A	9/1978	Robertson	
4,416,414 A	11/1983	Edgerton	
4,470,571 A *	9/1984	Hartman	248/452
4,496,127 A *	1/1985	Nelson	211/43
4,531,642 A *	7/1985	Racich	211/42

4,712,760 A	12/1987	Winter	
4,787,595 A *	11/1988	Hegarty	248/447
4,925,146 A *	5/1990	Hegarty	248/447
5,052,650 A	10/1991	Beile et al.	
5,060,904 A *	10/1991	Hegarty	248/447
D327,172 S *	6/1992	Pagano	248/460
5,154,391 A *	10/1992	Hegarty	248/205.2
5,230,535 A *	7/1993	Figlenski	248/441.1
5,351,927 A *	10/1994	Howell	16/18 R
5,356,109 A *	10/1994	Biasini	248/441.1
D366,568 S	1/1996	Pagano	
5,634,623 A *	6/1997	Hoijtink	248/448
D381,212 S	7/1997	Pagano	
5,855,329 A	1/1999	Pagano	
5,979,858 A	11/1999	Bronson	
6,367,760 B1 *	4/2002	Pagano	248/451
6,425,567 B2 *	7/2002	Schutze	248/452

\* cited by examiner

*Primary Examiner*—Kimberly Wood


*Assistant Examiner*—Naschica S. Morrison

(74) *Attorney, Agent, or Firm*—Harpman & Harpman

(57) **ABSTRACT**

A convertible book holder for holding and positioning books and documents. The book holder includes a freestanding document display and support portion with an integral resilient clip and independent paper engagement clip. An adaptive enlarged L-shaped document support is removably secured over the freestanding support portion to enhance the holding capabilities for larger and oversize text of instructional type books.

**8 Claims, 6 Drawing Sheets**







FIG. 2






FIG. 3





FIG. 5







FIG. 6






FIG. 8




FIG. 9

**BOOK HOLDER****BACKGROUND OF THE INVENTION****1. Technical Field**

This device relates to book and copy holders that are used to hold and retain different size copy and books for independent hands free use.

**2. Description of Prior Art**

Prior art devices of this type have relied on a variety of different constructions for supporting a book or papers in an upstanding readable position without user assistance. Heretofore, it was required that the user uses at least one hand to hold the book open in an upright position for use. Hardback books could be propped up by leaning on some article and non-rigid publications such as workbooks, for example, would require more support. Accordingly, a number of book and page holders have been developed to address this problem.

Typically, prior art book holders of this type have a support frame with attachment straps, hooks or clamps to hold the books on the support stand in open position. Such devices can be seen in U.S. Pat. Nos. 1,899,404, 2,156,225, 2,441,932, 4,416,414, 4,712,760, 5,052,650 and 5,979,858. Applicant's own U.S. Pat. No. D366,568, D381,212, and U.S. Pat. No. 5,855,392.

In U.S. Pat. No. 1,899,404, a book holder and table can be seen having a book support platform pivotally secured to an adjustable frame stand with a center engagement clip and a pair of adjustable leaf retainers.

U.S. Pat. No. 5,979,858 is directed to a copyholder having an L-shaped free stand copy rest with an upright support panel. A copy engagement clip is positioned over the upper edge of the panel with legs that apply pressure towards one another for engaging the copy against the support panel.

Applicant's U.S. Pat. Nos. D366,568 and D381,212 disclose designs having freestanding book holder in D366,568 with an engagement slot and a holder adapter in D381,212 that has an enlarged L-shaped support panel to be interengaged with applicant's book holder of U.S. Pat. No. D366,568.

In U.S. Pat. No. 5,855,329 applicant's book holder is shown having multiple document engagement clips that are engageable from the main support surface.

**SUMMARY OF THE INVENTION**

A book holder of the present invention for supporting and displaying a variety of different size books and documents in an upright usable position. The holder includes a freestanding leg support adapted to lockingly engage on an elongated angled support surface thereon. The leg support has bi-lateral offset braces to allow for vertical nesting of multiple holders for storage.

**DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a perspective view of the book holder of the invention;

FIG. 2 is a rear elevational view of the book holder as seen in FIG. 1;

FIG. 3 is a side elevational view of the free standing support portion of the book holder with the elongated support surface shown in broken lines as to be engaged thereon;

FIG. 4 is a front elevational view of the freestanding support with the elongated support surface indicated in broken lines;

FIG. 5 is an enlarged partial cross-sectional view of the registration between the freestanding support and elongated support surface;

FIG. 6 is an elongated partial rear elevational view of the registration as seen in FIG. 5;

FIG. 7 is an enlarged partial rear elevational view of interengaging portions of the book holder when in stacked stored position; and

FIG. 8 is an enlarged partial side elevational view of the free standing portion illustrating deflection of the resilient areas in broken lines.

FIG. 9 is an enlarged partial side elevational view of the free standing portion illustrating the resilient clip in solid and broken lines extending tiered from.

**DESCRIPTION OF THE PREFERRED EMBODIMENT**

Referring now to FIGS. 1 and 2 of the drawings, a book holder **10** of the invention can be seen having a free standing support portion **11** and a removable enlarged book support portion **12**. The freestanding support portion **11** has a document engagement surface **13** having an integral angular base **14** with a front wall foot **15** extending vertically from the base **14**. A pair of longitudinally spaced registration engagement notches **13A** and **13B** are formed within the engagement surface **13** adjacent the base **14** as best seen in FIGS. 3 and 4 of the drawings. A support leg portion **16** extends integrally from the end of the document engagement surface **13** having a return portion **17** in spaced parallel relation thereto. A ground engagement extension **18** extends integrally from the return portion **17** in oppositely disposed angular relation to said engagement surface **13**. A resilient clip **19** extends integrally from the ground engagement extension **18** with an upstanding-inclined surface **20** providing engaging force against the return portion **17**. A two-part page-retaining clip fitting **21** is formed on an angular end surface **22** of the inclined surface **20** as best seen in FIGS. 8 and 9 of the drawings.

The page-retaining clip **21** has an upper portion **23** that extends in spaced parallel relation to the surface **22**. The upper portion **23** is contoured on its inner surface **24**. A paper engagement spacing lug **25** is in vertical spaced relation there below. An upstanding paper engagement ridge **25A** extends transversely on the surface of the lug **25**.

A pair of brackets **26** and **27** interconnects the engagement surface **13** and the ground engagement extension **18**. It will be seen that the respective brackets **26** and **27** are staggered vertically to afford stackability of multiple units for storage as will be illustrated in FIG. 7 of the drawings as is well understood by those skilled in the art.

The brackets **26** and **27** along with the respective leg **16** and engagement surface **13** form a structural triangle of the freestanding support portion **11** as best seen in FIG. 3 of the drawings.

Referring now to FIGS. 1-4 of the drawings, the enlarged angle book support portion **12** can be seen having an inclined upper surface **28** with a base **29** extending angularly there from. The base **29** has an upper engagement surface **30** with a vertically disposed front **31** portion of which form a pair of oppositely disposed legs **32**. The upper surface **30** of the base **29** and front surface **31** have respective interconnecting sidewall surfaces **33** and **34**.

Referring now to FIG. 2 of the drawings, the book support portion **12** has a top perimeter edge **35** with a notch at **36** extending inwardly therefrom. A pair of guide bars **37** and

3

38 extend from a backside 39 of the book support portion 12 in spaced parallel relation to said notch 36. Engagement tabs 40 and 41 extend from portions of said respective guide bars 37 and 38 for registration with the document engagement surface 13 when attached thereto as will be discussed in greater detail hereinafter. 5

A pair of fastening lugs 42 and 43 extend integrally from the backside 39 of the book support portion 12 as best seen in FIGS. 2, 3, 5 and 6 of the drawings. Each of the lugs 42 and 43 have a recessed registration area at 42A and 43A extending transversely across their respective upper surfaces. Accordingly, the lugs 42 and 43 are registerable within the respective notches 13A and 13B as best seen in FIGS. 5 and 6 of the drawings. 10

It will be noted that the lugs 42 and 43 are frictionally engaged on their recessed areas 42A and 43A by the notched surface of the document engagement surface 13 securely holding the book support portion 12 thereto. 15

It will be evident from the above description that the free standing support portion 11 also can be used independently to hold single sheet documents and small books and the like by placement on the L-shaped document engagement surface 13. Alternately the enlarged support book portion 12 can be attached thereto as hereinbefore described to provide a larger book and document support area while still maintaining a single sheet (P) holding capability afforded by the page retaining clip fitting 21 as seen in FIG. 8 in broken lines and engagement of book portions (not shown) by the resilient portion 19 as hereinbefore described. 20

Once attached, the enlarged book supporting portion 12 can easily be removed by applying pressure between the inside of the front surface 31 and front wall foot 15 as indicated by broken line arrow in FIG. 5 of the drawings. 25

Having thus described my invention, it will be apparent to those skilled in the art that various changes and modifications may be made therein without departing from the spirit of the invention. 30

Therefore I claim:

1. A book holder comprises in combination; 35

a freestanding portion and a book support portion removably secured thereto;

said Standing portion having a planar document engagement surface with an integral angular extending base extending there from and an angularly extending leg portion; 40

a resilient clip integrally extending from said leg portion; said resilient clip having an upstanding inclined surface there above; 45

a paper retaining clip extending from said upstanding inclined surface in spaced relation to said planar document engagement surface, said paper retaining clip having an elongated body member with contoured a inner surface and an engagement lug in spaced relation to said contoured surface; 50

a pair of spaced independent horizontal brackets that are vertically offset from each other extending between said leg portion and said planar document engagement surface; 55

said book support portion comprises:

a planar inclined upper support surface with an integral document support base extending at a right angle 60

4

there from having a front wall surface angularly extending from said document support base;

oppositely disposed bifurcated fixation lugs extending from the intersection of said planar inclined upper support surface and said integral document support base of said book support portion for selective registration within notches in said planar document engagement surface of said free standing portion.

2. The book holder set forth in claim 1 wherein said front wall surface has a pair of integral oppositely disposed feet extending there from.

3. The book holder set forth in claim 1 wherein said planar inclined upper support surface is substantially flat having a notch extending inwardly from a top perimeter edge thereof. 15

4. The book holder set forth in claim 3 wherein said notch in said upper support surface has a pair of parallel spaced guide bars adjacent said notch, and means for selective engagement of said planar document engagement surface therewith. 20

5. The book holder set forth in claim 4 wherein said means for selective engagement of said planar document engagement surface comprises locking tabs extending from a portion of said guide bars, and overlying said notch in spaced parallel relation to one another. 25

6. A book holder comprising;

freestanding portion and a book support portion removably secured thereto;

said freestanding portion having an inclined planar document engagement surface with an interconnected angularly disposed document support base and an angularly extending leg portion;

a resilient clip integrally extending from said leg portion; said resilient clip having an upstanding inclined surface there above;

a paper retainer clip extending from said resilient clip, brackets extending between said leg portion and inclined planar document engagement surface in vertical spaced relation to each other;

said book support portion comprises;

an upper support surface having a notch extending inwardly from a top perimeter edge thereof, a pair of parallel oppositely disposed guide bars adjacent said notch, locking tabs extending from a portion of said guide bars overlying said notch in spaced parallel relation to one another, an integral base extending from the upper support surface having a front leg surface, locking fixtures extending from said book support portion for selective registration on said inclined document engagement surfaces.

7. The book holder set forth in claim 6 wherein said locking tabs comprise:

a pair of longitudinally spaced lugs extending from the intersection of said upper support surface and integral base.

8. The book holder set forth in claim 6 wherein said inclined planar document engagement surface of said free standing portion has a pair of longitudinally spaced locking registration notches within.

\* \* \* \* \*