



US006861639B2

(12) **United States Patent**
Al-Ali

(10) **Patent No.:** **US 6,861,639 B2**
(45) **Date of Patent:** **Mar. 1, 2005**

(54) **SYSTEMS AND METHODS FOR INDICATING AN AMOUNT OF USE OF A SENSOR**

5,337,744 A 8/1994 Branigan
5,438,986 A 8/1995 Disch et al.
5,452,717 A 9/1995 Branigan et al.
5,482,036 A 1/1996 Diab et al.
5,490,505 A 2/1996 Diab et al.
5,490,523 A 2/1996 Isaacson et al.

(75) Inventor: **Ammar Al-Ali**, Tustin, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(List continued on next page.)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **10/357,531**

EP 0262 779 A1 4/1988
EP 0 481 612 A1 4/1992
EP 0 745 348 A1 12/1996
EP 0 832 598 A2 9/1997
WO WO 97/23159 7/1997

(22) Filed: **Feb. 3, 2003**

(65) **Prior Publication Data**

US 2003/0111592 A1 Jun. 19, 2003

OTHER PUBLICATIONS

Related U.S. Application Data

<http://www.masimo.com/systemo.htm>, "System Overview & Performance," 2 pages reviewed on Sep. 17, 1999.
<http://www.masimo.com/pandt.htm>, "Products & Technology," 1 page reviewed on Sep. 17, 1999.
<http://www.masimo.com/cables.htm>, "Patient Cables," 1 page reviewed on Sep. 17, 1999.

(63) Continuation of application No. 09/502,032, filed on Feb. 10, 2000, now Pat. No. 6,515,273, which is a continuation-in-part of application No. 09/420,544, filed on Oct. 19, 1999, now Pat. No. 6,580,086.

(List continued on next page.)

(60) Provisional application No. 60/150,922, filed on Aug. 26, 1999.

Primary Examiner—Que T. Le

(51) **Int. Cl.**⁷ **H01L 31/00**

(74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson & Bear, LLP

(52) **U.S. Cl.** **250/214.1; 250/214 R**

(57) **ABSTRACT**

(58) **Field of Search** 250/214.1, 559.1


Aspects of the present invention include systems and methods for indicating an amount of use of a pulse oximetry sensor. According to one embodiment, the system includes an oximeter that monitors the amount of use for a given sensor. The oximeter and/or the sensor may advantageously include a visual alarm, an audio alarm, a vibrational alarm, a power down function, or the like, which can be activated when a predetermined amount of use has expired. According to another embodiment, the system includes a sensor having a memory device storing a unique identifier.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,621,643 A 11/1986 New, Jr. et al.
4,685,464 A 8/1987 Goldberger et al.
RE33,643 E 7/1991 Isaacson et al.
5,090,410 A 2/1992 Saper et al.
5,170,786 A 12/1992 Thomas et al.
5,247,931 A 9/1993 Norwood
5,309,908 A 5/1994 Friedman et al.
5,313,940 A 5/1994 Fuse et al.
5,319,355 A * 6/1994 Russek 340/573.1

13 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

5,588,427 A 12/1996 Tien
 5,638,816 A 6/1997 Kiani-Azarbayjany et al.
 5,638,818 A 6/1997 Diab et al.
 5,645,440 A 7/1997 Tobler et al.
 5,660,567 A 8/1997 Nierlich et al.
 5,685,299 A 11/1997 Diab et al.
 D393,830 S 4/1998 Tobler et al.
 5,743,262 A 4/1998 Lepper, Jr. et al.
 5,758,644 A 6/1998 Diab et al.
 5,760,910 A 6/1998 Lepper, Jr. et al.
 5,769,785 A 6/1998 Diab et al.
 5,782,757 A 7/1998 Diab et al.
 5,807,248 A 9/1998 Mills
 5,810,724 A 9/1998 Gronvall
 5,817,010 A 10/1998 Hibl
 5,823,950 A 10/1998 Diab et al.
 5,860,919 A 1/1999 Kiani-Azarbayjany et al.
 5,890,929 A 4/1999 Mills et al.
 5,919,133 A 7/1999 Taylor et al.
 5,919,134 A 7/1999 Diab
 5,934,925 A 8/1999 Tobler et al.
 5,939,609 A 8/1999 Knapp et al.
 5,940,182 A 8/1999 Lepper, Jr. et al.
 5,991,355 A 11/1999 Dahlke
 5,995,855 A 11/1999 Kiani et al.
 5,997,343 A 12/1999 Mills et al.
 6,002,952 A 12/1999 Diab et al.
 6,011,986 A 1/2000 Diab et al.
 6,036,642 A 3/2000 Diab et al.
 6,067,462 A 5/2000 Diab et al.
 6,081,735 A 6/2000 Diab et al.
 6,088,607 A 7/2000 Diab et al.
 6,110,522 A 8/2000 Lepper, Jr. et al.
 6,151,516 A 11/2000 Kiani-Azarbayjany et al.
 6,152,754 A 11/2000 Gerhardt et al.
 6,157,850 A 12/2000 Diab et al.
 6,165,005 A 12/2000 Mills et al.
 6,184,521 B1 2/2001 Coffin, IV et al.
 6,206,830 B1 3/2001 Diab et al.
 6,229,856 B1 5/2001 Diab et al.
 6,236,872 B1 5/2001 Diab et al.
 6,256,523 B1 7/2001 Diab et al.
 6,263,222 B1 7/2001 Diab et al.
 6,278,522 B1 8/2001 Lepper, Jr. et al.
 6,280,213 B1 8/2001 Tobler et al.
 6,285,896 B1 9/2001 Tobler et al.
 6,308,089 B1 * 10/2001 von der Ruhr et al. 600/338
 6,334,065 B1 12/2001 Al-Ali et al.
 6,349,228 B1 2/2002 Kiani et al.
 6,360,114 B1 3/2002 Diab et al.
 6,371,921 B1 4/2002 Caro et al.
 6,377,829 B1 4/2002 Al-Ali
 6,388,240 B2 5/2002 Schulz et al.
 6,397,091 B2 5/2002 Diab et al.
 6,430,525 B1 8/2002 Weber et al.
 6,470,199 B1 10/2002 Kopotic et al.
 6,501,975 B2 12/2002 Diab et al.
 6,515,273 B2 2/2003 Al-Ali
 6,525,386 B1 2/2003 Mills et al.
 6,526,300 B1 2/2003 Kiani et al.
 6,541,756 B2 4/2003 Schulz et al.
 6,542,764 B1 4/2003 Al-Ali et al.
 6,580,086 B1 6/2003 Schulz et al.
 6,584,336 B1 6/2003 Ali et al.
 6,597,933 B2 7/2003 Kiani et al.
 6,606,511 B1 8/2003 Ali et al.
 6,632,181 B2 10/2003 Flaherty et al.
 6,640,116 B2 10/2003 Diab
 6,643,530 B2 11/2003 Diab et al.

6,650,917 B2 11/2003 Diab et al.
 6,654,624 B2 11/2003 Diab et al.
 6,658,276 B2 12/2003 Kianl et al.
 6,671,531 B2 12/2003 Al-Ali et al.
 6,678,543 B2 1/2004 Diab et al.
 6,684,090 B2 1/2004 Ali et al.
 6,697,656 B1 2/2004 Al-Ali
 6,697,658 B2 2/2004 Al-Ali
 6,699,194 B1 3/2004 Diab et al.

OTHER PUBLICATIONS

<http://www.masimo.com/adt.htm>, "Inop-adt—Adult Disposable Digit Sensor," 1 page reviewed on Sep. 17, 1999.
http://www.mrequipment.com/products/pulse_oximetry.htm, "MR Equipment Magnetic Resonance Equipment Corporation, Pulse Oximetry in MRI Model 3500 Pulse Oximeter," 2 pages reviewed on Sep. 17, 1999.
http://www.mrequipment.com/products/oximetry_patient_mntrg.htm, "MR Equipment Magnetic Resonance Equipment Corporation, MR-Compatible High-Performance Optical Fiber Sensors, Pulse Oximetry Sensors for MRI Fiber Optic Sensors for use with MR-Compatible Pulse Oximeter," 2 pages reviewed on Sep. 17, 1999.
 Article entitled "Masimo Corporation, Discrete Saturation Transform Example," reviewed on Sep. 17, 1999.
<http://www.dalsemi.com>, "Dallas Semiconductor," p. 1 only, reviewed on Jan. 12, 2000.
http://www.dalsemi.com/Prod_info/AudoID/index.html, "Dallas Semiconductor Automatic Information Overview," 10 pages reviewed on Jan. 12, 2000.
 Awtry, "Sensors: The Journal of Applied Sensing Technology, Transmitting Data and Power over One-Wire Bus," 4 pages, Feb. 1997.
 Dallas Semiconductor, Application Note 30, "Recording Power Cycling Information Using the DS1602/DS1603," pp. 7-9, 1993.
 Dallas Semiconductor, "DS 1602 Elapsed Time Counter," pp. 468-476, 1993.
 Dallas Semiconductor, "DS 1603 Elapsed Time Counter Modual," pp. 477-484, 1993.
 Dallas Semiconductor "DS2401 Silicon Serial Number," 10 pages, Oct. 21, 1999.
 Dallas Semiconductor "DS2502 1Kbit Add-Only Memory," pp. 149-169, 1993.
 Patent Abstract of Japan; Publication No.: 10314149; Publication Date: Feb. 12, 1998; Application No.: 09/129,922; Application Date: May 20, 1997; Inventor: Suzuki Hiroaki; Title Probe Exchangeable Electric Measurement Device, Probe Management Method and Pulse Oximeter.
 Patent Abstract of Japan; Publication No.: 1053662; Publication Date: Feb. 26, 1999.
 Patent Abstract of Japan; Publication No.: 02017462; Publication Date: Jan. 22, 1990.
 Patent Abstract of Japan; Publication No.: 11185193; Publication Date: Jul. 9, 1999.
 PCT International Search Report, App. No.: PCT/US 00/22849, App. Date: Aug. 21, 2000, 4 pages.
 PCT International Search Report, App. No.: PCT/US01/04265, App. Date Feb. 9, 2001, 4 pages.
 International publication corresponding to copending U.S. Appl. No. 09/420,544, filed Oct. 19, 1999.
 Copending U.S. Appl. No. 09/770,757, published on Nov. 29, 2001 as U.S. Pub. No. US 2001/0045532 A1.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

SYSTEMS AND METHODS FOR INDICATING AN AMOUNT OF USE OF A SENSOR

REFERENCE TO RELATED APPLICATION

The present application claims priority benefit under 35 U.S.C. §120 to and is a continuation of U.S. patent application Ser. No. 09/502,032, filed Feb. 10, 2000, now U.S. Pat. No. 6,515,273 entitled "A System for Indicating the Expiration of the Useful Operating Life of a Pulse Oximetry Sensor," which is a continuation-in-part of U.S. patent application Ser. No. 09/420,544, filed Oct. 19, 1999, Now U.S. Pat No. 6,580,086 entitled "Shielded Optical Probe and Method," which claimed a priority benefit to U.S. Provisional Patent Application Ser. No. 60/150,922, filed Aug. 26, 1999, by the same title. The present application incorporates the foregoing disclosures herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention in general relates to sensors for measuring oxygen content in the blood, and, in particular, relates to an apparatus and method for monitoring the life of a pulse oximetry sensor.

2. Background

Early detection of low blood oxygen is critical in a wide variety of medical applications. For example, when a patient receives an insufficient supply of oxygen in critical care and surgical applications, brain damage and death can result in just a matter of minutes. Because of this danger, the medical industry developed pulse oximetry, a noninvasive procedure for measuring the oxygen saturation of the blood. A pulse oximeter interprets signals from a sensor attached to a patient in order to determine that patient's blood oxygen saturation.

A conventional pulse oximetry sensor has a red emitter, an infrared emitter, and a photodiode detector. The sensor is typically attached to a patient's finger, earlobe, or foot. For a finger, the sensor is configured so that the emitters project light from one side of the finger, through the outer tissue of the finger, and into the blood vessels and capillaries contained inside. The photodiode is positioned at the opposite side of the finger to detect the emitted light as it emerges from the outer tissues of the finger. The photodiode generates a signal based on the emitted light and relays that signal to the pulse oximeter. The pulse oximeter determines blood oxygen saturation by computing the differential absorption by the arterial blood of the two wavelengths (red and infrared) emitted by the sensor.

The foregoing conventional sensor is typically detachable from the oximeter to allow for periodic replacement. Periodic replacement is advantageous for a wide variety of reasons. For example, the sensor can become soiled, thereby possibly inhibiting sensor sensitivity or causing cross-patient contamination. Furthermore, the electronic circuitry in the sensor can become damaged, thereby causing sensor failure or inaccurate results. Moreover, the securing mechanism for the sensor, such as an adhesive substrate, can begin to fail, thereby improperly positioning the sensor in proximity to a measurement site and providing inaccurate data. Accordingly, periodic replacement of the sensor is an important aspect of maintaining a sterile, highly sensitive, accurate pulse oximetry system.

However, a conventional pulse oximetry sensor is wholly reliant on an operator for timely replacement of soiled,

damaged, or otherwise overused sensors. This approach is problematic not only from the standpoint of operator mistake or negligence, but also from the perspective of deliberate misuse for cost saving or other purposes.

Based on the foregoing, significant drawbacks exist in the reliance on the operator for the periodic replacement of conventional pulse oximetry sensors. Accordingly, a need exists for a pulse oximetry sensor having the ability to monitor its own usable life.

SUMMARY OF THE INVENTION

Accordingly, one aspect of the present invention is to provide an inexpensive, highly accurate sensor life monitoring system for monitoring the useful and safe life of a pulse oximetry sensor. According to one embodiment, the sensor life monitoring system includes a timer and a sensor life indicator. According to another embodiment, the timer includes a divide-by-n counter and a non-volatile RAM, while the sensor life indicator includes at least one LED or incandescent bulb.

Therefore, one aspect of the present invention is a pulse oximetry sensor comprising a drive connection carrying a drive signal, wherein the drive signal has pulses. The pulse oximetry sensor further comprises a timer connected to the drive connection and configured to generate a timer output signal after a predetermined number of pulses are generated in the drive signal; and a sensor life indicator connected to the timer output signal and configured to provide an indication when the timer output signal is generated. The pulse oximetry sensor further comprises an LED network connected to the drive connection and configured to project light through a measurement site when pulsed by the drive signal; and a photodetector configured to detect the projected light and output a signal representative of constituents or characteristics of the measurement site.

Another aspect of the present invention is a sensor life monitoring system comprising a timer connected to a sensor drive signal; and a sensor life indicator connected to the timer such that the sensor life indicator is configured to indicate the expiration of the useful or safe life of a pulse oximetry sensor.

Another aspect of the present invention is a pulse oximetry system that comprises a pulse oximeter; a sensor connected to the pulse oximeter; and a sensor life monitor connected to the sensor and configured to monitor the useful and safe life of the sensor.

Another aspect of the present invention is a method of manufacturing a sensor. The method comprises connecting a timer to one of a sensor input and a sensor output; and connecting an indicator to the timer such that when the timer expires, the indicator is activated.

Another aspect of the present invention is a method for monitoring the life of an oximetry sensor. The method comprises monitoring a parameter responsive to repeated use of a sensor. When the parameter indicates that the sensor has expired, the method generates an expiration indication.

Another aspect of the present invention is an oximetry sensor life indicator that comprises a non-volatile counter connected to receive a drive signal having a plurality of transitions where the counter changes a count value in response to the transitions. The oximetry sensor life indicator further includes a sensible indicia connected to the counter, where the sensible indicia has a first state, and a second state and the sensible indicia changes from the first state to the second state to indicate the end of life of the oximetry sensor when the count value in the counter reaches a predetermined value.

3

Another aspect of the present invention is an oximetry system comprising an oximeter; a sensor attached to the oximeter through a cable; a timer connected to at least one of a sensor drive signal and a sensor return signal; and a sensor life indicator connected to the timer.

Another aspect of the present invention is an oximetry system comprising a sensor having a timer, wherein the timer produces a sensor expiration signal. An oximeter is connected to the sensor and is configured to receive the sensor expiration signal from the timer.

Another aspect of the present invention is an oximetry system comprising a sensor having a reset indicator. An oximeter is connected to the sensor and is configured to monitor whether the reset indicator has been set.

Another aspect of the present invention is a pulse oximetry system comprising a pulse oximeter and a sensor connected to the pulse oximeter. The sensor is adapted to measure a physiological parameter. The pulse oximetry system also comprises a memory device connected to the sensor and adapted to measure the useful life of the sensor.

Another aspect of the present invention is a pulse oximetry system comprising a sensor having an emitter, a detector, and a memory device storing a characteristic of the sensor. The pulse oximetry system also comprises a pulse oximeter connected to the sensor and adapted to read the characteristic of the sensor and the output of the detector. The pulse oximetry system also comprises a database connected to the pulse oximeter and adapted to store the characteristic along with a longevity measurement corresponding to the sensor.

For the purposes of summarizing the invention, certain aspects, advantages, and novel features of the invention have been described. Of course, it is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or a group of advantages, as taught herein, without necessarily achieving other advantages as may be taught or suggested herein.

Other aspects and advantages of the invention will be apparent from the detailed description below and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is described in more detail below in connection with the attached drawings, which are meant to illustrate and not limit the invention, and in which:

FIG. 1 illustrates a block diagram of a typical oximetry system;

FIG. 2 illustrates a block diagram of a sensor life monitoring system according to an embodiment of the invention;

FIG. 3 illustrates a block diagram of the sensor life monitoring system of FIG. 2, according to another embodiment of the invention;

FIG. 4 illustrates a block diagram of an oximetry system having a sensor life monitoring system, according to yet another embodiment of the invention;

FIG. 5 illustrates a block diagram of an oximetry system having a sensor life monitoring system, according to yet another embodiment of the invention;

FIG. 6 illustrates a flow diagram of the operation of a microprocessor of the oximetry system of FIG. 5;

FIG. 7 illustrates a block diagram of an oximetry system having a sensor life monitoring system, according to yet another embodiment of the invention; and

4

FIG. 8 illustrates a block diagram of an oximetry system having a sensor life monitoring system, according to yet another embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The inventions are described in detail below with reference to the figures, wherein like elements are referenced with like numerals throughout.

FIG. 1 illustrates a block diagram of a typical oximetry system **100** used to determine arterial oxygen saturation. The oximetry system **100** includes an oximeter **105** and a sensor **110** connected to the oximeter **105** via a patient cable **115**. The oximeter **105** includes a microprocessor (μ p) **120**, a speaker **125** and a display **130**. The sensor **110** includes a drive connection **135** connected to at least one LED network **140**, a photo detector **145** connected to a return signal connection **150**, and a cable connector **155** housing one end of each of the drive connection **135** and the return signal connection **150**. As mentioned, the sensor **110** attaches to the oximeter **105** via the patient cable **115**. The patient cable **115** includes a sensor connector **160** for electrically mating with the cable connector **155** of the sensor **110**.

As previously mentioned, the typical oximetry system **100** produces a drive signal and transmits the drive signal through the patient cable **115** and the drive connection **135** to the LED network **140** such that light energy is transmitted from the LED network **140** through tissue. The photo detector **145** senses the light energy, which has now been attenuated by the blood in tissue, and sends a representative signal of the light energy back to the oximeter **105** through the return signal connection **150** and the patient cable **115**. The oximeter **105** analyzes the representative signal from the photo detector **145** to determine constituency and characteristics of the blood in the tissue.

The sensor **110** typically includes the foregoing electronic circuitry and an attachment mechanism formed to secure the electronic circuitry to a measurement site. The sensor **110** may be disposable, wherein the attachment mechanism is likely formed from an adhesive structure. Moreover, the sensor **110** may be reusable, wherein the attachment mechanism is likely formed from a clip-on structure. Also, the sensor **110** may be a combination of the disposable and reusable type sensors, wherein a disposable attachment mechanism removably attaches the electronic circuitry such that the electronic circuitry is reusable. Furthermore, the sensor **110** may include an information element electrically connected to the LED network **140**. Such an information element advantageously provides quality control, security, and identification functions.

An example of the combination sensor having an information element distributed in the disposable attachment mechanism is described in U.S. patent application Ser. No. 09/456,666, filed on Dec. 9, 1999, titled, "Responsible Pulse Oximetry Sensor," assigned to the assignee of the current application, and incorporated by reference herein.

FIG. 2 illustrates a block diagram of a pulse oximetry sensor **200**, according to an embodiment of the invention. As shown in FIG. 2, the sensor **200** includes a wholly incorporated sensor life monitoring system **203**. The sensor life monitoring system **203** includes a timer **205** and a sensor life indicator (SLI) **210**. According to this embodiment, the timer **205** is electrically connected to the drive connection **135** such that the timer **205** also receives the drive signal from the oximeter **105**. The timer **205** also connects to the sensor life indicator **210**.

As the oximeter **105** drives the LED network **140**, the timer **205** monitors the number of drive pulses produced and keeps a running count. After the oximeter **105** produces a predetermined number of drive signals, the timer **205** provides a signal to the sensor life indicator **210**, such that the sensor life indicator **210** produces an indication that the sensor **200** has expired and should be replaced.

FIG. **3** illustrates a block diagram of an example of the sensor life monitoring system **203** of FIG. **2**, according to one embodiment of the invention. As shown in FIG. **3**, the timer **205** advantageously comprises a non-volatile counter. One embodiment of the non-volatile counter advantageously comprises a counter **300** having an output that connects to an input of a logic gate **302**. An output of the logic gate **302** connects to an adder **304**. As used herein, an "adder" can be an arithmetic unit, which may also be implemented as a subtractor or the like. The adder **304** connects to a non-volatile (NV) RAM **305** (A non-volatile RAM does not lose data when the power is turned off or otherwise terminated). An output of the NVRAM **305** reconnects as feedback to the adder **304**. Also, an output of the most significant bit (MSB) of the NVRAM **305** connects to both an inverter **307** and the sensor life indicator **210**. The inverter **307** connects as feedback to another input of the logic gate **302**. Moreover, the output of the logic gate **302** activates or clocks the NVRAM **305**.

According to one embodiment, the counter **300** comprises a divide-by-n counter, producing an incremental output count only after n input pulses, or transitions, of the drive signal. Using a divide-by-n counter advantageously reduces the capacity requirements of the NVRAM **305**. Furthermore, according to one embodiment, the logic gate **302** is an AND gate, the adder **304** is a plus-one adder. Thus, each time the adder **304** receives an input, it adds one to the current count stored in the NVRAM **305**. According to one embodiment, the NVRAM **305** is a seventeen-bit non-volatile memory that clocks, for example, on the trailing edge of the output of the logic gate **302**.

According to an embodiment of the invention, the sensor life indicator **210** comprises a sensible indicia, such as visible light. For example, the sensible indicia may advantageously be an LED **310**, or the like. Alternatively, the sensible indicia may be audible, vibrational, a power down of the sensor **200** or the oximeter **105**, or the like.

The operation of the foregoing timer **205** and sensor life indicator **210** will be disclosed with reference to two differing time frames. The first time frame refers to when a new sensor **200** is initially attached to the oximeter **105** and provided with a drive signal. The second time frame refers to when the sensor **200** has previously been used, and a new drive signal is applied.

First Use of the Sensor **200**

According to the foregoing embodiment, the sensor life monitoring system **203** initially functions as follows. The oximeter **105** outputs a drive signal at, for example, one kHz. The counter **300** comprises a divide-by-1000 counter that advantageously produces, for example, an output only after one thousand cycles of the drive signal, or every one second. Furthermore, assuming the count stored in the NVRAM **305** is initially zero, the output of the MSB of the NVRAM **305** is zero. The inverter **307** inverts the output of the MSB such that the logic gate **302** passes the output of the counter **300** to the adder **304**. Thus, according to this example, the adder **304** receives a pulse every second from the counter **300**. With each pulse, the adder **304** adds one to count stored in the NVRAM **305**. Thus, after one second, the adder **304** places a one in the NVRAM **305**. After another

second, the adder **304** places a two in the NVRAM **305**, and so forth until the NVRAM **305** fills to capacity, or the oximeter **105** ceases producing the drive signal. Both events are further discussed as follows.

Subsequent Use of the Sensor **200**

When the oximeter **105** sends pulses to a previously used sensor **200**, the NVRAM **305** will already have a previous count stored therein. The previous count is loaded into the adder **304** such that as the logic gate **302** outputs the foregoing signal every second, the adder **304** adds one to the previous count. For example, if the previous count were one hour, or 3,600 seconds, the first pulse received by the adder **304** from the counter **300** will store 3,601 in the NVRAM **305**. Thus, much like an automobile odometer, the NVRAM **305** stores a running count, or times, the used life of the sensor **200**.

When the count stored in the NVRAM **305** reaches capacity (in other words, sets the MSB), the output of the MSB switches. Therefore, the output of the inverter **307** switches such that the logic gate **302** blocks any future signals output from the counter **300** from reaching the adder **304**. Moreover, the output of the MSB further activates the LED **310** such that the LED **310** indicates the sensor **200** has expired. This indication by the LED **310** signals the operator to replace the used sensor **200** with a new one. The indication advantageously provides multiple people with the knowledge that the sensor **200** should be changed. For example, doctors, nurses, visitors, and even the patient may perceive the indication that the sensor **200** has expired.

According to the foregoing embodiment where every second that the oximeter **105** sends drive pulses to the sensor **200**, the seventeen-bit NVRAM **305** is incremented, the MSB of the NVRAM **305** will set after 131,072 seconds, or, one day, twelve hours, twenty-four minutes and thirty two-seconds. In other words, according to this embodiment, the useful life of the sensor **200** expires after the sensor **200** has received drive pulses for a combined total of the foregoing time.

A skilled artisan will understand that a wide number of differing logic mechanisms may be employed in the foregoing embodiment. For example, employing different sized counters **300** or NVRAMs **305** will adjust the predetermined expiration time. Moreover, the counter **300** may advantageously divide by more than one thousand, thereby further reducing the capacity requirements of the NVRAM **305**. Also, the timer **205** may advantageously comprise a non-volatile counter that has internal registers that retain their values when the power is turned off. Such non-volatile counters are available, for example, from Dallas Semiconductor Corporation of Dallas, Tex. These non-volatile counters may include, for example, Dallas Semiconductor's DS1602 or DS1603. In the foregoing embodiments employing a non-volatile counter, the adder **304** and the counter **300** may not be needed.

A skilled artisan will also understand that the sensor **200** may advantageously employ a wide variety of differing timers **205** and differing sensor life indicators **210**. Moreover, the choice may advantageously coincide with particular types of the sensor **200**. For example, a purely disposable sensor suggests a less costly solution than that of the reusable sensor because of manufacturing costs and the relatively short life of the disposable sensor. On the other hand, the combination sensor may incorporate a more expensive solution into the reusable portion of the electronic circuitry without dramatic cost changes to the disposable portion.

Moreover, a skilled artisan will recognize that the timer **205** may advantageously comprise a capacitor that is

charged when the sensor **200** is connected to the oximeter **105**. In such case, the capacitor has known discharge characteristics such that the voltage across the capacitor can be used to measure the useful life of the sensor **200**. Also, rather than using the pulses of the drive signal, the timer **205** may employ an oscillator configured to trigger at the beginning of sensor use.

Further, the sensor life indicator **210** may include several LEDs of differing colors, such as green and red, to indicate whether the sensor **200** has expired. The sensor life indicator **210** may comprise an incandescent light, an audio or vibrational alarm, a digital or LCD display, or other sensible indicia. Moreover, the sensor life indicator **210** may include a blocking signal for automatically terminating the functionality of the sensor **200**. For example, a logic gate may be advantageously added to the drive signal such that the logic gate has the drive signal as an input and has the output of the timer **205** as the another. When the output of the timer **205** is a logic level signaling expiration, the logic gate blocks the drive signal from passing, thus rendering the sensor **200** inoperative. The foregoing logic circuit may also be used to block the signal transferred through the return signal connection **150**. On the other hand, the blocking signal may also comprise a fuse that once blown, renders the sensor **200** inoperative.

Accordingly, a skilled artisan may perceive a variety of differing devices to measure the longevity of the sensor **200**. Furthermore, the type of the sensor **200** may provide guidance on which of the wide variety of devices to use.

FIG. 4 illustrates a block diagram of yet another embodiment of an oximetry system **400** including a sensor life monitoring system **405**. According to this embodiment, the sensor life monitoring system **405** employs the timer **205** and a return signal **410** to the oximeter **105**. Similar to the foregoing embodiment, the timer **205** connects to the drive connection **135** and uses the pulses of the drive signal to measure the useful and safe life of the sensor **200**. In contrast to the foregoing embodiment, the timer **205** then outputs an incremental count of pulses to the oximeter **105** via the return signal **410**, the cable connector **155**, the sensor connector **160**, and the patient cable **115**. In this embodiment, the microprocessor **120** of the oximeter **105** receives the incremental count from the timer **205** and compares the incremental count with a predetermined amount. If the count is greater than the predetermined amount, the microprocessor **120** issues an expiration indication of the sensor **200** through the oximeter **105**.

A skilled artisan will recognize that the oximeter **105** may issue the expiration indication through a wide variety of devices including, but not limited to, those described in relation to the sensor life indicator **210** of FIGS. 2-3. Moreover, the oximeter **105** may take advantage of the more costly technology already associated therewith. For example, the oximeter **105** may issue the expiration indication by employing an audio alarm through the speaker **125**, a visual alarm through the display **130**, or a power-down function where the oximeter **105** is inoperable until the sensor **200** is replaced.

FIG. 5 illustrates a block diagram of yet another embodiment of an oximetry system **500** including a sensor life monitoring system **505**. According to this embodiment, the sensor life monitoring system **505** employs a reset indicator **510** and the sensor life indicator **210**, as an integral part of the sensor **200**. The reset indicator **510** and the sensor life indicator **210** connect to the oximeter **105** through the cable connector **155**, the sensor connector **160**, and the patient cable **115**. Also according to this embodiment, the microprocessor **120** includes a timer **515**.

According to this embodiment, the microprocessor **120** measures the useful and safe life of the sensor **200**. For example, the microprocessor **120** may track the pulses in the drive signal created by the microprocessor **120**, or take advantage of a date/time function to measure actual time. Furthermore, the microprocessor **120** employs the reset indicator **510** on the sensor **200** to indicate whether the sensor **200** is newly attached or has previously expired. For example, the reset indicator **510** may comprise a one-bit memory or a fuse technology, wherein the one-bit memory is set, or the fuse is blown, when the sensor **200** first connects to the oximeter **105** through the mating of the cable and sensor connectors, **155** and **160** respectively.

As shown in FIG. 5, the sensor life indicator **210** remains an integral part of the sensor **200** and, therefore, may advantageously take any of the forms discussed above with reference to FIGS. 2 and 3. Preferably, the sensor life indicator **210** comprises the LED **310** of FIG. 3.

FIG. 6 illustrates a flow diagram **600** of the steps taken by the microprocessor **120** of the oximetry system **500** of FIG. 5, according to one embodiment of the invention. As shown in FIG. 6, the process begins when the oximeter **105** is activated to a sensing state by, for example, an operator, in a STEP **603**. The oximeter **105** first checks the reset indicator **510**, in a STEP **605**, to determine whether the sensor **200** has been previously used. If the sensor **200** is new, the microprocessor **120** resets the timer **515**, in a STEP **610**, and sets the reset indicator **510** on the sensor **200**, in a STEP **615**. The microprocessor **120** then proceeds with normal operation, e.g., to output a drive signal to the sensor **200**, in a STEP **620**.

On the other hand, if in the STEP **605**, the reset indicator **510** indicates that the sensor **200** has been previously used, or when the sensor **200** is in normal operation, in the STEP **620**, the microprocessor **120** checks whether the timer **515** indicates the sensor **200** has reached its predetermined longevity, in a STEP **625**. For example, the timer **515** may advantageously compare the number of drive pulses to a predetermined number to conclude whether the sensor **200** has expired.

If the sensor **200** has not expired, the microprocessor **120** again proceeds with normal operation, in the STEP **620**. On the other hand, if the timer **515** indicates that the sensor **200** has expired, the microprocessor **120** activates the sensor life indicator **210**, in a STEP **630**, and then the process terminates, in a STEP **635**.

One having ordinary skill in the art will understand that the microprocessor **120** may employ an interrupt driven mechanism for the timer **515**. For example, during normal operation, the microprocessor **120** may not continually, or periodically, check the timer **515**, as in the STEP **625**. Rather, the microprocessor **120** may continually send drive pulses until the timer **515** generates an interrupt that instructs the microprocessor **120** to activate the sensor life indicator **210**. A skilled artisan will appreciate that there are a wide number of mechanisms for generating microprocessor interrupts.

FIG. 7 illustrates a block diagram of yet another embodiment of an oximetry system **700** including a sensor life monitoring system **705**. According to this embodiment, the oximetry system **700** is similar to that described in reference to FIG. 5. Like FIG. 5, the microprocessor **120** of the oximeter **105** includes the timer **515**, or timer-like functions. Also, the sensor life monitoring system **705** advantageously employs the reset indicator **510** to ensure replacement of new sensors when the sensor **200** expires. Moreover, like FIG. 4, the oximetry system **700** employs the oximeter **105** to provide an expiration indication once the sensor **200** expires.

Thus, according to one embodiment, the microprocessor **120** of the oximeter **105** checks the reset indicator **510** to ensure the sensor **200** has not previously been used. Then, the microprocessor **120** drives the LED network **140** and tracks the timing functions. When the predetermined number of drive pulses is reached, the microprocessor **120** employs various mechanisms on the oximeter **105** to generate the expiration indication. For example, the microprocessor **120** may use the speaker **125** or the display **130**, even power down the oximeter **105**, or the like, to create the expiration indication.

FIG. **8** illustrates a block diagram of yet another embodiment of an oximetry system **800**. According to this embodiment, the oximetry system **800** includes a sensor life monitoring system **805** having a memory device **810**. The memory device **810** is preferably a single wire memory device having a unique identifier, such as memory devices commercially available from companies such as Dallas Semiconductor Corporation. For example, Dallas Semiconductor's DS2401 includes a unique, 64-bit identification number. In this way, the memory device **810** can uniquely identify the sensor **200** from all other sensors.

The oximetry system **800** further includes the microprocessor **120** of the oximeter **105** connected to a memory, such as a database **815**. According to the preferred embodiment, the database **815** is stored locally in the memory of the oximeter **105**. The oximeter **105** reads the unique identifier from the memory device **810** on the sensor **200** and, if necessary, creates a record in the database **815** corresponding to the unique identifier. Then, as the sensor **200** is used, the oximeter **105** accesses the record corresponding to the unique identifier so as to update the information relating to the longevity of the sensor **200**. This information may advantageously include timing information, such as a decremented or incremented chronological count. The information may also, or alternatively, include the number of times the sensor **200** has been used, the number of drive signals the sensor **200** has received, or other similar methods of determining the amount of use for the particular sensor **200** having the particular unique identifier.

According to this embodiment, when the information stored in the database **815** reaches a predetermined threshold for a particular unique identifier, the oximeter **105** advantageously produces the expiration indication in a similar manner to that described in reference to FIG. **4**. For example, the oximeter **105** may issue the expiration indication by employing an audio alarm through the speaker **125**, a visual alarm through the display **130**, or a power-down function that renders the oximeter **105** inoperable. These expiration indications may advantageously continue until the sensor **200** having the unique identifier is replaced with one having a different unique identifier.

Although the database **815** is described as being stored in memory associated with the oximeter **105**, the invention is not meant to be limited thereby. Rather, a skilled artisan would recognize that the database **815** may advantageously be stored in a central location, such a remote server connected through a wide number of known technologies, such as a local or wide area network, the internet, or other communications connection. In this way, a monitoring authority, ranging from a pair of pulse oximeters, to one or a number of hospitals, to a particular sensor manufacturer, and the like, can monitor the useful life of sensors identified through their unique identifier stored in the memory device **810**.

As an alternative to, or in addition to, the foregoing embodiment where the memory device **810** includes a

unique identifier, the memory device **810** may include the ability to store data. Again, such memory devices are commercially available from, for example, Dallas Semiconductor Corporation, and typically allow for read/write access over a single wire. For example, Dallas Semiconductor's DS2502 has the ability to accept new data for non-volatile storage.

According to this embodiment, the oximeter **105** reads data stored in the memory device **810** relating to longevity, and updates that data according to use. For example, the oximeter **105** may read the memory device **810** of sensor **200** and determine that the sensor **200** has been in use for one increment of time, such as one minute. After the sensor **200** has been used for another increment of time, such as another minute as measured by the oximeter **105**, the oximeter may write to the memory device **810** such that the memory device **810** now reflects that the sensor **200** has been used for two minutes. This periodic read and write to the memory device **810** continues until the memory device **810** reflects a longevity measurement greater than a predetermined threshold. At that time, the oximeter **105** may advantageously issue the foregoing expiration indication.

A skilled artisan would recognize that a wide variety of timing schemes may be implemented using the foregoing read/write technique. For example, the oximeter **105** may advantageously decrement from a predetermined threshold stored in the memory device **810**. On the other hand, the memory device may store the number of times the sensor **200** has been used, the number of drive signals the sensor **200** has received, or other similar methods of determining the amount of use for the particular sensor **200**.

Moreover, a skilled artisan would recognize that the foregoing embodiments may advantageously be combined such that the memory device **810** includes both the unique identifier and the ability to store other data. This other data may advantageously include the foregoing read/write timing data, manufacturing data such as sensor type, manufacturing source indication, tolerance levels, operating characteristics, and the like.

Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art. For example, a skilled artisan will recognize the distinction in the foregoing embodiments between those components described as being integral with the sensor **200**, or on-sensor components, and those components described as not being integral with the sensor **200**, or off-sensor components. The on-sensor components may advantageously be housed in the disposable, reusable, or combination sensors. With respect to the combination sensors, the on-sensor components may be advantageously housed in the disposable portion, the reusable portion, or both portions, of the combination sensor.

Further, the off-sensor- components may be housed in any of the longer lasting components associated with the oximeter **105**. For example, the off-sensor components may be advantageously located on the sensor connector **160** or on the patient cable **115** where they are readily seen, heard, or felt by the operator or patient.

Moreover, the foregoing embodiments incorporating the memory device **810** of FIG. **8** may advantageously be combined with those embodiments describing the sensor life indicator **210** housed on the sensor **200**. In such embodiment, the oximeter **105** may advantageously provide the expiration indication to the sensor life indicator **210** when the oximeter **105** determines that the sensor **200** had expired.

11

Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to the appended claims.

What is claimed is:

1. A noninvasive optical probe capable of indicating an amount of use in a determination of whether the noninvasive optical probe has expired from overuse, the noninvasive optical probe comprising:

one or more emitters capable of emitting light;

at least one conductor capable of communicating an emitter drive signal to the one or more emitters;

a memory device electrically connected to the at least one conductor and capable of monitoring an amount of use of the noninvasive optical probe; and

a detector capable of detecting the light after the light has been attenuated by body tissue, wherein attenuated light is indicative of one or more physiological parameters of the body tissue.

2. The noninvasive optical probe of claim 1, further comprising an expiration indicator capable of being activated when the amount exceeds a predetermined amount of use.

3. The noninvasive optical probe of claim 2, wherein the activating comprises activating at least one of an audio and visual alarm.

4. The noninvasive optical probe of claim 1, wherein the amount comprises a value representative of a number of pulses of the emitter drive signal received by the one or more emitters.

5. The noninvasive optical probe of claim 1, wherein the memory device comprises a timer.

6. The noninvasive optical probe of claim 5, wherein the amount comprises an amount of time.

12

7. The noninvasive optical probe of claim 1, wherein the noninvasive optical probe communicates the amount to a processing device.

8. The noninvasive optical probe of claim 7, wherein the processing device further comprises an expiration indicator capable of being activated when the amount exceeds a predetermined amount of use.

9. The noninvasive optical probe of claim 8, wherein the activating comprises activating at least one of an audio and visual alarm.

10. A method of determining an amount of use of an optical probe, the method comprising:

communicating with one or more emission devices of a noninvasive optical probe over at least one conductor to drive the one or more emission devices;

communicating with a timer of the noninvasive optical probe over the at least one conductor used to drive the one or more emission devices;

incrementing the timer during use of the noninvasive optical probe; and

when the timer is proximate to a predetermined amount, activating an indicator configured to illustrate that the use of the noninvasive optical probe is proximate the predetermined amount.

11. The method of claim 10, further comprising:

determining whether the noninvasive optical probe is new; and

when the noninvasive optical probe is new, resetting a timer.

12. The method of claim 11, wherein the determining comprises accessing a memory identifying whether the noninvasive optical probe has been used.

13. The method of claim 11, wherein the determining comprises accessing a memory identifying the noninvasive optical probe.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,861,639 B2
APPLICATION NO. : 10/357531
DATED : March 1, 2005
INVENTOR(S) : Ammar Al-Ali et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In Column 10, Line 54, after "off-sensor" please delete "-".

Signed and Sealed this

Nineteenth Day of June, 2007

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

Director of the United States Patent and Trademark Office