

US006863168B1

(12) **United States Patent**  
**Gerrity et al.**

(10) **Patent No.:** **US 6,863,168 B1**  
(45) **Date of Patent:** **Mar. 8, 2005**

(54) **METHOD AND APPARATUS FOR  
CONDITIONING COINS PRIOR TO  
DISCRIMINATION**

(75) Inventors: **Dan Gerrity**, Bellevue, WA (US);  
**Aaron Finch**, Seattle, WA (US); **Chris  
Ferguson**, Redmond, WA (US); **Scott  
Scherer**, Seattle, WA (US); **Rick  
Riday**, Redmond, WA (US); **Larry D.  
Cannon**, Bothell, WA (US)

(73) Assignee: **Coinstar, Inc.**, Bellevue, WA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/652,953**

(22) Filed: **Aug. 28, 2003**

3,763,871 A	10/1973	Jobst	
3,788,440 A	1/1974	Propice et al.	
3,791,574 A	2/1974	Picquot	
4,083,776 A	4/1978	Shimoiizaka et al.	
4,092,990 A *	6/1978	Bayne .....	453/55
4,360,034 A	11/1982	Davila et al.	
4,376,442 A	3/1983	Gomez et al.	
4,383,540 A	5/1983	DeMeyer et al.	
4,436,103 A	3/1984	Dick	
4,964,495 A	10/1990	Rasmussen	
5,100,367 A	3/1992	Abe	
5,429,551 A	7/1995	Uecker et al.	
5,564,546 A	10/1996	Molbak et al.	
5,620,079 A	4/1997	Molbak	
5,842,916 A	12/1998	Gerrity et al.	
6,021,883 A	2/2000	Casanova et al.	
6,071,187 A	6/2000	Knutsson et al.	
6,093,094 A	7/2000	Uecker et al.	
6,174,230 B1	1/2001	Gerrity et al.	
6,179,703 B1	1/2001	Knutsson et al.	
6,318,536 B1	11/2001	Korman et al.	

**Related U.S. Application Data**

(63) Continuation of application No. 10/304,384, filed on Nov.  
25, 2002, now Pat. No. 6,666,318, which is a continuation  
of application No. 09/704,178, filed on Oct. 31, 2000, now  
Pat. No. 6,484,884, which is a continuation of application  
No. 09/042,784, filed on Mar. 17, 1998, now Pat. No.  
6,174,230, which is a continuation of application No.  
08/807,340, filed on Feb. 28, 1997, now Pat. No. 5,842,916.  
(60) Provisional application No. 60/012,964, filed on Mar. 7,  
1996.

(30) **Foreign Application Priority Data**

Feb. 28, 1997 (WO) ..... PCT/US97/03136

(51) **Int. Cl.**<sup>7</sup> ..... **G07D 3/00**

(52) **U.S. Cl.** ..... **194/347**

(58) **Field of Search** ..... 194/347, 215,  
194/216, 217, 348; 235/2, 4

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,398,955 A	4/1946	O'Toole	
3,048,251 A *	8/1962	Bower .....	194/219
3,121,435 A	2/1964	White	
3,147,839 A	9/1964	White, Jr.	
3,196,887 A *	7/1965	White, Jr. ....	453/8

**FOREIGN PATENT DOCUMENTS**

JP	5-200364	8/1993
WO	WO96/30877	10/1996

\* cited by examiner

*Primary Examiner*—Donald P. Walsh  
*Assistant Examiner*—Mark J. Beauchaine  
(74) *Attorney, Agent, or Firm*—Perkins Coie LLP

(57) **ABSTRACT**

Methods and systems for cleaning coins and issuing a  
redeemable voucher for same. In one embodiment, an appa-  
ratus for issuing a redeemable voucher includes a coin input  
region configured to receive a plurality of coins, and a user  
interface configured to receive a request for a redeemable  
voucher. The apparatus can further include a debris separa-  
tion device having a first opening configured to receive the  
plurality of coins from the coin input region, and at least a  
first wall forming an interior surface and an exterior surface.  
The first wall of the debris separation device includes at least  
one second opening smaller than the first opening and sized  
to prevent passage therethrough of the smallest coin of the  
plurality of coins. A driver can be configured to move the  
debris separation device and agitate the plurality of coins.

**52 Claims, 16 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 6











FIG. 9




FIG. 10




FIG. 11




FIG. 12







FIG. 13







FIG. 15










FIG. 17





FIG. 18






FIG. 19A




FIG. 19E

FIG. 19D




FIG. 19B




FIG. 20




FIG. 19C





FIG. 21








FIG. 22.

## METHOD AND APPARATUS FOR CONDITIONING COINS PRIOR TO DISCRIMINATION

The present application is a continuation of application 5  
Ser. No. 10/304,384 filed Nov. 25, 2002 now U.S. Pat. No.  
6,666,318, which is a continuation of to application Ser. No.  
09/704,178 filed Oct. 31, 2000, now U.S. Pat. No. 6,484,  
884, issued Nov. 26, 2002, which is a continuation of Ser.  
No. 09/042,784, filed Mar. 17, 1998, now U.S. Pat. No. 10  
6,174,230, issued Jan. 16, 2001, which is a continuation of  
Ser. No. 08/807,340, filed Feb. 28, 1997, now U.S. Pat. No.  
5,842,916, issued Dec. 1, 1998, and claims priority in U.S.  
provisional application Ser. No. 60/012,964, filed Mar. 7,  
1996 for METHOD AND APPARATUS FOR CONDI- 15  
TIONING COINS PRIOR TO TRANSPORT, SORTING  
AND COUNTING. The present application also claims  
Priority in PCT Application US97/03136, filed Feb. 28,  
1997. The entire disclosures of the prior applications are  
considered to be part of the disclosure of the present 20  
application and are hereby incorporated by reference.

This invention relates to a device and method for con- 25  
ditioning coins and in particular for removing debris,  
contamination, corrosion and unwanted materials from coins  
prior to transport to devices for automatically counting  
and/or sorting the coins.

### BACKGROUND INFORMATION

Coin counting and sorting equipment is often adversely 30  
affected by the presence of foreign matter. Mechanical and  
electronic sorting systems and methods can fail, be  
damaged, caused to misread and/or become jammed.

Mechanical devices such as coin transport mechanisms, 35  
coin hoppers and the like may be caused to jam or otherwise  
malfunction by foreign matter. Sensors may be prevented  
from accurately identifying a coin because of non-coin  
matter accompanying the coins. Sensors may become 40  
blocked or rendered ineffective because of non-coin matter  
collecting and or being deposited onto sensor parts. When  
the sensors fail the coin counting process has failed and  
coins are often undesirably rejected or are accepted as the  
incorrect denomination. The amount of non-coin matter 45  
varies and is unpredictable. In many situations, the reliabil-  
ity and accuracy of coin sorting, identification and/or count-  
ing processes is very important and thus the process of  
removing non-coin matter before the coins are transported to  
sorting, identification and/or counting sensors is important.  
The presence of non-coin matter is believed to be especially  
troublesome in the context of self-service, stand-alone, 50  
unmonitored and/or unattended devices, e.g. devices for  
counting/sorting coins by the general public or other non-  
trained persons. Accordingly, it would be useful to provide  
self-service coin processing machinery which can process  
coins which are accompanied by non-coin matter.

The removal of one type of undesirable non-coin matter 55  
does not often eliminate other kinds because the material is  
so varied. Metal objects may be identified by properties such  
as density, shape magnetic characteristics, etc. Typically,  
removing dense matter such as rocks is entirely different 60  
than removing metal or paper objects. Coins may have been  
stored with materials that have caused corrosion or have  
become coated with oils, glue and other liquids that collect  
dirt and other debris. These coins contaminate others as they  
come into physical contact and may cause adhesion, clump- 65  
ing or grouping of coins. A magnetic separator would not  
eliminate all this various non-coin matter.

## SUMMARY OF THE INVENTION

The present invention provides for separating non-coin 5  
objects from coins in a coin-sorting, discriminating or count-  
ing device, preferably prior to coins reaching certain coin  
transport devices, such as transport devices for transporting  
coins toward a hopper or sensor, preferably prior to coins  
reaching a coin hopper which provides coins to sensors and  
preferably prior to the coins reaching the counter/sorting  
sensors. In one embodiment the separation device is a  
generally tubular or concave surface, having one or more  
openings through which non-coin objects travel, and which  
cause coins introduced thereto to undergo relative move- 10  
ment to assist in separation of non-coin objects. In one  
embodiment, the relative movement preferably involves  
lifting some coins with respect to others and may be  
achieved by pivoting or rotating the tubular or concave  
surface, e.g., about an axis. Agitation may be further  
enhanced by projections formed in or attached to the surface,  
such as vanes, fins, blades, spines, dimples, ridges, and the  
like. Movement of coins through or across the tubular or 15  
concave surface may be effected or enhanced by various  
mechanisms. Although gravity feed may be used, in one  
embodiment blades such as angled, spiral or helical blades  
assist in moving the coins e.g. in a screw conveyor fashion.

Except for coin entrance and exit ports, diameters, sizes or 20  
shapes of the openings are configured to prevent passage  
therethrough of the smallest coin intended to be counted by  
the counting device. In one embodiment, a drive mechanism  
rotates the cylinder about its longitudinal axis to agitate the  
coins therein by lifting coins and, preferably, moving the  
coins through the cylinder by a screw mechanism.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a coin-counting device of 35  
a type which may be configured to incorporate features of  
the present invention,

FIG. 2 is a rear perspective view of a receiving tray and 40  
rib slide of a type which may be provided in the apparatus  
of FIG. 1;

FIG. 3 is a schematic side view of a feed tray and tumbler 45  
device according to an embodiment of the present invention,

FIG. 4 is a schematic depiction of the position of a helical 50  
blade in an embodiment of the present invention;

FIG. 5 is a partial side view of a tumbler device according 55  
to an embodiment of the present invention,

FIG. 6 is an end view of a tumbler device according to an 60  
embodiment of the present invention;

FIG. 7 is a partial perspective view, partially exploded, of 65  
a tumbler device according to an embodiment of the present  
invention,

FIG. 8 is a partial perspective view, partially exploded, of  
a tumbler device according to an embodiment of the present  
invention,

FIG. 9 is a rear perspective view of a modular feed 65  
tray/tumbler device according to an embodiment of the  
present invention, which may be incorporated into the  
apparatus of FIG. 1;

FIG. 10 is a side view of the apparatus of FIG. 9;

FIG. 11 is an end perspective view of the apparatus of 70  
FIG. 9,

FIG. 12 is an end view of a tumbler cylinder, according to  
an embodiment of the present invention;

FIG. 13 is a front perspective view, with exploded cover 75  
plate, of an apparatus according to an embodiment of the  
present invention;



FIG. 14 is a front perspective view, partially exploded, of the apparatus of FIG. 13;

FIG. 15 is a rear perspective view, partially exploded, of the apparatus of FIG. 13;

FIG. 16 is a perspective view, partially exploded, of a trommel assembly, according to an embodiment of the present invention;

FIG. 17 is a perspective view of a first end cap which may be used in connection with an embodiment of the present invention;

FIG. 18 is a perspective view of a trommel body, according to an embodiment of the present invention;

FIG. 19A–D are right side elevational, top plan, left side elevational and end views of a trommel body in open configuration, according to an embodiment of the present invention;

FIG. 19E is a side view of a vane which may be used in connection with an embodiment of the present invention;

FIG. 20 is a perspective view of a long object trap of a type which may be used in connection with an embodiment of the present invention; and

FIG. 21 is a cross sectional view taken along line 21—21 of the device of FIG. 20.

FIG. 22 is an illustration of an embodiment of the coin exchange apparatus in a likely environment.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 depicts a coin-counting device which may incorporate features of the present invention. FIG. 1 depicts a device in perspective with various doors opened, and a bag trolley 1610a partially withdrawn. In the embodiment of FIG. 1 a coin tray 1402 is mounted pivotally about axis 1414 (FIG. 2), so that a user, after inserting coins in the tray 1402 may lift the tray, using handle 1404, to move coins out of the tray area 1424, over the ridge or peak 1414, and onto a slope 1429, for movement past a gate 1432, and onto a ribbed chute 1406. Coins are moved into a hopper 1604 for transfer to a counter or sorter 1212, where sorted or counted coins are diverted to bins or, in the embodiment of FIG. 1, bags 1608 held in the trolley 1610a, 1610b. Information processing and/or communication devices and/or printers or dispensers 1628, 1874, which may include, e.g., a computer and/or printer may be provided for outputting information about the sorted coins or counted coins, as described, for example, in PCT application PCT/US95/05356 filed May 1, 1995, and/or U.S. application Ser. No. 08/255,539 filed Jun. 6, 1994, both of which are incorporated herein by reference.

Although the invention is described herein in the context of a device for discriminating or handling coins, the device can generally be applied to separating small, typically unwanted matter or material from larger items. For purposes of the following discussion, the smaller separated items or material (which can include e.g., without limitation, dust, sand, lint, paper, hair, liquids, and myriad other items) will be referred to from time to time herein generically as “dirt” with the understanding that many types of small items or materials, some of them valuable items or materials, can be separated using the present invention.

While the device of FIG. 2 has proved to be useful and can assist, to at least some degree, in removing non-coin matter from a batch or plurality of coins deposited in the tray 1402, e.g., through perforations therein and/or traveling over the chute 1406 (e.g., by perforations therein). It is believed additional improvements in preparing coins for counting/

sorting can be achieved by incorporating a device which lifts or otherwise moves coins, relative to one another, to assist in separating non-coin matter.

In general, FIGS. 3 through 12 and FIGS. 13 through 21 illustrate different embodiments of the present invention, with the understanding that the illustrated embodiments are not necessarily either mutually exclusive (since features or aspects of one embodiment might be incorporated or substituted into another embodiment), nor incompatible (in the sense that some features or aspects of the invention may be common to more than one embodiment).

In the embodiment depicted in FIG. 13, a device is illustrated which may be generally considered in four sections: an input tray section 1302, a trommel feed section 1304, a trommel section 1306, and trommel output section 1308. The illustrated input tray section 1302 is substantially similar to that described in U.S. Pat. Ser. No. 08/255,539 (now U.S. Pat. No. 5,564,546) and/or PCT/US95/05356, and as described briefly above. The trommel feed region 1304 contains, in the illustrated embodiment, a first chute 1310, and a second chute 1312 for conveying coins and other materials to an input opening of the trommel (described below). The trommel feed region 1304 may contain devices for performing additional functions such as stops or traps, e.g., for dealing with various types of elongate objects, a gate for controlling flow of coins and other objects, lights or other signaling devices, e.g., for prompting input of coins or cessation thereof, and/or drive devices or transmissions for rotating or otherwise moving the trommel as described below. The trommel region 1306 contains a perforated-wall trommel 1314 rotatably mounted via end caps 1316, 1318, which preferably contain bearing surfaces. The trommel output region 1308 provides an output chute for directing the (at least partially) cleaned coins exiting the trommel in a desired direction 1320, e.g., towards a hopper 1604 or similar device.

As best seen in FIG. 15, the first chute 1310 may be provided with first and second pins 1322a, 1322b. The pins 1322a, 1322b are provided to block passage of elongate flexible items such as lottery tickets, cardboard, paper and the like. The spacing between the pins 1322a, 1322b or between the pins and the sides of the chute 1310, determines the size of the largest item which may be allowed to pass. In one embodiment, the pins are positioned to allow a coin with a diameter of about 34 mm to pass, but to block items larger than about 34 mm. In one embodiment, the tray 1310 is stainless steel and the pins 1322a, 1322b are steel pins welded to the chute 1310. Although two pins are depicted, more or fewer pins could be provided, it being understood, however, that pins tend to slow down coin feed rates somewhat. In the depicted embodiment, the pins 1322a, 1322b are about two inches (about 5 cm) apart, disposed symmetrically of the center line of the first chute 1310. In the depicted embodiment, the pins are about 0.5 inch (about 12 mm) high.

A controllable gate 1324 is mounted transverse to the first chute 1310 to permit rotation from the closed configuration depicted in FIG. 15, blocking passage of coins, to an open configuration permitting passage of coins or other objects past the gate. Preferably the gate 1324 is formed of rubber, e.g., to avoid pinching of fingers. Rotation of the gate 1324 is controlled by a solenoid 1326. The solenoid 1326 is activated in response to a signal from a control device such as a computer or other information processing device 1628, 1874 (FIG. 1). The gate may be controlled to open or close for a number of purposes, such as in response to sensing of a jam, sensing of load in the trommel or hopper, and the like.



In the depicted embodiment, signal devices such as LED or other lights **1328a**, **1328b**, can provide a user with an indication of whether the gate **1324** is open or closed (or otherwise to prompt the user to feed or discontinue feeding coins or other objects). Although instructions to feed or discontinue may be provided on the computer screen (FIG. **1**), indicator lights **1328** are believed useful since users often are watching the throat of the chute **1310**, rather than the computer screen, during the feeding of coins or other objects.

Downstream of the first chute **1310** and gate **1324** is a second chute assembly **1312**. Preferably, the second chute **1312** provides a funneling effect by having a greater width **1330** at its upstream edge than its downstream edge. Preferably, the coins cascade or “waterfall” when passing from the first chute **1310** to the second chute **1312**, e.g. to increase momentum and tumbling of the coins. In one embodiment the width at the upstream edge is about 5.2 inches (about 13 cm), and the width at the downstream edge is about 2.5 inches (about 6 cm). Preferably, the depth of the chute increases in the directional flow, such as providing a depth of about one inch (about 2.5 cm) at the upstream edge, and a depth of about 1.5 inches (about 3.8 cm) at the downstream edge.

Preferably, the chute **1312** is configured to facilitate coin travel, e.g., by reducing or eliminating the effects of friction, surface tension, and the like. Preferably, the chute **1312** upper surface has no flat region large enough for a coin to contact the surface over one of the faces of the coin, i.e., preferably the coin which touches the chute **1312** preferably makes contact on, at most, two points. Preferably, the surface of the chute **1312** is constructed such that it has a finite radius of curvature along any plane normal to its longitudinal axis **1332**, and preferably with such radii of curvature increasing in the direction of coin flow.

Preferably the chute **1312** has an upper surface which is substantially smooth and free from protrusions, ridges, throughholes or other holes, and the like. In one embodiment the chute **1312** is formed from injected molded plastic such as an acetal resin or plastic, a polyamide polymer, such as a nylon, Delrin®, available from E. I. DuPont de Nemours & Co., and the like. Other materials that can be used for the chute include metals, ceramics, fiberglass, reinforced materials, epoxies, ceramic-coated or -reinforced materials and the like.

As best seen in FIG. **14**, the trough assembly **1312** terminates in a collar **1333** defining a mouth **1334**, which is configured to feed coins from the chute **1312** into a first opening **1336** of the trommel assembly **1338**. The mouth **1334** is formed with an upper lip **1340**. In the depicted embodiment the first opening **1336** of the trommel assembly **1338** is defined by a first end cap **1316** which is coupled to a trommel body **1314**. The first end cap **1316** has a smooth cylindrical bearing surface **1342** configured to mate with a bearing surface **1344** of the chute collar, supporting the rotation of the trommel assembly **1338** about a rotation axis **1346** in a manner described more fully below. An exterior surface of the first end cap **1316** is geared **1348** to mesh with a drive gear **1350** powered by a drive motor **1352**. The drive gear **1350** is preferably spaced from the stationary bearing **1344** sufficiently to permit manual engagement of the end cap gear **1348** with the drive gear **1350** and simultaneous mating of the first end cap bearing **1342** with the stationary bearing **1340** by merely grasping the trommel assembly **1338**, aligning it with the collar **1333** (preferably facilitated by a bevel), rotating the trommel assembly **1338** about its longitudinal axis as needed to mesh the gears **1348**, **1350**,

and pushing towards the chute collar **1333**. Similarly, the trommel assembly **1338** may be manually disengaged from the drive gear **1350** and bearing **1344** by pulling in a direction away from the chute collar **1333**. Preferably, as best seen in FIGS. **16** and **17**, the end cap **1316** includes resilient tabs **1712a**, **1712b**, **1712c**, **1712d** for engaging slots **1812a**, **1812b**, **1812c**, **1812d**, respectively, and tabs **1714a**, **1714b**, **1714c**, **1714d** for capturing corners of the trommel **1314**.

A similar system of tabs **1612a**, **1612b**, **1612c**, **1612d**, **1614a**, **1614b**, **1614c**, **1614d** engage and capture slots **1814a**, **1814b**, **1814c**, **1814d**, and corners of the downstream end of the trommel **1314**. Preferably, the tab and slot system **1712a**, **1712b**, **1712c**, **1712d**, **1812a**, **1812b**, **1812c**, **1812d**, or the trommel **1314** and first endcap **1316** are different from the tabs **1612a**, **1612b**, **1612c**, **1612d**, **1814a**, **1814b**, **1814c**, **1814d** of the second end cap **1318** in such a manner that the end caps **1316**, **1318** are coupled to the first and second ends **1616a**, **1616b** of the trommel **1314**, respectively, and not the other way around. In the depicted embodiment, the downstream tabs and slots have dual protrusions and openings corresponding to the single protrusions and openings of the upstream tabs and slots. Preferably, the resiliency of the tabs **1712A**, -B, -C, -D, **1612A** -B, -C, -D is such that the end caps **1316**, **1318** remain securely coupled to the trommel **1314** during normal use, but may be manually removed without the use of special tools, preferably without the use of any tools, e.g., for cleaning, as described below. Preferably, the end caps **1316**, **1318** are formed of a plastic material such as an acetal plastic, nylon, Delrin® and the like. Preferably, when both the end caps **1316**, **1318** and the bearing surfaces **1344**, **1360** are formed of plastic, different plastics are used for mating bearing surfaces, such as by forming the end caps **1316**, **1318** of Delrin® and the bearing surfaces **1344**, **1360** of a nylon. This is believed to reduce friction and facilitate rotation of the trommel.

As best seen in FIG. **18**, the trommel **1314** is shaped to define four rectangular walls **1816a**, **1816b**, **1816c**, **1816d** to define a substantially square cross section. In the view of FIG. **18**, interior vanes have been removed, for clarity. The trommel **1314** provides at least one hole for permitting passage or exit of dirt from the trommel and, preferably, as depicted, includes a plurality of such holes **1818**. The holes **1818** are sufficiently small to prevent passage of the smallest coins (or other object to be discriminated). In one embodiment, when the device is used in connection with U.S. coins, the holes **1818** have a diameter of about 0.61 inches (about 1.5 mm) to prevent passage of U.S. dimes. In the depicted embodiment, the holes have an inter-row and inter-column spacing **1916a**, **1916b** of about 0.7 inches (about 18 mm). The number, density and distribution of holes **1818** can be configured in a number of ways, other than that depicted. Many factors affect the choice of the number, size, density and distribution of holes. For example, the configuration of the holes affects the overall strength and stability of the trommel **1314** and thus the configuration of the holes may be modified to accommodate the characteristics of different materials used for forming the trommel **1314**. The configuration depicted in FIG. **18** is generally believed to provide a relatively large, total hole area (to facilitate removal of dirt) while maintaining the desired structural integrity and sturdiness of the trommel **1314**. The depicted distribution of holes in rows and columns is believed to contribute to stability, although other configurations are also possible, such as hexagonally-centered holes, randomly positioned holes, and the like. Although in the configuration of FIG. **18** all the holes are of the same



size, it is possible to provide holes in various sizes (smaller than the largest hole which prevents passage of the smallest coin to be treated). Although it is preferred to distribute holes **1818** over substantially the entire inner surface of the trommel **1314**, it would be possible, if desired, to position holes such that some areas of the trommel are substantially free from holes.

In the depicted embodiment dimples **1820** are formed protruding slightly into the interior region of the trommel **1314**. The dimples **1820** are believed to facilitate throughput by avoiding adhesion (such as surface tension—induced adhesion) and/or friction between coins and the interior surface of the trommel. The dimples are believed to reduce the likelihood of adhering a customer's coins to the trommel wall, resulting in loss of credit to the customer. It is believed the dimples prevent or reduce surface-to-surface contact of coins with an interior surface of the trommel over a substantial region of the coin face surface and, accordingly, in the depicted embodiment, dimples **1820** are positioned in any location of the interior surface where a flat region of substantial area would otherwise occur (such as regions between holes). Other shapes, sizes, locations and distributions of protrusions, ridges, fingers, and the like may also be useful to facilitate throughput.

A configuration of a trommel according to one embodiment of the invention is illustrated in FIGS. **19A** through **19D**. In the depicted embodiment, the trommel is formed from two halves **1902a**, **1902b**, rotationally coupled, e.g. by a hinge, such as a piano hinge **1904** or other rotational device such as clips, screws, interconnecting tabs and slots, and the like. The hinge **1904** permits the two halves **1902a**, **1902b** to be reconfigured in a “clam shell” fashion between the closed operating configuration depicted in FIG. **18**, and an open configuration (e.g., for maintenance) depicted in FIGS. **19A** through **19D**. The edges **1906a**, **1906b** diagonally opposed to the hinge **1904** are fitted with latching devices such as tabs **1908a**, **1908b**, **1908c**, **1908d**, which resiliently latch, in an interference fashion, with corresponding regions **1910a**, **1910b**, **1910c**, **1910d** of opposing edges. The end caps **1316**, **1318** further assist in maintaining the trommel in the closed configuration during operation.

The dimensions of the trommel may be selected depending upon the desired capacity and throughput, as well as the structural requirements for the trommel. In the depicted embodiment, the trommel has a length **1912** of about 10.6 inches (about 27 cm), with each wall having an effective width **1914** of about 2.9 inches (about 7.5 cm).

In general, it is preferred to provide a trommel which causes or at least urges coins, during rotation of the trommel, to freely fall through at least a portion of the interior of the trommel (as opposed to, for example, merely rolling or tumbling in a mass adjacent the lowest surface of the trommel). Thus, preferably the trommel assists in lifting coins, as it rotates, and dropping the coins from an elevated height through at least a portion of the interior of the trommel. Without wishing to be bound by any theory, a number of features of the trommel are believed to contribute to the desired coin lifting/free-fall. It has been found, for example, that a trommel with a circular cross-section tends to result in coins remaining adjacent the lower surface (albeit while tumbling), without substantial lifting or free-fall. It is believed that providing a trommel cross-section which defines flat surfaces and/or corners (i.e., surfaces meeting at an angle) assists in coin lifting/free-fall. In the depicted embodiment, the trommel has a substantially square cross-section, thus defining four substantially flat surfaces, and four corners. It is believed that other cross-

sections may provide at least some desirable lifting/free-fall, including cross-section which have corners but no flat surfaces, and/or cross-section with more or fewer than four flat surfaces. Cross-sections which are non-regular (such as isosceles triangular cross-sections) or which have local concavities, such as star-shaped cross-sections, may be useful in some contexts. Other potential cross sections include triangles, pentagons, hexagons, octagons, semicircles, rectangles, inflated or pillowed cross-sectional shapes (such as defined by three or more intersecting circular or elliptical arcs), cross-sections with surfaces defined by various non-linear shapes such as ellipses, parabolas, hyperbolas, and the like. Although the depicted embodiment provides a trommel which has a cross-section that is substantially constant along its longitudinal axis, it is also possible to provide trommels with cross-sections that vary along the longitudinal axis such as tapering or flaring cross-sections. Although a number of trommel configurations are operable and each may provide certain advantages in some circumstances, the depicted configuration is believed to provide at least the advantages of relatively low manufactured cost, easy access, low parts count, wider material choice and ease of design, construction, and maintenance.

Another feature which is believed to contribute to the desired lifting/free-fall behavior of the coins or other objects is a provision of one or more vanes protruding into the interior of the trommel **1922a**, **1922b**, **1922c**, **1922d**, **1924a**, **1924b**, **1924c**, **1926a**, **1926b**, **1926c**, **1926d**, **1928a**, **1928b**, **1928c**, **1928d**. It is believed that by positioning vanes at an angle such as about 15° **1930** to a plane passing through the longitudinal axis **1932**, the vanes assist not only in providing coin-lifting/free-fall, but also assist in moving the coins in a direction towards the output region **1308**. Although it would be possible to provide one or more vanes whose lateral position (with respect an interior surface of the trommel) changed monotonically, it is believed such configuration is not as effective in assisting with movement of coins towards the output portion **1308**, as a configuration in which the lateral position of the vane changes non-monotonically. In the depicted embodiment this is accomplished by providing the vanes in several subparts or segments, defining discontinuities or nodes at longitudinal positions **1936a**, **1936b**, **1936c**, **1938a**, **1938b**, **1940a**, **1940b**, **1940c**, **1942a**, **1942b**, **1942c** therebetween. Without wishing to be bound by any theory, it is believed that a configuration in which the nodes for adjacent sides of the trommel are at similar longitudinal positions does not promote the desired transport of coins towards the output end **1308**. Accordingly, the nodes **1936a**, **1935b**, **1936c**, **1938a**, **1938b**, **1940a**, **1940b**, **1940c**, **1942a**, **1942b**, **1942c**, are perfectly configured such that nodes defined on one surface are at longitudinal positions different from the node positions for an adjacent surface and, preferably, different from node positions for all other surfaces, as depicted. In the depicted embodiment, eleven of the fifteen vane segments are the same length (about 2.7 inches or about 6.8 cm in the depicted embodiment), with the desired node offset resulting in the remaining segments **1922a**, **1922d**, **1926a**, **1928d** being shorter.

In the depicted embodiment, vanes are separately formed and attached to the interior surfaces of the trommel. Preferably, attachment is via tabs (not shown) protruding from the undersurface of the vanes and engaging with slots (not shown) formed in the trommel surfaces. In the depicted embodiment, rivets **1948** are used for attachment. Attachment could also be by interference fit, bolts and nuts, welding, brazing, soldering, adhesives, or vanes may be



integrally formed with the trommel. In one embodiment the vanes are formed of a material similar to the material used to form the trommel surfaces, preferably stainless steel, although plastics, fiberglass, ceramics, and the like can also be used.

In one embodiment, as depicted in FIG. 19E, the vanes protrude a distance 1952 into the interior of the trommel of about 0.45 inches (about 1.2 cm). In the depicted embodiment, the upper portion (such as the upper 0.2 inches (about 5 mm) 1954 is angled (e.g., at about 45°) 1956 to a normal 1958 to the adjacent trommel surface. The angled portion 1954 is believed to assist in lifting the coins higher (compared to non-angled vanes) during trommel rotation.

In the depicted embodiment use of vanes for assistance in moving the coins towards the output in 1308 is particularly useful since the depicted configuration shows a substantially horizontal longitudinal axis 1346. If desired, a device can be constructed such that the rotation axis 1346 departs from the horizontal, such as being inclined towards the output end 1308. e.g., to assist in movement of coins towards the output portion 1308. The inclination, or lack thereof, of the rotation axis 1346 is determined by the location of the downstream bearing 1360 which engages the cylindrical bearing surface 1362 of the second end cap 1318. Preferably, the bearing ring 1360 is formed of a plastic material such as a nylon or Delrin®, and is preferably formed of a material different from the material of the bearing surface 1362 of the second end cap 1318. The second end cap 1318 defines an opening 1364 through which coins or other objects exit from the trommel assembly 1338.

The output bearing 1360 is held in position by an end wall 1366. In the depicted embodiment, the end wall 1366 is mounted to the frame 1368 so as to permit the end wall 1366 to be moved so as to allow the trommel assembly 1338 to be withdrawn, e.g., for cleaning or maintenance. In the depicted embodiment, the end wall 1366 is coupled to legs 1372a, 1372b which fit into rails 1374a, 1374b, 1374c, 1374d, to permit sliding movement in an engagement direction 1376a or disengagement 1376b direction. Springs 1378a, 1378b, normally urges the legs 1372a, 1372b, and thus the wall 1366 in the engagement direction 1376a. The springs 1378a, 1378b are sufficiently strong to securely maintain the trommel assembly 1338 in the engaged position (i.e., the position shown in FIG. 13) during normal operation, but permit the output portion 1308 to be moved in the disengagement direction 1376b manually (i.e., without the use of special tools, preferably without the use of any tools) in an amount sufficient to prevent disengagement and withdrawal of the trommel assembly 1338, e.g., for maintenance, cleaning, replacement, inspection, and the like. Preferably, a limit screw 1377a, 1377b provides a stop to prevent the force of the springs 1378a, 1378b from causing the bearing 1360 to thrust against the end cap 1318, undesirably increasing friction. In the depicted embodiment, the tray 1382 is formed in two portions 1382a, 1383b, coupled in a sliding fashion to permit the tray to be collapsed in a direction 1385. Collapsing the tray is believed useful in assisting in tray removal, for certain configurations, e.g., where space is restricted. Preferably the tray 1382 has sufficient capacity that tray emptying is required no more often than about once every two weeks, during normal anticipated use. Other fashions of permitting disengagement or movement of the bearing ring 1360 can be used, such as providing for hinged or pivoting movement. The depicted sliding movement is believed to permit removal of the trommel 1338, e.g., through the open bottom 1382 of the frame, while reducing or minimizing longitudinal space requirements. In the

depicted embodiment, an output chute 1374 is provided adjacent the output opening of the trommel. In the depicted configuration the output chute 1374 is configured to direct coins, output from the trommel, in a substantially downward direction 1320. A tapered region 1378 assists in directing the coins.

Preferably, a tray or other container 1382 is located beneath the trommel assembly 1338 to catch dirt which passes through the trommel dirt openings. Preferably, the tray 1382 is configured to be easily removed (e.g., for emptying, cleaning, and/or permitting access to the under-portion of the device). In the depicted embodiment, the first edge 1384 of the tray 1382 engages a rail or lip formed on the frame 1368, and the opposite edge 1386 may be rotated upward to engage with spring clips 1390a, 1390b on the opposite side of the frame.

In one embodiment, a long object trap 2000 (FIG. 20) may be positioned between the input tray 1402 and the trommel 1306 to assist in preventing insertion of long, relatively rigid objects such as a popsicle stick, into the trommel. In the depicted embodiment, the long object trap includes a first, upstanding wall 2002 and, somewhat downstream, a second, descending wall 2004. As depicted in FIG. 21, any attempt to insert a rigid elongated object 2006 will result in the object contacting a floor region 2008, preventing further passage.

In operation, the user of the embodiment of FIGS. 13–21 places a mass of coins, preferably all at once (typically accompanied by dirt or other non-coin objects) in the input tray 1402. The user is prompted to push a button to inform the machine that the user wishes to have coins discriminated. Thereupon, the computer causes the input gate 1324 to open (via solenoid 1326) and illuminates a signal to prompt the user to begin feeding coins. When the gate 1324 is open, the motor 1352 is activated to begin rotating the trommel assembly 1338. The user moves coins over the peak defined by the hinge 1414, typically by lifting the tray 1402 at least partially, and/or manually feeding coins over the peak 1414. The coins pass the gate 1396 (typically set to prevent passage of more than a predetermined number of stacked coins, such as by defining an opening equal to about 3.5 times a typical coin thickness). The coins move down the first trough 1310, where the pins 1322a and 1322b prevent passage of certain long objects such as lottery tickets and the like. A long object trap (if any) prevents passage of other types of objects such as popsicle sticks. Coins continue to flow down the second trough or chute 1312. Coins travel through the chute collar mouth 1334 and into the interior of the rotating trommel assembly 1338. Within the rotating assembly 1338 the coins are lifted and free-fall, at least partially, through the interior of the trommel, preferably at least partially in response to provision of flat surfaces, corners, and/or vanes within the trommel. As the coins free-fall or are otherwise agitated by the rotating trommel, dirt particles or other non-coin objects pass through the holes of the trommel and fall into the tray 1382. Coins travel through the trommel, e.g., in response to angled disposition of the vanes and the inclination of the trommel, if any. In general is believed that a larger angle provides for shorter residence time, but less thorough cleaning or lifting of the coins. Thus the angle selection may require a compromise between the desire for thorough cleaning and the desire for short residence time (which contributes to higher throughput). The depicted configuration, when the trommel rotates at about 36 RPM, and using a typical mixture of U.S. coins, provides a coin residence time of approximately 10 seconds. Under these conditions, throughput during normal



use is believed to be sustainable at about 600 coins per minute or more. Configuration and operating conditions can be adjusted to increase or decrease throughput, e.g., by changing the size, length or capacity of the trommel, increasing rotation rate, changing vane configuration or angles, and the like, within structural constraints for desired durability, lifetime and maintenance costs. The coins, after being at least partially cleaned, exit the second opening **1364** of the trommel, and are directed by the output chute **1374** in an output direction **1320** toward downstream components such as the hopper of a coin transport/discrimination device.

Preferably, operation of the device is monitored, such as by monitoring current draw for the motor **1338**. In this configuration, a sudden increase or spike in current draw may be considered indicative of an undesirable load and/or jam of the trommel assembly **1338**. The system may be configured in various ways to respond to such a sensed jam such as by turning off the motor **1352** to stop attempted trommel rotation and/or reversing the motor, or altering motor direction periodically, to attempt to clear the jam. Jamming or undesirable load can also be sensed by other devices such as magnetic, optical or mechanical sensors. In one embodiment, when a jam or undesirable load is sensed, coin feed is stopped or discouraged, e.g., by closing gate **1324** and/or illuminating a "stop feed" indicator **1328b**.

Turning, now, to the embodiments of FIGS. 3–12, in FIG. **3**, the perforated tray **1402** provides a device for moving coins therein (upon lifting the tray **1402** about pivot axis **1414**) through a slot **312**, past a gate **314** which may be, e.g., a controllable gate, and via chute **316** into a perforated-wall cylinder **318**. Preferably, the perforated wall cylinder **318** is configured to assist in or cause the relative movement of coins introduced thereto, such as by being rotatable in a first direction **322** about its longitudinal axis **324**. Various rates of rotation can be used. Preferably, a high feed rate through the cylinder is achieved, such as a rate of at least 100 coins per minute, preferably at least 200 coins per minutes, more preferably at least about 600 coins per minute or more.

Preferably, the perforations or holes **326** formed in the surface or wall of the cylinder **318** are shaped or sized to prevent or avoid passage, through the holes **326**, of the smallest coins which are intended to be counted by the counting device. Various hole or opening sizes and shapes are possible, giving due consideration to the size or diameter of the coins and, in some cases, the tumbling speed or rotational velocity. In one embodiment, oblong openings are provided and are believed to be useful, in some embodiments, in further assisting removal of non-coin matter.

Preferably, openings **326** are as large as possible to accommodate large non-coin matter without undesirably diverting or hindering the feed rate of smaller diameter coins. A number of factors may affect the choice of hole sizes. As described below, internal vanes, fins, ridges and other projections may be positioned, e.g., on the inside surface of the cylinder, and there must be sufficient remaining surface to allow these projections to be attached and/or formed. The size of the holes and/or the spacing and/or pattern of the holes may affect the strength or load capacity of the cylinder **318**. Removing non-coin debris is important, and having a large amount of open surface area (total surface area of all holes in the cylinder **318**) tends to increase the effectiveness of eliminating large objects, including large, dense and/or odd-shaped objects. However, the total area occupied by holes in the drum, while being desirably as large as feasible, should not be so large as to cause the cylinder to lose structural integrity, having a small than desired load capacity, and/or be subject to unwanted deflection or failure.

A number of different materials can be used for forming a cylinder **318**. In one embodiment, the cylinder may be formed of cast urethane. In one embodiment, longitudinal steel and/or stainless tubing is used for the tumbler cylinder **318**. Preferably, the tube is non-magnetic, such as being formed of stainless steel such as T-**304**, T-**316**, and/or ELC grade steel. By providing a non-magnetic tumbler, cylinder **318**, avoids interfering with devices such as magnets (not shown) that may be provided for eliminating ferrous coins and/or ferrous non-coin matter. The thickness of the drum **318** can be selected to provide a desired coin capacity or load-bearing ability, a desired usable lifetime and/or desired wear factor. In one embodiment the cylinder **318** is constructed from corrugated spiral lock seam tubing. This embodiment is particularly useful in that blades or furs can be configured to be positioned adjacent to the spiral seams, which is believed to offer enhanced strength and/or higher pressure differentials, and thus allow a reduction in wall thickness and overall mass of the cylinder over what would otherwise be required. A suitable tubing may be obtained from Perforated Tubes Incorporated of Ada, Mich.

Preferably, one or more protrusions are provided extending inwardly into the interior of the cylinder **318**. As depicted in FIG. **4**, a helical blade **402** may be provided. The blade assists in moving the coins such as by lifting coins from a lower position to a higher position, and releasing the lifted coin on the upper level of the coins in cylinder **318**, as the cylinder **318** is rotated **322**. Further, in the depicted embodiment, the blade, being helical-shaped **402**, acts to convey the coins in a direction **332** toward later or downstream apparatus such as a hopper **334**. In this fashion, even though in the embodiment of FIG. **3** the axis **324** of the cylinder **318** is horizontal, coins may be moved in a direction **332**, without the need for relying on a gravity feed. Such a configuration is useful in order to minimize the vertical extent **336** required for the device. If desired, however, the tumbler cylinder **318** may be tilted, e.g. as in FIG. **5**, and, if desired, a gravity feed may be used to assist in moving coins.

Various materials may be used for forming or coating the interior surface and/or projections **402** of cylinder **318**. A low friction or non-stick material such as Teflon may be used to avoid unwanted adhesion of coins or non-coin matter to the tumbler **318**. In one embodiment, the surfaces that will come in contact with the coins and non-coin matter will be chemically resistant and inert, to avoid corrosion and/or reaction with materials that may be introduced into the tumbler **318**. In one embodiment, the surfaces are durable since they will be constantly impacted by the coins and other materials. Wear-resistant materials that may be used include silicon carbide, or other ceramic material, steel, carbon-impregnated or carbon fiber or fiber-impregnated metals or ceramics or carbon impregnated foam, titanium, aluminum or other metals, nylon, polyvinyl chloride or other plastics or resins, and the like. In one embodiment the tumbler **318** is provided with materials for adsorbing, absorbing trapping or dissipating moisture, oils, finely divided particles, and the like. In one embodiment fins, blades or surfaces of the tumbler **318** are designed to abrade away over time, and are formulated to include materials which may assist in conditioning, cleaning, polishing, or otherwise conditioning the coins. For example, dry silicon lubricants may be included in the formulation, or abrasives for assisting or polishing coins. In one embodiment the fins, blades or other projections are removable so that they can be replaced or changed in shape or materials, as desired, to improve mechanical action, abrasion, polishing or other characteristics, or if replacement is required because of



wear. Even if the projections or surfaces of the tumbler do not impart an abrasive material, it is believed that some abrasive or polishing action of the coins against each other will be achieved. It is believed that a material that self-destructs or disintegrates over time not only indicates wear, but also can be used for imparting cleaning abrader to not only help clean the coins, but eventually clean transport mechanisms, hoppers, sensors, sorting and counting mechanisms and other mechanisms throughout the machinery.

A number of devices for accommodating rotation of the tumbler **318** can be used. The tumbler assembly may be supported by a pillow block **702** (FIG. 7), a roller-supported **704a**, **704b**, **704c** end cap **706**, or may be provided with rollers or roller bearings **502a**, **502b**, **502c**, or a bracket engaging a race or annular recess **504**, or other bearing surface **708**. If desired, one or more rollers **502a** may be pivotable or spring loaded **524**, e.g., to accommodate installation or removal of the cylinder **318**, e.g., for maintenance, repair, inspection, and the like. It is particularly desirable that the tumbler be configured for ease of removal so that it can be easily cleaned or replaced or jams may be cleared.

A number of devices may be provided for driving the rotationally-mounted cylinder. The cylinder may be coupled to a toothed pulley or gear **710**. The toothed pulley or gear **710** may be driven via a gear train or a toothed belt, such as a timing belt, coupled to a motor, such as an alternating current or DC gear motor. In the embodiment of FIG. 9, an alternating current gear motor **802** has a shaft that connects to a pulley **804** for driving a toothed belt **806**, which engages a pulley such as a toothed pulley **808**, coaxial with the perforated cylinder **810**. Suitable belts, motors or pulleys can be obtained, e.g. from SDT components company.

In one embodiment, materials which move through the perforations **326**, are received in a tray or other receiving area, preferably one which may be easily removed for emptying and/or cleaning **338**. Although in the embodiment depicted in FIG. 3 the tray **338** receives materials expelled from only the tumbler **318**, and a separate tray **343** receives materials which moves through the perforations of the tilting tray **1402**, if desired, a single tray or other receptacle can be provided for both purposes.

Preferably, the tumbler **318** or tumbler assembly is grounded appropriately to avoid static electric charge buildup, which could have the adverse effect of attracting certain non-coin materials to the drum. Conductive or non-static coatings or components may be used in constructing the drum **318**. Preferably all materials along the coin path and tumbler are conductive and grounded. In one embodiment, a multi-fingered conductive charge gatherer, similar to a Christmas garland, may be used to collect and/or dissipate static.

In one embodiment, the apparatus is configured to provide a flow of air or other fluid past the contents of the tumbler to assist in removing lighter and low-density non-coin material. Air flow devices may include a positive pressure device, a negative pressure or vacuum device, or both, although it is believed that a vacuum system may, in some environments, create an undesirable amount of noise. Preferably, in the case of a vacuum, a filter or filter bag is provided for capturing materials. Positive pressure air may be configured to pass through a filter on the feed end **342** of the tumbler chamber. In one embodiment, cleansed air is flushed through the system and additional air flow is used to dissipate moisture and heat. A suitable filtering system may be obtained from Nikro Industries, Villa Park, Ill. 60181. In one embodiment, a filter is used conforming to specifica-

tions: 88 inches of water lift, 95 cubic feet per minute, 1.25 horsepower, meeting MIL-F-51079 and MIL-F-51068B. An example is model number DC00288.

In one embodiment a low back-pressure air transfer system may be used. In this system, a fan is mounted adjacent the coin-exit end of the tumbler **344**, and a suction hose is positioned adjacent the coin-input end **342**. The intake end of the suction hose may be screened or filtered to avoid damage to fans or other devices that power of the suction. Preferably there is little back pressure in the system and a relatively large amount of air is moved through as the coins are tumbled. In one embodiment the perforated cylinder **318** is enveloped and sealed with a housing to assist in directing air flow in the desired counter-current direction **334**. The housing may be in the form of a semi-cylinder covering which seals with a waste removal tray **338**. Such a housing preferably also is useful in diminishing or deadening the noise of the tumbler device.

In one embodiment the system is substantially modular such as being contained, along with a feed tray **1402**, in a rectangular or other modular housing. Preferably the modular design is configured to accommodate retrofitting in devices which do not currently have a tumbler. For example, a device such as that depicted in FIG. 1 may be retrofitted by removing the rectangular housing depicted in FIG. 2 and replacing with the rectangular modular unit of FIGS. 8 through 11. In one embodiment the tubular tumbler is formed from two semi-cylindrical mating polyurethane components.

The present invention includes a number of features and embodiments. According to one embodiment, the invention includes a coin agitator for use in separating non-coin matter from coins for use in a coin counting device prior to transfer of said coins to a sensor mechanism of said coin counting device including a container with at least a first opening. In this embodiment, the coin agitator may include a tube. The tube may be movable by being rotatable substantially about its longitudinal axis. The tube may be perforated. A perforated tube may have a largest perforation size configured to prevent passage of a smallest desired coin. A plurality of projections may extend inwardly from a surface of said coin agitator. The agitator may include at least a first helical vane. The agitator may include at least a first fan configured for producing air flow through said coin agitator.

According to one embodiment, a coin conditioning apparatus for use in a coin discriminating may include a device for receiving a plurality of coins in a first region and for tumbling said received coins to assist in separating non-coin material; and a device for moving said coins through said receiving device. The apparatus may include a device for causing a fluid to flow through said receiving means during said tumbling. The apparatus may include a device for imparting a coin conditioning material into said plurality of coins. In one embodiment, said coin conditioning material is selected from the group consisting of a lubricant and an abrasive. In one embodiment, said coin conditioner is substantially modular to accommodate retrofitting. The apparatus may include a device configured to direct air flow in a direction counter-current to at least a first direction of coin movement. The apparatus may include a housing encompassing said coin conditioning device for reducing perceivable noise. The apparatus may include a positive pressure device for causing air flow through said coin conditioner. The apparatus may include a vacuum device for providing air flow through said coin conditioning.



15

In one embodiment, the invention provides a method for cleaning coins including:

- introducing said coins into a rotatably mounted tube having sidewall perforations;
- rotating said tube about its longitudinal axis to dislodge non-coin material;
- moving coins in a first longitudinal direction through said rotating tube; and
- flowing air through said rotating tube.

In light of the above description, a number of advantages of the present invention can be seen. The embodiment of FIGS. 13 through 21 is believed to particularly provide for thorough and efficient cleaning of coins while maintaining relatively high throughput, relatively low noise, and providing for ease of maintenance, replacement, inspection, and/or cleaning. This embodiment is useful in avoiding adhesion or slowing of coins along the depicted coin path by reducing or minimizing the potential for surface-to-surface contact of a coin with surfaces of the device. The device is relatively inexpensive to design, fabricate, construct, install and/or maintain, with many of the components being configured so that they may be formed by standard plastics or sheet metal fabrication processes such as stamping, drilling, injection molding and the like. Preferably the device is constructed with a shape, dimension and "footprint" that is compatible with earlier or in-service devices to permit ease of upgrading existing in-service devices, or ease of converting production facilities from production of existing devices, to production of devices according to the present invention.

The present invention provides an economical system and method for delivering clean coins to improve accuracy, durability and reliability of systems that identify, count, sort, discriminate and/or process coins and reducing jamming in input feed, transport and/or hopper devices. This system provides a system and method for self cleaning of a self-service coin processing device. The invention drives a tumbling mechanical agitation system for removing non-coin debris. The system reduces or eliminates the need for special-services such as continually stopping a coin-counting device in order to perform maintenance of the identification, counting, sorting or transport components. The system preferably provides for wear indicating components such as wear indicating inner fins or other projections inside a tumbler. Preferably, the projections or other tumbler components are capable of imparting lubricants and/or abrasives or abrasive compounds. Preferably, the system provides a liquid or moisture removal system within the tumbler for removal of excess moisture or liquids, oils and the like, e.g., through an absorbent, adsorbent or desiccant component or feature of the tumbler fins or surfaces. In one embodiment, components are provided for dislodging or removing trapped items such as a floating or loose insert for dislodging items (such as a ball or other item which is too large to exit the exit hole) and/or finger rakes for dislodging trapped and/or dropped items.

A number of variations and modifications of the invention can be used. Although the invention is principally described as being useful in connection with cleaning coins, some or all features of the present invention can be used in connection with cleaning other types of devices such as regularly shaped items (e.g., golf balls), irregularly shaped items (such as screws, nuts, bolts, nails, and the like), and similar manufactured items. Although in one embodiment the device is controlled by a computer, other control devices can be used such as non-programmable or hard-wired control devices, application specific integrated circuits (ASICS), and the like. Although, in the above, items which are

16

retained within the walls of the trommel are described as the objects to be cleaned and material passing through the holes in the walls of the trommel are described as "dirt," the device can be used in the opposite fashion, i.e. to recover relatively small valuable objects that pass through the holes of the trommel walls and discarding the large objects retained within the walls of the trommel. Similarly, the device can be used to separate large objects from small objects, neither of which is to be discarded.

In the above description, a number of surfaces (such as the chute surfaces and trommel interior surfaces) are provided with features which are believed to assist in avoiding the slowing or stopping of coin movement or flow (such as may result from friction, adhesion, surface tension or the like).

These features may include dimples, surface curvature, ridges, holes and the like, and are believed to operate by reducing or eliminating surface-to-surface contact between a coin face and a surface of the apparatus. In general, any or all of these features may be used on any or all of the apparatus surfaces that are coin-contact surfaces, such that, for example the first and/or second chutes may be provided with dimples or ridges (with or without the curvature described above), or the trommel interior surface may be provided with a degree of curvature (with or without the dimples described above.)

In addition to, or in place of, moving coins by providing a rotatable cylinder, other types of movement of the tubular or concave surface may also be used for moving or agitating the coins, such as a rocking or tilting motion, a swinging motion, a vibrating-motion, and the like. Although, in one embodiment, a circular cross-section tumbler is depicted, other shapes may be used in this embodiment such as triangular, square, pentagonal, hexagonal, octagonal, or other polygonal cross-section tubing, conical or parabolic-sided or other tapering or flaring tubing and the like. In one embodiment it would be possible to provide a separation device which is U-shaped and, rather than being rotated, is driven to swing through an arc or tilt in order to agitate the coins. While it is preferred to provide perforations in the tube of the concave surface, it is also possible to provide an embodiment in which a tube or concave surface is unperforated, and air flow is used for removing materials dislodged during tumbling, e.g., when only lightweight or low-density contaminants are anticipated. If desired, the vanes, fins or other agitating/moving devices may be separate from or movable with respect to the tubular or concave surface. It is possible to rotate or otherwise move the fins relative to either a fixed or rotating tube, including rotating the tube and fins in opposite directions. If desired, the tubular or concave surface and/or the projections may be coated with or may incorporate substances or surfaces to assist in cleaning, polishing or otherwise conditioning the coins, such as absorbent or adsorbent materials for removing liquids, oils, finely divided particles, and the like, or materials for transferring lubricants, abrasives, polishing compounds, and the like, to the coins. The tubular or concave surface or projections may incorporate or provide materials for reducing friction, avoiding static electric charges, avoiding corrosion, and the like. The tumbler and/or housing may be made from or may include anechoic, sound-deadening and/or anti-static material. The drum, internal vanes, etc. can be connected to a transmission and/or speed reducer that is computer controlled, e.g. to adjust tumbling speed based on sensed temperature, humidity, load weight, and/or in-feed or out-feed rate, or to suspend out-feed, e.g. in response to a sensed jam or other malfunction. If desired, a low of au or other gases or, if



desired, liquids, aerosols, mists, gels, and the like, may be introduced, preferably in a counter-current fashion with respect to the coin flow, to assist in conditioning the coins, e.g. by removing non-coin objects, especially small or lightweight non-coin matter such as hair and dust. A pressurized air and/or vacuum system may be used for causing such flow. If desired, filters may be provided for trapping some removed materials. In one embodiment, a cylindrical body having vanes rising from the inner diameter and a plurality of openings is used. If desired, it would be possible to construct a device in which the perforated surface is maintained stationary, and a separate screw drive or other drive agitates and moves the coins to or across the stationary surface.

FIG. 22 is an illustration of a coin exchange kiosk 2200 in a possible environment; a supermarket. Kiosk 2200 is free-standing, and has been designed with a small footprint to minimize the required floor space. The lower front surface 2210 is clear, allowing the user to watch the coins as they are separated, counted, and dropped into escrow tray 2205. By making the process visible to the user, trust in the machine is encouraged. Furthermore, since watching the sorting process is interesting, the user becomes integrated into the machine's operation and is further encouraged to use the machine.

Initially the coins are placed in coin tray 2220 where small foreign objects fall through perforations in the bottom of the tray and the user can remove large foreign materials prior to coin sorting. When the user is ready to begin the sorting process, they must push "go" button 2215. Button 2215 initializes the coin counter, activates the coin sorter, and activates the fan within the waste management chute. If the system does not detect coins within a predetermined period of time, both the coin sorter and the fan are deactivated. The user next raises the edge of tray 2220. The tray is hinged on the right side and acts as a chute to funnel the coins into the kiosk. User directions, transaction information, store bargains, and advertisements appear on video screen 2230. Screen 2230 can also be used to show attention getting displays in order to attract potential users. Once the coins are admitted into the kiosk and the go button has been pushed, the waste removal and coin sorting process begins. During the coin sorting process, coins which do not meet the necessary physical criteria are rejected and returned to the user via chute 2265. In the preferred embodiment, as the coins are counted the video screen displays both the total monetary value and the number of coins collected within each denomination.

At the conclusion of the sorting process, the user is asked to either accept the stated coin value and continue the transaction, or cancel the transaction. This selection is made by pushing one of two buttons 2250. If the user continues the transaction, then the coins in the escrow tray 2205 are dumped into a depository and the user is issued a voucher through slot 2260. In the preferred embodiment, the voucher is worth the value of the counted coins and is redeemable at the retailer's cashier for cash or credit towards purchases. Store coupons, printed by the voucher printer and good towards store bargains, are dispensed with the cash voucher. Manufacturers' coupons are dispensed through an adjoining slot 2265 at no cost to the user. If the user cancels the transaction the coins are returned in area 2270. The upper back portion 2240 of kiosk 2200 is a display board where advertisements and notices can be placed. Display board 2240 can also be used to indicate what coupons the machine is currently dispensing.

Although the invention has been defined by way of a preferred embodiment and certain variation modifications, other variations and modifications can also be used.

What is claimed is:

1. An apparatus for issuing a redeemable voucher, the apparatus comprising:

a user interface configured to receive a request for a redeemable voucher;

a coin input region configured to receive a plurality of coins in random orientation;

a debris separation device having a first opening configured to receive the plurality of coins from the coin input region, the debris separation device further having at least a first wall forming an interior surface and an exterior surface, the first wall having at least one second opening smaller than the first opening and sized to prevent passage therethrough of the smallest coin of the plurality of coins;

a driver operably coupled to the debris separation device and configured to move the debris separation device and agitate the plurality of coins; and

a coin discriminator configured to receive the plurality of coins from the debris separation device, the coin discriminator including at least one coin sensor configured to discriminate at least one coin denomination.

2. The apparatus of claim 1 wherein the debris separation device further includes a third opening, the third opening being larger than the second opening and configured to permit at least a portion of the plurality of coins to exit the debris separation device.

3. The apparatus of claim 1 wherein at least a portion of the first wall forms at least a portion of a circular cylinder.

4. The apparatus of claim 1 wherein at least a portion of the first wall is at least generally flat.

5. The apparatus of claim 1 wherein the debris separation device further includes at least second and third walls extending adjacent to the first wall, the first wall having a first shape, the second wall having a second shape, and the third wall having a third shape, and wherein the second and third shapes are at least generally the same as the first shape.

6. The apparatus of claim 1 wherein the first wall further includes a plurality of dimples protruding at least partially inwardly relative to the debris separation device.

7. The apparatus of claim 1 wherein the coin input region includes a tray that is upwardly pivotable about a pivot axis to move the plurality of coins from the tray and into the debris separation device.

8. The apparatus of claim 1 wherein the driver is operably coupled to the debris separation device to rotate the debris separation device about at least a first axis.

9. The apparatus of claim 1 wherein the driver is operably coupled to the debris separation device to pivot the debris separation device about at least a first axis.

10. The apparatus of claim 1 wherein the debris separation device is configured to rotate about an axis and the first wall further includes means for urging the plurality of coins in a direction at least generally parallel to the axis as the debris separation device rotates about the axis.

11. The apparatus of claim 1 wherein the debris separation device is configured to rotate about a non-horizontal axis.

12. The apparatus of claim 1 wherein the debris separation device includes a plurality of openings including the second opening configured to permit dirt to exit the debris separation device.

13. The apparatus of claim 1, further comprising at least a first vane protruding inwardly from the interior surface of the debris separation device.

14. The apparatus of claim 13 wherein the first vane contacts the interior surface of the debris separation device



## 19

in a first region defining at least a first plane tangent to the interior surface in the first region, and wherein at least a portion of the first vane is non-orthogonal to the first plane.

15. The apparatus of claim 13 wherein the first vane contacts the interior surface of the debris separation device in a first region defining at least a first plane tangent to the interior surface in the first region, and wherein at least a first portion of the first vane is non-orthogonal to the first plane and a second portion of the first vane is orthogonal to the first plane.

16. The apparatus of claim 1 wherein the debris separation device defines a first longitudinal axis, wherein the apparatus further comprises at least a first vane protruding inwardly from the interior surface of the debris separation device and defining a second longitudinal axis, and wherein the second longitudinal axis is non-parallel to the first longitudinal axis.

17. The apparatus of claim 1 wherein the interior surface of the debris separation device includes substantially flat walls.

18. The apparatus of claim 1, further comprising a debris tray positioned at least generally below the debris separation device, the debris tray being configured to receive dirt and other non-coin items passing through the at least one second opening in the first wall of the debris separation device.

19. The apparatus of claim 1, further comprising a signaling device configured to indicate when additional coins may be moved from the coin input region along a path toward the debris separation device.

20. The apparatus of claim 1, further comprising a voucher dispenser configured to dispense a voucher for at least a portion of the discriminated coins, wherein the voucher is redeemable at a point of sale in a non-bank retail location in exchange for products sold at the retail location.

21. The apparatus of claim 1 wherein the user interface includes a depressible button.

22. The apparatus of claim 1 wherein the debris separation device further includes a second wall and a third wall extending upwardly from opposing edges of the first wall.

23. The apparatus of claim 1 wherein the debris separation device is at least generally U-shaped.

24. The apparatus of claim 1 wherein the driver is configured to vibrate the debris separation device in the absence of rotation to agitate the plurality of coins.

25. The apparatus of claim 1 wherein the user interface includes a touch screen.

26. The apparatus of claim 1 wherein the debris separation device further includes a second wall and a third wall extending upwardly from opposing edges of the first wall to provide the debris separation device with an at least generally U-shaped cross-section, and wherein the driver is configured to vibrate the debris separation device in the absence of rotation to agitate the plurality of coins.

27. The apparatus of claim 1 wherein the first wall of the debris separation device is inclined from horizontal and further includes a second wall and a third wall extending upwardly from opposing edges of the first wall to provide the debris separation device with an at least generally U-shaped cross-section, and wherein the driver is configured to vibrate the debris separation device to agitate the plurality of coins.

28. An apparatus for issuing a redeemable voucher, the apparatus comprising:

means for receiving a user request for a redeemable voucher

input means for receiving a plurality of randomly oriented coins from a user;

means for separating debris from the plurality of coins received from the user, the means for separating defin-

## 20

ing an interior space having at least a first opening sized to let dirt and other non-coin items exit the means for separating to the exclusion of any one of the plurality of coins;

5 motive means operably coupled to the means for separating and configured to move the means for separating to cause at least some of the plurality of coins to exit the interior space; and

10 coin discriminator means configured to receive the plurality of coins from the means for separating, the coin discriminator means including at least one coin sensor configured to discriminate at least one coin denomination.

29. The apparatus of claim 28 wherein the means for separating further includes means for preventing face-to-face contact between an entire face of any one of the plurality of coins and an interior surface of the means for separating.

30. The apparatus of claim 29 wherein the means for preventing face-to-face contact includes protrusions extending inwardly from the interior surface of the means for separating.

31. The apparatus of claim 29 wherein the means for preventing face-to-face contact includes an interior surface curvature of the means for separating.

32. The apparatus of claim 28, further comprising means for preventing rigid elongate objects from entering the means for separating.

33. The apparatus of claim 32, further comprising means for reversing the means for separating in response to sensing a slowing or halting of movement of the means for separating.

34. The apparatus of claim 28, further comprising means for flowing air through the means for separating.

35. The apparatus of claim 28, further comprising means for dispensing a redeemable voucher for at least a portion of the discriminated coins, wherein the voucher is redeemable at a point of sale in a non-bank retail location in exchange for products sold at the retail location.

36. The apparatus of claim 28 wherein the motive means includes means for vibrating the debris separation device in the absence of rotation.

37. A method for issuing a redeemable voucher, the method comprising:

receiving a randomly oriented plurality of coins in a coin input region;

receiving a user request for a redeemable voucher;

transferring the plurality of coins from the coin input region to a debris separation device positioned to receive coins from the coin input region, the debris separation device having a plurality of holes sized to prevent passage therethrough of the smallest coin of the plurality of coins;

50 moving the debris separation device to agitate the plurality of coins and permit non-coin matter within the debris separation device to pass through one or more of the plurality of holes and exit the debris separation device; and

transferring the plurality of coins from the debris separation device to a coin discriminator, the coin discriminator including at least one coin sensor configured to discriminate at least one coin denomination.

38. The method of claim 37 wherein moving the debris separation device includes rotating the debris separation device about an axis to agitate the plurality of coins.

39. The method of claim 37, further comprising providing at least a first vane adjacent an interior surface of the debris



## 21

separation device to assist in moving the plurality of coins through the debris separation device.

40. The method of claim 37 wherein transferring the plurality of coins to the debris separation device includes pivoting a coin tray upwardly to move the plurality of coins from the coin input region.

41. The method of claim 37, further comprising dispensing a redeemable voucher for at least a portion of the discriminated coins, wherein the voucher is redeemable at a point of sale in a non-bank retail location in exchange for products sold at the retail location.

42. The method of claim 37 wherein moving the debris separation device to agitate the plurality of coins includes vibrating the debris separation device in the absence of rotation.

43. An apparatus for cleaning coins, the apparatus comprising:

a coin input receptacle configured to receive a plurality of coins in random orientation;

a debris separation device having an at least generally U-shaped cross-section and having a first opening configured to receive the plurality of coins from the coin input receptacle, the debris separation device further having at least a first wall forming an interior surface and an exterior surface, the first wall having at least one second opening smaller than the first opening and sized to prevent passage therethrough of the smallest coin of the plurality of coins; and

a driver operably coupled to the debris separation device and configured to move the debris separation device and agitate the plurality of coins.

44. The apparatus of claim 43 wherein the first wall is a bottom wall, and wherein the debris separation device

## 22

further includes a second wall and a third wall extending upwardly from opposing edges of the first wall.

45. The apparatus of claim 43 wherein the driver is configured to vibrate the debris separation device in the absence of rotation to agitate the plurality of coins.

46. The apparatus of claim 43 wherein the first wall of the debris separation device is inclined from horizontal.

47. The apparatus of claim 43 wherein the coin input receptacle is upwardly pivotable about a pivot axis to move the plurality of coins from the coin input receptacle and into the debris separation device.

48. The apparatus of claim 43 wherein the driver is operably coupled to the debris separation device to rotate the debris separation device about at least a first axis.

49. The apparatus of claim 43 wherein the driver is operably coupled to the debris separation device to pivot the debris separation device about at least a first axis.

50. The apparatus of claim 43 wherein the debris separation device includes a plurality of openings including the second opening configured to permit dirt to exit the debris separation device.

51. The apparatus of claim 43, further comprising a debris tray positioned at least generally below the debris separation device, the debris tray being configured to receive dirt and other non-coin items passing through the at least one second opening in the first wall of the debris separation device.

52. The apparatus of claim 43 wherein the first wall is a bottom wall, and wherein at least a portion of the first wall is at least generally flat.

\* \* \* \* \*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,863,168 B1  
DATED : March 8, 2005  
INVENTOR(S) : Dan Gerrity et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 16,

Line 65, "ard/or" should be -- and/or --;

Line 68, "au" should be -- air --;

Signed and Sealed this

Twelfth Day of July, 2005

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

*Director of the United States Patent and Trademark Office*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,863,168 C1  
APPLICATION NO. : 90/008683  
DATED : September 6, 2011  
INVENTOR(S) : Gerrity et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, item (73), "JPMorgan Chase Bank, Houston, TX (US)" should be  
-- Coinstar, Inc., Bellevue, WA (US) --.

Signed and Sealed this  
Twenty-ninth Day of November, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive style with a large initial 'D' and 'K'.

David J. Kappos  
*Director of the United States Patent and Trademark Office*



US006863168C1

(12) **EX PARTE REEXAMINATION CERTIFICATE** (8514th)  
**United States Patent**  
**Gerrity et al.**

(10) **Number:** **US 6,863,168 C1**  
(45) **Certificate Issued:** **\*Sep. 6, 2011**

(54) **METHOD AND APPARATUS FOR  
CONDITIONING COINS PRIOR TO  
DISCRIMINATION**

(75) Inventors: **Dan Gerrity**, Bellevue, WA (US);  
**Aaron Finch**, Seattle, WA (US); **Chris  
Ferguson**, Redmond, WA (US); **Scott  
Scherer**, Seattle, WA (US); **Rick Riday**,  
Redmond, WA (US); **Larry D. Cannon**,  
Bothell, WA (US)

(73) Assignee: **JPMorgan Chase Bank**, Houston, TX  
(US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

269,461 A	12/1882	Rakestraw
383,166 A	5/1888	Bailey
446,303 A	2/1891	Thompson
545,185 A	8/1895	Yost
1,010,993 A	12/1911	White
1,234,707 A	7/1917	Whistler
1,345,858 A	7/1920	Jenkins
1,473,745 A	11/1923	Stedman
1,585,242 A	* 5/1926	Hageman ..... 453/12

(Continued)

**Reexamination Request:**

No. 90/008,683, Jun. 5, 2007

**Reexamination Certificate for:**

Patent No.: **6,863,168**  
Issued: **Mar. 8, 2005**  
Appl. No.: **10/652,953**  
Filed: **Aug. 28, 2003**

(\*) Notice: This patent is subject to a terminal disclaimer.

Certificate of Correction issued Jul. 12, 2005.

FOREIGN PATENT DOCUMENTS

CA	1053598	2/1979
----	---------	--------

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 09/662,977, filed Sep. 15, 2000, Knutsson et al.  
Accessories Brochure, undated, 3 pages.  
Australian Patent Office, Examiner's First Report, May 11, 1999, Australian Application No. 71948/98, 2 pages.

(Continued)

**Related U.S. Application Data**

(63) Continuation of application No. 10/304,384, filed on Nov. 25, 2002, now Pat. No. 6,666,318, which is a continuation of application No. 09/704,178, filed on Oct. 31, 2000, now Pat. No. 6,484,884, which is a continuation of application No. 09/042,784, filed on Mar. 17, 1998, now Pat. No. 6,174,230, which is a continuation of application No. 08/807,340, filed on Feb. 28, 1997, now Pat. No. 5,842,916.

(60) Provisional application No. 60/012,964, filed on Mar. 7, 1996.

(51) **Int. Cl.**  
**G07D 3/00** (2006.01)

(52) **U.S. Cl.** ..... **194/347**


(58) **Field of Classification Search** ..... 194/216,  
194/347

See application file for complete search history.

Primary Examiner—Jimmy G Foster

(57) **ABSTRACT**

Methods and systems for cleaning coins and issuing a redeemable voucher for same. In one embodiment, an apparatus for issuing a redeemable voucher includes a coin input region configured to receive a plurality of coins, and a user interface configured to receive a request for a redeemable voucher. The apparatus can further include a debris separation device having a first opening configured to receive the plurality of coins from the coin input region, and at least a first wall forming an interior surface and an exterior surface. The first wall of the debris separation device includes at least one second opening smaller than the first opening and sized to prevent passage therethrough of the smallest coin of the plurality of coins. A driver can be configured to move the debris separation device and agitate the plurality of coins.





U.S. PATENT DOCUMENTS					
			4,398,550 A	8/1983	Shireman
			4,412,292 A	10/1983	Sedam et al.
			4,412,607 A	11/1983	Collins et al.
1,668,626 A	5/1928	Brandt	4,434,359 A	2/1984	Watanabe et al.
1,711,049 A	4/1929	Fonda et al.	4,442,850 A	4/1984	Austin et al.
1,813,296 A	7/1931	Kidwell	4,447,714 A	5/1984	Lundblad et al.
1,847,940 A	3/1932	Giles	4,503,963 A	3/1985	Steiner
1,945,948 A	2/1934	Morin	4,504,357 A	3/1985	Holbein et al.
2,014,505 A	9/1935	Patche	4,506,685 A	3/1985	Childers et al.
2,119,676 A	* 6/1938	Heller ..... 209/288	4,509,122 A	4/1985	Agnew et al.
2,317,351 A	4/1943	Andalikiewicz et al.	4,509,633 A	4/1985	Chow
2,461,314 A	2/1949	Davis et al.	4,533,054 A	8/1985	Sommer, Jr. et al.
2,519,357 A	8/1950	Dougherty	4,535,915 A	8/1985	West
2,569,360 A	9/1951	Weingart	4,542,817 A	9/1985	Paulson
2,644,470 A	7/1953	Labbe	4,543,969 A	10/1985	Rasmussen
2,646,805 A	7/1953	Anderson	4,554,446 A	11/1985	Murphy et al.
2,865,561 A	12/1958	Rosapepe	4,558,711 A	12/1985	Ikuta Yoshiaki et al.
2,869,723 A	1/1959	Autio	4,577,744 A	3/1986	Doucet et al.
2,881,774 A	4/1959	Labbe	4,587,984 A	5/1986	Levasseur et al.
2,960,377 A	1/1960	Simjian	4,597,487 A	7/1986	Crosby et al.
3,007,576 A	11/1961	Hannaford	4,598,378 A	7/1986	Giacomo
3,009,555 A	11/1961	Seckula, Sr.	4,611,205 A	9/1986	Eglise et al.
3,048,251 A	* 8/1962	Bower ..... 194/219	4,616,323 A	10/1986	Hayashi
3,056,132 A	9/1962	Simjian	4,616,776 A	10/1986	Blumenthal et al.
3,065,467 A	11/1962	Prevost	4,620,559 A	11/1986	Childers et al.
3,132,654 A	5/1964	Adams	4,622,456 A	11/1986	Naruto et al.
3,147,839 A	9/1964	White, Jr.	4,677,565 A	6/1987	Ogaki et al.
3,173,742 A	3/1965	Simjian	4,694,845 A	9/1987	Zay
3,196,257 A	7/1965	Buchholtz et al.	4,706,577 A	11/1987	Jones et al.
3,292,818 A	12/1966	Jaworski	4,706,795 A	11/1987	Mikami et al.
3,396,737 A	8/1968	Picollo	4,716,799 A	1/1988	Hartmann
3,415,348 A	12/1968	Wahlberg	4,723,212 A	2/1988	Mindrum et al.
3,599,771 A	8/1971	Hinterstocker	4,733,765 A	3/1988	Watanabe et al.
3,603,327 A	9/1971	Buchholz et al.	4,753,625 A	6/1988	Okada et al.
3,680,566 A	8/1972	Tanaka et al.	4,775,353 A	10/1988	Childers et al.
3,695,448 A	10/1972	Johansson et al.	4,775,354 A	10/1988	Rasmussen et al.
3,804,249 A	4/1974	Gibbons et al.	4,809,837 A	3/1989	Hayashi et al.
3,815,717 A	6/1974	Arseneau	4,814,589 A	3/1989	Storch et al.
3,941,226 A	3/1976	Drakes	4,831,374 A	5/1989	Masel
3,960,293 A	6/1976	Sweet, II et al.	4,833,308 A	5/1989	Humble
3,969,584 A	7/1976	Miller et al.	4,883,158 A	11/1989	Kobayashi et al.
3,998,237 A	12/1976	Kressin et al.	4,884,672 A	12/1989	Parker
4,014,424 A	3/1977	Hall	4,896,791 A	1/1990	Smith
4,036,242 A	7/1977	Breitenstein et al.	4,898,564 A	2/1990	Gunn et al.
4,058,954 A	11/1977	Asami et al.	4,910,672 A	3/1990	Off et al.
4,059,122 A	11/1977	Kinoshita et al.	4,915,205 A	4/1990	Reid et al.
4,099,722 A	7/1978	Rodesch et al.	4,921,463 A	5/1990	Primdahl et al.
4,100,925 A	7/1978	Fukunaga et al.	4,936,436 A	6/1990	Keltner
4,106,610 A	8/1978	Heiman	4,953,086 A	8/1990	Fukatsu et al.
4,124,109 A	11/1978	Bissell et al.	4,959,624 A	9/1990	Higgins, Jr. et al.
4,141,372 A	2/1979	Gdanski et al.	4,963,118 A	10/1990	Gunn et al.
4,167,949 A	9/1979	Hashimoto et al.	4,969,549 A	11/1990	Eglise et al.
4,172,462 A	10/1979	Uchida et al.	4,978,322 A	12/1990	Paulsen
4,225,056 A	9/1980	Flubacker	4,995,848 A	2/1991	Goh et al.
4,228,811 A	10/1980	Tanaka et al.	4,997,406 A	3/1991	Horiguchi et al.
4,230,213 A	10/1980	Spring	5,010,238 A	4/1991	Kadono et al.
4,236,999 A	12/1980	Burgess et al.	5,021,967 A	6/1991	Smith
4,238,324 A	* 12/1980	Musselmann et al. .... 209/255	5,022,889 A	6/1991	Ristvedt et al.
4,240,589 A	12/1980	Martin et al.	5,025,139 A	6/1991	Halliburton, Jr.
4,249,552 A	2/1981	Margolin et al.	5,027,937 A	7/1991	Parish et al.
4,266,121 A	5/1981	Hirose	5,039,848 A	8/1991	Stoken
4,275,751 A	6/1981	Bergman	5,040,657 A	8/1991	Gunn et al.
4,278,543 A	7/1981	Maniquis et al.	5,055,657 A	10/1991	Miller et al.
4,306,644 A	12/1981	Rockola et al.	5,056,644 A	10/1991	Parker
4,321,672 A	3/1982	Braun et al.	5,073,767 A	12/1991	Holmes et al.
4,326,620 A	4/1982	Felix et al.	5,083,765 A	1/1992	Kringel
4,346,798 A	8/1982	Agey, III	5,083,814 A	1/1992	Guinta et al.
4,356,829 A	11/1982	Furuya et al.	5,088,587 A	2/1992	Goodrich et al.
4,360,034 A	* 11/1982	Davila et al. .... 453/8	5,091,713 A	2/1992	Horne et al.
4,369,442 A	1/1983	Werth et al.	5,098,339 A	3/1992	Dabrowski
4,369,800 A	1/1983	Watanabe et al.	5,098,340 A	3/1992	Abe
4,374,557 A	2/1983	Sugimoto et al.			
4,380,316 A	4/1983	Glinka et al.			



5,111,927 A	5/1992	Schulze, Jr.	6,138,106 A	10/2000	Walker et al.
5,114,381 A	5/1992	Ueda et al.	6,144,946 A	11/2000	Iwamura
5,122,094 A	6/1992	Abe et al.	6,179,703 B1 *	1/2001	Knutsson et al. .... 453/3
5,135,433 A	8/1992	Watanabe et al.	6,185,545 B1	2/2001	Resnick et al.
5,163,868 A	11/1992	Adams et al.	6,227,343 B1	5/2001	Neathway et al.
5,173,851 A	12/1992	Off et al.	6,230,928 B1	5/2001	Hanna et al.
5,174,608 A	12/1992	Benardelli et al.	6,233,564 B1	5/2001	Schulze, Jr.
5,183,142 A	2/1993	Latchinian et al.	6,289,324 B1	9/2001	Kawan
5,195,626 A	3/1993	Le Hong et al.	6,292,211 B1	9/2001	Pena
5,201,396 A	4/1993	Chalabian et al.	6,349,972 B1	2/2002	Geiger et al.
5,219,059 A	6/1993	Furuya et al.	6,375,080 B1	4/2002	Cremonese
5,226,519 A	7/1993	DeWoolfson	6,401,010 B1	6/2002	Takahashi
5,236,339 A	8/1993	Nishiumi et al.	6,405,182 B1	6/2002	Cuervo
5,251,738 A	10/1993	Dabrowski	6,415,262 B1	7/2002	Walker et al.
5,252,811 A	10/1993	Henochowicz et al.	6,484,863 B1	11/2002	Molbak
5,293,981 A	3/1994	Abe et al.	6,484,884 B1	11/2002	Gerrity et al.
5,299,673 A	4/1994	Wu	6,494,776 B1	12/2002	Molbak
5,302,811 A	4/1994	Fukatsu et al.	6,505,774 B1	1/2003	Fulcher et al.
5,316,120 A	5/1994	Ibarrola et al.	6,536,037 B1	3/2003	Guheen et al.
5,316,517 A	5/1994	Chiba et al.	6,554,184 B1	4/2003	Amos
5,321,242 A	6/1994	Heath, Jr.	6,666,318 B2	12/2003	Gerrity et al.
5,330,041 A	7/1994	Dobbins et al.	6,704,039 B2	3/2004	Pena
5,350,906 A	9/1994	Brody et al.	6,705,448 B1	3/2004	Steel
5,355,988 A	10/1994	Shirasawa	6,736,251 B2	5/2004	Molbak
5,365,046 A	11/1994	Haymann	6,758,316 B2	7/2004	Molbak et al.
5,374,814 A	12/1994	Kako et al.	6,854,581 B2	2/2005	Molbak et al.
5,388,680 A	2/1995	Hird et al.	6,863,168 B1	3/2005	Gerrity et al.
RE34,872 E	3/1995	Lucera	6,976,570 B2	12/2005	Molbak
5,409,092 A	4/1995	Itako et al.	7,017,729 B2	3/2006	Gerrity et al.
5,421,147 A	6/1995	Holden et al.	7,028,827 B1	4/2006	Molbak et al.
5,429,222 A	7/1995	Delay et al.	7,113,929 B1	9/2006	Beach et al.
5,435,777 A	7/1995	Takatani et al.	7,131,580 B2	11/2006	Molbak
5,441,139 A	8/1995	Abe et al.	7,290,645 B2	11/2007	Hill et al.
5,449,058 A	9/1995	Kotler et al.	2002/0026423 A1	2/2002	Maritzen et al.
5,457,305 A	10/1995	Akel et al.	2006/0191770 A1	8/2006	Gerrity
5,469,951 A	11/1995	Takemoto et al.			
5,480,061 A	1/1996	Ellinger			
5,483,363 A	1/1996	Holmes et al.			
5,506,393 A	4/1996	Ziarno			
5,513,738 A	5/1996	Hird et al.			
5,554,070 A	9/1996	Takatoshi et al.			
5,555,497 A	9/1996	Helbling			
5,560,467 A	10/1996	Takemoto			
5,564,546 A *	10/1996	Molbak et al. .... 194/216			
5,577,959 A	11/1996	Takemoto et al.			
5,637,845 A	6/1997	Kolls			
5,652,421 A	7/1997	Veeneman et al.			
5,665,952 A	9/1997	Ziarno			
5,679,070 A	10/1997	Ishida et al.			
5,696,908 A	12/1997	Muehlberger et al.			
5,699,328 A	12/1997	Ishizaki et al.			
5,732,398 A	3/1998	Tagawa			
5,743,429 A	4/1998	Morofsky			
5,746,299 A	5/1998	Molbak et al.			
5,746,322 A	5/1998	LaVeine et al.			
5,799,767 A	9/1998	Molbak			
5,839,956 A	11/1998	Takemoto			
5,842,916 A	12/1998	Gerrity et al.			
5,868,236 A	2/1999	Rademacher			
5,880,444 A	3/1999	Shibata et al.			
5,909,792 A	6/1999	Gerlier et al.			
5,909,794 A	6/1999	Molbak et al.			
5,974,146 A	10/1999	Randle et al.			
5,991,413 A	11/1999	Arditti et al.			
6,047,807 A	4/2000	Molbak et al.			
6,053,807 A	4/2000	Metzger et al.			
6,068,550 A	5/2000	Breitholtz et al.			
6,105,009 A	8/2000	Cuervo			
6,110,044 A	8/2000	Stern			
6,116,402 A	9/2000	Beach et al.			
6,119,099 A	9/2000	Walker et al.			

FOREIGN PATENT DOCUMENTS

CA	2060630	11/1992
CA	2067987	11/1992
CH	680171	6/1992
DE	660354	5/1938
DE	2528735	9/1976
DE	3021327	12/1981
DE	3147603	6/1983
EP	0091731	10/1983
EP	0351217	1/1990
EP	0420163	4/1991
EP	0477722	4/1992
EP	0924662	6/1999
EP	0924664	6/1999
EP	0924665	6/1999
FR	2042254	2/1971
FR	2342531	9/1977
FR	2845189	4/2004
GB	958741	5/1964
GB	1564723	4/1980
GB	2095452	9/1982
GB	2121582	12/1983
GB	2153128	8/1985
GB	2715427	11/1986
GB	2186411	8/1987
GB	2188467	9/1987
GB	2198274	6/1988
GB	2223340	4/1990
GB	2223872	4/1990
GB	2255666	11/1992
JP	52-49892	4/1977
JP	62-50876	3/1987
JP	1-258092	10/1989
JP	1-307891	12/1989
JP	2-81193	3/1990



JP	3-63795	3/1991
JP	3-92994	4/1991
JP	3-252795	11/1991
JP	4-67776	6/1992
JP	4-315288	11/1992
JP	4-344995	12/1992
JP	52-50296	4/1997
SE	44-244	9/1988
SE	44-247	9/1988
SE	8801851	11/1989
SE	50-250	8/1991
SE	9501091	9/1996
WO	WO-94/06101	3/1994
WO	WO-94/09440	4/1994
WO	WO-95/30215	11/1995
WO	WO96/30877	* 10/1996
WO	WO-97/33257	9/1997
WO	WO-99-50785	10/1999
WO	WO-00-10138	2/2000

OTHER PUBLICATIONS

Bedienungsanleitung CDS 500/MCC 500, 1991, 9 pages.  
 Cash, M., "Bank blends new technology with service," Winnipeg Free Press, Sep. 4, 1992, 1 page.  
 CASE-ICC Limited, "CDS Automated receipt giving cash deposit system," Undated, 3 pages.  
 F. Zimmerman Co., "Reference Manual Contovit/Sortovit, Perconta Money Counting and Sorting Systems," Aug. 1995, pp. I-III, 1-31, and three pages of specifications.  
 Geldinstitute Literature, Scan Coin, Mar. 1990, 2 pages.  
 Hamilton, "Turning Cans into Cold Cash," The Washington Post, Jul. 2, 1991, pp. D1 and D4.  
 Kundenselbstbedienung, undated, 3 pages.  
 Leitch, C., "High-tech bank counts coin," Report on Business, The Globe and Mail, Sep. 18, 1991, 1 page.  
 Llemeon, J., "Royal's Burlington drive-in bank provides customers 24-hour tellers," The Toronto Star, Aug. 21, 1991, 1 page.  
 Oxby, M., "Royal Bank opens 'super branch'," The Gazette Montreal, Sep. 14, 1991, 1 page.  
 Reis Eurosystems Geldbearbeitungssysteme, "Test-Programme CS 3110 Selectronic coin sorting and counting machine", Jul. 1992, 5 pages.  
 Reis Eurosystems, "Operating Instructions CS 3110 Selectronic Coin Sorting and Counting Machine With Central Sensor", Jul. 1992, 10 pages.  
 Scan Coin CDS 640 Cash Deposit System Brochure, undated 2 pages.  
 Scan Coin CDS Cash Deposit System, undated, 2 pages.  
 Scan Coin correspondence regarding supermarkets, Sep. 11, 1992, 4 pages.  
 Scan Coin International Report Apr. 1987, 49 pages.  
 Scan Coin Money Processing Systems, Oct. 1, 1988, 10 pages.  
 Scan Coin Newsletter, May 1991, 2 pages.  
 Scan Coin Sales Invoices for Coin Counters in the United States, 1989-1993, 28 pages.  
 Scan Coin Technical Manual CDS MK 1 Coin Deposit System; 1991, 98 pages.  
 Scan Coin Technical Manual SC 102 Value Counter, undated, 28 pages.  
 Scan Coin, Technical Reference [sic] Manual, CDS, 1989, 47 pages (odd pages only).

Scan Coin World Newsletters, Scan Coin AB, Jagerfhillgatan 26, S-213 75 Malmo, Sweden, 1988-1990, 6 pages.  
 "Slide Changing Apparatus With Slide Jam Protection", Research Disclosure 30509, Sep. 1989.  
 Super Branch Literature, Feb. 1992, 2 pages.  
 Technical Specifications GBS9401 SB, undated, 24 pages.  
 User's Manual Scan Coin CDS 600, Dec. 12, 1990, 14 pages.  
 User's Manual Scan Coin CDS 640, 1988, 7 pages.  
 Technical Manual, Cash Deposit System, Model CDS 600 & CDS 640, 1991, 46 pages.  
 "Kundema fixer vaxein," Prektiska, 2 pages.  
 Svenska Penninglotteriet Documents, 1988, 70 pages.  
 Fri Kopenskap articles, Mar. 18, 1988, Apr. 27, 1989 and Nov. 25, 1988, 6 pages.  
 Priab Prisma article, 1989, 7 pages.  
 Scan Coin CDS Cash Deposit System, Brochure, Sep. 1988, 6 pages.  
 Scan Coin CDS Mini Cash Deposit System, Brochure, Undated, 2 pages.  
 Scan Coin 102 Value Counter, Brochure, Undated, 2 pages.  
 Scan Coin CDS 600 Cash Deposit System, Brochure, Undated, 2 pages.  
 SC4000 Coin Discriminating System, Including Perforated Vibrating Coin Feeding and Cleaning Tray Assembly, sold in the United States as early as Dec.1994 [includes 8 color copies].  
 Scan Coin 4000 Value Sorter Brochure, 1994, 5 pages.  
 Scan Coin 4000 Value Sorter, Operator's Instruction Manual, 2001.  
 SC 4000 Operating Instructions, SCT-OI-01-001, Aug. 10, 1994, 5 pages.  
 U.S. Appl. No. 10/353,575, filed Jan. 29, 2003, Masen et al.  
 U.S. Appl. No. 11/016,088, filed Dec. 17, 2004, Masen et al.  
 U.S. Appl. No. 11/371,310, filed Mar. 8, 2006, Knutsson et al.  
 U.S. Appl. No. 11/728,612, filed Mar. 26, 2007, Masen et al.  
 U.S. Appl. 90/008,677, filed Jun. 5, 2007, Re-Examination of Patent 6484884.  
 Facsimile from Claes Breitholtz of Scan Coin AB to Aaron Finch of Coinstar, Inc., apparently transmitted on Feb. 8, 1996, 4 pages.  
 Information Disclosure Statement received by the USPTO on Feb. 17, 2004 in U.S. Appl. No. 10/670,111.  
 Information Disclosure Statement received by the UPSTO on Dec. 18, 2006 in U.S. Appl. No. 10/670,111.  
 Scan Coin AB, "Scan Coin 4000 Value Sorter" and product photos, on sale in the U.S. prior to Sep. 2001.  
 Scan Coin 4000 Value Sorter, Operator's Instruction Manual, published before Sep. 2001.  
 SC4000 Coin Discriminating System, Including Perforated, Vibrating Coin Feeding and Cleaning Tray Assembly; On sale in the US by Scan Coin Since at least as early as Dec. 1994 (including photographs, drawings and parts lists).  
 Scan Coin 4000 Value Sorter Operator's Instruction Manual-1995.  
 Scan Coin SC4000 Operating Instructions, dated Aug. 10, 1994.  
 Scan Coin Technical Manual SC4000, dated Jul. 29, 1994.  
 U.S. Appl. No. 12/273,172, filed Nov. 18, 2008, Gerrity et al.  
 \* cited by examiner

1

**EX PARTE  
REEXAMINATION CERTIFICATE  
ISSUED UNDER 35 U.S.C. 307**

THE PATENT IS HEREBY AMENDED AS  
INDICATED BELOW.

AS A RESULT OF REEXAMINATION, IT HAS BEEN  
DETERMINED THAT:

2

The patentability of claims 32 and 33 is confirmed.

Claims 1-5, 8-14, 16-18, 20-22, 28, 29, 31, 35, 37-39 and  
41 are cancelled.

5 Claims 6, 7, 15, 19, 23-27, 30, 34, 36, 40 and 42-52 were  
not reexamined.

\* \* \* \* \*