



US006865532B2

(12) **United States Patent**
Anderson

(10) **Patent No.:** **US 6,865,532 B2**
(45) **Date of Patent:** **Mar. 8, 2005**

(54) **METHOD FOR RECOGNIZING SPOKEN IDENTIFIERS HAVING PREDEFINED GRAMMARS**

6,223,158 B1 * 4/2001 Goldberg 704/252
6,400,805 B1 * 6/2002 Brown et al. 379/88.01
6,430,557 B1 * 8/2002 Gaussier et al. 707/5
6,493,662 B1 * 12/2002 Gillam 704/9
6,532,446 B1 * 3/2003 King 704/270.1

(75) Inventor: **David B. Anderson**, Belmont, MA (US)

* cited by examiner

(73) Assignee: **Mitsubishi Electric Research Laboratories, Inc.**, Cambridge, MA (US)

Primary Examiner—Susan McFadden

Assistant Examiner—Huyen X. Vo

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 601 days.

(74) *Attorney, Agent, or Firm*—Dirk Brinkman; Andrew J. Curtin

(21) Appl. No.: **09/956,307**

(57) **ABSTRACT**

(22) Filed: **Sep. 19, 2001**

A method for selecting and recognizing spoken identifiers first defines a phrase having word slots. The word slots are arranged in the phrase in a predetermined order and according to a predetermined grammatical structure of a target language. A set of unique words selected from the target language is assigned to each word slot in the phrase according to the grammatical structure. Then, a unique identifiers can be generated by selecting one word from each set for each slot for each identifier such that a concatenating of the selected words in the predetermined order form the unique identifier.

(65) **Prior Publication Data**

US 2003/0061045 A1 Mar. 27, 2003

(51) **Int. Cl.**⁷ **G10L 15/18**

(52) **U.S. Cl.** **704/257**; 704/251; 704/252; 707/5; 379/88.01


(58) **Field of Search** 704/9, 252, 251, 704/209, 270.1; 707/5; 379/88.01

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,208,959 B1 * 3/2001 Jonsson et al. 704/209

8 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

**METHOD FOR RECOGNIZING SPOKEN
IDENTIFIERS HAVING PREDEFINED
GRAMMARS**

FIELD OF THE INVENTION

This invention relates generally to voice operated communication devices, and more particularly to recognizing spoken identifiers.

BACKGROUND OF THE INVENTION

A number of radio communication modes are known. Simple two-way radio communications primarily use a simplex synchronous channel. This means that a single channel (frequency) is used, and a user can either send (speak) or receive (hear), but not both at the same time. In either case, whether the user is acting as a sender or a receiver, the sending and receiving of the signal occurred substantially simultaneously at both ends of the channel. Hence the communication is said to be synchronous. Common embodiments of such two-way synchronous radios are typically operated by depressing the "talk" button on the microphone. Of course, if both users depress their talk buttons at the same, then neither user hears anything.

A more modern version of such a two-way radio uses a duplex synchronous channel. In this case, both users can send and receive at the same time, and each user hears the other user's words as they are spoken. The most common form of this type of radio is the ubiquitous cellular telephone.

A characteristic of synchronous communication devices is that both the transmitter and receiver must be connected to the channel for the entire time that the communications occur. This is a problem in heavily populated urban areas where the number of available channels is much smaller than the number of potential users. In addition, cellular telephones requires a large number of buttons, and a display. This makes it difficult and distracting to operate the device. In addition, many users may desire to receive communications only at times selected by them, not at the times selected by senders.

Another problem with voice operated devices is to correctly recognize numbers, such as spoken telephone numbers, especially in the case that the identifier is in the form of large sequence of numbers, such as a security code or an account code much may well run twenty digits long.

One-way asynchronous communications devices have been available in the form of pagers. Typically, such devices can only passively receive and display simple textual messages such as telephone numbers of calling numbers. In most cases, a service provider is required to connect the pagers to standard telephone networks.

U.S. Pat. No. 4,860,359 issued to Eicher on Aug. 22, 1989 "Method of voice operated transmit control," described a voice activated audio transmission system. There, an input signal was compared with an anti-VOX signal. As soon as a voice was detected, the voice signal was coupled for synchronous transmission.

U.S. Pat. No. 5,008,954 issued to Oppendahl on Apr. 16, 1991 "Voice-activated radio transceiver," described a voice-activated transceiver that provided audio tones through earphones of the transceiver to announce the transition to and from transmit mode. By listening for the tones, the user was continuously apprised of the status of the transceiver.

U.S. Pat. No. 5,042,063 issued Sakanishi, et al. on Aug. 20, 1991 "Telephone apparatus with voice activated dialing function," described a telephone in which a call could be placed by either dialing or speaking telephone numbers.

U.S. Pat. No. 5,584,052 issued to Gulau, et al. on Dec. 10, 1996 "Integrated microphone/pushbutton housing for voice activated cellular phone," described a voice controlled vehicle accessory system responsive to voice commands and manual commands. Manual commands were entered via a single pushbutton having multiple functions depending upon an instantaneous state of a system controller. Predetermined voice commands were entered via a microphone. The types of accessories that could be coupled to the controller included the car throttle, audio system, climate system, and a cellular telephone.

U.S. Pat. No. 6,010,216 issued to Jesiek on Jan. 4, 2000 "Hear speak' two-way voice radio communications eyeglasses," described a radio transceiver incorporated into eyeglasses. The transceiver included a voice activated switch to switch between receive and transmit mode.

U.S. Pat. No. 6,212,408 issued to Son, et al. on Apr. 3, 2001 "Voice command system and method," described a system that allowed a communication device to accept voice commands from a user. The voice commands included commands to execute or dial key sequences or commands to control device functionality. Voice commands were received from a user of the communication device, indicating a command to be carried out by said communication device. Manual entry could be requested by the user in response to button activity or by a spoken command.

U.S. Pat. No. 6,236,969 issued to Ruppert, et al. on May 22, 2001 "Wearable telecommunications apparatus with voice/speech control features," described a wearable communication apparatus in the form of a self-contained telephone headset. The headset could be activated by rotation of the mouthpiece into an operative position and deactivated by rotation out of that position. The base could be connected to a telephone network via a traditional landline, and communicate with the headset via an RF antenna. The headset included voice recognition capabilities that allowed the user to dial telephone numbers, access a memory of stored numbers, and direct certain headset functions simply by spoken commands.

Therefore, there is a need to provide two-way asynchronous data communications in a portable device that can be entirely controlled by spoken commands and identification phrases.

SUMMARY OF THE INVENTION

The invention provides a method for selecting and recognizing spoken identifiers first defines a phrase having word slots. The word slots are arranged in the phrase in a predetermined order and according to a predetermined grammatical structure of a target language. A set of unique words selected from the target language is assigned to each word slot in the phrase according to the grammatical structure. Then, a unique identifiers can be generated by selecting one word from each set for each slot for each identifier such that a concatenating of the selected words in the predetermined order form the unique identifier.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view of a two-way asynchronous radio according to the invention;

FIG. 2 is a block diagram of the radio of FIG. 1;

FIG. 3 is a flow diagram of transmitting audio messages by the radio of FIG. 1;

FIG. 4 is a flow diagram of receiving audio messages by the radio of FIG. 1;

FIG. 5 is a block diagram of a packet-switched network use with radios according to the invention; and

FIG. 6 is a graph of a probability lattice.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

System Components and Structure

External

As shown in FIG. 1, our two-way asynchronous radio **100** includes an antenna **101**, an indicator light, e.g., a LED **102**, a mechanical indicator (vibrator or ringer) **103**, a speaker **104**, an on/off switch **106** for a microphone **105**, and a volume control **107** all mounted on a housing **110**. The radio **100** can also include a multiple position select switch **109** to a select different modes of operation.

It should be noted, that the two-way radio according to the invention lacks the display and numerous buttons found in conventional two way communication devices such as cellular telephones.

Internal

As shown in FIG. 2, the housing **110** also contains a transmitter **201**, a receiver **202**, an output buffer **204**, a speech recognizer **205**, a speech synthesizer **206** all coupled to a controller **200**, and all operated by a battery supply **220**. The controller can be a microprocessor that maintains state **230** of the radio. The controller **200** also includes local memory **250** to store programs, and user supplied data, described in greater detail below. For example, the state can indicate whether a spoken command or message is expected as a next input acoustic signal. The radio can also be equipped with accelerometers (ACC) **208**.

System Operation

Transmitting

As shown in FIG. 3 for the operation of transmitting **300** output audio messages **302**, a user speaks into the microphone **104** while pressing the switch **106** to generate a first acoustic signal **310**. The user can supply either a voice command **301** or spoken message **302** by speaking into the microphone **105**. These are translated to acoustic signals by the microphone **104**. Acoustic signals are acquired and processed as long as the switch remains pressed. Releasing the switch terminates signal acquisition. The speech recognizer **205** and the state **230** determine whether the acoustic signal is a command or a message. If the signal is a command **301**, then a response **303** to the command is generated by the speech synthesizer **206**, and played on the speaker **104**.

Alternatively, responses can be given via the light or mechanical indicator **102–103**. If the radio is equipped with the accelerometer **108**, then the user can move the radio **100** according to predetermined patterns to signal alternative commands. For example, vertical movements can indicate accord, and horizontal movements can mean cancellation.

Otherwise, if acoustic signal **310** is not a command, then the message **302** is stored in the output buffer **203**, and the transmitter **201** sends the stored message as an output audio message **304** when a communications channel is available.

Receiving

As shown in FIG. 4 for the operation of receiving input audio messages **410**. The input messages **410** are received by the receiver **202** and stored in the input buffer **204** when the communications channel is available. When an input message is received and stored, the light or mechanical indicators **102–103** can be activated. In this case, as above, the user speaks into the microphone **104** while depressing the switch **106** to supply voice commands **401**, and an appropriate response is generated. The stored input message **410** is sent to the speaker **104** only if the command is a play command.

If the radio includes the select switch for different modes of operation, one mode may be “silent” mode where the light and mechanical indicators **102–103** are used for output signaling, and the accelerometers **208** is used for signaling commands, while the speaker plays messages at the lowest audible setting using the volume control **107**. Cancellation

can also be indicated by rapidly depressing the switch **106** a predetermined number of times.

Network

As shown in FIG. 5, messages can be transmitted and received over communications channels via basestations **501** or a satellite **502**. In a practical embodiment, many users of the two-way radios **100** according to the invention concurrently communicate with each other using appropriate two-way wireless data communications technology, such as CDPD, GSM, GPRS, ReFLEX, 802.11b, and the like. The basestations **501** (or satellites) are connected to servers **510** operated by communications service providers.

The servers **510** act as a gateway, relaying messages to and from the radios **100**, and storing messages until they can be received by the radios. The servers **510** are interconnected by a conventional wide area network **520**, including the packet-switched Internet so that the radios **100** can communicate with Internet compatible devices. For example, in FIG. 4, the input message **410** can be sent to a PC or appliance **420**.

Commands

Because the radio **100** is primarily voice operated, a number of commands can be defined as indicated below in Table A. The commands and definitions are self explanatory. The commands can be associated with modifiers, such as “first,” “next,” “new,” “previous,” “last.” Note, these are only exemplary, other commands and modifiers can also be used. The key requirements is that the individual commands are intuitive, accurate, understandable, and distinguishable by the voice recognizer.

TABLE A

Command	Definition
Call	Send a message
Play	Play selected message
Repeat	Repeat last command
Delete	Deleted selected message
Cancel	Cancel last command, and return to previous state
Detail	Provide details on selected message
Send	Send message to selected address
Status	Provided status on radio, battery, memory, etc.
Help	Provide help information according to current state

Device Identification and Message Addresses

The two-way asynchronous radio according to the invention can use the following identification scheme to address messages. Three types of identification spaces are defined, physical, logical, and name space.

Each radio has a unique physical identification that is “factory” assigned and unalterable. In practice, the useable physical identification space is very large, e.g., $>10^{10}$, or larger.

Associated with each physical identification is a user assigned logical identification. The logical identification is specified by a spoken phrase that includes a predetermined number of word “slots,” e.g., six slots. The words to fill the slots are selected from relatively small sets of unique words according to a vocabulary in a target language, e.g., there is a set of thirty-two word choices for each of the six slot in the phrase. Therefore, the number of different possible logical identifications is 32^6 . It should be understood, that larger identification spaces can be constructed by extending the size of the phrase or the size of the vocabulary, or both.

The user assigns the selected logical identification when the two-way radio is first used. At that time, the physical identification and logical identification can be stored in the memory **250** and transmitted to a common storage of a service provider for verification as to its uniqueness.

The order of the words in the phrase have a predetermined grammatical structure for the target language. For example, in the English language, the grammatical construction of the six words is:

5

number:adjective:noun:verb:preposition:proper-noun

Moreover, to make the words easier to remember and select in a particular language, they can be further constrained. For example, the nouns in example Table B below are animals, the adjectives colors, the verbs are past-tense and motion related, and the proper-nouns are cities.

TABLE B

1	one	yellow	dogs	ran	over	Boston
2	two	green	snakes	flew	under	Beijing
3	three	white	horse	swam	around	Chicago
4	four	black	pandas	drove	through	Tokyo
...

The selected words in the phrase can also be mapped to numeric identifiers, for example, the phrase “four green dogs flew through Boston,” translates to “4.2.1.2.4.1.” Therefore, on a universal basis, the same unique identifier can have different expressions of word orders and grammars in different target languages. Thus, it is possible, for the same physical identification, to have expressions as different logical identifications (spoken phrases) for users in different countries.

Each user can further associate a local name, e.g. “John,” with each logical identification. This logical-name association is stored in a “phone-book” in the memory **250** of the controller. Then, the recognition of the logical phrases is only needed occasionally, e.g., when entering a logical names into the phonebook. Of course, different users can assign different local names to the same logical identification.

With this identification and addressing, a message can simply be sent by the command “Call John” which will asynchronously send a message to the two-way radio with a physical identification associated with the logical identification “4.2.1.2.4.1.”

This identification scheme has a number of advantages over prior art numeric identifiers such as telephone numbers. First, the phrases are much simpler to remember while still providing a large number of possible identification numbers with a fairly small number of words in the phrase. Also, the phrase is more resistant to error, either by the user, or by the speech recognizer **205**. It is well known that spoken telephone numbers are difficult to interpret correctly.

For example, a probability lattice can be used to correct or validate the output of the speech recognizer **205**. To determine the probability that a particular acoustic signal represents a particular phrase the speech recognizer **205** can generate a probability lattice. The probability lattice for the phrase represents a determination of the probabilities for each possible state path for the sequence of words in the phrase. The probability lattice contains a node for each possible state that the speech recognizer **205** can be in for each word in the phrase. Each node contains the accumulated probability that the words processed so far will result in the recognizer being in the state associated with that node. The sum of the probabilities in the nodes for a particular phrase indicates the likelihood that the words processed so far represent a prefix portion of the phrase.

FIG. 6 illustrates a probability lattice **600** for a phrase. The vertical axis **601** corresponds to a concatenation of the states of the speech recognizer **205** for the words that compose the phrase. Node **610** represents a final state for the phrase and contains the maximum probability of all the state paths that lead to that node. The bolded lines of FIG. 6

6

represent the state path with the highest probability that ends at node **610**. In certain applications, it is helpful to identify a number of possible state paths in order of their probabilities. One well-known process for identifying such a state paths is the well Viterbi algorithm.

The output of the above probability analysis can be used in two ways. First, the most probably phrase can be mapped to its numeral equivalent, and a forward error correction techniques can be applied to correct any errors. Alternatively, the n most probably phrases can be further analyzed, and the phrase that is most self constant according to redundancy information encoded in the phrase is selected as the correct phrase.

This invention is described using specific terms and examples. It is to be understood that various other adaptations and modifications may be made within the spirit and scope of the invention. Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

I claim:

1. A method for selecting and recognizing spoken identifiers, comprising:

defining a phrase having a plurality of word slots, the plurality of word slots arranged in the phrase in a predetermined order and according to a predetermined grammatical structure of a target language;

associating a set of unique words with each word slot, the words in each set selected from the target language according to the grammatical structure;

generating a plurality of unique identifiers by selecting one word from each set for each word slot for each identifier such that a concatenating of the selected words in the predetermined order form the unique identifier.

2. The method of claim 1 wherein the words for each unique identifier are selected by an associated user, and further comprising:

verifying the unique identifiers using a common storage device.

3. The method of claim 1 wherein each unique identifier is a logical identifier, and further comprising:

associating each logical identifier with a physical identifier.

4. The method of claim 1 wherein a plurality of target languages are associated with the phrase, each target language having associated sets of words and grammatical structure different than all other target languages.

5. The method of claim 4 wherein a particular unique identifier is a different concatenation of different words in each target language.

6. The method of claim 5 wherein each different concatenation of different words for the particular unique identifier maps to a single numeric identifier.

7. The method of claim 1 further comprising:

recognizing a particular unique identifier with a speech recognizer.

8. The method of claim 7 further comprising:

applying forward error correction to the recognized unique identifier.

* * * * *