



US006879680B2

(12) **United States Patent**
Donovan et al.

(10) **Patent No.:** **US 6,879,680 B2**
(45) **Date of Patent:** ***Apr. 12, 2005**

(54) **METHOD OF AND SYSTEM FOR
EXTENDING INTERNET TELEPHONY
OVER VIRTUAL PRIVATE NETWORK
DIRECT ACCESS LINES**

(75) Inventors: **Steven R. Donovan**, Plano, TX (US);
Matthew J. Cannon, Dallas, TX (US)

(73) Assignee: **MC, Inc.**, Ashburn, VA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **10/045,880**

(22) Filed: **Jan. 11, 2002**

(65) **Prior Publication Data**

US 2002/0057786 A1 May 16, 2002

Related U.S. Application Data

(63) Continuation of application No. 09/364,536, filed on Jul. 29,
1999, now Pat. No. 6,453,034.

(51) **Int. Cl.**⁷ **H04M 7/00**; H04L 12/66

(52) **U.S. Cl.** **379/220.01**; 370/356; 370/401;
370/410; 370/466; 370/467; 379/230; 379/231;
379/234; 379/900; 379/901

(58) **Field of Search** 370/352, 354,
370/356, 389, 392, 401, 410, 466, 467;
379/90.01, 93.07, 219, 220.01, 221.15,
230, 231, 232, 233, 234, 900, 901

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,303,286 A 4/1994 Wiedeman
5,434,907 A 7/1995 Hurst et al.
5,634,012 A 5/1997 Logston et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0794650 9/1997 H04M/3/50
EP 0123456 1/2000
WO 97/16007 5/1997 H04L/12/66
WO WO97/22209 6/1997
WO 97/22210 6/1997 H04Q/3/00
WO WO97/22209 2/1999

OTHER PUBLICATIONS

H. Schulzrinne, A Comprehensive Multimedia Control
Architecture for the Internet, 1997 IEEE, pp. 65–76.
Rosenberg et al. Internet Telephony Gateway Location,
1998 IEEE, pp. 488–496.
Schulzrinne et al. Signaling for Internet Telephony, IEEE,
Sep. 1998, pp. 298–307.
Wedlund et al. Mobility Support Using SIP, 1999 Associa-
tion for Computing Machinery, pp. 76–82.
Handley et al., “SIP: Session Initiation Protocol”, Network
Working Group, Request for Comments 2543, Mar. 1999,
pp. 1–104.
Camarillo et al., “The SDP Fid Attribute”, Internet Engi-
neering Task Force, Internet Draft, Apr. 2001, pp. 1–4.
Rosenberg, “SIP: Past, Present and Future”, May 10, 2000.
Cable Television Laboratories, Inc., “PacketCable CMS to
CMS Signaling Specification”, Nov. 28, 2000.


(Continued)

Primary Examiner—Harry S. Hong

(57) **ABSTRACT**

A virtual private network includes an internet protocol (IP)
network and a public switched telephone network (PSTN).
An enterprise gateway is operably connected to the IP
network. The enterprise gateway is operably connected to a
switch of the PSTN through a direct access line (DAL). The
set-up signaling for virtual private network calls and the
calls themselves are transported across the internet protocol
network and the public switched telephone network through
the direct access line.

41 Claims, 2 Drawing Sheets



U.S. PATENT DOCUMENTS


5,664,009 A 9/1997 Hurst et al.
 5,680,116 A 10/1997 Hashimoto et al.
 5,699,359 A 12/1997 Suga
 5,732,219 A 3/1998 Blumer et al.
 5,742,763 A 4/1998 Jones
 5,745,556 A 4/1998 Ronen
 5,794,039 A 8/1998 Guck
 5,802,510 A 9/1998 Jones
 5,826,039 A 10/1998 Jones
 5,832,221 A 11/1998 Jones
 5,859,898 A 1/1999 Checco
 5,864,610 A 1/1999 Ronen
 5,867,494 A 2/1999 Krishnaswamy et al.
 5,867,495 A 2/1999 Elliott et al.
 5,883,894 A 3/1999 Patel et al.
 5,889,774 A 3/1999 Mirashrafi et al.
 5,907,547 A 5/1999 Foladtre et al.
 5,913,176 A * 6/1999 Barabash 455/560
 5,923,659 A 7/1999 Curry et al.
 5,930,348 A 7/1999 Légnier et al.
 5,951,638 A 9/1999 Hoss et al.
 5,953,504 A 9/1999 Sokal et al.
 5,956,391 A 9/1999 Melen et al.
 5,958,005 A 9/1999 Thorne et al.
 5,960,416 A 9/1999 Block
 5,999,525 A 12/1999 Krishnaswamy et al.
 6,064,653 A 5/2000 Farris et al.
 6,069,890 A 5/2000 White et al.
 6,073,160 A 6/2000 Grantham et al.
 6,078,583 A 6/2000 Takahara et al.
 6,081,518 A 6/2000 Bowman-Amuah
 6,084,952 A 7/2000 Beerman, Jr. et al.
 6,094,525 A 7/2000 Perleman et al.
 6,118,864 A 9/2000 Chang et al.
 6,134,235 A 10/2000 Goldman et al. 370/352
 6,137,869 A 10/2000 Voit et al.
 6,144,667 A 11/2000 Doshi et al.
 6,147,975 A 11/2000 Bowman-Amuah
 6,151,390 A 11/2000 Volftsun et al. 379/229
 6,151,629 A 11/2000 Trewitt
 6,157,648 A 12/2000 Voit et al.
 6,161,008 A 12/2000 Lee et al.
 6,163,536 A 12/2000 Dunn et al. 370/352
 6,167,042 A 12/2000 Garland et al.
 6,178,181 B1 1/2001 Gritho
 6,188,760 B1 2/2001 Oran et al.
 6,195,697 B1 2/2001 Bowman-Amuah
 6,201,858 B1 3/2001 Sundhar
 6,202,081 B1 3/2001 Naudus
 6,215,858 B1 4/2001 Bartholomew et al.
 6,226,289 B1 5/2001 Williams et al.
 6,233,318 B1 5/2001 Picard et al.
 6,240,391 B1 5/2001 Ball et al.
 6,253,249 B1 6/2001 Belzile
 6,282,270 B1 8/2001 Porter
 6,292,479 B1 9/2001 Bartholomew et al.
 6,301,609 B1 10/2001 Aravamudan et al.
 6,333,931 B1 12/2001 LaPier et al. 370/385
 6,335,927 B1 1/2002 Elliott et al.

6,335,968 B1 1/2002 Malik
 6,339,594 B1 1/2002 Civanlar et al. 370/352
 6,381,316 B2 4/2002 Joyce et al. 379/114.2
 6,411,705 B2 6/2002 Oran et al. 379/230
 6,453,034 B1 * 9/2002 Donovan et al. 370/356
 6,463,053 B1 10/2002 Chen 370/352
 6,507,647 B1 1/2003 Mandalia 379/219
 6,515,997 B1 2/2003 Feltner et al. 370/401
 6,519,242 B1 2/2003 Emery et al. 370/338
 6,529,499 B1 3/2003 Doshi et al. 370/352
 6,567,399 B1 5/2003 Schuster et al. 370/352
 6,570,869 B1 * 5/2003 Shankar et al. 370/352
 6,633,571 B1 * 10/2003 Sakamoto et al. 370/401

OTHER PUBLICATIONS

Marshall et al., "SIP Proxy-to-Proxy Extensions for Supporting DCS" SIP Working Group Internet Draft, Nov. 2000, pp. 1-24.
 Woods, D., "Translating Menus at the VOIP Café", Dec. 27, 1999, pp. 1-4.
 Cisco Systems, Inc., "Architecture for Voice", Video and Integrated Data, 2000, pp. 1-23.
 Schulzrinne, H., "The Session Initiation Protocol (SIP)", Sep. 28, 2000.
 Schulzrinne, H., Internet Telephony and Multimedia, Status and Directions, Aug. 7, 2000.
 Schulzrinne et al., "The Session Initiation Protocol: Internet-Centric Signalling", IEEE Communications Magazine, Oct. 2000, pp 134-141.
 Dalgic et al., "True Number Portability and Advanced Call Screening in a SIP-Based IP Telephony System", IEEE Communications Magazine, Jul. 1999, pp. 96-101.
 Zimmerer, Eric, "SIP+ (Inter MGC Protocol); Edition 0.0", Level 3 Communications, Dec. 4, 1998, paragraph 0002, 02.1, 02.4 and Figure 4, cs.columbia.edu/sip/drafts/SIP+01.doc.
 Donovan, S., "The SIP Info Method", Internet Engineering Task Force, Feb. 8, 1999, the whole document.
 Sijben, P. et al., "Toward the PSTN/Internet Inter-Networking; Media Device Control Protocol", Internet Engineering Task Force, Version .03, Feb. 9, 1999, paragraph 10.1 and 11.4.
 Schulzrinne et al., "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals", Internet Engineering Task Force, Jun. 9, 1999, paragraph 0001, openphone.org/docs/dtmf/tones.pdf.
 Schulzrinne, H. et al., "Signaling for Internet Telephony", IEEE, Oct. 13, 1998, pp. 298-307.
 Rosenberg et al., "Programming Internet Telephony Services", IEEE Network, IEEE Inc., New York, US, vol. 13, No. 1, May 1999, pp. 42-49.
 Lennox et al., "Transporting User Control Information in SIP Register Payloads", Internet Engineering Task Force, Feb. 23, 1999, pp. 1-9.

* cited by examiner



(Prior Art)

FIG. 1




FIG. 2




FIG. 3

**METHOD OF AND SYSTEM FOR
EXTENDING INTERNET TELEPHONY
OVER VIRTUAL PRIVATE NETWORK
DIRECT ACCESS LINES**

CROSS REFERENCE TO RELATED PATENTS

This application is a Continuation of Ser. No. 09/364,536, U.S. Pat. No. 6,453,034 B1, filed Jul. 29, 1999, entitled "METHOD OF AND SYSTEM FOR EXTENDING INTERNET TELEPHONY OVER VIRTUAL PRIVATE NETWORK DIRECT ACCESS LINES."

BACKGROUND

The present invention relates generally to the field of virtual private networks, and more particularly to a method of and system for providing a virtual private network in which a portion of each call is transported through an internet protocol network.

DESCRIPTION OF THE PRIOR ART

Some larger organizations with far-flung sites and locations use virtual private networks (VPNs) as an alternative to traditional long distance services for their intra-organizational telephone communications. Virtual private networks are created within the public switched telephone system but they provide a communication system that appears from the users prospective to be private.

Referring to FIG. 1, there is shown a simplified block diagram of a virtual private network. An intra-location telephone system includes a plurality of telephones 11 operably connected to a private branch exchange (PBX) 13. As is well known to those skilled in the art, several or even hundreds of telephones may be operably connected to PBX 13.

PBX 13 provides intra-site communication between telephone and other telephones at the site. Additionally, a user of a telephone 11 may make a local or long distance call outside of the location by entering a digit, such as "9", to obtain an outside line. Additionally, a user of telephone 11 may make a VPN call by entering another digit, such as "8", to reach a member of the organization at another location. The other location may be in a separate city, state, or even country. Typically, VPN numbers have the appearance of local seven digit telephone numbers. A three digit prefix number identifies a location and the remaining four digits identify a telephone within the location.

In the example of FIG. 1, a user of telephone 11 at a location located in, for example, California, wishes to place a VPN call to a telephone 15 located at a site of the organization in, for example, New York. The telephones 15 of the site in New York are operably connected to a PBX 17 that services the site. For purposes of illustration, the VPN number associated with telephone 15 is 555-1234. To initiate the call, a user takes telephone 11 off hook and receives a dial tone from PBX 13. The user enters "8" to identify the call as a VPN call and receives another dial tone. Then, the user enters the digits 555-1234. PBX 13 forwards the call to a switch 19 of a public switched telephone network (PSTN) 21 over a direct access line (DAL 23). Switch 19 is identified in PSTN 21 by a unique originating switch identifier (OSID). DAL 23 is identified by an originating trunk group (OTG) identifier. When switch 19 receives the dialed digits on the DAL 23, it must consult a service control point (SCP) 25 for routing instructions. SCP 25 uses the OSID and the OTG to determine the identity of the VPN customer and

provides routing instructions to switch 19 based on the customer identification and the dialed digits. Switch 19 routes the call through PSTN 21 to an appropriate terminating switch 27. Switch 27 is operably connected to PBX 17 to complete the call to telephone 15.

One of the problems with VPN service is that the public switched telephone network does not extend reliably to all parts of the world. Because of the unreliability of the PSTN in certain parts of the world, certain locations of organizations particularly, those located in developing nations, are unable to use VPN services.

Recently, organizations have begun to build and use packet switched data networks, such as private intranets and the Internet itself, for mission critical communications. Even in regions without reliable access to the public switched telephone system, organizations have built or have gained access to robust high speed data networks for the transfer of data and electronic communications, such as e-mail, between locations.

It is an object of the present invention to provide a system that extends VPN services through data networks, such as private intranets and the Internet.

SUMMARY

The present invention provides a virtual private network (VPN) that includes an internet protocol (IP) network and a public switched telephone network (PSTN). An egress enterprise gateway is operably connected to the IP network. The egress enterprise gateway is operably connected to a switch of the PSTN through a direct access line (DAL). The set-up signaling for virtual private network calls and the calls themselves are transported across the IP network and the PSTN through the DAL. An intelligent layer in the IP network has the ability to route IP network originated calls to a traditional PSTN DAL.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a virtual private network of the prior art.

FIG. 2 is a block diagram illustrating a virtual private network according to the present invention.

FIG. 3 is a block diagram illustrating the operation of enterprise gateways according to the present invention.

DETAILED DESCRIPTION

Referring now to FIG. 2, a VPN according to the present invention is designated generally by the numeral 31. A portion of VPN 31 is implemented in a traditional PSTN environment. The PSTN part of network 31 includes a switch 33 that is served by a SCP 35. Switch 33 is operably connected to a PSTN 37, which in turn is operably connected to a switch 39. Switch 39 is operably connected to a PBX 41 at a location of an organization through a DAL 45. PBX 41 is operably connected to a plurality of telephones, even though only one is shown as telephone 43.

According to the present invention, a portion of VPN 31 is also implemented in an IP network environment. The IP network environment of VPN 31 includes an IP network, which is generally designated by the numeral 47. IP network 47 may comprise a private intranet, the Internet, or a combination of a private intranet and the Internet. IP network 47 provides traditional Internet and web-based services, as well as IP telephony services.

A local organization's telephone system includes a PBX 51 and a plurality of telephones, even though only one is

shown as telephone **53**. Telephone **53** operates in the normal way. A user can use telephone **53** to call other telephone extensions within PBX **51**. PBX **51** can also provide a telephone **53** with an outside line on which the user of telephone **53** can make local and long distance calls.

According to the present invention, a user can use telephone **53** and PBX **51** to make VPN calls. PBX **51** is operably connected to an ingress enterprise gateway (EG) **55**. Although gateway **55** is labeled as an "ingress" EG, it is a bidirectional EG and the label "ingress" is only for identification relative to the call flow from telephone **53** to telephone **43**. Referring to FIG. 3, EG **55** includes a signaling gateway **57** and a media gateway **59**. Signaling gateway **57** provides bi-directional protocol translation from a telephony signaling protocol, such as SS7, ISDN, or channel associated signaling (CAS), depending upon the signaling protocol used by PBX **51**, to an Internet telephony signaling protocol, such as session initiation protocol (SIP) or H.323. The preferred embodiment of the present invention is based upon the SIP signaling protocol. However, other embodiments are contemplated based on other protocol, such as H.323. Media gateway **59** provides bi-directional protocol translation between traditional telephony time division multiplexed voice circuits to an IP transport protocol such as real-time transport protocol (RTP). In the case of ISDN or SS7 signaling, signaling gateway **57** is connected to PBX **51** by a signaling link, which is either an SS7 signaling link or an ISDN D-channel. In the case of CAS signaling, signaling gateway **57** receives signaling information from media gateway **59**.

SIP and RTP packets are transported across IP network **47** to an egress enterprise gateway EG **61**. Although gateway **55** is labeled as an "ingress" EG, it is a bidirectional EG and the label "ingress" is only for identification relative to the call flow from telephone **53** to telephone **43**. EG **61** includes a signaling gateway **63** and a media gateway **65**. Signaling gateway **63** and media gateway **65** perform bidirectional protocol translations in the manner described with respect to signaling gateway **57** and media gateway **59**, respectively. Referring again to FIG. 2, EG **61** is connected to switch **33** of PSTN **27** by DAL **23**.

Referring again to FIG. 2, a VPN call can be placed from telephone **53**, located for example in Malaysia, to a telephone **43**, located for example in New York. A user takes telephone **53** off hook and dials a VPN number in the normal way. For example, the user dials 8-777-4321. PBX **51** sends a normal set up message with the dialed digits 777-4321 to EG **55**. EG **55** performs a protocol translation and formulates a SIP invite message of the form:

```
INVITE:7774321@xyzus.com
FROM:5551234@xyzmalaysia.com
TO:7774321@xyzus.com
```

In the preferred embodiment, SIP URLs are of the form "telephone_number@gateway." Thus, EG **55** is identified as xyzmalaysia.com and EG **61** is identified at xyzus.com. The SIP invite message is transported across IP network **47** to EG **61**. EG **61** performs a protocol translation and sends set up message for VPN number 777-4321 to switch **33** over DAL **23**. Switch **33** recognizes the call as a VPN call and consults SCP **35** for routing instructions. SCP **35** uses the dialed digits, the OSID of switch **33**, and the OTG of DAL **23** to provide routing instructions to switch **33**. Based upon the instructions received from SCP **35**, the call is set up across PSTN **37** to telephone **43** using normal telephony signaling. During call setup, egress enterprise gateway **61** passes IP telephony signaling through IP network **47** back to ingress enterprise gateway **55**.

The system of the present invention also provides VPN services initiated from telephones **43** served by PSTN **37** to

telephones **53** served by IP network **47**. A user takes telephone **43** off hook and dials a VPN number, for example, the user dials 8-555-1234. PBX **51** sends a set up message with the dialed digits 555-1234 to switch **39** over DAL **45**. Switch **39** recognizes the call as a VPN call and consults a SCP **63** for routing instructions. SCP **63** uses the dialed digits, the OSID of switch **39**, and the OTG of DAL **45** to provide routing instructions to switch **39**.

Based upon the instructions received from SCP **63**, switch **39** sends an SS7 initial address message (IAM) to **33**. Switch **33** sends a setup message to EG **61**. EG **61** performs a protocol translation and formulates a SIP invite message of the form:

```
INVITE:5551234@xyzmalaysia.com
FROM:7774321@xyzus.com
TO:5551234@xyzmalaysia.com
```

The SIP invite message is transported across IP network **47** to egress enterprise gateway **55**. EG **55** performs a protocol translation and sends set up message for VPN number 555-1234 to PBX **51**.

From the foregoing, it may be seen that the present invention uses IP telephony to extend the architecture and infrastructure of virtual private networks to areas with unreliable access to the PSTN. A portion of the call is setup and transported across an IP network using a layer of intelligence that routes the call and its signaling to an appropriate enterprise gateway. A portion of the call is setup and transported across the PSTN using traditional VPN infrastructure. Additionally, the present invention may be used to provide virtual private network services to Internet devices and appliances, such as IP phones **65** and IP telephony enabled personal computers **67**.

The present invention has been illustrated and described with respect to a presently preferred embodiment. Those skilled in the art will recognize alternative embodiments given the benefit of the foregoing disclosure. Accordingly, the foregoing disclosure is for purposes of illustration and not of limitation.

Thus, having fully described the present invention by way of example with reference to attached drawings figures, it will be readily appreciated that many changes and modifications may be made to the invention and to any of the exemplary embodiments shown and/or described herein without departing from the spirit or scope of the invention, which is defined in the appended claims.

What is claimed is:

1. An apparatus for providing virtual private network services, comprising:

an enterprise gateway configured to translate between virtual private network internet telephony signal protocol signals and virtual private network telephony signaling protocol signals between virtual private network internet protocol transport signals and virtual private network telephony time division multiplexed signals;

a direct access line operably connected to the enterprise gateway; and

a switch of a public switched telephone network operably connected to the direct access line.

2. The apparatus of claim 1, wherein the enterprise gateway includes a packet switched network interface.

3. The apparatus of claim 1, wherein the enterprise gateway comprises:

a signaling gateway; and

a media gateway.

4. The apparatus of claim 3, wherein the signaling gateway comprises means for converting internet protocol call set-up messages to telephone call set-up messages.

5

5. The apparatus of claim 3, wherein the signaling gateway comprises means for converting internet session initiation protocol messages to telephone call set-up messages.

6. The apparatus of claim 1, comprising:

a second enterprise gateway operably connected to an internet protocol network; and

an originating private branch exchange operably connected to the second enterprise gateway.

7. The apparatus of claim 6, wherein the second enterprise gateway comprises:

a signaling gateway; and

a media gateway.

8. The apparatus of claim 7, wherein the signaling gateway of the second enterprise gateway comprises means for converting telephone call set-up messages to internet protocol call set-up messages.

9. The apparatus of claim 7, wherein the signaling gateway of the second enterprise gateway comprises means for converting telephone call set-up messages to internet session initiation protocol messages.

10. The apparatus of claim 1, comprising:

a terminating private branch exchange operably connected to the public switched telephone network.

11. A virtual private network apparatus for providing virtual private network services between a public switched telephone network and an internet protocol network, comprising:

a signaling gateway configured to receive telephony signaling protocol signals, the telephony signaling protocol signals providing call signaling for a virtual private network call initiated by a caller, the signaling gateway being configured to convert the telephony signaling protocol signals to internet telephony signaling protocol signals, the signaling gateway being further configured to receive internet telephony signaling protocol signals and convert the received internet telephony signaling protocol signals to telephony signaling protocol signals; and

a media gateway coupled to the signaling gateway, the media gateway configured to translate between telephony time division multiplexed signals and internet protocol transport signals.

12. The apparatus of claim 11, wherein the telephony signaling protocol signals are signaling system 7 signals.

13. The apparatus of claim 11, wherein the telephony signaling protocol signals are ISDN signals.

14. The apparatus of claim 11, wherein the telephony signaling protocol signals are channel associated signaling signals.

15. The apparatus of claim 11, wherein the internet telephony signaling protocol signals are session initiation protocol signals.

16. The apparatus of claim 11, wherein the internet telephony signaling protocol signals are H.323 signals.

17. The apparatus of claim 11, wherein the internet protocol transport signals are real-time transport protocol signals.

18. The apparatus of claim 11, wherein the signaling gateway comprises means for converting internet protocol call set-up messages to telephone call set-up messages.

19. The apparatus of claim 11, wherein the signaling gateway comprises means for converting internet session initiation protocol messages to telephone call set-up messages.

20. The apparatus of claim 11, wherein the signaling gateway is also configured to convert telephone call set-up messages to internet protocol call set-up messages.

21. The apparatus of claim 11, wherein the signaling gateway is also configured to convert telephone call set-up messages to internet session initiation protocol messages.

6

22. A virtual private network apparatus for providing virtual private network services between a public switched telephone network and an internet protocol (IP) network, comprising:

a signaling gateway configured to receive internet telephony signal protocol signals, the internet telephony signal protocol signals providing call signaling for a virtual private network call initiated by a caller, the signaling gateway being configured to convert the internet telephony signal protocol signals to telephony signaling protocol signals; and

a media gateway coupled to the signaling gateway, the media gateway being configured to translate between internet protocol transport signals and telephony time division multiplexed signals.

23. The apparatus of claim 22, wherein the telephony signaling protocol signals are signaling system 7 signals.

24. The apparatus of claim 22, wherein the telephony signaling protocol signals are ISDN signals.

25. The apparatus of claim 22, wherein the telephony signaling protocol signals are channel associated signaling signals.

26. The apparatus of claim 22, wherein the internet telephony signaling protocol signals are session initiation protocol signals.

27. The apparatus of claim 22, wherein the internet telephony signaling protocol signals are H.323 signals.

28. The apparatus of claim 22, wherein the internet protocol transport signals are real-time transport protocol signals.

29. The apparatus of claim 22, wherein the signaling gateway comprises means for converting internet protocol call set-up messages to telephone call set-up messages.

30. The apparatus of claim 22, wherein the signaling gateway comprises means for converting internet session initiation protocol messages to telephone call set-up messages.

31. The apparatus of claim 22, wherein the signaling gateway is also configured to convert telephone call set-up messages to internet protocol call set-up messages.

32. The apparatus of claim 22, wherein the signaling gateway is also configured to convert telephone call set-up messages to internet session initiation protocol messages.

33. A method for providing virtual private network (VPN) services in a virtual private network that includes a public switched telephone network (PSTN) and an Internet Protocol (IP) network, the method comprising:

receiving a first call setup message from a first device for establishing a VPN call to a second device, the first call setup message including a VPN number;

translating the first call setup message to an IP protocol message, the IP protocol message including the VPN number;

transmitting the IP protocol message across the IP network;

translating the IP protocol message to a second call setup message, the second call setup message including the VPN number; and

establishing the VPN call with the second device through the PSTN using the second call setup message.

34. The method of claim 33, wherein the first call setup message is received from a private branch exchange.

35. The method of claim 33, wherein the IP protocol message includes a session initiation protocol (SIP) invite message.

36. The method of claim 33, wherein the establishing the VPN call includes:

transmitting the second call setup message to a switch associated with the PSTN via a direct access line.

7

37. The method of claim **36**, wherein the establishing the VPN call further includes:

obtaining routing instructions based on the VPN number, an identifier associated with the switch, and an identifier of the direct access line.

38. A method for providing virtual private network (VPN) services in a virtual private network that includes a public switched telephone network (PSTN) and an Internet Protocol (IP) network, the method comprising:

receiving a first call setup message from a first device for establishing a VPN call to a second device, the first call setup message being received from the PSTN and including a VPN number;

translating the first call setup message to an IP protocol message, the IP protocol message including the VPN number;

transmitting the IP protocol message across the IP network;

8

translating the IP protocol message to a second call setup message, the second call setup message including the VPN number; and

establishing the VPN call with the second device using the second call setup message.

39. The method of claim **38** wherein the first call setup message is received from a switch associated with the PSTN via a direct access line.

40. The method of claim **38** wherein the IP protocol message includes a session initiation protocol (SIP) invite message.

41. The method of claim **38** wherein the establishing the VPN call includes:

transmitting the second call setup message to a private branch exchange associated with the second device.

* * * * *