



US006880559B2

(12) **United States Patent**
Dombek

(10) **Patent No.:** **US 6,880,559 B2**
(45) **Date of Patent:** **Apr. 19, 2005**

(54) **METHOD OF AND APPARATUS FOR MAKING PERFORATIONS IN THE WRAPPERS OF ROD-SHAPED PRODUCTS**

5,135,008 A 8/1992 Oesterling et al.
5,148,818 A 9/1992 Arthur

FOREIGN PATENT DOCUMENTS

(75) Inventor: **Manfred Dombek**, Dassendorf (DE)

DE 27 51 522 C2 8/1978

(73) Assignee: **Hauni Maschinenbau Aktiengesellschaft**, Hamburg (DE)

DE 33 10 930 C2 10/1983

DE 34 31 051 C2 3/1985

DE 34 31 067 C2 3/1985

DE 42 18 266 A1 12/1993

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 245 days.

DE 198 56 413 6/2000

EP 0 659 354 A1 6/1995

EP 0 672 356 A1 9/1995

OTHER PUBLICATIONS

(21) Appl. No.: **10/291,841**

(22) Filed: **Nov. 12, 2002**

(65) **Prior Publication Data**

US 2003/0075190 A1 Apr. 24, 2003

Related U.S. Application Data

(62) Division of application No. 09/603,623, filed on Jun. 26, 2000, now Pat. No. 6,532,966.

(30) **Foreign Application Priority Data**

Jul. 2, 1999 (DE) 199 30 330

(51) **Int. Cl.**⁷ **A24C 1/38**

(52) **U.S. Cl.** **131/281; 131/280**

(58) **Field of Search** **131/281, 280**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,265,254 A 5/1981 Koch et al.
4,281,670 A 8/1981 Heitmann et al.
4,665,930 A 5/1987 Arthur et al.

“Training A Laser Beam And Pacing Lead With A Deflectable Tip”, Research Disclosure, Mar. 1997, vol. 187:39546–39547.


Primary Examiner—Dionne A. Walls

(74) *Attorney, Agent, or Firm*—Venable LLP; Robert Kinberg

(57) **ABSTRACT**

An method for increasing the permeability of tubular wrappers of a succession of cigarettes by at least one pulsed beam of coherent radiation issuing from a laser has a hollow drum-shaped conveyor cooperating with a rolling member to define an arcuate channel wherein successive cigarettes roll while advancing sideways past a perforating station. Each beam of coherent radiation is generated in or is caused to enter the interior of the conveyor prior to being influenced by one or more deflecting and/or focussing elements to be propagated substantially radially and through an opening of the hollow conveyor and to impinge upon the wrapper of a cigarette rolling at the perforating station.

5 Claims, 2 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4

**METHOD OF AND APPARATUS FOR
MAKING PERFORATIONS IN THE
WRAPPERS OF ROD-SHAPED PRODUCTS**

CROSS-REFERENCE TO RELATED CASES

This application is a divisional application of application Ser. No. 09/603,623, filed Jun. 26, 2000, now U.S. Pat. No. 6,532,966 and claims the priority of commonly owned German patent application Serial No. 199 30 330.4, filed Jul. 2, 1999. The disclosure of the above-referenced German patent application, as well as that of each U.S. and foreign patent and patent application mentioned in the specification of the present application, is incorporated herein by reference.

BACKGROUND OF THE INVENTION

The invention relates to improvements in apparatus for and in methods of increasing the permeability of wrapping material for rod-shaped products, especially rod-shaped smokers' products, and more particularly to improvements in methods of and apparatus for perforating tubular envelopes or wrappers of cigarettes or the like.

It is well known to enhance: the permeability of cigarette paper or other wrapping material for rod-shaped tobacco fillers and/or rod-shaped filters for tobacco smoke prior as well as subsequent to the conversion of a running web of wrapping material into a tubular envelope forming part of a continuous tobacco-containing rod; the leader of such rod is thereupon severed at regular intervals to yield a succession of discrete cigarettes, cigars, cigarillos or other rod-shaped smokers' products. It is equally known to enhance the permeability of selected portions of tubular envelopes forming part of discrete plain or filter cigarettes or analogous rod-shaped smokers' products while the products rotate about their own axes.

As a rule, a modem apparatus for enhancing the permeability of selected portions of a running web or of selected portions of tubular wrappers of successive rod-shaped smokers' products (hereinafter called cigarettes for short) comprises at least one source of high-energy radiation (such as a laser beam) and means for directing the beam or beams into one or more selected portions of the path for a running web of wrapping material or of the path for successive plain or filter cigarettes. If the apparatus is designed to perforate the finished (tubular) wrappers of plain or filter cigarettes, the cigarettes are caused to roll about their own longitudinal axes while moving sideways past the perforating station. The purpose of the perforating treatment is to ensure that the permeability of the tubular wrappers rises to a value at which an optimum quantity of atmospheric air is caused to enter the column of tobacco smoke flowing from the lighted end of a cigarette toward the mouth of the smoker. Cool atmospheric air is believed to exert a beneficial influence upon the nicotine and/or condensate contents of tobacco smoke.

U.S. Pat. No. 5,148,818 discloses a perforating apparatus which employs a source of coherent radiation (hereinafter called laser). The means for rolling successive cigarettes about their respective axes during advancement past the perforating station employs two coaxial drum-shaped conveyors and an endless flexible band. The path for the cigarettes is flanked by the band on the one hand, and by the conveyors on the other hand. The speed of the belt departs from the peripheral speeds of the conveyors, and this causes the cigarettes to roll about their respective axes. The laser is installed midway between the two rotary conveyors, and the beam of coherent radiation issuing from the laser is caused

to circulate while impinging upon a tubular wrapper at a selected frequency to thus provide the wrapper with an array of perforations.

Published German patent application Serial No. 33 10 930 discloses a perforating apparatus wherein the peripheral surface of a rotary drum-shaped conveyor transports a series of cigarettes sideways past a station where the wrappers of the cigarettes are acted upon by a laser beam. The laser is confined in and is caused to move relative to a complex heart-shaped reflector. Such apparatus are complex, bulky and unreliable.

Another perforating apparatus is disclosed in published German patent application Serial No. 34 31 051 which proposes a different combination of a mobile laser and a directing system for the laser beam. The directing system employs a complex array of mirrors and rotary reflectors which are intended to focus a laser beam upon successive cigarettes while the cigarettes rotate about their respective axes and are simultaneously advanced sideways by a rotary conveyor toward, past and beyond the perforating station.

Published German patent application Serial No. 34 31 067 discloses an apparatus which combines the features of the apparatus disclosed in the aforesaid published German patent applications Serial Nos. 33 10 930 and 34 31 051.

Published German patent application Serial No. 42 18 266 discloses a perforating apparatus wherein the cigarettes are transported and rolled by a set of drum shaped conveyors one of the conveyors carries a polygonal mirror which serves to direct a laser beam into the path for the cigarettes.

A further perforating apparatus is disclosed in published German patent application Serial No. 27 51 522. This publication proposes to roll successive cigarettes between the peripheral surface of a rotary drum-shaped conveyor and the complementary concave surface of a stationary rolling member. A laser beam trails successive cigarettes during sidewise movement of the cigarettes in an arcuate rolling channel between the moving peripheral surface of the drum-shaped conveyor and the stationary surface of the rolling member. The movement of the laser beam is initiated and regulated by a rotary drum-shaped member having a mirrored peripheral surface.

A drawback which is common to all of the above-enumerated perforating (permeability enhancing) apparatus is that the space requirements of such apparatus are excessive, that the apparatus are complex and hence expensive, as well as that their perforating action cannot be regulated and maintained with a desired or required degree of accuracy and facility.

Another drawback of certain conventional perforating apparatus is that, owing to their kinematics, the tubular wrapper of a cigarette can be perforated only during one-half of each revolution of a cigarette about its axis. Therefore, such apparatus are set up to expose the cigarettes to the action of laser beams which penetrate through the entire cigarette so that each beam provides perforations which are angularly offset by 180 degrees. Such solution is not entirely satisfactory because the energy requirements of the laser are very pronounced and also because the dimensions of at least one of two simultaneously burned perforations in the tubular wrapper of the cigarette are excessive.

OBJECTS OF THE INVENTION

An object of the invention is to provide an apparatus which is simple, compact and inexpensive and occupies space that is available but is not utilized in many machines or production lines for the making of rod-shaped articles

with gas-permeable tubular envelopes. Another object of the invention is to provide an apparatus which is constructed and assembled in such a way that the beam or beams of coherent radiation need not penetrate transversely across the entire rod-shaped commodity (such as a plain or filter cigarette) at the perforating station. A further object of the invention is to provide an apparatus which can form perforations while a rod-shaped article rotates through an angle of 360° while advancing past the perforating station.

An additional object of the invention is to provide a novel and improved method of manipulating high-energy beams of radiation in the course of enhancing the penetrability of tubular wrappers for rod-shaped tobacco fillers and/or for rod-shaped filters for tobacco smoke.

Still another object of the invention is to provide a novel laser-conveyor combination which can be put to use in the above outlined apparatus. A further object of the invention is to provide a novel conveyor which can be utilized with a source of high-energy radiation in the apparatus of the present invention.

Another object of the invention is to provide the above outlined apparatus with novel and improved means for rolling rod-shaped articles preparatory to and during enhancement of permeability of their wrappers, such as wrappers made of cigarette paper, tipping paper or the like.

An additional object of the invention is to provide a cigarette making machine which embodies, or cooperates with, an apparatus exhibiting the above outlined novel characteristics.

Still another object of the invention is to provide an apparatus which occupies space that is normally available in a machine or production line for the making of plain and/or filter cigarettes or analogous rod-shaped commodities of the tobacco processing industry.

A further object of the invention is to provide an apparatus which can dispense with mirrored rotary bodies forming part of numerous presently employed apparatus for enhancing the permeability of tubular wrappers of rod-shaped articles being turned out by the tobacco processing industry.

An additional object of the invention is to provide an apparatus which exhibits the above outlined desirable novel characteristics and which can be designed to subject the wrappers of successive rod-shaped articles of the tobacco processing industry to the action of a single beam of high-energy radiation or to simultaneous action of plural high-energy radiation beams.

Another object of the invention is to provide rod-shaped smokers' products having tubular wrappers which were perforated in accordance with the above outlined method and/or in the above outlined apparatus.

SUMMARY OF THE INVENTION

One feature of the instant invention resides in the provision of an apparatus for increasing or enhancing the permeabilities of tubular envelopes or wrappers forming part of rod-shaped commodities and being adapted to be perforated in response to exposure to high-energy radiation. The improved apparatus comprises means for rolling a series of successive rod-shaped commodities sideways along a predetermined path. The rolling means includes an at least partially hollow conveyor having an external surface bounding a portion of the aforementioned path, and the apparatus further comprises a source of high-energy radiation and means for directing at least some of the radiation issuing from the source through the hollow conveyor and against the

envelopes of commodities rolling along the aforementioned portion of the predetermined path. The source can include at least: one pulsating laser, and the commodities can include or constitute rod-shaped smokers' products (such as plain or filter cigarettes, cigars or cigarillos). The at least partially hollow conveyor can include a hollow rotary drum which is rotatable about a predetermined (e.g., horizontal) axis, and the aforementioned external surface can constitute a cylindrical surface of the hollow drum. The rolling means of such apparatus can further comprise a rolling member (e.g., a stationary rolling member) having a second surface cooperating with the peripheral surface of the hollow drum to bound a channel which defines a portion of the predetermined path.

At least a portion of the radiation directing means is or can be located (installed) in the at least partially hollow conveyor. Such radiation directing means can include at least one mobile mirror, e.g., a pivotable mirror.

The improved apparatus further comprises means for supplying the series of commodities into the predetermined path, preferably in such a way that successive commodities of the series are maintained at predetermined (particularly uniform) distances from each other. The rolling means can include means (such as the means for rotating the drum-shaped conveyor) for moving the external surface at a speed which is required to ensure that any point of the envelope of a commodity rolling along the aforementioned portion of the predetermined path, covers a distance greater than the circumferential length of a commodity while the supplying means advances each of the successive commodities through one of the predetermined distances. In such apparatus, the radiation directing means preferably includes at least one radiation reflecting element which is movable from a predetermined starting position while directing high-energy radiation upon the envelope of a commodity rolling in the aforementioned portion of the predetermined path (within a predetermined interval of time) back to the starting position. The speed of moving any point of an envelope of a commodity rolling along the aforementioned portion of the predetermined path is preferably such that the interval during which the aforementioned point covers that part of the aforesaid distance which exceeds the circumferential length of an envelope at least matches the predetermined interval of time to thus permit or enable the radiation reflecting element to reassume its starting position while a commodity is on its way into the aforementioned portion of the predetermined path.

The radiation directing means can comprise a mirror having a radiation reflecting surface, and such radiation directing means can further comprise means for pivoting the mirror about an axis which intersects the radiation reflecting surface of the mirror.

As already mentioned above, the at least partially hollow conveyor can comprise a hollow rotary drum-shaped conveyor which is rotatable about a predetermined (such as horizontal) axis, and the means for directing radiation can comprise a mirror which is pivotable about a second axis which (a) is at, least substantially parallel to the predetermined axis, or (b) coincides with the predetermined axis. In the latter instance, the radiation directing means is or can be arranged to direct radiation upon the envelope of a commodity in the aforementioned portion of the predetermined path at a distance from the predetermined axis which is less than the radius of the external surface of the hollow drum-shaped conveyor.

The radiation directing means can comprise at least one light refracting element (e.g., a plano-convex lens). Such

radiation directing means can further comprise a pivotable mirror; the at least one light refracting element can be disposed between the radiation source and the pivotable mirror, or between the pivotable mirror and the locus of impingement of high-energy radiation upon the envelope of a commodity in the aforementioned portion of the predetermined path.

As a rule, the radiation directing means of the improved apparatus will comprise at least one of (a) a collector lens, (b) a diffractive optical element, and (c) a combination of a collector lens and a diffractive optical element.

If the at least partially hollow conveyor includes or is constituted by a hollow drum which is rotatable about a predetermined (e.g., horizontal) axis and the aforementioned external surface is a cylindrical external surface of the drum, the source can be located outside of such at least partially hollow conveyor and can be set up to direct at least some of the high-energy radiation into the drum along a second path which is at least substantially parallel to the predetermined axis. The radiation directing means of such apparatus can comprise a pivotable mirror which is arranged to direct radiation upon the envelope of a commodity rolling along the aforementioned portion of the predetermined path, and means for deflecting radiation issuing from the source and for directing deflected radiation upon the pivotable mirror.

The at least partially hollow conveyor is provided with at least one opening which is disposed in the external surface of such conveyor and is partially overlapped by a commodity rolling along the aforementioned portion of the predetermined path. The radiation directing means is arranged to direct radiation upon a commodity in the aforementioned portion of the predetermined path from the interior of the at least partially hollow conveyor and through the at least one opening. The at least one opening can constitute an arcuate slot extending at least substantially circumferentially of the cylindrical surface of the hollow drum-shaped conveyor. The path for successive commodities can include or constitute an arcuate channel having its center of curvature at least close to the axis of the cylindrical external surface of the drum-shaped conveyor. The latter can be provided with a plurality of arcuate openings, and the radiation directing means can include means for splitting a beam of coherent radiation issuing from the source into a plurality of discrete beams and means for directing each discrete beam through a different opening of the conveyor.

Another feature of the invention resides in the provision of a method of perforating tubular envelopes of rod-shaped commodities by exposure to high-energy radiation. The method comprises the steps of rolling successive commodities of a series of such commodities sideways along a predetermined path which partially surrounds a hollow conveyor, establishing a source of high-energy radiation (such as a laser which emits a beam of coherent radiation), and directing from the source at least one beam of high-energy radiation in the hollow conveyor (such as into and/or within the hollow conveyor) and thence against the envelopes of successive commodities of the series rolling sideways along the predetermined path.

The establishing step can include locating the source or sources of high-energy radiation outside of the hollow conveyor.

The commodities can constitute rod-shaped smokers' products (such as plain or filter cigarettes, cigars or cigarillos) each of which has a rod-like filler (e.g., of natural, reconstituted and/or artificial tobacco and/or filter material for tobacco smoke) confined in the respective envelope (e.g.,

an envelope consisting of or comprising cigarette paper, tipping paper and/or other wrapping material customarily employed in the tobacco processing industry).

The establishing step of the improved method can comprise providing or employing a laser, and the radiation directing step of such method can comprise splitting the at least one beam into a plurality of (e.g., into two) discrete laser beams and directing the discrete laser beams upon different portions of envelopes of successive commodities of the series while the commodities roll sideways along the predetermined path.

The novel features which are considered as characteristic of the invention are set forth in particular in the appended claims. The improved perforating apparatus itself, however, both as to its construction and the modes of assembling, installing and utilizing the same, together with numerous additional important and advantageous features and attributes thereof, will be best understood upon perusal of the following detailed description of certain presently preferred specific embodiments with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic front elevational view of an apparatus which embodies one form of the invention and is designed to form perforations in selected portions of tubular envelopes of successive rod-shaped smokers' products while the products roll sideways through an arcuate channel between a hollow drum-shaped or cage-like rotary conveyor and a stationary rolling member, with the radiation source omitted;

FIG. 2 is a fragmentary schematic plan view of a radiation source and of a portion of the apparatus shown in FIG. 1, certain constituents of the illustrated structure being at least partially confined in the hollow conveyor;

FIG. 3 is a view similar to that of FIG. 1 but showing a portion of a modified apparatus; and FIG. 4 is a view similar to that of FIG. 2 but showing certain parts of the apparatus embodying the structure of FIG. 3.

DESCRIPTION OF PREFERRED EMBODIMENTS

The apparatus 1 of FIG. 1 can be installed in a cigarette maker or in another machine or production line for the making of elongated rod-shaped commodities constituting smokers' products of the type wherein one or more tubular envelopes surround a rod-like filler of filter material for tobacco smoke and/or of comminuted natural, reconstituted and/or artificial tobacco. It is assumed that the commodities are filter cigarettes of double unit length wherein a filter mouthpiece of double unit length is coaxial with and is located between and abuts the adjacent ends of two plain cigarettes of unit length. Each plain cigarette contains a rod-like tobacco filler and a tubular envelope or wrapper of cigarette paper, and each filter mouthpiece contains a rod-like filler of filter material (e.g., acetate fibers) for tobacco smoke and a tubular envelope of cigarette paper or the like. Furthermore, each commodity comprises an adhesive-coated uniting band which can be made of artificial cork or another suitable tipping paper and is convoluted around the entire filter mouthpiece of double unit length as well as about the adjacent inner end portions of the respective plain cigarettes of unit length.

A machine which turns out filter cigarettes of double unit length is disclosed, for example, in commonly owned U.S.

Pat. No. 5,135,008 granted Aug. 4, 1992 to Oesterling et al. for "METHOD OF AND APPARATUS FOR MAKING FILTER CIGARETTES", and in commonly owned U.S. Pat. No. 4,265,254 granted May 5, 1981 to Koch et al. for "APPARATUS FOR PERFORATING CIGARETTE PAPER OR THE LIKE". A machine for making plain cigarettes is disclosed, for example, in U.S. Pat. No. 4,281,670 granted Aug. 4, 1981 to Heitmann et al. for "APPARATUS FOR INCREASING THE PERMEABILITY OF WRAPPING MATERIAL FOR ROD-SHAPED SMOKERS' PRODUCTS".

The apparatus **1** of FIG. **1** comprises an at least partially hollow drum-shaped conveyor **16** which forms part of a means for rolling successive commodities (hereinafter called cigarettes for short) sideways along an arcuate path one side of which is bounded by a portion of the cylindrical peripheral (external)—surface **14** of the conveyor **16**. Such portion of the moving peripheral surface **14** and a concave surface **18** of a stationary rolling member **17** define an arcuate channel **12** having a width which at most matches the diameter of a cigarette **10** but is preferably slightly less to thus ensure that successive cigarettes of a series of equidistant cigarettes are caused to roll about their respective axes and to simultaneously move sideways in the direction indicated by arrows **22** while advancing through that portion of their path which extends through the channel **12**.

The inlet of the channel **12** receives successive cigarettes **10** of the aforementioned series from a supplying means **2** here shown as a drum-shaped conveyor which is driven to rotate in a counterclockwise direction (arrow **4**). The peripheral surface of the supplying conveyor **2** is provided with equidistant axially parallel ribs **8**, and the front (leading) sides of the ribs **8** are provided with suction ports (not specifically shown in FIG. **1**) which attract cigarettes **10** during transport of cigarettes from a source (such as a conveyor whereon pairs of plain cigarettes of unit length are connected with filter mouthpieces of double unit length by adhesive coated uniting bands, e.g., in a manner as described in the aforementioned U.S. Pat. No. '008 patent to Oesterling et al.) to the inlet of the channel **12**. The axis **6** of the supplying conveyor **2** is but need not always be parallel to the axis of the hollow conveyor **16**. The aforementioned suction ports at the front sides of the ribs **8** are disconnected from a suction generating device (not shown) not later than at the inlet of the channel **12** to thus ensure predictable entry of successive cigarettes **10** into the channel **12** wherein the cigarettes roll about their respective longitudinal axes, and simultaneously advance sideways in the direction of arrows **22** at a speed determined by the means (such as a driven shaft **16D**) which serves to rotate the drum-shaped conveyor **16** about the axis **20**.

The stationary rolling member **17** can be replaced with a mobile rolling member which, defines the rolling surface **18** (e.g., by a portion of a driven belt), as long as the difference between the speeds of the surfaces **14**, **18** is such that successive cigarettes **10** of the series supplied by the conveyor **2** (or any other suitable cigarette supplying means) suffices to ensure that each cigarette advancing in the channel **12** completes a predetermined number of revolutions about its own axis while simultaneously covering a predetermined distance in the direction indicated by the arrows **22**. Such combined rolling and sidewise movement is necessary to ensure a highly predictable change (increase) of permeability of the tubular envelope during advancement of a cigarette **10** in a predetermined portion of its path in the channel **12**, namely while the envelope is being perforated

by coherent high-energy radiation **34** supplied by a suitable source **L**, e.g., a laser shown schematically in FIG. **2**. The just discussed difference between the (zero) speed of the concave rolling surface **18** and the speed of the convex rolling surface **14** is selected in such a way that any given point at the external surface of the envelope of a cigarette **10** rolling in the channel **12** covers a distance exceeding the circumference of a cigarette while a cigarette on the supplying conveyor **2** covers a distance matching that between two neighboring ribs **8**.

A cigarette **10** which leaves the channel **12** is attracted by suction ports (not shown) at the front side of the oncoming axially parallel peripheral rib **30** provided on a rotary drum-shaped take-off conveyor **24**.

The latter is rotatable counterclockwise (see the arrow **28**) about an axis **26** which is parallel to the axes **6** and **20**. It will be noted that the conveyors **2** and **24** rotate counterclockwise whereas the conveyor **16** rotates clockwise. The conveyor **24** delivers successive (freshly perforated) cigarettes **10** into the range of a severing tool which divides each such rod-shaped article into two filter cigarettes of unit length. Reference should be had again to the aforementioned U.S. '008 patent to Oesterling et al.

Referring to FIG. **2**, the laser **L** is or can be located outside of or in the interior of the hollow drum-shaped conveyor **16**. The view of FIG. **2** is taken in the direction of arrow **44** shown in FIG. **1** but with the conveyor **16** omitted. The pulsating beam of high-energy radiation issuing from the laser **L** is split and deflected by a mirror **32** forming part of means for directing radiation upon the envelopes of successive cigarettes **10** rolling and advancing sideways in a predetermined portion of the channel **12**. The beam **34** which is deflected by the mirror **32** impinges upon a pivotable mirror **36**. If the laser **L** is located outside of the hollow conveyor **16**, the beam issuing from the laser enters the interior of the conveyor **16**, preferably by advancing in parallelism with the axis **20**, to impinge upon the mirror **32** which, in turn, directs the beam **34** against the pivotable mirror **36**, namely at a 90° angle to the axis **20**. The mirror **36** deflects the oncoming beam **34** toward the internal surface of the hollow conveyor **16**, and more specifically into one of a plurality of arcuate slit- or slot-shaped openings **38** provided in the cylindrical body of the drum-shaped conveyor **16**. A cigarette **10**, the envelope of which is being perforated, rolls relative to the surface **14** along an opening **38** so that the rolling cigarette is in contact with the surface **14** practically all the way from end to end save for the narrow gap caused by the provision of the opening **38** which is necessary in order to enable the pulsating beam **34** of high-energy radiation to impinge upon and to perforate predetermined portions of the envelope.

As already mentioned above, a cigarette **10** which advances in the direction of arrows **22** while rolling about its own axis on the way from the inlet to the outlet of the channel **12** completes more than one full revolution, i.e., more than is necessary to provide its envelope with a circumferentially complete array of perforations. This renders it possible to pivot the mirror **36** back to a starting angular position in which the mirror is ready to direct the beam **34** upon the envelope of the next-following cigarette **10** which has entered the channel **12**. This novel feature renders it possible that the permeability of the envelopes of each of a short or long series of successive cigarettes **10** supplied by the conveyor **2** is increased to the same extent.

FIGS. **1** and **2** further show a plano-convex lens **40** which is installed in the path of the beam **34** from the pivotable

mirror **36** to one of the slot-shaped openings **38** in the hollow conveyor **16**. The purpose of the lens **40** is to focus the beam **34** in such a way that the focal point of the laser beam **34** is located exactly at the locus **42** of impingement of the beam **34** upon the envelope of the cigarette **10** in the rolling channel **12**.

The pivotable mirror **36** causes the beam **34** to follow a rolling cigarette **10** on its way from the inlet toward the outlet of the channel **12**. This ensures that the envelope of such cigarette is provided with a circumferentially complete array of perforations formed by the pulsating beam **34**. The exact loci of perforations are determined by the axial position of a cigarette **10** rolling in the channel **12** relative to that arcuate slot **38** which permits the beam **34** to propagate itself from the pivoting mirror **36**, through the focussing lens **40**, and into the rolling channel **12**.

FIG. **2** shows a driving unit **46** which serves as a means for pivoting the mirror **36** relative to the mirror **32** and lens **40** about an axis **46A** in order to direct the beam **34** upon the envelope of the cigarette **10** in the rolling channel **12**. FIG. **2** further shows that the mirror **32** is partly reflecting so that a portion (**34'**) of the beam issuing from the laser **L** can penetrate through the mirror **32** to impinge upon the fully reflecting mirror **32'**. The latter deflects the beam **34'** upon a second pivotable mirror **36'** which, in turn, directs the beam **34'** against a second plano-convex; focussing lens **40'** serving to direct this beam upon a selected (second) portion of the envelope of a cigarette **10** rolling in the channel **12**. Thus, the apparatus **1** including the structure of FIGS. **1** and **2** can simultaneously provide a tubular envelope with two axially spaced-apart arrays of perforations, e.g., one array for each of the two ultimate products (filter cigarettes of unit length). The mirror **36'** is pivotable by a second driving unit **46'** which is, or which can be, identical with the driving unit **46** for the mirror **36**. Driving units (**46**, **46'**) which can be utilized to pivot mirrors serving to reflect discrete laser beams are well known in the relevant arts.

The arrangement can be such that the deflecting mirror **32** directs 50% of radiation issuing from the laser **L** toward the pivotable mirror **36** and permits the remaining 50% of radiation (namely the beam **34'**) to impinge upon and to be fully reflected by the mirror **32'**.

FIGS. **3** and **4** show certain relevant details of a second permeability enhancing apparatus **1'**. All such parts of the apparatus **1'** which are identical with or clearly analogous to the corresponding parts of the apparatus **1** of FIGS. **1** and **2** are denoted by similar reference characters. The only significant difference between the apparatus **1** and **1'** is that, in the apparatus **1'**, the plano-convex lenses **40**, **40'** are replaced with similar lenses **48**, **48'** which are respectively located between the mirrors **32**, **32'** on the one hand, and the pivotable mirrors **36**, **36'** on the other hand. Thus, the lenses **48**, **48'** respectively focus the laser beams **34**, **34'** upon the pivotable mirrors **36**, **36'** before these mirrors direct the focussed beams **34**, **34'** upon selected portions of the envelope of a cigarette **10** rolling along the external surface **14** of the hollow conveyor **16** and over the respective slot- or slit-shaped openings **38**.

It goes without saying that each of the apparatus **1** and **1'** can operate only with one mirror (**32** or **32'**), with one mirror (**36** or **36'**) and with one lens (such as **40** or **48**).

An important advantage of the improved method and apparatus is that they are simpler and the apparatus **1**, **1'** are more compact than heretofore known permeability enhancing methods and apparatus. Thus, the various mirrors and lenses can be accommodated in a space (in the interior of the conveyor **16**) which is available but not utilized in conventional perforating apparatus. Moreover, the paths for the beams of coherent high-energy radiation are shorter and can

thus be controlled with a higher degree of accuracy. Still further, the various mirrors and lenses are simpler and less expensive than those which must be employed in conventional apparatus. For example, it is possible to dispense with complex and expensive mirrored drums.

The mirrors **36** and **36'** are preferably mounted in such a way that their pivot axes intersect the respective radiation reflecting surfaces. FIGS. **1** and **3** show that the mirrors **36** are pivotable about axes which are parallel to the axis **20** of the hollow conveyor **16**. However, it is equally possible and within the purview of the invention to mount the mirrors **36** (as well as the mirrors **36'**) in such a way that their pivot axes coincide with the axis **20**, i.e., that the length of that portion of a beam **34** or **34'** which propagates itself from the mirror **36** or **36'** to the tubular envelope of a cigarette **10** in the rolling channel **12** matches or closely approximates the radius of the external surface **14**. Also, such design ensures that the length of the beam portion between the mirror **36** or **36'** and the envelope of a cigarette **10** in the rolling channel **12** remains unchanged during each and every stage of enhancement of permeability of such envelope.

An advantage of the embodiments which are actually shown in FIGS. **1** and **3**, namely of the embodiments wherein the pivot axes for the mirrors **36** and **36'** are nearer to the rolling channel **12** than the axis **20** of the hollow conveyor **16** (i.e., wherein the radius of the surface **14** is greater than the distance from the reflecting surface of the mirror **36** or **36'** to the envelope of a cigarette **10** in the channel **12**) is that the lens **40** or **40'**, or the lens **48** or **48'**, renders it possible to focus the beam (**34** or **34'**) impinging upon the envelope of a cigarette **10** within the conveyor **16** with a degree of accuracy such that one can provide the envelope with perforations having diameters in the desirable range of 0.1 mm or thereabout. In contrast to the just described operation of the illustrated apparatus **1** and **1'**, conventional apparatus must employ complex optical elements which are called upon to reduce the diameters of laser beams from a diameter in the range of between about 5 and 11 mm to a diameter which is needed to make perforations with diameters (maximum dimensions) in the range of 0.1 mm.

In most or in many instances, the optical elements **40**, **40'** or **48**, **48'** constitute collector lenses or diffractive optical elements or combinations of collector lenses and diffractive optical elements. An advantage of the embodiment (apparatus **1**) which is shown in FIGS. **1** and **2** is that relatively small lenses **40**, **40'** suffice to focus the respective beams **34**, **34'** upon the envelopes of cigarettes **10** in the channel **12**. This renders it possible to readily accommodate the lenses **40**, **40'** in the interior of the conveyor **16**.

It is also within the purview of the present invention to install the mirrors **36'** and/or **36**, **36'** in the conveyor **16** in such a way that the radius of the surface **14** is smaller than the distance of mirror(s) **36** and/or **36**, **36'** from the locus (**42**) of impingement of a laser beam **34** or **34'** upon the envelope of a cigarette **10** in the rolling channel. All that is necessary is to select appropriate mirrors and/or lenses which render it possible to adequately focus the laser beam or beams upon the surfaces of the cigarettes **10** in the channel **12** in order to make perforations having the desired diameters.

As already mentioned hereinbefore, it is desirable and advantageous to select the ratio of distances between the ribs **8** on the supplying conveyor **2** to the distance covered by any point on the envelope of a cigarette **10** in the channel **12** in such a way that the distance covered by such point exceeds the circumferential length of an envelope before a next-following cigarette enters that portion of the channel **12** wherein it begins to be acted upon by a beam **34'** and/or **34**. This enables the mirror **36'** and/or **36** to reassume its starting

angular position (in response to pivoting by the drive 46' and/or 46) in good time to proceed with the next perforating step. All that is necessary is to properly relate the speeds of the conveyors 2, 16 to each other and to the speed of pivoting the mirror 36' and/or 36 (by the drive 46' and/or 46) back to the starting position(s) of the mirror 36' and/or 36; this establishes an interval of time which follows the making of a circumferentially complete array or set of perforations and is long enough to enable the mirror 36' and/or 36 to thereupon reassume its starting position.

The above considerations apply independently of the distances between successive cigarettes 10 in the rolling channel 12. For example, if the angular spacing of ribs 8 on the conveyor 2 equals 12π , the spacing between successive cigarettes 10 in the channel 12 can also equal 12π or it can slightly exceed or be slightly smaller than 12π . This feature is believed to constitute a patentable innovation in combination with or independently of the feature of installing one or more radiation directing elements (such as L, 32, 32', 36, 36', 40, 40', 48, 48') in the interior of the rolling conveyor 16.

The just discussed feature of the invention can be resorted to irrespective of whether the lens or lenses (40, 40') is or are installed between the mirror(s) 36 or 36' and the channel 12 (see FIGS. 1 and 2) or between the mirror (s) 32 or 32' and the mirror or mirrors 36 or 36' (see FIGS. 3 and 4). All that is necessary is to properly select the characteristics of the lenses 40, 40', 48 and/or 48'.

In each of the aforesaid embodiments, it is possible to provide the collector lenses with surface coatings to thus obtain so-called diffractive optics. For example, the coatings can be of a nature such that a laser beam having a circular cross-sectional area is converted into a beam having a polygonal cross-sectional area; this is advisable when the envelopes of the cigarettes 10 or analogous rod-shaped products are to be provided with non-circular perforations.

Still further, and as shown in FIGS. 2 and 4, the components 32 of the radiation directing means can constitute diffractive optics capable of splitting an incoming beam of high-energy radiation into a plurality of discrete beams. Diffractive optics are particularly desirable when it is necessary to enhance the focussing of a laser beam. Thus, even if the improved apparatus employs a relatively weak collector lens, and if the diameter of the round cross-sectional area of a laser beam is relatively large (e.g., in excess of 7 mm), the apparatus can make relatively small perforations with diameters below 0.1 mm. Still further, each embodiment of the present invention is preferably (or can be) designed to achieve as pronounced depth of field of the optically imaged laser beam as possible. The reason is that this renders it possible to disregard those variations of distances between the pivotable mirror 36 and/or 36' and the locus or loci of impingement of the beam(s) upon a rolling envelope which are attributable to the fact that the pivot axis of the pivotable mirror does not coincide with the axis 20 of the hollow conveyor 16.

It is often preferred to install the laser L (or another suitable source of high-energy radiation) outside of the conveyor 16, i.e., to utilize this hollow or partially hollow conveyor as a housing for various components of the radiation directing means but not for the radiation source. An advantage of such apparatus is that the laser L or an equivalent or analogous source of high-energy radiation is readily or more readily accessible at all times. Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic and specific aspects of the aforesaid contribution to the art of perforating cigarette paper or the like and, therefore, such

adaptations should and are intended to be comprehended within the meaning and range of equivalence of the appended claims.

What is claimed is:

1. A method of perforating tubular envelopes of rod-shaped commodities by exposure to high-energy radiation, comprising the steps of:

rolling successive commodities of a series of commodities sideways along a predetermined path partially surrounding a hollow conveyor;

establishing a source of high-energy radiation at the hollow conveyor; and

directing from the source at least one beam of high-energy radiation in the hollow conveyor and thence against the envelopes of successive commodities of said series rolling sideways along said predetermined path, wherein said establishing step includes locating the source of high-energy radiation outside of the hollow conveyor.

2. The method of claim 1, wherein said establishing step includes providing a laser and said directing step includes splitting the at least one beam into a plurality of discrete laser beams and directing said discrete laser beams upon different portions of envelopes of successive commodities of said series while the commodities roll sideways along said predetermined path.

3. The method of claim 1, wherein the commodities are rod shaped smokers' products each having a rod-like filler confined in the respective envelope.

4. A method of perforating tubular envelopes of rod-shaped commodities by exposure to high-energy radiation, comprising the steps of:

rolling successive commodities of a series of commodities sideways along a predetermined path;

supplying said series of commodities into said path while maintaining successive commodities of said series at predetermined distances from each other, said rolling step including rolling the commodities at a speed such that any point of the envelope of a commodity rolling along a predetermined portion of said path covers a distance greater than the circumferential length of a commodity during advancement of each of said successive commodities through one of said predetermined distances;

establishing a source of high-energy radiation; and

directing from the source at least one beam of high-energy radiation against the envelopes of successive commodities of said series rolling sideways along said predetermined portion of said path.

5. The method of claim 4, wherein said directing step includes moving at least one radiation reflecting element from a predetermined starting position while

directing radiation upon the envelope of a commodity in said predetermined portion of said path and within a predetermined interval of time back to said starting position, said speed of moving any point of an envelope of a commodity rolling along said predetermined portion of said path being such that the interval during which said point covers the part of said distance exceeding said circumferential length at least matches said predetermined interval of time to thus enable the radiation reflecting element to reassume its starting position while a commodity is on its way into said predetermined portion of said path.