



US006888185B2

(12) **United States Patent**
Salling et al.

(10) **Patent No.:** **US 6,888,185 B2**
(45) **Date of Patent:** **May 3, 2005**

(54) **JUNCTION-ISOLATED DEPLETION MODE FERROELECTRIC MEMORY DEVICES**

(75) Inventors: **Craig T. Salling**, Plano, TX (US);
Brian W. Huber, Allen, TX (US)

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

5,119,329 A	6/1992	Evans, Jr. et al.
5,146,299 A	9/1992	Lampe et al.
5,273,927 A	12/1993	Gnadinger
5,289,410 A	2/1994	Katti et al.
5,345,414 A	9/1994	Nakamura
5,361,225 A	11/1994	Ozawa
5,449,935 A *	9/1995	Nakamura 257/295
5,615,144 A	3/1997	Kimura et al.
5,633,821 A	5/1997	Nishimura et al.
5,654,568 A	8/1997	Nakao

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **10/926,617**

(22) Filed: **Aug. 26, 2004**

(65) **Prior Publication Data**

US 2005/0024919 A1 Feb. 3, 2005

Related U.S. Application Data

(62) Division of application No. 10/306,592, filed on Nov. 27, 2002, which is a division of application No. 09/652,557, filed on Aug. 31, 2000, now Pat. No. 6,515,889.

(51) **Int. Cl.**⁷ **H01L 31/119**

(52) **U.S. Cl.** **257/295; 257/288; 257/290; 257/296; 257/314; 257/315; 257/316**

(58) **Field of Search** **257/295, 290, 257/296, 288, 314, 315, 316**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,888,630 A 12/1989 Paterson

JP	403101168 A	4/1991
JP	411040784 A	2/1999
JP	2001229685	8/2001

Primary Examiner—Richard Elms


Assistant Examiner—Douglas Menz

(74) *Attorney, Agent, or Firm*—Leffert Jay & Polglaze PA

(57) **ABSTRACT**

Depletion mode ferroelectric transistors are adapted for use as non-volatile memory cells. Various embodiments are described having a diode interposed between the bit line and a source/drain region of the transistor for added margin against read disturb. Various additional embodiments are described having an array architecture such that two memory cells sharing the same bit line also share the same program line. Using this configuration, non-selected cells are readily supplied with gate/source voltages sufficient to maintain the cells in a deactivated state during read and write operations on selected cells.

19 Claims, 11 Drawing Sheets



US 6,888,185 B2

Page 2

U.S. PATENT DOCUMENTS

5,680,344 A	10/1997	Seyyedy	6,031,754 A	2/2000	Derbenwick et al.
5,715,196 A	2/1998	Odake et al.	6,034,882 A	3/2000	Johnson et al.
5,768,185 A *	6/1998	Nakamura et al. 365/185.01	6,049,477 A	4/2000	Taira
5,812,442 A	9/1998	Yoo	6,067,244 A	5/2000	Ma et al.
5,847,989 A	12/1998	Seyyedy	6,108,236 A	8/2000	Barnett
5,905,672 A	5/1999	Seyyedy	6,121,072 A	9/2000	Choi et al.
5,907,861 A	5/1999	Seyyedy	6,121,642 A	9/2000	Newns
5,909,389 A	6/1999	Kawakubo et al.	6,144,579 A	11/2000	Taira
5,973,911 A	10/1999	Nishioka	6,324,101 B1	11/2001	Miyawaki
5,990,507 A	11/1999	Mochizuki et al.	6,337,805 B1	1/2002	Forbes et al.
5,999,439 A	12/1999	Seyyedy	6,538,273 B2 *	3/2003	Willer et al. 257/295
6,026,024 A	2/2000	Odani et al.	6,587,365 B1	7/2003	Salling
6,028,784 A	2/2000	Mori et al.	6,670,661 B2 *	12/2003	Haneder et al. 257/295

* cited by examiner




Fig. 1
Prior Art




Fig. 2




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 3D




Fig. 4




Fig. 5




Fig. 6




Fig. 7A




Fig. 7B




Fig. 8A




Fig. 8B




Fig. 9A




Fig. 9B




Fig. 9C




Fig. 10

JUNCTION-ISOLATED DEPLETION MODE FERROELECTRIC MEMORY DEVICES

RELATED APPLICATIONS

This is a divisional application of U.S. patent application Ser. No. 10/306,592 (pending), filed Nov. 27, 2002 and titled "JUNCTION-ISOLATED DEPLETION MODE FERROELECTRIC MEMORY DEVICES, USES AND OPERATION," which is a divisional application of U.S. patent application Ser. No. 09/652,557, filed Aug. 31, 2000 and issued Feb. 4, 2003 as U.S. Pat. No. 6,515,889, each of which is commonly assigned, and the entire contents of which are incorporated herein by reference.

This application is further related to U.S. patent application Ser. No. 09/653,074 filed Aug. 31, 2000 and issued Jul. 1, 2003 as U.S. Pat. No. 6,587,365, which is commonly assigned.

TECHNICAL FIELD OF THE INVENTION

The present invention relates to ferroelectric memory devices, and particularly to memory cells and memory array architectures making use of junction-isolated ferroelectric depletion-mode field-effect transistors.

BACKGROUND OF THE INVENTION

Ferroelectric materials are a class of materials that can be thought of as having electrical properties somewhat analogous to the magnetic properties of ferromagnetic materials. A uniaxial ferromagnetic material can be magnetized in one of two directions, and thereafter will retain a magnetic field in that direction even after the applied magnetic field is removed; similarly, a ferroelectric material can be "polarized" in either direction (by applying an electric field to it), and thereafter will retain an electric field in that direction, even after the applied electric field is removed.

Ferroelectric materials have been successfully integrated into integrated circuit processes, but this integration can have some drawbacks. Ferroelectric materials having sufficient thermal stability for integrated circuit processing often include incompatible metals that must be separated from a silicon substrate. Such ferroelectric materials also tend to be strong oxygen sources, increasing the risk of undesirable oxidation of adjacent materials. Additionally, ferroelectric materials generally can only withstand a finite number of polarization reversals before their performance degrades.

Ferroelectric memories exploit the properties of ferroelectric materials. These materials are useful in semiconductor memories as they have characteristics to provide a non-volatile memory function; after a ferroelectric material has been polarized in one direction, it will hold that polarization for an extended time without further power input. In contrast, dynamic random access memory (DRAM) requires periodic refresh to maintain its data value, thus losing its data value upon the removal of its power source.

Since the physics of ferroelectric floating-gate memories are similar to standard floating-gate memories (such as Flash memories), the sensing operation is correspondingly similar. Typically, floating-gate memories are sensed by detecting the activation/deactivation of the selected transistor in response to a given gate/source voltage. Although a typical floating-gate memory's activation/deactivation state is dependent on a stored charge of its floating gate, and a ferroelectric floating-gate memory's activation/deactivation state is dependent on a polarization of a ferroelectric layer, they both can exhibit this binary behavior.

At the microscopic scale, the ferroelectric material can be seen to be divided into domains. A domain is a volume within which the polarization of the material is uniform. Each domain can have only two stable polarization states. The magnitude of the polarization state of the bulk material is a composite of the individual domain polarization states.

FIG. 1 schematically shows a typical hysteresis curve **12** for a ferroelectric material. When the applied electric field E is increased to a positive value E_1 , the polarization of the material will increase to a value P_1 . When the applied positive field is subsequently removed, the polarization will fall back to a positive "remanent polarization" value P_r . In a similar manner, when the applied electric field is increased in the opposite direction, to a negative value $-E_2$, the polarization of the material will go to a negative value $-P_2$. When the applied negative field is subsequently removed, the polarization will fall back to a negative remanent polarization value $-P_r$. Thus, the material can take either of two polarization states in the absence of an electric field, depending on how it has been affected by the previously applied field. For electrical circuit analysis, the polarization state of a ferroelectric film can be thought of in terms of surface charge density, i.e., as amount of charge per unit area (usually written as " σ "). Curve **14** is an example of a minor hysteresis curve obtained when the same material is cycled between electrical potentials having insufficient magnitude to cause complete reversal of the polarization.

When an increasingly strong electric field is applied to a ferroelectric material, more and more of the domains will change their state to line up with the applied field. The electric field seen by any one domain is affected by the polarization states of the other domains which are nearby. Consequently, a full reversal of polarization requires not only some threshold energy level, but also some delay as individual domains align. This is inconvenient for ferroelectric memories, since it limits the write speed of any such memory. Moreover, in memories that use a destructive read, i.e., a read operation using a voltage sufficient to cause reversal of polarity, this phenomenon is also an important constraint on read access time as the data must be rewritten after sensing. This has been a problem with commercialization of ferroelectric memories, since it is highly desirable for ferroelectric memories to have access times approximately as fast as those for DRAM memories.

For the reasons stated above, and for other reasons stated below that will become apparent to those skilled in the art upon reading and understanding the present specification, there is a need in the art for alternate architecture and methods of operation of ferroelectric semiconductor memory devices.

SUMMARY OF THE INVENTION

The above-mentioned problems with memory devices and other problems are addressed by the present invention and will be understood by reading and studying the following specification.

Depletion-mode ferroelectric transistors are described herein for use as non-volatile memory cells. Such memory cells find use in non-volatile memory devices as well as other electronic systems having non-volatile memory storage. Various embodiments are described having a diode interposed between the bit line and a source/drain region of the transistor for added margin against read disturb, i.e., undesirable reversal of polarity. Various additional embodiments are described having an array architecture such that two memory cells sharing the same bit line also share the

same program line. Using this configuration, non-selected cells are readily supplied with gate/source voltages sufficient to maintain the cells in a deactivated state during read and write operations on selected cells while avoiding undesirable reversal of polarity.

For one embodiment, the invention provides a memory cell. The memory cell includes a ferroelectric layer formed overlying a substrate and a control gate formed overlying the ferroelectric layer and coupled to a word line. The memory cell further includes a first source/drain region having a first conductivity type formed in the substrate and coupled to a program line, a second source/drain region having the first conductivity type formed in the substrate, and a channel region having the first conductivity type formed in the substrate and interposed between the first and second source/drain regions. The memory cell still further includes a diode interposed between the second source/drain region and a bit line.

For another embodiment, the invention provides a memory cell. The memory cell includes a ferroelectric layer formed overlying a substrate and a control gate formed overlying the ferroelectric layer and coupled to a word line. The memory cell further includes a first source/drain region having a first conductivity type formed in the substrate and coupled to a program line, a second source/drain region having the first conductivity type formed in the substrate, and a channel region having the first conductivity type formed in the substrate and interposed between the first and second source/drain regions. The memory cell still further includes a diode formed in the second source/drain region and interposed between the second source/drain region and a bit line.

For a further embodiment, the invention provides a memory cell. The memory cell includes a conductively-doped polysilicon layer having a first conductivity type formed overlying a substrate having the first conductivity type. The memory cell further includes a ferroelectric transistor formed overlying the polysilicon layer. The transistor has a control gate, a ferroelectric layer interposed between the polysilicon layer and the control gate, a first source/drain region having the first conductivity type formed in the polysilicon layer, a second source/drain region having the first conductivity type formed in the polysilicon layer, and a channel having the first conductivity type formed in the polysilicon layer interposed between the first and second source/drain regions. The memory cell still further includes a well region having a second conductivity type opposite the first conductivity type. The well region is interposed between the second source/drain region and the substrate.

For a further embodiment, the invention provides a method of writing to a selected ferroelectric memory cell in an array of ferroelectric memory cells. The method includes applying a programming voltage to a first word line coupled to a control gate of the selected memory cell, wherein a gate/source voltage equal to the programming voltage is sufficient to cause a reversal of polarity of each memory cell. The method further includes applying a fraction of the programming voltage to other word lines coupled to control gates of non-selected memory cells not associated with the first word line. The method still further includes applying a ground potential to a first program line coupled to a first source/drain region of the selected memory cell and to a first bit line coupled to a second source/drain region of the selected memory cell through a diode. The method still further includes applying the fraction of the programming voltage to other program lines coupled to first source/drain regions of non-selected memory cells not associated with the

first program line and to other bit lines coupled, through diodes, to second source/drain regions of non-selected memory cells not associated with the first bit line.

For yet another embodiment, the invention provides a method of reading a selected ferroelectric memory cell in an array of ferroelectric memory cells. The method includes applying a first fraction of a programming voltage to a first word line coupled to a control gate of the selected memory cell, wherein a gate/source voltage equal to the programming voltage is sufficient to cause a reversal of polarity of each memory cell. The method further includes applying a ground potential to other word lines coupled to control gates of non-selected memory cells not associated with the first word line. The method still further includes applying the first fraction of the programming voltage to a first program line coupled to a first source/drain region of the selected memory cell and to other program lines coupled to first source/drain regions of non-selected memory cells not associated with the first program line. The method still further includes applying a second fraction of the programming voltage to a first bit line coupled to a second source/drain region of the selected memory cell through a diode and to other bit lines coupled, through diodes, to second source/drain regions of non-selected memory cells not associated with the first bit line.

The invention further provides apparatus, systems and methods of various scope.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of typical hysteresis curves for a ferroelectric material.

FIG. 2 is a schematic of a portion of a memory device showing an array architecture in accordance with an embodiment of the invention.

FIGS. 3A–3D are cross-sectional views of memory cells at various stages in their fabrication in accordance with one embodiment of the invention.

FIG. 4 is a diagram of current/voltage curves (I_{DS} VS. V_{GS}) for two different polarization states of a transistor in accordance with the invention in relation to a comparable transistor without a ferroelectric layer.

FIG. 5 is a cross-sectional view of memory cells in accordance with another embodiment of the invention.

FIG. 6 is a cross-section view of a memory cell in accordance with a further embodiment of the invention.

FIGS. 7A–7B are voltage diagrams of the array architecture of FIG. 2 during a write operation.

FIGS. 8A–8B are voltage diagrams of the array architecture of FIG. 2 during a read operation.

FIGS. 9A–9C are cross-sectional views of memory cells showing applied voltages and depletion/accumulation effect during various stages of a read operation.

FIG. 10 is a block diagram of a memory device in accordance with an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the present embodiments, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific embodiments in which the inventions may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that process, electrical or

mechanical changes may be made without departing from the scope of the present invention. The terms wafer or substrate used in the following description include any base semiconductor structure. Both are to be understood as including silicon-on-sapphire (SOS) technology, silicon-on-insulator (SOI) technology, thin film transistor (TFT) technology, doped and undoped semiconductors, epitaxial layers of a silicon supported by a base semiconductor structure, as well as other semiconductor structures well known to one skilled in the art. Furthermore, when reference is made to a wafer or substrate in the following description, previous process steps may have been utilized to form regions/junctions in the base semiconductor structure, and terms wafer or substrate include the underlying layers containing such regions/junctions. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims and equivalents thereof.

Memory cells in accordance with various embodiments of the invention include a ferroelectric (FE) field-effect transistor (FET), such as a metal-ferroelectric-metal-oxide-semiconductor (MF MOS) FET. Each FE FET of the various embodiments has at least one source/drain region having the same conductivity type as its channel. The FE FETs include an FE dielectric material.

The fabrication of the structures of the various example embodiments are demonstrated using silicon MOS technology. Memory cells of the example embodiments are fabricated on a p-type silicon substrate. However, as noted above, other substrates may be used for integrated circuit fabrication. Furthermore, the various embodiments could similarly be fabricated on a substrate having opposite conductivity, using appropriate changes in dopants and applied voltages. Additionally, various components of the memory cells may be fabricated in an order different from the example embodiments while still producing a memory cell in accordance with the invention.

FIG. 2 shows a sample layout of a portion of a memory device using the disclosed memory cells. In this drawing, bit lines **209** and program lines **201** are both orthogonal to the word lines **202** which they overlie. Furthermore, two memory cells coupled to the same bit line **209** will also be coupled to the same program line **201**. Using this configuration, non-selected cells are readily supplied with gate/source voltages sufficient to maintain the cells in a deactivated state during read and write operations on selected cells as described with reference to FIGS. 7A-7B, 8A-8B and 9A-9C.

The program lines **201** are vertically separated from the word lines **202** by a layer of dielectric material. Examples of dielectric materials include silicon oxides, silicon nitrides and silicon oxynitrides. Furthermore, the dielectric materials may include doped silicon oxides, such as borophosphosilicate glass (BPSG). The bit lines **209** are vertically separated from the word lines **202** and program lines **201** by a further layer of dielectric material. Word lines **202** form the gates of the memory cells (not shown in FIG. 2). Program line contacts (PLCT) **211** are coupled to first source/drain regions of the memory cells while bit line contacts (BLCT) **219** are coupled to second source/drain regions of the memory cells.

FIGS. 3A-3D show a cross-section of the embodiment of FIG. 2 taken along dotted line A-A' at various stages of fabrication. It will be appreciated that the program lines **201** and bit lines **209** run parallel to the section taken, with only their contact structures **211** and **219** being seen in FIGS.

3A-3D, while word lines **202** extend normal to the cross-section. Thus, the word lines **202** are orthogonal to the program lines **201** and bit lines **209**.

The gate dielectric layer **203** is formed overlying a semiconductor region having a conductivity type, such as an n-well **102** formed in a p-type substrate **101**. Formation of the n-well **102** includes formation of the source/drain regions and channel regions of the memory cell transistors. Note that since the transistors are depletion-mode devices, the doping level of the n-well **102** will be such that the channel region can be depleted by one of the two states of the later-deposited ferroelectric layer. For one embodiment, the substrate **101** is doped with an n-type impurity, such as phosphorus, to a doping level of approximately $1.0E18 \text{ cm}^{-3}$ and to a depth of approximately 800 \AA , thereby forming the n-well **102**. For additional embodiments, the substrate **101** is doped with an n-type impurity ranging from a doping level of approximately $4.0E18 \text{ cm}^{-3}$ at a depth of approximately 300 \AA to a doping level of approximately $1.0E17 \text{ cm}^{-3}$ at a depth of approximately 1200 \AA . For yet another embodiment, the doping level of the source/drain regions of a transistor is the same as the doping level of the channel region of the transistor.

The gate dielectric layer **203** is a non-ferroelectric dielectric material, such as a silicon oxide. The silicon oxide may be formed by conventional methods, such as thermal oxidation. As an example, the substrate **101** may be placed in an oxygen-containing ambient at approximately 900° C . to grow the gate dielectric layer **203**. Other methods of forming the gate dielectric layer **203** include physical vapor deposition (PVD) and chemical vapor deposition (CVD) as is known in the art of integrated circuit fabrication. For another embodiment, the gate dielectric layer **203** is silicon nitride formed by a PVD process, such as jet vapor deposition. Other dielectric materials may be used for the gate dielectric layer **203**. Specific examples include silicon oxides, silicon nitrides and silicon oxynitrides.

The floating gate **204** contains a conductive material, such as conductively-doped polysilicon, metal silicide, metal or metal alloy. Polysilicon layers are generally formed by CVD. Metal silicide layers may be formed directly through CVD, or they may be formed sequentially, such as by depositing a layer of metal on a silicon-rich layer, and reacting the layer of metal with the underlying silicon-rich layer. Metals and metal alloys are generally formed by a PVD process, such as sputtering.

The floating gate **204** will generally have the gate dielectric layer **203** on one side and the FE layer **206** on the other side. As such, the floating gate **204** may require multiple layers to provide adhesion to adjoining layers and/or to provide barrier properties for the ferroelectric material. For one embodiment, the floating gate **204** contains a metal layer overlying a conductively-doped polysilicon layer. For a further embodiment, the metal layer contains more than one metal layer, such as a layer of platinum overlying a layer of titanium. For another embodiment, the metal layer contains a layer of iridium overlying a layer of iridium oxide (Ir_2O_3).

The FE layer **206** is formed overlying the floating gate **204**. For one embodiment, the FE layer **206** is a metal oxide, such as strontium bismuth tantalite (SBT) or lead zirconium titanate (PZT). Other metal oxides having ferroelectric properties may be used for the FE layer **206**. Some examples include lanthanum-doped PZT (PLZF), lithium niobate (LiNbO_3), or additional metal oxides having a perovskite crystalline structure. The metal oxide may be formed by such CVD techniques as metal organic decomposition. For

one embodiment, the floating gate **204** is eliminated for cases where the gate dielectric layer **203** is compatible with the FE layer **206**, such that the FE layer **206** is overlying and adjoining the gate dielectric layer **203**. For a further embodiment, the gate dielectric layer **203** and the floating gate **204** are eliminated where the semiconductor material, e.g., n-well **102**, is compatible with the FE layer **206**, such that the FE layer **206** is overlying and adjoining the semiconductor material.

A control gate **207** is formed overlying the FE layer **206**. The control gate **207** contains a conductive material. For one embodiment, the control gate **207** includes a barrier layer, such as a metal barrier layer. For a further embodiment, the control gate **207** contains more than one layer. As one example, the control gate **207** may contain a layer of titanium overlying a layer of platinum. As another example, the control gate **207** may contain a metal layer overlying a conductive metal oxide layer, such as a layer of iridium overlying a layer of iridium oxide.

A cap layer **212** is generally formed overlying the control gate **207** to act as an insulator and barrier layer for the word line stack. The cap layer **212** contains an insulator and may include such insulators as silicon oxide, silicon nitride, and silicon oxynitrides. For one embodiment, the cap layer **212** is silicon nitride, formed by such methods as CVD or PVD.

The gate dielectric layer **203**, the floating gate **204**, the FE layer **206**, the control gate **207** and the cap layer **212** are subsequently patterned to define the word line stack as depicted in FIG. 3A. Patterning can include use of standard photolithographic techniques. As an example, a layer of photoresist may be deposited, exposed with an energy source, and developed to expose portions of the word line stack. Material is then removed from the exposed portions of the word line stack, including the exposed portions of the gate dielectric layer **203**, the floating gate **204**, the FE layer **206**, the control gate **207** and the cap layer **212**. Such removal may typically include chemical or ion etching. The resist is then removed, such as by plasma etch.

While the definition of the word line stack in the foregoing description is performed in a single patterning step, the layers may be individually patterned. For one embodiment, the gate dielectric layer **203** and the floating gate **204** are patterned prior to formation of the FE layer **206**. The FE layer **206** is then patterned to have a width less than the width of the previous layers. Such a structure can provide additional diffusion barrier characteristics upon formation of the control gate **207**; the control gate **207** can overlie both the surface and sidewalls of the FE layer **206**.

The sidewalls of the word lines **202** are then insulated using sidewall spacers **214**. The sidewall spacers **214** contain an insulator and may include the same materials as the cap layer **212**. The sidewall spacers **214** are typically formed by blanket depositing an insulating layer, such as a layer of silicon nitride, over the entire structure and then anisotropically etching the insulating layer to preferentially remove the horizontal regions and the leave only the vertical regions adjacent the sidewalls of the word line stacks. The resulting transistor is shown in FIG. 3B.

A bulk insulator layer **220** is formed overlying the word line stacks and patterned to define contact holes **214** for the program line contacts as shown in FIG. 3C. Conductive plugs **211** are formed in the contact holes **214** and the program lines **201** are formed overlying the plugs **211** and the bulk insulator layer **220** (outside the plane of the figure). Example plug structures include a conductively-doped polysilicon plug material with a metal silicide interface between

the n-well **102** and the plug material. The plugs **211** are coupled to the program lines **201** using extensions to laterally offset the program lines **201** from their associated bit lines **209** in order to facilitate subsequent formation of the bit line contacts.

The bulk insulator layer **220** is extended in FIG. 3D and patterned to define contact holes for the bit line contacts. Conductive plugs **219** are formed in the contact holes and the bit lines **209** are formed overlying the plugs **219** and the extended bulk insulator layer **220** as depicted in FIG. 3D. The conductive plugs **211** and **219** provide electrical communication between the semiconductor material and the program lines **201** and bit lines **209**, respectively.

The bit lines **209** and program lines **201** are coupled to columns of memory cells of a memory array. Each contains a conductive material. For one embodiment, the bit line **209** and/or program line **201** contains a metal. For another embodiment, the bit line **209** and/or program line **201** contains a metal alloy. For a further embodiment, the bit line **209** and/or program line **201** contains more than one layer of conductive material. The bit lines **209** and program lines **201** may make use of an insulative cap layer as with the word lines **202**. The word lines **202** further contain a conductive material. The word lines **202** may double as the control gate **207** of the memory cell transistors and thus be coupled to and have the same construction as the control gate **207** described with reference to FIGS. 3A–3D. Alternatively, the cap layer **212** may be eliminated and the word lines **202** may be formed to overlie and couple to the control gates **207**. The word lines **202** are coupled to rows of memory cells of the memory array.

Each transistor of each word line **202** can have a first programmed state representing a first data value, such as a data value of 1, or a second programmed state representing a second data value, such as a data value of 0. The programmed state is a function of the polarization of the FE layer **206**. Word line **202A** depicts an FE layer **206** programmed to the second programmed state. In the second programmed state, the additional negative voltage at the gate dielectric layer **203** causes a depletion layer to form underneath the gate, so that the transistor is deactivated at a zero gate/source voltage corresponding to an “off” state. Word line **202B** depicts an FE layer **206** programmed to the first programmed state. In the first programmed state, the additional positive voltage at the gate dielectric layer **203** will attract electrons, such that the transistor is activated at a zero gate/source voltage corresponding to an “on” state.

FIG. 4 shows example current/voltage curves (I_{DS} VS. V_{GS}) for the two different polarization states of one embodiment of the transistor. A ferroelectric transistor that is in the first programmed state will turn on at a lower gate/source voltage V_{GS} (in this example, where $V_{GS}=V_{G2}=-2V$) relative to a comparable depletion-mode transistor without a ferroelectric layer, shown as “A” in FIG. 4. Likewise, a ferroelectric transistor that is in the second programmed state will turn on at a higher V_{GS} (in this example, where $V_{GS}=V_{G1}=1V$). While specific potential levels were used in the example, FIG. 4 is provided for illustrative purposes to show that varying the polarization of the ferroelectric layer **206** will alter the threshold voltage of the transistor, thus determining whether the transistor will be activated or deactivated in response to a given V_{GS} . Accordingly, the invention is not limited to the specific values of V_{GS} .

In another embodiment, shown in FIG. 5, the disclosed array is seen formed on a silicon-on-insulator substrate.

Complete isolation of the active areas from the underlying silicon substrate **101** is provided by a buried oxide (BOX) layer **104** or other layer of dielectric material, while shallow trench isolation (STI) areas **105** separate adjacent pairs of transistors. This cross-section is similar to the cross-section seen in FIG. **3**, differing primarily in the area of device isolation. Formation of the buried oxide layer **104** and areas of shallow trench isolation **105** is well known in the art. Furthermore, formation of the memory cells can be accomplished as described with reference to FIG. **3**. Accordingly, detailed discussion of fabrication techniques is omitted for clarity.

The embodiment of FIG. **5** shows further that a p-well **108** can be formed beneath the bit line contacts **219** to be interposed between the bit line **209** and a source/drain region of the transistor. The p-well **108** may be formed by doping an exposed portion of the n-well **102** with a p-type impurity, such as boron, after patterning the bulk insulator layer to define the contact hole for the bit line contact and before formation of the contact plug. Additionally, doping of the p-well **108** may occur prior to formation of the bulk insulator layer, using a separate mask. Such doping is usually performed through ion implantation techniques. However, other methods are known such as diffusion techniques using gaseous, liquid or solid dopant sources.

The pn junction between the n-well **102** and the p-well **108** forms a diode providing isolation between the source/drain region and the bit line during read/write biasing for added margin against read disturb. This diode configuration may also be used in the embodiment of FIGS. **3A–3D**. However, the n-well **102** in FIGS. **3A–3D** must be sufficiently deeper than the p-well **108** below the bit line contact **219** in order to avoid shorting of the p-well **108** to the underlying p-type substrate **01**. The diodes of the various embodiments are isolated from the control gates **207** and, thus, the word lines **202**.

In a further embodiment, the channel can be formed of polysilicon, rather than monocrystalline silicon. FIG. **6** is an example of a memory cell formed over polysilicon. In the embodiment shown in FIG. **6**, the cells are formed so that they may overlie the sense amplifiers and row-column decode circuits (not shown in FIG. **6**) formed on a substrate **601**.

For the embodiment depicted in FIG. **6**, the substrate **601** is an n-type substrate. The substrate **601** could further be a p-type substrate or a doped well of a first conductivity type, such as an n-well, formed in a doped substrate of a second and opposite conductivity type, such as a p-type substrate. Formation of the memory cell follows semiconductor fabrication techniques of the type described with reference to FIGS. **3A–3D**, so details are omitted for clarity.

The memory cell includes a transistor as a portion of a word line **202**. The transistor may have the same construction as that depicted in FIGS. **3A–3D**, such as the gate dielectric layer **203**, floating gate **204**, FE layer **206**, control gate **207**, cap layer **212** and sidewall spacers **214**. The word line **202** is formed overlying a conductively-doped polysilicon layer **602**. The polysilicon layer **602** has a first conductivity type, such as an n-type conductivity. The first source/drain region of the transistor is coupled to a program line **201** through a conductive plug **611**. The second source/drain region of the transistor is coupled to a bit line **209** through a conductive plug **619**. A well **608** having the second conductivity type is formed in the substrate **601** interposed between the second source/drain region and the bit line **209**, the substrate **601** having the first conductivity type. Thus, a

diode is formed between the bit line **209** and a source/drain region of the memory cell transistor.

The word lines **202** and bit lines **209** run normal to the face of FIG. **6** for such an embodiment. Likewise, the program lines **201** for this embodiment run parallel to the face of FIG. **6**.

An overview of the read and write operations will now be provided, with particular reference to the array architecture of FIGS. **2** and **3A–3D**. It is assumed for the following examples that the voltage drop needed to change the state of the ferroelectric layer is approximately 2V. The gate/source voltage V_{GS} generally can be broken down into two primary components, i.e., a voltage drop across the gate dielectric layer and a voltage drop across the ferroelectric layer. Determination of the voltage drop across each of these dielectric layers of the gate stack can be made using standard calculations for the voltage drop across a series capacitance.

The programming voltage V_{pp} must be sufficient to produce a voltage drop across the ferroelectric layer that is equal to or greater than the remanent coercivity of the ferroelectric layer, i.e., an electric field sufficient to cause reversal of polarity of the ferroelectric layer. As noted above, this is assumed to be approximately 2V for the example embodiment. While the value of V_{pp} will depend upon the chosen fabrication materials and transistor dimensions, as used in the examples herein V_{pp} will be presumed to have a magnitude sufficient to cause reversal of polarity of the given ferroelectric layer when applied across the gate of the transistor. While it is generally preferred that V_{pp} have the minimum magnitude necessary to cause reversal of polarity (while accounting for engineering margins), higher values can be used provided the resulting voltage drops across non-selected cells does not exceed the remanent coercivity of the ferroelectric layer of any such non-selected cell. For the example embodiments, V_{pp} is approximately 6V.

Write Operation

FIGS. **7A–7B** show the voltages applied to the array for writing a first data value, e.g., a data value of 1, or a second data value, e.g., a data value of 0, respectively, to the cell located in the lower left-hand corner of each of the drawings and represented by the intersection of **WL0** and **BL0**. In FIG. **7A**, to write the first data value, the bit line, program line, and word line of all non-selected rows and columns (**BL1**, **PL1**, and **WL1** in this drawing) are set to some fraction of V_{pp} in order to avoid disturbing the polarity of the non-selected memory cells. For one embodiment, the bit line, program line, and word line of all non-selected rows and columns are set to approximately $V_{pp}/2$ (3V in this example). The selected bit line (**BL0**) and program line (**PL0**) are set to a ground potential, i.e., 0V. The selected word line (**WL0**) is set to V_{pp} (6V in this example). By applying a voltage differential across the ferroelectric layer equal to or exceeding the programming voltage, the cell can be forced to a data value of 1. Furthermore, as seen in the figure, the change in voltage (ΔV) seen across the non-selected cells is either 0V (for a cell in which neither the row nor column was selected) or $V_{pp}/2$ (for a cell in which either the row or the column, but not both, was selected), neither of which is sufficient to reverse the cell's polarity. Thus, data values of the non-selected cells are not altered during the write operation of the selected cell.

In FIG. **7B**, writing the second data value is shown. Non-selected rows and columns again have their bit lines, program lines, and word lines set to some fraction of V_{pp} , such as $V_{pp}/2$. In the selected column, the bit line and program line are set to V_{pp} , and in the selected row, the word line is set to 0V. Again, non-selected cells see a ΔV of 0V or

11

of $-V_{pp}/2$, neither of which will change the state of these cells, but the selected cell will see a ΔV of $-V_{pp}$, which is sufficient to cause a cell having the first data value to reverse its polarity.

In write mode, the resulting matrix of voltages seen by the cells will therefore be as shown in Table 1 below (where two values are shown, the first is for writing the first data value and the second, in parenthesis, is for writing the second data value).

TABLE 1

	First Source/Drain Region	Second Source/Drain Region	Gate	V_{GS}
Selected Cell	0V (V_{pp})	0V (V_{pp})	V_{pp} (0V)	V_{pp} ($-V_{pp}$)
Half-selected (same row)	$V_{pp}/2$	$V_{pp}/2$	V_{pp} (0V)	$V_{pp}/2$ ($-V_{pp}/2$)
Half-selected (same column)	0V (V_{pp})	0V (V_{pp})	$V_{pp}/2$	$V_{pp}/2$ ($-V_{pp}/2$)
Non-selected	$V_{pp}/2$	$V_{pp}/2$	$V_{pp}/2$	0V

Read Operation

FIGS. 8A–8B and 9A–9C demonstrate an example of the READ operation of the cell. FIG. 9A shows a cross-section of two cells, giving the voltages at which they are normally held in stand-by mode; in this case, approximately $V_{pp}/2$ (3V in this example) on all lines. Before the read operation, the word line voltages are dropped to the ground potential, as shown in FIG. 8A, from this stand-by mode. In this example, the resulting effective gate/source voltage V_{GS} on every cell is thus approximately $-2V$. As the curves of FIG. 4 show, no cells are able to turn on at this V_{GS} , so all cells are shut off. FIG. 9B shows a cross-section of two cells during this initialization phase, demonstrating the depletion region that is formed under these conditions.

In the read phase, shown in FIG. 8B, the selected word line WL0 is brought up to approximately $V_{pp}/3$ or approximately 2V. Concurrently, each program line voltage is dropped to approximately $V_{pp}/3$ or approximately 2V. This means that V_{GS} for the selected cells is now approximately $-0.5V$. As FIG. 4 shows, cells programmed to a first programmed state are able to conduct at this voltage, but cells programmed to the second programmed state are not. Conduction in this example will be from the selected bit line to its corresponding program line as the program line is at a smaller fraction of the programming voltage than the bit line. Suitable sensing architectures will detect a current drain, and thus a voltage drop, on the selected bit line. For sensing architectures adapted to detect an incoming current to the bit line, and thus a voltage rise on the selected bit line, voltages of the bit lines and program lines would correspondingly be swapped.

During the read phase, the V_{GS} of the non-selected cells remains below their turn-on point, while the V_{GS} of the selected cell is sufficient to cause activation of the transistor if it is in the first programmed state and insufficient to cause activation of the transistor if it is in the second programmed state. FIG. 9C shows a cross-section of the same two cells, where the left-hand cell is being read and is programmed to the first programmed state. This transistor will turn on and pull its respective bit line down. Conventional sensing architectures and methods can be used to sense the conducting state of the selected cells.

Devices and Systems

FIG. 10 shows a general block diagram of a memory device 1050 incorporating ferroelectric floating-gate memory cells and array architectures in accordance with the

12

various embodiments of the invention. The ferroelectric memory device 1050 is coupled to a processor 1051 to form an electronic system. The memory device includes a memory array 1052, column decoder 1054 and row decoder 1056, and a control circuit 1058. The memory array 1052 contains memory cells arranged in rows and columns. The memory array 1052 contains the ferroelectric floating-gate memory cells and/or array architectures in accordance with the various embodiments of the invention.

The memory device 1050 further includes input 1060 and output 1062 buffers connected to data input and data output lines, respectively. The data input and output lines can be multiplexed together, but have been illustrated separately for simplicity. Address lines 1063 are provided as input to the column decoder 1054 and row decoder 1056 to address a portion of the memory array 1052.

In operation, the memory device control circuit 1058 responds to control inputs 1059 from the processor 1051 to control operations performed on the memory array 1052. In particular, the control circuit 1058 is used to read data from and write data to the memory array 1052. During one of these access operations, an address provided on the address lines 1063 is decoded by the row decoder 1056 to activate a word line, thereby accessing a row of the memory array 1052. Likewise, an address provided on the address lines 1063 is decoded by the column decoder 1054 to activate at least one bit line, thereby accessing at least one column of the memory array 1052. An addressed memory cell is located at the intersection between each activated word line and each activated bit line. During a read operation, the data stored in the addressed memory cell(s) is then transferred to the output buffer 1062 and provided on the data output lines. In a write operation, the addressed memory cell is accessed and data provided on the data input lines is stored in the cell.

CONCLUSION

Depletion-mode ferroelectric transistors have been described for use as non-volatile memory cells. Such memory cells find use in non-volatile memory devices as well as other electronic systems having non-volatile memory storage. Various embodiments are described having a diode interposed between the bit line and a source/drain region of the transistor for added margin against read disturb. Various additional embodiments are described having an array architecture such that two memory cells sharing the same bit line also share the same program line. Using this configuration, non-selected cells are readily supplied with gate/source voltages sufficient to maintain the cells in a deactivated state during read and write operations on selected cells.

While specific dimensions were referred to in the example embodiments, the invention is not limited to the specific dimensions provided. It is recognized that there is a continuing drive to reduce device dimensions in integrated circuit manufacture. Accordingly, the referenced dimensions are intended only as guidelines under current manufacturing practices.

Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement that is calculated to achieve the same purpose may be substituted for the specific embodiments shown. Many adaptations of the invention will be apparent to those of ordinary skill in the art. Accordingly, this application is intended to cover any adaptations or variations of the invention. It is manifestly intended that this invention be limited only by the following claims and equivalents thereof.

13

What is claimed is:

1. A memory cell, comprising:
 - a ferroelectric layer formed overlying a well region having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
 - a control gate formed overlying the ferroelectric layer and coupled to a word line;
 - a first source/drain region having the first conductivity type formed in the well region and coupled to a program line;
 - a second source/drain region having the first conductivity type formed in the well region;
 - a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and
 - a diode interposed between the second source/drain region and a bit line.
2. The memory cell of claim 1, wherein the diode is a well region having the second conductivity type formed in the second source/drain region.
3. The memory cell of claim 1, wherein the ferroelectric layer is adjoining the well region.
4. The memory cell of claim 1, wherein the ferroelectric layer comprises a material selected from the group consisting of strontium bismuth tantalite, lead zirconium titanate, lanthanum-doped lead zirconium titanate, lithium niobate and metal oxides having a perovskite crystalline structure.
5. The memory cell of claim 1, further comprising:
 - a gate dielectric layer interposed between the channel region and the ferroelectric layer; and
 - a floating gate interposed between the gate dielectric layer and the ferroelectric layer.
6. The memory cell of claim 5, wherein the floating gate comprises a conductive material.
7. The memory cell of claim 6, wherein the conductive material includes at least one material selected from the group consisting of conductively-doped polysilicon, metal silicides, metals and metal alloys.
8. The memory cell of claim 7, wherein the floating gate comprises a metal layer overlying a conductively-doped polysilicon layer.
9. The memory cell of claim 1, further comprising:
 - a gate dielectric layer interposed between the channel region and the ferroelectric layer;
 wherein the ferroelectric layer is overlying and adjoining the gate dielectric layer.
10. A memory cell, comprising:
 - a ferroelectric layer formed overlying and adjoining a well region having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
 - a control gate formed overlying the ferroelectric layer and coupled to a word line;
 - a first source/drain region having the first conductivity type formed in the well region and coupled to a program line;
 - a second source/drain region having the first conductivity type formed in the well region;
 - a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and
 - a diode interposed between the second source/drain region and a bit line.

14

11. A memory cell, comprising:
 - a gate dielectric layer formed overlying and adjoining a well region having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
 - a ferroelectric layer formed overlying the gate dielectric layer;
 - a control gate formed overlying the ferroelectric layer and coupled to a word line;
 - a first source/drain region having the first conductivity type formed in the well region and coupled to a program line;
 - a second source/drain region having the first conductivity type formed in the well region;
 - a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and
 - a diode interposed between the second source/drain region and a bit line.
12. The memory cell of claim 11, wherein the ferroelectric layer is overlying and adjoining the gate dielectric layer.
13. A memory cell, comprising:
 - a gate dielectric layer formed overlying and adjoining a well region having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
 - a conductive floating gate formed overlying the gate dielectric layer;
 - a ferroelectric layer formed overlying the conductive floating gate;
 - a control gate formed overlying the ferroelectric layer and coupled to a word line;
 - a first source/drain region having the first conductivity type formed in the well region and coupled to a program line;
 - a second source/drain region having the first conductivity type formed in the well region;
 - a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and
 - a diode interposed between the second source/drain region and a bit line.
14. The memory cell of claim 13, wherein the ferroelectric layer is overlying and adjoining the conductive floating gate.
15. A memory cell, comprising:
 - a ferroelectric layer formed overlying and adjoining a well region having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
 - a control gate formed overlying the ferroelectric layer and coupled to a word line;
 - a first source/drain region having the first conductivity type formed in the well region and coupled to a program line;
 - a second source/drain region having the first conductivity type formed in the well region;
 - a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and
 - a diode formed as a second well region of the second conductivity type in the second source/drain region and coupled to a bit line.
16. The memory cell of claim 15, wherein the ferroelectric layer comprises a material selected from the group consist-

15

ing of strontium bismuth tantalite, lead zirconium titanate, lanthanum-doped lead zirconium titanate, lithium niobate and metal oxides having a perovskite crystalline structure.

17. A memory cell, comprising:

- a gate dielectric layer formed overlying a well region 5 having a first conductivity type, wherein the well region is formed in a substrate having a second conductivity type opposite the first conductivity type;
- a conductive floating gate formed overlying the gate dielectric layer;
- a ferroelectric layer formed overlying the conductive floating gate;
- a control gate formed overlying the ferroelectric layer and coupled to a word line;
- a first source/drain region having the first conductivity 15 type formed in the well region and coupled to a program line;

16

a second source/drain region having the first conductivity type formed in the well region;

a channel region having the first conductivity type formed in the well region and interposed between the first and second source/drain regions; and

a diode formed as a second well region of the second conductivity type in the second source/drain region and coupled to a bit line.

18. The memory cell of claim **17**, wherein the ferroelectric layer is formed overlying and adjoining the conductive floating gate.

19. The memory cell of claim **17**, wherein the ferroelectric layer comprises a material selected from the group consisting of strontium bismuth tantalite, lead zirconium titanate, 15 lanthanum-doped lead zirconium titanate, lithium niobate and metal oxides having a perovskite crystalline structure.

* * * * *