

US006893566B2

(12) **United States Patent**  
**Fassbender**

(10) **Patent No.:** **US 6,893,566 B2**  
(45) **Date of Patent:** **May 17, 2005**

(54) **SEWAGE TREATMENT SYSTEM**

(76) **Inventor:** **Alexander G. Fassbender**, 3100  
George Washington Way, Suite 153,  
Richland, WA (US) 99352

(\*) **Notice:** Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** **10/375,809**

(22) **Filed:** **Feb. 26, 2003**

(65) **Prior Publication Data**

US 2004/0164019 A1 Aug. 26, 2004

(51) **Int. Cl.<sup>7</sup>** ..... **C02F 3/30**; C02F 11/04;  
C02F 11/18

(52) **U.S. Cl.** ..... **210/603**; 210/605; 210/609;  
210/613; 435/262.5

(58) **Field of Search** ..... 210/603, 605,  
210/612, 613, 620, 621, 623, 630, 609;  
435/262, 262.5; 48/127.3

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 3,959,125 A \* 5/1976 Teletzke ..... 210/603
- 3,973,043 A \* 8/1976 Lynn ..... 426/55
- 3,980,556 A \* 9/1976 Besik ..... 210/616
- 4,246,099 A \* 1/1981 Gould et al. .... 210/603
- 5,256,251 A \* 10/1993 Holcombe ..... 159/47.3
- 5,264,009 A \* 11/1993 Khan ..... 48/197 R
- 5,282,980 A \* 2/1994 Kew et al. .... 210/787

- 5,292,442 A \* 3/1994 Khan et al. .... 210/770
- 5,746,919 A \* 5/1998 Dague et al. .... 210/603
- 5,833,856 A \* 11/1998 Liu et al. .... 210/605
- 5,846,425 A \* 12/1998 Whiteman ..... 210/606
- 5,853,589 A \* 12/1998 Desjardins et al. .... 210/605
- 6,090,240 A \* 7/2000 Eneberg et al. .... 159/47.3
- 6,113,789 A \* 9/2000 Burke ..... 210/609
- 6,291,232 B1 \* 9/2001 Miller, III ..... 435/262
- 6,325,935 B1 \* 12/2001 Hojsgaard ..... 210/609
- 6,444,124 B1 \* 9/2002 Onyeche et al. .... 210/603

\* cited by examiner


*Primary Examiner*—Fred G. Prince

(74) *Attorney, Agent, or Firm*—Speed & Rogers, P.A.

(57) **ABSTRACT**

A sewage treatment system is disclosed in which a waste stream is separated into a primary sludge and water effluent, and the primary sludge is anaerobically digested and dewatered to produce a Class A biosolid. The water effluent is aerobically digested and separated to provide a waste activated sludge. The waste activated sludge is heated in a two-stage process with steam injection and indirect steam before it is passed to a hydrothermal process. The pH of the treated waste activated sludge is then increased, and the nitrogen is stripped and recovered as an ammonium salt. A low nitrogen stream with volatile fatty acids and soluble organics is then separated and fed to the aerobic digester. Biogas generated during anaerobic digestion provides energy for heating the waste activated sludge for the hydrothermal process, and reject heat from the hydrothermal process heats the primary sludge for thermophilic anaerobic digestion.

**20 Claims, 5 Drawing Sheets**






FIG. 1




FIG. 2



	DTPD	WTPD	SOLIDS %	IPM	GPM	PRES. PSIA	PRES. BAR	TEMP C	TEMP F	DENSITY KG/M <sup>3</sup>
A PRIMARY SLUDGE FROM CLARIFIER	50	3,333	1.5%	2,023	534	14.7	1.0	20	68	998
B THICKENED PRIMARY SLUDGE*	50	833	6.0%	506	133	14.7	1.0	20	68	998
C THICKENER RETURN	-	2,500	0.0%	1,517	400	14.7	1.0	20	68	998
D HEATED PRIMARY SLUDGE TO DIGESTER	50	883	6.0%	514	136	14.7	1.0	60	140	993
E DIGESTED PRIMARY SLUDGE	20	803	25%	495	131	14.7	1.0	60	140	993
F BIGAS FROM DIGESTER	30	-	100%	-	-	14.7	1.0	60	140	993
G DEWATERED CLASS A SLUDGE	20	80	2.5%	49	13	14.7	1.0	60	140	993
H DEWATERING RETURN	-	703	0.0%	431	114	14.7	1.0	60	140	993
I WAS FROM CLARIFIER	50	5,556	0.9%	3,405	899	14.7	1.0	20	68	998
J WAS FROM GRAVITY THICKENER	50	1,429	3.5%	876	231	14.7	1.0	20	68	998
K GRAVITY THICKENER RETURN	-	4,127	-	2,529	668	14.7	1.0	20	68	998
L WAS FROM BELT THICKENER	50	833	6.0%	511	135	14.7	1.0	20	68	998
M BELT THICKENER RETURN	-	3,294	-	2,019	533	14.7	1.0	20	68	998

FIG. 3A

#	DTPD	WTPD	SOLIDS %	IPM	GPM	PRES. PSIA	PRES. BAR	TEMP C	TEMP F	DENSITY KG/M <sup>3</sup>
1	50	833	6.0%	511	135	14.7	1.0	20	68	998
1a	50	833	6.0%	518	135	14.7	1.0	57	135	984
2	-	80.4	-	49	13	1,246	85.9	300	572	712
2a	50	914	5.5%	706	186	862	59.5	255	491	791
3	50	914	5.5%	736	194	862	59.5	275	527	759
4	50	914	5.5%	736	194	862	59.5	275	527	759
5	50	914	5.5%	599	158	862	59.5	133	271	932
6	4	12	33.3%	6.3	1.7	862	59.5	20	68	998
7	50	926	5.4%	591	156	862	59.5	100	212	958
8	45.8	873	5.2%	557	147	25	-	100	212	958
9	4.3	48	8.8%	33,805	8,922	25	1.7	100	212	0.983
10	45.8	873	5.2%	538	142	14.7	1.0	40	104	992

FIG. 3B

#	DTPD	WTPD	SOLIDS %	IPM	GPM	PRES. PSIA	PRES. BAR	TEMP C	TEMP F	DENSITY KG/M <sup>3</sup>
11	22.9	254	9.0%	157	41	14.7	1.0	40	104	992
12	18.3	619	3.0%	382	101	14.7	1.0	40	104	992
13	6.9	69	10%	42	11	14.7	1.0	40	104	992
14	11.4	550	2.1%	339	90	14.7	1.0	40	104	992
15	18.3	25	74%	15	4	14.7	1.0	40	104	992
16	16.5	18	94.0%	11	3	14.7	1.0	40	104	992
17	-	38	-	40,389	10,660	14.7	1.0	100	212	0.598
18	20.8	28	75.0%	18	5	14.7	1.0	100	212	958
19	-	38	-	24	6	14.7	1.0	70	158	978
20	-	80.4	-	1,099	-	1,246	85.9	300	572	46
21	-	59.5	-	814	-	1,246	85.9	300	572	46

FIG. 3C



## SEWAGE TREATMENT SYSTEM

## BACKGROUND OF THE INVENTION

This invention relates to a sewage treatment system and, more particularly to a wastewater treatment system.

Wastewater treatment systems are well known in the art. Typical wastewater treatment systems generate raw primary sludge and waste activated sludge, which they typically thicken, heat, and digest in anaerobic digesters. Anaerobic digesters are typically operated under mesophilic conditions, from approximately 20° C. to approximately 35° C., and the product from these digesters is typically dewatered to produce Class B sludge. The Class B sludge is typically hauled away to land application or is composted or lagooned to produce a Class A sludge. The National Institute of Occupational Safety and Health (NIOSH) has classified Class B sludge as a biohazard, so the wastewater treatment industry is moving away from producing Class B sludge and toward producing Exceptional Quality Class A sludge (EQ Class A). The present invention combines a number of known elements in new and creative ways with a surprising synergy of mechanical, thermal, and chemical integration to generate EQ Class A sludge at low capital and operating cost.

U.S. Pat. No. 5,221,486, issued in 1993 to Fassbender, U.S. Pat. No. 5,433,868, issued in 1995 to Fassbender, U.S. Pat. No. 5,785,852, issued in 1998 to Rivard et al. in 1998, and U.S. Pat. No. 6,143,176, issued in 2000 to Nagamatsu et al., describe and disclose a number of prior art approaches to wastewater treatment systems. The disclosures of U.S. Pat. Nos. 5,221,486, 5,433,868, 5,785,852, and 6,143,176 are incorporated herein by reference. Waste activated sludge is more difficult to dewater and digest because of its hydrophilic and cellular nature. To address this problem, the '852 patent discloses the use of low temperature heat, in the range from 180° F. to 385° F., and explosive flash and shear forces to disrupt cells so that the soluble material in the cells is released and available for anaerobic digestion. The '868 patent describes a process in which a combined stream of waste activated sludge and primary sludge is treated at high temperature hydrothermal conditions to produce oil, char, and an ammonia containing wastewater stream. The wastewater stream is further processed with another hydrothermal process to convert the ammonia to nitrogen gas. The '176 patent describes the use of a hydrothermal process for heating anaerobically digested sludges to generate a carbon slurry that is dewatered to provide a concentrated carbon slurry of char and oil having a high heating value. The aqueous phase separated from the carbon slurry to form the concentrated carbon slurry is returned for additional anaerobic digestion.

These systems offer a number of advantages in processing wastewater. They generally do a relatively good job of recovering valuable resources from wastes and of reducing the amounts of such wastes that must be sent to landfills. Still, they suffer from a number of disadvantages. For example, because the sludges contain large amounts of water, subjecting both a primary sludge and a waste activated sludge to one or more hydrothermal processes requires a great deal of energy just to heat and cool the water contained therein. Combining the primary sludge and waste activated sludge in an anaerobic digester would result in a large energy demand to heat the anaerobic digester feed, particularly if the anaerobic digester is to be operated under more desirable thermophilic conditions. Combining the primary sludge and waste activated sludge in an anaerobic

digester would also tend to force an operator to choose between undesirably increased capital cost or undesirably decreased treatment time. Similarly, combining the primary sludge and waste activated sludge in the anaerobic digester would also force an operator to choose between undesirably increased operating costs for heating or undesirably low operating temperature, perhaps leading to the use of acceptable but less desirable mesophilic conditions rather than thermophilic conditions. Further, the primary sludge typically includes more solids and particulate matter that is hard on equipment operating at high temperature and pressure, such as the conditions typically encountered in hydrothermal processes. Again, heating both the primary sludge and the waste activated sludge to the high temperatures called for in a hydrothermal process requires a great deal of energy. Also, in systems that use aerobic and anoxic zones in a digester to treat the water effluent and generate the waste activated sludge, maintaining optimal conditions for the nitrate reducing and phosphorous accumulating bacteria in the aerobic/anoxic digester typically requires additional raw sewage to be fed into the aerobic/anoxic digester or that a water soluble carbon source such as methanol feed stream be provided. Further still, the sludges often cause clogging or fouling problems, as they are being prepared for and passed to and through hydrothermal processes. This common problem typically leads to the use of scraped surface heat exchangers in an effort to combat or counter such problems. Also, because the primary sludge and waste activated sludge are typically treated together or at similar temperature ranges, there is little or no opportunity for efficient heat transfer between the two to offset operating expenses.

## SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a waste treatment system that takes advantage of surprising synergy of mechanical, thermal, and chemical integration to generate an EQ Class A biosolid at low capital and operating costs.

It is a further object of the present invention to provide a system of the above type that uses thermal energy from generated biogas to supply heat for a hydrothermal process.

It is a still further object of the present invention to provide a system of the above type that uses thermal energy from generated biogas to supply between 50 to 100 percent of the heat energy required for the hydrothermal process.

It is a still further object of the present invention to provide a system of the above type that uses thermal energy from a hydrothermal process to provide heat for operating an anaerobic digester at thermophilic conditions.

It is a still further object of the present invention to provide a system of the above type that uses thermal energy from generated biogas twice, first to provide heat for a hydrothermal process and then to provide heat for an anaerobic digester.

It is a still further object of the present invention to provide a system of the above type that allows for increased operating temperatures and retention times in an anaerobic digester without undesirable increases in capital or operating costs.

It is a still further object of the present invention to provide a system of the above type that significantly increases sludge retention time available at an existing anaerobic digestion facility.

It is a still further object of the present invention to provide a system of the above type that provides for the production of EQ Class A biosolids by increasing ferment-



tation temperature and duration without undesirably increasing capital and operating costs.

It is a still further object of the present invention to provide a system of the above type that reduces the amount of feed material that must be heated to high temperatures in a hydrothermal process.

It is a still further object of the present invention to provide a system of the above type that strips nitrogen from a waste activated sludge, and recovers the nitrogen in the form of an ammonia-water solution or an ammonium salt, without the need for a separate hydrothermal process.

It is a still further object of the present invention to provide a system of the above type that provides for enhanced performance of bacteria in the aerobic/anoxic digester.

It is a still further object of the present invention to provide a system of the above type that offers enhanced biological nitrogen removal and biological phosphorus removal in the aerobic/anoxic digester.

It is a still further object of the present invention to provide a system of the above type to recover a low nitrogen stream containing volatile fatty acids and soluble organics for recycle to the aerobic/anoxic digester.

It is a still further object of the present invention to provide a system of the above type that reduces or eliminates fouling and clogging problems encountered in processing sludges in a hydrothermal process.

It is a still further object of the present invention to provide a system of the above type that uses staged heating for the hydrothermal process to avoid fouling and clogging problems while reducing boiler feed water consumption, further reducing capital and operating costs.

It is a still further object of the present invention to provide a system of the above type that reduces or eliminates the amount of grit, solids, and large particulates that must be pumped through process equipment, particularly through hydrothermal process equipment that is operated at high temperatures and pressures, thereby reducing capital costs and increasing reliability.

Toward the fulfillment of these and other objects and advantages, in a system of the present invention, a waste stream is separated into a primary sludge and a water effluent, and the primary sludge is anaerobically digested and dewatered to produce a Class A biosolid. The water effluent is digested in a digester having aerobic and anoxic zones and excess bacteria are separated to provide a waste activated sludge. The waste activated sludge is heated in a two-stage process with steam injection and indirect steam to approximately 255° C. before it is passed to a hydrothermal process. The pH of the treated waste activated sludge is then increased, and the nitrogen is stripped as an ammonium salt. A low nitrogen stream with volatile fatty acids and soluble organics is then separated and fed to the aerobic digester. Biogas generated during anaerobic digestion of the primary sludge provides energy for heating the waste activated sludge for the hydrothermal process, and reject heat from the hydrothermal process heats the primary sludge for thermophilic anaerobic digestion.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above brief description, as well as further objects, features and advantages of the present invention will be more fully appreciated by reference to the following detailed description of the presently preferred but nonetheless illustrative embodiments in accordance with the present inven-

tion when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a flow chart showing a waste treatment system of the present invention;

FIG. 2 is a flow chart focusing on the treatment of waste activated sludge according to the present invention; and

FIG. 3 is a table showing theoretical mass balances and operating conditions of the systems depicted in FIGS. 1 and 2.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 1, the reference numeral **100** refers in general to a system of the present invention. According to the present invention, an aqueous waste stream **102**, such as raw sewage, wastewater, or the like is first subjected to pretreatment using equipment such as a bar screen and grit chamber (not shown) for removing much of the larger particulate matter. The pretreated waste stream **102** passes to a primary clarifier **104** where it is separated into a primary sludge, containing the bulk of the readily settleable material and a water effluent containing dissolved and suspended material. Pound for pound, the primary sludge will have most of the chemical energy of the waste stream. The water effluent will have significantly more nitrogen, approximately twice as much as the primary sludge.

The primary sludge is then passed to a gravity thickener **106** to remove some of the water. The primary sludge typically dewateres or thickens relatively easily to approximately 5%–9% solids by weight, most typically to approximately 5% solids by weight. Water is removed and passed via thickener return **108** to the primary clarifier **104**. The thickened primary sludge then passes through a heat exchanger **110** to heat the thickened primary sludge as the thickened primary sludge passes to the anaerobic digester **112**. The thickened primary sludge is preferably heated to a temperature so that the anaerobic digester **112** may operate under thermophilic or mesophilic conditions and is more preferably heated to a temperature so that the anaerobic digester **112** may operate under thermophilic conditions. The thickened primary sludge is heated to a temperature that is preferably greater than or equal to approximately 20° C., that is more preferably greater than or equal to approximately 40° C., and that is most preferably greater than or equal to approximately 60° C. Treating the thickened primary sludge in the anaerobic digester **112** yields a biogas and a digested primary sludge. Using staged anaerobic digestion of the thickened primary sludge typically yields up to approximately 63% conversion of volatile organics, and the anaerobic digestion process is highly resistant to shocks. The biogas passes to a boiler **114** for reasons to be described below. The digested primary sludge then passes to dewatering equipment **116**. The dewatering equipment **116** produces a stream **118** that is primarily water, which is returned to the primary clarifier **104**. The dewatered sludge from the dewatering equipment **116** is preferably a Class A biosolid and is more preferably an EQ Class A biosolid. This dewatered biosolid has a solid content that is preferably greater than or equal to approximately 20% by weight and that is more preferably greater than or equal to approximately 25% by weight.

The water effluent passes to an aerobic digester **120**, such as an aeration basin or tank. The aerobic digester is preferably operated with aerobic and anoxic zones. The digested water effluent passes to a secondary clarifier **122** and is separated into a treated water discharge **124**, a return acti-



vated sludge, and a waste activated sludge. The return activated sludge contains a large fraction of the bacteria that passes from the aerobic digester **120** to the secondary clarifier **122**, although some of the bacteria is present in the waste activated sludge. Waste activated sludge is more difficult to dewater or thicken than the primary sludge. Waste activated sludge may typically be thickened to a solids content of approximately 3% to approximately 6% by weight. The waste activated sludge passes to and through a gravity thickener **126** and a belt thickener **128** and is dewatered or thickened to a solids content that is preferably approximately 5% weight and that is more preferably approximately 6% by weight. The high water content requires larger flows but provides properties close to those of water for heat transfer purposes. Water removed from the waste activated sludge by the gravity and belt thickeners **126** and **128** may be returned to the primary clarifier **104** via streams **130** and **132** respectively. The waste activated sludge contains approximately half of the solids that were originally contained in the raw waste stream but contains significantly less grit and large particulate matter than the primary sludge, so the waste activated sludge is better suited for pumping through process equipment, particularly at high temperatures and pressures. This reduces the capital costs, reduces wear and tear, and increases the reliability of the system **100**.

The thickened waste activated sludge passes to the sludge conditioner and pump **134** and is pumped through heat exchangers **136** and **138** and into the reactor **140** for carrying out the hydrothermal process. As mentioned above, biogas from the anaerobic digester **112** is passed to the boiler **114** and where it is combusted to convert water to steam. The biogas generated by the anaerobic digester **112** is capable of providing between approximately 50% to approximately 100% of the heat energy needed for the hydrothermal process. This significantly reduces the operating costs of the system **100**. Further, because only the waste activated sludge is subjected to a hydrothermal process, the energy required to operate the system **100** is significantly lower than would be needed if the primary sludge and waste activated sludge were both subjected to a hydrothermal process.

As best seen in FIG. 2, the boiler **114** supplies steam to a steam injector **136** and to an indirect steam heater **138**. This two-stage heating process helps to reduce or eliminate fouling or clogging conditions that are often encountered when subjecting a sludge to a hydrothermal process. When a sludge is heated it will often exhibit an undesirable degree of stickiness while it is within a temperature range of from approximately 60° C. to approximately 120° C., with this stickiness being more obvious while it is within a range of from approximately 68° C. to approximately 105° C. The thickened waste activated sludge of the present invention is therefore supplied to the steam injector **136** at a temperature that is preferably less than or equal to approximately 68° C., that is more preferably less than or equal to approximately 60° C., and that is most preferably approximately 57° C. Steam is injected into the thickened waste activated sludge to provide for extremely rapid heat transfer so that the stream almost instantaneously is heated to a temperature that is preferably greater than or equal to approximately 255° C., that is more preferably greater than or equal to approximately 120° C., and that is most preferably greater than or equal to approximately 105° C.

The boiler **114** also supplies steam to the indirect steam heat exchanger **138**, such as a shell and tube type heat exchanger. As the preheated waste activated sludge passes through the indirect steam heat exchanger **138**, it is passed

in a heat exchange relationship with steam from the boiler **114** and then in a counter-current heat exchange relationship with a stream exiting the hydrothermal process reactor **140**. In the indirect steam heat exchanger **138**, the waste activated sludge is heated to a temperature that is preferably greater than or equal to approximately 200° C., that is more preferably greater than or equal to approximately 250° C. and that is most preferably greater than or equal to approximately 275° C. Using indirect steam heating reduces boiler **114** feed water consumption and further reduces capital and operating costs.

In the hydrothermal process reactor **140**, the waste activated sludge is subjected to high temperature and pressure conditions to change the chemical composition of the stream. Any number of different hydrothermal processes may be used, including but not limited to a sludge-to-oil reactor system (STORS) process. A variety of common hydrothermal processes are discussed in more detail in U.S. Pat. Nos. 5,221,486, 5,433,868, and 6,143,176, the contents of which are incorporated herein by reference. As mentioned before, the effluent of the hydrothermal process reactor **140** passes through the heat exchanger **138** in counter-current flow with the preheated waste activated sludge before being further treated for nitrogen removal and the like.

The effluent from the hydrothermal process reactor **140** then passes to an inline mixer **142** in which a base such as sodium hydroxide is added to raise the pH. From the inline mixer **142**, the stream passes to a flash valve and gas separator **144**, and a vapor emission is flashed that is composed primarily of carbon dioxide gas with small amounts of hydrogen sulfide, ammonia, and the like. The flashed vapor passes to a pebble bed ammonia absorber **146**, and sulfuric acid is added to lower the pH, which facilitates stripping nitrogen from the flashed vapor in the form of an ammonium salt solution, such as an ammonium sulfate solution. Vapor from the pebble bed ammonia absorber **146** is further treated, such as by passing it to a gas scrubber cooler **148**, adding process water, and passing it for disposal or additional wastewater treatment processing. Using a simple process of raising the pH and stripping nitrogen in the form of ammonia and recovering an ammonium salt is much more energy efficient than subjecting the stream to yet another hydrothermal reaction to release the nitrogen in the form of nitrogen gas.

The reactor effluent from the flash valve and gas separator **144** is then passed to the heat exchanger or effluent cooler **110** where it is placed in an indirect heat exchange relationship with the primary sludge. The thickened primary sludge from gravity thickener **106** acts as a heat sink for the reject heat from the hydrothermal process. The thermal energy required to heat the primary sludge to the desired temperature for thermophilic anaerobic digestion corresponds closely to the energy available from the reactor effluent leaving the hydrothermal process. There is also a sufficient temperature difference between the streams to allow for efficient heat transfer. Using the reject heat from the hydrothermal process significantly reduces the operating costs of the system **100**. Further, because only the thickened primary sludge is heated for anaerobic digestion, the energy required to operate the system **100** is significantly lower than would be required if the primary sludge and the waste activated sludge were both subjected to thermophilic anaerobic digestion. It is of course understood that the reactor effluent from the flash valve and gas separator **144** may provide thermal energy to the primary sludge in any number of different ways. For example, the reactor effluent may be used to heat water that is stored in a tank and used as needed.



The cooled reactor effluent leaves the heat exchanger **110** and passes to a settling tank **150**. Settled solids are removed and dewatered, such as using a plate and frame dewatering press **152**, or similar dewatering equipment **1116**, to produce a char only or an oil and char fuel product. The fuel may be used in any number of ways, including to further offset operating costs of the system **100** if desired. The dissolved and suspended solids pass from the settling tank **150** to filtering equipment **154**, such as a vibratory filter. The concentrated solids from the filtering equipment **154** may be passed to the thickened primary sludge. Stream **14** is a low nitrogen stream containing volatile fatty acids and soluble organics. It may be passed for further wastewater treatment processing, but at least a portion of this stream is preferably passed to the aeration basin or tank **120** to aid in aerobic/anoxic digestion. In that regard, this stream is beneficial to bacteria in an anoxic zone of the aeration tank **120** and can reduce or eliminate the need to add raw sewage or the need to add methanol to the aeration tank **120**. The stream enhances biological nitrogen removal and biological phosphorus removal during aerobic/anoxic digestion.

Other modifications, changes and substitutions are intended in the foregoing, and in some instances, some features of the invention will be employed without a corresponding use of other features. For example, the primary sludge and waste activated sludge may both be subjected to the hydrothermal process, in which case nitrogen may be removed from the treated, combined sludge product by raising the pH and stripping the nitrogen in the form of ammonia gas for recovery as an ammonium salt. Further, the settled cooled stream from the settling tank **150** may be passed to its own separate dewatering equipment **152** or to the dewatering equipment **116** used to treat the digested primary sludge. Although clarifiers **104** and **122** and thickeners **106**, **126**, and **128** have been described, it is understood that any number of different types and kinds of equipment may be used to obtain the separation and filtration as needed. Further, although it is preferred to use a two-stage heating process with steam injection and indirect steam heating to prepare the waste activated sludge for the hydrothermal process, it is understood that either steam injection or indirect steam heating may be used in a single stage process. Further still, the use of direct steam injection to avoid fouling or clogging problems may be used in connection with a wide variety of hydrothermal processes or other sludge treatment steps to avoid similar problems when the sludge to be processed falls within the specified temperature ranges, regardless of whether other features of the present invention are also used. It is also understood that all quantitative information given is by way of example only and is not intended to limit the scope of the present invention. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

What is claimed is:

**1.** A method, comprising:

- (1) separating a waste stream into a primary sludge and a water effluent;
- (2) anaerobically digesting said primary sludge and dewatering said digested primary sludge to convert said primary sludge to a Class A biosolid without subjecting said primary sludge to a hydrothermal process;
- (3) aerobically digesting said water effluent;
- (4) separating said digested water effluent to provide a waste activated sludge; and
- (5) treating said waste activated sludge using a hydrothermal process without subjecting said waste activated sludge to anaerobic digestion.

**2.** The method of claim **1**, further comprising:

after step (4), heating said waste activated sludge to a temperature that is greater than or equal to approximately 200° C.

**3.** The method of claim **1**, further comprising:

after step (4), heating said waste activated sludge to a temperature that is greater than or equal to approximately 240° C.

**4.** The method of claim **1**, further comprising:

after step (4), injecting steam into said waste activated sludge to preheat said waste activated sludge from a first temperature that does not exceed approximately 60° C. to a second temperature that is greater than or equal to approximately 105° C.

**5.** The method of claim **1**, further comprising:

after step (4), injecting steam into said waste activated sludge to preheat said waste activated sludge from a first temperature that does not exceed approximately 68° C. to a second temperature that is greater than or equal to approximately 120° C.

**6.** The method of claim **4**, further comprising:

heating said preheated waste activated sludge from said second temperature to a third temperature that is greater than or equal to approximately 200° C.

**7.** The method of claim **4**, further comprising:

heating said preheated waste activated sludge from said second temperature to a third temperature that is greater than or equal to approximately 250° C.

**8.** The method of claim **1**, further comprising:

(6) generating heat from a biogas created during said anaerobic digestion of said primary sludge; and

(7) before step (5), transferring said generated heat to said waste activated sludge.

**9.** The method of claim **8**, wherein:

step (6) comprises, combusting said biogas and transferring heat from combustion of said biogas to water to produce steam; and

step (7) comprises, before step (5), transferring heat from said steam to said waste activated sludge.

**10.** The method of claim **8**, further comprising:

after step (5), transferring heat from said treated waste activated sludge to said primary sludge.

**11.** The method of claim **1**, further comprising:

(6) after step (5), raising a pH of said treated waste activated sludge; and

(7) after step (6), stripping an ammonium salt from said treated waste activated sludge.

**12.** The method of claim **1**, wherein:

step (3) comprises aerobically digesting said water effluent in an aeration tank; and further comprising:

after step (5), separating said treated waste activated sludge to provide a low nitrogen stream comprising volatile fatty acids and soluble organics; and

feeding said stream to said aeration tank.

**13.** A method comprising:

(1) providing a waste stream comprising at least one nitrogen containing compound, said waste stream being at a first temperature that is less than or equal to approximately 60° C.;

(2) injecting steam into said waste stream to preheat said waste stream to a second temperature that is greater than or equal to approximately 255° C.; and

(3) subjecting said preheated waste stream to indirect steam heating to heat said preheated waste stream to a



9

third temperature that is greater than or equal to approximately 275° C.

14. The method of claim 13, wherein said first temperature is less than or equal to approximately 68° C. and said second temperature is greater than or equal to approximately 255° C. 5

15. The method of claim 13, wherein:

said waste stream comprises a waste activated sludge; and step (1) comprises:

providing a wastewater stream; 10

separating said wastewater stream into a primary sludge and a water effluent;

aerobically digesting said water effluent;

separating said waste activated sludge from said digested water effluent; and 15

providing said waste activated sludge at said first temperature.

16. The method of claim 15, further comprising:

anaerobically digesting said primary sludge to generate a biogas; 20

combusting said biogas to generate heat; and

transferring said biogas heat to water to generate said steam that is injected into said waste activated sludge. 25

17. A method, comprising:

(1) separating a waste stream into a primary sludge and a water effluent;

(2) anaerobically digesting said primary sludge to generate a biogas; 30

(3) treating said water effluent to create a waste activated sludge;

(4) combusting said biogas;

(5) transferring heat from said combustion of said biogas to said waste activated sludge to create a heated waste activated sludge; and 35

10

(6) passing said heated waste activated sludge through a heat exchanger to provide indirect heat transfer from said heated waste activated sludge to said primary sludge.

18. The method of claim 17, wherein step (5) comprises: transferring heat from said combustion of said biogas to said waste activated sludge to create said heated waste activated sludge having a first temperature, said first temperature being greater than or equal to approximately 200° C.

19. The method of claim 17, wherein step (5) comprises: transferring heat from said combustion of said biogas to said waste activated sludge to create said heated waste activated sludge having a first temperature, said first temperature being greater than or equal to approximately 250° C.

20. The method of claim 17, wherein:

step (3) comprises, treating said water effluent to create a waste activated sludge, said waste activated sludge having a first temperature that is less than or equal to approximately 60° C.; and

step (5) comprises:

transferring heat from said combustion of said biogas to water to generate steam;

injecting a first portion of said steam into said waste activated sludge to preheat said waste activated sludge to a second temperature that is greater than or equal to approximately 105° C.; and

placing a second portion of said steam in an indirect heat exchange relationship with said preheated waste activated sludge to heat said preheated waste activated sludge from said second temperature to a third temperature that is greater than or equal to approximately 200° C.

\* \* \* \* \*