

US006895006B1

(12) **United States Patent**
Tasaki et al.

(10) **Patent No.:** **US 6,895,006 B1**
(45) **Date of Patent:** **May 17, 2005**

(54) **UNICAST/MULTICAST SYSTEM**

(75) Inventors: **Yuuichi Tasaki**, Tokyo (JP); **Kazuhiko Isoyama**, Tokyo (JP)

(73) Assignee: **Juniper Networks, Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 752 days.

(21) Appl. No.: **09/676,559**

(22) Filed: **Oct. 2, 2000**

(30) **Foreign Application Priority Data**

Oct. 1, 1999 (JP) 11-281549

(51) **Int. Cl.⁷** **H04L 12/28**

(52) **U.S. Cl.** **370/390; 370/392; 370/395.31**

(58) **Field of Search** 370/270, 351, 370/389, 390, 392, 395.1, 398, 395.2, 395.3, 395.31, 395.32, 412, 417, 418, 428, 429

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,267,235 A * 11/1993 Thacker 370/396

6,115,379 A * 9/2000 Flanders et al. 370/392
6,212,182 B1 * 4/2001 McKeown 370/390
6,349,097 B1 * 2/2002 Smith 370/390

FOREIGN PATENT DOCUMENTS

JP A 5-136814 6/1993
JP A 5-236011 9/1993
JP A 8-251173 9/1996
JP A 9-93257 4/1997
JP A 10-190663 7/1998

* cited by examiner

Primary Examiner—John Pezzlo

Assistant Examiner—D Levitan

(74) *Attorney, Agent, or Firm*—Harrity & Snyder, L.L.P.

(57) **ABSTRACT**

A unicast/multicast system has an internal cell generating section that generates an internal cell to include its output index information based on user data, and an output port conversion table that stores the relation of output index information and output port number for the internal cell in the form of one-to-one for the unicast and one-to-multiple for the multicast.

7 Claims, 6 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3





FIG. 7






FIG. 4

FIG. 5


OUTPUT PORT NUMBER

	1	1	1	1	1	1	0	9	7	6	5	4	3	2	1	0
	5	4	3	2	1	0	0	9	7	6	5	4	3	2	1	0
001 _H	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
002 _H	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
003 _H	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0
004 _H	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0
005 _H	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
006 _H																
00F _H	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
010 _H	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1
011 _H	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1
012 _H	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1
⋮																
⋮																
⋮																
⋮																
⋮																
⋮																
FFF _H																

FOR UNICAST

FOR MULTICAST

FIG. 6



1

UNICAST/MULTICAST SYSTEM

FIELD OF THE INVENTION

This invention relates to a system for unicasting or multicasting IP packets. ATM cells etc.

BACKGROUND OF THE INVENTION

As a switch for processing a multicast cell, for example. Japanese patent application laid-open No.9-162879 (1997) discloses a shared buffer type ATM. This ATM switch has address buffers provided for its output ports, respectively. The multicast is conducted by sequentially transferring the address pointer of a shared buffer where a multicast cell is stored. Also, the ATM switch needs to be provided with a counter for confirmation of the number of broadcast to be decremented every time a multicast cell is output.

However, the ATM switch has problems below.

The first problem is that it is necessary to provide a large amount of the buffer for multicast so as to cope with a case that the ratio of multicast calls in traffic increases.

The second problem is that it may cause the lowering of throughput since the subsequent multicast processing cannot be run before the counter for confirmation of the number of broadcast becomes zero.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide a unicast/multicast system that allows a unicast cell and a multicast cell to be processed in the same circuit.

According to the invention, a unicast/multicast system, comprises:

an internal cell generating section that generates an internal cell based on user data;

an internal cell receiving section that outputs the internal cell to a timing generating section and outputs a header field of the internal cell to an index search section;

an output port conversion table that stores the relation of output index information and output port number in the form of one-to-one for the unicast and one-to-multiple for the multicast;

the index search section that extracts output index information from the header field to be sent from the internal cell receiving section, refers to the output port conversion table for an output port number corresponding to the output index information extracted, and outputs the output port number obtained from the output port conversion table to a destination-based distribution section;

the destination-based distribution sections that controls a gate section based on the output port number input from the index search section;

a timing generating section that delays the internal cell input from the internal cell receiving section and then outputs it the gate section;

the gate section that distributes the internal cell input from the timing generating section to the gate section according to the control of the destination-based distribution section;

a plurality of buffers that each store the internal cell distributed from the gate section and, when receiving the internal cell distributed from the gate section, sends switching request signal to a switching request adjusting section;

2

the switching request adjusting section that adjusts the switching request signal input from the buffers between the buffers and determines a route in a crosspoint switch; and

the crosspoint switch that outputs the internal cell stored in the buffers through the route determined by the switching request adjusting section.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be explained in more detail in conjunction with the appended drawings, wherein:

FIG. 1 is a block diagram showing the schematic composition of a unicast/multicast system in a preferred embodiment according to the invention;

FIG. 2 is a flow chart showing the operation of the unicast/multicast system in FIG. 1;

FIG. 3 is a format diagram showing an internal cell used in the unicast/multicast system in the embodiment of the invention;

FIG. 4 is a block diagram showing the composition of a unicast/multicast system in a first preferred embodiment according to the invention;

FIG. 5 is a table showing the content of a memory 13B in FIG. 4;

FIG. 6 is a block diagram showing the composition of a unicast/multicast system in a second preferred embodiment according to the invention; and

FIG. 7 is a format diagram showing an internal cell used in the unicast/multicast system in FIG. 6.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The preferred embodiments of the invention will be explained below, referring to the drawings.

FIG. 1 is a block diagram showing the schematic composition of a unicast/multicast system according to the invention. In FIG. 1, **10** is an internal cell generating section to generate a cell (hereinafter referred to internal cell) with a fixed length and a specific format dedicated to switching, based on user data such as IP packet (Internet protocol), ATM (asynchronous transfer mode) cell etc. **11** is an internal cell receiving section that has a function to extract a header field from the internal cell. **12** is an index search section to get output port information corresponding to output index information included in the header field by referring to an output port conversion table **13**. **13** is the table to store multiple index information and multiple output port number information in the form of one-to-one for the unicast and one-to-multiple for the multicast. **14** is a timing generating section to make the output of internal cell delay a predetermined time. **15** is a gate section that functions as a route to buffers **17-1** to **17-n** to store the internal cell. **16** is a destination-based distribution section that controls the gate section **15** according to the output port information. **17-1** to **17-n** are the FIFO (first-in first-out) type buffers that are provided for output ports, respectively, and store the internal cell for corresponding one of the output ports. Optionally, the buffers **17-1** to **17-n** may be divided into buffers for the unicast and buffers for the multicast. **19** is a switching request adjusting section that controls a crosspoint switch **20** according to a switching request from the buffers **17-1** to **17-n**.

Referring to FIGS. 1, 2 and 3, the operation of the unicast/multicast system explained above will be explained below.

3

The internal cell generating section **10** converts global user data such as IP packet and ATM cell into internal cell. As shown by a format diagram in FIG. 3, an internal cell **40** is composed of a header field **41** and a data field **42**. The header field **41** stores destination information such as VPI/VCI (virtual path identifier/virtual channel identifier) etc. that is converted into particular and simple form so that the internal cell is correctly subject to the switching inside the unit. The data field **42** stores the original user data. The internal cell receiving section **11** receives the internal cell **40** (step S11). Then, the internal cell receiving section **11** sends the header field **41** of the received internal cell **40** to the index search section **12**, and sends the entire internal cell **40** to the timing generating section **14** (step S12). The index search section **12** extracts output index information from the header information of the header field **41** (step S15). After extracting the output index information of the header field **41**, the index search section **12** gets output port number by referring to the output port conversion table **13** (step S16). The index search section **12** sends the obtained output port number to the destination-based distribution section **16**. The destination-based distribution section **16** controls the gate section **15** according to the output port number received from the index search section **12** (step S17). In this case, when only one output port number is obtained, the gate to one output port opens, and when multiple output port numbers are obtained, the gates to multiple output ports open. On the other hand, the timing generating section **14** makes the internal cell sent to the timing generating section **14** delay the predetermined time that is necessary for the index search section **12** to search the output port number and for the destination-based distribution section **16** to control the gate section **15** (step S13). After the route of gate section **15** is determined, the internal cell is stored, through the gate section **15**, into a specific buffer **17-i** ($1 \leq i \leq n$) corresponding to the output port in case of the unicast, and into multiple buffers **17-i₁**, . . . , **17-i_m** ($i_1 \geq 1$ and $i_m \leq n$) in case of the multicast (step S14, S18). After the internal cell is stored in the buffer **17-i** or buffers **17-i₁**, . . . , **17-i_m**, the buffer **17-i** or buffers **17-i₁**, . . . , **17-i_m** sends the switching request to the switching request adjusting section **19** (step S19). The switching request adjusting section **19** conducts fairly the adjustment to the switching request received from the multiple buffers **17-1** to **17-n** in a unit time, and determines the route of the crosspoint switch **20** (step S20). The crosspoint switch **20** establishes the route to pass the internal cell based on the route information from the switching request adjusting section **19**, and conducts the switching of the internal cell (step S21).

First Embodiment

A unicast/multicast system in the first preferred embodiment according to the invention will be explained below, referring to FIGS. 4 and 5.

In this embodiment, as the output port conversion table **13**, a memory **13B** such as RAM (random access memory) or ROM (read-only memory) is used. In this case, the output index information to be extracted by a memory reading control circuit **12B** to function as the index search section **12** corresponds to an address of the memory **13B**, and the output port number corresponds to data to be written in each address of the memory **13B**. Also, the memory **13D** also functions as the destination-based distribution section **16**. The output port number is stored in the form of bit pattern so as to facilitate the control of the gate section **15B**. In case of the bit pattern form, the number n of ports corresponds to the data width of the memory **13B**. Therefore, when a

4

complete unicast region is, in advance, made using a memory of wide data width, it can cope with even such a case that the number n of ports increases, by adding bit pattern information for the multicast to the memory **13B**.

FIG. 5 shows an example of the content of the memory **13B** in a case that there are 4095 ($\approx 2^{12} \cdot 1$) types of output index information and there are **16** output ports. According to need, the output index information can be expanded to 65535 ($\approx 2^{16} - 1$) types. The address range of 000H to 00FH is used for the unicast, and the address range of 010H to FFFH is used for the multicast. In this way, bit patterns of "1" for only one bit are used for the unicast, and bit patterns of "1" for multiple bits are used for the multicast. Therefore, by using the composition and operation for the multicast, the unicast can be also handled.

When the memory reading control circuit **12B** receives a header field from the internal cell receiving section **10**, it extracts the output index information from the header field and then conducts the read operation to the memory **13B** using the extracted output index information as address. In reply to this, the memory **13B** outputs, as output port number, data corresponding to the output index information (\approx memory address). The gate section **15B** allows a buffer corresponding to a bit with "1" of the data output from the memory **13B** to be enabled.

On the other hand, an internal cell sent to a delay circuit **14B** is delayed in the delay circuit **14B** during the processing time required to determine the route of the gate section **15B**. After the internal route of the gate section **15B** is determined, the internal cell is output from the delay circuit **14**, passing through the enabled buffer of the gate section **15B**, written into only a FIFO type buffer corresponding to the enabled buffer. In case of the multicast, they are written into multiple FIFO buffers of the FIFO buffers **17-1** to **17-n**, and in case of the unicast, it is written into one FIFO buffer of the FIFO buffers **17-1** to **17-n**.

Second Embodiment

In the second preferred embodiment of the invention, even in a case that a multicast cell is desired to be subject to the priority switching, it is not necessary to provide separate circuits for the unicast and multicast in an existing circuit composition.

Referring to FIGS. 6 and 7, the second embodiment will be explained below.

FIFO buffers **17C-1** to **17C-n** are provided for output ports, respectively, and FIFO buffers **17D-1** to **17D-n** are provided for output ports, respectively. The FIFO buffers **17C-1** to **17C-n** are provided for the unicast, and the FIFO buffers **17D-1** to **17D-n** are provided for the multicast. Also, a FIFO buffer **17C-1** and a FIFO buffer **17D-i** are provided for an i -th output port. The gate section **15B** is the same as that in the first embodiment. A gate section **15C** in the second embodiment is an additional gate, and allows an internal cell passed through the gate section **15B** to be alternatively supplied to either FIFO **17C-i** for the unicast or FIFO **17D-i** for the multicast. The internal cell receiving section **10**, memory **13B** and delay circuit **14** are the same as those in the first embodiment.

FIG. 7 shows the format of internal cell used in the second embodiment. In FIG. 7, an internal cell **40** used in the second embodiment is provided with a unicast/multicast identifier **71** and output index information **72** in header field **41**. Similarly to the first embodiment, global user data such as IP packet and ATM cell are stored in data field **73**.

When the internal cell receiving section **10** receives an internal cell, it extracts the header field of the internal cell

5

and sends it to the memory reading control circuit 12C. Then, the memory reading control circuit 12C outputs the unicast/multicast identifier 71 of the header field to the gate section 15C, and outputs the output index information 72 thereof to the memory 13B. The memory 13B outputs, similarly to the first embodiment, a bit pattern corresponding to the output index information. The gate section 15B allows, similarly to the first embodiment, a buffer corresponding to a bit with "1" of the output bit pattern to be enabled. The gate section 15C allows a buffer corresponding to a FIFO buffer 17C-i for the unicast or a FIFO buffer 17D-i for the multicast to be enabled, according to the value of the unicast/multicast identifier 71. On the other hand, like the first embodiment, the internal cell sent from the internal cell receiving section 10 to the delay circuit 14B is delayed in the delay circuit 14B during a predetermined time, then passed through the enabled buffer of the gate section 15B. Then, if the unicast is designated by the unicast/multicast identifier 71, the internal cell passed through the enabled buffer of the gate section 15B is passed through a buffer of the gate section 15C corresponding to a FIFO buffer 17C-i for the unicast and written into the FIFO buffer 17C-i for the unicast. If the multicast is designated by the unicast/multicast identifier 71, the internal cell is passed through buffers of the gate section 15C corresponding to FIFO buffers 17D-i for the multicast and written into the FIFO buffers 17D-i for the multicast. Buffer management sections 17E-1 to 17E-n monitor the existence of internal cell stored in the FIFO buffers 17C-1 to 17C-n and 17D-1 to 17D n. When it detects that the internal cell is stored in any of the FIFO buffers, it sends the switching request to the switching request adjusting section 19. When the transfer allowance to the crosspoint switch is issued from the switching request adjusting section 19, if there is stored a multicast cell, the buffer management sections 17E-1 to 17E-n transfers, by priority, the multicast cell to the crosspoint switch.

Advantages of the Invention

First, since a unicast cell is similarly handled in the particular form of multicast cell, separate circuits for unicast cell and multicast cell is not necessary. Therefore, the processing circuit can be simplified.

Second, although the conventional system needs to be provided with separate buffers for the storing inside the system since the unicast cell and multicast cell are processed therein separately, in this invention the buffers for the multicast are not needed since the multicast cell is processed like the unicast cell.

Third, even when it is used with a crosspoint switch having no multicast function (=being not able to connect simultaneously to multiple routes), the multicast can be achieved.

Although the invention has been described with respect to specific embodiment for complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modification and alternative constructions that may be occurred to one skilled in the art which fairly fall within the basic teaching here is set forth.

What is claimed is:

1. A unicast/multicast system, comprising:

an internal cell generating section that generates an internal cell based on user data;

an internal cell receiving section that outputs the internal cell to a timing generating section and outputs a header field of the internal cell to an index search section;

an output port conversion table that stores the relation of output index information and output port number in the form of one-to-one for the unicast and one-to-multiple for the multicast;

6

said index search section that extracts output index information from the header field to be sent from said internal cell receiving section, refers to said output port conversion table for an output port number corresponding to the output index information extracted, and outputs the output port number obtained from said output port conversion table to a destination-based distribution section;

said destination-based distribution section that controls a gate section based on the output port number input from said index search section;

a timing generating section that delays the internal cell input from said internal cell receiving section and then outputs it said gate section;

said gate section that distributes the internal cell input from said timing generating section to said gate section according to the control of said destination-based distribution section;

a plurality of buffers that each store the internal cell distributed from said gate section and, when receiving the internal cell distributed from said gate section, sends switching request signal to a switching request adjusting section;

said switching request adjusting section that adjusts the switching request signal input from said buffers between said buffers and determines a route in a crosspoint switch; and

said crosspoint switch that outputs the internal cell stored in said buffers through the route determined by said switching request adjusting section.

2. A unicast/multicast system, according to claim 1, wherein:

said output port conversion table is a memory to an address of which the output index information is assigned, data stored in the address being represented as a bit pattern and corresponding to an output port number.

3. A unicast/multicast system, according to claim 1, wherein:

said buffers have buffers for the unicast and buffers for the multicast assigned to one output port number;

said header section has a unicast/multicast identifier in addition to the output index information;

said destination-based distribution section controls said gate section based on the unicast/multicast identifier as well as the output index information; and

said gate section distributes the internal cell input from said timing generating section to the unicast buffer or multicast buffer designated by said destination-based distribution section.

4. A unicast/multicast system, according to claim 3, further comprising:

a buffer management section that, if there is stored an internal cell in the multicast buffer when the transfer allowance is issued from said crosspoint switch, transfers, by priority, the internal cell in the multicast buffer to the crosspoint switch.

5. A unicast/multicast system, according to claim 1, wherein:

said user data is of IP packet or ATM cell.

6. A unicast/multicast system, according to claim 1, wherein:

said buffers each are of a FIFO type buffer.

7. A combined unicast and multicast system, comprising: plural data output ports connected to output data toward an input side of a crosspoint switch, each of the plural data output ports designated by an output port number,

7

an internal cell generating section to i) receive an original user data in a format, and ii) generate, from user data destination information within the accepted original user data, an internal cell comprising a header field added to the original user data,

the header field comprising output port index information indexing the user data destination information to one of the output ports when the data is unicast and to plural of the output ports when the data is multicast,

the internal cell generating section having a first output that outputs the internal cell toward the plural data output ports and a second output that outputs the header field, and

an output port conversion section connected to i) accept the header field from the second output, ii) extract the output port index information from the header field, and iii) determine output port numbers by using the extracted output port index information as an entry to a table providing a relationship between the output port index information and the output port numbers, wherein,

entries of the table index to only one of the output ports when the data is unicast and to plural of the output ports when the data is multicast,

the header field further comprises an identifier indicated whether the original user data is unicast or multicast,

8

the output port conversion section extracts the identifier and, from the identifier, determines whether the original user data is unicast or multicast, and

the plural data output ports comprise

a first gate section of plural gates connected to a second gate section of plural gates, each of the gates of the first gate section connected to plural of the gates of the second gate section,

the second gate section connected to a buffer section of plural buffers, each of the gates of the second gate section connected to one of the buffers, the buffers connecting to the crosspoint switch, a first set of the buffers dedicated for data that is unicast and a second set of the buffers dedicated for data that is multicast,

the determined output port numbers from the table enabling selected ones of the gates of the first gate section to pass the original user data to the second gate section, and

the extracted identifier enabling gates of the second gate section so that gates connected to the first set of buffers are enabled when the data is unicast and gates connected to the second set of buffers are enabled when the data is multicast.

* * * * *