



US006896016B1

(12) **United States Patent**  
**Smith et al.**

(10) **Patent No.:** **US 6,896,016 B1**  
(45) **Date of Patent:** **May 24, 2005**

(54) **PLATE JOINER**

(75) Inventors: **John C. Smith**, Jackson, TN (US);  
**Earl R. Clowers**, Jackson, TN (US)

(73) Assignee: **Porter-Cable Corporation**, Jackson,  
TN (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/603,280**

(22) Filed: **Jun. 25, 2003**

**Related U.S. Application Data**

(63) Continuation of application No. 10/042,536, filed on  
Jan. 8, 2002, now Pat. No. 6,612,349, which is a  
continuation of application No. 09/276,393, filed on  
Mar. 25, 1999, now Pat. No. 6,422,275, which is a  
continuation of application No. 08/872,015, filed on  
Jun. 9, 1997, now Pat. No. 6,336,483.

(51) **Int. Cl.**<sup>7</sup> ..... **B27C 5/10**

(52) **U.S. Cl.** ..... **144/136.95; 144/154.5;**  
**30/371; 30/374; 30/377; 409/182**

(58) **Field of Search** ..... **144/368, 371,**  
**144/136.1, 136.95, 154.5, 218, 373; 409/180,**  
**409/182; 30/371, 374-377**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,858,662 A \* 8/1989 Bosten et al. .... 144/136.95  
4,913,204 A \* 4/1990 Moores et al. .... 144/136.95

4,971,122 A \* 11/1990 Sato et al. .... 144/136.95  
5,257,654 A \* 11/1993 Bean et al. .... 144/136.95  
5,273,091 A \* 12/1993 Shibata ..... 144/136.95  
5,381,595 A \* 1/1995 Keith et al. .... 29/467  
5,865,230 A \* 2/1999 Smith et al. .... 144/136.95  
5,881,784 A \* 3/1999 Morikawa et al. .... 144/136.95  
6,021,826 A \* 2/2000 Daniell ..... 144/73

\* cited by examiner

*Primary Examiner*—Allen Ostrager

*Assistant Examiner*—Shelley Self


(74) *Attorney, Agent, or Firm*—Suiter West PC LLO

(57) **ABSTRACT**

A plate joiner including a fence support, a drive, and a fence system. The fence support includes a cutter and a contact surface, which defines a cutter slot. The cutter is arranged and configured to protrude from fence support through cutter slot to make a plunge cut into a surface of a workpiece when the contact surface is pressed against the surface and the cutter is plunged into the workpiece by pushing on a rearward handle portion of the tool. The drive is arranged and configured to rotatably drive the cutter through a motor.

A preferred fence system includes an angle adjustment system arranged and configured to position the fence at a wide range of fence angles and, at any selected distance from a top face of the workpiece to the fence, the distance from the top face of the workpiece to the cutter remains constant as the front fence angle is adjusted. A preferred fence system includes a trunnion which pivotally couples the front fence to the fence system. A preferred fence system also includes an angle segment member, which has two slots used to position the fence in two ranges of fence angles.

**21 Claims, 28 Drawing Sheets**






FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8





FIG. 9








FIG. 11








FIG. 14





FIG. 15








FIG. 17




FIG. 18

FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D





FIG. 19E






FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 21C




FIG. 21D




FIG. 21B





FIG. 21E






FIG. 22A




FIG. 22C




FIG. 22D




FIG. 22B




FIG. 23






FIG. 24




FIG. 25A




FIG. 25B




FIG. 26A




FIG. 26B




FIG. 27A




FIG. 27B




FIG. 27D





FIG. 27C

28B



28A





FIG. 28C



## PLATE JOINER

## CROSS REFERENCE

The present application is a Continuation and claims priority under 35 U.S.C. §120, to U.S. patent application Ser. No. 10/042,536 now U.S. Pat. No. 6,612,349, entitled: Plate Joiner, filed on Jan. 8, 2002, which in turn is a Continuation and claims priority under 35 U.S.C. §120, to U.S. patent application Ser. No. 09/276,393, now U.S. Pat. No. 6,422,275 entitled: Plate Joiner, filed on Mar. 25, 1999 (issued Jul. 23, 2002) which in turn is a Continuation and claims priority under 35 U.S.C. §120, to U.S. patent application Ser. No. 08/872,015, now U.S. Pat. No. 6,336,483 entitled: Plate Joiner Fence Angle Adjustment System, filed on Jun. 9, 1997 (issued Jan. 8, 2002) all of which are hereby incorporated by reference in their entirety.

## BACKGROUND OF THE INVENTION

The present invention relates to a plate joiner including a fence support, a drive, and a fence system. The fence support includes a cutter and a contact surface, which defines a cutter slot. The cutter is arranged and configured to protrude from fence support through cutter slot to make a plunge cut into a surface of a workpiece when the contact surface is pressed against the surface and the cutter is plunged into the workpiece by pushing on a rearward handle portion of the tool. A motor is connected to the drive, which is arranged and configured to rotatably drive the cutter.

A preferred fence system includes an angle adjustment system arranged and configured to position the fence at a wide range of fence angles and, at any selected distance from a top face of the workpiece to the fence, the distance from the top face of the workpiece to the cutter remains constant as the front fence angle is adjusted. A preferred fence system includes a trunnion which pivotally couples the front fence to the fence system. A preferred fence system also includes an angle segment member, which has two slots used to position the fence in two ranges of fence angles.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a side elevational view of a preferred embodiment of the present plate joiner and fence system;

FIG. 2 illustrates a left side elevational view of the plate joiner and fence system shown in FIG. 1;

FIG. 3 shows a top plan view of the plate joiner and fence system shown in FIG. 1;

FIG. 4 shows a bottom plan view of the plate joiner and fence system shown in FIG. 1;

FIG. 5 shows a front elevational view of the plate joiner and fence system shown in FIG. 1;

FIG. 6 shows a back elevational view of the plate joiner and fence system shown in FIG. 1;

FIG. 7 shows a top left perspective view of the plate joiner and fence system shown in FIG. 1;

FIG. 8 shows a bottom right perspective view of the plate joiner and fence system shown in FIG. 1;

FIG. 9 shows a left elevational cross-sectional profile (taken along cutting line 8—8 of FIG. 6) illustrating the preferred plate joiner as well as a preferred fence system;

FIG. 10 illustrates a right elevational view of the fence system shown in FIG. 1;

FIG. 11 shows a left elevational view of the fence system shown in FIG. 10;

FIG. 12 shows a top plan view of the fence system shown in FIG. 10;

FIG. 13 shows a front elevational view of the fence system shown in FIG. 10;

FIG. 14 illustrates a bottom plan view of the fence system shown in FIG. 10, with a portion of the cutter cover base cut away;

FIG. 15 shows a rear elevational view of the fence system shown in FIG. 10;

FIG. 16 shows a top plan cross-sectional profile (taken along cutting line 14—14 of FIG. 15) illustrating a preferred fence system;

FIG. 17 shows a left side elevational cross-sectional profile (taken along cutting line 15—15 of FIG. 13) illustrating a preferred fence system;

FIG. 18 illustrates a back elevational cross-sectional profile (taken along cutting line 16—16 of FIG. 16) illustrating a preferred fence system including portions of the lower gear housing of the plate joiner;

FIGS. 19A–E show elevational and top and bottom plan views of the fence system of FIG. 10 with the front fence at an angle of zero degrees;

FIGS. 20A–E show elevational and top and bottom plan views of the fence of FIG. 10 with the front fence at an angle of 90 degrees in the first range of front fence angles;

FIGS. 21A–E show elevational and top and bottom plan views of the fence system of FIG. 10 with the front fence at an angle of 90 degrees with the height of the front fence raised compared to the position in FIG. 20;

FIGS. 22A–D show elevational and top and bottom plan views of the fence system of FIG. 10 with the front fence at an angle of 135 degrees;

FIG. 23 shows a bottom plan view of the fence system of FIG. 10 with the cutter cover base removed and the safety lever in a rearward release position;

FIG. 24 shows a bottom plan view of the fence system of FIG. 10 with the cutter cover base removed and with the safety lever in a forward release position;

FIGS. 25A and 25B show a top left perspective view and a bottom right perspective view of the front fence, of the fence system of in FIG. 10, illustrating and the groove member of the trunnion;

FIGS. 26A and 26B show a bottom left perspective view and a top right perspective view and a top right perspective view, respectively, of the rear fence, of the fence system of in FIG. 10;

FIGS. 27A–D show perspective views of the trunnion member illustrating the ridge member;

FIG. 28A shows a front view of an embodiment of a fence system including a quick release screw;

FIG. 28B illustrates a top view of an embodiment of the fence system including a quick release screw;

FIG. 28C is a left-side elevational cross-sectional profile taken along cutting line 28—28 of FIG. 28A illustrating the quick release screw.

## DESCRIPTION OF THE INVENTION

A plate joiner makes a plunge cut in a joint surface of a piece of wood which allows the piece of wood to be joined to another piece of wood having an oppositely disposed groove. A biscuit (a thin plate of wood or other material) and glue are placed in the grooves, and the pieces of wood are joined to provide an accurate and strong joint. A plate joiner generally includes a housing, a drive unit, and a rotating cutter. A portion of the housing contacts a joint surface and, as a portion of the housing is pushed forward, the rotating

cutter moves forward, engages the joint surface at the desired location, and cuts into the joint surface. Releasing forward pressure on the housing then retracts the cutter. Thus, a plate joiner provides an easy method of producing a strong and aesthetic joint in wood.

The cutter is driven by a drive including a motor located within the housing, and a gear system driven by the motor and located in a forward gear housing portion of the housing. The gear system includes a motor driven shaft rotatably driven by the motor, a generally right angle coupling of the motor driven shaft, using beveled gear, to a cutter shaft that rotatably drives the cutter. The rotating cutter is configured to cut into the joint surface.

The preferred plate joiner tool can be configured into many highly versatile configurations. The plate joiner system is arranged and configured with a fence that can be positioned in a wide range of fence angles and, at any selected distance from a top face of the workpiece to the fence, the distance from the top face of the workpiece to the cutter remains constant as the front fence angle is adjusted. The plate joiner is configured for substantially continuous adjustment of fence height while restraining lateral and torsional movement of the fence and providing an accurate measure of the height of the fence from any point in the thickness of the blade. The plate joiner system is also arranged and configured to provide a plurality of release positions that reduce the distance traveled in making a plunge cut for a smaller blade and to prevent a blade from protruding from the tool in a release position. Such versatility is found in no other plate joiner system.

To accomplish this, the present plate joiner system preferably includes a fence system including an angle adjustment system having a trunnion and an angle segment member. The angle segment member includes two slots used to position the fence in two ranges of fence angles. The plate joiner system, preferably, also includes a height adjustment system including an adjustment screw arranged and configured to provide substantially continuous adjustment of fence height and guide pins which restrain lateral and torsional movement of the fence at the height it is adjusted and locked. A preferred plate joiner system also includes a cutter plunge system **86** arranged and configured for sliding the cutter from one of a plurality of release positions to a plunge position. A preferred plate joiner includes a cutter inside a removable cutter base cover.

The preferred plate joiner system includes a fence support **14**, a drive **170**, and a fence system **129** (see FIG. 9). Preferred fence support **14** includes a cutter **113** and a contact surface **24**, which defines a cutter slot **38**. Cutter **113** is arranged and configured to protrude from fence support **14** through cutter slot **38** to make a plunge cut into a surface of a workpiece when contact surface **24** of fence support **14** is pressed against the surface and cutter **113** is plunged into the workpiece by pushing on a rearward handle portion **172** of the tool. Drive **170** is arranged and configured to rotatably drive cutter **113** through a motor which may be an electrical motor operated live or battery power, or which may be an air motor. In a preferred configuration, contact surface **24** includes abrasive, which provides stability of the surface against the work piece. For example, the grit of the abrasive contacts the workpiece and prevents motion of the tool relative to the workpiece.

A preferred fence system **129** includes a front fence **12** and an angle adjustment system **39**, which is arranged and configured for adjusting an angle of front fence **12**. Using this preferred fence system **129**, at any selected distance from a top face of the workpiece to the front fence **12**, the

distance from the top face of the workpiece to cutter **113** remains constant as the angle of front fence **12** is adjusted. The preferred mechanism for accomplishing this is described further below. Front fence **12** includes a planar face **40**, which, at a fence angle of  $0^\circ$ , is coplanar with contact surface **24**. At fence angles greater than  $0^\circ$ , planar face **40** of front fence **12** defines a plane that intersects with the plane of contact surface **24**. The distance from this intersection to any particular part of cutter **113** is the distance from a top face of the workpiece to any particular part of cutter **113**. As shown in FIG. 13, front fence **12** includes cut away portions so that from the front of the plate joiner, front fence **12** has a shape resembling a squared-off letter "A". The cut away portions of front fence **12** reduce the weight of the fence and, optionally, accommodate protruding portions of gear housing **125** when making a plunge cut.

Front fence **12** pivots with respect to fence support **14** and cutter **113** by employing angle adjustment system **39**. Angle adjustment system **39** and front fence **12** define an axis on which front fence **12** pivots. When this pivot axis is not in the plane of contact surface **24**, that is, when this pivot axis is in front of or behind the contact surface, the distance from the top face of the workpiece to any particular part of cutter **113** changes as the front fence angle is varied. Advantageously, angle adjustment system **39** and front fence **12** are arranged and configured to provide a pivot axis substantially in a plane defined by contact surface **24**. This orientation of the pivot axis is a way to achieve a fence system in which, at any selected distance from a top face of the workpiece to any particular part of cutter **113**, [the distance from the top face of the workpiece to the particular part of cutter **113**], remains constant as a front fence angle is adjusted.

Advantageously, angle adjustment system **39** employs a trunnion **41** to pivot front fence **12** on a pivot axis in a plane defined by contact surface **24**. A trunnion typically includes a cup shaped receptacle which supports a rod or disk on which a device swivels. For example, the two opposite gudgeons on which a cannon swivels or pivots vertically form a trunnion. In this respect, a trunnion is particularly useful for providing a consistent vertical pivot motion without substantial lateral play.

Trunnion **41**, in which a generally semicircular cup **42** receives a generally semicircular disk **43**, is a mechanism that provides a pivot axis that is in the plane of contact surface **24**. Cup **42** is defined by an arcuate ridge member **44**. Disk **43**, is a portion of groove member **45**, which defines an arcuate groove **46** around disk **43**. Arcuate groove **46** pivotally engages ridge member **44** in a manner such that disk **43** is retained in cup **42**. Preferably, front fence **12** includes groove member **45** and rear fence **13** includes ridge member **44**.

In the embodiment shown in the Figures, rear fence **13** includes a rear fence member **47** and a trunnion member **48**, which includes a groove member **45**. Generally, ridge member **44** can be a component of either front fence **12** or rear fence **13**, groove member **45** can be a component of whichever of front fence **12** or rear fence **13** does not include ridge member **44**, and trunnion member **48** can include either ridge member **44** or groove member **45**.

In the embodiment shown in the Figures, trunnion **41**, includes left side trunnion pivot member **31** including ridge member **44** and groove member **45**, and a right side trunnion pivot member **32** including ridge member **44** and a groove member **45**. Generally trunnion **41** will include two trunnion pivot members, although a single member can include the features of both right side and left side trunnion pivot members.

## 5

Trunnion **41** can be arranged and configured to provide a pivot axis in a plane defined by contact surface **24**, in a plane defined by planar surface **40** of front fence **12**, in both of these planes, or in neither of these planes.

A preferred embodiment of the plate joiner system includes, as part of the system for adjusting the fence angle, an angle segment member **15** arranged and configured to position front fence **12** at a selected angle between a plane defined by planar surface **40** of front fence **12** and a plane defined by contact surface **24**. Angle segment member **15** defines first slot **49** and second slot **50**, which are arranged and configured to position the fence in a first and second range of fence angles, respectively.

FIG. **10** illustrates a preferred embodiment of angle segment member **15**. In this embodiment, angle segment member includes a plate **51** pivotally coupled to front fence **12** and configured to define slots **49** and **50**. First slot **49** and second slot **50** are each configured as an arcuate slot and are connected by third slot **52**. In the embodiment shown in FIG. **10**, the first range of fence angles is about  $0^\circ$  to about  $90^\circ$ , and the second range of fence angles is about  $90^\circ$  to about  $135^\circ$ . First angle scale **29** and second angle scale **30** are generally parallel to the corresponding slots and include numerical indicia **76** arranged and configured to indicate the angle of front fence **12**. Slots **49** and **50** are arranged and configured to provide approximately evenly spaced indicia **76** for a given change in fence angles. FIG. **10** illustrates approximately evenly spaced indicia **76** for each  $10^\circ$  change in fence angle.

First angle scale **29** and second angle scale **30** are each associated with an angle indicator, first angle indicator **54** and second angle indicator **55**, respectively. When front fence **12** is positioned in the first range of fence angles, first angle indicator **54** is generally adjacent to first angle scale **29** and indicates the fence angle on first angle scale **29**. When front fence **12** is positioned in the second range of fence angles, second indicator **55** is generally adjacent to second angle scale **30** and indicates the fence angle on second angle scale **30**.

Advantageously, first angle indicator **54** is not adjacent to first angle scale **29** when front fence **12** is positioned in the second range of fence angles. That is, angle segment **15** moves so that first angle indicator **54** is dissociated from first angle scale **29** when front fence **12** is positioned in the second range of fence angles (see-FIG. **22**). Similarly, second angle indicator **55** is not adjacent to second angle scale **30** when front fence **12** is positioned in the first range of fence angles. That is, angle segment **15** moves so that second angle indicator **55** is dissociated from second angle scale **30** when front fence **12** is positioned in the first range of fence angles (see FIG. **10**).

In another preferred embodiment, angle adjustment system **39** is arranged and configured to provide a positive stop at one or more fence angles. For example, angle segment member **15** can include a stop member, such as tab **56**, that contacts another portion of the fence system to provide a positive stop. Such a positive stop can be adjustable if either tab **56** or the part contacted by tab **56** includes a stop adjustment mechanism, such as an adjustable set screw.

FIGS. **12** and **14** show stop member **56** configured to provide a positive stop at  $90^\circ$ . Using first slot **49** to position front fence **12** at  $90^\circ$  brings stop member **56** into contact with rear fence **13** providing a positive stop. Optionally, rear fence **13** can include an adjustable set screw (not shown) at the point at which stop member **56** contacts rear fence **13** to provide an adjustable positive stop. It is advantageous to provide an adjustable stop at  $90^\circ$  so that plunge cuts can be

## 6

adjusted to be made accurately at substantially  $90^\circ$ . An analogous arrangement of stop member **56** and contact point on rear fence **13** can provide a positive stop at  $135^\circ$  (not shown). A positive stop at  $0^\circ$  is provided by contact between rear fence **13** and a contact point **78** on the rearward surface of front fence **12**.

Front fence **12** can be retained at a desired fence angle. Angle adjustment system **39** includes an angle locking system **57**. Angle locking system **57** includes angle locking knob **3** that is arranged and configured to bias against angle segment member **15**. Angle locking knob **3** is threadably engaged on a pin (not shown) that slidably engages slots **49** and **50** in angle segment member **15**. Knob **3** when tightened on the threaded pin biases angle segment member **15** against rear fence **13**.

The preferred plate joiner system includes a height adjustment system **58**, which is a subsystem of fence system **129**. Height adjustment system **58** is preferably arranged and configured to adjust the distance from the top face of a workpiece to the cutter in a substantially continuous manner and with torsional and lateral stability. Optionally, height adjustment system **58** can provide a combination of rapid, discontinuous height adjustment to approximately the desired fence height, and substantially continuous adjustment to achieve the desired fence height.

Height adjustment system **58** achieves substantially continuous adjustment of fence height using a threaded rod **59**. Threaded rod **59** is supported by and rotatably retained by a vertical member **60** portion of fence support **14** and threadably engages rear fence **13**. Vertical member **60** and rear fence **13** are both substantially perpendicular to cutter **113**. Threaded rod **59** does not move vertically relative to vertical member **60**, and as threaded rod **59** is rotated, rear fence **13** moves up and down relative to vertical member **60** and cutter **113**. Since front fence **12** is pivotally attached to rear fence **13**, front fence **12** also moves vertically with rear fence **13** and relative to cutter **113**.

Threadable engagement of rear fence **13** with threaded rod **59** results in substantially continuous vertical adjustment of the fence. Small increments of rotation allow small increments of vertical movement on the incline of the threads. In a preferred embodiment, by knowing the pitch of the thread, each revolution or partial revolution provides a predetermined height adjustment. Optionally, using a quick release screw **80** rear fence **13** can disengage from the threads of threaded rod **59**, for rapid, discontinuous height adjustment. When the approximate fence height is achieved by discontinuous adjustment, rear fence **13** can reengage the threads of threaded rod **59** for continuous adjustment to the desired fence height.

Height adjustment is achieved with torsional and lateral stability by using first guide rod **61** and second guide rod **18** to guide vertical adjustment of rear fence **13**. As shown in the Figures, first guide rod **61** and second guide rod **18** are components of fence support **14**. Guide rod frames **62** and **63** are components of rear fence **13**. In this way, guide rods **18** and **61** are retained by fence support **14** vertical member **60**, and cannot move vertically relative to vertical member **60**. Yet, guide rods **18** and **61** slidably engage rear fence **13**, so that rear fence **13** can slide vertically relative to the guide rods for height adjustment.

As shown in FIGS. **7** and **22C** first guide rod **61** is positioned by first guide rod frame **62** and second guide rod **18** is positioned by second guide rod frame **63**. Each guide rod frame defines a space around the corresponding guide rod. Preferably, first guide rod frame **62** comprises first through hole **64** in rear fence **13** and second guide rod frame



63 comprises second through hole 65 in rear fence 13. The space between first guide rod 61 and first guide rod frame 62 is advantageously narrower than the space between second guide rod 18 and second guide rod frame 63. Preferably, first through hole 64 has a substantially smaller diameter than second through hole 65, which results in a narrow space between first guide rod 61 and first guide rod frame 62 than between second guide rod 18 and second guide rod frame 63. First guide rod 61 and second guide rod 62 are advantageously of substantially equal diameter. The combination of a tight tolerance for first guide rod 61 and a looser tolerance for second guide rod 18 is one manner in which lateral and torsional movement of rear fence 13 is restrained, while maintaining manufacturing economies.

Height adjustment system 58 includes a height locking system 82 for securing front fence 12 at the desired height and for providing reproducible lateral and torsional positioning and stability of front fence 12 at different heights. Height locking system 82 includes height locking knob 84, threaded pin 66 and plug 19. Height locking system 82 is arranged and configured to bias against a second guide rod 18 and to bias first guide rod 61 against first guide rod frame 62. Individual components of height locking system 82 are configured to bring this about. Turning knob 84 threadably advances threaded pin 66 into rear fence 13 which biases plug 67 against guide rod 18. As this biasing continues rear fence 13 is moved laterally through a distance less than the space surrounding first guide pin 61, and first guide pin 61 is biased against guide rod frame 62. Biasing guide rod 61 against guide rod frame 62 provides reproducible and stable lateral and torsional positioning of rear fence 13, and front fence 12.

The preferred fence system also includes a height gauge 68, which is arranged and configured to provide a reading of fence height relative to any point on the thickness of cutter 113, which corresponds to any point in the thickness of the slot cut by cutter 113. In an especially preferred embodiment, height gauge 68 provides an accurate reading of fence height at any fence angle.

Height gauge 68 includes a scale 10 and a height indicator 69. As shown in the figures, height scale 10 is arranged on a surface of fence support 14 vertical member 60, and height indicator 69 is on rear fence 13 generally adjacent to vertical member 60. Height indicator 69 includes a visible indicator 70 with a thickness along the height scale 10 substantially equivalent to the thickness of the cutter that indicates fence height using height scale 10. In one preferred embodiment, visible indicator 70 is in the shape of a raised rectangle.

As a consequence of this arrangement, by visualizing measurement along the thickness of the visible indicator 70, height gauge 68 indicates the distance from a face of the workpiece to any point in the thickness of cutter 113. With this arrangement of the height gauge and a preferred embodiment of the angle adjustment system, in which at any selected distance from a top face of the workpiece to the fence, the distance from the top face of the workpiece to the cutter remains constant as the front fence angle is adjusted, the height gauge is accurate each selected front fence angle.

In making a plunge cut with the plate joiner, cutter 113 starts in a release position and, as contact surface 24 is pressed against the workpiece, by pushing on a rearward handle portion of the tool, cutter 113 moves forward to a plunge position while cutting a slot in the workpiece. Preferably, in a release position, cutter 113 is completely within fence support 13, which includes cutter housing cover 16, and cutter housing base 17. If such a plate joiner has only a single release position and can use different sized

blades, a smaller blade must travel a greater distance before it contacts the workpiece, which is an inconvenience for the plate joiner operator.

Preferred cutter sizes include diameters of about 4 inches and about 2 inches. A more convenient arrangement provides a plurality of release positions to reduce the distance from release position to plunge position for smaller blades.

A preferred embodiment of the plate joiner system includes a cutter plunge system 86 arranged and configured for sliding cutter 113 from one of a plurality of release positions to a plunge position. The release positions are configured to reduce the distance between the release and plunge positions as cutter size is reduced. Preferably the distance from the forward edge of the blade in the release position to the contact surface is approximately constant for different sized blades in different release positions.

Cutter plunge system 86 includes safety lever system 71, which is arranged and configured to position the cutter at one or more release positions. Safety lever system 71 includes pivot pin 28, which can be a rivet, safety lever 25, and guide pin 26. Safety lever 25 pivots on pivot pin 28 and guide pin 26 engages an aperture 72 in blade housing cover 16 and stoppably engages lower gear housing 73 to retain the cutter in the release position.

The plurality of release positions configures the plate joiner system to advantageously house cutters of two more different sizes. For example, a four inch cutter is advantageous for general use, and a smaller, two inch, cutter is advantageous for applications such as joining face frames. The preferred plate joiner system can house either a two inch blade or a four inch blade, and the cutter plunge system 86 provides for reduced travel of the two inch cutter.

In the release position providing reduced travel for a smaller blade, safety lever 25 prevents installing a larger blade, preferably by physically blocking installation of the larger blade. In such a manner, a safety lever prevents installing a large blade in a release position in which it would protrude from the cutter slot in the release position. The larger blade is accommodated at a more rearward release position.

In a forward position, safety lever 25 is configured to direct cutting dust toward dust aperture 74. The slightly arcuate shape of safety lever 25 provides smooth circulation of air and dust when safety lever 25 is in a rearward release position, and aids in directing dust towards aperture 74 when safety lever 25 is in a forward release position.

The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

What is claimed is:

1. A plate joiner, comprising:

- a plunge cutting element, for plunge cutting a recess in a surface included in a workpiece;
- a rear fence, adjustably positionable along an axis generally perpendicular to the plunge cutting element; and
- a workpiece positioning system including:
  - a front fence pivotally coupled to said rear fence, said front fence being configured and arranged so as to position the cutting element with respect to a side of the workpiece adjacent the surface of the workpiece into which a plunge cut is to be made; and
  - an angular adjustment system pivotally coupled to said front fence, for adjustably fixing the angular relation of said front fence with respect to said rear fence;

9

wherein the angular adjustment system permits angular adjustment of said front fence greater than 90° (degrees) from the surface of the workpiece into which a recess is to be made.

2. The plate joiner of claim 1, wherein the angular adjustment system is adjustable in the range of about 0° (zero degrees) through about 135° (degrees).

3. The plate joiner of claim 1, wherein the angular adjustment system includes an angled segment member including a first arcuate slot for positioning said front fence member in the range of between about 0° (zero degrees) and about 90° (degrees) and a second arcuate slot for positioning said front fence from between 90° (degrees) and 135° (degrees) from the surface of the workpiece into which a recess is to be made.

4. The plate joiner of claim 3, wherein the angled segment member slidably engages said rear fence.

5. The plate joiner of claim 3, wherein the first and the second arcuate slots individually include a positive stop for positioning said front fence at 90° (degrees) with respect to the surface of the workpiece into which a recess is to be made.

6. The plate joiner of claim 1, wherein the angular adjustment system includes a locking mechanism for fixedly securing the angular position of said front fence.

7. The plate joiner of claim 6, wherein the locking mechanism is a knob threadly connected to a pin extending from said rear fence for fixedly securing the angular position of said front fence.

8. The plate joiner of claim 1, wherein the angular adjustment system is configured to include a positive stop at 90° (degrees).

9. The plate joiner of claim 1, wherein the angular adjustment system is configured to include a positive stop at 135° (degrees).

10. The plate joiner of claim 1, wherein the pivotal connection between said front fence and said rear fence is a trunnion member.

11. The plate joiner of claim 1, wherein the angle adjustment system is configured and arranged to provide a positive stop at one or more front fence angles.

12. A plate joiner, comprising:

a plunge cutting element, for plunge cutting a recess in a surface included in a workpiece;

a rear fence, being adjustably positionable along an axis generally perpendicular to the plunge cutting element; and

a workpiece positioning system including:

a front fence pivotally coupled to said rear fence, said front fence being configured and arranged so as to position the cutting element with respect to a side of the workpiece adjacent the surface into which a plunge cut is to be made; and

10

an angular adjustment system including an angled segment member having a first arcuate slot for positioning said front fence member in the range of between about 0° (zero degrees) and about 90° (degrees) and a second arcuate slot for positioning said front fence from between about 90° (degrees) and about 135° (degrees), said angular adjustment system being pivotally coupled to said front fence, for adjustably fixing the angular relation of said front fence with respect to the surface of the workpiece into which a recess is to be made.

13. The plate joiner of claim 12, wherein the angled segment member slidably engages said rear fence.

14. The plate joiner of claim 12, wherein the first and the second arcuate slots individually include a positive stop for positioning said front fence at 90° (degrees) with respect to the surface of the workpiece into which a recess is to be made.

15. The plate joiner of claim 12, wherein the angular adjustment system includes a locking mechanism for fixedly securing the angular position of said front fence.

16. The plate joiner of claim 15, wherein the locking mechanism is a knob threadly connected to a pin extending from the rear fence for fixedly securing the angular position of said front fence.

17. The plate joiner of claim 12, wherein the angular adjustment system is configured to include a positive stop at 90° (degrees).

18. The plate joiner of claim 12, wherein the angular adjustment system is configured to include a positive stop at 135° (degrees).

19. The plate joiner of claim 12, wherein the pivotal connection between said front fence and said rear fence is a trunnion member.

20. The plate joiner of claim 12, wherein the angle adjustment system is configured and arranged to provide a positive stop at one or more front fence angles.

21. A plate joiner, comprising:

a plunge cutting element, for plunge cutting a recess in a surface included in a workpiece; and

means for angularly positioning the cutting element with respect to a workpiece such that the distance from a side of the workpiece adjacent the surface into which a plunge cut is to be made and the cutting element remains substantially constant with angular variation;

wherein the angular positioning means permits angular adjustment greater than 90° (degrees) from between the adjacent surface of the workpiece and an axis generally parallel from the surface of the workpiece into which a recess is to be made.

\* \* \* \* \*