

US006899735B2

(12) **United States Patent**
Coates et al.

(10) **Patent No.:** **US 6,899,735 B2**
(45) **Date of Patent:** **May 31, 2005**

(54) **MODULAR INTERVERTEBRAL PROSTHESIS SYSTEM**
(75) Inventors: **Bradley J. Coates**, Rossville, TN (US); **James E. Van Hoeck**, Cordova, TN (US); **T. Andrew Simonton**, Germantown, TN (US); **Regis Haid**, Atlanta, GA (US); **Kevin Foley**, Germantown, TN (US)

(73) Assignee: **SDGI Holdings, Inc.**, Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 208 days.

5,562,738 A 10/1996 Boyd et al.
5,674,296 A 10/1997 Bryan et al.
5,865,846 A 2/1999 Bryan et al.
5,899,901 A 5/1999 Middleton
6,019,792 A 2/2000 Cauthen
6,106,557 A * 8/2000 Robioneck et al. 623/17.15
6,113,637 A 9/2000 Gill et al.
6,146,421 A * 11/2000 Gordon et al. 623/17.15
6,179,874 B1 1/2001 Cauthen
6,375,683 B1 * 4/2002 Crozet et al. 623/17.15
6,419,706 B1 7/2002 Graf
6,440,168 B1 8/2002 Cauthen
6,517,580 B1 * 2/2003 Ramadan et al. 623/17.15
6,579,290 B1 * 6/2003 Hardcastle et al. 606/61

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **10/263,115**

(22) Filed: **Oct. 2, 2002**

(65) **Prior Publication Data**

US 2004/0068318 A1 Apr. 8, 2004

(51) **Int. Cl.**⁷ **A61F 2/44**

(52) **U.S. Cl.** **623/17.16; 623/17.11**

(58) **Field of Search** **623/17.11, 17.15, 623/17.16**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,759,709 A 7/1988 Luken, Jr. et al.
4,805,602 A 2/1989 Puno et al.
5,002,576 A 3/1991 Fuhrmann et al.
5,005,562 A 4/1991 Cotrel
5,176,678 A 1/1993 Tsou
5,236,460 A 8/1993 Barber
5,258,031 A 11/1993 Salib et al.
5,370,697 A 12/1994 Baumgartner
5,425,773 A 6/1995 Boyd et al.
5,458,641 A 10/1995 Ramirez Jimenez
5,458,642 A 10/1995 Beer et al.
5,534,029 A * 7/1996 Shima 623/17.15
5,556,431 A 9/1996 Büttner-Janz

EP 0 699 426 3/1996
FR 2 718 635 10/1995
FR 2 805 457 8/2001
WO WO 99/65412 12/1999


Primary Examiner—Pedro Philogene
Assistant Examiner—D. Austin Bonderer

(74) *Attorney, Agent, or Firm*—Coats & Bennett, P.L.L.C.

(57) **ABSTRACT**

A modular intervertebral prosthesis system includes first and second baseplates and an insert designed to mate to the baseplates. The baseplates include a mounting section and a intervertebral section extending away from the mounting section generally perpendicular thereto. The intervertebral section has at least one aperture passing therethrough. When installed, the insert is disposed between the intervertebral sections of the baseplates and faces the apertures. In this way, the insert is not insulated from the vertebral members, thereby allowing for osteoinduction, osteoconduction, and/or osteointegration, if desired. The insert may take the form of an articulating-type insert or a fusion-type insert, with the baseplates being operative with both types of inserts. After installation of the insert between the baseplates, the insert may be readily removed, at least initially.

58 Claims, 4 Drawing Sheets



US 6,899,735 B2

Page 2

U.S. PATENT DOCUMENTS

6,579,320	B1 *	6/2003	Gauchet et al.	623/17.15	2004/0030387	A1 *	2/2004	Landry et al.	623/16.11
6,610,093	B1 *	8/2003	Pisharodi	623/17.15	2004/0034423	A1 *	2/2004	Lyons et al.	623/17.13
6,648,917	B2 *	11/2003	Gerbec et al.	623/17.11	2004/0049270	A1 *	3/2004	Gewirtz	623/17.11
6,682,561	B2 *	1/2004	Songer et al.	623/17.11	2004/0073314	A1 *	4/2004	White et al.	623/17.15
2003/0187506	A1 *	10/2003	Ross et al.	623/17.13	2004/0102846	A1 *	5/2004	Keller et al.	623/17.11
2003/0204261	A1 *	10/2003	Eisermann et al.	623/17.14	2004/0133278	A1 *	7/2004	Marino et al.	623/17.14

* cited by examiner




FIG. 1




FIG. 2









FIG. 5

FIG. 4

FIG. 3




FIG. 7




FIG. 6

1

MODULAR INTERVERTEBRAL PROSTHESIS SYSTEM

BACKGROUND

In the treatment of diseases, injuries or malformations affecting spinal motion segments, and especially those affecting disc tissue, it has long been known to remove some or all of a degenerated, ruptured or otherwise failing disc. In cases involving intervertebral disc tissue that has been removed or is otherwise absent from a spinal motion segment, corrective measures are indicated to insure the proper spacing of the vertebrae formerly separated by the removed disc tissue. Sometimes, the two adjacent vertebrae are fused together using transplanted bone tissue, an artificial fusion component, or other compositions or devices. Other times, different types of intervertebral disc arthroplasty devices have been employed to prevent the collapse of the intervertebral space between adjacent vertebrae while maintaining a certain degree of stability and range of pivotal and rotational motion therebetween. Such devices typically include two or more articular components that are attached to respective upper and lower vertebrae. The articular components are anchored to the upper and lower vertebrae by a number of methods, including the use of bone screws that pass through corresponding openings in each of the elements and thread into vertebral bone, and/or by the inclusion of spikes or teeth that penetrate the vertebral endplates to inhibit migration or expulsion of the device. The articular components are typically configured to allow the elements, and correspondingly the adjacent vertebrae, to pivot and/or rotate relative to one another.

However, it is not always possible to determine a priori whether a fusion approach or an articulating joint approach is appropriate for a given situation. Further, it may be necessary to change the type or size of the articulating joint, and/or to change from an articulating joint to a fusion joint, after a first articulating joint has been installed. As such, there remains a need for intervertebral prosthesis systems that address one or more of these problems.

SUMMARY

The present invention relates generally to a modular intervertebral prosthesis system and a method of using the same. While the actual nature of the invention covered herein can only be determined with reference to the claims appended hereto, certain forms of the invention that are characteristic of embodiments disclosed herein are described briefly as follows.

One embodiment of the modular intervertebral prosthesis system of the present invention includes first and second baseplates and an insert designed to mate to the baseplates. The baseplates include a mounting section and an intervertebral section extending away from the mounting section such that the baseplates have a generally L-shaped side profile. The intervertebral section has at least one aperture passing therethrough. When installed, the insert is disposed between the intervertebral sections of the baseplates, and faces the apertures. In this way, the insert is not insulated from the vertebral members, thereby allowing for osteoinduction and/or osteoconduction and/or osteointegration, if desired. The insert may take the form of an articulating-type insert or a fusion-type insert, with the baseplates being operative with both types of inserts.

After installation of the insert between the baseplates, the insert may be readily removed, so as to allow the surgeon to

2

try another size or type of insert during the same surgery without removing the baseplates from the vertebral members. In addition, if the insert has not fused to the vertebral members, the insert may be removed during a later surgery to allow for replacement of the insert, or substitution of another type of insert.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of the prosthesis system in accordance with the present invention.

FIG. 2 is a partially exploded view of another embodiment of the prosthesis system in accordance with the present invention.

FIG. 3 is a side view of the baseplates of FIG. 2.

FIG. 4 is a front view of the baseplates of FIG. 3.

FIG. 5 is a bottom view of the baseplates of FIG. 3.

FIG. 6 shows the prosthesis system of FIG. 2 installed in a vertebral column.

“FIG. 7 is a front view of an insert mounted between the baseplates.”

DETAILED DESCRIPTION

Referring to FIGS. 1–6, the modular prosthesis system of the present invention, generally indicated at **10**, includes two baseplates **20** and at least one insert **70**. In some embodiments, the system **10** comprises more than one insert **70**. The baseplates **20** include a mounting section **30** for mounting to a vertebral member **4,6** and an intervertebral section **50** that is intended to be disposed substantially between the two vertebral members **4,6**. The mounting section **30** may be a rigid, generally planar section. In one embodiment, mounting section **30** has a slight curve to conform with the patient's anatomy (see FIG. 5). The mounting section **30** includes two spaced apart countersunk screw holes **32** for receiving mounting screws **40a** that mount the baseplate **20** to the respective vertebral member **4,6**. Between the two screw holes **32** is a smaller hole **36** for a locking screw **40b** or other locking mechanism, such as a snap, etc. The area around hole **36** may advantageously be slightly recessed so as to accept an associated retaining ring **37** as discussed below. In addition, the edge of the mounting section **30** closest to the intervertebral section **50** may advantageously include a notch **34** for a corresponding tab **74** on an insert **70**, as described more fully below. The portion of the mounting section **30** near where the intervertebral section joins the mounting section **30** may include shoulder sections **38** if desired for added strength.

The intervertebral section **50** may extend away from the mounting section **30** so that the baseplate **20** has a L-shaped side profile (see FIG. 3). Indeed, the intervertebral section **50** may advantageously extend away from the mounting section **30** in a generally perpendicular (i.e., $90^\circ \pm 20^\circ$) fashion. The intervertebral section **50** includes an aperture **60** that extends through the intervertebral section **50** (e.g., from the inferior side to the superior side). The aperture **60** may take the form of a hole, or may be simply the space between two arms **52** that extend out from the mounting section **30** (see FIGS. 2, 5). The arms **52** may advantageously include grooves **54** on their interior sides, for engaging corresponding rails **76** on some insert designs, as discussed below. The distal ends of the arms **52** may optionally be bridged by a linking bridge member **58** (see FIG. 1), such that the aperture **60** is bounded on all sides when viewed from above. While the two baseplates **20** may be different, the baseplates **20** may advantageously be substantially identical so as to be interchangeable.

One advantage of the prosthesis system **10** shown in FIGS. 1–5 is that it may employ a variety of inserts **70**. For instance, the baseplates **20** may be used with one version of an articulating joint, such as the ball and trough arrangement **70a** shown in FIG. 2. Such ball and trough insert arrangements may include two principle parts, with one part **72** having a ball shape and one part **78** having a corresponding hollow (or trough). The two portions **72,78** of the articulating type insert **70a** are designed to slide into the corresponding baseplates **20**. As pointed out above, the inserts **70a** may have rails **76** on their sides for engaging the grooves **54** in the baseplates **20**, for purposes of alignment and/or stabilization. In addition, one edge of each part **72,78** of the articulating insert **70a** may include a tab **74** that co-operates with the notch **34** on the corresponding baseplates **20** to prevent over-insertion with respect to the baseplates **20**, and to aid in securing the insert **70** to the baseplate **20**. Reference is made to U.S. patent application Ser. No. 10/042,589 entitled “Artificial Disc Implant,” filed Jan. 9, 2002, U.S. Provisional Application No. 60/375,354 entitled “Articular Disc Prosthesis And Method For Implanting The Same,” filed Apr. 25, 2002, and U.S. Pat. No. 6,113,637 entitled “Artificial Intervertebral Joint Permitting Translational And Rotational Motion,” all incorporated herein by reference, for additional details concerning design of the ball and trough surfaces. Of course, other forms of inserts **70** may also be employed to form an articulating joint in association with the baseplates **20**, with the particular details being unimportant other than the ability to connect to the baseplates **20**. For instance, an insert **70** based on a single flexible member, an enclosed ball-and-socket, a hinge, or the like may be used without departing from the broadest forms of the present invention.

In one embodiment, the articulating type inserts **70a** are removable from the baseplates **20** once installed. For the embodiments shown in FIGS. 1–5, the insert parts are secured in place via retaining ring **37**, screw **40b**, and threaded hole **36**, with the outer diameter of the retaining ring **37** being large enough to overlap the tab **74** on the insert parts **72,78** and hold tab **74** in notch **34** and against the mounting section **30** of the corresponding baseplate **20**. Once installed, the insert parts **72,78** may be readily removed for inspection and/or replacement by simply removing screw **40b** and retaining ring **37**, and then sliding the insert parts **72,78** out from their respective baseplates **20**. The insert parts **72,78** may, if desired, be replaced with insert parts **72,78** of another size and/or design, or an insert of a different type, such as insert **70b**. Note, however, that care should be taken when replacing or otherwise removing the articulating type insert **70a** to take into account any osteointegration that may have taken place between the bone and the insert **70a**, particularly through the apertures **60**.

As an alternative to the articulating type inserts **70a** discussed above, the insert **70** may be of a type known as “fusion” inserts **70b**. For example, the insert **70b** may comprise a portion of precision milled allograft bone harvested from a cadaver, a portion of autograft bone harvested from the same patient, or some synthetic material. One example of a commercially available product that may be used as a fusion-type insert **70b** is sold under the trademark “CORNERSTONE” by Medtronic Sofamor Danek of Memphis, Tenn. In one embodiment, the insert **70b** includes a central passage that extends **82** from one end to the other of the insert **70b**. When the insert **70b** is positioned between the baseplates **20**, the passage **82** faces the apertures **60** in the baseplates **20**, thereby providing a direct path from the vertebral member **4,6** to the fusion insert **70b**, so as to promote osteoinduction and osteoconduction.

The baseplates **20** should be made from a suitable rigid material, such as stainless steel, various titanium alloys known in the art, cobalt-chrome-molybdenum alloys ASTM F-799 or F-75, or any other metallic alloy known in the art. The articulating type inserts **70a** may also be made from metallic alloys, but may also include suitable plastic and/or ceramic materials as desired. The fusion inserts **70b** may be made from actual bone material, demineralized bone matrix, ceramics (e.g., hydroxy apatite), polymers (e.g., polyetheretherketone bioinert polymer (PEEK)), or any other suitable material, including bioresorbable materials. Indeed, the fusion inserts **70b** may be made from, or filled with, bone growth inducing materials, such as a sponge, matrix, and/or other structural carrier impregnated with a protein such as bone morphogenic protein (BMP), LIM mineralization protein (LMP), etc.

Referring to FIG. 6, the prosthesis system **10** may be seen installed in the gap **8** between a superior vertebral member **4** and an inferior vertebral member **6**. In the illustrated embodiment of the invention, the prosthesis **10** is inserted into the intervertebral disc space via an anterior approach; however, it should be understood that posterior and lateral approaches are also possible. With appropriate distraction applied to the vertebral members **4,6**, one baseplate **20** is secured to the superior vertebral member **4** using screws **40a**, and the other baseplate **20** is secured to the inferior vertebral member **6**, likewise using screws **40a**. With the baseplates **20** installed, the surgeon may chose to install either an articulating-type insert **70a** or a fusion-type insert **70b**; indeed, the decision as to which type of insert **70** to employ need not be made prior to the start of surgery, but may be delayed until the site has been examined during surgery. Assuming that an articulating-type insert **70a** of the type shown in FIG. 2 is selected, the ball portion of the insert **72** may be slid into the baseplate **20** associated with the superior vertebral member **4** until tab **74** rests against notch **34**. The retaining ring **37** may be placed in the recessed area of the mounting section **30**, over the tip of the tab **74**, and locking screw **40b** inserted through the center of retaining ring **37** and into threaded hole **36**. When screw **40b** is fully threaded into hole **36**, the retaining ring **37** urges the tab **74** firmly against the notch **34**, thereby securing the ball portion **72** of the insert **70a** to the corresponding baseplate **20**. The other portion **78** of the insert **70a** may then be mated to the other baseplate **20** in a similar fashion. Alternatively, both portions **72,78** of the insert **70a** may be inserted into their respective baseplates **20** simultaneously, and thereafter locked in place via respective locking mechanisms (e.g., locking screw **40b** and retaining ring **37**). Thereafter, the surgical site is closed using conventional techniques.

It should be noted that the insert **70a** is readily removable from the baseplates **20** immediately after installation. For the illustrated embodiments, the surgeon need only undo the locking mechanism, such as by removing locking screws **40b** and retaining rings **37**, and then slide the insert portions **72,78** out of engagement with the baseplates **20**. With the first insert **70a** removed, another insert **70a** or **70b** may be mated to the baseplates **20** without removing the baseplates **20** from the vertebral member **4,6**. As such, the surgeon is free to try another an insert **70** of a different configuration (e.g., different in size, design, or type) in order to achieve the desired results. Indeed, the surgeon may initially try an articulating-type insert **70a**, but then change to a fusion-type insert **70b** without the need to install new baseplates **20**, and during the same surgery. Once the proper insert **70** has been selected and installed, the surgeon may add an optional flexible or rigid element (not shown) secured to the exterior

5

of mounting sections **30** of the two baseplates **20**, if desired. If the optional element is flexible, it may function as an artificial ligament; if the optional element is rigid, it may function as a stabilizer.

One advantage of the present prosthesis system **10** is that it enables a fusion-type insert **70b** to “see” the bone of the relevant vertebral members **4,6**. That is, when the insert **70b** is installed in the baseplates **20**, the insert **70b** faces the bone through the aperture **60** of the corresponding baseplate **20**. Over time, bone may grow through these apertures **60**, “fusing” the insert **70b** to the vertebral members **4,6**. As such, while fusion-type inserts **70b** may be readily removable immediately after installation, the insert **70b** may become fixed in place over time. In order to promote this fusion process, the insert **70b** may include appropriate ridges and/or pores on its end surfaces, and the insert **70b** may include fusion promoting materials, as indicated above.

While the illustrative embodiments discussed above have assumed that the prosthesis system **10** replaces a single intervertebral disc, the present invention also encompasses situations where the prosthesis system **10** replaces more than one intervertebral disc—a so-called corpectomy construct. This can be achieved through the use of longer length inserts **70**, or by having the insert **70** include an additional member acting as a substitute vertebral member between parts of the insert.

The discussion above has also described a situation where one insert **70** is installed, then removed and replaced with another insert **70** during the same surgery. However, the subsequent replacement may alternatively occur during a subsequent surgery, such as to replace a worn insert **70** or the like.

Additionally, although the devices and methods illustrated and described above are particularly useful in treating the cervical region of the spine, it should nevertheless be understood that the present invention is also applicable to other portions of the spine, including the lumbar or thoracic regions of the spine.

While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character. For instance, a different method of mounting the baseplates **20** to the vertebral members **4,6**, such as using a different number of holes **32** and screws **40a** and/or adhesives, may be employed if desired. Likewise, other locking mechanisms may be used to retain the inserts **70** in the baseplates **20**, such as clips, snaps, or the like, and the retaining ring **37** may be integrated into the locking screw **40b** if desired. It should therefore be understood that only some embodiments have been shown and described and that all changes and modifications that come within the meaning and equivalency range of the appended claims are intended to be embraced therein.

What is claimed is:

1. A modular intervertebral prosthesis assembly, comprising:

a first baseplate having a first mounting section and a first intervertebral section extending away from said first mounting section, said first intervertebral section having a first aperture passing therethrough;

a second baseplate having a second mounting section and a second intervertebral section extending away from said second mounting, said second intervertebral section having a second aperture passing therethrough;

at least a first insert disposed between said first and second baseplates so as to face said first and second apertures and adapted to engage said first and second baseplates; and

6

a retaining mechanism mounted to said first mounting section and on contact with said first insert to prevent the removal of said first insert from between said first and second baseplates, said retaining mechanism being spaced from said second baseplate such that said first insert is exposed between said first and second baseplates.

2. The assembly of claim **1** wherein said first and second baseplates have a generally L-shaped side profile.

3. The assembly of claim **1** wherein said first insert comprises a fusion element.

4. The assembly of claim **3** wherein said fusion element is selected from the group consisting of allograft bone and autograft bone.

5. The assembly of claim **1** wherein said first insert comprises an articulating insert.

6. The assembly of claim **5** wherein said first insert comprises at least two distinct members designed to move relative to one another after installation.

7. The assembly of claim **1** further comprising at least a second insert adapted to be disposed between said first and second baseplates so as to face said first and second apertures, said second insert of a different configuration than said first insert.

8. The assembly of claim **1** wherein said first insert connects to said first and second baseplates in a fashion so as to be removable therefrom immediately after installation.

9. The assembly of claim **8** wherein said first intervertebral section comprises a groove for mating with said rail.

10. The assembly of claim **1** wherein said first intervertebral section comprises at least two arms extending away from said first mounting section.

11. The assembly of claim **10** wherein said first intervertebral section further comprises a member bridging said arms and space from said first mounting section.

12. The assembly of claim **1** further comprising a plurality of fasteners for securing said mounting sections of said first and second baseplates to respective vertebral members.

13. The assembly of claim **1** wherein said first intervertebral section extends away from said first mounting section generally perpendicular thereto.

14. The assembly of claim **13** wherein said second intervertebral section extends away from said second mounting section generally perpendicular thereto.

15. The assembly of claim **1** wherein said first and second baseplates are interchangeable.

16. The assembly of claim **1** wherein:

said first insert includes a rail;

said first intervertebral section comprises at least two arms extending generally perpendicular away from said first mounting section and a groove for mating with said rail on said first insert;

said first and second baseplates are interchangeable; and said first insert connects to said first and second baseplates in a fashion so as to be removable therefrom immediately after installation.

17. The assembly of claim **16** further comprising at least a second insert adapted to be disposed between said first and second baseplates so as to face said first and second apertures, said second insert of a different configuration than said first insert.

18. The device of claim **1**, wherein said retaining mechanism comprises a screw having a head that extends over the first insert to prevent the insert from moving from between the first and second baseplates.

19. The device of claim **18**, wherein the screw includes a retaining ring having a larger diameter than the head, the retaining ring extending over the first insert.

20. The device of claim **18**, comprising a retaining ring having a central opening through which the screw extends and having a ring body that extends over the first insert.

21. The device of claim **1**, further comprising a second retaining mechanism mounted to said second mounting section to prevent the removal of the first insert.

22. The device of claim **21**, wherein the second retaining mechanism is spaced from said first baseplate such that the first insert is exposed between said first and second baseplates.

23. A modular intervertebral prosthesis kit, comprising:

a first baseplate having a first mounting section and a first intervertebral section extending away from said first mounting section, said first intervertebral section having a first aperture passing therethrough;

a second baseplate having a second mounting section and a second intervertebral section extending away from said second mounting, said second intervertebral section having a second aperture passing therethrough;

a first insert disposed between said first and second baseplates so as to face said first and second apertures and removably mated to said first and second baseplates;

a second insert adapted to be disposed between said first and second baseplates so as to face said first and second apertures when said first insert is unmated from said first and second baseplates, said second insert of a different configuration than said first insert; and

a retaining mechanism removably attached to the first baseplate, and on contact with the first insert to prevent removal of the first insert and the second insert when disposed between the first and second baseplates, the retaining mechanism sized to be spaced away from the second baseplate when mounted to expose the first insert and the second insert.

24. The assembly of claim **23** wherein said first intervertebral section comprises at least two arms extending away from to said first mounting section.

25. The assembly of claim **23** wherein said first insert comprises an articulating insert.

26. The assembly of claim **23** wherein one of said first and second inserts comprises an articulating insert and the other of said first and second inserts comprises a fusion insert.

27. The assembly of claim **23** wherein said first and second baseplates are interchangeable.

28. The device of claim **23**, further comprising a tab that extends outward from the first insert, the tab contacting the first mounting section when the first insert is mounted between the first and second intervertebral sections to prevent over-insertion.

29. The device of claim **28**, wherein one of the first mounting section comprises a recessed notch to receive the tab when the first insert is disposed between the first and second baseplates.

30. The device of claim **23**, wherein the retaining mechanism comprises a screw sized to extend over the first insert and the second insert.

31. The device of claim **30**, wherein the screw includes a retaining ring that extends outward from the screw to extend over the first insert and the second insert.

32. A modular intervertebral prosthesis assembly, comprising:

a first baseplate having a first mounting section and a first intervertebral section extending away from said first mounting section, said first intervertebral section having a first aperture passing therethrough;

a second baseplate having a second mounting section and a second intervertebral section extending away from said second mounting, said second intervertebral section having a second aperture passing therethrough;

at least a first insert disposed between said first and second baseplates proximate said first and second apertures and removably engaging said first and second baseplate; and

a screw mountable to one of the first and second mounting sections to retain the first insert within the first and second baseplates, the screw sized such that the first insert is exposed.

33. The assembly of claim **32** wherein said first insert comprises an articulating insert.

34. The assembly of claim **32** further comprising at least a second insert adapted to be disposed between said first and second baseplates when said first insert is disengaged from said first and second baseplates, said second insert of a different configuration than said first insert.

35. The assembly of claim **32** wherein said first and second baseplates have a generally L-shaped side profile.

36. The assembly of claim **32** wherein said first and second baseplates are interchangeable.

37. The assembly of claim **32**, further comprising a ring attached to the screw, the ring sized to extend over the first insert.

38. A intervertebral prosthesis method, comprising:

providing a first baseplate having a first mounting section and a first intervertebral section extending away from said first mounting section, said first intervertebral section having a first aperture passing therethrough;

providing a second baseplate having a second mounting section and a second intervertebral section extending away from said second mounting section, said second intervertebral section having a second aperture passing therethrough;

securing said first baseplate to a superior vertebral member via said first mounting section;

securing said second baseplate to an inferior vertebral member via said second mounting section;

mating a first insert to said first and second baseplates, between the intervertebral sections thereof, such that said first insert faces said first and second apertures, said first insert being initially removably mated to said first and second baseplates; and

mounting a mechanism to the first baseplate and on contact with the first and retaining the first insert between the intervertebral sections while a front of the first insert remains exposed between the first and second mounting sections.

39. The method of claim further comprising removing said first insert and mating a second insert to said first and second baseplates, between the intervertebral sections thereof, such that said second insert views said first and second apertures.

40. The method of claim **38** wherein said first insert comprises a fusion element.

41. The method of claim **40** comprising fusing said fusion element to said superior and inferior vertebral members via said first and second apertures, respectively.

42. The method of claim **40** wherein said fusion element is selected from the group consisting of allograft bone and autograft bone.

43. The method of claim **38** wherein said first insert comprises an articulating insert.

44. The method of claim 38 further comprising:
unmating said first insert from said first and second
baseplates;

thereafter mating a second insert to said first and second
baseplates, between the intervertebral sections thereof,
such that said second insert faces said first and second
apertures, said second insert being initially removably
mated to said first and second baseplates immediately
after installation thereof.

45. The method of claim 44 wherein said second insert is
of a different configuration than said first insert.

46. The method of claim 44 wherein said first insert
comprises an articulating insert.

47. The method of claim 38, the step of retaining the first
insert between the intervertebral sections comprises posi-
tioning a retaining ring over the first insert.

48. The method of claim 38, wherein the step of retaining
the first insert between the intervertebral sections further
comprises retaining securing members to one of the inferior
or superior vertebral members.

49. A modular intervertebral prosthesis assembly, com-
prising:

a first baseplate having a first mounting section and a first
intervertebral section extending away from said first
mounting section, said first mounting section having a
first aperture to receive a screw to attach the first
baseplate to a first intervertebral member;

a second baseplate having a second mounting section and
a second intervertebral section extending away from
said second mounting;

an insert disposed between said first and second interver-
tebral sections; and

a retaining mechanism attached to the first mounting
section to prevent removal of the screw from the first
intervertebral member and prevent removal of the
insert from between the first and second intervertebral
sections, the retaining mechanism sized such that the
insert is exposed between the first and second base-
plates.

50. The assembly of claim 49, wherein the retaining
mechanism comprises a retaining screw that extends over
the screw and the insert.

51. The assembly of claim 50, wherein the retaining
mechanism comprises a retaining ring sized to extend over
the screw and the insert.

52. The assembly of claim 49, further comprising a
second aperture in the first mounting section to receive a
second screw to attach the first baseplate to the first inter-
vertebral member, the retaining mechanism sized to extend
over the second screw.

53. A modular intervertebral prosthesis assembly, com-
prising:

a first baseplate having a first mounting section and a first
intervertebral section extending away from said first
mounting section, said first intervertebral section hav-
ing a first aperture passing therethrough;

a second baseplate having a second mounting section and
a second intervertebral section extending away from
said second mounting, said second intervertebral sec-
tion having a second aperture passing therethrough; and

at least a first insert disposed between said first and second
baseplates so as to face said first and second apertures
and adapted to engage said first and second baseplates,
the at least first insert further comprises an outwardly-
extending tab that contacts one of the first and second
mounting sections to prevent over-insertion when the
first insert is positioned between the first and second
baseplates.

54. The device of claim 53, wherein one of the first and
second mounting sections comprises a recessed notch in
which the tab contacts when the insert is positioned between
the first and second baseplates.

55. The device of claim 53, further comprising a screw
inserted within one of the first and second mounting
sections, the screw having a head that extends over the tab
to prevent the insert from moving from between the first and
second baseplates.

56. The device of claim 55, wherein the screw includes a
retaining ring having a larger diameter than the head, the
retaining ring extending over the tab.

57. The device of claim 55, further comprising a retaining
ring having a central opening through which the screw
extends and having a ring body that extends over the tab.

58. The device of claim 53, further comprising a retaining
mechanism for retaining the insert within the baseplates.