

US006927834B2

(12) **United States Patent**
Deary et al.

(10) **Patent No.:** **US 6,927,834 B2**
(45) **Date of Patent:** **Aug. 9, 2005**

(54) **LIQUID CRYSTAL ASSEMBLY AND METHOD OF MAKING**

(75) Inventors: **Randall J. Deary**, Littleton, MA (US);
Peter J. Miller, Newburyport, MA (US)

(73) Assignee: **Cambridge Research and Instrumentation, Inc.**, Woburn, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 277 days.

(21) Appl. No.: **10/144,362**

(22) Filed: **May 13, 2002**

(65) **Prior Publication Data**

US 2003/0025869 A1 Feb. 6, 2003

Related U.S. Application Data

(60) Provisional application No. 60/346,329, filed on Jan. 7, 2002, and provisional application No. 60/290,366, filed on May 11, 2001.

(51) **Int. Cl.**⁷ **G02F 1/13**

(52) **U.S. Cl.** **349/158**

(58) **Field of Search** 349/158, 113,
349/43

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,364,039 A	12/1982	Penz	
4,832,460 A	5/1989	Fujimura et al.	
5,257,122 A	10/1993	Dubal et al.	
5,276,747 A	1/1994	Pan	
5,557,692 A	9/1996	Pan et al.	
5,953,087 A	9/1999	Hoyt	
6,018,380 A	1/2000	Hu et al.	
6,172,730 B1	1/2001	Fujita	
6,535,257 B2	3/2003	Miller	349/113
2003/0184705 A1	* 10/2003	Murade et al.	349/158

FOREIGN PATENT DOCUMENTS

WO WO01/81990 A1 11/2001

* cited by examiner


Primary Examiner—James A. Dudek

(74) *Attorney, Agent, or Firm*—Fish & Richardson P.C.

(57) **ABSTRACT**

A method for producing a liquid crystal device, the method including: assembling two substrates to form at least one liquid crystal cell; and removing material from a first one of the assembled substrates to produce a first region of the first substrate that is thinner than a second region of the first substrate.

42 Claims, 16 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B

LIQUID CRYSTAL ASSEMBLY AND METHOD OF MAKING

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority from the following U.S. provisional patent applications: Ser. No. 60/346,329, entitled "Method for fabricating liquid crystal cells with wedged outer faces" by Randy Deary and Peter J. Miller, filed Jan. 7, 2002, and Ser. No. 60/290,366, entitled "Stress-relief of Liquid Crystal Cells" by Randall J. Deary, filed May 11, 2001. The contents of both provisional application are incorporated herein by reference.

BACKGROUND

The invention relates to liquid crystal devices and methods of making liquid crystal devices. Liquid crystal technology has many applications. For example, liquid crystal devices can be used to selectably vary the retardance, intensity, and/or polarization of an incident beam. Such devices may include a single liquid crystal component or multiple liquid crystal components in optical series. Each liquid crystal component includes two substrates sandwiching a layer of liquid crystals, and the substrates each support an electrode. An electric field can be applied across the liquid crystal layer via the electrodes to cause a change in the orientation of the liquid crystals, which in turn causes an incident beam to see a change in the retardance of the liquid crystal layer. The component(s) can be combined with additional optical elements (e.g., polarizers, waveplates, fixed retarders, etc.) for modifying the output of an incident beam. As is common in the art, such liquid crystal devices can be configured in both reflective and transmissive arrangements.

One problem that can occur when using liquid crystal devices is that undesired reflections from one or more interfaces in the device can interfere with the main output beam and degrade the optical performance of the device. Such interference effects can be especially significant for a coherent input beam. Sometimes a wedge is introduced into the device to reduce the overlap between the main output beam and one or more of the reflected beams.

A second problem that can occur is thermal expansion of the liquid crystals within the device. Such expansion can degrade the optical performance of the device and ultimately lead to mechanical failure (e.g., failure of the perimeter seal).

Another consideration relates to the manufacturability of such liquid crystal devices. For many applications (e.g., telecom applications), the liquid crystal device should be small and compact. Unfortunately, it can be difficult to achieve robust and economical manufacture when handling and assembling such small components.

SUMMARY

The inventors have realized that after two substrates are assembled into a liquid crystal cell, one or both of the substrates can be ground to remove material and shape the substrate(s). Notably, such grinding can be accomplished without degrading the liquid crystal cell. The grinding is especially robust when, for example, the liquid crystal cell is filled with liquid crystals, because the liquid crystals provide hydrostatic support to the assembled substrates.

The shaping may include forming a wedge in one or both of the substrates to reduce interference effects caused by

undesired reflections. Furthermore, the shaping may include thinning a region of one or both of the substrates such that it deforms to accommodate thermal expansion of the liquid crystals and thereby provides stress relief. In either case, at least one of the substrates adjacent the liquid crystal layer has a first region thinner than a second region of the substrate. Because the substrate is ground after it is assembled into a cell, it is easier to handle because it is supported by the rest of the cell, which, in addition to the opposite substrate and liquid crystal layer, may further include one or more additional optical components secured to the cell adjacent the opposite substrate. Moreover, because the substrate is supported, it may be initially thin (e.g., less than 1.2 mm), and a portion of it may be ground to be even thinner (e.g., less than 1.0 mm, or even less than 0.5 mm). This can lead to a more compact device.

Furthermore, because the shaping can occur after the liquid crystal cell is assembled, the liquid crystal cell can be produced from an array of liquid crystal cells mass produced from large, substantially planar substrates. Such planar substrates lend themselves to large scale lithography techniques that can be used to pattern the substrates with electrodes for multiple cells. The patterned substrates can then be assembled into an array of liquid crystal cells, and subsequently die cut to produce individual cells or sub-arrays of cells (e.g., strips of cells) using the highly-developed tools, fixtures, and processes developed by the display industry. For example, such tool and processes are used in the steps of depositing a suitable alignment layer, substrate lamination, and filling with liquid crystal.

In some embodiments, rather than shape individual liquid crystal cells, the shaping may be applied to one (or both) of the substrates of an array or sub-array of liquid crystal cells, which are then subsequently divided into individual cells. This may ease handling of the cells during the grinding process by increasing the size of the object being ground. Furthermore, in additional embodiments, shaping may be applied to a large substrate prior to its assembly into an array of liquid crystal cells, which are subsequently divided into individual cells.

In general, in one aspect, the invention features a method for producing a liquid crystal device. The method includes: assembling two substrates to form at least one liquid crystal cell; and removing material from a first one of the assembled substrates to produce a first region of the first substrate that is thinner than a second region of the first substrate.

Embodiments of the method may include any of the following features

The method may further include filling the cell with liquid crystals. Furthermore, the cell may be filled with liquid crystals before the material is removed from the first substrate, or after the material is removed from the first substrate.

Removing material from the first substrate may include grinding the first region of the first substrate. It may further include polishing the first region of the first substrate. During the grinding, the temperature of the first substrate may be preferably maintained to within 5° C. of a nominal temperature.

Assembling the two substrates may include forming an array of liquid crystal cells. The array may be, for example, a one-dimensional array (e.g., a strip) or a two-dimensional array. The method may further include dividing the array of liquid crystal cells into separate liquid crystal cells, wherein the removal of the material from the first substrate includes removing material from the first substrate of at least one of

3

the separated liquid crystal cells. Alternatively, the array of liquid crystals may be a two-dimensional array and the method may further include dividing the two-dimensional array into separate one-dimensional strips of liquid crystal cells, wherein the removal of the material from the first substrate includes removing material from the first substrate of at least a first one of the strips of liquid crystal cells. In such embodiments, the method may further include dividing the first strip of liquid crystal cells into separate liquid crystal cells after removing the material from the first substrate. Finally, the method may further include dividing the array of liquid crystal cells into separate liquid crystal cells after removing the material from the first substrate. In such embodiments, the first and second regions of the first substrate may extend across multiple ones of the liquid crystal cells in the array.

Prior to the assembly of the liquid crystal cell, the two substrates may planar substrates. After the removal of the material, the first region of the first substrate may have a thickness less than 1.2 mm, or even less than 1.0 mm. Also, the method may include patterning each substrate with at least one electrode for use with the liquid crystal cell.

In some embodiments, the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of liquid crystals in the liquid crystal cell over a range of operating temperatures. For example, the range of operating temperatures may span at least 30° C. (e.g., the range of operating temperatures may be from about 5° C. to at least 70° C.). The second region of the first substrate may be at least 20% thicker than, or even twice as thick as, the first region of the first substrate.

In some embodiments, the removal of the material may introduce a wedge to the first substrate (e.g., the wedge may define a wedge angle of at least 0.25°). The wedge may be used to reduce interference effects caused by an undesired reflection from the first substrate during use of the liquid crystal cell. The wedge may include the thinner first region and the thicker second region. Alternatively, or in addition, the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of liquid crystals in the liquid crystal cell over a range of operating temperatures. In such embodiments, the wedge may extend over at least a portion of the second region.

The method may further include removing material from the second assembled substrate to produce a first region of the second substrate that is thinner than a second region of the second substrate.

The method may further include securing an optical component to the liquid crystal cell in series with an optical aperture of the liquid crystal cell. The optical component may be, e.g., a retarder, a polarizer, another liquid crystal cell, or an optical window. For example, the optical window may be used to stiffen at least a portion of the cell. Instead of, or in addition to, securing an optical component to the cell, the method may further include securing a stiffening component (e.g., a metal) to at least a portion of the cell. In general, the optical component or stiffening component may be secured to the cell adjacent the second substrate prior to removing the material from the first substrate, or the optical component or stiffening component may be secured to the cell after removing the material from the first substrate. The stiffening component and/or optical component may be secured to only the first substrate, only the second substrate, or to both substrates.

4

In those embodiments that involve an array of liquid crystal cells, the method may further include securing an optical component to be in optical series with the array of liquid crystal cells. The optical component may be, e.g., a retarder, a polarizer, another liquid crystal cell, or an optical window. For example, the optical window may be used to stiffen at least a portion of the cell array. Instead of, or in addition to, securing an optical component to the cell array, the method may further include securing a stiffening component (e.g., a metal) to at least a portion of the cell array. In general, the optical component or stiffening component may be secured to the cell array adjacent the second substrate prior to removing the material from the first substrate, or the optical component or stiffening component may be secured to the cell array after removing the material from the first substrate. The stiffening component and/or optical component may be secured to only the first substrate, only the second substrate, or to both substrates. The method may further include dividing the array of cells and the secured optical component into separate liquid crystal devices.

In general, in another aspect, the invention features a method for producing a liquid crystal device. The method includes: assembling two substrates to form at least one liquid crystal cell; and removing material from a first one of the assembled substrates to produce a wedge along the first substrate.

In general, in another aspect, the invention features a method for producing a liquid crystal device. The method includes: assembling two substrates to form at least one liquid crystal cell; and removing material from a first one of the assembled substrates to produce a first region of the first substrate that is thinner than a second region of the first substrate, wherein the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of liquid crystals in the liquid crystal cell over a range of operating temperatures.

In general, in another aspect, the invention features a method for producing multiple liquid crystal devices. The method includes: providing two substrates; removing material from a first one of the substrates to produce a first region of the first substrate that is thinner than a second region of the first substrate; assembling the substrates to form an array of liquid crystal cells; and after the substrate material is removed from the first substrate, dividing the array of liquid crystal cells into separate liquid crystal cells. The removal of the material may occur before the assembly of the substrates into the array liquid crystal cells, or the removal of the material may occur after the assembly of the substrates into the array liquid crystal cells. The method may further include any of the other method features described above.

In general, in another aspect, the invention features a liquid crystal device including: two unitary substrates sandwiching a layer of liquid crystals, wherein each substrate supports at least one electrode, wherein a first one of the substrate has a first region that is thinner than a second region of the first substrate, and wherein the first region of the first substrate has a thickness less than 1.2 mm.

Embodiments of the liquid crystal device may include any of the following features.

The first region of the first substrate may be sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of the liquid crystals over a range of operating temperatures. For example, the range of operating temperatures may span at least 30° C. (e.g., the range of operating temperatures may

5

be from about 5° C. to at least 70° C.). The second region of the first substrate may be at least 20% thicker than, or even twice as thick as, the first region of the first substrate. The first substrate may include a wedge (e.g., the wedge may define a wedge angle of at least 0.25°). The wedge may be used to reduce interference effects caused by an undesired reflection from the first substrate during use of the liquid crystal device. The wedge may include the thinner first region and the thicker second region. Alternatively, or in addition, the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of the liquid crystals over a range of operating temperatures. In such embodiments, the wedge may extend over at least a portion of the second region.

The second substrate may include a first region that is thinner than a second region of the second substrate.

The first region of the first substrate may have a thickness less than 1.2 mm, or even less than 1.0 mm.

The device may further include an optical component secured in optical series with at least a portion of the liquid crystal layer. The optical component may be, e.g., a retarder, a polarizer, another liquid crystal cell, or an optical window. For example, the optical window may be used to stiffen at least a portion of the cell. Instead of, or in addition to, an optical component being secured to the cell, the device may include a stiffening component (e.g., a metal) secured to at least a portion of the cell. The stiffening component and/or optical component may be secured to only the first substrate, only the second substrate, or to both substrates.

In general, in another aspect, the invention features a liquid crystal device including: two unitary substrates sandwiching a layer of liquid crystals, wherein each substrate supports at least one electrode, wherein a first one of the substrates has a wedge and a thickness less than 1.2 mm.

In general, in another aspect, the invention features a liquid crystal device including: two unitary substrates sandwiching a layer of liquid crystals, wherein each substrate supports at least one electrode, wherein the first substrate has a first region that is thinner than a second region of the first substrate, and wherein the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of the liquid crystals over a range of operating temperatures.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1A is a front view of a liquid crystal device with integral stress relief.

FIGS. 1B–C are side views of a liquid crystal device with integral stress relief.

FIGS. 2a–b are side views of a liquid crystal device with an integral wedged substrate.

FIG. 3 is a side view of a liquid crystal device with an integral wedged substrate and integral stress relief.

FIG. 4 is a side view of a liquid crystal device with an integral wedge and stress relief on both substrates.

FIG. 5A is a side view of a composite liquid crystal device with integral wedged substrates and stress relief.

FIG. 5B is a side view of a transmissive liquid crystal device with an integral wedged substrate, a substrate with a stress relief portion, and an external stiffener.

6

FIG. 5C is a side view of a reflective liquid crystal device with an integral wedged substrate, a substrate with a stress relief portion, and an external stiffener.

FIG. 6 is a system that uses a liquid crystal device.

FIG. 7 is a flow chart of a method for forming liquid crystal devices.

FIG. 8a is a schematic diagram of an apparatus for grinding a stress relief portion of a liquid crystal device.

FIG. 8b is a schematic diagram of an apparatus for grinding and polishing a wedged portion of a liquid crystal device.

FIG. 8c is a perspective view of a liquid crystal array with an integral stress relief portion formed into a substrate.

FIGS. 9A–B are side views of alternate embodiments of composite liquid crystal devices.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

Liquid crystal devices are described in which material is removed from at least one of the substrates that sandwich the liquid crystal layer to form a shaped substrate that addresses one or both of the problems of interference from spurious reflections and thermal expansion of the liquid crystals. For example, the shaped substrate can be wedged to reduce interference from spurious reflections. Furthermore, the substrate can be shaped to produce a stress-relief region that deforms to accommodate thermal expansion of the liquid crystals.

The substrate can be shaped by grinding and polishing it. Notably, such grinding and polishing can be applied to the substrate after the assembly of the liquid crystal cell. As a result, large substrates that are initially planar may be used to mass produce an array of liquid crystal cells prior to the grinding and polishing. Such mass production is more economical and tends to produce more robust cells.

In the description that follows, we first discuss a number of embodiments of the devices, and then discuss suitable methods for producing such devices.

Referring to FIGS. 1A–C, a liquid crystal device **100** is shown. Device **100** includes two substrates **110** and **120** that form the front and back of the device respectively. The substrates **110** and **120** are held together by adhesive bead **130**. The substrates and the adhesive bead **130** form a first and second volumes **142** and **144** respectively. A passage **160** connects the two volumes. The volumes are filled with a liquid crystal **105**. An inlet **180** in the adhesive bead **130** allows the introduction of the liquid crystal into the two volumes **142** and **144** and is subsequently sealed by a plug **190**. Referring to FIGS. 1B and 1C, cross sectional views of device **100** are shown about axes **101** and **102** respectively. Substrate **110** includes a first portion **112** and a second portion **114**. Portion **114** is thinner than portion **112**. The first portion **112** corresponds to the portion of the substrate **110** that forms one of the walls for the first volume **142**. The second portion **114** corresponds to the portion of substrate **110** that forms one of the walls for the second volume **144**.

In some embodiments, the liquid crystal layer formed in volume **142** is designed to interact with light passing through the device and is known as the optical or display portion of the device. Typically, the interaction of light with liquid crystal depends on the alignment of the liquid crystal molecules. The inner surfaces of the substrates may be treated to enhance the alignment of the liquid crystals. Examples of such layers are buffed polymer alignment films.

Furthermore, the optical interaction is modulated by way of electric fields that modulate the alignment of the liquid crystals. The inner surface of substrates **110** and **120** have electrodes **160** and **150** respectively. Voltages applied to the electrodes produce the electric fields that modulate the interaction of light with the liquid crystal layer. Positioning of the electrodes on the outer surface of the substrates or elsewhere is possible.

In some embodiments, the substrate is patterned to define an array of individually addressable electrodes. Voltages on each of the individual electrodes independently modulate the light interaction in the vicinity of the electrode and thus define a corresponding pixel in the display portion. Controlling the individual voltages spatially modulates the optical properties of the device from pixel to pixel across the display region. Often such device is referred to as a spatial light modulator (SLM). In addition, liquid crystal devices can be either transmissive or reflective type devices. For transmissive type liquid crystal devices, the electrodes are often transparent indium-tin oxide (ITO) electrodes. For reflective type liquid crystal devices, the electrodes on one of the substrates can be a reflective metal layer such as gold. In other embodiments of reflective type liquid crystal devices, both sets of electrodes are transparent and the reflective portion is some other reflective layer for example an external mirror attached to the device.

In most applications the interaction of light with the liquid crystal layer also depends on the thickness of the liquid crystal layer. For example, the retardance, R , of a layer is given by

$$R = 2\pi \frac{\Delta n(V)L}{\lambda} \quad [1]$$

wherein λ is the wavelength of the light, $\Delta n(V)$ is the voltage dependent birefringence, and L is the thickness of the liquid crystal layer (assuming a single pass device). From Eq. [1] it is clear that if the thickness varies then the performance of the device varies. Furthermore, variations in thickness across the display aperture produce variations in device performance as a function of position. In many embodiments, it is desirable to have a uniform liquid crystal thickness across the display portion. Typical devices have liquid crystal layers with thicknesses for example in the range from about 1 μm to about 30 μm . In some embodiments, the layer thickness varies by no more for example 30 nm. Mechanical spacers (not shown) can aid in maintaining uniform spacing between the substrates during manufacture.

As the temperature of the device changes, the liquid crystal expands and contracts. As the liquid crystal **105** is very nearly incompressible, expansion of the liquid crystal leads to changing pressures on the substrates **110** and **120**, the adhesive bead **130** and the plug **190**. Such pressures can lead to mechanical failure of liquid crystal devices. Furthermore such pressures can deform the substrates that form the optical display region and thus deform the thickness of the liquid crystal layer.

To reduce the variations in liquid crystal layer thickness and thus variations in optical performance, the second portion **114** of substrate **110** is substantially thinner than the first portion **114** of substrate **110**. Portion **114** is also thinner than substrate **120**. As a result, the second portion **114** has a stiffness that is substantially less than the stiffness of the first portion **112** of substrate **110** or substrate **120** (assuming they are constructed from materials with similar mechanical properties). As the pressure builds in the device due to

thermal expansion of the liquid crystal **105**, the second portion **114** deflects outwards increasing the volume available for the liquid crystal and moderating the increase in pressure. This provides a stress relief function for the liquid crystal device.

Similarly as the liquid crystal layer contracts, the internal pressure decreases. Such a pressure drop can lead to cavitation or bubble formation in the liquid crystal layer degrading optical performance. In some embodiments or under extreme operating conditions, such a low internal pressure can even deform the liquid crystal thickness in the optical display region. To avoid such low internal pressures, the second portion **114** deflects inward as the liquid crystal layer contracts with temperature. This moderates the internal pressure of the liquid crystal layer.

The stiffness of portion **114** relative to portion **112** and relative to substrate **120** over a large range of deformations of portion **114** ensures that the stress relief deformation occurs primarily in portion **114** and not appreciably in portion **112**. This maintains the uniformity of the liquid crystal layer thickness over a large range of temperatures. Furthermore by moderating both the maximum and minimum pressure inside the device, the stress relief function of portion **114** reduces the probability of pressure related failure of the cell.

The stress relief function is provided by the thickness of portion **114** relative to portion **112** and relative to substrate **120**. For example, the thickness of the portion **114** is typically at least 100 microns less than the first portion **112**. A transition of thickness between first portion **112** and second portion **114** is formed by connecting portion **113**. The connecting portion preferably provides a smooth transition from the thicker portion **112** to the thinner portion **114**. This avoids fracturing the substrate **110** as the portion **114** deflects due to changes in the volume of the liquid crystal.

Furthermore, in embodiments that use device **100** adjacent to another optical component (as will be described subsequently), the stress relief function is typically not impeded by a planar optical element that sits flush against portion **112**.

In addition to considering the stiffness of the second portion **114** relative to first portion **112** and substrate **120**, the relative volumes of volume **142** and volume **144** may also be considered. Given the total volume of the liquid crystal layer at one temperature, the volume at another temperature can be readily calculated. These changes in volume are accommodated by the deformation of the second portion **114**. A larger (by area) second portion **114** produces a larger change in volume for the same amount of vertical deflection. In some applications, the area of the second portion can be relevant, for example, when trying to minimize the size of the device. In such cases, a reduction in the area of the second portion can be compensated by a reduction in the stiffness of the second portion.

The design is based on the overall mechanical properties of the expansion region. It includes the area and geometry of the expansion region, as well as the thickness of the glass. The stiffness preferably is kept low enough in absolute terms to permit expansion without the high pressure that could cause mechanical failure, and low enough relative to the aperture that the majority of the deformation occurs in the stress relief portion, and not in the optical display region.

The relationship between the relative volumes, the relative stiffnesses, the failure limits of the cell components, and the operating conditions for the cell is calculated and optimized using well known engineering techniques. For example, commercially available finite-element computer

programs such as NASTRAN, from MacNeal, Schwendler Corp., are used to determine the stiffnesses of the cell components using the actual design geometry and materials used. Similarly, the modeling of the deformation of the cell under varying design choices and varying conditions is based on conventional mechanical engineering techniques known to those skilled in the art, such as described by R. D. Cook in Concepts and Application of Finite Element Analysis, (Wiley & Sons, NY, 1989). Given a set of desired performance parameters (for example, size, materials, operating temperature range, thickness uniformity of the liquid crystal layer) such techniques are used to define mechanical proportions of devices with the desired performance.

In addition to concerns about liquid crystal layer uniformity, the optical interfaces in liquid crystal devices lead to spurious reflections. The spuriously reflected beams can interfere with the main beam of the device often degrading optical performance. A wedged surface reduces the interference from such reflections. Referring to FIG. 2A, a liquid crystal **200a** device is shown. Similar to device **100**, the liquid crystal device has two substrates **210a** and **220a** joined by adhesive bead **230a**. The substrate **210a** has a wedged portion **212a**. Device is a transmissive type cell with transparent electrodes **250a** and **260a**. Typically such electrodes are formed from ITO. Two light beams are shown. Beam **270a** shows the main beam that passes through the device. A beam **280a** results from the spurious reflection of the main beam off the back surface of substrate **220a** (the normal reflection should reflect at a normal angle but is drawn at a non normal angle for clarity of the beam path). This beam subsequently reflects from the front surface of wedged substrate **210a** and exits the cell. In the case of two parallel surfaces (ie no wedge), such reflections overlap and can interfere. The wedge eliminates the spatial overlap of the two beams by deflecting the unwanted beam out of the optical path and thus reduces the optical interference.

Referring to FIG. 2B, a liquid crystal **200b** device is shown. Similar to device **100**, the liquid crystal device has two substrates **210b** and **220b** joined by adhesive bead **230b**. The substrate **210b** is wedged. The device is a reflective type cell with reflective electrode **250b** and transparent electrode **260b**. The reflective electrode is typically formed from a reflective metal such as gold. Three light beams are shown. Beam **270b** shows the main beam that passes through the liquid crystal layer **205b** and is reflected back through the layer and out of the device. Beam **280b** results from the spurious reflection of the main beam off the front surface of substrate **210b** and the reflection from the reflective electrode **250b**. Similarly a beam **290b** results from reflection of the main beam of the wedged substrate. The wedge eliminates the spatial overlap of these two beams with the main beam by deflecting them out of the optical path and thus reduces the optical interference. In other embodiments of reflective cells, both electrodes can be transparent and another reflective surface provides the reflectivity. For example, an external mirror can be affixed to the wedged portion **212a** of device **200a** to form a reflective cell.

A particular embodiment of device **200b** is given. The substrates are 0.5 mm thick Corning 1737F glass supplied by Corning Glass, Corning N.Y. Substrate **210b** has a size of 8×16 mm while substrate **220b** has a size of 12×16 mm. A transparent electrode **260b** is on the inner surface of substrate **210b** and a reflective gold electrode **250b** is on the inner surface of substrate **220b**. The gold layer forms the reflective layer. The outer face of substrate **210b** is polished to impart a 0.5 degree wedge onto substrate **220b** (the methods by which the wedge is formed is discussed below). The wedge is directed along the short axis of substrate **220b**.

In yet other embodiments, other wedge angles can be employed with unequal wedges on either substrate oriented along either axis of the face of the substrate. For example, in another embodiment, an 8×12 mm cell is formed from two 0.5 mm substrates. A 0.5 degree wedge is polished on each of the outer faces of the substrates along the same axis but with the wedges in opposite directions. The resulting assembly is wedged by 1 degree and the liquid crystal layer is not parallel to either substrate face. Often such devices are stacked in series with other optical devices such as other liquid crystal devices, retarders, waveplates, and polarizers. In such composite devices, each optical interface generates spurious reflections. Thus the wedging angle of a liquid crystal device **200** can be designed not only to reduce interferences between surfaces within that device but also between surfaces of a composite optical device that includes liquid crystal device **200**.

In device **200a**, the interfering beam required two reflections from the relatively low reflectivity surfaces. In contrast, in device **200b**, the interfering beams required only one low reflectivity reflections. The low reflectivity surfaces are surfaces that are not intended to reflect the main beam but due to an optical interface reflect a smaller spurious beam. Therefore devices similar to device **200b** are more susceptible to interference effects. In addition to the reflections already considered in device **200a** and **200b**, there are a number of surfaces in typical liquid crystal devices that form spurious reflections. Not all pairs of surfaces need to be wedged relative to each other to avoid interference. The spectral separation between peaks in a fringe pattern is related to the optical path difference between the two interfering beams. A small optical path difference results in a low order interference and therefore a large spectral separation between fringe peaks. On the other hand, a large optical path difference leads to high order interference and therefore a small spectral separation. The coherence length of the light being used bounds the upper limit of such high order interferences. In many applications, especially where specific wavelengths are used, the low order/large separation interferences can be suitably filtered from the system by frequency dependent filtering. On the other hand, the higher order interferences with smaller spectral separation become increasingly difficult to filter. In such situations, the integral optical wedging of a substrate discussed above can reduce such high order fringing by sufficiently deflecting one of the beams and reducing interference.

Referring to FIG. 3 a cross sectional view of a liquid crystal device **300** is shown. Device **300** includes features similar to those in devices **100** and **200**. Device **300** includes two substrates **310** and **320** joined by adhesive bead **330**. The device has electrodes **350** and **360**. A first portion **312** of the substrate **310** is wedged. A second portion **314** of substrate **310** is substantially thinner than substrate **320** and first portion **312** of substrate **310** and thus portion **314** provides a stress relief function for device **300** while the wedge of portion **312** reduces fringing and interference effects. A connecting portion **313** connects portions **312** and **314** and preferably provides a smooth transition between the two portions. Some embodiments of device **300** are transmissive type cells and some embodiments are reflective type cells.

Referring to FIG. 4, a cross sectional view of a liquid crystal device **400** is shown. Device **400** includes two substrates **410** and **420** joined by adhesive bead **430**. A first portion **412** of the substrate **410** has a wedge of angle θ_1 . Furthermore, substrate **410** has a second portion **414** that is substantially thinner than first portions **412** or **422**.

11

Similarly, substrate **420** has a first portion **422** that is wedged with angle θ_2 and a second portion that is substantially thinner than first portions **422** and **412**. The second portions provide a stress relief function for the device and the wedged first portions reduce optical interference and fringing. The device includes electrodes **450** and **460**. Some embodiments of device **400** are transmissive type cells and some embodiments are reflective type cells. The wedge angles θ_1 and θ_2 can be different and the wedge axes can be opposite, orthogonal or even at some arbitrary angle to the plane of the substrates. Such choices typically depend on the intended use of the device. In some embodiments of device **400**, the dual stress relief of substrates **414** and **424** of device **400** also affords greater design flexibility. Both portions **414** and **424** provide stress relief and thus for a given area, portions **414** and **424** together provide roughly twice as much as expansion volume as available with portion **114** in device **100**. In some applications, especially where device size becomes important such design flexibility can be useful.

The liquid crystal devices similar to devices **100**, **200**, **300** or **400** are stacked in series with similar liquid crystal devices or with other optical elements to provide a composite liquid crystal device. Referring to FIG. 5A, a composite liquid crystal device **500** is shown. The composite device includes two liquid crystal devices **500a** and **500b** that are similar to device **400**. Device **500a** includes substrates **510a** and **520a** joined by adhesive bead **530a**. The device **500a** includes electrodes **550a** and **560a**. A first portion **512a** of the substrate **510a** has a wedge of angle θ_A . Furthermore, substrate **510a** has a second portion **514a** that is substantially thinner than first portions **512a** or **522a**. The second portions provide a stress relief function for the device and the first wedged portions reduce fringing and interference. Device **500b** includes substrates **510b** and **520b** joined by adhesive bead **530b**. The device **500b** includes electrodes **550b** and **560b**. A first portion **512b** of the substrate **510b** has a wedge of angle θ_B . Furthermore, substrate **510b** has a second portion **514b** that is substantially thinner than first portions **512b** or **522b**. The second portions provide a stress relief function for the device and the first wedged portions reduce fringing and interference. As shown in FIG. 5A, the two devices **500a** and **500b** are stacked such that the stress relief portions **544a** and **544b** are directed in opposite directions but the relative orientation of the stress relief portions can be varied to suit the specific application. The stacked devices may be joined by using an index matched adhesive, or optical contact binding, or by other known techniques for bonding the devices together. Furthermore, the wedges of device **500** (i.e., surfaces **512a**, **512b**, **522a**, and **522b**) can have differing angles and orientations. As noted before, fringing occurs between pairs of interfaces and thus device **500** has not only intra cell pairs of surfaces but also inter cell pairs of surfaces. By considering the spacing of pairs of surfaces in the composite device including surfaces from elements such as retarders, polarizers, and or waveplates, choices in wedging angles and orientations are made that minimize the fringing and interference effects within the composite device. Such choices and the resulting performance of the optical device can be tested using known ray tracing techniques. Although composite device **500** is shown in FIG. 5A with only two devices stacked together, in other embodiments multiple liquid crystal devices can be stacked and interleaved with multiple other optical elements. For example, an element such as a retarder, polarizer or waveplate can be sandwiched between the liquid crystal cells. Furthermore, the liquid crystal devices that form the composite device can be combinations of transmissive and reflective cells.

12

As devices are stacked together, the contacting regions mechanically support each other. In some embodiments, the design of liquid crystal cells for a composite device incorporates this fact. The mechanical engineering calculations discussed above can consider the additional mechanical support provided by elements other than the substrates of each device alone. In some embodiments, such considerations allow the reduction of the substrate thickness in the contacting region since the mechanical support of the adjacent structures allows for thinner substrates.

In some embodiments, external components are attached to a substrate in order to mechanically stiffen the substrate. Referring to FIG. 5B, a liquid crystal device **500'** is shown. The device includes substrates **510'** and **520'**. Substrate **510'** includes a wedged portion **512'** and substrate **520'** includes a stress relief portion **524'**. The device includes transparent electrodes **550'** and **560'**. Device **500'** includes an external component **526'** that is attached to the optical portion **522'** of substrate **520'**. In this particular embodiment, the external component includes an optical window that is transparent as indicated by transmitted light beam **570'**. The external component stiffens the optical display portion of the device and thus reduce pressure induced variations in the liquid crystal thickness. Even in embodiments wherein the external component extends past the connecting portion **523'** as shown, the external component does not compromise the stress relief function of portion **524'** by physically blocking the expansion of portion **524'**. The external component may provide a convenient location for attaching the device to a housing. As noted previously, in some embodiments an external optical component may be added to the substrate, therefore, in those embodiments, external component **526'** can be an external optical component that provides both a mechanical and optical function to the device.

In other embodiments, the external component need not be a transparent element. Referring to FIG. 5C, a reflective liquid crystal cell **500''** is shown. The device includes substrates **510''** and **520''**. Substrate **510''** includes a wedged portion **512''** and substrate **520''** includes a stress relief portion **524''**. The device includes transparent electrode **560''** and reflective electrode **550''**. Device **500''** includes external component **526''** that is attached to the optical portion **522''** of substrate **520''**. The external component stiffens the optical display portion of the device and thus reduce pressure induced variations in the liquid crystal thickness. Because the device is a reflective device configured as shown, note beam path **570''**, the external component **526''** need not have a transparent window and thus can be a metal or other suitable material that stiffens the portion **522''**. The external component also provides a handle for attaching the device to a housing.

Referring to FIG. 6, a system **600** that uses a liquid crystal device is shown. System **600** includes a light source **610** that produces light beam **620**. The light beam **620** passes through optical element **630** that may be for example a retarder, polarizer or waveplate. The light beam interacts with liquid crystal device **640**. Device **640** can be any of the single or composite liquid crystal devices discussed above. Controller **645** controls the voltages of the liquid crystal device electrodes (not shown). After being output by the liquid crystal device **640**, the light passes through optical element **650** that may be for example a retarder, polarizer or waveplate, resulting in output light beam **660**. Although schematically drawn as a transmissive device, in other embodiments the liquid crystal device **640** may be either transmissive or reflective.

For example, in some embodiments, the device **640** is stacked in series with a fixed optical retarder **630**. Such a

retarder is placed in series with the device and oriented with its slow axis either parallel to or perpendicular to the retarder axis of the liquid crystal device. Often such configurations are used to compensate for the residual retardance of the liquid crystal device that remains even at high applied voltages. The fixed retardance effectively can cancel the residual retardance of the device and produce a device with zero retardance, or some other desired retardance as may be required by the task at hand.

The above discussion outlines several embodiments of liquid crystal devices, now we turn to a discussion of the methods for forming these devices. Referring to FIG. 7, a flowchart outlines method **700**. The method preferably begins by obtaining two panels (Step **705**). The positioning and manipulation of these panels uses known manufacturing techniques and equipment and therefore for ease of manipulation and precision placement and alignment, the panels are preferably flat planar panels. The method processes the two panels into a laminated array of cells (Step **710**). Typically a dispenser forms an array of adhesive beads by repeatedly depositing adhesive beads onto one of the panels in a tiled pattern. The other panel is placed onto the bead and the two panels are joined together. Spacers can be used to provide an exact and uniform spacing between the two glass panels. Typical panels sizes are, for example, about 1 mm thick and 50 to 600 mm on a side. The spacing between the substrates is, for example, about 1 μm to about 30 μm .

These arrays can be 1x1, 1xn, or mxn sized arrays. The method is amenable to mass production of the liquid crystal devices. The processing of a single array panel with mxn individual devices highlights the efficiency of the method. All mxn devices are moved, positioned, and processed at the same time. This increases reliability and throughput. Optionally, the panelized assembly of cells is partially singulated into strips of cells or completely singulated into individual cells (Step **720**). Typically a scribe or a laser singulates the panelized assemblies. Using either the individual cells or the partially singulated strips each cell is filled with liquid crystal and the fill hole is subsequently sealed (Step **730**). In other embodiments discussed below, the filling and or singulating of the cells is performed later in the method.

A grinder and/or polisher grinds or polishes the surface of a substrate (Step **740**). The grinding and polishing is applied to one or both substrates of the device. Either substrate can be ground or polished to form either one or both of a wedged portion or a stress relief portion in the substrate. Referring to FIG. **8a**, a schematic diagram of an apparatus for grinding a stress relief portion of a substrate is shown. A grinder **800** removes material from the surface of a substrate **310a**. The grinder **800** includes a chuck **840** that holds the liquid crystal device or the substrate while plate **820** moves with an orbital motion relative to substrate **310a**. Positioner **810** maintains the relative position and orientation of plate **820** with respect to substrate **310a**. A grinding slurry **830** is introduced to the surface of substrate **320** by slurry injector **835**. Typically the slurry **830** includes an abrasive compound. The orbital action of the plate relative to the surface **320a** in conjunction with the slurry grinds away material from the surface. The polishing plate **820** includes a flat **822** and a connecting portion **823**. The flat and connecting portion are designed such that as the material is removed, both a thinner second portion **314a** is formed and an additionally a connecting portion **313a** is formed. As the second portion **314a** provides the stress relief for the device, the surface of the second portion need not be smooth enough for high precision optical performance. Thus while the second portion is being

formed, the grade of abrasive is chosen to remove material efficiently. In the preferred embodiment, the liquid crystal cells are filled and sealed prior to the grinding of step **740**. This provides a number of advantages. The liquid crystal layer **305a** provides hydrostatic support for the substrate and thus reduces device failure during grinding. Furthermore, the laminated device is typically stronger and more robust than the substrates alone and therefore the laminated substrate can be thinned substantially more than the substrate alone allowing for a greater flexibility in design of the devices. Furthermore, contamination, especially water contamination, of the empty volumes can be a problem. Therefore it is preferable to fill and seal the devices soon after the substrates are laminated together.

Referring to FIG. **8b**, a schematic diagram of the grinding apparatus being used for wedging a portion of a liquid crystal device is shown. After grinding the second portion of the substrate, the plate **820** is tilted relative to substrate **310a**. The tilt angle θ_3 is determined by the amount of wedge that is desired. The chuck **840** moves the cell relative to the plate such that the plate is positioned over a first portion **322a** of the substrate. Again the orbital motion of the plate relative to the substrate in conjunction with the slurry removes material to form the desired wedge on the surface of the first portion. The first portion is typically the optical portion. As the substrate material is removed, the slurry injector **835** introduces finer and finer grades of abrasives. This polishing step produces a surface of suitable flatness and surface smoothness for precision optical applications. For example, a standard optical finish is flat to $\frac{1}{10}$ wave, with smoothness of a few nm. In some embodiments, the polishing uses another machine built specifically for that purpose.

In embodiments that fill and seal the cells before grinding, the temperature of the substrate, the liquid crystal layer **305a** and preferably the entire cell are preferably maintained at a constant temperature. Typically this temperature is close to the desired operating temperature of the device. Excessive temperature or temperature variation during the grinding and polishing produce pressures due to the expanding liquid crystal layer as described above. If the optical portion of the substrate is deflecting during the grinding/polishing process then, once the liquid crystal layer cools and the deflection eases, the surface may no longer be flat. To avoid this, the temperature of the cell is controlled during the grinding and polishing of the first portion. Typically, the grinding and polishing maintains the temperature to within 5° C. of the nominal operating temperature. In some embodiments, the slurry injector **835** regulates the temperature of the injected slurry in order to control the temperature of the device.

In one embodiment, the grinder/polisher **800** is a planetary, single-face polisher with a slurry that includes diamond paste and high purity ethylene glycol. Typically plate **820** is made of copper. A minimal amount of slurry is typically used so that there is minimal contamination of the side and back faces of the liquid crystal cells by the slurry.

Typically, planar glass substrates of about 1 mm thick are used. The grinding and polishing described in step **740** can form the structures in the substrates before or after the individual cells are filled and sealed. In yet other embodiments, the grinding and polishing can be applied to substrates before lamination. In all of these embodiments, the methods forming either one or both of stress relief portions and wedged portions in the substrates can be used to efficiently produce these structures in large numbers.

An example of the mass production of the cells is shown in FIG. **8c**. A strip array of liquid crystal cells **850** is shown after completion of the grinding in step **640** of method **600**.

15

The strip array **850** includes two substrates **860** and **870**. The substrates are laminated with adhesive beads **880a**, **880b** and **880c**. The substrates and the beads enclose the liquid crystal layers **890a**, **890b**, and **890c**. In the embodiment shown in FIG. **8c**, the device has a stress relief portion **854** formed in substrate **860**. Other embodiments have one or both of stress relief and wedging in one or both substrates.

In yet other embodiments, the wedge and or the stress relief portion of the substrate can be formed using methods other than grinding or polishing. Other well-known methods for forming the structures in substrates are machining, etching, cutting, sawing, casting, extruding, and molding.

Once the desired wedge or stress relief portion is formed in one or both of the substrates, the devices are cleaned to remove the slurry residue (Step **750**). If the panels were singulated into individual cells in step **720**, then the cells are complete. If instead the panels were cut into strips, then the cells are singulated into individual cells (Step **760**). In embodiments that skipped either one or both of the steps of singulating and filling the individual cells, the panels are singulated into strips or cells (if not done so already) and the cells are filled and sealed. Typically a scribe, dicing saw, or a laser singulates the panelized assemblies.

In some embodiments, fixed optical devices such as retarders, polarizers, or waveplates, are joined to a substrate of a panelized array before it is singulated into strips or cells. As the panels are processed and singulated, the cells that are produced from such a panel have a fixed optical element already joined to them. This is accomplished in essentially one step as opposed to separately joining each final cell with its own fixed optical element.

In the discussion of composite device **500** a composite device typically is formed from individual devices that are subsequently bonded together to form the composite device. Referring to FIGS. **9a** and **9b**, alternate embodiments of composite liquid crystal devices are shown. FIG. **9a** shows composite device **900**. The device includes substrates **910a**, **910b**, **910c**, and **910d** that sandwich adhesive beads **930a**, **930b**, and **930c**. Regions **915a**, **915b**, **915c**, **915d**, **915e**, and **915f** form stress relief regions for liquid crystal layers **940a**, **940b**, and **940c**. Methods similar to those described above are employed to form such devices. Grinding, polishing, machining, etching, cutting, sawing, casting, extruding, or molding can form the regions **915a**, **915b**, **915c**, **915d**, **915e**, or **915f**. Similarly, FIG. **9b** shows a composite device **950**. The device includes substrates **950a**, **950b**, **950c**, and **950d** that sandwich adhesive beads **960a**, **960b**, and **960c** and liquid crystal layers **970a**, **970b**, and **970c**. Regions **955a**, **955b**, **955c**, **955d**, **955e**, **955f**, and **955h** provide stress relief for the liquid crystal layers. The composite devices **900** and **950** can also have other optical elements such as polarizers or retarders interleaved in the composite device.

Although devices **900** and **950** provide for a reduction in the number of interfaces compared to a similar device **500**, devices **900** and **950** are typically more difficult to manufacture by putting increasingly strict demands on positioning and manipulation of the devices as each part of the composite sandwich is formed. In the previous embodiments, the grinding and or polishing is along an axis that is normal with the faces of the substrates. In some embodiments of devices **900** and **950**, grinding, polishing, or sawing along an axis that is parallel to substrates can also form the stress relief structures shown. Although not shown, the faces of the substrates in devices **900** and **950** are amenable to optical wedging. In such embodiments, the substrates are wedged prior to lamination into the composite device.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various

16

modifications may be made without departing from the spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A liquid crystal device comprising:

two unitary substrates sandwiching a layer of liquid crystals,

wherein each substrate supports at least one electrode.

wherein a first one of the substrates has a first region that is thinner than a second region of the first substrate,

wherein the first region of the first substrate has a thickness less than 1.2 mm, and

wherein the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of the liquid crystals over a range of operating temperatures that spans at least 30° C.

2. The device of claim 1, wherein the range of operating temperatures is from about 5° C. to at least 70° C.

3. The device of claim 1, further comprising an optical component secured in optical series with at least a portion of the liquid crystal layer.

4. The device of claim 3, wherein the optical component is a retarder.

5. The device of claim 3, wherein the optical component is a polarizer.

6. The device of claim 3, wherein the optical component is another liquid crystal cell.

7. The device of claim 3, wherein the optical component is an optical window.

8. The device of claim 1, further comprising a stiffening component secured to at least a portion of one of the substrates.

9. A liquid crystal device comprising:

two unitary substrates sandwiching a layer of liquid crystals,

wherein each substrate supports at least one electrode,

wherein a first one of the substrates has a first region that is thinner than a second region of the first substrate,

wherein the first region of the first substrate has a thickness less than 1.2 mm,

wherein the first region of the first substrate is sufficiently thin relative to the second region of the first substrate to relieve stress caused by thermal expansion and contraction of the liquid crystals over a range of operating temperatures, and

wherein the second region of the first substrate is at least 20% thicker than the first region of the first substrate.

10. The device of claim 9, wherein the second region of the first substrate is twice as thick as the first region of the first substrate.

11. The device of claim 9, further comprising an optical component secured in optical series with at least a portion of the liquid crystal layer.

12. The device of claim 11, wherein the optical component is a retarder.

13. The device of claim 11, wherein the optical component is a polarizer.

14. The device of claim 11, wherein the optical component is another liquid crystal cell.

15. The device of claim 11, wherein the optical component is an optical window.

16. The device of claim 9, further comprising a stiffening component secured to at least a portion of one of the substrates.

17

17. A liquid crystal device comprising:
 two unitary substrates sandwiching a layer of liquid
 crystals,
 wherein each substrate supports at least one electrode,
 wherein a first one of the substrates has a first region that
 is thinner than a second region of the first substrate,
 wherein the first region of the first substrate has a thick-
 ness less than 1.2 mm, and
 wherein the second substrate comprises a first region that
 is thinner than a second region of the second substrate.

18. The device of claim 17, further comprising an optical
 component secured in optical series with at least a portion of
 the liquid crystal layer.

19. The device of claim 18, wherein the optical compo-
 nent is a retarder.

20. The device of claim 18, wherein the optical compo-
 nent is a polarizer.

21. The device of claim 18, wherein the optical compo-
 nent is another liquid crystal cell.

22. The device of claim 18, wherein the optical compo-
 nent is an optical window.

23. The device of claim 17, further comprising a stiffening
 component secured to at least a portion of one of the
 substrates.

24. A liquid crystal device comprising:
 two unitary substrates sandwiching a layer of liquid
 crystals,
 wherein each substrate supports at least one electrode,
 wherein a first one of the substrates has a first region that
 is thinner than a second region of the first substrate, and
 wherein the first region of the first substrate has a thick-
 ness less than 1.0 mm.

25. The device of claim 24, further comprising an optical
 component secured in optical series with at least a portion of
 the liquid crystal layer.

26. The device of claim 25, wherein the optical compo-
 nent is a retarder.

27. The device of claim 25, wherein the optical compo-
 nent is a polarizer.

18

28. The device of claim 25, wherein the optical compo-
 nent is another liquid crystal cell.

29. The device of claim 25, wherein the optical compo-
 nent is an optical window.

30. The device of claim 24, further comprising a stiffening
 component secured to at least a portion of one of the
 substrates.

31. A liquid crystal device comprising:
 two unitary substrates sandwiching a layer of liquid
 crystals, wherein each substrate supports at least one
 electrode, wherein a first one of the substrates has a
 wedge and a thickness less than 1.2 mm.

32. The device of claim 31, wherein wedge comprises a
 thinner first region and a thicker second region.

33. The device of claim 32, wherein the first region of the
 first substrate is sufficiently thin relative to the second region
 of the first substrate to relieve stress caused by thermal
 expansion and contraction of the liquid crystals over a range
 of operating temperatures.

34. The device of claim 33, wherein the wedge extends
 over at least a portion of the second region.

35. The device of claim 31, wherein wedge defines a
 wedge angle of at least 0.25 °.

36. The device of claim 31, wherein the wedge reduces
 interference effects caused by an undesired reflection from
 the first substrate during use of the liquid crystal device.

37. The device of claim 31, further comprising an optical
 component secured in optical series with at least a portion of
 the liquid crystal layer.

38. The device of claim 37, wherein the optical compo-
 nent is a retarder.

39. The device of claim 37, wherein the optical compo-
 nent is a polarizer.

40. The device of claim 37, wherein the optical compo-
 nent is another liquid crystal cell.

41. The device of claim 37, wherein the optical compo-
 nent is an optical window.

42. The device of claim 31, further comprising a stiffening
 component secured to at least a portion of one of the
 substrates.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,927,834 B2
DATED : August 9, 2005
INVENTOR(S) : Randall J. Deary and Peter J. Miller

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 16,

Line 8, after "electrode" delete "." and insert -- , --.

Signed and Sealed this

Fourteenth Day of March, 2006

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive, stylized script. The "J" is large and loops around the "on". The "W" is written with two distinct peaks. The "D" is large and loops around the "udas".

JON W. DUDAS

Director of the United States Patent and Trademark Office