



US006930232B2

(12) **United States Patent**  
**Shigenaga**

(10) **Patent No.:** **US 6,930,232 B2**  
(45) **Date of Patent:** **Aug. 16, 2005**

(54) **HIGH-HAT STAND**

(75) Inventor: **Fumihiko Shigenaga, Hamamatsu (JP)**

(73) Assignee: **Yamaha Corporation, Shizuoka (JP)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

(21) Appl. No.: **09/882,545**

(22) Filed: **Jun. 15, 2001**

(65) **Prior Publication Data**

US 2001/0052282 A1 Dec. 20, 2001

(30) **Foreign Application Priority Data**

Jun. 16, 2000 (JP) ..... 2000-181646

(51) **Int. Cl.<sup>7</sup>** ..... **G10D 13/02**

(52) **U.S. Cl.** ..... **84/422.3**

(58) **Field of Search** ..... 84/422.1, 422.2, 84/422.3; 248/121, 122.1, 124.2, 125.8, 126

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,381,690 A \* 5/1983 Kimble ..... 84/422.3  
4,488,471 A \* 12/1984 Youakim ..... 248/158  
5,018,426 A \* 5/1991 Suzuki ..... 84/422.3

5,388,495 A \* 2/1995 Atsumi ..... 84/422.3  
5,482,235 A \* 1/1996 Atsumi ..... 248/121  
6,075,192 A \* 6/2000 Hoshino ..... 84/422.3  
6,229,080 B1 \* 5/2001 Ishimatsu ..... 84/422.1  
6,239,343 B1 \* 5/2001 Hoshino ..... 84/422.3

**FOREIGN PATENT DOCUMENTS**

JP 37-11712 5/1962  
JP 37-12757 9/1962  
JP H3-62214 6/1991  
JP H11-15466 1/1999  
JP H11-242480 9/1999

\* cited by examiner

*Primary Examiner*—Kimberly Lockett

(74) *Attorney, Agent, or Firm*—Koda & Androlia

(57) **ABSTRACT**

An operating rod of a high-hat stand comprising an upper rod member and a lower rod member that are threadably connected to each other by a connecting assembly so that the operating rod is movable upward and downward by a foot pedal and causes a movable cymbal to move up and down with respect to a stationary cymbal. The connecting assembly includes an elastic section that is compressed upon connection of the upper and lower rod members and elastically recovers to its original shape when the upper and lower rod members are separated. The elastic section is formed inside the connecting assembly and can be provided on an exterior thereof.

**2 Claims, 7 Drawing Sheets**





FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10






FIG. 11






**FIG. 12**  
**PRIOR ART**



**FIG. 13**  
**PRIOR ART**





## 1

## HIGH-HAT STAND

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to a high-hat stand used in, for instance, drum sets and more particularly to a structure of a connecting section that connects an upper rod member and a lower rod member.

## 2. Prior Art

In a high-hat stand, an operating rod is set inside a hollow pipe member so as to be movable upward and downward by a foot pedal, and the operating rod moves a movable cymbal attached at the top thereof up and down relative to a stationary cymbal. The operating rod is comprised of an upper rod member and a lower rod member, and these rod members are threadably connected so that they can be separated.

One example this type of connecting structure for the upper and lower rod members is shown in FIG. 12.

In this connecting structure for a high-hat stand, the upper rod member **100** and the lower rod member **101** are connected by a connecting nut **102**; and an upper lock nut **103** and lower lock nut **104** are further employed. However, when the lock fastening of the connecting nut **102** by the upper lock nut **103** is weak, the upper rod member **100** and the connecting nut **102** become loose during play (musical performance), and noise generates upon the up and down movement of the threadably connected upper and lower rod members **100** and **101**. In other words, noise is generated when a foot pedal (not shown) is operated.

Japanese Patent Application Laid-Open (Kokai) No. H11-242480 solves this problem. As seen from FIG. 13, in this prior art, the lower end surface **110** of an upper nut **111** is formed in a protruding conical shape, and the upper end surface **112** of a connecting nut **113** is formed in a recessed conical shape; and these nuts **111** and **113** are engaged at their conical end surfaces with the lower end surface **110** of the upper nut **111** snugly disposed in the upper end surface **112** of the connecting nut **113**. As a result, a more secure thread-engagement of the upper and lower rods **114** and **115** compared to the prior art of FIG. 12 is obtained.

However, as described above, when the lock fastening of the connecting nut **102** by the upper lock nut **103** is weak, noise is generated. Though Japanese Patent Application Laid-Open (Kokai) No. H11-242480 attempts to solve this problem, the structure of this prior art requires conical shape processing on the upper nut **111** and connecting nut **113** that requires a fairly high precision work.

## SUMMARY OF THE INVENTION

Accordingly, one object of the present invention is to provide a structure that prevents looseness in the connecting section for upper and lower rod members in high-hat stands.

It is another object of the present invention to provide a connecting section that connects upper and lower rod members with a different structure from prior art so as to eliminate the need for bothersome conical shape processing on the connecting elements.

The above objects are accomplished by a unique structure for an upper and lower rod member connecting structure of the present invention for a high-hat stand in which an operating rod, which is movable upward and downward by a foot pedal so as to cause a movable cymbal to move up and down relative to a stationary cymbal, is comprised of an

## 2

upper rod member and a lower rod member that are threadably connected by a connecting section; and in the present invention, an elastic section which is compressed upon connection of the rod members and undergoes elastic recovery upon separation of the rod members is disposed in the connecting section.

With this elastic section provided in the connecting section, the resilient force of the elastic section firmly holds the threaded connection of the rod members, and such an elastic section prevents loosening of the rod members that would be caused by vibration during play.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an overall perspective view of the high-hat stand according to the present invention;

FIG. 2 shows a connecting structure between the operating rod and a pedal in the high-hat stand of the present invention;

FIG. 3 is a perspective view of the connecting section of the high-hat stand according to the present invention;

FIG. 4 shows a longitudinal cross-section of the connecting section of the high-hat stand according to the present invention;

FIG. 5 is a side view of the upper nut member that comprises the connecting section of the high-hat stand of the present invention;

FIG. 6 is a longitudinal sectional view of the upper nut member of FIG. 5;

FIG. 7 is a side view of the upper nut member thereof connected to a connecting nut;

FIG. 8 is a side view of the upper nut member of the connecting section of another embodiment of the high-hat stand according to the present invention;

FIG. 9 is a side view of the upper nut member connected to a connecting nut;

FIG. 10 is a partially sectional side view of the upper nut member of the connecting section of the high-hat stand according to the present invention;

FIG. 11 is a side view of the upper nut member of FIG. 10 connected to a connecting nut;

FIG. 12 shows a cross section of prior art connecting structure for upper and lower rod members; and

FIG. 13 shows a cross section of another prior art connecting structure for upper and lower rod members.

## DETAILED DESCRIPTION OF THE INVENTION

As seen from FIG. 1, the high-hat stand **20** of the present invention substantially comprises a hollow stand main body **22**, an operating rod **1**, a spring device **23**, and a pedal assembly **24**.

The hollow stand main body **22** is installed vertically on a floor surface by means of a foldable tripod **21**. The operating rod **1** passes through the hollow stand main body **22** so that the operating rod **1** is movable upward and downward. The spring device **23** drives the operating rod **1** upward. The pedal assembly **24** is disposed on the lower portion of the stand main body **22**. A lower stationary cymbal **8A** is attached to the upper portion of the stand main body **22** by an attachment piece **37**, and an upper movable cymbal **8B** is attached to the upper portion of the operating rod **1** by an attachment screw **39**.

The detail of the spring device **23** is shown in FIG. 2. The structure of the spring device **23** is similar to that disclosed in Japanese Patent Application Laid-Open (Kokai) No. H11-15466.



The spring device **23** comprises a pipe housing **26** which is fastened to the outer circumference of the stand main body **22**, a return spring **7** which is installed inside the pipe housing **26** with its upper end connected to the pipe housing **26**, and a spring rod **28** which is inserted into the interior of the pipe housing **26** from below with its upper end connected to the lower end of the return spring **7**. The spring rod **28** is set vertically on a connecting member **25** that is attached to the lower end of the operating rod **1**.

The pedal assembly **24** is comprised of, along with other components, a pedal frame **6** which is set on the floor surface, a pedal **5** which is connected to the heel **31** of the pedal frame **6** so that the pedal **5** pivots up and down at the rear end, and a transmission member **32** which connects the front end of the pedal **5** to the lower end of the operating rod **1**.

One example of the connecting structure of the operating rod **1** and pedal **5** is shown also in FIG. **2**. This structure is similar to that disclosed in Japanese Patent Application Laid-Open (Kokai) No. H11-15466.

More specifically, a roller link **34** is attached to the connecting member **25** via a bearing **33**. The roller link **34** is formed long in the forward-rearward direction of the pedal **5**. The center of the roller link **34** is shaft-supported by a rotating shaft **35** installed on the bearing **33** so that the roller link **34** swings up and down. Rotating bodies **36A** and **36B** which are rotatably shaft-supported by pins **37** are respectively disposed on the front and rear end portions of the roller link **34**. The rotating bodies **36A** and **36B** are identical, and they are installed so as to be separated from the pivoting center **O** of the roller link **34** by a fixed distance. One end of the transmission member **32** is fastened to the front end portion of the pedal **5**, while another end thereof is connected via an length adjustment mechanism **38** to a connecting portion **6A** installed integrally to the pedal frame **6**. The mid-point portion of the transmission member **32** is installed across the rotating bodies **36A** and **36B**.

In the initial state, the pedal **5** is held so that front end of the pedal **5** floats upward as shown in FIGS. **1** and **2**. When the pedal **5** is depressed by foot during play, the connecting member **25** is pulled down overcoming the spring force of the return spring **7**. As a result, the operating rod **1** connected to the connecting member **25** is lowered as an integral unit with the connecting member **25**, and the upper movable cymbal **8B** strikes the lower stationary cymbal **8A**.

The stand main body **22** is comprised of an upper pipe member **22A** and a lower pipe member **22B** as seen from FIG. **1**. The upper and lower pipe members **22A** and **22B** are fastened together by a tightening screw **41** provided on an attachment ring **40**. The operating rod **1** is comprised of an upper rod member **1A** and a lower rod member **1B**, and these rod members **1A** and **1B** are connected to each other by a connecting section **42** in a manner that the rod members **1A** and **1B** can be separated.

In the connecting section **42**, an elastic section **43** is provided so that the elastic section **43** is compressed when the rod members **1A** and **1B** are connected by the connecting section **42** and then undergoes elastic recovery when the rod members **1A** and **1B** are separated.

More specifically, as seen from FIGS. **3** and **4**, the upper rod member **1A** and the lower rod member **1B** are disengageably connected by the connecting section **42** via a thread-engagement. The connecting section **42** is comprised of a connecting nut **44** and an upper nut member **47**, and the connecting section **42** connects the upper rod member **1A** and the lower rod member **1B** co-axially or in end-to-end

relation. In other words, an external thread **45** is formed on the lower portion of the upper rod member **1A**, and an external thread **46** is formed on the upper portion of the lower rod member **1B**; and these threads **45** and **46** are connected by an internal thread formed on the inside surface of the connecting nut **44**. The rod members **1A** and **1B** are thus threadably connected by the connecting nut **44**.

The connecting nut **44** can be fastened to the lower rod member **1B** by press-fitting or some other appropriate method and not via threads as described above. The upper rod member **1A** is threadably engaged to the connecting nut **44** by turning the upper nut member **47**.

The upper nut member **47** is preferably made of a synthetic resin, and it is fastened to the upper rod member **1A** by press-fitting or some other appropriate method so that the upper nut member **47** is disposed in the area above the external thread **45**. A roulette-worked portion is formed on the outer surface of the upper nut member **47**. The roulette-worked portion is formed in order to facilitate the turning of the upper nut member **47**. A hexagonal nut portion **47A** is, as shown in FIG. **5**, formed on the upper end of the upper nut member **47** in order to allow turning of the upper nut member **47** by a spanner and the like tools.

Accordingly, the upper rod member **1A** is turned and threadably engaged with the connecting nut **44** as seen from FIG. **4** when the upper nut member **47** is turned, and the upper rod member **1A** and lower rod member **1B** are thus connected co-axially. When the rod members **1A** and **1B** are thus connected by the connecting nut **44**, by way of the load from the upper rod member **1A** to which the movable cymbal **8B** is attached, a firm connection of the upper nut member **47** and the connecting nut **44** is attained.

A lock nut **51** is screwed on the external thread **46** of the lower rod member **1B**. The lock nut **51** contacts the under-surface of the connecting nut **44** and prevents loosening of the connecting nut **44**.

In the present invention, an elastic section **43**, which is compressed upon connection of the rod members **1A** and **1B** and elastically recovers upon separation of the rod members **1A** and **1B**, is disposed in the connecting section **42**. The elastic section **43** is disposed in the area in which the upper nut member **47** and the connecting nut **44** are joined; and the elastic section **43** is provided on one of or both of these components, the upper nut member **47** and the connecting nut **44**. In addition, the elastic section **43** can be obtained by way of forming the upper nut member **47** and/or the connecting nut **44** with an elastic material. In the shown preferred embodiment, the elastic section **43** is provided in the upper nut member **47**.

In the embodiment shown in FIGS. **5** through **7**, the upper nut member **47** is formed with an axial hole **48**, which is fastened by press-fitting to the upper rod member **1A**, and a lateral hollow portion **49**, which extends in the lateral direction or at right angles relative to the axial hole **48** in the lower portion of the upper nut member **47**. The elastic section **43** is thus formed in the area that surrounds the lateral hollow portion **49**. As best seen from FIG. **6**, a part of the axial hole **48** that locates below the lateral hollow portion **49** has a larger diameter than the rest of the axial hole **48** (that locates above the lateral hollow portion **49**), so that a flexible shape portion **50** in the lower part of the upper nut member **47** can change its shape as described below.

With the structure above, when the rod members **1A** and **1B** are connected by the connecting section **42**, as shown in FIG. **7** the flexible shape portion **50** of the upper nut member **47** that is located below the lateral hollow portion **49** is



5

pressed by the connecting nut **44** and squeezed so as to change its shape. As a result, the vertical dimension of the lateral hollow portion **49** is narrowed or compressed to zero. In other words, the elastic section **43** formed in the area around the lateral hollow portion **49** is compressed against the elasticity of the elastic section **43**. Accordingly, the thread engagement between the external thread **45** of the upper rod member **1A** and the internal thread formed on the inside surface of the connecting nut **44** is firmly maintained, and loosening of the upper nut member **47** (and the rod members **1A** and **1B**) by vibration during play can be prevented.

The material of the upper nut member **47** is selected with the function of the elastic section **43** taken into consideration. Thus, it is preferable that the upper nut member **47** be formed into a specified shape from, for instance: a synthetic resin such as a polypropylene, polyurethane type elastomer and polyester type elastomer; a rubber material such as natural rubber and a synthetic rubber (e.g., butyl rubber, butadiene rubber, NBR (nitrile butadiene rubber) or CR (chloroprene rubber)); and foamed materials thereof. The hardness values of these materials range from 90 to 100 (in Shore A hardness).

When the rod members **1A** and **1B** are separated by turning the upper nut member **47**, the vertical dimension of the lateral hollow portion **49** increases to its original value, the lateral hollow portion **49** and the flexible shape portion **50** return to their original shapes by the elastic recovery force of the elastic section **43**, and the elastic section **43** thus recovers.

FIGS. **8** and **9** illustrate another embodiment of the present invention. In this embodiment, the elastic section **43** is a cylindrical block that is made from a material such as natural rubber, a synthetic resin, etc. that possesses elasticity. The cylindrical block is disposed on the undersurface of the upper nut member **47** as an integral part thereof by bonding, etc.

When the rod members **1A** and **1B** are connected, the elastic section or the cylindrical block **43** is compressed as shown in FIG. **9**. Thus, the thread engagement between the external thread **45** of the upper rod member **1A** and the internal thread of the inside surface of the connecting nut **44** is firmly maintained.

In this embodiment also, the material of the elastic section or the cylindrical block **43** is selected with the function of the elastic section **43** taken into consideration. Thus, it is preferable that the elastic section **43** be formed into a specified shape from, for instance: a synthetic resin such as a polypropylene, polyurethane type elastomer and polyester type elastomer; and a rubber material such as natural rubber and a synthetic rubber (e.g., butyl rubber, butadiene rubber, NBR or CR). The hardness values of these materials range from 90 to 100 (in Shore A hardness). The upper nut member **47** can be molded from a similar material.

FIGS. **10** and **11** illustrate still another embodiment of the present invention. In this embodiment, the elastic section **43** is a cylindrical block disposed in the connecting section **42**, and it is comprised of a material such as a synthetic resin and natural rubber that possesses elasticity. The elastic section or the cylindrical block **43** is attached to the undersurface of the upper nut member **47** by means of, for instance, bonding, and a reinforcing plate **52** is attached to the undersurface of the cylindrical block **43** by means of, for example, bonding.

Thus, when the rod members **1A** and **1B** are connected, the elastic section or the cylindrical block **43** is compressed via the reinforcing plate **52** as shown in FIG. **11**. As a result,

6

the thread engagement between the external thread **45** of the upper rod member **1A** and the internal thread formed on the inside surface of the connecting nut **44** is firmly maintained.

In this embodiment also, the material of the elastic section **43** is selected with the function of the elastic section **43** taken into consideration. Thus, it is preferable that the elastic section **43** or the cylindrical block be formed into a specified shape from, for instance: a synthetic resin such as a polypropylene, polyurethane type elastomer and polyester type elastomer; and a rubber material such as natural rubber and a synthetic rubber (e.g., butyl rubber, butadiene rubber, NBR or CR). The hardness values of these materials range from 80 to 90 (in Shore A hardness). The upper nut member **47** can be molded from a similar material to the cylindrical block **43**; and in this case, the hardness value of the material is set at a slightly harder Shore A hardness of 90 to 100.

In the embodiments shown in FIGS. **8** through **11**, the cylindrical block **43** can be divided into a plurality of arc pieces, so that these arc pieces are arranged in a circular fashion with equal intervals in between along the circumferential edge of the upper nut member **47**.

In the above embodiments, when the upper nut member **47** is molded from a synthetic resin, the elastic section **43** can be integrally molded from a synthetic resin on the lower portion of the upper nut member **47** by a double molding method. In this case, the process of bonding a separate part (the cylindrical block **43**) is eliminated, and manufacture of the upper nut member **47** is facilitated.

In addition, in the above embodiments, the elastic section **43** is provided on the upper nut member **47** internally and externally. However, it goes without saying that the elastic section **43** can be formed inside the connecting nut **44** or be provided on its end surface that faces the upper nut member **47**.

As seen from the above, in the high-hat stand of the present invention, the upper rod member and lower rod member are threadably connected in a disengageable fashion by a connecting section; and an elastic section, which is compressed upon connection of the rod members and elastically recovers when the rod members are separated, is disposed in the connecting section. Accordingly, the resilient force in the elastic section reinforces the connecting force of the threads of the connecting section, and loosening of the upper and lower rod members can be prevented. As a result, looseness of the movable cymbal during play (musical performance) is prevented, and a desired cymbal play can be assured. Furthermore, this effect can easily be achieved by disposing the elastic section on the upper nut member so that the elastic section is compressed when the connecting nut is connected. Moreover, there is no danger that the elastic section will come loose from the upper nut member and be lost.

The present invention is not limited to the embodiments described above. Various alterations are possible without departing from the technical scope of the present invention, and the present invention includes various embodiments involved in such alterations.

With the present invention, the upper and lower rod members that are threadably connected each other is prevented from loosening without any need to work the shapes of the upper nut member and connecting nut into conical shapes as in the conventional structure.

Furthermore, since the elastic section is disposed on the upper nut member and compressed when the upper nut member is connected to the connecting nut, loosening in these components can be prevented with a simple structure. In

7

addition, the number of parts is reduced and assembling becomes easier since the elastic section is molded as an integral part of the upper nut member.

What is claimed is:

1. A high-hat stand comprising:

an upper rod member with a movable cymbal at one end thereof and an external thread formed at another end thereof;

a lower rod member with a foot pedal connected at one end thereof and an external thread formed at another end thereof;

a connecting nut that threadably connects said another end of said upper rod member to said another end of said lower rod member;

an upper nut member that is disposed near said another end of said upper rod, said upper nut member coming into contact with said connecting nut when said upper rod member and said lower rod member are connected by said connecting nut, said upper nut member being provided with an elastic section that is compressed

8

upon connection of said upper and lower rod members and undergoes elastic recovery upon separation of said upper and lower members; and wherein

said elastic section is comprised of a cylindrical block that is provided on an end surface of said upper nut member so that said cylinder block is disposed between said upper nut member and said connecting nut when said upper and lower rod members are connected; and

a reinforcing plate is attached to said cylindrical block so that said cylindrical block is disposed between said upper nut member and said connecting nut when said upper and lower rod members are connected.

2. The high-hat stand according to claim 1, wherein said cylindrical block is formed from a material selected from the group consisting of polypropylene, polyurethane type elastomer, polyester type elastomer, natural rubber and a synthetic rubber.

\* \* \* \* \*