



US006934278B1

(12) **United States Patent**
Champa et al.

(10) **Patent No.: US 6,934,278 B1**
(45) **Date of Patent: Aug. 23, 2005**

(54) **MULTIMEDIA INTERFACE FOR A COMMUNICATIONS NETWORK**

(75) Inventors: **John J. Champa**, Dearborn, MI (US);
Daniel A. Shyti, Sterling, VA (US)

(73) Assignee: **Unisys Corporation**, Blue Bell, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/221,447**

(22) Filed: **Dec. 28, 1998**

(51) **Int. Cl.**⁷ **H04L 12/66**

(52) **U.S. Cl.** **370/352; 379/88.13; 379/93.21; 709/204; 348/14.08**

(58) **Field of Search** 370/493, 495, 370/497, 465, 466, 467, 487, 353, 354, 355, 356, 391, 395.3, 469, 395.5, 401, 395.52, 395.53, 463, 481, 494, 264, 352; 379/93.05, 88.13, 93.08, 88.23, 93.09, 93.21; 345/853; 455/557, 556; 709/225, 223, 238, 217, 231, 234, 236, 204; 348/14.08, 14.05, 14.12, 14.13, 14.15

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,206,859 A	*	4/1993	Anzai	348/14.11
5,389,965 A	*	2/1995	Kuzma	348/14.05
5,497,373 A	*	3/1996	Hulen et al.	370/259
5,519,640 A	*	5/1996	Ganesan et al.	709/231
5,610,910 A	*	3/1997	Focsaneanu et al.	370/351
5,677,728 A	*	10/1997	Schoolman	379/93.17
5,689,553 A	*	11/1997	Ahuja et al.	348/14.09
5,706,290 A	*	1/1998	Shaw et al.	345/723

5,708,659 A	*	1/1998	Rostoker et al.	370/392
5,761,294 A	*	6/1998	Shaffer et al.	370/271
5,768,350 A	*	6/1998	Venkatakrishnan	370/418
5,805,636 A	*	9/1998	Rao et al.	375/222
5,892,764 A	*	4/1999	Riemann et al.	370/395.52
5,966,427 A	*	10/1999	Shaffer et al.	379/21

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 97/47119 * 12/1997 H04M/3/42

OTHER PUBLICATIONS

Gary A. Thom, H.323: The Multimedia Communications Standard for Local Area Networks, Dec. 1996, IEEE Communication Magazine, pp. 52-56.*
Computer Telephony, Oct. 1997, pp. 81-85 and 87-90.

Primary Examiner—Duc Ho


Assistant Examiner—Phuongchau Ba Nguyen

(74) *Attorney, Agent, or Firm*—Lise A. Rode; Mark T. Starr; David G. Rasmussen

(57) **ABSTRACT**

A multimedia interface circuit is used to connect multimedia signal sources such as a telephone to a network. The multimedia interface circuit has a telephone communication interface circuit for receiving the telephone signal from the telephone. A signal conditioner receives the signal from the telephone communication interface circuit and conditions it for use on the network. A phone environment simulator cooperates with the signal conditioner to add an artificially simulated phone environment to the signal. The signal is then sent by a network communication circuit to the network. Personal computers and video sources may also be connected by the multimedia interface circuit to the network.

17 Claims, 4 Drawing Sheets



US 6,934,278 B1

Page 2

U.S. PATENT DOCUMENTS

5,974,043	A	*	10/1999	Solomon	370/352	6,215,515	B1	*	4/2001	Voois et al.	379/93.21
5,999,985	A	*	12/1999	Sebestyen	370/465	6,246,490	B1	*	6/2001	Sebestyen	370/469
6,011,579	A	*	1/2000	Newlin	379/93.21	6,259,449	B1	*	7/2001	Saxena et al.	345/853
6,044,403	A	*	3/2000	Gerszberg et al.	709/217	6,266,782	B1	*	7/2001	Carter et al.	370/467
6,046,762	A	*	4/2000	Sonesh et al.	379/93.21	6,295,293	B1	*	9/2001	Tomby et al.	370/389
6,064,653	A	*	5/2000	Farris	370/237	6,324,265	B1	*	11/2001	Christie et al.	379/88.23
6,075,784	A	*	6/2000	Frankel et al.	370/352	6,324,280	B2	*	11/2001	Dunn et al.	379/230
6,122,255	A	*	9/2000	Bartholomew et al.	370/237	6,335,927	B1	*	1/2002	Elliott et al.	370/352
6,122,665	A	*	9/2000	Bar et al.	709/224	6,377,818	B2	*	4/2002	Irube et al.	455/556
6,130,880	A	*	10/2000	Naudus et al.	370/235	6,430,176	B1	*	8/2002	Christie, IV	370/355
6,141,341	A	*	10/2000	Jones et al.	370/352	6,449,260	B1	*	9/2002	Sassin et al.	370/352
6,163,531	A	*	12/2000	Kumar	370/260	6,452,922	B1	*	9/2002	Ho	370/352
6,185,288	B1	*	2/2001	Wong	370/352	6,549,534	B1	*	4/2003	Shaffer et al.	370/355

* cited by examiner




Figure 1 (Prior Art)




Figure 2 (Prior Art)




Figure 3 (Prior Art)




FIGURE 4




Figure 5

MULTIMEDIA INTERFACE FOR A COMMUNICATIONS NETWORK

BACKGROUND OF INVENTION

1. Field of the Invention

The present invention relates to a common multimedia interface (MMIF) circuit that allows any signal source, whether it be an analog phone, digital phone, PC, or video device, to be connected through the MMIF circuit to a network such as an intranet.

2. Description of the Related Art

A communication system in an office or site environment may have a variety of signal sources such as analog and digital telephones, PC's, and video sources that all need to be connected to a network, for example an intranet. An intranet is a private network built around internet technology and standards. An example would be a government agency that may have a variety of offices in a number of locations that are all connected by an intranet.

FIG. 1 shows a typical prior art office environment having an analog telephone system in parallel with a digital local area network (LAN) using, for example, Ethernet protocol to which personal computers (PCs) are connected. The disadvantage of this system is that the analog phone system and digital LAN network have separate transmission lines.

FIG. 2 shows a more advanced prior art communication system in which one set of transmission lines is eliminated. Telephones are connected through multimedia PCs to the LAN thus eliminating one set of transmission lines. The disadvantage of having the analog telephones go through the PCs is that this requires adding a telephone interface card to the PC. Secondly, if the PC fails, the phone is unusable. In addition, when the phone is in operation the PC operation is degraded.

FIG. 3 is a schematic drawing of the latest state of the art system that provides long distance telephone calls over the internet. The system connects the telephone to a "box" which performs a long distance call over the internet to another "box" which has a phone connected to it. The disadvantage of this system is the reliability of connections over the internet for a telephone call.

What would be desirable is a communication system in an office environment in which each signal source connects through its own standard interface box to the network such that each signal source may communicate to any other signal source without having to modify any of the signal sources.

SUMMARY OF THE INVENTION

The present invention provides a common multimedia interface (MMIF) circuit in a box that allows any signal source, whether it be an analog phone, digital phone, PC, or video device, to be connected through the MMIF circuit to a LAN network such as an intranet. After connection they can be connected through the intranet to any other signal source connected to a similar MMIF circuit. Each MMIF circuit has an input port for each of the signal sources. None of the signal sources needs to be modified to connect to an MMIF circuit.

The MMIF circuit has telephone, computer, and video ports for receiving and transmitting telephone, computer, and video signals. The MMIF circuit operates with only one signal source at a time. If a telephone is connected, a telephone communication interface circuit receives the telephone signals from the telephone port. Then a signal con-

ditioner receives the telephone signal from the telephone communication interface circuit. The signal conditioner has a transcoder to receive the telephone signal if it is digital and a voice codec to receive the telephone signal if it is analog.

The transcoder conditions and compresses the digital telephone signal and sends it to a voice packetizer. The voice codec converts the analog telephone signal to a digital signal, compresses the signal, conditions it and sends it to the voice packetizer. In addition the transcoder and voice codec cooperate with a telephone digital signal processor to receive the digital signal and add an artificially simulated phone environment to the digital telephone signal.

The voice packetizer packetizes the compressed digital telephone signal. A network interface receives the packetized digital telephone signal and formats it to be compatible with the network. If the network is an intranet, the signal then goes to a network port connected to the intranet. The telephone signal is routed to the correct internet protocol address (IP address) for the telephone to be connected to. The telephone signal then goes through an MMIF circuit for the phone to be connected to in the reverse direction. The two phones are now connected via the intranet.

If a computer, for example a PC, is connected to the MMIF circuit the computer port receives signals from the computer and provides them to the network interface. The network interface forwards the computer signals through the network port to the intranet. The computer signal is routed to the correct internet IP address for the second computer to be connected to. The computer signal then goes through an MMIF circuit for the second computer in the reverse direction. The two computers are now connected via the intranet.

If a video source, for example a camera, is connected to the MMIF circuit a video port receives signals from the camera and provides them to the to a video codec which compresses the signal and forwards it to a video packetizer which packetizes the signal and sends it to the network interface. From there the video signal is routed to the correct internet IP address whether it be through the network port to the intranet or through a computer port to a computer with an MMIF circuit.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a prior art office environment having an analog telephone system in parallel with a digital LAN.

FIG. 2 is a block diagram of a more advanced prior art communication LAN using one digital transmission line in which telephones are connected through multimedia PCs to the LAN.

FIG. 3 is a schematic drawing of a state of the art system that provides long distance telephone calls over the internet.

FIG. 4 is a block diagram of an office communications system that incorporates the multimedia interface of the invention to connect multimedia signal sources to a LAN.

FIG. 5 is a schematic diagram of the multimedia interface of FIG. 5.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows a typical prior art office environment having an analog telephone system in parallel with a digital LAN using, for example, Ethernet protocol to which personal computers (PCs) are connected. The analog phone system and digital LAN have separate transmission lines. In FIG. 1 telephones are connected to a private branch exchange

3

(PBX) switching system **12** that may switch phone calls to the public telephone company service (POTS) **14** or to other services such as voice mail system **16**.

Each PC **20** has an internal network interface card (NIC) that connects through to an RJ **45** jack to a cable extending to an LAN hub **22** which acts as a distribution point for the signal to server **24** or to other servers and PCs. Server **24** is connected by a LAN to the LAN hub **22**. Server **24** is typically a high end PC that contains applications that it will provide through a router **26** to a LAN **28** or WAN **30**.

The big disadvantage of the parallel systems of FIG. **1** is that two separate side by side transmission lines are needed.

FIG. **2** shows a more advanced prior art communication system in which one transmission line is eliminated. Telephones are connected through multimedia PCs to the LAN thus eliminating one transmission line. Looking more closely at FIG. **2**, telephones **34** are connected to telephone interface cards in multimedia PCs **36**. The telephone interface cards digitize and packetize the phone signal. Each PC provides a digital signal to an asynchronous transfer mode (ATM) high-speed hub switch **38**. This switch routes the PC digital signal to an outside telephone POTS line through LAN server **40**, to a private branch exchange (PBX) telephone hub **42** and phones **44** (either digital or analog), or to a WAN or other network through an ATM switch **46**.

The disadvantage of having the telephones go through the PCs is that this requires adding a telephone interface card to the PC for the phone to be connected to. Secondly, if the PC fails, the phone is unusable. In addition, when the phone is in operation the PC operation is degraded and vice-versa.

FIG. **3** is a schematic drawing of the latest state of the art system that provides long distance telephone calls over the internet. APLIO INC. of San Bruno Calif. manufactures the system. This system connects the telephone to a "box" which performs the long distance call over the internet to another "box" which has a phone connected to it. In FIG. **3**, an APLIO box **52** is connected in series between a telephone **50** and ordinary telephone service (POTS) station **54**. POTS station **54** can dial and receive internet protocol (IP) addresses through internet service provider ISP **56** and also communicate with POTS location **58**. An APLIO box **60** is connected to POTS location **58**. In addition, POTS location **58** can dial and receive IP addresses through internet service provider ISP **62**. Telephone **64** is connected to APLIO box **60**.

The procedures to make an internet telephone call are as follows:

1. Pick up the receiver for telephone **50**.
2. Dial in the telephone number of telephone **64** which has APLIO black box **60** connected.
3. When the call goes through, the parties agree that one party will make the internet call on the "master" box. (e.g. APLIO box **52**).
4. The party with the master APLIO box **52** presses the call button on box **52**.
5. APLIO box **52** connects to APLIO box **60** through POTS locations **54**, **58**. Master APLIO box **52** provides an indication to both parties to hang up the telephones **50** and **64**.
6. After telephones **50,64** are hung up APLIO boxes **52,60** take over.
7. Master APLIO box **52** logs onto the internet with its ISP user number and password.
8. APLIO boxes **52,60** find a common server on the internet.

4

8. Both APLIO boxes **52,60** check into the common server and provide identifier numbers and their IP addresses to the server.

9. Both APLIO boxes **52,60** dial their own local ISP telephone number for a point to point protocol (PPP) connection.

10. APLIO boxes **52,60** both make local connection to the internet through their own ISP and find the common server.

11. The master APLIO box **52** presents its serial number and identifier number and the serial number of the slave box.

12. The master APLIO box **52** establishes a socket connection through the internet into the slave box **60**. The connection is box to box.

13. Both APLIO boxes **52,60** ring the bell tone on their respectively connected telephones **50,64**.

14. As each party picks up his phone he connects through his APLIO box to the internet to consummate the internet telephone call.

15. When the call is complete each party hangs up.

16. APLIO boxes **52,60** log off the internet.

This system is used to make calls over the internet and not to provide communications within an intranet system.

FIG. **4**. Shows a typical office communications system connected together by a LAN **100** that may be any network, for example, an intranet. For descriptive purposes an intranet will be described. The system has the following communication signal sources; telephone **102**, personal computer (PC) **104** and video source **106**. The hub for intranet LAN **100** is LAN switch **108**. An example of a LAN switch would be an Ethernet or ATM switch. LAN switches are well known in the art and available from Intel Corporation or Cisco Corporation.

Multimedia interface (MMIF) circuits **110a-z** form the heart of the present invention. The MMIF circuits allow any signal source having an IP address to be connected through intranet LAN **100** to any other signal source having an IP address without having to modify any of the signal sources. For example, an analog telephone at one IP address of intranet LAN **100** can be connected with a digital telephone at another IP address without the need to go through a PC as is needed in the prior art. Each MMIF circuit **110a-z** has an input for each of the signal sources. For example, MMIF **110a** has inputs for telephone, personal computer and video signals **102**, **104**, and **106** respectively. Only one of the sources can be connected to MMIF circuit **110a** at a time. Each signal source connected to intranet LAN **100** has its own MMIF circuit **110a-110z**.

LAN switch **108** also allows access from intranet LAN **100** to the outside world through site router **114** and IP telephone gateway **116**. These do not form part of the invention. Site router **114** allows access to other networks including local area network LAN **118**, wide area network WAN **120**, and internet **122**. IP telephone gateway **116** allows telephone service to the telephone company (i.e. POTS) **124**, integrated service digital network (ISDN) **126** and virtual private network (VPN) **128**. IP gateway servers are well known and are available from Lucent Technologies.

FIG. **5** is a block diagram of the MMIF circuit **110a** shown in FIG. **4**. Assume that a telephone is connected to MMIF circuit **110a**. Telephone communication interface circuit **136** receives an analog phone input **140** or a digital phone input **142** from the phone **102** shown in FIG. **4**. The phone has an IP address on intranet LAN **100**. Telephone communication interface circuit **136** is made up of RJ11 telephone port **138**,

telephone interface **144** (i.e. packet handler interface) and POTS switch **146**. The purpose of telephone communication interface circuit **136** is to process the incoming telephone signal and provide the telephone signal to signal conditioner **148** or to POTS port **150**.

RJ11 telephone port **138** is a common telephone six conductor modular jack that is typically wired for four conductors. The analog or digital phone signal from RJ11 port **138** is provided to a telephone interface **144** which recognizes whether the phone signal is analog or digital and whether there are any control signals. The phone signals and any control signals are forwarded to POTS switch **146**. The POTS switch recognizes from the control signal whether to route the signal to signal conditioner **148** or to RJ11 port **150** which is connected to the ordinary outside telephone POTS service. If the phone signal is meant to go straight to the outside telephone POTS lines then the signal goes to RJ11 port **150**. RJ11 port **150** is shown in FIG. 4 as IP telephone gateway **116** and outside telephone POTS line **124**. If the phone signal is meant to be used on the intranet LAN **100**, the signal goes to transcoder **152** or G.7xx voice codec **154** which are part of signal conditioner **148**. The signal goes to transcoder **152** if it is digital and to voice codec **154** if it is analog. Both signals then go to voice packetizer **156** (i.e. IP voice packetizer). The purpose of signal conditioner **148** for a signal coming from the POTS switch **146** is to preprocess, compress, digitize, and packetize to internet protocol (IP) (or other protocol depending on the LAN). The preprocessing is normally for signal enhancement to replace portions of the signal corrupted during signal conditioning. For a signal in the opposite the process is reversed. Transcoder **152** converts the digital phone signal from a propriety digital signal to a standard digital audio signal recognizable by the voice packetizer. In addition, the transcoder may perform signal enhancement and compression on the signal. Voice codec **154** performs signal enhancement and compression on the phone signal. An example of the voice codec is an HMP 8201 manufactured by Harris Semiconductor. The outputs of voice codec **154** and transcoder **152** are compressed digital signals provided to H.323 voice packetizer **156** that packetizes the digital signal. Voice packetizer **156** is a commercially available chip set, H323, manufactured by Hewlett Packard. Transcoders are commercially available from Accord Video Telecommunications LTD located in Petach-Tivka, Israel.

Voice codec **154** and transcoder **152** also communicate with telephone environment simulator **158** that is made up of telephone digital signal processor (DSP) **159** and tone generator **160**. DSP **159** receives a ring tone, dial tone and white noise from tone generator **160**. DSP **159** adds these signals to the digital phone signals in voice codec **154** and transcoder **152**. The purpose is to artificially simulate a phone environment since there is no audio noise in a digital phone system. Alternatively, dial and ring tones could be stored in permanent memory in DSP **159** or other storage location as is known in the art.

Voice packetizer **156** provides digital packets to network communication circuit **161** which includes network interface **162** (e.g. internal Ethernet interface) and network port **164**. Network interface **164** puts the digital packets in the proper format to be applied to network port **164** and to intranet LAN **100** (shown in FIG. 4). Network port **164** is a network interface card (NIC). The telephone signal will be directed to the correct IP address of the telephone to be connected to by LAN switch **108** (shown in FIG. 4). The latter telephone needs to be connected to the intranet LAN by an MMIF circuit also.

If PC **104**, shown in FIG. 4, is connected to MMIF circuit **10a** and wants to connect to a second PC on intranet LAN **100**, the second PC needs to be connected to the LAN through an MMIF circuit. In addition both PCs need to have IP addresses. PC **104** is connected through its network interface card (NIC) to computer port **166** that is a NIC for network interface **162**. In network interface **162** the PC signal is formatted to be applied to network port **164** and to LAN **100**. The computer signal is sent to the IP address of the second computer.

If video source **106**, shown in FIG. 4, is connected to MMIF circuit **110a** and wants to be connected to second video device on intranet LAN **100**, the second video device needs to be connected to the LAN through an MMIF circuit. In addition, both the video source and the second video device must have an IP address. Video source **106** is connected through video port **170** to an H 263 video codec **172**, in signal conditioner **148**, where the video signal is compressed. Hewlett Packard manufactures H 263 video codec **172**. The compressed video signal is then sent to video packetizer **174** (i.e. IP voice packetizer) which packetizes the compressed video signal. The signal is then sent to network interface **162**, which sends the signal through network port **164** to the second video device at the desired IP address.

In operation, a communication system in an office environment may have a variety of signal sources such as analog and digital telephones, PC's, or video sources which all need to be connected to an intranet network in the office, site or general location. An example would be a government agency that may have a variety of offices in a number of locations that are all connected by an intranet LAN. In the prior art described previously an analog phone would have to be connected to its own analog POTS network in the office or would have to be connected through a PC to digitize the phone signal so it could go on the intranet LAN. This required adding a communications card to the PC for the phone to be connected to. In addition, if the PC went down the phone was unusable. Also when the phone was in operation the PC operation was degraded.

The invention allows each of the signal sources to be connected to an MMIF circuit interchangeably. An operator simply plugs his telephone (analog or digital), PC or video device into any available MMIF circuit. The MMIF circuit automatically transfers the signal to the correct IP address on intranet LAN **100**.

Looking more specifically at FIGS. 4 and 5, if a government employee has an analog phone and wants to connect to a second digital phone at another location on intranet LAN **100**, he begins by plugging his analog phone into the telephone port **138** of one of MMIF circuits **110a-z**. This circuit is connected to a node of intranet LAN **100** at a specified IP address. The employee dials the number of the second digital phone. This signal is passed through telephone port **138** and goes to telephone interface **144** that determines whether the telephone signal is digital or analog and looks for control signals. The signal is fed to optional POTS switch **146** which looks for a control signal and switches the signal either through RJ11 port **150** to outside POTS telephone service **124** or to signal conditioner **148**. For example, a code may be dialed before the phone number that indicates if the phone call is to go to the outside POTS service.

In this case the phone signal is to go to an IP address of intranet **100**, and since the signal is analog, it is sent to voice codec **148** for signal conditioning, compression and conversion to a digital signal.

At this point there is no ring tone or dial tone on the digital signal output of voice codec **148**. These must be added so that someone answering the phone call will know there is a phone call on the line. Tone generator **158** provides the ring and dial tones to telephone DSP **159** that adds them to the digital signals of voice codec **148**. The digital signal of voice codec **148** is then forwarded to voice packetizer **156** that packetizes the signal.

The packetized digital phone signal is fed to network interface **162** and to network port **164** which sends the signal to the LAN switch **108** which is the hub for intranet LAN **100**. LAN switch **108** routes the phone signal to the correct IP address for the second digital telephone.

The second digital telephone is connected through an MMIF circuit to intranet LAN **100** also. The MMIF circuit for the digital phone receives the phone signal and processes the signal in the reverse direction to provide the phone signal to the digital phone. In this case the reverse signal would go through transcoder **152** since the receiving phone is digital. The phone signal has ring tone and dial tone and the source of the call is transparent as to whether it was from a digital or analog phone. This means analog or digital phones can be interchangeably connected at any IP address site on the intranet LAN **100**.

If the employee wants to transfer files between PC **104** and a second PC, PC **104** is connected to the computer port of MMIF circuit **110a** and the second PC is connected to the computer port of a second MMIF circuit. Both MMIF circuits are then connected to nodes at different IP addresses on the intranet LAN **100**.

PC **104** is connected through its network interface card (NIC) to computer port **166** that is a NIC for network interface **162**. There the PC signal is formatted to be applied to network port **164** which sends the signal to LAN switch **108** the hub for intranet LAN **100**. LAN switch **108** routes the PC **104** computer signal to the correct IP address for the second PC.

Similar procedures are followed if the employee wants to connect a video signal source **106** to another video device on intranet LAN **106**. Both devices need to be connected to MMIF circuits and have IP addresses on LAN **106**. The MMIF circuits will route the signals through video port **170**, video codec **172**, and video packetizer **174** to the network interface. The signal then goes through the LAN to the correct IP address in the same way as the PC or telephone signal.

The advantage of the MMIF circuit to the employee is its simplicity. The employee may use one box to plug in his telephone, PC or video device to the LAN. There is no need to run the telephone through a PC to get to the intranet LAN as the prior art requires. This means that the PC does not need to be modified to handle telephones and its performance is not degraded when a phone call is made. In addition, the employee may use whatever telephone is available whether analog or digital to make calls. The type of telephone is transparent to the LAN.

While the preferred embodiments of the invention have been shown and described, numerous variations and alternative embodiments will occur to those skilled in the art. Accordingly, it is intended that the invention be limited only in terms of the appended claims.

We claim:

1. A multimedia interface circuit having ports for interchangeably connecting any one of a plurality of multimedia signal sources including a telephone to a network comprising,

a telephone communication interface circuit, including a telephone interface, for receiving a telephone signal

from said telephone, for determining if said telephone signal is analog or digital, and for interfacing said telephone signal to said multimedia interface circuit,

a signal conditioner receiving the output of said telephone communication interface circuit for providing a compressed and packetized digital telephone signal as an output,

a phone environment simulator communicating with said signal conditioner to add an artificially simulated phone environment to said digital telephone signal,

a network communication circuit receiving said signal conditioner output for communicating said signal conditioner output to said network,

a video port for receiving and transmitting video signals, said signal conditioner receiving the output of said video port, said signal conditioner for compressing and packetizing said video signal,

said network communication circuit receiving said video signal output of said signal conditioner, said network communication circuit capable of providing said signal conditioner video output signal to said network,

wherein any one of said plurality of multimedia signal sources connected to said multimedia interface circuit can be connected via said network to any of said plurality of multimedia signal sources connected to another said multimedia interface circuit.

2. A multimedia interface circuit having ports for interchangeably connecting any one of a plurality of multimedia signal sources including a telephone to a network comprising,

a POTS port capable of being connected to a POTS telephone network;

a telephone communication interface circuit, including a telephone interface, for receiving a telephone signal from said telephone, for determining if said telephone signal is analog or digital, and for interfacing said telephone signal to said multimedia interface circuit, said telephone communication interface circuit including a POTS switch for receiving said telephone signal and for determining whether said telephone signal is to be routed to said POTS telephone network or to a signal conditioner,

said signal conditioner receiving the output of said telephone communication interface circuit providing a compressed and packetized digital telephone signal as an output,

a phone environment simulator communicating with said signal conditioner to add an artificially simulated phone environment to said digital telephone signal, and

a network communication circuit receiving said signal conditioner output for communicating said signal conditioner output to said network,

a video port for receiving and transmitting video signals, a video codec receiving the output of said video port, said video codec for compressing said video signal,

a video packetizer receiving the output of said video codec, said video packetizer for packetizing the output of said video codec; and,

said network communication circuit receiving the output of said video packetizer, said network communication circuit capable of providing said video packetizer signals to said network,

wherein any one of said plurality of multimedia signal sources connected to said multimedia interface circuit

9

can be connected via said network to any of said plurality of multimedia signal sources connected to another said multimedia interface circuit.

3. The multimedia interface circuit of claim 1 further comprising,

a POTS port capable of being connected to a POTS telephone network, and

a POTS switch in said telephone communication interface circuit for receiving said telephone signal and for determining whether said telephone signal is to be routed to said POTS telephone network or to the signal conditioner.

4. The multimedia interface circuit of claim 1 or 2 in which said telephone communication interface circuit includes,

a telephone port for receiving said telephone signal, and providing said telephone said signal to said telephone interface.

5. The multimedia interface circuit of claim 4 in which said phone environment simulator includes,

a digital signal processor receiving said digital telephone signal for adding an artificially simulated phone environment to said digital telephone signal.

6. The multimedia interface circuit of claim 5 in which said phone environment simulator includes a tone generator for producing said artificially simulated phone environment.

7. The multimedia interface circuit of claim 5 in which said phone environment simulator produces a ring tone and a dial tone.

8. The multimedia interface circuit of claim 6 in which said signal conditioner includes:

a transcoder capable of receiving a digital telephone signal from said telephone communication interface circuit for transcoding and compressing said digital telephone signal,

a voice codec capable of receiving an analog telephone signal from said telephone communication interface circuit for converting said analog telephone signal to a digital signal and compressing said digital telephone signal, and

a voice packetizer capable of receiving said digital telephone signals from said transcoder and said voice codes for packetizing said digital telephone signals.

9. The multimedia interface circuit of claim 8 in which said network communication circuit includes,

a network interface receiving said packetized digital telephone signal from said voice packetizer, for formatting said packetized digital telephone signal to be compatible with said network, and

a network port connected to said network, said network port receiving said digital telephone signal from said network interface for providing said telephone signal to said network.

10. The multimedia interface circuit of claim 9 in which said network is an intranet.

11. The multimedia interface circuit of claim 1 having a computer port capable of receiving and transmitting computer signals, said computer port connected to said network interface, said network interface capable of providing said computer signals through said network port to said network.

12. The multimedia interface circuit of claim 2 including a computer port capable of receiving and transmitting computer signals, said computer port connected to said network interface, said network interface capable of providing said computer signals through said network port to said network.

10

13. A multimedia interface circuit for interchangeably connecting any one of a plurality of multimedia signal sources including a telephone to a network comprising:

a telephone port for receiving a telephone signal;

a telephone interface receiving said telephone signal from said telephone port for interfacing said telephone signal to said multimedia interface circuit and determining if said telephone signal is analog or digital;

a transcoder capable of receiving a digital telephone signal from said telephone interface for transcoding and compressing said digital telephone signal;

a voice codec capable of receiving an analog telephone signal from said telephone interface for converting said analog telephone signal to a digital signal and compressing said digital telephone signal;

a voice packetizer capable of receiving said digital telephone signals from said transcoder and said voice codec for packetizing said digital telephone signals;

a digital signal processor cooperating with said transcoder and said voice codec for adding an artificially simulated phone environment to said digital telephone signal,

a network interface receiving said packetized digital telephone signal from said voice packetizer, for formatting said packetized digital telephone signal to be compatible with said network;

a network port connected to said network, said network port receiving said digital telephone signal from said network interface;

a video port for receiving and transmitting video signals; a video codec receiving the output of said video port, said video codec for compressing said video signal; and,

a video packetizer receiving the output of said video codec, said video packetizer for packetizing the output of said video codec, said network interface receiving the output of said video packetizer, said network interface capable of providing said video packetizer signals through said network port to said network,

wherein any one of said plurality of multimedia signal sources connected to said multimedia interface circuit can be connected via said network to any of said plurality of multimedia signal sources connected to another said multimedia interface circuit.

14. The multimedia interface circuit of claim 13 in which said network is an intranet.

15. The multimedia interface circuit of claim 13 in which said artificially simulated phone environment includes a ring and a dial tone.

16. The multimedia interface circuit of claim 13, including:

a POTS port capable of being connected to a POTS telephone network; and,

a POTS switch receiving said telephone signal from said telephone interface for determining whether said telephone signal is to be routed to said POTS telephone network or to the transcoder.

17. The multimedia interface circuit of claim 13 including,

a computer port capable of receiving and transmitting computer signals, said computer port connected to said network interface, said network interface capable of providing said computer signals through said network port to said network.