



US006934957B2

(12) **United States Patent**
Kanada et al.

(10) **Patent No.:** **US 6,934,957 B2**
(45) **Date of Patent:** **Aug. 23, 2005**

(54) **RECORDING MEDIUM DRIVING DEVICE**

(75) Inventors: **Tokio Kanada**, Kanagawa (JP);
Mikinori Matsuda, Kanagawa (JP)

(73) Assignee: **Sony Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 184 days.

(21) Appl. No.: **10/258,993**

(22) PCT Filed: **Mar. 13, 2002**

(86) PCT No.: **PCT/JP02/02383**

§ 371 (c)(1),
(2), (4) Date: **Feb. 6, 2003**

(87) PCT Pub. No.: **WO02/073613**

PCT Pub. Date: **Sep. 19, 2002**

(65) **Prior Publication Data**

US 2004/0004865 A1 Jan. 8, 2004

(30) **Foreign Application Priority Data**

Mar. 13, 2001 (JP) 2001-71134

(51) **Int. Cl.**⁷ **G11B 17/03**; **G11B 33/02**

(52) **U.S. Cl.** **720/638**; **369/75.11**

(58) **Field of Search** **720/638, 636,**
720/640; 369/75.11, 77.11

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,360,174 A * 11/1982 Tomita et al. 242/339
5,504,730 A * 4/1996 Kanada 720/640

* cited by examiner


Primary Examiner—Allen Cao

(74) *Attorney, Agent, or Firm*—Jay H. Maioli

(57) **ABSTRACT**

A driving device includes a holder movably carried by a chassis and adapted for transporting a disc cartridge that the holder holds between an insertion/ejection position and a loading position, and an ejection lever for ejecting the disc cartridge from the holder. The driving device also includes a slider movable in a direction of inserting the disc cartridge into the holder and in a direction of ejecting the disc cartridge from the holder. The slider causes the holder to be moved to the loading position when the slider is moved in the disc cartridge inserting direction, while causing the holder to be moved to the insertion/ejection position when the slider is moved in the disc cartridge ejecting direction. The driving device also includes a spring member provided between the ejection lever and the slider for biasing the ejection lever in a direction of ejecting the disc cartridge from the holder and for biasing the slider in the disc cartridge inserting direction.

5 Claims, 59 Drawing Sheets






FIG. 1
(PRIOR ART)




FIG. 2 (PRIOR ART)




FIG. 3 (PRIOR ART)




FIG. 4 (PRIOR ART)




FIG. 5 (PRIOR ART)




FIG.6 (PRIOR ART)




FIG.7 (PRIOR ART)




FIG. 8




FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG.18




FIG.19




FIG.20




FIG.21




FIG.22




FIG. 23




FIG.24




FIG.25




FIG.26




FIG.27




FIG.28




FIG.29




FIG.30




FIG.31




FIG.32




FIG.33




FIG.34




FIG.35




FIG.36




FIG.37




FIG.38




FIG.39




FIG.40




FIG.41




FIG. 42




FIG. 43




FIG.44




FIG. 45




FIG. 46




FIG.47




FIG.48




FIG.49




FIG. 50




FIG.51




FIG.52




FIG.53




FIG. 54




FIG.55




FIG. 56




FIG.57




FIG. 58




FIG. 59




FIG.60




FIG. 61




FIG.62




FIG. 63




FIG. 64

RECORDING MEDIUM DRIVING DEVICE

TECHNICAL FIELD

The present invention relates to a recording medium driving device for recording information signals and for reproducing the signals for a recording medium. More particularly, the present invention relates to a recording medium driving device in which a recording medium held by a holder is ejected by an ejection lever.

BACKGROUND ART

There are recording medium driving devices for reproducing information signals recorded on the disc-shaped recording mediums. In certain ones of the recording medium driving devices, a slider held by a holder is moved in one direction when a recording medium is held on the holder to lower the holder to load the recording medium on the loading unit, while the slider is moved in the opposite direction to elevate the holder to eject the recording medium from the holder by an ejection lever.

As typical of this sort of the recording medium driving device, there is known a device shown in FIGS. 1 to 5. With this driving device, upwardly opened guide grooves 102, 102 are formed in both lateral sides of a chassis 101. In these guide grooves 102, 102, there are slidably supported a pair of rearwardly positioned support pins 104, 104 provided on both lateral surfaces of a holder 123, there being another pair of forwardly positioned similar support pins provided on both lateral surfaces of the holder 123.

On the holder 123, there is mounted a slider 105 for sliding in the fore-and-aft direction. The slider 105 includes lateral surface sections 106, 106 and a connecting portion 107 interconnecting the lateral surface sections 106, 106. In the lateral surface sections 106, 106, there are cam grooves 108, 108 which are spaced apart from each other in the fore-and-aft direction. In the cam grooves 108, 108, the support pins 104, 104 of the holder 123 are supported for sliding movement. A slider biasing spring 109 is mounted under tension between the lateral surfaces 106, 106 of the slider 104 and a rearward portion of the chassis 101 for biasing the slider 105 rearwards.

At the rear end of the chassis 101, there is mounted a lever supporting lug 110, and an ejection lever 111 is rotatably mounted at the foremost part of the supporting lug 110. A lever biasing spring 112 is mounted under tension between the ejection lever 111 and the holder 123 for biasing the ejection lever 111 in a direction indicated by arrow R1 in FIG. 1. The foremost part of the ejection lever 111 is provided with an operating piece 113 which is bent downwards.

Before insertion of the recording medium into the holder 123, the ejection lever 111 includes a control edge 114 engaged with a mating control edge 116 of the slider 105 so that the slider 105 is held at its foremost movement stroke end (see FIGS. 1 and 2).

When a recording medium 117 is inserted from the forward side into the holder 123, the operating piece 113 of the ejection lever 111 is thrust rearwards by the recording medium 117, so that the ejection lever 111 is rotated in the direction indicated by arrow R2 against the bias of the lever biasing spring 112 (see FIG. 3). When the ejection lever 111 is rotated in the direction indicated by arrow R2 in FIG. 3, the control edge 114 is disengaged from the mating control edge 116, so that the slider 105 is slid rearwards by the slider biasing spring 109 (see FIG. 4).

When the slider 105 is moved rearwards, the positions of the support pins 104, 104 of the holder 123 in the cam grooves 108, 108 are changed, such that the rearward side support pins 104, 104 are moved within the guide grooves 102 of the chassis 101 to cause descent of the holder 123 (see FIG. 5). With the descent of the holder 123, the recording medium 117 which it holds is loaded on a loading unit, not shown, thereby setting up a state enabling the reproducing operation of information signals for the recording medium 117. The slider 105 is moved rearwards at this time as the mating control edge 116 has a sliding contact with a portion of the ejection lever 111. The ejection lever 111 has its portion engaged with the mating control edge 116 of the slider 105, moved rearwards, so that the ejection lever is held at the end of the rotation indicated by arrow R2.

When the reproducing operation comes to a close, such that an ejection button, not shown, is actuated, a driving motor, not shown, is rotated to cause forward movement of the slider 105 under the driving force of the motor against the biasing force of the slider biasing spring 109.

When the slider 105 is moved forwards, the positions of the support pins 104, 104 of the holder 123 in the cam grooves 108, 108 are changed, such that the holder 123 is lifted by the rearward side support pins 104, 104 being moved in the guide groove 102b of the chassis 101.

When the slider 105 has been moved forwards by the ejection lever 111, the ejection lever 111 is rotated by the lever biasing spring 112 in a direction indicated by arrow R1. Consequently, the recording medium 117 is thrust forwards and ejected out of the holder 123 by the operating piece 113 of the ejection lever 111.

When the slider 105 is moved to a forward side preset position, the rotation of the driving motor ceases. The slider 105 is moved rearwards, under the force of the slider biasing spring 109, and the mating control edge 116 is engaged with the control edge 114 of the ejection lever 111, which is positioned at the end of the movement stroke in the direction R1. The slider 105 again is held at the forward end in the range of movement.

In the above-described recording medium driving device of the related art, described above, the lever biasing spring 112 for biasing the ejection lever 111 and the slider biasing spring 109 for biasing the slider 105 are required, with the consequence that the number of components is correspondingly increased. When inserting the recording medium 117 into the holder 123, the slider 105, moved towards rear, has a sliding contact with the ejection lever 111. Since the lever biasing spring 112 at this time is in the fully stretched state, the frictional resistance between the slider 105 and the ejection lever 111 is large, with the result that the slider 105 and the ejection lever 111 are lowered in durability. Moreover, the load imposed on the driving motor for ejecting the recording medium 117 is increased in an amount corresponding to the increased frictional resistance between the slider 105 and the ejection lever 111, thus increasing the power consumption.

Another instance of the recording medium driving device is a recording and/or reproducing apparatus for recording and/or reproducing information signals for the recording medium. In a certain type of this recording and/or reproducing apparatus, there is such an apparatus in which, when the recording medium is held by the holder, the slider held by the holder is moved in one direction to lower the holder to load the recording medium on the loading unit, and in which, when the slider is moved in the opposite direction, the holder is elevated, at the same time as the recording medium is ejected by the ejection lever from the holder.

As this sort of the recording and/or reproducing apparatus, there is such apparatus constructed as shown in FIGS. 6 and 7.

The recording and/or reproducing apparatus, shown in FIGS. 6 and 7, includes a holder **201** movable vertically relative to the chassis.

The holder **201** is movable vertically relative to the chassis, not shown. A cam lever **202** is supported by the holder **201** for sliding in the fore-and-aft direction. The cam lever **202** includes a cam **203** and a vertically extending support leg **204**, which support leg **204** is supported for movement in the up-and-down direction in a support opening **205** formed in the chassis.

A supporting piece **206** is provided on the upper surface of the holder **201**. The supporting piece **206** rotationally supports a head shift lever **207**. The head shift lever **207** is provided with a mating operating portion **208** that is in sliding contact with the cam **203** of the cam lever **202**.

A pickup includes a mounting portion **209**. On the upper surface of the mounting portion **209**, there is mounted a rear end of a head mounting plate **211**, the distal end of which carries a magnetic head **210**. The head mounting plate **211** is formed of an elastic material.

The above-described holder **201** and the chassis etc. are arranged within an outer casing of the recording and/or reproducing apparatus. A top plate **213** of the outer casing is provided on top of the holder **201**.

FIG. 6 shows the state in which the magnetic head **210** is at a first retreat position. During reproduction of information signals from a recording medium, for example, the magnetic head **210** is not in use, so that the magnetic head **210** is retreated from the recording medium held on the holder **201**, and is at the first retreat position. At this time, the mating operating portion **208** of the head shift lever **207** is engaged with the uppermost end of the cam **203** of the cam lever **202**, with the head mounting plate **211** being lifted by the head shift lever **207** in a forwardly descending state. The magnetic head **210** is at a position of being retreated from the recording medium held by the holder **201** right above the upper surface of the holder **201**.

When the information signal reproducing operation for the recording medium has been finished, such that the recording medium is ejected forwards from the holder **201**, the holder **201** is moved upwards from the state of FIG. 58, while the cam lever **102** is also moved upwards in unison with the holder **201** (see FIG. 7).

When the holder **201** and the cam lever **202** are moved upwards, the relative position between the head shift lever **207** and the cam **203** is not changed. However, since the cam **203** is at substantially the same height level as the mounting portion **209**, the magnetic head **210** is moved to a second retreat position with a rising gradient in the forward direction, so that the magnetic head **210** is at a higher height level than the above-mentioned first retreat position (see FIG. 7).

In the above-described recording and/or reproducing apparatus of the related art, the head mounting plate **211**, which has been lifted with the forwardly descending gradient, is lifted with a forwardly rising gradient when the recording medium is ejected from the holder **201**. As a consequence, in the recording and/or reproducing apparatus of the related art, there is required a large space between the upper surface of the holder **201** and the outer casing **213** of the outer casing, in order to permit the magnetic head **210** to be moved between the first and second retreat positions, thus increasing the overall thickness of the recording and/or reproducing apparatus.

Moreover, the recording medium driving device is designed for recording and/or reproducing information signals for the disc-shaped recording medium loaded on the disc table. This sort of the disc recording and/or reproducing apparatus includes an ejection mechanism for ejecting the disc-shaped recording medium loaded on the disc table on completion of the recording and/or reproduction of the information signals, and a head movement mechanism for causing movement of the magnetic head, adapted for applying the magnetic field to the disc-shaped recording medium during recording, in a direction into contact with or away from the disc-shaped recording medium.

In certain versions of this sort of the recording medium driving device, both the operations of the ejection mechanism and the head movement mechanism are operated by the driving power of a sole driving motor, in order to make common use of the sole driving motor. In a disc recording and/or reproducing apparatus of the related art, in which a sole driving motor is used in common, a slider is supported for movement on a holder holding a disc-shaped recording medium, and is moved a first movement amount in one direction with respect to the holder. On completion of the loading, the slider is moved by a second movement amount relative to the holder in the same sole direction by the driving motor to actuate the head movement mechanism, and the magnetic head is moved in a direction of contacting with the so loaded disc-shaped recording medium to set up the recording mode.

Consequently, when the recording of the information signals has come to a close, the driving motor is rotated in reverse, while the slider is moved relative to the holder in a direction opposite to the aforementioned one direction by a second amount of movement, with the magnetic head being moved in a direction away from the disc-shaped recording medium to cancel the setting of the recording mode. When the disc-shaped recording medium is to be ejected in the canceled state of the setting of the recording mode, rotation of the driving motor is continued to cause the slider to be moved relative to the holder by the first amount of movement in an opposite direction to the aforementioned one direction to cause the operation of the ejection mechanism.

In the above-described driving device of the related art, when the recording of the information signals has come to a close and the disc-shaped recording medium is to be ejected, the slider is moved in the same direction to actuate the ejection mechanism or the head movement mechanism, so that a movement stroke corresponding to the sum of the first and second amounts of movement is required.

As a consequence, the recording medium driving device is increased in size by an amount corresponding to the increased amount of the slider movement stroke.

There is also a recording medium driving device adapted for driving a disc cartridge in a casing member of which a disc-shaped recording medium is rotatably mounted and in which a shutter is also supported for sliding on the casing member.

In such driving device, the shutter is slid by a shutter opening/closing mechanism, usually at the time of inserting the disc cartridge into the holder to open a through-hole formed in the casing member to permit the laser light to be illuminated from a light source of the optical pickup to the disc-shaped recording medium contained in the casing member.

The shutter slid is held at an open position, however, if the shutter is vibrated in this case to produce resonant vibrations, it may be impossible to maintain optimum repro-

5

ducing operations for the disc-shaped recording medium of the disc driving device.

In order to combat this inconvenience, a certain disc driving device of the related art includes retention means, such as a spring plate, on a portion of an outer casing, in the inside of which a holder or a chassis is mounted, such that, when the disc-shaped recording medium is loaded on the disc table, the shutter is retained by this retention means to suppress the vibrations which will otherwise be produced.

In the recording medium driving device of the related art, in which the retention means are provided at a portion of the outer casing thereof, the vibrations transmitted from outside to the disc driving device tends to be transmitted to the shutter through the retention means, with the result that vibrations cannot be suppressed sufficiently.

DISCLOSURE OF THE INVENTION

It is an object of the present invention to provide a novel recording medium driving device which overcomes the problems the above-described recording medium driving device of the related art suffers.

It is another object of the present invention to provide a recording medium driving device in which it is possible to reduce the number of components and to improve durability of the respective components as well as to reduce the power consumption.

It is still another object of the present invention to provide a recording medium driving device in which collision between a recording medium inserted into or ejected from the holder and the magnetic head may be avoided to reduce the size of the apparatus itself.

It is a further object of the present invention to provide a recording medium driving device in which the operations of the ejection mechanism and the head movement mechanism are carried out by a sole driving motor to reduce the size of the apparatus itself.

It is yet another object of the present invention to provide a recording medium driving device in which vibrations of the shutter may be efficiently suppressed to assure an optimum operation.

For accomplishing the above object, the present invention provides a recording medium driving device including a loading unit for loading a recording medium thereon, and a holder movably carried by a chassis, with the holder holding the recording medium and transporting the recording medium between an insertion/ejection position of inserting or ejecting the recording medium and a loading position of loading the recording medium on the loading unit. The recording medium driving device also includes an ejection lever for ejecting the recording medium from the holder, a slider movable in a direction of inserting the recording medium into the holder and in a direction of ejecting the recording medium from the holder, with the slider causing the holder to be moved to the loading position when the slider is moved in the inserting direction, with the slider causing the holder to be moved to the insertion/ejection position when the slider is moved in the ejecting direction. The recording medium driving device also includes a spring member provided between the ejection lever and the slider for biasing the ejection lever in a direction of ejecting the slider from the holder and for biasing the slider in the inserting direction.

Preferably, the ejection lever is rotatably mounted at a corner of the chassis and includes at its one end an operating portion for ejecting the recording medium from the holder,

6

while including at its other end a control portion for controlling the slider towards the ejecting direction. When the recording medium is not loaded on the recording medium driving device, the slider is arranged in the ejecting direction and the operating portion of the ejection lever is biased and rotated in the ejecting direction, the controlling portion engaging with a controlled portion of the slider to control the slider in the ejecting direction.

In the recording medium driving device according to the present invention, when the recording medium is introduced into the holder, the operating portion of the ejection lever thrusting the forward end of the recording medium is inserted so that the operating portion is rotated in the inserting direction. The controlling portion is rotated with such rotation to be disengaged from the controlled portion so that the slider is moved in the inserting direction under the bias of the spring member. The slider has a portion thereof engaged with a portion of the other end of the ejection lever to hold the ejection lever at the inserting direction. The holder is moved to the loading position with movement of the slider in the inserting direction for loading the recording medium inserted in the holder to the loading position.

Preferably, the recording medium driving device further includes ejection controlling means for causing the slider to be moved in the ejecting direction responsive to a user's command. The slider is moved in the ejecting direction under control by the ejection controlling means to cause the holder to be moved to the insertion/ejection position and to extend the spring member. The operating portion of the ejection lever is moved in the ejecting direction to eject the recording medium by a portion of the slider being disengaged from a portion of the opposite end of the ejection lever with movement of the slider. The controlling portion of the ejection lever is re-engaged with the controlled portion of the slider to control the slider at the ejecting direction.

The present invention also provides a recording medium driving device including a loading unit for loading a recording medium thereon, and a holder for holding the recording medium, which holder is movable between an insertion/ejection position inserting/ejecting the recording medium and a loading position loading the recording medium on the loading unit. The recording medium driving device also includes an ejection lever for ejecting the recording medium from the holder at the inserting/ejecting position, and a slider movable in a direction of inserting the recording medium into the holder and in a direction of ejecting the recording medium from the holder. When the slider is moved in the inserting direction, the slider causes the holder to be moved from the inserting/ejecting position towards the loading position. When the slider is moved in the ejecting direction, it causes the holder to be moved from the loading position to the insertion/ejection position. The recording medium driving device also includes a head for recording information signals on the recording medium, a head shift lever for causing the head to be moved in a direction of contacting with and separating from the recording medium, and a cam lever carried by the holder for movement in the inserting direction and in the ejecting direction. The cam lever operates the head shift lever. The head is retreated to a first retreat position receded from the recording medium as held by the holder, when the recording medium is ejected from the holder positioned at the insertion/ejection position under the driving force of the driving motor. The head is also retreated to a second retreat position receded from the recording medium when information signals are reproduced from the recording medium at the loading position. The holder is moved to the insertion/ejection position when the recording

medium is ejected from the holder by a manual operation by a user during the recording of information signals on the recording medium in the loading unit. Also, the head is retreated to a third retreat position receded from the recording medium ejected from the holder. In the first, second and third retreat positions, the relative position between the head and the holder relative to the contacting or separating direction is substantially the same.

In this recording medium driving device, the cam lever includes a first cam portion for operating the head shift lever to cause the head to be receded to the first retreat position receded from the recording medium held by the holder when the recording medium is ejected from the holder at the insertion/ejection position, under the driving force of the driving motor, a second cam portion for operating the head shift lever so that, when the information signals are reproduced at the loading unit from the recording medium, the head will be receded to the second retreat position receded from the recording medium, and a third cam portion for operating the head shift lever so that, when the recording medium is ejected by a manual operation of the user when information signals are being recorded on the recording medium in the loading unit, the holder will be moved to the insertion/ejection position, the head being receded to the third retreat position in which the head is receded from the recording medium.

The present invention also provides a recording medium driving device including a loading unit for loading a disc thereon, a head movement mechanism for causing a recording head, recording the information signals on a disc loaded on the loading unit, to be moved in a direction of contacting with or separating from the disc, an ejection mechanism for ejecting the disc loaded on the loading unit to outside, a driving gear rotated in one direction or in the other direction by a driving motor, a joint lever which, when the driving gear is rotated in one direction, is moved through the driving gear to operate the ejection mechanism, and a driving lever which, when the driving gear is rotated in the other direction, is moved through the driving gear to operate the head movement mechanism.

Preferably, the recording medium driving device further includes a driving power transmitting portion provided to the driving gear for transmitting the driving power of the driving motor, and an operating lever which, when the driving gear is rotated in the other direction, is thrust by the driving power transmitting portion to impart the driving power of the driving motor to the driving lever, and which, when the driving gear is rotated in the one direction, is thrust by the driving power transmitting portion to be receded from the trajectory of the driving power transmitting portion.

The present invention also provides a recording medium driving device for driving a disc cartridge including a disc and a cartridge having the disc held therein, with the disc cartridge opening/closing an information recording surface of the disc by a shutter movably mounted in the cartridge. The recording medium driving device includes readout means movable along the radius of the disc for reading out the information from the information recording surface of the disc, a chassis on which the readout means is mounted for movement radially of the disc, a holder movably mounted on the chassis for holding the disc cartridge, a disc table for loading a disc in the disc cartridge as held by the holder, a shutter opening/closing mechanism for opening/closing the shutter, and retention means provided on the chassis or the holder for holding the shutter opened by the shutter opening/closing mechanism when the disc is loaded on the disc table.

The retention means may be a spring plate member having one end mounted to the chassis and having retention means at the other end. The retention means is resiliently contacted with the shutter.

The retention means may be a detection switch having a mating operating shaft resiliently contacted with the shutter when the holder is moved. By the mating operating shaft being operated by resilient contact with the shutter, the detection switch detects whether or not writing on an information recording surface of the disc is inhibited.

Other objects, features and advantages of the present invention will become more apparent from reading the embodiments of the present invention as shown in the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 show the operation of a recording and/or reproducing apparatus of the related art, and is a plan view showing the state prior to rotation of the ejection lever,

FIG. 2 is a side view thereof, showing the state prior to descent of the holder,

FIG. 3 is a plan view thereof, showing the state prior to descent of the holder,

FIG. 4 is a plan view thereof, showing the state in which the ejection lever has been rotated to shift the slider backwards, and

FIG. 5 is a side view thereof showing the state in which the holder has been lowered.

FIG. 6 shows the operation of another recording and/or reproducing apparatus of the related art, and is a side view, shown partially in cross-section, and showing the state in which, when the holder has been lowered, the magnetic head has retreated, and

FIG. 7 is a schematic enlarged side view, shown partially in cross-section, and showing the state in which, when the holder is lifted, the magnetic head has been retreated.

FIG. 8 is a perspective view showing the recording and/or reproducing apparatus to which the present invention is applied, and a disc cartridge.

FIG. 9 is a perspective view showing the chassis and respective portions or units supported by the chassis.

FIG. 10 is a perspective view showing the inner structure of a disc recording and/or reproducing apparatus according to the present invention.

FIG. 11 is a plan view, partially cut away, and showing various portions or units supported by the chassis.

FIG. 12 is a plan view showing a holder and a cam lever held by the holder.

FIG. 13 is an enlarged side view showing the holder and the cam lever held by the holder.

FIG. 14 is a plan view showing the holder and the cam lever as well as the slider held by the cam lever.

FIG. 15 is an enlarged side view showing the holder and the cam lever as well as the slider held by the cam lever.

FIG. 16 is a perspective view showing a chassis.

FIG. 17 is a perspective view showing the holder, partially cut away.

FIG. 18 is a plan view showing a head shift lever.

FIG. 19 is a side view showing the head shift lever.

FIG. 20 is a plan view showing a cam lever.

FIG. 21 is a side view showing the cam lever.

FIG. 22 is a plan view showing a slider.

FIG. 23 is a left side view showing the slider.

FIG. 24 is a right side view showing the slider.

FIG. 25, showing a sequence of assembling the slider on the holder, is a side view showing the state in which a holder supporting pin is engaged in a lower horizontal portion of a slider cam groove,

FIG. 26 is a side view showing the state in which the slider is moved forwards and the holder supporting pin is engaged in the upper horizontal portion of the slider cam groove,

FIG. 27 is an enlarged side view showing the state in which the slider has been placed on the holder, and

FIG. 28 is an enlarged side view showing the state in which the assembling of the slider on the holder has been completed.

FIG. 29 is a plan view showing an ejection lever.

FIG. 30 is a front view thereof.

FIG. 31 is a side view showing a joint lever.

FIG. 32 shows a disc detection switch and is a cross-sectional view showing the switch in the non-operated state, and

FIG. 33 is a cross-sectional view showing the switch in the operated state.

FIG. 34 is a plan view showing a driving lever.

FIG. 35 is a plan view showing a limit lever.

FIG. 36 is a plan view showing a converting lever.

FIG. 37 is a cross-sectional view showing the converting lever.

FIG. 38 is a bottom view showing the limit lever and an operating lever supported by the limit lever.

FIG. 39 is a plan view showing the operating lever.

FIG. 40 is an enlarged cross-sectional view showing the state of mounting a spring plate member to the chassis.

FIG. 41 is a block diagram showing the structure of a portion of the disc recording and/or reproducing apparatus.

FIG. 42 shows the operation of the disc recording and/or reproducing apparatus and is a plan view showing the initial state prior to operation of respective portions or units,

FIG. 43 is a side view showing the initial state prior to operation of respective portions or units, with a joint lever being omitted, and

FIG. 44 is a side view showing the initial state prior to operation of the respective portions or units.

FIG. 45 is a plan view showing, of the constituent elements carried by the lower chassis surface, the initial state prior to operation of respective portions or units of the disc recording and/or reproducing apparatus, and

FIG. 46 is a side view, shown partially in cross-section, and showing the initial state prior to operation of the respective portions or units as the position relationships between the cam lever and the magnetic head.

FIG. 47 is a plan view showing the state in which a disc cartridge is being introduced into a cartridge holder.

FIG. 48 is a plan view showing the state in which the slider has been moved to the rear end of its movement stroke.

FIG. 49 is a side view showing the state of descent of the holder, with the joint lever being omitted.

FIG. 50 is a side view, shown partially in cross-section, and showing the state in which a disc cartridge has been introduced into the cartridge holder and the holder is being lowered, as the position relationships between the cam lever and the magnetic head.

FIG. 51 is a side view, shown partially in cross-section, and showing the state of completion of descent of the holder, as the position relationships between the cam lever and the magnetic head.

FIG. 52 is a cross-sectional view showing the state in which a spring plate member used as retention means has been resiliently contacted by a shutter.

FIG. 53 is a cross-sectional view showing the state in which a mating operating shaft of a disc detection switch used as retention means has been resiliently contacted by the shutter.

FIG. 54 is a plan view showing, of the constituent elements supported by the lower surface of the chassis, the state in which a driving gear has been rotated in a first direction and the limit lever has been moved to the forward side end of the movement stroke, while the driving lever has been moved to the rear movement stroke end.

FIG. 55 is a side view showing the state in which the magnetic head has been inserted via a head inserting opening in the holder, as the position relationships between the cam lever and the magnetic head.

FIG. 56 is a plan view showing, of the constituent elements carried on the lower chassis surface, the state in which the driving gear has been rotated in a second direction, the limit lever has been moved to the rear movement stroke end and the driving lever has been moved to the forward movement stroke end.

FIG. 57 is a side view showing the state in which, when the driving gear has been rotated in the second direction, the joint lever is positioned at the rear stroke end.

FIG. 58 is a plan view showing, of the constituent elements carried by the lower chassis surface, the state in which the driving gear has been rotated in the second direction and the joint lever has been moved forwards.

FIG. 59 is a side view showing the state in which the driving gear has been rotated in the second direction and the joint lever has been moved to the forward movement stroke end.

FIG. 60 is a plan view showing the state in which the disc cartridge has been ejected from the holder and in which the slider has been moved forwards.

FIG. 61 is a plan view showing, of the constituent elements carried by the lower chassis surface, the state in which the driving gear has been rotated in the second direction and the thrusting lug has a sliding contact with a mating operating edge, with the operating lever having been rotated.

FIG. 62 is a side view showing the state in which the thrusting lug of the driving gear is disengaged from the mating operating piece of the joint lever, with the joint lever having been moved to the rear movement stroke end.

FIG. 63 is an enlarged plan view showing, of the constituent elements carried by the lower chassis surface, the state in which the detection by a rotation detection switch has been made and the rotation of the driving motor ceases.

FIG. 64 is an enlarged side view, partially shown in section, and showing the state in which manual ejection has been performed in the recording mode, as the position relationships between the cam lever and the magnetic head.

BEST MODE FOR CARRYING OUT THE INVENTION

In the following, certain preferred embodiments of the present invention will be explained with reference to the

11

drawings. The following embodiments are directed to a disc recording and/or reproducing apparatus in which information signals are recorded on or reproduced from a magneto-optical disc having a diameter of approximately 64 mm, such as Mini-Disc.

A recording and/or reproducing apparatus **1**, according to the present invention, has an outer casing **2** of a thin box shape, within which respective members and mechanisms as required are accommodated, as shown in FIG. **8**. A horizontally elongated rectangular insertion/ejection opening **2a** is formed in the front surface of the outer casing **2**. The outer casing **2** carries a door **3** for opening/closing the insertion/ejection opening **2a**. If, in introducing the disc cartridge, as later explained, into the outer casing **2**, the disc cartridge is ejected from the outer casing **2**, the door **3** is actuated to open the insertion/ejection opening **2a**. At a preset location of the outer casing **2** are arranged plural operating buttons **4** for performing various functions, as shown in FIG. **8**. The reproducing operation, the recording operation, cessation of the operation, change of sound volume, ejection of the disc cartridge from the outer casing **2** and various editing functions may be carried out by actuating these operating buttons **4**.

Within the outer casing **2**, there is arranged a chassis **5**, as shown in FIGS. **9** to **11**. The chassis **5** is formed integrally by a major surface portion **6**, side supporting portions **7**, **8** arranged on left and right side edges of the major surface portion **6**, and a lever supporting portion **9** as well as a lever controlling portion **10**, with the lever supporting portion **9** and the lever controlling portion **10** upstanding from the rear edge of the major surface portion **6** and being spaced apart from each other in the left and right direction, as shown in FIG. **16**. A pickup mounting opening **6a** is formed towards the right side of the major surface portion **6**, while a switch mounting opening **6b** is formed in the forward left side thereof. A retention unit mounting opening **6c** is formed towards the front right side of the major surface portion **6**. Towards the right side of the major surface portion **6**, positioning pins **11**, **11** are formed integrally in a staggered relationship in the fore-and-aft direction. Each positioning pin **11** is made up by a positioning projections **11a** and a support portion **11b** formed on the rim of the positioning projections **11a**, **11a**. Towards the left side end of the major surface portion **6** are formed receptacles **12**, **12** in a staggered relationship in the fore-and-aft direction. The upper surfaces of these receptacles **12**, **12** are flush with the upper surfaces of the support portions **11b**, **11b** of the positioning pins **11**, **11**.

Towards the forward and rear ends of the side supporting portions **7**, **8** are respectively formed supporting projections **13**, **14**, which supporting projections **13**, **14** are formed with forwardly opening supporting grooves **13a**, **14a**, respectively. On the rear sides of the rear side supporting projections **14**, **14**, the side supporting portions **7**, **8** are formed with lugs **15**, **15**, with portions lying between the supporting projections **14**, **14** and the lugs **15**, **15** being opened upwards to serve as guide grooves **15a**, **15a**. On the upper ends of the supporting projection **14** and the lug **15** of the side supporting portion **7** on the left side, there are formed spring retention pieces **14b**, **15b**, respectively.

The lever supporting portion **9** of the chassis **5** is made up by an upstanding portion **9a**, protruded upwards from the major surface portion **6**, and a supporting portion **9b** protruded forwards from the upper edge of the upstanding portion **9a**. The lever controlling portion **10** of the chassis **5** is made up by an upstanding portion **10a**, protruded upwards from the major surface portion **6**, and a supporting portion

12

10b protruded forwards from the upper edge of the upstanding portion **10a**. The supporting portion **10b** is formed with a control opening **10c** elongated in the forward and aft direction.

A holder **16** is vertically movably supported by the side supporting portions **7**, **8**, as shown in FIG. **10**. The holder **16** is formed of a plate-shaped elastic metal material, and is formed integrally from a top plate portion **17**, side plate portions **18**, **19**, and support plates **20**, **20**, protruded from the lower edges of the side plate portions **18**, **19** in a direction approaching to each other. The disc cartridge is inserted and held in a flattened spacing defined by the top plate portion **17**, side plate portions **18**, **19** and the support plates **20**, **20**.

In the top plate portion **17**, a retention spring **17a** is segmented so that it is slightly inclined towards its distal end. In the top plate portion **17**, there is also formed a head inserting opening **17b** in register with the pickup mounting opening **6a** of the chassis **5**. The right side end of the top plate portion **17** is formed integrally with a shift lever restoration spring **17c** which is protruded rearwards. The left rear end of the top plate portion **17** is formed integrally with a relief opening **17d**.

The forward ends of the side plate portions **18**, **19** of the holder **16** are respectively formed with embossed supports **18a**, **19a** which are protruded outwards. The rear ends of the side plate portions **18**, **19** are formed with outwardly protruded support pins **18b**, **19b**, respectively. The right side plate portion **19** is provided with a shutter opening/closing mechanism which is formed by a shutter restoration spring **21** and an unlock piece **22** which are formed by partially segmenting the side plate portion **19**. The shutter restoration spring **21** is protruded slightly forwards and is inclined relative to the side plate portion **19** so that its distal end will be positioned inwardly of the side plate portion **19**. The distal end of the shutter restoration spring **21** is bent for protruding inwards and provided as a holding portion **21a**.

The unlock piece **22** is extended in the fore-and-aft direction so that its major surface is directed in the up-and-down direction.

The forward end of the left side support plate **20** is formed with an operating opening **20a**.

The top plate portion **17** of the holder **16** rotatably supports a head shift lever **23**, as shown in FIGS. **10**, **12** and **17**. The head shift lever **23** is mounted proximate to the rear end of the head inserting opening **17b** and is protruded towards the head inserting opening **17b**. From the left side edge of the head shift lever **23**, a rotation controlling piece **23a** and a mating operating piece **23b**, spaced apart from each other in the fore-and-aft direction, are protruded leftwards, as shown in FIGS. **18** and **19**. The mating operating piece **23b** is in the form of a letter V in cross-section, with the apex pointing downwards, when seen from its lateral side, as shown in FIGS. **18** and **19**. The right side edge of the head shift lever **23** is formed with the rightwardly protruded rotation controlling piece **23a**. The foremost part of the shift lever restoration spring **17c** provided on the top plate portion **17** of the holder **16** is elastically contacted with the right side end of the head shift lever **23**. As a consequence, the head shift lever **23** is biased so that its foremost part will be moved substantially downwards.

A cam lever **24** is supported by the holder **16** for movement in the fore-and-aft direction, as shown in FIGS. **10**, **12** and **13**. The cam lever **24** and the head shift lever **23** operate as a head movement mechanism for uplifting and lowering a magnetic head which will be explained subsequently.

13

The cam lever **24** is formed with a supported portion **25**, elongated in the fore-and-aft direction, a protruding portion **26**, protruded rightwards from the supported portion **25** and a cam leg **27** protruded downwards from the supported portion **25**, as shown in FIGS. **20** and **21**. The supported portion **25** has a plural number of support openings **25a**, elongated in the fore-and-aft direction. The supporting pin **17** or the supporting piece **17f** provided on the top plate portion **17** is inserted into these support openings **25a** to permit movement in the fore-and-aft direction. A protruded portion **26** is protruded rightwards from the right side edge of the supported portion **25** so that its foremost part is elongated in the fore-and-aft direction. At the foremost part of the protruded portion **26**, a retention piece **28** and a cam piece **29**, both of which are bent from the foremost portions of the protruded portion **26**, are provided in a spaced-apart relationship to each other. The cam piece **29** is provided, looking from the rear side, with a first cam portion **29a**, a second cam portion **29b**, at a lower portion than the first cam portion **29a**, and a third cam portion **29c**, at a lower portion than the second cam portion **29b**, with the first cam portion **29a** being at substantially the same height level as the third cam portion **29c**. The portion of the cam leg **27** lower than a mid portion in the vertical direction is formed as a cam portion **30**. This cam portion **30** is made up by an upper portion, extending from an upper position for a short length in the vertical direction, an inclined portion **30b**, contiguous to the upper portion **30a** and deflected progressively downwards towards rear and a lower portion **30c** contiguous to the inclined portion **30b** and extending from the inclined position for a short length in the vertical direction.

A slider **31** is supported by the holder **16** for movement in the fore-and-aft direction, as shown in FIGS. **10**, **14** and **15**. The slider **31** is made up by a connecting portion **32**, elongated in the left and right direction, extensions **33**, **34**, protruded rearwards from the left and right ends of the connecting portion **32**, and side portions **35**, **36** depending from the side edges of the extensions **33**, **34**, as shown in FIGS. **22** and **24**. The left side extension **33** is provided with a spring retention projection **33a**, protruded leftwards from the left side edge thereof, and a spring retention projection **33b**, protruded rightwards from the right side edge thereof. A controlled piece **33c** is provided at the rear end of the extension **33** by bending a portion of the extension **33**. The rear end of the extension is formed with an edge **33d** inclined so as to be progressively deflected rightwards in the forward direction. The side portions **35**, **36** are provided with supported pins **35a**, **36a**, which are spaced apart from each other in the fore-and-aft direction. The side portions **35**, **36** are also provided with cam grooves **37**, **38**, which are spaced apart from each other in the fore-and-aft direction. The forward side cam groove **37** is formed with an upper horizontal portion **37a**, an inclined portion **37b** and a lower horizontal portion **37c**, in this order, beginning from the rear side, with the upper horizontal portion **37a** being opened rearwards. The rear side cam groove **38** is formed with an upper horizontal portion **38a**, an inclined portion **38b** and a lower horizontal portion **38c**, in this order, beginning from the rear side, with the lower horizontal portion **38c** being opened forwards. Directly at back of the cam grooves **37**, **37**, there is no portion of the slider **31**. Here, relief openings **35b**, **36b**, opened downwards and rearwards, are formed.

The left side portion **35** is formed with thrust pieces **35c**, **35d**, directly at back and at the rear end of the relief opening **35b**.

The slider **31** is assembled to the holder **16** as follows (see FIGS. **25** to **28**).

14

First, the slider **31** is connected to the rear side of the holder **16**, as the slider is inclined so that its forward end is positioned upwards, in such a manner that the supporting pins **18b**, **19b** of the holder **16** will be inserted into the cam grooves **38**, **38** of the slider **31** (see FIG. **25**).

The slider **31** is then moved forwardly of the holder **16** so that the supporting pins **18b**, **19b** will be engaged in the rear ends of the cam grooves **38**, **38** (see FIG. **26**).

The slider **31** is then rotated relative to the holder **16** until the connecting portion **32** rests on the top plate portion **17**. Since the relief openings **35b**, **36b** are formed directly at back of the cam grooves **37**, **37** of the slider **31**, there is no risk of the slider **31** colliding against the supporting portions **18a**, **19a** of the holder **16**, such that, when the connecting portion **32** is set on the top plate portion **17**, the support portions **18a**, **19a** of the holder **16** are positioned directly at back of the upper horizontal portions **37a**, **37a** of the cam grooves **37**, **37** (see FIG. **27**).

Finally, the slider **31** is moved slightly rearwards relative to the holder **16** so that the support portions **18a**, **19a** are inserted and engaged in the cam grooves **37**, **37** from the rear side (see FIG. **28**). This causes the slider **31** to be supported by the holder **16** for movement in the fore-and-aft direction.

For assembling the slider **31** to the holder **16**, it is only sufficient that the support pins **18b**, **19b** are inserted from the forward side into the cam grooves **38**, **38** of the slider **31**, the slider **31** is then rotated relative to the holder **16** and subsequently the slider is moved towards rear. As a consequence, there is no necessity to provide an allowance in the distance between the slider **31** and the holder **16** in the left and right direction corresponding to the amount of protrusion of the support portions **18a**, **19a** and the support pins **18b**, **19b** from the side plate portions **18**, **19**, respectively. The result is that the width in the left and right direction of the slider **31** may be correspondingly reduced to reduce the size of the disc recording and/or reproducing apparatus **1**.

On the lever supporting portion **9** of the chassis **5**, an ejection lever **39** is supported for rotation, as shown in FIGS. **9** and **10**. As for the slider **31** and the ejection lever **39**, the ejection lever **39**, operating as an ejection mechanism for ejecting the disc cartridge held by the holder **16** from the holder **16**, is formed integrally by a rotation fulcrum point **40**, a control projection **41** protruded from the rotation fulcrum point **40**, a protrusion **42** extending from the rotation fulcrum point **40** in a direction substantially perpendicular to the control projection **41** and an operating portion **43** extending downwards from the distal end of the protrusion **42**, as shown in FIGS. **29** and **30**. The control projection **41** has its distal end edge formed as a control edge **41a** contacted with the controlled piece **33c** of the slider **31**. A roll **44** is carried for rotation by the distal end of the control projection **41**. This roll **44** is carried as it is protruded downwards from the control projection **41**. The forward edge of the protrusion **42** has a spring retainer **42a**, while its rear edge includes an insertion piece **42b** bent downwards. The insertion piece **42b** is inserted into the control opening **10c** of the lever controlling portion **10** of the chassis **5**. Rotation of the ejection lever **39** in a forward direction indicated by arrow **R1** in FIG. **10** is controlled by the insertion piece **42b** contacting with the forward opening edge of the control opening **10c**.

The holder **16**, carrying the cam lever **24** and the slider **31**, is slidably engaged from an inner side in guide grooves **15a**, **15a** of the side supporting portions **7**, **8** of the chassis **5**, as the support pins **18b**, **19b** are protruded from the cam

15

grooves **38, 38** of the slider **31**. The slider **31**, carried by the holder **16**, has the supported pins **35a, 36a** slidably engaged from the inner side in the supporting grooves **13a, 14a** of the side supporting portions **7, 8** of the chassis **5**. As a consequence, the holder **16** is movable in the vertical direction relative to the chassis **5** along with the cam lever **24**. The slider **31** is movable in the fore-and-aft direction relative to the holder **16**, by the support portions **18a, 19a** and the support pins **18b, 19b** being moved in the cam grooves **37, 38** of the slider **31** during movement of the holder **16**.

When the holder **16** has been supported by the chassis **5** as described above, a spring member **45** as a tension coil spring is mounted under tension between the spring retainer **42a** of the ejection lever **39**, rotatably carried by the lever supporting portion **9**, and the spring retention projection **33b** of the slider **31** (see FIG. 10). As the ejection lever **39** is biased in a direction indicated by arrow **R1** in FIG. 10, the slider **31** is biased rearwards, with the controlled piece **33c** of the slider **31** being contacted with the control edge **41a** of the control projection **41** of the ejection lever **39**, positioned at the stroke end of rotation in the direction indicated by arrow **R1** in FIG. 10, to control the rearward movement of the slider **31**.

Between the spring retention projection **33a** of the slider **31** and the spring retention piece **14b** of the side supporting portion **7** of the chassis **5**, an auxiliary spring **46**, having a spring force weaker than the spring force of the spring member **45**, is mounted under tension. This also biases the slider **31** rearwards (see FIG. 10).

On the side supporting portion **7**, a joint lever **47** is supported for movement in the fore-and-aft direction, as shown in FIGS. 9 and 10. The joint lever **47** is elongated in the fore-and-aft direction and is formed with supported openings **47a, 47a** which are spaced apart from each other in the fore-and-aft direction (see FIG. 31). The forward lower edge of the joint lever **47** is formed with a mating operating piece **47b**, whereas the upper edge of the joint lever between the paired supported openings **47a, 47a** thereof is formed with an upwardly projecting thrusting piece **47b**. A spring retainer **47d** is formed above the rear supported opening **47a** of the joint lever **47**. The rear end of the joint lever **47** is bent rightwards to form a thrusting portion **47e**. The support pins **7a, 7a** provided on the side supporting portion **7** are inserted into the supported openings **47a, 47a** of the joint lever **47** so as to be carried for movement in the fore-and-aft direction. With the joint lever **47** supported by the side supporting portion **7**, a tension coil spring **48** is mounted under tension between the spring retainer **47d** and the spring retention piece **15b** of the side supporting portion **7** for biasing the joint lever **47** rearwards.

At a mid portion of the major surface portion **6** of the chassis **5**, a spindle motor, not shown, is mounted, and a disc table **49** is secured to a motor shaft of the spindle motor (see FIGS. 2 and 4). The disc table **49** includes a centering boss **49a**, fitted in a center opening of a disc-shaped recording medium, and a table **49b** on which is set an inner rim of the disc-shaped recording medium. A suction magnet, not shown, is embedded in the centering boss **49a**.

Within the pickup mounting opening **6a** of the major surface portion **6**, an optical pickup **50** is mounted for movement radially of the disc-shaped recording medium, as shown in FIGS. 9 and 11. The optical pickup **50** includes a biaxial actuator **52**, having an objective lens **52a**, carried on a movable base **51**. The movable base **51** has its forward and rear ends carried for sliding movement by guide shafts **53,**

16

54 mounted on the lower surface of the major surface portion **6**, respectively. A nut, not shown, provided on the movable base **51**, is engaged with a lead screw **55** provided on the lower surface of the major surface portion **6**. The lead screw **55** is rotated by a feed motor **56** provided on the lower surface of the major surface portion **6**. When the lead screw **55** is rotated by the feed motor **56**, the nut meshing with the lead screw **55** is fed along the axial direction of the lead screw **55**, whereby the optical pickup **50** is guided by the guide shafts **53, 54** so as to be moved along the radius of the disc-shaped recording medium.

The rear end of the optical pickup **50** carries the lower surface of a U-shaped connecting member **57** with the opening of the letter U being opened forwards when seen from the lateral side. The connecting member **57** includes an intermediate portion, lying directly at back of the rear edge of the major surface portion **6**, while having an upper surface portion lying directly above the rear end of the holder **16** (see FIG. 10). On the upper surface of the connecting member **57** are mounted a head mounting arm **58** and an arm control plate **59** for controlling excess upward shifting of the head mounting arm **58** (see FIG. 10). The head mounting arm **58**, formed by an elastic metal sheet of a thin thickness, is elongated in the fore-and-aft direction, and has its rear end mounted to the connecting member **57**. The head mounting arm is set at a mid portion thereof in the fore-and-aft direction on the head shift lever **23** carried by the holder **16**. A magnetic head **58a** is mounted on the forward end of the head mounting arm **58** directly on top of the objective lens **52a** of the biaxial actuator **52**. The arm control plate **59** is elongated in the fore-and-aft direction, and has its rear end mounted to the connecting member **57** from above the head mounting arm **58**. The arm control plate includes lateral projections for holding the head mounting arm **58** from above.

Since the optical pickup **50** and the head mounting arm **58** are interconnected by the connecting member **57**, the head mounting arm **58**, carrying the optical pickup **50** and the magnetic head **58a**, may be moved in unison along the radius of the disc-shaped recording medium.

A circuit board **60** is mounted on the forward lower surface of the major surface portion **6** of the chassis **5**, and carries plural disc detection switches **61** on the forward left end of the major surface portion **6** of the chassis **5**, as shown in FIG. 9. A disc detection switch **61** is mounted via a connection board **62**, mounted in turn on the circuit board **60**, and includes a switch casing **63** and a mating operating shaft **64** vertically movably supported on the switch casing **63**, as shown in FIGS. 32 and 33. The switch casing **63** includes a rectangular bottom surface **63a**, a peripheral wall section **63b**, upstanding from the periphery of the bottom surface **63a** and an anti-extrication portion **63c** projected inwards from the peripheral wall section **63b**. The lower end of the peripheral wall section **63b** includes contacts **63d, 63d**. The mating operating shaft **64** is arbor-shaped, with the diameter of a lower end **64a** being thicker in thickness than the other portions. The operating shaft includes a pair of contacts **64b, 64b** provided on its lower end **64a**. A compression spring **65** is mounted under compression between the bottom surface **63a** of the switch casing **63** and the lower surface of the mating operating shaft **64**, so that the mating operating shaft **64** is biased upwards. When the mating operating shaft **64** is not acted on, the lower end **64a** is engaged with the anti-extrication portion **63c** of the switch casing **63**, thus establishing a non-detection state in which the contacts **64b, 64b** are not connected to the contacts **63d, 63d**, as shown in FIG. 32. When the mating operating shaft

64 is acted on by being thrust downwards by the disc cartridge, the contacts 64b, 64b are connected to the contacts 63d, 63d to set up a detection state.

On the leftward lower surface portion of the circuit board 60, a rotation detection switch 66 is mounted as shown in FIG. 11. A mating operating portion 66a of the rotation detection switch 66 is protruded substantially laterally.

On the lower left surface portion of the major surface portion 6, a driving lever 67 is mounted for movement in the fore-and-aft direction, as shown in FIG. 11. The driving lever 67 is elongated in the fore-and-aft direction and is formed with supported openings 67a, 67a at the forward and rear ends thereof (see FIG. 34). The forward end of the driving lever 67 is formed with an engagement opening 67b. In this engagement opening 67b is inserted and engaged the cam leg 27 of the cam lever 24. The rearward end of the driving lever 67 is formed with a connection opening 67c, while the mid portion thereof in the fore-and-aft direction is formed with a spring retention piece 67d.

By the support pins 6d, 6d on the lower surface of the major surface portion 6 being inserted into the supported openings 67a, 67a of the driving lever 67, and by the cam leg 27 of the cam lever 24 being inserted and engaged with the engagement opening 67b, the cam lever 24 is moved in the fore-and-aft direction with movement of the driving lever 67 in the fore-and-aft direction. Between the spring retention piece 67d and a spring retention projection 6e provided on the lower surface of the major surface portion 6, a tension coil spring 68 is mounted under tension for biasing the driving lever 67 in the forward direction, as shown in FIG. 11.

On the lower surface of the major surface portion 6, a limit lever 69 is mounted for movement in the fore-and-aft direction, in a side-by-side relationship to the driving lever 67, as shown in FIG. 11. The limit lever 69 is elongated in the fore-and-aft direction and is formed at forward and rear ends with supported openings 69a, 69a (see FIG. 35). Towards the forward end of the limit lever 69, there is provided a lever supporting portion 69b. A support shaft 69c is mounted in rear of the lever supporting portion 69b. The limit lever 69 has a spring retention opening 69d and a forwardly directed support piece 69e on the right-hand side and on the left-hand side of the support shaft 69c, respectively. The limit lever 69 is formed with a thrust piece 69f at back of the support piece 69e, while being formed with a connection opening 69g towards its rear end. In the supported openings 69a, 69a of the limit lever 69, support pins 6f, 6f provided on the lower surface of the major surface portion 6 are inserted and carried for movement in the fore-and-aft direction (see FIG. 11). A stop edge 6g formed on the major surface portion 6 of the chassis 5 is positioned ahead of the support piece 69e of the limit lever 69 (see FIG. 11).

The driving lever 67 and the limit lever 69 are interconnected by a conversion lever 70, as shown in FIG. 11. The conversion lever 70 has a center supported tube 70a and upwardly projecting connection pins 70b, 70b on both sides of the supported tube 70a (see FIGS. 36 and 37).

A support shaft 6h of the conversion lever 70, provided between the driving lever 67 on the lower surface of the major surface portion 6 and the limit lever 69, is inserted into the supported tube 70a, for rotation relative to the major surface portion 6, as shown in FIG. 11. The connection pins 70b, 70b are rotatably engaged in the connection opening 67c of the driving lever 67 and in the connection opening 69g of the limit lever 69. As a result, the

driving lever 67 and the limit lever 69 are moved in the opposite directions in the fore-and-aft direction.

The lower surface of the limit lever 69 rotatably carries an operating lever 71, as shown in FIGS. 11 and 38. The operating lever 71 is substantially L-shaped and has its one end formed as a rotation fulcrum point 71a, which rotation fulcrum point 71a is rotatably carried by the lever supporting portion 69b of the limit lever 69 (see FIGS. 38 and 39). The bent portion of the operating lever 71 is formed with a short arcuate guide opening 71b. The support shaft 69c of the limit lever 69 is inserted into the guide opening 71b. The operating lever 71 is rotatable relative the limit lever 69 within an extent of the guide opening 71b.

The operating lever 71 has its distal edge bent to form a curved mating operating edge 71c, and includes a linear controlled edge 71d and a linear thrust edge 71e on both opposite sides of the mating operating edge 71c.

A spring retention projection 71f is protruded from the rotation fulcrum point 71a of the operating lever 71. A tension spring 72 is mounted under tension between the spring retention projection 71f and the spring retention opening 69d of the limit lever 69. Thus, the operating lever 71 is biased counterclockwise in the plane of FIG. 11. Except if the force in the clockwise direction in FIG. 11 is accorded to the operating lever 71 in FIG. 11, the controlled edge 71d is contacted with the support piece 69e of the limit lever 69.

A driving motor 73 is mounted on the lower surface of the major surface portion 6 of the chassis 5, and drives a gear set 74, made up of four gears, carried on the lower surface of the major surface portion 6 (see FIG. 11). A switching gear 75 meshes with the fourth gear of the gear set 74 counted from the side of the driving motor 73 (see FIG. 11). An operating boss 75a is formed as one with the lower surface of the switching gear 75. Rotation of the switching gear 75 actuates the mating operating portion 66a of the rotation detection switch 66. When the mating operating portion 66a is actuated, rotation of the driving motor 73 ceases transiently.

A driving gear 76 meshes with the switching gear 75. The upper surface of the driving gear 76 is formed with a thrusting boss 76a (see FIG. 11). The thrusting boss 76a plays the role of a driving power transmission for transmitting the driving power of the driving motor 73 through the limit lever 69, conversion lever 70 and the driving lever 67 to the cam lever 24, as a portion of the head movement mechanism, and of transmitting the driving power of the driving motor 73 through the joint lever 47 to the slider 31 as a portion of the ejection mechanism. The driving gear 76 is mounted at such a position that the thrusting boss 76a is able to thrust the thrust piece 69f of the limit lever 69, the mating operating edge 71c of the operating lever 71 and the thrust edge 71e of the operating lever 71.

A spring plate member 77, which plays the role of retaining a shutter, as later explained, of the disc cartridge, is mounted between the major surface portion 6 of the chassis 5 and the circuit board 60 (see FIGS. 9 and 40). The spring plate member 77 has its one end 77a mounted on the major surface portion 6. The portion of the spring plate member towards the other end thereof is formed as an upwardly protruding retainer 77b, which retainer 77b is projected upwards through the retention unit mounting opening 6c (see FIG. 40). The upper end of the retainer 77b is positioned above the support portion 11b of the positioning pin 11 provided on the major surface portion 6 and the receptacle 12 (see FIG. 40).

The circuit board 60 carries a controller (micro-computer) including a central processing unit (CPU) 78 (see FIG. 41).

The controller 78 sends a control signal to each component based on a detection signal yielded on actuation of the disc detection switch 61 and the rotation detection switch 66. The controller 78 also sends a control signal to each component based on an operating signal yielded on actuation of any of the operating buttons 4 provided on the outer casing 2.

The driving motor 73 is run in rotation or halted based on a control signal sent from the controller 78 through a motor driver 79. The optical pickup 50 is driven or halted based on a control signal sent from the controller 78 through an optical pickup driver 80. The feed motor 56 and the spindle motor are also driven or halted based on the control signal input from the controller 78.

The disc cartridge 120 includes a flattened rectangular box-shaped casing 121, within which a magneto-optical disc 122 as a disc-shaped recording medium is rotationally mounted, as shown in FIG. 8. Centrally of the lower surface of the casing 121 is formed an insertion opening, not shown, and a through-hole, not shown, is formed laterally of the insertion opening. In the upper surface of the casing 121, there is formed, in register with the through-hole, a head access opening 121a, into which is inserted the magnetic head 58a. In the casing 121 is slidably mounted a shutter 123 for opening or closing the through-hole and the head access opening 121a. In the lateral surface of the casing 121 carrying the shutter 123 is formed a groove 121b extending in the fore-and-aft direction. In the lateral surface of the shutter 123 is formed an engagement opening 123a. The shutter is locked by a lock mechanism, not shown, provided in the casing 121, in a state in which the shutter has closed the through-hole and the head access opening 121a. In the lower surface of the casing 121 are formed positioning openings, not shown, separated from each other in the fore-and-aft direction.

The center portion of the disc-shaped recording medium 122 is formed with a center opening, on an opening edge of which is fitted a hub formed of a magnetic metal material.

The operation of the disc recording and/or reproducing apparatus 1 is hereinafter explained (see FIGS. 42 to 64).

First, the state prior to the loading of the disc cartridge 120 is explained (see FIGS. 42 to 46).

The ejection lever 39 is positioned at the end of the rotational stroke in the direction indicated by arrow R1 in FIG. 42. The controlled piece 33c of the slider 31 is contacted with the control edge 41a of the control projection 41, under the force of the spring member 45, for holding the slider 31 at a forward position (see FIG. 42). Thus, the support portions 18a, 19a and the support pins 18b, 19b of the holder 16 are engaged in the upper horizontal portions 37a, 38a of the cam grooves 37, 38 of the slider 31, and hence the holder 16 is held at an upper movement stroke end, that is at a position of inserting or ejecting the disc cartridge 120 (see FIG. 43).

The joint lever 47, carried by the side supporting portion 7, is held at the rear stroke end under the force of the tension coil spring 48, as shown in FIG. 7. The switching gear 75, carried by the lower surface of the major surface portion 6 of the chassis 5, is halted in contact with the mating operating portion 66a of the rotation detection switch 66, while the driving gear 76 is at a position in which the thrusting boss 76a abuts against or in proximity to the thrust piece 69f of the limit lever 69, that is at a reference position (see FIG. 38). The limit lever 69 is positioned at the rear stroke end, while the operating lever 71 supported by the limit lever 69 is in such a state in which the controlled edge 71d is kept in abutment against the support piece 69e of the

limit lever 69 (see FIG. 45). Since the limit lever 69 is at the rear stroke end, the driving lever 67, connected to the limit lever 69 through the conversion lever 70, is positioned at the forward stroke end (see FIG. 45).

Since the driving lever 67 is at the forward stroke end and the holder 16 is held at the insertion/ejection position, the cam lever 24 has the lower portion 30c of the cam leg 27 engaged in the engagement opening 67b of the driving lever 67 (see FIGS. 43 and 46). The cam lever 24 is positioned at the forward end of the movement stroke (see FIG. 42). Thus, the head shift lever 23 is kept at a first retreat position in which the mating operating piece 23b is engaged in the first cam 29a of the cam lever 24, the head mounting arm 58 is substantially at a horizontal position and the magnetic head 58a is not collided against the disc cartridge being introduced into the holder 16 (see FIG. 46).

When the disc cartridge 120 is inserted through the insertion/ejection opening 2a of the outer casing 2, the door 3 is rotated, and the disc cartridge 120 is inserted into the holder 16 (see FIG. 47). The operating portion 43 of the ejection lever 39 is thrust towards rear by the inserted disc cartridge 120, so that the ejection lever 39 is rotated in the direction indicated by arrow R2 in FIG. 47 against the force of the spring member 45.

As the disc cartridge 120 is inserted into the holder 16, the lateral side of the casing 121 is brought into sliding contact with the shutter restoration spring 21, provided on the side plate portion 19 of the holder 16, so that the shutter restoration spring 21 is flexed outwards. The unlock piece 22 then is moved forwards in the groove 121b of the disc cartridge 120 to unlock the shutter 123. The unlock piece then thrusts the edge of the shutter 123 to cause the sliding of the shutter 123. As the shutter 123 is slid, the holding portion 21a of the shutter restoration spring 21 is engaged in the engagement opening 123a of the shutter 123 to hold the disc cartridge 120 within the holder 16. As the shutter 123 is slid, the through-hole and the head access opening 121a formed in the casing member 121 are opened.

When the disc cartridge is inserted into the holder 16, the retention spring 17a provided to the top plate portion 17 of the holder 16 is brought into resilient contact with the casing member 121 of the disc cartridge 120 to hold the casing member 121.

When the ejection lever 39 is rotated in the direction indicated by arrow R2 in FIG. 48 and the control edge 41a is disengaged from the controlled piece 33c of the slider 31, the slider 31 is moved rearwards under the force of the spring member 45. Since the slider 31 is also pulled rearwards by the auxiliary spring 46, mounted under tension between the spring retention projection 33a and the spring retention piece 14b of the side supporting portion 7 of the chassis 5, the slider 31 is positively moved to the rear movement stroke end.

When the slider 31 is moved rearwards, the roll 44 supported by the ejection lever 39 rolls on the inclined edge 33d, so that the slider 31 is smoothly moved rearwards as shown in FIG. 48.

Although the auxiliary spring 46 is used in the disc recording and/or reproducing apparatus 1 of the present invention, such auxiliary spring 46 may be dispensed with subject to proper adjustment of the force of the spring member 45. As a consequence, only the spring member 45 suffices, and hence the number of components may be reduced.

With the disc recording and/or reproducing apparatus 1 of the present invention, the length of the extended spring

member 45 is progressively shortened as the slider 31 is moved rearwards, as described above. Thus, the slider 31 and the ejection lever 39 may be improved in durability, and hence the load on the driving motor 73 in ejecting the disc cartridge 120, as later explained is relieved to lower the power consumption in an amount corresponding to the diminished frictional resistance of the slider 31 and the ejection lever 39. In addition, the spring force of the spring member 45 may be reduced due to reduction in the load.

As the slider is moved rearwards, the support portions 18a, 19a and the support pins 18b, 19b of the holder 16 perform relative movement from the upper horizontal sections 37a, 38a of the cam grooves 37, 38 and the inclined sections 37b, 38b to the lower horizontal sections 37c, 38c (see FIG. 49). Thus, the holder 16 is moved to the lower end of the movement stroke, as it is guided by the guide grooves 15a, 15a formed in the side supporting portions 7, 8, until the holder gets to the loading position in contact with the major surface portion 6 of the chassis 5. When the holder 16 is moved downwards, the cam lever 24 is also moved downwards, with movement of the holder 16. The cam lever 24, the lower portion 30c of the cam leg 27 of which has been engaged in the engagement groove 67b of the driving lever 67, is moved through the inclined section 30b (see FIG. 50) until the upper side section 30a is engaged in the engagement groove 67b, with the cam lever 24 being moved slightly rearwards relative to the holder 16 (see FIGS. 41 to 44). The result is that the head shift lever 23 has its mating operating piece 23b engaged in the second cam portion 29b of the cam lever 24, so that the head shift lever is raised in its forward portion (see FIG. 51). Since the holder 16 has been lowered, the head mounting arm 58 has its forward portion lowered. However, the head shift lever 23 has its forward portion elevated, and hence the magnetic head 58a is kept at the second retreat position directly overlying the top plate portion 17 of the holder 16 and is not introduced into the head inserting opening 17b. In terms of the relative position of the holder 16 relative to the top plate portion 17, this second retreat position is substantially the same as the aforementioned first retreat position.

When the holder 16 gets to the loading position corresponding to the lower end of its movement stroke, the disc table 49 is inserted via an insertion opening of the casing member 121 of the disc cartridge 120, held by the holder 16, so that the centering boss 49a of the disc table 49 is introduced into the center opening of the disc-shaped recording medium 122, while the hub of the disc-shaped recording medium 122 is sucked by a magnet provided on the centering boss 49a, whereby the disc-shaped recording medium 122 is loaded on the disc table 49.

When the holder 16 is moved downwards, the operating shafts 64, 64, 64 of the disc detection switches 61, 61, 61 are thrust and actuated by the casing member 101 of the disc cartridge 120 for use for write protect detection, AD/MD-DATA2 (trademark) detection and disc reflectance detection, that is for detection whether the disc is a ROM (optical disc carrying information signals as pits) or a RAM (magneto-optical disc). A loading detection switch for detecting whether the disc-shaped recording medium 122 has been loaded on the disc table 49 is provided as a separate unit, even though such loading detection switch is not shown. Alternatively, the disc detection switch 61 may be used to detect that the disc-shaped recording medium 122 has been loaded on the disc table 49.

When the disc-shaped recording medium 122 has been loaded on the disc table 49, the inner edge of the disc-shaped recording medium 122 is set on the table portion 49b, while

the disc-shaped recording medium 122 is positioned at a location slightly above the inner lower surface of the casing member 121.

When the disc-shaped recording medium 122 has been loaded on the disc table 49, the positioning projections 11a, 11a of the positioning pins 11, 11 provided on the major surface portion 6 of the chassis 5 are introduced into the positioning openings of the casing member 121 for positioning the disc cartridge 120 relative to the chassis 5. When the disc cartridge 100 has been positioned relative to the chassis 5, the casing member 121 is set on the support portion 11a of the positioning pin 11 and on the receptacle 12 (see FIG. 52). The retainer 77b of the spring plate member 77, mounted on the lower surface of the major surface portion 6, is brought into resilient contact with the shutter 123 of the disc cartridge 120 at this time from the lower side (see FIG. 52). Consequently, the vibrations of the shutter 123 during the reproduction and recording of the disc-shaped recording medium 122 can be suppressed to assure optimum reproducing and recording operations.

Since the spring plate member 77 for suppressing the vibrations of the shutter 123 is mounted on the chassis 5 arranged within the outer casing 2, the vibrations otherwise transmitted from outside to the disc recording and/or reproducing apparatus 1 can scarcely be transmitted through the spring plate member 77 to the shutter 123 to suppress the vibrations efficiently and sufficiently.

Moreover, since the spring plate member 77, having its one end 77a mounted on the major surface portion 6 of the chassis 5, is used as retention means for holding the shutter 123 to suppress its vibrations, the vibrations to the shutter 123 may be effectively prohibited by a simplified structure, such that provision of retention means does not raise the cost.

In the foregoing description, the spring plate member 77 is used as retention means. Alternatively, the disc detection switch 61 may also be used as retention means in place of the spring plate member 77 (see FIG. 53). In this case, the disc detection switch 61 is arranged on the circuit board 60 at such a position that the mating operating shaft 64 is projected upwards from the retention unit mounting opening 6c formed in the major surface portion 6, in place of arranging the disc detection switch 61 provided at the left end of the circuit board 60.

When the holder 16 is lowered, the mating operating shaft 64 is brought into resilient abutting contact from below against the shutter 123 of the disc cartridge 120, under the spring force of the compression coil spring 65, to suppress the vibrations of the shutter 123. At the same time, the loading of the disc-shaped recording medium 22 on the disc table 49 is detected by the operation on the mating operating shaft 64. Thus, if the disc detection switch 61 is used as retention means, suppression of vibrations of the shutter 123 and the above detection can be achieved simultaneously, so that there is no necessity of providing dedicated retention means in addition to the disc detection switch 61, thus achieving reduction in the number of component parts and in cost.

As the retention means, the spring plate member 77 and the disc detection switch 61 may be used in combination.

If, when the holder 16 carrying the disc cartridge 120 is lowered and the disc-shaped recording medium 122 has been loaded on the disc table 49, a replay button (operating button) 4, provided on the outer casing 2, is actuated, the disc table 49 and hence the disc-shaped recording medium 122 are run in rotation by the driving of the spindle motor,

while the optical pickup **50** is guided by the guide shafts **53**, **54** by the driving of the feed motor **56** and hence is moved radially of the disc-shaped recording medium **122**. At this time, a laser light beam is illuminated from the objective lens **52a** of the biaxial actuator **52** of the optical pickup **50** through the through-hole of the casing member **121** to the disc-shaped recording medium **122** to reproduce information signals.

If a stop button (operating button) **4** is actuated, the rotation of the disc table **49** is halted, while the optical pickup **50** ceases to be operated to stop the reproduction of the information signals.

If, as the holder **16** carrying the disc cartridge **120** is lowered so that the disc-shaped recording medium **122** is loaded on the disc table **49**, a recording button (operating button) **4** provided on the outer casing **2** is actuated, so that the driving motor **73** and hence the gear set **74** are run in rotation in one direction. When the gear set **74** is run in rotation, the switching gear **75** is run in rotation, so that the driving gear **76** meshing with the switching gear is run in rotation in one direction, with the consequence that the thrusting boss **76a** of the **g76** thrusts the thrust edge **71e** of the operating lever **71** forwards (see FIG. **54**).

When the thrust edge **71e** of the operating lever **71** is thrust, since the controlled edge **71d** is contacted with the support piece **69e** of the limit lever **69**, positioned at the rear end of the movement stroke, the support piece **69e** is thrust forwards by the controlled edge **71d** to cause forward movement of the limit lever **69** (see FIG. **54**). When the limit lever **69** is moved forwards, the driving lever **67**, positioned at the forward end of the movement stroke, is moved rearwards by the rotational movement of the conversion lever **70** (see FIG. **54**). By the rearward movement of the driving lever **67**, the cam lever **24**, the upper side portion **30a** of which is engaged in the engagement opening **67b**, is moved towards rear with respect to the holder **16** (see FIG. **55**).

The limit lever **69**, moved forwards, is moved to the forward end of its movement stroke, as a result of the contact of the support piece **69e** with the stop edge **6g** formed on the major surface portion **6**. At this time, the rotation of the driving motor **73** ceases, so that the driving lever **67** is halted at the rear end of its movement stroke (see FIG. **54**). When the driving lever **67** is halted at the rear end of its movement stroke, the cam portion **30** of the cam lever **24** has been moved to a point at back of the mating operating piece **23b** of the head shift lever **23**, such that the head shift lever **23** is held at the lower end of its rotational movement, with the controlling piece **23a** in contact with the opening edge of the head inserting opening **17b** of the holder **16**. Consequently, the head mounting arm **58** is inclined so that its forward end is lowered (see FIG. **55**). The magnetic head **58a** is introduced into the holder **16** through the head inserting opening **17b** into contact with the disc-shaped recording medium **122** through the head access opening **121a** formed in the casing member **121** of the disc cartridge **120**. One of the rotation controlling pieces **23a** of the head shift lever **23** is positioned below the retention piece **28** of the cam lever **24** and is retained by the retention piece **28**.

With continued driving of the spindle motor, the disc table **49** is run in rotation, while the optical pickup **50** is guided by the guide shafts **53**, **54**, by the driving of the feed motor **56**, so as to be moved radially of the disc-shaped recording medium **102**. At this time, a laser light beam is illuminated from the objective lens **52a** of the biaxial actuator **52** of the optical pickup **50** through the through-hole of the casing

member **121** to the disc-shaped recording medium **122**, at the same time as a magnetic field is applied through the magnetic head **58a** to the disc-shaped recording medium **122**, to record information signals.

If a stop button (operating button) **4**, among the operating buttons **4**, is actuated, the driving motor **73** is rotated in an opposite direction to that in the previous operation to run the gear set **74** and the switching gear **75** into rotation. The driving gear **76** is run in rotation in a second direction so that the thrust piece **69f** of the limit lever **69** is thrust rearwards by the thrusting boss **76a** of the driving gear **76** (see FIG. **56**). When the thrust piece **69f** of the limit lever **69** is thrust, the limit lever **69** and the operating lever **71** are moved rearwards in unison, while the driving lever **67**, located at the rear end of the movement stroke, is moved forwards by the rotational movement of the conversion lever **70** (see FIG. **56**). By the forward movement of the driving lever **67**, the cam lever **24**, the upper side portion **30a** of which is engaged in the engagement opening **67b**, is moved forwards relative to the holder **16**.

When the mating operating portion **66a** of the rotation detection switch **66** is actuated by the operating boss **75a** of the switching gear **75**, a stop signal is input to the driving motor **73**, so that the operation of the driving motor **73** ceases. The limit lever **69** is halted when it has been moved to the rear end of the movement stroke, while the driving lever **67** is halted at the forward end of its movement stroke (see FIG. **56**). The driving gear **76** is reverted to its reference position.

When the driving lever **67** is halted at the forward movement stroke end, the mating operating piece **23b** of the head shift lever **23** is engaged with the second cam portion **29b** of the cam lever **24**, the magnetic head **58a** is moved upwards from the head inserting opening **17b** of the holder **16**, and the magnetic head **58a** is kept at the second retreat position directly overlying the top plate portion **17** of the holder **16** (see FIG. **50**). Simultaneously, the rotation of the disc table **49** is halted to terminate the operation of recording the information signals.

When the stop button (operating button) **4** is operated to terminate the reproducing or recording operation, as described above, the driving lever **67** is positioned at the forward movement stroke end, while the limit lever **69** is located at the rear movement stroke end (see FIG. **56**) and the joint lever **47** is at the rear movement stroke end (see FIG. **57**).

If, when the reproducing or recording operation is finished, the ejection button, as one of the operating buttons **4**, is actuated, the driving motor **73** is rotated in the opposite direction. When the driving motor **73** is rotated in the opposite direction, the driving gear **76** is rotated in the second direction, and the mating operating piece **47b** of the joint lever **47** is thrust forwards, with the joint lever **47** being then moved forwards against the bias of the tension coil spring **48** (see FIG. **58**).

When the joint lever **47** is moved forwards, the thrust piece **35c** of the slider **31** is thrust forwards by a thrusting piece **47c**, with the slider **31** being moved forwards (see FIG. **59**). When the slider **31** is moved forwards, the support portions **18a**, **19a** and the support pins **18b**, **19b** of the holder **16** perform relative movement from the lower horizontal portions **37c**, **38c** of the cam grooves **37**, **38** through the inclined portions **37b**, **38b** to the upper horizontal portions **37a**, **38a** (see FIG. **43**). Consequently, since the support pins **18b**, **19b** of the holder **16** guided by the guide groove **15a** formed in the side supporting portions **7**, **8** of the chassis **5**

are elevated, while the disc cartridge **120** held by the holder **16** is elevated along with the holder **16**, the disc-shaped recording medium **122** is unloaded from the disc table **49**.

When the holder **16** is elevated with the forward movement of the slider **31**, the cam lever **24**, the upper side portion **30a** of which has been engaged in the engagement opening **67b** of the of the driving lever **67**, has the lower side portion **30c** engaged in the engagement opening **67b**. The cam lever **24** is moved forwards relative to the holder **16** a distance equal to the distance between the upper side portion **30a** and the lower side portion **30c** in the fore-and-aft direction. Consequently, the head shift lever **23** has the mating operating piece **23b** engaged in the first cam portion **29a** of the cam lever **24**, with the head mounting arm **58** being substantially in the horizontal position (see FIG. **46**). With forward movement of the slider **31**, the spring member **45** is extended to increase the biasing force of the ejection lever **39** in the direction indicated by arrow **R1** in FIG. **46**. When the ejection lever **39** is rotated clockwise, as the roll **44** rolls on the inclined edge **33d** of the slider **31**, and the control edge **41a** is spaced apart from the controlled piece **33c**, the ejection lever **39** is rotated significantly clockwise under the force of the spring member **45**, such that the ejection lever **39** is rotated in the direction indicated by arrow **R1** in FIG. **60** until the insertion piece **42b** is brought into contact with the forward opening edge of the control opening **10c** of the lever supporting portion **9** provided to the chassis **5**. At this time, the holder **16** has been rotated to the insertion/ejection position. When the ejection lever **39** is rotated in the direction indicated by arrow **R1** in FIG. **60**, the casing member **21** of the disc cartridge **120** is thrust forwards by the operating portion **43**, so that a portion of the disc cartridge **100** is ejected from the holder **16**.

When the disc cartridge **120** is ejected from the holder **16**, the holder **21a** of the shutter restoration spring **21** is engaged in the engagement opening **123a** of the shutter **123**, so that the shutter **123** is slid to stop up the through-hole and the head access opening **121a** formed in the casing member **121**. The through-hole and the head access opening **121a** are closed.

The driving gear **76** continues to be rotated and the thrusting boss **76a** is disengaged from the mating operating piece **47b** of the joint lever **47** into engagement with the mating operating edge **71c** of the operating lever **71** (see FIG. **61**). Since the mating operating piece **47b** of the joint lever **47** is disengaged from the thrusting boss **76a**, the joint lever **47** is moved to the rear movement stroke end under the bias of the tension coil spring **48** (see FIG. **62**).

When the thrusting boss **76a** of the driving gear **76** is engaged with the operated edge **71c** of the operating lever **71**, the operating lever **71** is rotated, with rotation of the driving gear **76**, against the bias of the tension spring **72**, such that the thrusting boss **76a** is brought into sliding contact with the mating operating edge **71c** (see FIG. **61**).

As the driving gear **76** further continues its rotation, the thrusting boss **76a** is disengaged from the mating operating edge **71c** of the operating lever **71**. The operating lever **71** is rotated under the bias of the tension spring **72** to return to a state in which the controlled edge **71d** is contacted with the support piece **69e** of the limit lever **69** (see FIG. **63**). The switching gear **75** is also run in rotation by rotation of the driving motor **73**. When the operating boss **75a** acts on the mating operating portion **66a** of the rotation detection switch **66**, a stop signal is input to the driving motor **73** to stop the rotation of the driving motor **73** (see FIG. **63**). The driving gear **76** is returned to its reference position.

The disc cartridge **120**, ejected from the holder **16**, is partially protruded via the insertion/ejection opening **2a** of the outer casing **2**. The protruded portion may be gripped and extracted to take out the disc cartridge **120**.

When taking out the disc cartridge **120**, the unlock piece **22** provided on the side plate portion **19** of the holder **16** is moved rearwards in the groove **101b** of the disc cartridge **120** by relative movement. The shutter **123** is again locked by a lock mechanism.

With the disc recording and/or reproducing apparatus **1** of the present invention, described above, the driving gear **76**, run in rotation by the driving power transmitted from the driving motor **73**, is rotated in the first direction to lower the magnetic head **58a** to set up a state enabling the recording operation of information signals. The driving gear **76** is run in rotation in the second direction opposite to the first direction to perform the ejecting operation of the disc cartridge **120**. Thus, when both the head movement mechanism and the ejection mechanism are operated by the driving motor **73**, there is no necessity of continuously moving one of the driving lever **67** and the joint lever **47** in the same direction to actuate the head movement mechanism and the ejection mechanism, the movement stroke of the driving lever **67** and that of the joint lever **47** may be correspondingly reduced to enable the size of the disc recording and/or reproducing apparatus to be reduced.

The disc recording and/or reproducing apparatus **1** of the present invention is provided with the operating lever **71** which operates the limit lever **69**, using the thrusting boss **76a** operating as the driving power transmitting portion, when the driving motor **73** is rotated in one direction, and which is receded from the trajectory of the thrusting boss **76a** when the driving motor **73** is rotated in the other direction. Consequently, the operating lever **71** does not obstruct rotation of the driving gear **76** when the driving motor **73** is rotated in the opposite direction to actuate the ejection mechanism, so that the operation of the disc recording and/or reproducing apparatus **1** may be optimum.

In addition, with the disc recording and/or reproducing apparatus **1**, since there is provided the rotation detection switch **66** which detects the end of the operation of the ejection mechanism and the end of the operation of the head movement mechanism, it is unnecessary to provide a dedicated switch detecting the state of completion of the operation, from one mechanism to another, thus enabling the number of component parts to be reduced.

The manual ejection operation for the disc cartridge **120** is now explained. The manual ejection operation in the disc recording and/or reproducing apparatus **1** may be classed into an ejection operation in the stop mode in which the recording or reproduction for the disc-shaped recording medium **122** has come to a close, an ejection operation in the replay mode and an ejection operation in the recording mode. It is when for example the driving motor **73** has ceased its operation due to battery down that the manual ejection operation is needed.

In the operation in any of these three modes, the joint lever **47** is moved forwards by manual operation to eject the disc cartridge **120**. The forward movement of the joint lever **47** may be achieved by for example inserting a pin into an insertion opening, not shown, formed in the back side of the outer casing **2**, to thrust the thrusting portion **47e** from rear side.

First, the operation of the manual ejection operation in the stop and replay modes and the ejecting operation during reproduction for the disc-shaped recording medium **122** are

explained. These two operations are accomplished by moving the joint lever 47 forwards as the mating operating piece 23b of the head shift lever 23 is engaged in the second cam portion 29b of the cam lever 24, as shown in FIG. 44.

When the joint lever 47 is moved forwards, the thrust piece 35c of the slider 31 is thrust forwards by the thrusting piece 47c, such that the support portions 18a, 19a and the support pins 18b, 19b of the holder 16 perform relative movement from the lower horizontal portions 37c, 38c of the cam grooves 37, 38 through the inclined portions 37b, 38b to the upper horizontal portions 37a, 38a (see FIG. 43). Consequently, the holder 16 is elevated to unload the disc-shaped recording medium 122 from the disc table 49.

When the holder 16 is elevated, the lower side portion 30c of the cam lever 24 is engaged in the engagement opening 67b, such that the cam lever 24 is moved forwards relative to the holder 16 by a distance corresponding to the distance between the upper side portion 30a and the lower side portion 30c in the fore-and-aft direction. Thus, the head shift lever 23, the mating operating piece 23b of which has been engaged in the second cam portion 29b of the cam lever 24, now has the mating operating piece 23b engaged in the first cam portion 29a of the cam lever 24, with the head mounting arm 58 then being in substantially the horizontal position (see FIG. 46).

As the slider 31 is moved forwards, the spring member 45 is extended. When the control edge 41a is separated from the controlled piece 33c, the ejection lever 39 is rotated appreciably in the direction indicated by arrow R1, under the force of the spring member 45. The casing member 121 of the disc cartridge 100 is thrust forwards significantly by the operating portion 43 to eject the disc cartridge 120 from the holder 16 (see FIG. 60).

The disc cartridge 120, ejected from the holder 16, is partially protruded via the insertion/ejection opening 2a of the outer casing 2. The protruded portion may be gripped and extracted to take out the disc cartridge 120.

The operation of manual ejection in the recording mode is now explained. This operation is carried out by causing forward movement of the joint lever 47, as the mating operating piece 23b of the head shift lever 23 is located ahead of the cam portion 30 of the cam lever 24, as shown in FIG. 55. When the joint lever 47 is moved forwards, the thrust piece 35c of the slider 31 is thrust forwards, by the thrusting piece 47c, so that the support portions 18a, 19a and the support pins 18b, 19b of the holder 16 perform relative movement from the lower horizontal portions 37c, 38c of the cam grooves 37, 38 through the inclined portions 37b, 38b to the upper horizontal portions 37a, 38a (see FIG. 43). Consequently, the holder 16 is elevated to unload the disc-shaped recording medium 122 from the disc table 49.

When the holder 16 is elevated, the lower side portion 30c of the cam lever 24 is engaged in the engagement opening 67b, such that the cam lever 24 is moved forwards relative to the holder 16 by a distance corresponding to the distance between the upper side portion 30a and the lower side portion 30c in the fore-and-aft direction. Thus, the head shift lever 23, the mating operating piece 23b of which has been engaged in the second cam portion 29b of the cam lever 24, now has the mating operating piece 23b engaged in the third cam portion 29c of the cam lever 24, with the head mounting arm 58 then being in substantially the horizontal state (see FIG. 64). As the head mounting arm 58 is at substantially the horizontal position, the magnetic head 58a is uplifted from the head inserting opening 17b of the holder 16. The magnetic head 58a is moved upwards from the head insert-

ing opening 17b of the holder 16 and is held at a third retreat position directly overlying the top plate portion 17 of the holder 16. The disc cartridge 120 may now be ejectable without contacting with the magnetic head 58a (see FIG. 64). This third retreat position, as the relative position of the holder 16 with respect to the top plate portion 17, is substantially the same as the first and second retreat positions described above. With forward movement of the slider 31, the spring member 45 is extended. When the control edge 41a is separated from the controlled piece 33c, the ejection lever 39 is rotated appreciably in the direction indicated by arrow R1, under the spring force of the spring member 45. The casing member 121 of the disc cartridge 120 is thrust forwards by the operating portion 43 to eject the disc cartridge 120 from the holder 16 (see FIG. 60). The disc cartridge 120 ejected from the holder 16 is partially protruded from the insertion/ejection opening 2a of the outer casing 2, so that the disc cartridge 120 can be taken out by gripping and pulling the protruded portion outwards.

Thus, in the recording mode, the cam lever 24 is moved forwards to retreat the magnetic head 58a to above the disc cartridge 120 being ejected and to hold the magnetic head 58a at the third retreat position to achieve the ejecting operation without damaging the magnetic head 58a.

With the disc recording and/or reproducing apparatus 1, according to the present invention, the magnetic head 58a is held at the first, second or third retreat position, for which the position relationships of the holder to the top plate portion 17 are substantially the same, except during the recording operation, when the disc cartridge 120 is held on the holder 16. Consequently, the spacing of movement of the magnetic head 58a between the upper surface of the outer casing 2 and the top plate portion 17 can be minimized to allow to reduce the thickness of the disc recording and/or reproducing apparatus 1.

Moreover, with the disc recording and/or reproducing apparatus 1, according to the present invention, the cam lever 24 is provided with the inclined portion 30b slidably engaged in the engagement opening 67b of the driving lever 67 and, when the cam lever 24 is uplifted or lowered with the uplifting or descent of the holder 16, the engaging position of the inclined portion 30b in the engagement opening 67b is changed to cause the cam lever 24 to be moved in the fore-and-aft direction with respect to the holder 16. Thus, it is sufficient to provide the inclined portion 30b for causing movement of the cam lever 24 relative to the holder 16 to simplify the structure or mechanism for ejection to realize positive ejection without increasing the cost.

In the disc recording and/or reproducing apparatus 1 according to the present invention, the recording head used is the magnetic head 58a. This, however, is merely illustrative, and any of recording heads consistent with the recording system for a recording medium, such as an optical head or a magneto-optical disc, may be used as the recording head.

The shape or structure of the various components, indicated in the above-described embodiments, are given only by way of examples in practicing the invention, and should not be construed in the sense of limiting the present invention.

INDUSTRIAL APPLICABILITY

With the disc recording and/or reproducing apparatus according to the present invention, in which the spring member is provided between the ejection lever and the slider and the ejection lever is biased by this spring member in a

direction of ejecting the recording medium from the holder, and in which the slider is also biased in the direction of introducing the recording medium, the mechanism of ejecting the recording medium may be simplified to reduce the number of component parts of the overall apparatus.

Moreover, with the disc recording and/or reproducing apparatus according to the present invention, in which the relative positions of the head, contacted with and separated away from the recording medium, and the holder, with respect to the contacting or separating direction, is substantially constant for the first retreat position receded from the recording medium held by the holder, the second retreat position receded from the recording medium during reproduction of the information signals and for the third retreat position receded from the recording medium being ejected from the holder, the spacing of movement of the magnetic head between the outer casing and the holder may be minimized to reduce the thickness of the overall apparatus.

In addition, with the disc recording and/or reproducing apparatus according to the present invention, in which the ejection mechanism or the head movement mechanism is operated depending on the direction of rotation of the driving gear, rotated in one or the opposite direction by the driving motor, the ejection mechanism and the head movement mechanism can be simplified to reduce the size of the apparatus.

Furthermore, with the disc recording and/or reproducing apparatus according to the present invention, in which, when the disc housed in the disc cartridge is loaded on the disc table, the shutter provided on the disc cartridge opened by the shutter opening/closing mechanism is retained by the retention mechanism, the shutter may undergo vibrations during the disc reproducing or recording operation only to a lesser extent for assuring stabilized recording and/or reproduction of information signals.

What is claimed is:

1. A recording medium driving device comprising:

a loading unit for having a recording medium loaded thereon;

a chassis:

a holder movably carried by said chassis, said holder holding said recording medium and transporting said recording medium between an insertion/ejection position of inserting or ejecting said recording medium and a loading position of loading said recording medium on said loading unit;

an ejection lever for ejecting said recording medium from said holder;

a slider movable in a direction of inserting said recording medium into said holder and in a direction of ejecting said recording medium from said holder, said slider when moved in said inserting direction causing said holder to be moved to said loading position, and said slider when moved in said ejecting direction causing said holder to be moved to said insertion/ejection position; and

a spring member provided between said ejection lever and said slider for biasing said ejection lever in a direction of ejecting said slider from said holder and for biasing said slider in said inserting direction.

2. The recording medium driving device according to claim 1 further comprising:

an auxiliary spring provided between said chassis and said slider for biasing said slider in said inserting direction.

3. The recording medium driving device according to claim 1 wherein said ejection lever is rotatably mounted at a corner of said chassis and includes at one end an operating portion for ejecting said recording medium from said holder, said ejection lever also including at an other end a control portion for controlling said slider towards said ejecting direction; wherein, when said recording medium is not loaded on said recording medium driving device, said slider is arranged in said ejecting direction and said operating portion of said ejection lever is biased and rotated in said ejecting direction, said controlling portion engaging with a controlled portion of said slider to control said slider in said ejecting direction.

4. The recording medium driving device according to claim 3 wherein, when said recording medium is introduced into said holder, said operating portion of said ejection lever thrusts a forward end of said recording medium being inserted so that said operating portion is rotated in said inserting direction; said controlling portion being rotated with said rotation to be disengaged from said controlled portion so that said slider is moved in said inserting direction under the bias of said spring member, said slider having a portion thereof engaged with a portion of said other end of said ejection lever to hold said ejection lever at said inserting direction;

said holder being moved to said loading position with movement of said slider in said inserting direction for loading said recording medium inserted in said holder to said loading position.

5. The recording medium driving device according to claim 4 further comprising:

ejection controlling means for causing said slider to be moved in said ejecting direction responsive to a user's command;

said slider being moved in said ejecting direction under control by said ejection controlling means to cause said holder to be moved to said insertion/ejection position and to extend said spring member;

said operating portion of said ejection lever being moved in said ejecting direction to eject said recording medium by a portion of said slider being disengaged from a portion of the opposite end of said ejection lever with movement of said slider;

said controlling portion of said ejection lever being re-engaged with said controlled portion of said slider to control said slider at said ejecting direction.