



US006944280B2

(12) **United States Patent**  
**Suzuki**

(10) **Patent No.:** **US 6,944,280 B2**  
(45) **Date of Patent:** **Sep. 13, 2005**

(54) **GATEWAY SYSTEM HAVING A REDUNDANT STRUCTURE OF MEDIA GATEWAY CONTROLLERS**

(75) Inventor: **Yuuji Suzuki**, Tokyo (JP)

(73) Assignee: **NEC Corporation**, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 396 days.

(21) Appl. No.: **09/945,753**

(22) Filed: **Sep. 5, 2001**

(65) **Prior Publication Data**

US 2002/0027983 A1 Mar. 7, 2002

(30) **Foreign Application Priority Data**

Sep. 6, 2000 (JP) ..... 2000-269459

(51) **Int. Cl.<sup>7</sup>** ..... **H04M 7/00**

(52) **U.S. Cl.** ..... **379/229; 379/230; 379/219**

(58) **Field of Search** ..... 379/210, 211, 379/215, 114, 118, 83.12, 88.17, 88.14, 88.2, 88.26, 229, 230, 219, 220.01, 221.01, 221.08

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,693,897 B1 \* 2/2004 Huang ..... 370/352  
2001/0036173 A1 \* 11/2001 Shmulevich et al. .... 370/352  
2001/0049730 A1 \* 12/2001 Brendes et al. .... 709/223  
2001/0055380 A1 \* 12/2001 Benedyk et al. .... 379/219

**FOREIGN PATENT DOCUMENTS**

GB 2354904 A 4/2001  
GB 2 469 000 A 5/2002  
JP 62-210563 9/1987  
WO WO 00/065785 A1 11/2000  
WO WO 01/49045 A2 7/2001

**OTHER PUBLICATIONS**

Masaaki Yoneda, "How Do Telephones Get Connected? How Does This Relate to IP Telephone Services?", Aug. 7, 2000, No. 323, pp. 100-105.

Yukiteru Nagatake et al., "Investigation Into High-Level IN and IP Network Connection Methods-Rules for Controller Services With Voice Over IP," Jun. 22, 2000, vol. 100, No. 153, pp. 1-6.

M. Arango et al., "Media Gateway Control Protocol (MGCP) Version 1.0", Oct. 1999.

\* cited by examiner


*Primary Examiner*—William J. Deane, Jr.

(74) *Attorney, Agent, or Firm*—Foley & Lardner LLP

(57) **ABSTRACT**

In a gateway system for connecting a telephone network utilizing a common channel signaling system No. 7 to an IP (Internet Protocol) network, the gateway system includes a media gateway and a media gateway controller group including a plurality of media gateway controllers which are assigned a common point code. Any one of the media gateway controllers is for terminating a No. 7 signal representative of a control signal of the common channel signaling system No. 7 in the telephone network and for carrying out call control and connection control to the IP network by controlling the media gateway through the IP network so that a communication path is established between the telephone network and the media gateway. Each of the media gateway controllers comprises a No. 7 signal processing portion for terminating the No. 7 signal and a call processing control portion for carrying out the call control and the connection control to the IP network by controlling the media gateway through the IP network so that the communication path is established between the telephone network and the media gateway. The No. 7 signal processing portion and the call processing control portion have a M3UA (SS7 (Signaling System No. 7) MTP3-User Adaptation Layer) function.

**8 Claims, 4 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4

## GATEWAY SYSTEM HAVING A REDUNDANT STRUCTURE OF MEDIA GATEWAY CONTROLLERS

### BACKGROUND OF THE INVENTION

This invention relates to a gateway system for connecting an existing telephone network utilizing a common channel signaling system to an IP (Internet Protocol) network.

In channel (or circuit) control for an existing telephone network utilizing a common channel signaling system, high reliability against occurrence of failure is required. In order to satisfy such a requirement, use is made of a technique in which signal transfer points or signal paths are switched so that signal processing is not interrupted even upon an occurrence of a failure. It is noted here that the common channel signaling system is a system in which a signal channel is provided in addition to a plurality of communication channels so that control signals for the communication channels are transmitted and received by the signal channel as a single data channel exclusively for the control signals. For example, a common channel signaling system No. 7 (SS7) is used in a carrier network.

On the other hand, development has been made of a gateway system for connecting the existing telephone network and an IP (Internet Protocol) network. The gateway system generally includes a plurality of media gateways. By the use of such a gateway system, various services on the IP network become available through the existing telephone network.

The above-mentioned gateway system further includes a media gateway controller (MGC) which terminates a No. 7 signal as a control signal of the common channel signaling system No. 7. The media gateway controller (MGC) controls a corresponding media gateway through the IP network to make the corresponding media gateway establish a communication path between the existing telephone network and the corresponding media gateway.

The above-mentioned media gateway controller (MGC) controls a plurality of media gateways. The media gateway controller serves as a node for carrying out call control and connection control and is therefore required to have a high reliability. On the other hand, upon occurrence of a failure, it is not possible to straightforwardly use a technique of switching the media gateway controller as a faulty node to another node as a new node.

This is because a particular communication channel between an exchange and the media gateway is identified by a destination point code (DPC) and a circuit (or channel) identification code (CIC). Therefore, the new node having a different point code (PC) can not identify the particular communication channel. Thus, the new node does not have a call status of the particular communication channel.

Upon occurrence of a failure in the media gateway controller itself or in a No. 7 network link or the IP network connected to the media gateway controller, call control for all channels controlled by the media gateway controller will be lost.

### SUMMARY OF THE INVENTION

It is therefore an object of this invention to provide a gateway system capable of assuring a high reliability without causing system down time even upon an occurrence of a failure.

Other objects will become clear as the description proceeds.

According to this invention, there is provided a gateway system for connecting a telephone network utilizing a common channel signaling system No. 7 to an IP (Internet Protocol) network. The gateway system includes a media gateway and a media gateway controller group comprising a plurality of media gateway controllers which are assigned with a common point code. Any one of the media gateway controllers is capable of terminating a No. 7 signal representative of a control signal of the common channel signaling system No. 7 in the telephone network. Each of the media gateway controllers is capable of carrying out call control and connection control to the IP network by controlling the media gateway through the IP network so that a communication path is established between the telephone network and the media gateway.

### BRIEF DESCRIPTION OF THE DRAWING

FIG. 1 is a block diagram of a gateway system according to one embodiment of this invention;

FIG. 2 is a functional block diagram of media gateway controllers belonging to a media gateway controller group illustrated in FIG. 1;

FIG. 3 is a sequence chart for describing an operation of the gateway system illustrated in FIG. 1; and

FIG. 4 is a sequence chart for describing the operation of the gateway system illustrated in FIG. 1 upon occurrence of a failure.

### DESCRIPTION OF THE PREFERRED EMBODIMENT

Before detailed description will be made of one embodiment of this invention with reference to the drawing, a gateway system of this invention will briefly be described for a better understanding of this invention.

A gateway system of this invention enables various services on an IP network to be provided through an existing telephone network. For example, a dial-up service using a remote access server (RAS) is known as one of such services. By realizing a redundant node structure of media gateway controllers (MGC) which serve as nodes for terminating a No. 7 signal as a control signal of a common channel signaling system No. 7 in the telephone network and for carrying out call control and connection control on the side of the IP network, the gateway system is capable of assuring high reliability without causing system down time even upon an occurrence of a failure in the media gateway controller or a signal link connected thereto.

In order to assure high reliability, the existing telephone network adopts a structure such that, in case of an occurrence of a failure in a signal transfer point (STP) as a faulty point or in a signal link as a faulty link, a signal path is switched to transfer the signal through another signal transfer point or through another signal link. Thus, the system is continuously operable without causing system down time.

Recently, development is made of the gateway system as a new system for providing various services on the IP network through the existing telephone network by the use of the media gateway (MG).

In the above-mentioned gateway system, it is essential to include the media gateway controller having a function as a signaling gateway for terminating the No. 7 signal and another function as a call agent for carrying out call control and connection control on the side of the IP network. Basically, the media gateway controller carries out call control so that the switching system applied to the signal

transfer point can not be used. Therefore, upon an occurrence of a failure in the media gateway controller, the gateway system will suffer system down time.

This invention relates to the media gateway controller used in the above-mentioned services. Specifically, a plurality of media gateway controllers are grouped so as to provide a redundant structure. Such a redundant structure assures the reliability to enable the operation to be continued without causing system down even upon an occurrence of a failure.

More specifically, in the gateway system of this invention, a plurality of media gateway controllers are grouped into a media gateway controller group having a redundant structure. The media gateway controllers belonging to each single group are assigned a common point code (PC).

Each of the media gateway controllers comprises two major functional components, i.e., a No. 7 signal processing portion and a call processing control portion. Each functional component has a function of M3UA [SS7 (Signaling System No.7) MTP3-User Adaptation Layer]. By the use of SCTP (Stream Control Transmission Protocol) through the IP network, signal information is transmitted and received between the media gateway controllers.

For example, an ISUP [ISDN (Integrated Services Digital Network) User Part] signal transmitted from a No. 7 network link to one of the media gateway controllers is processed by the No. 7 signal processing portion to obtain signal information. The No. 7 signal processing portion transmits the signal information to the call processing control portion. Simultaneously, the signal information is transmitted through the IP network to the other media gateway controllers. Thus, a call status is shared by the media gateway controllers.

It is assumed that a communication channel is established between an exchange and a media gateway through a particular media gateway controller. Upon occurrence of a failure in the particular media gateway controller, the exchange or the media gateway transmits the ISUP signal or a message, which is to be transmitted to the particular media gateway controller, to another media gateway controller in the media gateway controller group. Thus, the processing for the communication channel is continued without being affected by the failure.

When the exchange transmits the ISUP signal to the media gateway controller group, an appropriate signal link is selected for the purpose of distribution in signal traffic. Thus, the load is distributed among the media gateway controllers to prevent each single media gateway controller from being assigned a heavy concentration of signal processing.

As described above, the media gateway controllers are grouped into a media gateway controller group having a redundant structure. The media gateway controllers in the media gateway controller group are assigned with the same PC and treated as a single media gateway controller. By the use of M3UA, the call status is shared among these media gateway controllers in the media gateway controller group. With this structure, the processing can continuously be carried out without causing system down time even upon an occurrence of a failure. Thus, high reliability can be assured.

Now, description will be made of one embodiment of this invention with reference to the drawing in detail.

Referring to FIG. 1, a gateway system according to one embodiment of this invention comprises a media gateway controller group (hereinafter abbreviated to an MGC group) **1**, an exchange **2**, and a media gateway **3**. The gateway

system serves to connect an existing telephone network **101** and an IP (Internet Protocol) network **102**.

The MGC group **1** comprises a plurality of media gateway controllers (hereinafter abbreviated to an MGC) **11** through **13**. All of the MGCs **11** through **13** belonging to the MGC group **1** have a common point code (PC). The media gateway **3** preliminarily acquires and stores IP addresses assigned to the MGCs **11** through **13** belonging to the MGC group **1** which controls the media gateway **3**.

The exchange **2** is an exchange in a telephone exchange station and is connected to the existing telephone network **101** (subscriber lines). The MGCs **11** through **13** belonging to the MGC group **1** are connected to the exchange **2** through signal links belonging to a single common signal link group. In a case where a particular signal link becomes unavailable, the particular signal link is switched to another signal link. In FIG. 1, the media gateway **3** is connected to the exchange **2** through a communication path **100**.

It is assumed that a user desires to use an IP network service through the existing telephone network **101**. In this event, one of the MGCs **11** through **13** establishes the communication path **100** between the media gateway **3** and the exchange **2** through the IP network **102**. The communication path **100** is identified by the MGCs **11** through **13** with reference to a destination point code (DPC) and a circuit (or channel) identification code (CIC). In this case, the destination point code has a value of the destination point code assigned to the MGC group **1**.

Referring to FIG. 2, the MGC **11** in the MGC group **1** comprises a No. 7 signal processing portion **11a** and a call processing control portion **11b**. Likewise, the MGC **12** comprises a No. 7 signal processing portion **12a** and a call processing control portion **12b**. The MGC **13** comprises a No. 7 signal processing portion **13a** and a call processing control portion **13b**.

Each of the MGCs **11** through **13** transfers signal information through the IP network **102** to other MGCs by the use of M3UA [SS7 (Signaling System No.7) MTP3-User Adaptation layer] on a SCTP (Stream Control Transmission Protocol).

Each of the No. 7 signal processing portions **11a**, **12a**, and **13a** processes a No. 7 signal as a control signal of the common channel signaling system No. 7 (SS7) and transmits an ISUP [ISDN (Integrated Services Digital Network) User Part] message received from a No. 7 network link to each of the call processing control portions **11b**, **12b**, and **13b**. Simultaneously, each of the No. 7 signal processing portions **11a**, **12a**, and **13a** has an M3UA function and, by the use of the M3UA function, transmits the information to the other MGCs. Each of the No. 7 signal processing portions **11a**, **12a**, and **13a** transmits the ISUP message from each of the call processing control portions **11b**, **12b**, and **13b** to the No. 7 network link.

Each of the call processing control portions **11b**, **12b**, and **13b** carries out call control and connection control, i.e., terminates the ISUP message received from each of the No. 7 signal processing portions **11a**, **12a**, and **13a** and transmits to the IP network a message for controlling the media gateway **3** in accordance with the ISUP message. Supplied with the message from the media gateway **3**, each of the call processing control portions **11b**, **12b**, and **13b** transmits the message to each of the No. 7 signal processing portions **11a**, **12a**, and **13a** and, simultaneously, transmits the information to the other MGCs by the use of M3UA.

As described above, the MGC group **1** has a redundant structure comprising a plurality of MGCs **11** through **13**. The

## 5

MGCs **11** through **13** belonging to the MGC group **1** are assigned the same point code.

Each of the MGCs **11** through **13** comprises two major functional components. Specifically, the MGC **11** comprises the No. 7 signal processing portion **11a** and the call processing control portion **11b**. Likewise, the MGC **12** comprises the No. 7 signal processing portion **12a** and the call processing control portion **12b**. The MGC **13** comprises the No. 7 signal processing portion **13a** and the call processing control portion **13b**. Each functional component has the M3UA function. The MGCs **11** through **13** transmit and receive signal information to and from one another through the IP network **102** by the use of the SCTP.

For example, the ISUP signal transmitted from the No. 7 network link to the MGC **11** is processed by the No. 7 signal processing portion **11a**. The No. 7 signal processing portion **11a** transmits the signal information to the call processing control portion **11b**. Simultaneously, the signal information is also transmitted to the other MGCs **12** and **13** through the IP network **102**. As a consequence, the MGCs **11** through **13** share the call status.

When the communication channel path is established between the exchange **2** and the media gateway **3** through the MGC **11**, it is assumed that a failure occurs in the MGC **11**. In this event, the exchange **2** or the media gateway **3** transmits the ISUP signal or the message, which is to be transmitted to the MGC **11**, to the other MGC **12** or **13** in the MGC group **1**. In this manner, the processing for the communication path **100** is continuously carried out without being affected by the failure.

When the exchange **2** transmits the ISUP signal to the MGC group **1**, an appropriate signal link is selected for the purpose of distribution in signal traffic. Thus, the load is distributed among the MGCs **11** through **13** to prevent each single one of the MGCs **11** through **13** from being assigned a heavy concentration of signal processing.

As described above, the MGCs **11** through **13** are grouped into the MGC group **1** having a redundant structure. The MGC group **1** is treated as a single MGC. Specifically, the MGCs **11** through **13** in the MGC group **1** are assigned with the same point code. By the use of M3UA, the call status is shared. Thus, processing is continuously carried out without causing system down time even upon an occurrence of a failure. Thus, high reliability is assured.

Referring to FIGS. **3** and **4** in addition to FIGS. **1** and **2**, description will be made of the operation of the gateway system of this embodiment.

It is assumed that a call is originated from the existing telephone network **101** (subscriber lines) and received by the exchange **2** connected thereto. In this event, the exchange **2** selects one of the MGCs **11** through **13** which corresponds to a designated telephone number and transmits an ISUP message (**A1** in FIG. **3**) to the selected one of the MGCs **11** through **13**.

For example, the exchange **2** transmits an IAM (Initializing Address Message) (**A1** in FIG. **3**) of the ISUP to the MGC **11**. In the MGC **11** supplied with the message, the message is transmitted through the No. 7 signal processing portion **11a** to the call processing control portion **11b**.

Simultaneously, the No. 7 signal processing portion **11a** processes the IAM message as a reception IAM message into an M3UA format so that the reception IAM message is transferred to the other MGCs **12** and **13** through the IP network **102** by the use of the SCTP (**A2**, **A3** in FIG. **3**). At this time, the No. 7 signal processing portion **11a** attaches a dummy flag to the IAM message to be transferred.

## 6

In the MGCs **12** and **13** supplied with the message, the call processing control portions **12b** and **13b** identify the dummy flag. Then, with respect to the message with the dummy flag attached thereto, the call processing control portions **12b** and **13b** do not transmit the message to the media gateway **3** but they do record the information of the call in question.

The call processing control portion **11b** identifies the channel with reference to a channel identification information (destination point code and channel identification code) contained in the IAM message. In accordance with a routing table (not shown) in the MGC **11**, the call processing control portion **11b** transmits a call setup message (**A4** in FIG. **3**) through the IP network **102** to the media gateway **3** which establishes the communication path **100**.

Similarly, when the MGC **11** receives a response message (**A5** in FIG. **3**) from the media gateway **3**, the call processing control portion **11b** of the MGC **11** transmits the ISUP-ACM message to the No. 7 signal processing portion **11a**. Simultaneously, this message is processed into the M3UA format. In the manner similar to the transmission technique by the No. 7 signal processing portion **11a**, the ACM message with the dummy flag attached thereto is transmitted to the other MGCs **12** and **13** (**A6** and **A7** in FIG. **3**).

In the MGCs **12** and **13**, the No. 7 signal processing function portion **12a** and **13a** do not transmit the message to the No. 7 network link but they do record the status as the information of the call in a case where the dummy flag is identified. The No. 7 signal processing portion **11a** of the MGC **11** transmits the ISUP-ACM message to the No. 7 network link (**A8** in FIG. **3**). By the above-mentioned operation, the call status is shared by the MGCs **11** through **13**. In this event, by the above-mentioned operation, the communication path **100** is established between the exchange **2** and the media gateway **3** (**A9** in FIG. **3**).

Next referring to FIG. **4**, description will be made of the operation in case where a failure occurs in the MGC **11** and communication with the MGC **11** becomes impossible.

It is assumed that the communication path **100** (**B10** in FIG. **4**) is established through the MGC **11**. When the exchange **2** transmits the ISUP message (**B1** in FIG. **4**) to the MGC **11**, the MGC **11** becomes inoperable due to a failure. In this event, a timer (**B2** in FIG. **4**) set in the exchange **2** detects "message time out".

The exchange **2** detects an error by the above-mentioned time out and sets the status of the MGC **11** as a faulty state. The exchange **2** inhibits the transmission of signals to the signal link in question so that the transmission of the signals is not carried out until the recovery from the faulty state. The exchange **2** transmits again the ISUP message (**B3** in FIG. **4**) of the same content to another signal link (in this case, the destination is the MGC **12**) belonging to the same signal link group connected to the MGC group **1**.

The MGC **12** receives the dummy message from the MGC **11** and shares the call status for the communication channel in question. Since the MGC **12** has the same point code as the MGC **11**, the channel is correctly identified. The No. 7 signal processing portion **12a** of the MGC **12** transmits the ISUP message to the call processing control portion **12b** and simultaneously transmits the ISUP message to the other MGCs **11** and **13** in the MGC group **1** in the manner similar to that mentioned above (**B4**, **B5** in FIG. **4**).

The MGC **11** in the faulty state can not receive the message. The MGC **12** detects this situation and sets the status of the MGC **11** as the faulty state and does not transmit any message until the MGC **11** is recovered from the faulty



state. By the above-mentioned operation, call control can be continuously carried out by the other MGCs **12** and **13** belonging to the same MGC group **1** even if a failure occurs in the MGC **11** (**B6**, **B7**, **B8**, **B9** in FIG. **4**).

That is, in **B6** in FIG. **4**, the MGC **12** transmits the call setup message through the IP network **102** to the media gateway **3** like in **A4** in FIG. **3**. In **B7** in FIG. **4**, the MGC **12** receives the response message from the media gateway **3** like in **A5** in FIG. **3**. In this event, the call processing control portion **12b** of the MGC **12** transmits the ISUP-ACM message to the No. 7 signal processing portion **12a**. Simultaneously, this message is processed into the M3UA format. In the manner similar to the transmission technique by the No. 7 signal processing portion **12a**, the ACM message with the dummy flag attached thereto is transmitted to the MGC **13** in **B8** in FIG. **4** (like in **A7** in FIG. **3**).

In the MGC **13**, the No. 7 signal processing function portion **13a** does not transmit the message to the No. 7 network link but it does record the status as the information of the call in a case where the dummy flag is identified. The No. 7 signal processing portion **12a** of the MGC **12** transmits the ISUP-ACM message to the No. 7 network link **B9** in FIG. **4** (like in **A8** in FIG. **3**).

As described above, in the system environment for providing the IP network service through the existing telephone network **101** by the use of the media gateway, the redundant structure of the MGCs **11** through **13** for processing the signaling and for carrying out the call control is realized. With this structure, even upon an occurrence of a failure in the MGCs **11** through **13** or in the signal link, the call control is assured by the use of the other MGCs without causing system down time. Thus, high reliability is assured. By flexibly combining the No. 7 signal processing portions **11a**, **12a**, and **13a** and the call processing control portions **11b**, **12b**, and **13b** and by distributing the processing among a plurality of the MGCs **11** through **13**, it is possible to achieve load distribution without heavy concentration of processing being assigned to a single node.

In the foregoing description, the number of the MGCs is equal to three. In the above-mentioned structure, however, the number of MGCs can be increased within a range such that the IP addresses can be assigned.

In order to share the call status among the MGCs **11** through **13**, use is made of the technique of transmitting the ISUP message through the IP network **102** by the use of the M3UA/SCTP. Alternatively, the MGCs may be connected by high-speed bus connection to transmit/receive/share the information. In this event, by flexibly changing a combination of the functional components including the No. 7 signal processing portions **11a**, **12a**, and **13a** and the call processing control portions **11b**, **12b**, and **13b** in accordance with the use ratio or the faulty state of each functional component, it is possible to distribute the load.

If the number of the MGCs is increased, each signal MGC group may be provided with a call status managing node. In this event, it is unnecessary to transmit the dummy message of ISUP to all of the MGCs **11** through **13**. By selecting the functional component having a lowest use ratio upon carrying out the processing, the redundant structure can be more effectively utilized.

As described above, in the gateway system for providing the IP network service through the existing telephone network by the use of the media gateway, a plurality of the media gateway controllers for terminating the No. 7 signal as the control signal of the common channel signaling system No. 7 in the existing telephone network and for

carrying out call control and connection control on the side of the IP network are grouped into the media gateway controller group having the redundant structure. Thus, even upon an occurrence of a failure, high reliability is assured without causing system down time.

What is claimed is:

1. A gateway system connecting a telephone network utilizing a common channel signaling system No. 7 to an IP (Internet Protocol) network, said gateway system comprising:

a media gateway; and

a media gateway controller group comprising a plurality of media gateway controllers which are assigned a common point code,

wherein each of said media gateway controllers in said media gateway controller group is capable of terminating a No. 7 signal representative of a control signal of the common channel signaling system No. 7 in said telephone network, and

wherein each of said media gateway controllers in said media gateway controller group is capable of carrying out call control and connection control to said IP network by controlling said media gateway through said IP network so that a communication path is established between said telephone network and said media gateway, and

wherein one of said media gateway controllers in said media gateway controller group transmits signal information with a dummy flag to all others of said media gateway controllers in said media gateway controller group, to thereby provide the signal information to be used to maintain a call by one of said others of said media gateway controllers in a case that said one of said media gateway controllers experiences a failure during the call.

2. A gateway system as claimed in claim 1, wherein said telephone network includes a dial up service using a remote access server.

3. A gateway system as claimed in claim 1, further comprising load distribution means for distributing a call load among said media gateway controllers of said media gateway controller group so as not to overload any one of said media gateway controllers.

4. A gateway system as for connecting a telephone network utilizing a common channel signaling system No. 7 to an IP (Internet Protocol) network, said gateway system comprising:

a media gateway; and

a media gateway controller group comprising a plurality of media gateway controllers which are assigned a common point code,

wherein each of said media gateway controllers in said media gateway controller group is capable of terminating a No. 7 signal representative of a control signal of the common channel signaling system No. 7 in said telephone network, and

wherein each of said media gateway controllers in said media gateway controller group is capable of carrying out call control and connection control to said IP network by controlling said media gateway through said IP network so that a communication path is established between said telephone network and said media gateway,

wherein each of said media gateway controllers comprises:

9

a No. 7 signal processing portion for terminating said No. 7 signal; and

a call processing control portion for carrying out the call control and the connection control to said IP network by controlling said media gateway through said IP network so that the communication path is established between said telephone network and said media gateway,

wherein said No. 7 signal processing portion and said call processing control portion each have a M3UA (SS7 (Signaling System No. 7) MTP (Message Transfer Part) 3-User Adaptation Layer) function,

wherein said No. 7 signal processing portion of one of said media gateway controllers in said media gateway controller group receives and processes an Integrated Services Digital Network User Part (ISUP) signal transmitted from said telephone network to obtain signal information, and transmits the signal information as an ISUP message to said call processing control portion of said one of said media gateway controllers, and also transmits the signal information as a Dummy ISUP message to all others of said media gateway controllers in said media gateway controller group, to thereby provide the signal information to be used to maintain a call by one of said others of said media gateway controllers in a case that said one of said media gateway controllers experiences a failure during the call.

10

5. A gateway system as claimed in claim 4, wherein said media gateway controllers of said media gateway controller group transmit and receive signal information to and from one another through said IP network by the use of SCTP (Stream Control Transmission Protocol).

6. A gateway system as claimed in claim 4, wherein said media gateway controllers of said media gateway controller group share the information of a call by the use of said M3UA function.

7. A gateway system as claimed in claim 6, wherein said media gateway controllers of said media gateway controller group transmit and receive signal information to and from one another through said IP network by the use of SCTP (Stream Control Transmission Protocol).

8. A gateway system as claimed in claim 4, wherein the Dummy ISUP message is not provided to said media gateway, and only said ISUP message is provided to said media gateway, and

wherein the Dummy ISUP message of said one of said others of said media gateway controllers is converted to said ISUP message and thereby sent to said media gateway, when said one of said media gateway controllers is determined to have experienced the failure.

\* \* \* \* \*