

(12) **United States Patent**
Tessien et al.

(10) **Patent No.: US 6,958,568 B1**
(45) **Date of Patent: Oct. 25, 2005**

(54) **ACOUSTIC DRIVER ASSEMBLY FOR A SPHERICAL CAVITATION CHAMBER**

5,998,908 A * 12/1999 Goodson 310/325
6,146,674 A * 11/2000 Manna et al. 426/238
6,361,747 B1 * 3/2002 Dion et al. 422/128

(75) Inventors: **Ross Alan Tessien**, Nevada City, CA (US); **Dario Felipe Gaitan**, Nevada City, CA (US); **Daniel A. Phillips**, Grass Valley, CA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 01/39205 A2 * 11/2000

(Continued)

OTHER PUBLICATIONS

M. Dan et al., Ambient Pressure Effect on Single-Bubble Sonoluminescence, Physical Review Letters, Aug. 30, 1999, Page(s) 1870-1873, vol. 83, No. 9, Published in: US.

(Continued)

Primary Examiner—Thomas M. Dougherty

(74) *Attorney, Agent, or Firm*—Patent Law Office of David G. Beck

(73) Assignee: **Impulse Devices, Inc.**, Grass Valley, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 5 days.

(21) Appl. No.: **10/943,680**

(22) Filed: **Sep. 17, 2004**

Related U.S. Application Data

(63) Continuation of application No. 10/931,918, filed on Sep. 1, 2004.

(51) **Int. Cl.**⁷ **B06B 1/06**; H01L 41/08

(52) **U.S. Cl.** **310/323.12**; 310/323.13; 310/323.18; 310/323.19; 310/328; 310/334

(58) **Field of Search** 310/323.12, 323.13, 310/323.18, 323.19, 322, 327, 334-337, 310/369, 328

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,140,859 A * 7/1964 Scarpa 366/114
4,333,796 A 6/1982 Flynn
4,339,247 A 7/1982 Faulkner et al.
4,563,341 A 1/1986 Flynn
4,757,227 A * 7/1988 Danley et al. 310/323.19
4,991,152 A 2/1991 Letiche
5,030,873 A 7/1991 Owen
5,658,534 A 8/1997 Desborough et al.
5,659,173 A * 8/1997 Putterman et al. 250/361 C
5,722,444 A * 3/1998 Prokopenko et al. 310/348
5,858,104 A 1/1999 Clark
5,994,818 A 11/1999 Abramov et al.

ABSTRACT

An acoustic driver assembly for use with a spherical cavitation chamber is provided. The acoustic driver assembly includes at least one transducer, a head mass and a tail mass, coupled together with a centrally located threaded means (e.g., all thread, bolt, etc.). The driver assembly is permanently attached to the exterior surface of the spherical cavitation chamber via brazing or diffusion bonding. In at least one embodiment, the transducer is comprised of a pair of piezo-electric transducers, preferably with the adjacent surfaces of the piezo-electric transducers having the same polarity. The surface of the head mass that is adjacent to the external surface of the chamber has a spherical curvature equivalent to the spherical curvature of the external surface of the chamber, thus providing maximum coupling efficiency between the acoustic driver and the cavitation chamber. In at least one embodiment a void filling material is interposed between one or more pairs of adjacent surfaces of the driver assembly.

20 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

6,617,765 B1 9/2003 Lagler et al.
6,690,621 B2 2/2004 Porzio

FOREIGN PATENT DOCUMENTS

WO WO 01/39205 5/2001
WO WO 02/087737 * 11/2002 B01F 11/00



OTHER PUBLICATIONS

C. Desilets et al., Analyses and Measurements of Acoustically Matched, Air-Coupled Tonpilz Transducers, IEEE Ultrasonics Symposium Proceedings—1999, Oct. 17, 1999, Page(s) 1045-1048, vol. 2, Publisher: IEEE.

S.C. Butler et al., A Broadband Hybrid Magnetostrictive/Piezoelectric Transducer Array, Magsoft Update, Jul. 2001, Page(s) 1-7, vol. 7, No. 1, Publisher: Magsoft Corporation, Published in: US.

M.J. Lodeiro et al, High Frequency Displacement and Dielectric Measurements in Piezoelectric Materials, CPM8. 1 Characterization of Advanced Functional Materials—Final Project Deliverables, Mar. 2002, Page(s) 1-12, vol. MATC(MN), No. 21, Publisher: United Kingdom National Physical Laboratory, Published in: United Kingdom.

* cited by examiner






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 11

ACOUSTIC DRIVER ASSEMBLY FOR A SPHERICAL CAVITATION CHAMBER

REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 10/931,918, filed Sep. 1, 2004.

FIELD OF THE INVENTION

The present invention relates generally to sonoluminescence and, more particularly, to an acoustic driver assembly for use with a sonoluminescence cavitation chamber.

BACKGROUND OF THE INVENTION

Sonoluminescence is a well-known phenomena discovered in the 1930's in which light is generated when a liquid is cavitates. Although a variety of techniques for cavitating the liquid are known (e.g., spark discharge, laser pulse, flowing the liquid through a Venturi tube), one of the most common techniques is through the application of high intensity sound waves.

In essence, the cavitation process consists of three stages; bubble formation, growth and subsequent collapse. The bubble or bubbles cavitates during this process absorb the applied energy, for example sound energy, and then release the energy in the form of light emission during an extremely brief period of time. The intensity of the generated light depends on a variety of factors including the physical properties of the liquid (e.g., density, surface tension, vapor pressure, chemical structure, temperature, hydrostatic pressure, etc.) and the applied energy (e.g., sound wave amplitude, sound wave frequency, etc.).

Although it is generally recognized that during the collapse of a cavitating bubble extremely high temperature plasmas are developed, leading to the observed sonoluminescence effect, many aspects of the phenomena have not yet been characterized. As such, the phenomena is at the heart of a considerable amount of research as scientists attempt to not only completely characterize the phenomena (e.g., effects of pressure on the cavitating medium), but also its many applications (e.g., sonochemistry, chemical detoxification, ultrasonic cleaning, etc.).

Although acoustic drivers are commonly used to drive the cavitation process, there is little information about methods of coupling the acoustic energy to the cavitation chamber. For example, in an article entitled *Ambient Pressure Effect on Single-Bubble Sonoluminescence* by Dan et al. published in vol. 83, no. 9 of Physical Review Letters, the authors describe their study of the effects of ambient pressure on bubble dynamics and single bubble sonoluminescence. Although the authors describe their experimental apparatus in some detail, they only disclose that a piezoelectric transducer was used at the fundamental frequency of the chamber, not how the transducer couples its energy into the chamber.

U.S. Pat. No. 4,333,796 discloses a cavitation chamber that is generally cylindrical although the inventors note that other shapes, such as spherical, can also be used. As disclosed, the chamber is comprised of a refractory metal such as tungsten, titanium, molybdenum, rhenium or some alloy thereof and the cavitation medium is a liquid metal such as lithium or an alloy thereof. Surrounding the cavitation chamber is a housing which is purportedly used as a neutron and tritium shield. Projecting through both the outer housing and the cavitation chamber walls are a number of acoustic

horns, each of the acoustic horns being coupled to a transducer which supplies the mechanical energy to the associated horn. The specification only discloses that the horns, through the use of flanges, are secured to the chamber/housing walls in such a way as to provide a seal and that the transducers are mounted to the outer ends of the horns.

U.S. Pat. No. 5,658,534 discloses a sonochemical apparatus consisting of a stainless steel tube about which ultrasonic transducers are affixed. The patent provides considerable detail as to the method of coupling the transducers to the tube. In particular, the patent discloses a transducer fixed to a cylindrical half-wavelength coupler by a stud, the coupler being clamped within a stainless steel collar welded to the outside of the sonochemical tube. The collars allow circulation of oil through the collar and an external heat exchanger. The abutting faces of the coupler and the transducer assembly are smooth and flat. The energy produced by the transducer passes through the coupler into the oil and then from the oil into the wall of the sonochemical tube.

U.S. Pat. No. 5,659,173 discloses a sonoluminescence system that uses a transparent spherical flask. The spherical flask is not described in detail, although the specification discloses that flasks of Pyrex®, Kontes®, and glass were used with sizes ranging from 10 milliliters to 5 liters. The drivers as well as a microphone piezoelectric were simply epoxied to the exterior surface of the chamber.

U.S. Pat. No. 5,858,104 discloses a shock wave chamber partially filled with a liquid. The remaining portion of the chamber is filled with gas which can be pressurized by a connected pressure source. Acoustic transducers are used to position an object within the chamber while another transducer delivers a compressional acoustic shock wave into the liquid. A flexible membrane separating the liquid from the gas reflects the compressional shock wave as a dilation wave focused on the location of the object about which a bubble is formed. The patent simply discloses that the transducers are mounted in the chamber walls without stating how the transducers are to be mounted.

U.S. Pat. No. 5,994,818 discloses a transducer assembly for use with tubular resonator cavity rather than a cavitation chamber. The assembly includes a piezoelectric transducer coupled to a cylindrical shaped transducer block. The transducer block is coupled via a central threaded bolt to a wave guide which, in turn, is coupled to the tubular resonator cavity. The transducer, transducer block, wave guide and resonator cavity are co-axial along a common central longitudinal axis. The outer surface of the end of the wave guide and the inner surface of the end of the resonator cavity are each threaded, thus allowing the wave guide to be threadably and rigidly coupled to the resonator cavity.

U.S. Pat. No. 6,361,747 discloses an acoustic cavitation reactor in which the reactor chamber is comprised of a flexible tube. The liquid to be treated circulates through the tube. Electroacoustic transducers are radially and uniformly distributed around the tube, each of the electroacoustic transducers having a prismatic bar shape. A film of lubricant is interposed between the transducer heads and the wall of the tube to help couple the acoustic energy into the tube.

PCT Application No. US00/32092 discloses several driver assembly configurations for use with a solid cavitation reactor. The disclosed reactor system is comprised of a solid spherical reactor with multiple integral extensions surrounded by a high pressure enclosure. Individual driver assemblies are coupled to each of the reactor's integral extensions, the coupling means sealed to the reactor's enclosure in order to maintain the high pressure characteristics of the enclosure.

3

Although a variety of cavitation systems have been designed, these systems typically provide inadequate coupling of the acoustic energy to the cavitation chamber. Accordingly, what is needed in the art is an acoustic driver assembly that efficiently couples energy to the cavitation chamber while being relatively easy to manufacture. The present invention provides such a system.

SUMMARY OF THE INVENTION

The present invention provides an acoustic driver assembly for use with a spherical cavitation chamber. The acoustic driver assembly includes at least one transducer, a head mass and a tail mass, coupled together with a centrally located threaded means (e.g., all thread, bolt, etc.). The driver assembly is permanently attached to the exterior surface of the spherical cavitation chamber via diffusion bonding or brazing. In at least one embodiment, the transducer is comprised of a pair of piezo-electric transducers, preferably with the adjacent surfaces of the piezo-electric transducers having the same polarity. The surface of the head mass that is adjacent to the external surface of the chamber has a spherical curvature equivalent to the spherical curvature of the external surface of the chamber, thus providing maximum coupling efficiency between the acoustic driver and the cavitation chamber. In at least one embodiment a void filling material is interposed between one or more pairs of adjacent surfaces of the driver assembly. In at least one embodiment a two-piece head mass is used, thus allowing driver assembly/disassembly that is independent of the driver/chamber coupling.

A further understanding of the nature and advantages of the present invention may be realized by reference to the remaining portions of the specification and the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of a spherical sonoluminescence cavitation chamber without ports in accordance with the prior art;

FIG. 2 is a cross-sectional view of the spherical cavitation chamber shown in FIG. 1;

FIG. 3 is an illustration of a driver assembly fabricated in accordance with the invention;

FIG. 4 is a cross-sectional view of the driver assembly of FIG. 3 attached to a spherical cavitation chamber such as the chamber illustrated in FIG. 1;

FIG. 5 is a cross-sectional view of a driver assembly with an alternate head mass shape;

FIG. 6 is a cross-sectional view of a driver assembly with an alternate head mass shape;

FIG. 7 is a cross-sectional view of a driver assembly with an alternate head mass shape;

FIG. 8 is a cross-sectional view of an alternate driver assembly in which the head mass coupling means is independent of the driver assembly coupling means;

FIG. 9 is a cross-sectional view of an alternate driver assembly in which the head mass is permanently coupled to the cavitation chamber exterior surface;

FIG. 10 is a cross-sectional view of an alternate driver assembly in which the head mass is comprised of a first portion permanently coupled to the cavitation chamber exterior surface and a second portion associated with the driver assembly; and

FIG. 11 is a graph of measured sonoluminescence data taken with a spherical cavitation chamber and a driver assembly in accordance with the invention.

4

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

FIG. 1 is an illustration of a spherical sonoluminescence cavitation chamber **101**, hereafter referred to as simply a cavitation chamber, according to the prior art. Transducers **109–112** are mounted to the lower hemisphere of chamber **101** and transducers **115–116** are mounted to the upper hemisphere of chamber **101**.

FIG. 2 is a cross-sectional view of spherical cavitation chamber **101**. Chamber **101** has an outer spherical surface **103** defining the outer diameter of the chamber, and an inner spherical surface **105** defining the inner diameter of the chamber. The fabrication of a spherical chamber is described in detail in co-pending application Ser. No. 10/925,070, filed Aug. 23, 2004, entitled *Method of Fabricating a Spherical Cavitation Chamber*, the disclosure of which is incorporated herein for any and all purposes.

Chamber **101** can be fabricated from any of a variety of materials, depending primarily on the desired operating temperature and pressure, as well as the fabrication techniques used to make the chamber. Typically the chamber is fabricated from a metal; either a pure metal or an alloy such as stainless steel.

With respect to the dimensions of the chamber, both inner and outer diameters, the selected sizes depend upon the intended use of the chamber. For example, smaller chambers are typically preferable for situations in which the applied energy (e.g., acoustic energy) is somewhat limited. Similarly, thick chamber walls are preferable if the chamber is to be operated at high static pressures. For example, the prior art discloses wall thicknesses of 0.25 inches, 0.5 inches, 0.75 inches, 1.5 inches, 2.375 inches, 3.5 inches and 4 inches, and outside diameters in the range of 2–10 inches. It should be appreciated, however, that the present invention is not limited to a particular outside chamber diameter, inside chamber diameter, chamber material, chamber shape, transducer number, or transducer mounting location. Such information, as provided herein, is only meant to provide exemplary chamber configurations for which the present invention is applicable.

FIG. 3 is a perspective view of a driver assembly **300** in accordance with the invention. FIG. 4 is a cross-sectional view of a preferred embodiment of driver assembly **300** attached to cavitation chamber **101**. Preferably piezo-electric transducers are used in driver **300** although magnetostrictive transducers can also be used, magnetostrictive transducers typically preferred when lower frequencies are desired. A combination of piezo-electric and magnetostrictive transducers can also be used, for example as a means of providing greater frequency bandwidths.

Driver assembly **300** can use a single piezo-electric transducer or a transducer stack. In the preferred embodiment assembly **300** uses a pair of piezo-electric transducer rings **301** and **302** poled in opposite directions. By using a pair of transducers in which the adjacent surfaces of the two crystals have the same polarity, potential grounding problems are minimized. An electrode disc **303** is located between transducer rings **301** and **302** which, during operation, is coupled to the driver power amplifier **305**.

The transducer pair is sandwiched between a head mass **307** and a tail mass **309**. In the preferred embodiment both head mass **307** and tail mass **309** are fabricated from stainless steel and are of equal mass. In alternate embodiments head mass **307** and tail mass **309** are fabricated from different materials. In yet other alternate embodiments, head mass **307** and tail mass **309** have different masses and/or

5

different mass diameters and/or different mass lengths. For example tail mass **309** can be much larger than head mass **307**.

Driver **300** is assembled about a centrally located all-thread **311** which is screwed directly into wall **401** of chamber **101**. A cap nut **313** holds the assembly together. As shown, preferably all-thread **311** does not pass through the entire chamber wall, thus leaving the internal chamber surface **105** smooth and preventing gas or liquid leaks at the point of driver attachment. Alternately, for example with thin walled chambers, the threaded hole to which all-thread **311** is coupled passes through the entire chamber wall. Typically in such an embodiment all-thread **311** does not pass through the entire chamber wall but is sealed into place with an epoxy or other suitable sealant. It is understood that all-thread **311** and cap nut **313** can be replaced with a bolt. An insulating sleeve **403** isolates all-thread **311**, preventing it from shorting electrode **303**.

End surface **315** of driver assembly **300** is preferably spherically shaped with a curvature matching that of external chamber surface **103**. This design insures the efficient transfer of acoustic energy into chamber **101**.

In a preferred embodiment of the invention, acoustic driver assembly **300** is approximately 2.5 inches in diameter, tail mass **309** and head mass **307** each weigh approximately 5 pounds and are fabricated from 17-4 PH stainless steel, and a pair of piezo-electric transducers fabricated by Channel Industries of Santa Barbara, Calif. is used. Driver **300** is assembled about a 0.5 inch all-thread **311**, insulating sleeve **403** is fabricated from Teflon and the assembly is tightened to 120 ft-lbs.

FIG. **5** is a cross-sectional view of an alternate embodiment of the invention. The majority of driver assembly **500** is the same as driver assembly **300**, equivalent components represented through the use of the same component labels. Driver assembly **500**, however, uses a head mass **501** in which end surface **503** has a curvature greater than that of external chamber surface **103**. As a result, rather than having the entire end surface being in contact with the external chamber surface **103**, only a ring **505** of contact is made between the two surfaces. If desired, the contact area **601** can be increased by chamfering the contact area of end surface **603** of the head mass **605** as illustrated in FIG. **6**.

FIG. **7** is a cross-sectional view of an alternate embodiment of the invention. As in FIGS. **5** and **6**, the use of the same component labels indicates component equivalency. Driver assembly **700** uses a head mass **701** in which end surface **703** has a curvature less than that of the external surface of chamber **101**. For example, as shown, end surface **703** is flat, leading to only a small portion **705** of surface **703** being in contact with external chamber surface **103**. A similar result can be obtained by having the curvature of surface **703** be less than that of external surface **103**, but more than a flat surface (not shown). Alternately, the curvature of head mass **307** can be inverted (not shown), also resulting in minimal contact between the two surfaces, the contact area being located around the central portion of the driver assembly.

In an alternate embodiment shown in FIG. **8**, the driver is assembled about a first threaded means **801** (e.g., all-thread or bolt) which is threaded into head mass **307**. Coupling means, for example an all-thread member **803** as shown, is used to couple driver assembly **800** to wall **401** of chamber **101**. The principal benefit of this configuration is that the driver assembly is independent of the driver-chamber coupling means. As a result, a driver can be attached to, or detached from, a cavitation chamber without disassembling

6

the actual driver assembly. This is especially beneficial given the susceptibility of piezo-electric crystals to damage. It is understood that this aspect of the invention is not limited to head mass **307**, rather it is equally applicable to head mass **501**, head mass **605** or head mass **701**. It is also understood that the coupling means between the head mass and the cavitation chamber surface is not limited to all-thread **803**; other means such as adhesives (e.g., epoxy) are clearly envisioned by the inventors.

FIG. **9** is an illustration of an alternate embodiment in which the head mass of the driver assembly is permanently coupled to the chamber. As shown, head mass **901** is attached to chamber exterior surface **103** along surface **903**. For small drivers, head mass **901** can be bonded to chamber surface **103**, for example with an epoxy. Due to the mass of larger drivers, and due to the vibration inherent in the assembly when operating, a more permanent coupling technique is preferred. Brazing is the preferred coupling technique although alternate techniques such as diffusion bonding are also acceptable. As the head mass in this embodiment is permanently coupled to the chamber surface, a threaded means such as all-thread **311** or **803** is not required although the embodiment does require a driver assembly threaded means **801**. If desired, and as a means of allowing the driver assembly to be assembled/disassembled separately from the chamber/head mass assembly, a two-piece head mass assembly can be used as illustrated in FIG. **10**. As shown, a first head mass portion **1001** is bonded to chamber exterior surface **103**, for example via brazing or diffusion bonding as noted above, while a second head mass portion **1003** is coupled to the driver assembly via threaded means **1005**. A second threaded means **1007** couples head mass portion **1001** to head mass portion **1003**.

Micro-surface imperfections, such as those between the head mass and the chamber exterior surface, impair efficient coupling of acoustic energy into the chamber. Accordingly bonding the head mass to the chamber as described above relative to FIGS. **9** and **10** has been found to improve acoustic energy coupling efficiency. For similar reasons it has been found that the inclusion of a void filling material between adjacent pairs of surfaces of the driver assembly and/or the driver assembly and the exterior surface of the cavitation chamber improves the overall coupling efficiency and operation of the driver. Therefore in the preferred embodiment of the invention a void filling material is interposed between one or more pairs of adjacent surfaces of the assembly. For example, such material can be included between the head mass and transducer **302**, and/or between transducer **302** and electrode **303**, and/or between electrode **303** and transducer **301**, and/or between transducer **301** and the tail mass. Further, if the head mass is not permanently bonded to the chamber exterior surface as described above, preferably void filling material is interposed between the adjacent surfaces of the head mass and the exterior chamber surface. Further, if the head mass is comprised of two portions as described relative to FIG. **10**, preferably void filling material is interposed between the adjacent surfaces of the two head mass portions. Suitable void filling material should be sufficiently compressible to fill the voids or surface imperfections of the adjacent surfaces while not being so compressible as to overly dampen the acoustic energy supplied by the transducers. Preferably the void filling material is a high viscosity grease, although wax, very soft metals (e.g., solder), or other materials can be used.

FIG. **11** is a graph that illustrates the sonoluminescence effect with a spherical cavitation sphere and six acoustic driver assemblies fabricated in accordance with the inven-

7

tion. The drivers were mounted as illustrated in FIG. 1. The sphere was fabricated from 17-4 stainless steel and had an outer diameter of 9.5 inches and an inner diameter of 8 inches. For the data shown in FIG. 11, the liquid within the chamber was acetone. During operation, the temperature of the acetone was -27.5°C . The driving frequency was 23.52 kHz, the driving amplitude was 59 V RMS, and the driving power was 8.8 watts. Two acoustic cycles are shown in FIG. 11. It will be appreciated that the data shown in FIG. 11 is only provided for illustration, and that the invention is not limited to this specific configuration.

As will be understood by those familiar with the art, the present invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. Accordingly, the disclosures and descriptions herein are intended to be illustrative, but not limiting, of the scope of the invention which is set forth in the following claims.

What is claimed is:

1. A cavitation system, comprising:

a spherical cavitation chamber, comprising:

an external surface defined by a spherical curvature; and

an internal surface, wherein said spherical cavitation chamber external surface and said spherical cavitation chamber internal surface define a spherical cavitation chamber wall;

an acoustic driver assembly coupled to said spherical cavitation chamber, comprising:

at least one piezo-electric transducer;

a tail mass adjacent to a first side of said at least one piezo-electric transducer;

a head mass comprising:

a first head mass portion and a second head mass portion, wherein a first end surface of said first head mass portion is brazed to said spherical cavitation chamber external surface, wherein said first end surface of said first head mass portion has a spherical curvature equivalent to said spherical curvature of said spherical cavitation chamber external surface, wherein a second end surface of said second head mass portion is adjacent to a second side of said at least one piezo-electric transducer, and wherein said second head mass portion includes a threaded hole; and

a first threaded means coupling said first and second head mass portions; and

a second centrally located threaded means coupling said tail mass, said at least one piezo-electric transducer and said second head mass portion together, wherein said second centrally located threaded means is threaded into said corresponding threaded hole in said second head mass portion.

2. The cavitation system of claim 1, wherein said at least one piezo-electric transducer is comprised of a first and a second piezo-electric transducer, wherein adjacent surfaces of said first and second piezo-electric transducers have the same polarity.

3. The cavitation system of claim 2, further comprising an electrode interposed between adjacent surfaces of said first and second piezo-electric transducers.

4. The cavitation system of claim 1, further comprising an insulating sleeve surrounding a portion of said second first centrally located threaded means, wherein said insulating sleeve is interposed between said second centrally located threaded means and said at least one piezo-electric transducer.

8

5. The cavitation system of claim 1, said second centrally located threaded means further comprising a corresponding threaded nut, wherein said threaded nut compresses said tail mass and said at least one piezo-electric transducer against said head mass.

6. The cavitation system of claim 1, wherein said tail mass and said head mass are of approximately equal mass.

7. The cavitation system of claim 1, wherein said tail mass and said head mass are comprised of stainless steel.

8. The cavitation system of claim 1, further comprising a void filling material interposed between said first surface of said head mass and said second side of said at least one piezo-electric transducer.

9. The cavitation system of claim 2, further comprising a void filling material interposed between said adjacent surfaces of said first and second piezo-electric transducers.

10. The cavitation system of claim 1, further comprising a void filling material interposed between said first side of said at least one piezo-electric transducer and said tail mass.

11. A cavitation system, comprising:

a spherical cavitation chamber, comprising:

an external surface defined by a spherical curvature; and

an internal surface, wherein said spherical cavitation chamber external surface and said spherical cavitation chamber internal surface define a spherical cavitation chamber wall;

an acoustic driver assembly coupled to said spherical cavitation chamber, comprising:

at least one piezo-electric transducer;

a tail mass adjacent to a first side of said at least one piezo-electric transducer;

a head mass comprising:

a first head mass portion and a second head mass portion, wherein a first end surface of said first head mass portion is diffusion bonded to said spherical cavitation chamber external surface, wherein said first end surface of said first head mass portion has a spherical curvature equivalent to said spherical curvature of said spherical cavitation chamber external surface, wherein a second end surface of said second head mass portion is adjacent to a second side of said at least one piezo-electric transducer and wherein said second head mass portion includes a threaded hole; and a first threaded means coupling said first and second head mass portions; and

a second centrally located threaded means coupling said tail mass, said at least one piezo-electric transducer and said second head mass portion together, wherein said second centrally located threaded means is threaded into said a corresponding threaded hole in said second head mass portion.

12. The cavitation system of claim 11, wherein said at least one piezo-electric transducer is comprised of a first and a second piezo-electric transducer, wherein adjacent surfaces of said first and second piezo-electric transducers have the same polarity.

13. The cavitation system of claim 12, further comprising an electrode interposed between adjacent surfaces of said first and second piezo-electric transducers.

14. The cavitation system of claim 11, further comprising an insulating sleeve surrounding a portion of said second centrally located threaded means, wherein said insulating sleeve is interposed between said second centrally located threaded means and said at least one piezo-electric transducer.

9

15. The cavitation system of claim 11, said second centrally located threaded means further comprising a corresponding threaded nut, wherein said threaded nut compresses said tail mass and said at least one piezo-electric transducer against said head mass.

16. The cavitation system of claim 11, wherein said tail mass and said head mass are of approximately equal mass.

17. The cavitation system of claim 11, wherein said tail mass and said head mass are comprised of stainless steel.

18. The cavitation system of claim 11, further comprising a void filling material interposed between said first surface

10

of said head mass and said second side of said at least one piezo-electric transducer.

19. The cavitation system of claim 12, further comprising a void filling material interposed between said adjacent surfaces of said first and second piezo-electric transducers.

20. The cavitation system of claim 11, further comprising a void filling material interposed between said first side of said at least one piezo-electric transducer and said tail mass.

* * * * *