



US00696887B2

(12) **United States Patent**
Hansen et al.

(10) **Patent No.:** **US 6,968,887 B2**
(45) **Date of Patent:** **Nov. 29, 2005**

(54) **WINDOW SHADE WITH A RATTLE-FREE GUIDANCE SYSTEM**

(75) Inventors: **Melf Hansen**, Baltmannsweiler (DE);
Matthias Maier, Esslingen (DE)

(73) Assignee: **BOS GmbH & Co. KG**, Ostfildern (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/602,274**

(22) Filed: **Jun. 24, 2003**

(65) **Prior Publication Data**

US 2004/0069425 A1 Apr. 15, 2004

(30) **Foreign Application Priority Data**

Jun. 24, 2002 (DE) 102 28 027

(51) **Int. Cl.⁷** **B60J 3/00**

(52) **U.S. Cl.** **160/370.22; 160/280; 160/41**

(58) **Field of Search** 160/370.22, 280,
160/274, 273.1, 271, 41; 296/97.8, 97.7,
296/37.16

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,741,609 A 12/1929 Brooks
1,904,968 A 4/1933 Bredin
2,491,765 A 12/1949 Rambo
3,489,200 A * 1/1970 Recchione 160/133

4,357,978 A * 11/1982 Keller et al. 160/41
4,467,853 A * 8/1984 Downey, Jr. 160/133
4,758,041 A * 7/1988 Labeur 296/152
4,792,178 A 12/1988 Kokx
5,201,810 A * 4/1993 Ojima et al. 160/265
5,404,926 A * 4/1995 Ojima et al. 160/280
5,482,104 A * 1/1996 Lichy 160/273.1
6,086,133 A * 7/2000 Alonso 296/97.8
6,095,231 A * 8/2000 Hahn 160/370.22
6,179,373 B1 1/2001 Bohm et al.
6,547,307 B2 * 4/2003 Schlecht et al. 296/97.4
6,598,929 B2 * 7/2003 Schlecht et al. 296/97.4
6,695,381 B2 * 2/2004 Schlecht et al. 296/97.4
6,739,375 B2 * 5/2004 Schlecht et al. 160/370.22
2002/0059989 A1 5/2002 Schlecht

FOREIGN PATENT DOCUMENTS

DE 1 905 163 U 11/1964
DE 3413966 A1 10/1985
DE 197 39 919 A1 3/1999
DE 198 03 129 A1 8/1999
DE 100 57 759 A1 6/2002
EP 1215063 A1 6/2002
FR 902518 9/1945

* cited by examiner


Primary Examiner—David Purol

(74) *Attorney, Agent, or Firm*—Leydig, Voit & Mayer, Ltd.

(57) **ABSTRACT**

In connection with a rear window shade, elastomeric profiled strips are assigned to the guide rails in which the pull rod is guided. The profiled strips are capable of holding the respective end of the pull rod in the guide rail in a substantially rattle-free manner.

19 Claims, 4 Drawing Sheets






Fig.1






Fig. 2





1

WINDOW SHADE WITH A RATTLE-FREE GUIDANCE SYSTEM

FIELD OF THE INVENTION

The present invention relates generally to window shades for motor vehicles.

BACKGROUND OF THE INVENTION

Rear window shades for motor vehicles are known in the prior art. Today, a rotatably seated winding shaft installed under the rear window ledge is usually a part of these shades. An edge of the shade web is fastened to the winding shaft and can be pulled out through a slit in the rear window ledge. Since the shade web is not rigid in itself, it is necessary for the shade web to be guided. To this end, guide rails, in which a pull rod arrangement is guided, extend at the sides of the side to be shaded. The pull rod arrangement is fastened to the front edge of the shade web, i.e. to that edge which travels the greatest distance when the window shade is extended and retracted.

The guide rails have an approximately C-shaped cross section, so that an undercut channel is created, which opens to the outside via a slit. The slits of the two guide rails face each other. The pull rod arrangement can include guide bodies that can be guided in the guide rails in such a way that the guide bodies cannot be pulled out at right angles to the longitudinal axis of the guide rail.

Although as a rule the guide bodies are pre-tensed by springs, and a spring motor force also acts on the pull rod arrangement which attempts to wind the shade web up on the winding shaft, such arrangements are not completely free of rattles. Force components, which are effective perpendicularly with respect to the plane defined by the extended window shade, are primarily only absorbed by the frictional connection which is used between the guide bodies and the actuating devices for transporting the pull rod arrangement along the guide rails. The forces can easily become larger, and the guide bodies can rattle in the transverse direction. The question as to whether this noise will develop depends on the position of the window shades, the installed position, the jarring being generated because of road conditions, and other factors.

Freedom from rattling cannot be completely assured by means of the previous solutions.

SUMMARY OF THE INVENTION

In view of the foregoing, an object of the invention is to produce a window shade for motor vehicles in which the pull rod arrangement can be guided in the guide rails without rattling.

As in the prior art, the pull rod arrangement of the novel window shade of the present invention is guided in one or two guide rails. The pull rod arrangement is moved along the guide rails with the aid of a transporting or actuating device.

To assure freedom from rattles, at least one elastic lip, which is elastically deformed by the pull rod arrangement, extends in the direction of the guide rail. The pull rod arrangement is pressed elastically and resiliently against an appropriate wall of the guide rail with the aid of the lip and with a comparatively large force. Because of this arrangement, vibrations in the vehicle cannot trigger rattling noises between the guide rail and the pull rod arrangement.

Moreover, the arrangement has the advantage that it covers the guide rail to a large extent. It is no longer

2

necessary to design the guide rail in a color corresponding to the color of the interior trim of the vehicle. It is sufficient if the color of the lip corresponds to the interior trim color, while the guide rail is a simple extruded profiled section, preferably made of aluminum.

So that the lip remains directly on the guide rail and cannot be pushed away by the elastic deformation, positive connecting mechanisms are preferably provided for connecting the lip with the guide rail. Positive connecting mechanisms are preferred over a material-to-material connection, because they are simpler to install and are permanent in every case.

The positively acting holding or connecting mechanism can comprise an undercut groove or a strip which, in cross section, is L- or Z-shaped. The lip has a corresponding fastening device.

The guide rail is preferably provided with a continuous flange strip for fastening the guide rail easily to the body. The guide rail can also have a flange strip on which a portion of the side trim can be fastened.

Where only a single lip is used, it is necessary to greatly deform the lip at the point where the pull rod arrangement is located, if the covering effect of the shiny portions of the guide rail is desired in addition to rattle prevention.

If a large deformation is not desired, it is practical to use two lips in place of a single lip, wherein the joint between the two lips follows the course of the slit.

The window shade in accordance with the invention can also be used in connection with windows wherein the width of the window changes along the path of the shade web. To this end, the length of the pull rod arrangement can be changed in a telescope-like manner. Changeability can be achieved if guide elements are provided which can be adjusted by means of a center piece. The cross section of the guide bodies is matched to the cross section of the channel in the guide rail.

Further developments are moreover the subject of dependent claims. In this connection, combinations of characteristics should also be considered to be claimed, which are not addressed by a specific exemplary embodiment.

An exemplary embodiment of the subject of the invention is represented in the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a rear view of a motor vehicle equipped with a rear window shade according to the invention.

FIG. 2 is a front view of the rear window shade of FIG. 1.

FIG. 3 is an enlarged partial section view of the rear window shade of FIG. 1 taken along a plane perpendicular to the longitudinal axis of the guide rail showing a single lip.

FIG. 4 is a view similar to FIG. 3 of an embodiment of the rear window shade of the invention having two lips.

In a schematic representation, FIG. 1 shows a rear view of a passenger car 1 with a roof 2, a trunk 3, as well as two C-pillars 4 and 5. A rear window opening 6 is located between the two C-pillars 4 and 5, which is bordered at the top by the rear roof edge 7 and on the bottom by the window ledge 8. A rear window glass 9 is seated in the rear window opening, glued in by means of window rubber strips, for example, in a known manner.

A shelf 10, extending horizontally between the lower window edge 8 and the rear seat back, not visible in the drawing, is located in the interior of the passenger car in front of the inside of the rear window glass 9. A straight outlet slit 11 extends in the shelf 10.

The outlet slit **11** is part of a rear window shade **12**, whose basic structure is represented in a greatly schematized way in FIG. 2.

The rear window shade **12** has a shade web **13**, which is shown in the extended state in FIG. 1. It has a trapezoidal shape in order to shade the rear window, whose entire shape is trapezoidal.

As shown in FIG. 2, a winding shaft **16** is rotatably seated underneath the shelf **10** with the aid of two angled brackets **14** and **15**. One edge of the shade web **13** is fastened on the winding shaft **16**. The other edge which is remote from the winding shaft **16**, is connected to a pull rod arrangement **17**.

The winding shaft **16** is pre-tensed in the direction of winding the shade web **13** by means of a spring motor, not visible, arranged inside the winding shaft **16**.

Two guide elements **19** of the pull rod arrangement **17**, which can be substantially displaced in a telescope-like manner, can be seen in FIG. 2. The telescope-like displaceable guide elements **19** run in two guide rails **20** and **21**, which extend inside of the vehicle on the other side of the lateral edges of the window **6**, so that they cannot be seen from the outside.

Thrust members, indicated in dashed lines at **22**, extend inside the two guide rails **20**, **21**. The guide rails **20** and **21** are continued below the shelf as guide tubes **23** and **24**, through which the guide rails **21** and **20** are connected with a gear **26** of a gear motor **27**. The thrust members **22** extend through the guide rails **20**, or **21**, as well as the connecting tubes **23** and **24**.

The thrust members **22** are linear flexible elements similar to Bowden cables, which are provided with a helically extending rib on the outside. With the aid of the ribs, the thrust members **22** mesh with an output gear wheel **28**, indicated in dashed lines. The free ends of the thrust members, which are **22** located inside the guide rails **20** and **21**, cooperate with the guide elements **19**.

FIG. 3 provides a detailed view, which shows the structure and design of the guide rail **21**, including the surrounding parts of the vehicle body. The structure of the guide rail **20**, as well as its installation in the vehicle body, is identical, so that the explanation with respect to the guide rail **21** will suffice for both.

A portion of an outer shell **31** of a vehicle body is visible in FIG. 3 that forms a flange at **32** on which the window glass **9** is glued by means of an elastomeric material **33**. The partial view in FIG. 3 furthermore shows a portion of the inner shell **34** of the vehicle body that is also provided with a flange **35**, which is connected with the flange **32**, for example, by spot welding.

Several tongues or clips **36** are notched out of the flange **35** and pushed up at substantially equidistant spacings from each other for fastening the guide rail **21**.

The guide rail **21** is an extruded profiled aluminum section, on which a flange **37** is formed and extends over the length of the guide rail **21**. The flange **37** lies flat on the tongues **36**. The flange **37** contains a bore **38** that is located at the height of each of the tongues **36** and is aligned with a bore **39** in the clip **36**. A blind rivet **41** extends through the bores by means of which the flange **37** is positively connected with the clip **36**. In this way, the guide rail **21** is connected with the vehicle body at several fastening points along a lateral edge of the rear window **9**.

Starting at the flange **37**, the profile of the guide rail **21** forms two legs **42** and **43**, which delimit a partially cylindrical guide groove **44** between them. Because of longitudinal strips **45** and **46** being formed, a slit **47** leading to the

outside is created, whose clearance is less than the diameter of the interior of the guide groove **44**.

Following, the strip **46**, the leg **42** makes a transition into a flange **48**, which extends approximately perpendicular with respect to the surface of the window glass **9**.

The flange **48** is used as a fastening flange for a portion of interior trim **49**.

The leg **43** also continues past the guide groove **44** and forms a flange **51**, which runs parallel with the flange **48** and terminates in the center of a flange **52**. The flanges **51** and **52** constitute a T-shaped profiled section.

The T-shaped profiled section consisting of the flanges **51** and **52** is used for positively holding an elastomeric profiled strip **53**, which forms a lip **54** made of an elastomeric material. At its root, the lip **54** makes a transition into a thickened section **55** containing a T-shaped groove **56** that fits positively over the profiled section made by the flanges **51** and **52**. A further lip **57** exists adjoining the thickened section **55**. The lip **57** rests sealingly against the window glass **9** in order to close off any gap that may exist without crowding occurring between the window glass **9** and the thickened area **55**.

The lip **54** (the cross sectional profile of which is visible in FIG. 3) extends over the entire length of the guide rail **21**, namely at least from the upper edge **7** of the rear window up to the outlet slit **11**. The lip **54** covers the slit **47** of the guide rail **21**, and the edge of the lip **54** remote from the window glass **9** rests on the lateral trim **49**.

The guide element **19** has an essentially cylindrical shaft **58** that can be displaced in a telescope-like manner arranged in a center piece of the pull rod arrangement **17**. On its free end, the cylindrical shaft **58** has a ball-shaped or cylindrical guide body **59** that slidingly moves in the guide groove **44**.

Since the lip **54** completely covers the gap between the leg **43** and the edge of the lateral trim **49**, the lip **54** is maintained elastically open by the cylindrical shaft **58** at the point where the cylindrical shaft **58** is located. Because of its inherent elasticity, however, the lip **54** again rests on the lateral trim **49**, i.e. above and below the shaft **58**, in the further course of the guide rail **21**. The lip **54** is raised only in the vicinity of the shaft **58**. Because of the inherent elasticity of the lip **54**, a force is continuously exerted on the shaft **58** and, in the illustrated embodiment, the force tends to push the shaft **58** away from the window glass **9** in the direction toward the oppositely located rim area of the guide groove **44**. The pre-tensioning that occurs in the course of this is so great that vibrations in the pull rod arrangement **11** are incapable of lifting the guide body **59** off the wall area against which the guide body **59** is being pressed as a result of the inherent elasticity of the lip **54**.

The shade otherwise operates in such a way that the schematically indicated thrust members **22** are pushed forward in the guide rails **20** and **21** when the drive motor **27** is started. The thrust members therefore push the guide bodies **59** of the pull rod arrangement **17** ahead of themselves with the guide bodies **59** being steadily pushed against the wall of the guide groove **44** by the lip **54** during their entire travel.

If the motor **27** is put into operation in the opposite direction, the thrust members **22** are retracted out of the guide rails **20** and **21**. The pull rod arrangement **17** follows this retrograde movement because of the force which the spring motor seated in the winding shaft **16** transmits to the pull rod arrangement **17** via the shade web **13**.

A slightly modified exemplary embodiment is shown in FIG. 4, which essentially differs from the exemplary embodiment in FIG. 3 in that in place of one profiled strip with a lip **54** two profiled strips **60** and **61** are used, which

5

cause two lips **63** and **64** to be created. To the extent that components appear in the exemplary embodiment of FIG. **4** which functionally correspond to components in the exemplary embodiment of FIG. **3**, the same reference symbols are being used without again providing a detailed description.

While in the exemplary embodiment of FIG. **3** the flange **37** extends centered between the two legs **42** and **43**, the flange **37** is bent at right angles in the exemplary embodiment of FIG. **4** and constitutes an extension of the leg **42**. The free end of the leg **42** terminates in a strip **65** angled in an L-shape, which is used as a holding member for the elastic profiled strip **61**. A leg **66**, which is bent in a Z-shape and terminates in a support flange **67** for the lateral trim **49**, extends from approximately the center of the guide groove **44**. An L-shaped support groove **68** is created between the leg **66** and the L-shaped leg **65**, which effectively secures the elastomeric profiled strip **61**. The profiled strip **61** runs around the L-shaped leg **65** and into the L-shaped groove **68**.

In the relaxed state, the free edge of the lip **65** extends approximately along the center of the guide groove **44**.

The other leg **43** also terminates in a strip **69** angled in an L-shape onto which the profiled strip **60** with a complementary groove **71** is pushed. The profiled strip moreover constitutes the lip **56** resting against the inside of the rear window glass **9**. In the relaxed state, i.e. if the shaft **58** is not at the appropriate location between the two lips **63** and **64**, the two lips **63** and **64** just rest level against each other.

Freedom from rattling is also assured by the large pre-tensioning force exerted by the two lips **63** and **64**. At the contact point with the shaft **58**, the two lips **63** and **64** act as friction dampers, and the two lips **63** and **64** damp vibrations at this location.

It should finally be noted that the two elastomeric profiled strips **60** and **61**, which run in the extension of the surface defined by the inside of the lateral trim **49**, form a continuous surface when the lip **63** or **64** is relaxed.

As in the previous example, the guide rails **21** and the guide groove **44** are thereby covered. With the aid of the profiled strips **60** and **61**, as well as the profiled strip constituting the lip **53**, it is possible to continue the color of the lateral trim **49**. The color of the guide rail itself is no longer important because it no longer makes an interfering appearance.

In connection with a rear window shade, elastomeric profiled strips are assigned to the guide rails in which the pull rod is guided. The profiled strips are capable of holding the respective end of the pull rod in the guide rail in an effectively rattle free manner.

What is claimed is:

1. A window shade for motor vehicles comprising:
 - a winding shaft mountable within an automobile adjacent a window of the automobile, a shade web having an edge fastened to the winding shaft,
 - a pull rod attached to the shade web at a location which is remote from where the shade web is connected to the winding shaft for movement with the window shade web between open and closed positions, said pull rod arrangement having an end extending laterally outwardly of said web,
 - at least one guide rail for receiving said outwardly extending end of said pull rod for guiding movement of the pull rod along the guide rail, and
 - at least one elastic lip mounted along the guide rail in contacting elastically deformed relation to the pull rod

6

for biasing and maintaining the pull rod into continuous rattle-free contact with the guide rail.

2. The window shade according to claim **1** wherein the lip is formed on an elastic profiled strip.

3. The window shade according to claim **1** wherein the guide rail is undercut in such a way that it forms a guide groove extending in the longitudinal direction that is accessible from the outside through a continuous slit extending in the longitudinal direction and wherein the clearance of the slit is less than the width of the guide groove measured in the same direction.

4. The window shade according to claim **1** wherein the guide groove has a circular cross section or a square cross section.

5. The window shade according to claim **1** wherein the guide rail includes a fastening flange that extends over substantially the entire length of the guide rail.

6. The window shade according to claim **1** wherein the guide rail is made from an extruded profiled element.

7. The window shade according to claim **1** wherein the guide rail includes a holding arrangement for fastening the elastic lip in a positive manner.

8. The window shade according to claim **7** wherein the holding arrangement for fastening the elastic lip comprises an undercut groove.

9. The window shade according to claim **1** wherein the lip has a corresponding fastening arrangement for connecting the lip positively with the guide rail.

10. The window shade according to claim **1** wherein the guide rail includes a flange for receiving a portion of a lateral trim of a motor vehicle.

11. The window shade according to claim **1** wherein two lips are provided.

12. The window shade according to claim **11** wherein the two lips directly touch each other.

13. The window shade according to claim **1** wherein said pull rod is moveable in a slit in said guide rail, and said lip is configured to cover the slit while allowing movement of said pull rod along said guide rail.

14. The window shade according to claim **1** wherein the length of the pull rod arrangement can be adjusted in a telescope-like manner.

15. The window shade according to claim **1** wherein the pull rod has a guide body on at least one end that works together with the guide rail.

16. The window shade according to claim **1** wherein the guide rail is connected with the pull rod via a neck and wherein measured in the direction transverse to a longitudinal extension of the guide rail the neck has a lesser diameter than the guide body.

17. The window shade according to claim **1** wherein the guide rail has a circular or polygonal cross section.

18. The window shade according to claim **1** wherein the guide rail has larger dimensions in the longitudinal direction than in the transverse direction such that the guide body cannot be rotated with respect to the guide rail.

19. The window shade according to claim **7** wherein the holding arrangement for fastening the elastic lip comprises a strip that has a T-shaped cross section.

* * * * *