

US006974280B2

(12) **United States Patent**
Satran et al.

(10) **Patent No.:** **US 6,974,280 B2**
(45) **Date of Patent:** **Dec. 13, 2005**

(54) **ROTARY CUTTING TOOL**

(75) Inventors: **Amir Satran**, Kfar Vradim (IL); **Yaron Eisen**, Kfar Vradim (IL)

(73) Assignee: **Iscar Ltd.**, Tefen (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/002,180**

(22) Filed: **Dec. 5, 2001**

(65) **Prior Publication Data**

US 2002/0066352 A1 Jun. 6, 2002

(30) **Foreign Application Priority Data**

Dec. 5, 2000 (IL) 140104

(51) **Int. Cl.**⁷ **B23C 5/02**

(52) **U.S. Cl.** **407/42; 407/113**

(58) **Field of Search** 407/42, 113, 114;
83/839, 847, 853, 955

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,729,050 A * 9/1929 Olson 407/61
3,828,409 A * 8/1974 Aspinwall 407/61

4,729,697 A * 3/1988 Lacey 407/42
5,123,786 A * 6/1992 Yates et al. 407/38
5,529,440 A * 6/1996 Schmidt 407/113
5,647,263 A * 7/1997 Wildey 83/835
5,685,670 A * 11/1997 Satran 407/42
5,718,540 A * 2/1998 Satran et al. 407/42
6,074,137 A * 6/2000 Betman et al. 407/103
6,126,366 A * 10/2000 Lundblad 407/102
6,167,958 B1 * 1/2001 Lynde 166/55.6
6,227,772 B1 * 5/2001 Heinloth et al. 407/113
6,238,146 B1 * 5/2001 Satran et al. 407/113
6,527,486 B2 * 3/2003 Wiman et al. 408/188
6,810,783 B1 * 11/2004 Larose 83/840

FOREIGN PATENT DOCUMENTS

EP 0 125 568 * 11/1984
EP 0 505 574 B1 9/1992 B23C 5/22
WO WO 00/02693 * 1/2000

* cited by examiner



Primary Examiner—Kenneth E. Peterson

(74) *Attorney, Agent, or Firm*—Womble Carlyle

(57) **ABSTRACT**

A rotary cutting tool having the general form of a circular disk with cutting inserts secured tangentially to the circumference of the tool's body, for metal machining in general and for machining cam lobes. The cutting inserts have concave side surfaces and concave cutting edges.

13 Claims, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 6




FIG. 7

1

ROTARY CUTTING TOOL**FIELD AND BACKGROUND OF THE INVENTION**

This invention relates to rotary cutting tools having a tool body the general form of a circular disk with cutting inserts secured tangentially to the circumference of the tool body, for metal machining in general and for machining cam lobes of camshafts of internal combustion engines in particular. Such cutting tools normally employ groups of two or more cutting inserts arranged in a circumferentially staggered formation. The individual cutting edges of the cutting inserts in each group are generally oriented at non-zero lead angles. Consequently, each cutting insert has a non-zero axial component cutting force acting on it. Since the cutting inserts are staggered, the cutting tool is unbalanced with respect to the axial component cutting forces.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a cutting tool of the above general nature that replaces each group of cutting inserts arranged in a staggered formation by a single indexable cutting insert giving rise to a balanced cutting tool with respect to the axial component cutting forces.

In accordance with the present invention there is provided a rotary cutting tool comprising:

a tool body in the form of a circular disk having a center and a periphery, with an axis of rotation passing through the center of the disk and a plurality of chip clearance recesses opening outwardly from and spaced angularly around the disk periphery, each chip clearance recess having a leading end and a trailing end;

a plurality of insert receiving pockets, each insert receiving pocket having an associated chip clearance recess and comprising a tangentially extending pocket base having a leading end and a trailing end, the leading end of the pocket base being adjacent the trailing end of the associated chip clearance recess and the trailing end of the pocket base being connected to a generally radially extending pocket rear surface;

a plurality of indexable cutting inserts, each cutting insert comprising an upper surface, a lower surface and a peripheral side surface therebetween, the peripheral side surface comprising four component side surfaces, each component side surface being joined to an adjacent side surface by a side corner, an opposite pair of the component side surfaces forming front and rear component side surfaces, each component side surface meeting the upper and lower surfaces at upper and lower component cutting edges, respectively, at least outer portions of each upper and lower component cutting edge extending generally inwardly from adjacent side corners and at least outer portions of each component side surface extending generally inwardly from adjacent side corners,

each cutting insert being removably retained in a given insert receiving pocket, wherein the lower surface of the cutting insert abuts the tangentially extending pocket base, the rear component side surface of the cutting insert abuts at two spaced apart abutment surfaces of the radially extending pocket rear surface, the front component side surface forming a rake surface and the upper component cutting edge of the front component side surface forming an operative cutting edge with outer portions of the operative cutting edge forming equally leading portions thereof.

2

In order to secure the cutting inserts in position, the pocket base has a radially extending threaded bore and each cutting insert of the plurality of cutting inserts has a through bore extending between the upper and lower surfaces and containing midpoints thereof, and each cutting insert is secured by a screw extending through the through bore and tightened into the threaded bore.

In accordance with a preferred embodiment of the present invention, each upper and lower component cutting edge is generally concave in form and each component side surface is generally concave in form extending inwardly from adjacent side corners.

Preferably, the upper and lower surfaces of the cutting insert each have a flat central portion for abutting the pocket base.

Further preferably, the upper and lower component cutting edges and the component side surfaces are divided into three portions, two outer portions and an inner portion, and the cutting insert is thicker in the region of the inner portion of the upper and lower component cutting edges than in the region of the outer portion thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

FIG. 1 is a perspective view of a rotary cutting tool in accordance with the present invention;

FIG. 2 is a perspective top view of a cutting insert receiving pocket in the rotary cutting tool shown in FIG. 1;

FIG. 3 is a perspective view of a cutting insert retained in the rotary cutting tool in accordance with the present invention;

FIG. 4 is a top view of the cutting insert shown in FIG. 3;

FIG. 5 is a top view of a cutting insert receiving pocket in the rotary cutting tool shown in FIG. 1 with a cutting insert retained therein.

FIG. 6 is a cross section taken along the line VI—VI in FIG. 5; and

FIG. 7 is a front view of the cutting insert of the invention showing a component side surface having a chip-forming groove.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Attention is drawn to the drawings in general and to FIG. 1 in particular, showing a rotary cutting tool in accordance with the present invention. The rotary cutting tool **10** comprises a tool body **12** in the form of a circular disk having a center **14** and a periphery **16**. The rotary cutting tool **10** has an axis of rotation **A** that passes through the center **14** of the tool body **12**, the axis of rotation defining the tool's plane of rotation **P**. The tool body **12** has a plurality of chip clearance recesses **18** opening outwardly from and spaced angularly around the tool body **12** periphery **16**, each chip clearance recess having a leading end **20** and a trailing end **22**. It will be appreciated that the leading end **20** precedes the trailing end **22** with respect to the direction of rotation **R** of the rotary cutting tool **10**.

Associated with each chip clearance recesses **18** is an insert receiving pocket **24**. All the insert receiving pockets are at the same radial distance from the center **14** of the tool body **12**. Each insert receiving pocket **24** comprises a tangentially extending pocket base **26** that is parallel to the axis of rotation **A**, the pocket base having a leading end **28**

and a trailing end **30**. The leading end **28** of the pocket base being adjacent the trailing end **22** of the associated chip clearance recess **18**. The trailing end **30** of the pocket base **26** being connected to a generally radially extending, substantially upright, pocket rear surface **32**. It will be appreciated that the term radially extending, is defined with respect to the axis of rotation A, whereas the term upright, is defined relative to the pocket base **26**. The pocket rear surface **32** and the pocket base **26** are separated by a stress relief groove **34**. It will be appreciated that when a workpiece (e.g., cam lobe) is machined, a leading portion of a given part of the cutting tool **10** will reach the workpiece before the trailing portion of that given part, as the cutting tool rotates.

As can be seen in the figures, each chip clearance recess **18** has a sloping chip deflecting surface **36** that slopes upwardly from the trailing end **22** of the chip clearance recess **18** to the leading end **20** thereof where it joins a circumferential portion **38** at the periphery **16** of the tool body **12**. As can be clearly seen in FIGS. 2 and 6, the chip clearance recess **18** together the associated insert receiving pocket **24** form a peripheral recess in the periphery **16** of the tool body **12**. The circumferential portions **38** on either side of such a peripheral recess belong to the circumference of the tool body, which would be a complete cylindrical surface if it were not for the presence of the peripheral recesses.

In each insert receiving pocket **24** there is retained an indexable cutting insert **40**. As depicted in FIGS. 1 and 5, all the cutting inserts are symmetric about a common plane of rotation P. Furthermore, each of the cutting inserts **40** in the rotary cutting tool **10** axially protrudes (i.e., protrudes along the rotary axis A) on both sides of the tool body **12** in a top view. And unlike cutting inserts arranged in the prior art circumferentially staggered formations, all the cutting inserts **40** in rotary cutting tool **10** are aligned with one another in the axial direction, each component side surface of one cutting insert being axially aligned with a corresponding component side surface of each of the other cutting inserts. Each cutting insert **40** comprises an upper surface **42**, a lower surface **44** and a peripheral side surface **46** therebetween. The upper surface **42** and lower surfaces **44** each have a flat central portion **48**. The peripheral side surface **46** comprises four component side surfaces **50**, **52**, **54**, **56**, each component side surface being joined to an adjacent side surface by a side corner **58**, **60**, **62**, **64**. An opposite pair of component side surfaces form front **50** and rear **54** component side surfaces. In terms of the rotation of the rotary cutting tool **10**, the front component side surface **50** is situated at the leading end of the cutting insert **40**, whereas the rear component side surface **54** is situated at the trailing end of the cutting insert **40**. Similarly, the side corners **58**, **64** adjacent the front component side surface **50** are leading side corners. Furthermore, each cutting insert **40** has another opposite pair of its component side surface **52**, **56** symmetrical with respect to the plane of rotation P of the cutting tool **10** and therefore the leading side corners **58**, **64** are equally leading side corners. Each component side surface **50**, **52**, **54**, **56** meets the upper surface at upper component cutting edges **66'**, **68'**, **70'**, **72'**. Likewise, each component side surface **50**, **52**, **54**, **56** meets the lower surface at lower component cutting edges **66''**, **68''**, **70''**, **72''**.

As seen in FIG. 3 and especially in the top view of the cutting insert **40** in FIG. 4, each upper component cutting edge **66'**, **68'**, **70'**, **72'** and each lower component cutting edge **66''**, **68''**, **70''**, **72''** is generally concave in form and each component side surface **50**, **52**, **54**, **56** is generally concave in form extending inwardly from adjacent side corners **58**,

60, **62**, **64**. By generally concave is meant herein that the upper and lower component cutting edges and the component side surfaces could be, but do not have to be, strictly concave in the sense that portions thereof may be straight as long as they extend inwardly. With reference to FIG. 4, it will be noted that the operative cutting edge **66'** are linear sections extending inwardly from adjacent side corners **58**, **64** to the inner portion **66_i'** and the inner portion **66_i'** is arcuate. In accordance with the definition given herein, the upper component cutting edge **66'** is generally concave. In a similar manner all the upper component cutting edges and all the lower component cutting edge and the component side surfaces are generally concave and divided into three portions with the same geometry as the upper component cutting edge **66'**.

The cutting insert **40** is removably retained in the insert receiving pocket **24** with the lower surface **44** of the cutting insert **40** abutting the tangentially extending pocket base **26** and two spaced apart abutment regions **74** of the rear component side surface **54** abutting the radially extending pocket rear surface **32** at two spaced apart abutment surfaces **76** that substantially match in shape the abutment regions **74** of the rear component side surface **54** of the cutting insert **40**. It should be noted that the two spaced apart abutment regions **74** of the rear component side surface **54** are linear sections extending inwardly from adjacent side corners **60**, **62**, as described above with respect to the upper component cutting edge **66'**. As seen in the figures, however, the rear component side surface **54** is the only component side surface abutted by the insert receiving pocket **24**.

With the cutting insert **40** retained in the insert receiving pocket **24**, the front component side surface **50** forms a rake surface of the cutting insert **40** and the upper component cutting edge **66'** of the front component side surface **50** forms an operative cutting edge of the cutting insert **40**, with the outer portions **66_o'** forming leading portions of the operative cutting edge **66'**. It should be noted that the two outer portions **66_o'** extend linearly inwardly with the same slope. It will be appreciated that cutting forces acting on the operative cutting edge **66'** can be resolved into two mutually perpendicular component cutting forces, an axial and a tangential component. Since the two outer portions **66_o'** extend linearly inwardly with the same slope and since they lead by equal amounts, the axial component cutting forces acting on the two outer portions **66_o'** will be equal in magnitude but opposite in direction, and will therefore cancel each other out, giving rise to a balanced rotary cutting tool **10**.

The pocket base **26** has a radially extending threaded bore **76** and the cutting insert **40** has a through bore **80** extending between the upper **42** and lower **44** surfaces. The through bore **80** is centrally located and therefore contains the midpoints of the upper **42** and lower **44** surfaces. The cutting insert **40** is removably retained in the insert receiving pocket **24** by a screw **82** which extends through the through bore **80** and is tightened into the threaded bore **76**.

It will be appreciated that in order to machine a straight line on a section of a workpiece such as a cam lobe, the operative cutting edge has to lie on the cylindrical circumference of the tool body **12** and therefore the cutting insert **40** has to be thicker in the region of the inner portion **66_i'** than in the region of the outer portion **66_o'** of the operative cutting edge **66'**. The same thickness relationship holds for all the component cutting edges. For a cutting insert having an average thickness of about 6 millimeters, a side length of about 20 millimeters with the central portion of the component side surface recessed by about 3 millimeters and for

5

a tool body having a diameter of approximately 30 centimeters, the difference in thickness between the inner and outer portions of the cutting insert will be approximately 0.1 millimeter.

As indicated in FIG. 7, the region of the inner portion 66' of the cutting insert 40 has a thickness T which is slightly greater than the thickness t of the outer portions 66_o' of the operative cutting edge 66'.

The cutting insert of the preferred embodiment is completely indexable in the sense that all four upper component cutting edges and all four lower component cutting edges can be used as operative cutting edges.

Although not an essential feature of the present invention, it will be appreciated that the component side surfaces can include chip forming elements such as chip forming grooves and chip deflectors. As a non-limiting example, a component side surface of the cutting insert 40 of the invention can be provided with a chip forming groove 84 as shown in a front view of the cutting insert in FIG. 7.

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications can be made without departing from the spirit or scope of the invention as hereinafter claimed.

What is claimed is:

1. A rotary metal cutting tool comprising:

a tool body in the form of a circular disk having a center and a periphery, with an axis of rotation passing through the center of the disk and a plurality of chip clearance recesses opening outwardly from and spaced angularly around the disk periphery, each chip clearance recess having a leading end and a trailing end, said axis of rotation defining a plane of rotation;

a plurality of insert receiving pockets, each insert receiving pocket having an associated chip clearance recess and comprising a tangentially extending pocket base parallel to said axis of rotation, said pocket base having a leading end and a trailing end, the leading end of the pocket base being adjacent the trailing end of the associated chip clearance recess and the trailing end of the pocket base being connected to a generally radially extending pocket rear surface;

a plurality of indexable cutting inserts, each cutting insert comprising an upper surface, a lower surface and a peripheral side surface therebetween, the peripheral side surface comprising four component side surfaces, each component side surface being joined to an adjacent side surface by a side corner, a first opposite pair of the component side surfaces forming front and rear component side surfaces, each component side surface meeting the upper and lower surfaces at upper and lower component cutting edges, respectively, at least outer portions of each upper and lower component cutting edge extending generally inwardly from adjacent side corners and at least outer portions of each component side surface extending generally inwardly from adjacent side corners,

each cutting insert being removably retained in a given insert receiving pocket, wherein the lower surface of the cutting insert abuts the tangentially extending pocket base, the rear component side surface of the cutting insert abuts the radially extending pocket rear surface at two spaced apart abutment surfaces, the front component side surface forming a rake surface and the upper component cutting edge of the front component side surface forming an operative cutting edge.

6

2. The rotary metal cutting tool according to claim 1, wherein the pocket base has a radially extending threaded bore and each cutting insert of the plurality of cutting inserts has a through bore extending between the upper and lower surfaces and containing midpoints thereof, and each cutting insert is removably retained by a screw extending through the through bore and tightened into the threaded bore.

3. The rotary metal cutting tool according to claim 1, wherein each upper and lower component cutting edge is generally concave in form and each component side surface is generally concave in form extending inwardly from adjacent side corners.

4. The rotary metal cutting tool according to claim 1, wherein the upper and lower surfaces of the cutting insert each have a flat central portion.

5. The rotary metal cutting tool according to claim 1, wherein the upper and lower component cutting edges and the component side surfaces are divided into three portions, two outer portions and an inner portion, the two outer portions being linear sections and the inner portion being arcuate and wherein the cutting insert is thicker in the region of the inner portion than in the region of the outer portion.

6. The rotary metal cutting tool according claim 1, wherein the upper and lower component cutting edges and the component side surfaces are divided into three portions, two outer portions and an inner portion, and the cutting insert is thicker in the region of the inner portion of the upper and lower component cutting edges than in the region of the outer portion thereof.

7. The rotary metal cutting tool according claim 1, wherein:

each cutting insert has a second opposite pair of its component side surfaces symmetrical with respect to said plane of rotation, and

each cutting insert axially protrudes on both sides of the tool body.

8. A rotary metal cutting tool comprising:

a tool body in the form of a circular disk having a center and a periphery, with an axis of rotation passing through the center of the disk, said axis of rotation defining a plane of rotation;

a plurality of insert receiving pockets spaced angularly around the disk periphery, each insert receiving pocket comprising a tangentially extending pocket base and a pocket rear surface; and

a plurality of indexable cutting inserts, each cutting insert removably retained in an insert receiving pocket, each cutting insert comprising an upper surface, a lower surface which abuts the tangentially extending pocket base, and a peripheral side surface therebetween, the peripheral side surface comprising at least four component side surfaces,

wherein:

each component side surface is joined to an adjacent side surface by a side corner;

each component side surface meets the upper and lower surfaces at upper and lower component cutting edges; and

each upper and lower component cutting edge is generally concave in form and each component side surface is generally concave in form extending inwardly from adjacent side corners;

wherein each cutting insert has:

a first opposite pair of its component side surfaces forming front and rear component side surfaces, the rear component side surface abutting the pocket rear surface at two spaced apart abutment surfaces; and

7

a second opposite pair of its component side surfaces symmetrical with respect to said plane of rotation, and wherein each cutting insert axially protrudes on both sides of the tool body.

9. The rotary metal cutting tool according to claim 8, wherein the pocket base has a radially extending threaded bore and each cutting insert of the plurality of cutting inserts has a through bore extending between the upper and lower surfaces and containing midpoints thereof, and each cutting insert is removably retained by a screw extending through the through bore and tightened into the threaded bore.

10. The rotary metal cutting tool according to claim 8, wherein:

all the cutting inserts are aligned with one another in an axial direction along the axis of rotation, each component side surface of one cutting insert being axially

8

aligned with a corresponding component side surface of each of the other cutting inserts.

11. The rotary metal cutting tool according to claim 8, wherein the upper and lower surfaces of the cutting insert each have a flat central portion.

12. The rotary metal cutting tool according to claim 1, wherein all the cutting inserts are aligned with one another in an axial direction along the axis of rotation, each component side surface of one cutting insert being axially aligned with a corresponding component side surface of each of the other cutting inserts.

13. The rotary metal cutting tool according to claim 8, wherein the rear component side surface is the only component side surface abutted by the insert receiving pocket.

* * * * *