

US006997090B2

(12) **United States Patent**
Gass et al.

(10) **Patent No.:** **US 6,997,090 B2**
(45) **Date of Patent:** **Feb. 14, 2006**

(54) **SAFETY SYSTEMS FOR POWER EQUIPMENT**

(75) Inventors: **Stephen F. Gass**, Wilsonville, OR (US); **David A. Fanning**, Vancouver, WA (US); **J. David Fulmer**, Tualatin, OR (US); **David S. D'Ascenzo**, Portland, OR (US); **Jonathan N. Betts-LaCroix**, Chatsworth, CA (US); **Robert L. Chamberlain**, Raleigh, NC (US); **Joel F. Jensen**, Redwood City, CA (US); **Andrew L. Johnston**, Redwood City, CA (US); **Sung H. Kim**, Palo Alto, CA (US); **Anwyl M. McDonald**, Palo Alto, CA (US); **Benjamin B. Schramm**, Los Gatos, CA (US)

(73) Assignee: **SD3, LLC**, Wilsonville, OR (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 105 days.

(21) Appl. No.: **10/785,361**

(22) Filed: **Feb. 23, 2004**

(65) **Prior Publication Data**

US 2004/0163514 A1 Aug. 26, 2004

Related U.S. Application Data

(63) Continuation of application No. 10/215,929, filed on Aug. 9, 2002, now abandoned

(60) Provisional application No. 60/312,141, filed on Aug. 13, 2001.

(51) **Int. Cl.**

B26D 5/00 (2006.01)
B26D 7/24 (2006.01)
B27B 5/18 (2006.01)

(52) **U.S. Cl.** **83/58**; 83/62.1; 83/72; 83/471.3; 83/477.1; 83/477.2; 83/473; 83/488; 83/490; 83/581; 83/DIG. 1; 192/129 R; 192/138; 30/388; 144/382; 144/356; 144/154.5

(58) **Field of Classification Search** 192/192 R, 192/133, 148, 144, 137, 138; 403/2, 28; 411/2, 411/89, 390; 385/142; 144/356, 384, 391, 144/427, 154.5; 292/DIG. 66; 307/116, 142, 307/131; 337/190, 237, 239, 1, 5, 10, 17, 337/70, 140, 148, 170; 361/1, 124; 340/590, 340/680; 83/DIG. 1, 58, 62.1, 526, 72, 76.8, 83/471.2, 397, 473, 477.1, 485, 487, 490, 83/491, 522.12, 544, 546, 564, 581, 590, 83/665, 471.3; 30/382, 381
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

146,886 A 1/1874 Doane et al.
162,814 A 5/1875 Graves et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CH 297525 6/1954
DE 76186 8/1921

(Continued)

OTHER PUBLICATIONS

Gordon Engineering Corp., Product Catalog, Oct. 1997, pp. cover, 1,3 and back, Brookfield, Connecticut, US.
U.S. Provisional Patent Appl. No. 60/157,340, filed Oct. 1, 1999, entitled "Fast-Acting Safety Stop."

(Continued)


Primary Examiner—Boyer D. Ashley

(74) *Attorney, Agent, or Firm*—SD3

(57) **ABSTRACT**

A saw with a safety system is disclosed. The safety system includes a detection system adapted to detect contact between a person and a blade while the blade is moving. The safety system further includes a brake system adapted to engage the blade and to stop the blade when the detection system detects contact between the person and the blade.

20 Claims, 2 Drawing Sheets



U.S. PATENT DOCUMENTS					
261,090 A	7/1882	Grill	2,261,696 A	11/1941	Ocenasek
264,412 A	9/1882	Kuhlmann	2,265,407 A	12/1941	Tautz
299,480 A	5/1884	Kuhlmann et al.	2,286,589 A	6/1942	Tannewitz
302,041 A	7/1884	Sill	2,292,872 A	8/1942	Eastman
307,112 A	10/1884	Groff	2,299,262 A	10/1942	Uremovich
509,253 A	11/1893	Shields	2,312,118 A	2/1943	Neisewander
545,504 A	9/1895	Hoover	2,313,686 A	3/1943	Uremovich
869,513 A	10/1907	Pfeil	2,328,244 A	8/1943	Woodward
941,726 A	11/1909	Pfalzgraf	2,352,235 A	6/1944	Tautz
997,720 A	7/1911	Troupenat	2,377,265 A	3/1945	Rady
1,037,843 A	9/1912	Ackley	2,425,331 A	8/1947	Kramer
1,050,649 A	1/1913	Harrold et al.	2,434,174 A	1/1948	Morgan
1,054,558 A	2/1913	Jones	2,466,325 A	4/1949	Ocenasek
1,074,198 A	9/1913	Phillips	2,496,613 A	2/1950	Woodward
1,082,870 A	12/1913	Humason	2,509,813 A	5/1950	Dineen
1,101,515 A	6/1914	Adam	2,517,649 A	8/1950	Frechtmann
1,126,970 A	2/1915	Folmer	2,518,684 A	8/1950	Harris
1,132,129 A	3/1915	Stevens	2,530,290 A	11/1950	Collins
1,148,169 A	7/1915	Howe	2,554,124 A	5/1951	Salmont
1,154,209 A	9/1915	Rushton	2,572,326 A	10/1951	Evans
1,205,246 A	11/1916	Mowry	2,590,035 A	3/1952	Pollak
1,228,047 A	5/1917	Reinhold	2,593,596 A	4/1952	Olson
1,240,430 A	9/1917	Erickson	2,623,555 A	12/1952	Eschenburg
1,244,187 A	10/1917	Frisbie	2,625,966 A	1/1953	Copp
1,255,886 A	2/1918	Jones	2,626,639 A	1/1953	Hess
1,258,961 A	3/1918	Tattersall	2,661,777 A	12/1953	Hitchcock
1,311,508 A	7/1919	Harrold	2,661,780 A	12/1953	Morgan
1,324,136 A	12/1919	Turner	2,675,707 A	4/1954	Brown
1,381,612 A	6/1921	Anderson	2,678,071 A	5/1954	Odlum et al.
1,397,606 A	11/1921	Smith	2,690,084 A	9/1954	Van Dam
1,427,005 A	8/1922	McMichael	2,695,638 A	11/1954	Gaskell
1,430,983 A	10/1922	Granberg	2,704,560 A	3/1955	Woessner
1,464,924 A	8/1923	Drummond	2,711,762 A	6/1955	Gaskell
1,465,224 A	8/1923	Lantz	2,722,246 A	11/1955	Arnoldy
1,496,212 A	6/1924	French	2,731,049 A	1/1956	Akin
1,511,797 A	10/1924	Berghold	2,736,348 A	2/1956	Nelson
1,526,128 A	2/1925	Flohr	2,758,615 A	8/1956	Mastriforte
1,527,587 A	2/1925	Hutchison	2,785,710 A	3/1957	Mowery, Jr.
1,551,900 A	9/1925	Morrow	2,786,496 A	3/1957	Eschenburg
1,553,996 A	9/1925	Federer	2,810,408 A	10/1957	Boice et al.
1,582,483 A	4/1926	Runyan	2,844,173 A	7/1958	Gaskell
1,600,604 A	9/1926	Sorlien	2,850,054 A	9/1958	Eschenburg
1,616,478 A	2/1927	Watson	2,852,047 A	9/1958	Odlum et al.
1,640,517 A	8/1927	Procknow	2,873,773 A	2/1959	Gaskell
1,662,372 A	3/1928	Ward	2,894,546 A	7/1959	Eschenburg
1,701,948 A	2/1929	Crowe	2,913,025 A	11/1959	Richards
1,711,490 A	5/1929	Drummond	2,945,516 A	7/1960	Edgmond, Jr. et al.
1,712,828 A	5/1929	Klehm	2,954,118 A	9/1960	Anderson
1,774,521 A	9/1930	Neighbour	2,978,084 A	4/1961	Vilkaitis
1,807,120 A	5/1931	Lewis	2,984,268 A	5/1961	Vuichard
1,811,066 A	6/1931	Tannewitz	3,005,477 A	10/1961	Sherwen
1,879,280 A	9/1932	James	3,011,529 A	12/1961	Copp
1,896,924 A	2/1933	Ulrich	3,011,610 A	12/1961	Stiebel et al.
1,902,270 A	3/1933	Tate	3,013,592 A	12/1961	Ambrosio et al.
1,904,005 A	4/1933	Masset	3,021,881 A	2/1962	Edgmond, Jr. et al.
1,910,651 A	5/1933	Tautz	3,047,116 A	7/1962	Stiebel et al.
1,938,548 A	12/1933	Tautz	3,085,602 A	4/1963	Gaskell
1,938,549 A	12/1933	Tautz	3,105,530 A	10/1963	Peterson
1,963,688 A	6/1934	Tautz	3,129,731 A	4/1964	Tyrrell
1,988,102 A	1/1935	Woodward	3,163,732 A	12/1964	Abbott
1,993,219 A	3/1935	Merrigan	3,184,001 A	5/1965	Reinsch et al.
2,007,887 A	7/1935	Tautz	3,186,256 A	6/1965	Reznick
2,010,851 A	8/1935	Drummond	3,207,273 A	9/1965	Jurin
2,020,222 A	11/1935	Tautz	3,224,474 A	12/1965	Bloom
2,038,810 A	4/1936	Tautz	3,232,326 A	2/1966	Speer et al.
2,075,282 A	3/1937	Hedgpeth	3,249,134 A	5/1966	Vogl et al.
2,095,330 A	10/1937	Hedgpeth	3,306,149 A	2/1967	John
2,106,288 A	1/1938	Tautz	3,315,715 A	4/1967	Mytinger
2,106,321 A	1/1938	Guertin	3,323,814 A	6/1967	Phillips
2,121,069 A	6/1938	Collins	3,356,111 A	12/1967	Mitchell
2,131,492 A	9/1938	Ocenasek	3,386,322 A	6/1968	Stone et al.
2,163,320 A	6/1939	Hammond	3,454,286 A	7/1969	Anderson et al.
2,168,282 A	8/1939	Tautz	3,538,964 A	11/1970	Warrick et al.
2,241,556 A	5/1941	MacMillin et al.	3,540,338 A	11/1970	McEwan et al.
			3,554,067 A	1/1971	Scutella
			3,581,784 A	6/1971	Warrick

US 6,997,090 B2

3,597,809 A	*	8/1971	Crane	16/48.5	4,589,047 A	5/1986	Gaus et al.
3,613,748 A		10/1971	De Pue		4,589,860 A	5/1986	Brandenstein et al.
3,670,788 A		6/1972	Pollak et al.		4,599,597 A	7/1986	Rotbart
3,675,444 A		7/1972	Whipple		4,599,927 A	7/1986	Eccardt et al.
3,680,609 A		8/1972	Menge		4,606,251 A	8/1986	Boileau
3,695,116 A		10/1972	Baur		4,615,247 A	10/1986	Berkeley
3,696,844 A		10/1972	Bernatschek		4,621,300 A	11/1986	Summerer
3,745,546 A		7/1973	Struger et al.		4,625,604 A	12/1986	Handler et al.
3,749,933 A		7/1973	Davidson		4,637,188 A	1/1987	Crothers
3,754,493 A		8/1973	Niehaus et al.		4,637,289 A	1/1987	Ramsden
3,772,590 A		11/1973	Mikulecky et al.		4,644,832 A	2/1987	Smith
3,785,230 A		1/1974	Lokey		4,653,189 A	3/1987	Andreasson
3,805,639 A		4/1974	Peter		4,657,428 A	4/1987	Wiley
3,805,658 A		4/1974	Scott et al.		4,679,719 A	7/1987	Kramer
3,808,932 A		5/1974	Russell		4,722,021 A	1/1988	Hornung et al.
3,827,039 A	*	7/1974	Agnese	340/586	4,751,603 A	6/1988	Kwan
3,829,850 A		8/1974	Guetersloh		4,756,220 A	7/1988	Olsen et al.
3,858,095 A		12/1974	Friemann et al.		4,757,881 A	7/1988	Jonsson et al.
3,861,016 A		1/1975	Johnson et al.		4,792,965 A	12/1988	Morgan
3,880,032 A		4/1975	Green		4,805,504 A	2/1989	Fushiya et al.
3,889,567 A		6/1975	Sato et al.		4,840,135 A	6/1989	Yamauchi
3,922,785 A		12/1975	Fushiya		4,864,455 A	9/1989	Shimomura et al.
3,924,688 A		12/1975	Cooper et al.		4,875,398 A	10/1989	Taylor et al.
3,931,727 A		1/1976	Luenser		4,906,962 A	3/1990	Duimstra
3,946,631 A		3/1976	Malm		4,934,233 A	6/1990	Brundage et al.
3,947,734 A		3/1976	Fyler		4,937,554 A	6/1990	Herman
3,949,636 A		4/1976	Ball et al.		4,965,909 A	10/1990	McCullough et al.
3,953,770 A		4/1976	Hayashi		5,020,406 A	6/1991	Sasaki et al.
3,967,161 A		6/1976	Lichtblau		5,025,175 A	6/1991	Dubois, III
3,994,192 A		11/1976	Faig		5,046,426 A	9/1991	Julien et al.
4,007,679 A		2/1977	Edwards		5,052,255 A	10/1991	Gaines
4,026,174 A		5/1977	Fierro		5,074,047 A	12/1991	King
4,026,177 A		5/1977	Lokey		5,081,406 A	1/1992	Hughes et al.
4,030,061 A	*	6/1977	Gaskell et al.	337/409	5,082,316 A	1/1992	Wardlaw
4,047,156 A		9/1977	Atkins		5,083,973 A	1/1992	Townsend
4,048,886 A		9/1977	Zettler		5,086,890 A	2/1992	Turczyn et al.
4,060,160 A		11/1977	Lieber		5,119,555 A	6/1992	Johnson
4,070,940 A		1/1978	McDaniel et al.		5,122,091 A	6/1992	Townsend
4,075,961 A		2/1978	Harris		5,174,349 A	12/1992	Svetlik et al.
4,077,161 A		3/1978	Wyle et al.		5,184,534 A	2/1993	Lee
4,085,303 A		4/1978	McIntyre et al.		5,198,702 A	3/1993	McCullough et al.
4,090,345 A		5/1978	Harkness		5,199,343 A	4/1993	OBanion
4,091,698 A		5/1978	Obear et al.		5,201,684 A	4/1993	DeBois, III
4,117,752 A		10/1978	Yoneda		5,207,253 A	5/1993	Hoshino et al.
4,145,940 A		3/1979	Woloveke et al.		5,212,621 A	5/1993	Panter
4,152,833 A		5/1979	Phillips		5,218,189 A	6/1993	Hutchison
4,161,649 A		7/1979	Klos et al.		5,231,359 A	7/1993	Masuda et al.
4,175,452 A		11/1979	Idel		5,231,906 A	8/1993	Kogej
4,190,000 A		2/1980	Shaull et al.		5,239,978 A	8/1993	Plangetis
4,195,722 A		4/1980	Anderson et al.		5,245,879 A	9/1993	McKeon
4,199,930 A		4/1980	Lebet et al.		5,257,570 A	11/1993	Shiotani et al.
4,249,117 A		2/1981	Leukhardt et al.		5,265,510 A	11/1993	Hoyer-Ellefsen
4,249,442 A		2/1981	Fittery		5,272,946 A	12/1993	McCullough et al.
4,267,914 A		5/1981	Saar		5,276,431 A	1/1994	Piccoli et al.
4,270,427 A		6/1981	Colberg et al.		5,285,708 A	2/1994	Bosten et al.
4,276,799 A		7/1981	Muehling		5,320,382 A	6/1994	Goldstein et al.
4,281,309 A	*	7/1981	Olson	337/409	5,321,230 A	6/1994	Shanklin et al.
4,291,794 A		9/1981	Bauer		5,331,875 A	7/1994	Mayfield
4,305,442 A		12/1981	Currie		5,377,554 A	1/1995	Reulein et al.
4,321,841 A		3/1982	Felix		5,377,571 A	1/1995	Josephs
4,366,465 A	*	12/1982	Veneziano	280/735	5,392,678 A	2/1995	Sasaki et al.
4,372,202 A		2/1983	Cameron		5,411,221 A	5/1995	Collins et al.
4,391,358 A		7/1983	Haeger		5,471,888 A	12/1995	McCormick
4,418,597 A		12/1983	Krusemark et al.		5,510,685 A	4/1996	Grasselli
4,466,233 A		8/1984	Thesman		5,513,548 A	5/1996	Garuglieri
4,470,046 A		9/1984	Betsill		5,534,836 A	7/1996	Schenkel et al.
4,510,489 A		4/1985	Anderson, III et al.		5,572,916 A	11/1996	Takano
4,512,224 A		4/1985	Terauchi		5,587,618 A	12/1996	Hathaway
4,518,043 A		5/1985	Anderson et al.		5,606,889 A	3/1997	Bielinski et al.
4,532,501 A		7/1985	Hoffman		5,667,152 A	9/1997	Mooring
4,532,844 A		8/1985	Chang et al.		5,671,633 A	9/1997	Wagner
4,557,168 A		12/1985	Tokiwa		5,695,306 A	12/1997	Nygren, Jr.
4,560,033 A		12/1985	DeWoody et al.		5,724,875 A	3/1998	Meredith et al.
4,566,512 A		1/1986	Wilson		5,730,165 A	3/1998	Philipp
4,573,556 A		3/1986	Andreasson		5,755,148 A	5/1998	Stumpf et al.
4,576,073 A		3/1986	Stinson		5,771,742 A	6/1998	Bokaie et al.

5,782,001 A	7/1998	Gray	2002/0017181 A1	2/2002	Gass et al.
5,787,779 A	8/1998	Garuglieri	2002/0017182 A1	2/2002	Gass et al.
5,791,057 A	8/1998	Nakamura et al.	2002/0017183 A1	2/2002	Gass et al.
5,791,223 A	8/1998	Lanzer	2002/0017184 A1	2/2002	Gass et al.
5,791,224 A	8/1998	Suzuki et al.	2002/0017336 A1	2/2002	Gass et al.
5,852,951 A	12/1998	Santi	2002/0020261 A1	2/2002	Gass et al.
5,861,809 A	1/1999	Eckstein et al.	2002/0020262 A1	2/2002	Gass et al.
5,875,698 A	3/1999	Ceroll et al.	2002/0020263 A1	2/2002	Gass et al.
5,921,367 A	7/1999	Kashioka et al.	2002/0020265 A1	2/2002	Gass et al.
5,937,720 A	8/1999	Itzov	2002/0020271 A1	2/2002	Gass et al.
5,942,975 A	8/1999	Sorensen	2002/0056348 A1	5/2002	Gass et al.
5,943,932 A	8/1999	Sberveglieri	2002/0056349 A1	5/2002	Gass et al.
5,950,514 A	9/1999	Benedict et al.	2002/0056350 A1	5/2002	Gass et al.
5,963,173 A	10/1999	Lian et al.	2002/0059853 A1	5/2002	Gass et al.
5,974,927 A	11/1999	Tsune	2002/0059854 A1	5/2002	Gass et al.
5,989,116 A	11/1999	Johnson et al.	2002/0059855 A1	5/2002	Gass et al.
6,018,284 A	1/2000	Rival et al.	2002/0066346 A1	6/2002	Gass et al.
6,037,729 A	3/2000	Woods et al.	2002/0069734 A1	6/2002	Gass et al.
6,052,884 A	4/2000	Steckler et al.	2002/0096030 A1	7/2002	Wang
6,095,092 A	8/2000	Chou	2002/0109036 A1	8/2002	Denen et al.
6,119,984 A	9/2000	Devine	2002/0170399 A1	11/2002	Gass et al.
6,133,818 A	10/2000	Hsieh et al.	2002/0170400 A1	11/2002	Gass
6,148,504 A	11/2000	Schmidt et al.	2002/0190581 A1	12/2002	Gass et al.
6,150,826 A	11/2000	Hokodate et al.	2003/0002942 A1	1/2003	Gass et al.
6,170,370 B1	1/2001	Sommerville	2003/0005588 A1	1/2003	Gass et al.
6,244,149 B1	6/2001	Ceroll et al.	2003/0015253 A1	1/2003	Gass et al.
6,257,061 B1	7/2001	Nonoyama et al.	2003/0019341 A1	1/2003	Gass et al.
6,366,099 B1	4/2002	Reddi	2003/0020336 A1	1/2003	Gass et al.
6,376,939 B1	4/2002	Suzuki et al.	2003/0037651 A1	2/2003	Gass et al.
6,404,098 B1	6/2002	Kayama et al.	2003/0056853 A1	3/2003	Gass et al.
6,405,624 B1	6/2002	Sutton	2003/0058121 A1	3/2003	Gass et al.
6,418,829 B1	7/2002	Pilchowski	2003/0074873 A1	4/2003	Freiberg et al.
6,420,814 B1	7/2002	Bobbio	2003/0089212 A1	5/2003	Parks et al.
6,430,007 B1	8/2002	Jabbari	2003/0090224 A1	5/2003	Gass et al.
6,431,425 B1	8/2002	Moorman et al.	2003/0101857 A1	6/2003	Chuang
6,450,077 B1	9/2002	Ceroll et al.	2003/0109798 A1	6/2003	Kermani
6,453,786 B1	9/2002	Ceroll et al.	2003/0131703 A1	7/2003	Gass et al.
6,460,442 B1	10/2002	Talesky et al.	2003/0140749 A1	7/2003	Gass et al.
6,471,106 B1	10/2002	Reining	2004/0040426 A1	3/2004	Gass et al.
6,479,958 B1	11/2002	Thompson et al.	2004/0226424 A1	11/2004	OBanion et al.
D466,913 S	12/2002	Ceroll et al.			
6,492,802 B1	12/2002	Bielski			
D469,354 S	1/2003	Curtsinger			
6,502,493 B1	1/2003	Eccardt et al.			
6,536,536 B1	3/2003	Gass et al.			
6,543,324 B1	4/2003	Dils			
6,546,835 B1	4/2003	Wang			
6,575,067 B1	6/2003	Parks et al.			
6,578,460 B1	6/2003	Sartori			
6,578,856 B1	6/2003	Kahle			
6,595,096 B1	7/2003	Ceroll et al.			
D478,917 S	8/2003	Ceroll et al.			
6,601,493 B1	8/2003	Crofutt			
6,607,015 B1	8/2003	Chen			
D479,538 S	9/2003	Welsh et al.			
6,617,720 B1	9/2003	Egan, III et al.			
6,619,348 B1	9/2003	Wang			
6,640,683 B1	11/2003	Lee			
6,644,157 B1	11/2003	Huang			
6,647,847 B1	11/2003	Hewitt et al.			
6,736,042 B1	5/2004	Behne et al.			
6,826,988 B1	12/2004	Gass et al.			
6,857,345 B1	2/2005	Gass et al.			
2001/0032534 A1	10/2001	Cerroll et al.			
2002/0017175 A1	2/2002	Gass et al.			
2002/0017176 A1	2/2002	Gass et al.			
2002/0017178 A1	2/2002	Gass et al.			
2002/0017179 A1	2/2002	Gass et al.			
2002/0017180 A1	2/2002	Gass et al.			

FOREIGN PATENT DOCUMENTS


DE	2800403	7/1979
DE	3427733	1/1986
DE	4235161 A1	5/1993
DE	4326313	2/1995
DE	19609771	6/1998
EP	146460	11/1998
ES	2152184	1/2001
FR	2556643	6/1985
FR	2570017	3/1986
GB	598204	2/1948
GB	2096844	10/1982
GB	2142571	1/1985

OTHER PUBLICATIONS

U.S. Provisional Patent Appl. No. 60/182,866, filed Feb. 16, 2000, entitled "Fast-Acting Safety Stop."
 IWF 2000 Challenges Award Official Entry Form, submitted Apr. 26, 2000, 6 pages plus CD (the portions of US patent applications referenced in the form are from U.S. Appl. No. 60/157,340 filed Oct. 1, 1999 and U.S. Appl. No. 60/182,866 filed Feb. 16, 2000).

* cited by examiner

Fig. 1






Fig. 2

SAFETY SYSTEMS FOR POWER EQUIPMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 10/215,929, filed Aug. 9, 2002 now abandoned, which claims the benefit of and priority from U.S. Provisional Patent Application Ser. No. 60/312,141, filed Aug. 13, 2001. Both of the above applications are hereby incorporated by reference in their entirety for all purposes.

BACKGROUND

Beginning with the industrial revolution and continuing to the present, mechanized equipment has allowed workers to produce goods with greater speed and less effort than possible with manually-powered tools. Unfortunately, the power and high operating speeds of mechanized equipment creates a risk for those operating such machinery. Each year thousands of people are maimed or killed by accidents involving power equipment.

As might be expected, many systems have been developed to minimize the risk of injury when using power equipment. Probably the most common safety feature is a guard that physically blocks an operator from making contact with dangerous components of machinery, such as belts, shafts or blades. In many cases, guards are effective to reduce the risk of injury, however, there are many instances where the nature of the operations to be performed precludes using a guard that completely blocks access to hazardous machine parts.

Various systems have been proposed to prevent accidental injury where guards cannot effectively be employed. For instance, U.S. Pat. Nos. 941,726, 2,978,084, 3,011,610, 3,047,116, 4,195,722 and 4,321,841, the disclosures of which are incorporated herein by reference, all disclose safety systems for use with power presses. These systems utilize cables attached to the wrists of the operator that either pull back a user's hands from the work zone upon operation or prevent operation until the user's hands are outside the danger zone. U.S. Pat. Nos. 3,953,770, 4,075,961, 4,470,046, 4,532,501 and 5,212,621, the disclosures of which are incorporated herein by reference, disclose radio-frequency safety systems which utilize radio-frequency signals to detect the presence of a user's hand in a dangerous area of the machine and thereupon prevent or interrupt operation of the machine.

U.S. Pat. Nos. 4,959,909, 5,025,175, 5,122,091, 5,198,702, 5,201,684, 5,272,946, and 5,510,685 disclose safety systems for use with meat-skipping equipment, and are incorporated herein by reference. These systems interrupt or reverse power to the motor, or disengage a clutch, upon contact with a user's hand by any dangerous portion of the machine. Typically, contact between the user and the machine is detected by monitoring for electrical contact between a fine wire mesh in a glove worn by the user and some metal component in the dangerous area of the machine. Although such systems are suitable for use with meat skinning machines, they are relatively slow to stop the motion of the cutting element because they rely on the operation of solenoids or must overcome the inertia of the motor. However, because these systems operate at relatively low speeds, the blade does not need to be stopped rapidly to prevent serious injury to the user.

U.S. Pat. Nos. 3,785,230 and 4,026,177, the disclosures of which are herein incorporated by reference, disclose a safety

system for use on circular saws to stop the blade when a user's hand approaches the blade. The system uses the blade as an antenna in an electromagnetic proximity detector to detect the approach of a user's hand prior to actual contact with the blade. Upon detection of a user's hand, the system engages a brake using a standard solenoid. Unfortunately, such a system is prone to false triggers and is relatively slow acting because of the solenoid. U.S. Pat. No. 4,117,752, which is herein incorporated by reference, discloses a similar braking system for use with a band saw, where the brake is triggered by actual contact between the user's hand and the blade. However, the system described for detecting blade contact does not appear to be functional to accurately and reliably detect contact. Furthermore, the system relies on standard electromagnetic brakes operating off of line voltage to stop the blade and pulleys of the band saw. It is believed that such brakes would take 50 ms–1 s to stop the blade. Therefore, the system is too slow to stop the blade quickly enough to avoid serious injury.

None of these existing systems have operated with sufficient speed and/or reliability to prevent serious injury with many types of commonly used power tools. Although proximity-type sensors can be used with some equipment to increase the time available to stop the moving pieces, in many cases the user's hands must be brought into relatively close proximity to the cutting element in the normal course of operation. For example, many types of woodworking equipment require that the user's hands pass relatively close to the cutting tools. As a result, existing proximity-type sensors, which are relatively imprecise, have not proven effective with this type of equipment. Even where proximity sensors are practical, existing brake systems have not operated quickly enough to prevent serious injury in many cases.

In equipment where proximity-type detection have not proven effective, the cutting tool must stop very quickly in the event of user contact to avoid serious injury. By way of example, a user may feed a piece of wood through a table saw at a rate of approximately one foot per second. Assuming an average reaction time of approximately one-tenth of a second, the hand may have moved well over an inch before the user even detects the contact. This distance is more than sufficient to result in the loss of several digits, severing of vital vessels and tendons, or even complete severing of a hand. If a brake is triggered immediately upon contact with the saw's blade, the blade must be stopped within approximately one-hundredth of a second to limit the depth of injury to one-eighth of an inch. Standard solenoids or other electromagnetic devices are generally not designed to act in this time scale, particularly where significant force must be generated. For instance, in the case of solenoids or electromagnetic brakes that operate on 60 hz electrical power, it is possible that the power line will be at a phase that has low voltage at the time the brake is triggered and several milliseconds may elapse before the voltage reaches a sufficient level even to begin physical displacement of the brake, much less achieve a complete stoppage of the blade or cutting tool.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic block diagram of a machine with a fast-acting safety system according to the present invention.

FIG. 2 is a schematic diagram of an exemplary safety system in the context of a machine having a circular blade.

DETAILED DESCRIPTION

A machine according to the present invention is shown schematically in FIG. 1 and indicated generally at 10.

Machine **10** may be any of a variety of different machines adapted for cutting workpieces, such as wood, including a table saw, miter saw (chop saw), radial arm saw, circular saw, band saw, jointer, planer, etc. Machine **10** includes an operative structure **12** having a cutting tool **14** and a motor assembly **16** adapted to drive the cutting tool. Machine **10** also includes a safety system **18** configured to minimize the potential of a serious injury to a person using machine **10**. Safety system **18** is adapted to detect the occurrence of one or more dangerous conditions during use of machine **10**. If such a dangerous condition is detected, safety system **18** is adapted to engage operative structure **12** to limit any injury to the user caused by the dangerous condition.

Machine **10** also includes a suitable power source **20** to provide power to operative structure **12** and safety system **18**. Power source **20** may be an external power source such as line current, or an internal power source such as a battery. Alternatively, power source **20** may include a combination of both external and internal power sources. Furthermore, power source **20** may include two or more separate power sources, each adapted to power different portions of machine **10**.

It will be appreciated that operative structure **12** may take any one of many different forms, depending on the type of machine **10**. For example, operative structure **12** may include a stationary housing configured to support motor assembly **16** in driving engagement with cutting tool **14**. Alternatively, operative structure **12** may include a movable structure configured to carry cutting tool **14** between multiple operating positions. As a further alternative, operative structure **12** may include one or more transport mechanisms adapted to convey a workpiece toward and/or away from cutting tool **14**.

Motor assembly **16** includes one or more motors adapted to drive cutting tool **14**. The motors may be either directly or indirectly coupled to the cutting tool, and may also be adapted to drive workpiece transport mechanisms. Cutting tool **14** typically includes one or more blades or other suitable cutting implements that are adapted to cut or remove portions from the workpieces. The particular form of cutting tool **14** will vary depending upon the various embodiments of machine **10**. For example, in table saws, miter saws, circular saws and radial arm saws, cutting tool **14** will typically include one or more circular rotating blades having a plurality of teeth disposed along the perimetrical edge of the blade. For a jointer or planer, the cutting tool typically includes a plurality of radially spaced-apart blades. For a band saw, the cutting tool includes an elongate, circuitous tooth-edged band.

Safety system **18** includes a detection subsystem **22**, a reaction subsystem **24** and a control subsystem **26**. Control subsystem **26** may be adapted to receive inputs from a variety of sources including detection subsystem **22**, reaction subsystem **24**, operative structure **12** and motor assembly **16**. The control subsystem may also include one or more sensors adapted to monitor selected parameters of machine **10**. In addition, control subsystem **26** typically includes one or more instruments operable by a user to control the machine. The control subsystem is configured to control machine **10** in response to the inputs it receives.

Detection subsystem **22** is configured to detect one or more dangerous, or triggering, conditions during use of machine **10**. For example, the detection subsystem may be configured to detect that a portion of the user's body is dangerously close to, or in contact with, a portion of cutting tool **14**. As another example, the detection subsystem may

be configured to detect the rapid movement of a workpiece due to kickback by the cutting tool, such as is described in U.S. Provisional Patent Application Ser. No. 60/182,866, filed Feb. 16, 2000, and U.S. Pat. No. 4,267,914, the disclosures of which are herein incorporated by reference. In some embodiments, detection subsystem **22** may inform control subsystem **26** of the dangerous condition, which then activates reaction subsystem **24**. In other embodiments, the detection subsystem may be adapted to activate the reaction subsystem directly.

Once activated in response to a dangerous condition, reaction subsystem **24** is configured to engage operative structure **12** quickly to prevent serious injury to the user. It will be appreciated that the particular action to be taken by reaction subsystem **24** will vary depending on the type of machine **10** and/or the dangerous condition that is detected. For example, reaction subsystem **24** may be configured to do one or more of the following: stop the movement of cutting tool **14**, disconnect motor assembly **16** from power source **20**, place a barrier between the cutting tool and the user, or retract the cutting tool from its operating position, etc. The reaction subsystem may be configured to take a combination of steps to protect the user from serious injury. Placement of a barrier between the cutting tool and teeth is described in more detail in U.S. Provisional Patent Application Ser. No. 60/225,206, filed Aug. 14, 2000, entitled "Cutting Tool Safety System," the disclosure of which is herein incorporated by reference. Retraction of the cutting tool from its operating position and/or the stopping of translational motion of the cutting tool are described in more detail in the following U.S. Provisional Patent Applications, all the disclosures of which are herein incorporated by reference: Ser. No. 60/225,089, filed Aug. 14, 2000, entitled "Retraction System For Use In Power Equipment," Ser. No. 60/270,941, filed Feb. 22, 2001, entitled "Power Saw with Improved Safety System," Ser. No. 60/270,942, filed Feb. 22, 2001, entitled "Miter Saw with Improved Safety System," Ser. No. 60/273,177, filed Mar. 2, 2001, entitled "Table Saw With Improved Safety System," Ser. No. 60/273,178, filed Mar. 2, 2001, entitled "Miter Saw with Improved Safety System," Ser. No. 60/273,902, filed Mar. 6, 2001, entitled "Miter Saw with Improved Safety System," Ser. No. 60/275,594, filed Mar. 13, 2001, entitled "Miter Saw with Improved Safety System," Ser. No. 60/275,595, filed Mar. 13, 2001, entitled "Safety Systems for Power Equipment," Ser. No. 60/279,313, filed Mar. 27, 2001, entitled "Miter Saw with Improved Safety System," and Ser. No. 60/292,081, filed May 17, 2001, entitled "Translation Stop for Use in Power Equipment."

The configuration of reaction subsystem **24** typically will vary depending on which action(s) are taken. In the exemplary embodiment depicted in FIG. 1, reaction subsystem **24** is configured to stop the movement of cutting tool **14** and includes a brake mechanism **28**, a biasing mechanism **30**, a restraining mechanism **32**, and a release mechanism **34**. Brake mechanism **28** is adapted to engage operative structure **12** under the urging of biasing mechanism **30**. During normal operation of machine **10**, restraining mechanism **32** holds the brake mechanism out of engagement with the operative structure. However, upon receipt of an activation signal by reaction subsystem **24**, the brake mechanism is released from the restraining mechanism by release mechanism **34**, whereupon, the brake mechanism quickly engages at least a portion of the operative structure to bring the cutting tool to a stop.

It will be appreciated by those of skill in the art that the exemplary embodiment depicted in FIG. 1 and described

above may be implemented in a variety of ways depending on the type and configuration of operative structure **12**. Turning attention to FIG. **2**, one example of the many possible implementations of safety system **18** is shown. System **18** is configured to engage an operative structure having a cutting tool in the form of a circular blade **40** mounted on a rotating shaft or arbor **42**. Blade **40** includes a plurality of cutting teeth (not shown) disposed around the outer edge of the blade. As described in more detail below, braking mechanism **28** is adapted to engage the teeth of blade **40** and stop the rotation of the blade. U.S. Provisional Patent Application Ser. No. 60/225,210, filed Aug. 14, 2000, entitled "Translation Stop For Use In Power Equipment," and U.S. Provisional Patent Application Ser. No. 60/233,459, filed Sep. 18, 2000, entitled "Translation Stop For Use In Power Equipment," the disclosures of which are herein incorporated by reference, describe other systems for stopping the movement of the cutting tool. Although the embodiment depicted in FIGS. **1** and **2** schematically illustrate machine **10** as a generic woodworking machine, it will be appreciated that safety system **18** may be incorporated into virtually any specific type of woodworking machine. For example, the following U.S. Provisional Patent Applications, the disclosures of which are herein incorporated by reference, describe safety system **18** in the context of various specific types of machines such as table saws, miter saws, radial arm saws, band saws, pneumatic up-cut saws, routers, etc.: U.S. Provisional Patent Application Ser. No. 60/225,058, filed Aug. 14, 2000, entitled "Table Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/225,057, filed Aug. 14, 2000, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/233,459, filed Sep. 18, 2000, entitled "Translation Stop For Use In Power Equipment," U.S. Provisional Patent Application Ser. No. 60/270,941, filed Feb. 22, 2001, entitled "Power Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/270,942, filed Feb. 22, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/273,177, filed Mar. 2, 2001, entitled "Table Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/273,178, filed Mar. 2, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/273,902, filed Mar. 6, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/275,594, filed Mar. 13, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/275,595, filed Mar. 13, 2001, entitled "Safety Systems For Power Equipment," U.S. Provisional Patent Application Ser. No. 60/279,313, filed Mar. 27, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/292,081, filed May 17, 2001, entitled "Translation Stop For Use In Power Equipment," U.S. Provisional Patent Application Ser. No. 60/292,100, filed May 17, 2001, entitled "Band Saw with Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/298,207, filed Jun. 13, 2001, entitled "Apparatus And Method For Detecting Dangerous Conditions In Power Equipment," and U.S. Provisional Patent Application Ser. No. 60/306,202, filed Jul. 18, 2001, entitled "Router With Improved Safety System."

In the exemplary implementation, detection subsystem **22** is adapted to detect the dangerous condition of the user coming into contact with blade **40**. The detection subsystem includes a sensor assembly, such as contact detection plates

44 and **46**, configured to detect any contact between the user's body and the blade. The detection subsystem is adapted to transmit a signal to control subsystem **26** when contact between the user and the blade is detected. Various exemplary embodiments and implementations of detection subsystem **22** are described in more detail in U.S. Provisional Patent Application Ser. No. 60/225,200, filed Aug. 14, 2000, entitled "Contact Detection System For Power Equipment," U.S. Provisional Patent Application Ser. No. 60/225,211, filed Aug. 14, 2000, entitled "Apparatus And Method For Detecting Dangerous Conditions In Power Equipment," U.S. Provisional Patent Application Ser. No. 60/270,011, filed Feb. 20, 2001, entitled "Contact Detection System for Power Equipment," U.S. Provisional Patent Application Ser. No. 60/292,100, filed May 17, 2001, entitled "Band Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/298,207, filed Jun. 13, 2001, entitled "Apparatus And Method For Detecting Dangerous Conditions In Power Equipment," and U.S. Provisional Patent Application Ser. No. 60/302,937, filed Jul. 2, 2001, entitled "Discrete Proximity Detection System," the disclosures of which are herein incorporated by reference.

Control subsystem **26** includes one or more instruments **48** that are operable by a user to control the motion of blade **40**. Instruments **48** may include start/stop switches, speed controls, direction controls, etc. Control subsystem **26** also includes a logic controller **50** connected to receive the user's inputs via instruments **48**. Logic controller **50** is also connected to receive a contact detection signal from detection subsystem **22**. Further, the logic controller may be configured to receive inputs from other sources (not shown) such as blade motion sensors, workpiece sensors, etc. In any event, the logic controller is configured to control operative structure **12** in response to the user's inputs through instruments **48**. However, upon receipt of a contact detection signal from detection subsystem **22**, the logic controller overrides the control inputs from the user and activates reaction subsystem **24** to stop the motion of the blade. Various exemplary embodiments and implementations of control subsystem **26** are described in more detail in U.S. Provisional Patent Application Ser. No. 60/225,059, filed Aug. 14, 2000, entitled "Logic Control For Fast Acting Safety System," and U.S. Provisional Patent Application Ser. No. 60/225,094, filed Aug. 14, 2000, entitled "Motion Detecting System For Use In Safety System For Power Equipment," the disclosures of which are herein incorporated by reference.

In the exemplary implementation, brake mechanism **28** includes a pawl **60** mounted adjacent the edge of blade **40** and selectively moveable to engage and grip the teeth of the blade. Pawl **60** may be constructed of any suitable material adapted to engage and stop the blade. As one example, the pawl may be constructed of a relatively high strength thermoplastic material such as polycarbonate, ultrahigh molecular weight polyethylene (UHMW) or Acrylonitrile Butadiene Styrene (ABS), etc., or a metal such as aluminum, etc. It will be appreciated that the construction of pawl **60** will vary depending on the configuration of blade **40**. In any event, the pawl is urged into the blade by a biasing mechanism in the form of a spring **66**. In the illustrative embodiment shown in FIG. **2**, pawl **60** is pivoted into the teeth of blade **40**. It should be understood that sliding or rotary movement of pawl **60** may also be used. The spring is adapted to urge pawl **60** into the teeth of the blade with sufficient force to grip the blade and quickly bring it to a stop.

The pawl is held away from the edge of the blade by a restraining mechanism in the form of a fusible member **70**. The fusible member is constructed of a suitable material adapted to restrain the pawl against the bias of spring **66**, and also adapted to melt under a determined electrical current density. Examples of suitable materials for fusible member **70** include NiChrome wire, stainless steel wire, etc. The fusible member is connected between the pawl and a contact mount **72**. Preferably member **70** holds the pawl relatively close to the edge of the blade to reduce the distance the pawl must travel to engage the blade. Positioning the pawl relatively close to the edge of the blade reduces the time required for the pawl to engage and stop the blade. Typically, the pawl is held approximately $\frac{1}{32}$ -inch to $\frac{1}{4}$ -inch from the edge of the blade by fusible member **70**, however other pawl-to-blade spacings may also be used within the scope of the invention.

Pawl **60** is released from its unactuated, or cocked, position to engage blade **40** by a release mechanism in the form of a firing subsystem **76**. The firing subsystem is coupled to contact mount **72**, and is configured to melt fusible member **70** by passing a surge of electrical current through the fusible member. Firing subsystem **76** is coupled to logic controller **50** and activated by a signal from the logic controller. When the logic controller receives a contact detection signal from detection subsystem **22**, the logic controller sends an activation signal to firing subsystem **76**, which melts fusible member **70**, thereby releasing the pawl to stop the blade. Various exemplary embodiments and implementations of reaction subsystem **24** are described in more detail in U.S. Provisional Patent Application Ser. No. 60/225,056, filed Aug. 14, 2000, entitled "Firing Subsystem For Use In Fast Acting Safety System," U.S. Provisional Patent Application Ser. No. 60/225,170, filed Aug. 14, 2000, entitled "Spring-Biased Brake Mechanism for Power Equipment," and U.S. Provisional Patent Application Ser. No. 60/225,169, filed Aug. 14, 2000, entitled "Brake Mechanism For Power Equipment," U.S. Provisional Patent Application Ser. No. 60/279,313, filed Mar. 27, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/292,081, filed May 17, 2001, entitled "Translation Stop For Use In Power Equipment," U.S. Provisional Patent Application Ser. No. 60/292,100, filed May 17, 2001, entitled "Band Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/302,916, filed Jul. 3, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," and U.S. Provisional Patent Application Ser. No. 60/307,756, filed Jul. 25, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," the disclosures of which are herein incorporated by reference.

It will be appreciated that activation of the brake mechanism will require the replacement of one or more portions of safety system **18**. For example, pawl **60** and fusible member **70** typically must be replaced before the safety system is ready to be used again. Thus, it may be desirable to construct one or more portions of safety system **18** in a cartridge that can be easily replaced. For example, in the exemplary implementation depicted in FIG. 2, safety system **18** includes a replaceable cartridge **80** having a housing **82**. Pawl **60**, spring **66**, fusible member **70** and contact mount **72** are all mounted within housing **82**. Alternatively, other portions of safety system **18** may be mounted within the housing. In any event, after the reaction system has been activated, the safety system can be reset by replacing cartridge **80**. The portions of safety system **18** not mounted within the cartridge may be replaced separately or reused as

appropriate. Various exemplary embodiments and implementations of a safety system using a replaceable cartridge are described in more detail in U.S. Provisional Patent Application Ser. No. 60/225,201, filed Aug. 14, 2000, entitled "Replaceable Brake Mechanism For Power Equipment," U.S. Provisional Patent Application Ser. No. 60/225,212, filed Aug. 14, 2000, entitled "Brake Positioning System," U.S. Provisional Patent Application Ser. No. 60/279,313, filed Mar. 27, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/306,202, filed Jul. 18, 2001, entitled "Router With Improved Safety System," U.S. Provisional Patent Application Ser. No. 60/302,916, filed Jul. 3, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," and U.S. Provisional Patent Application Ser. No. 60/307,756, filed Jul. 25, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," the disclosures of which are herein incorporated by reference.

Additional variations and modifications of safety system **18** are described in U.S. Provisional Patent Application Ser. No. 60/182,866, filed Feb. 16, 2000, and 60/157,340, filed Oct. 1, 1999, both entitled "Fast-Acting Safety Stop," the disclosures of which are herein incorporated by reference.

It is believed that the disclosure set forth above encompasses multiple distinct inventions with independent utility. While each of these inventions has been disclosed in its preferred form, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and sub-combinations of the various elements, features, functions and/or properties disclosed herein. No single feature, function, element or property of the disclosed embodiments is essential to all of the disclosed inventions. Similarly, where the claims recite "a" or "a first" element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements.

It is believed that the following claims particularly point out certain combinations and sub-combinations that are directed to one of the disclosed inventions and are novel and non-obvious. Inventions embodied in other combinations and sub-combinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are directed to a different invention or directed to the same invention, whether different, broader, narrower or equal in scope to the original claims, are also regarded as included within the subject matter of the inventions of the present disclosure.

What is claimed is:

1. A saw comprising:

- a blade configured to move to cut a work piece, where the blade includes a cutting edge;
- a motor adapted to move the blade;
- a detection system adapted to detect contact between a person and the blade while the blade is moving and to distinguish that contact from contact between green wood and the blade by imparting a signal to the blade and monitoring that signal for a predetermined rate of change indicative of contact with a person; and
- a replaceable brake cartridge adapted to stop the blade when the detection system detects contact between a person and the blade, the brake cartridge including:

9

a housing;
 a brake pawl pivotally connected with the housing and
 having a blade-contact surface;
 a biasing mechanism at least partially enclosed by the
 housing and adapted to urge the brake pawl to pivot
 relative to the housing; and
 a release mechanism at least partially enclosed by the
 housing and adapted to release the brake pawl to
 pivot relative to the housing under the urging of the
 biasing mechanism when the detection system
 detects contact between a person and the blade;

where the brake cartridge is positioned in the saw so that
 the blade-contact surface can pivot into contact with the
 cutting edge of the blade to stop the blade.

2. The saw of claim 1, further comprising a frame
 supporting the blade, and where the blade is electrically
 isolated from the frame.

3. The saw of claim 1 where the detection system is
 adapted to capacitively impart an electric signal on the blade
 and to detect the occurrence of a determined change in the
 signal.

4. The saw of claim 1, where the biasing mechanism
 includes a spring configured to pivot the brake pawl.

5. The saw of claim 1, where the release mechanism
 includes a fuse wire that is melted upon detection of contact
 between the person and the blade.

6. The saw of claim 1 where the blade is circular and the
 blade-contact surface is spaced radially outward from the
 cutting edge of the blade when the brake cartridge is
 positioned in the saw.

7. The saw of claim 1, where the machine is a table saw.

8. The saw of claim 1, where the machine is a miter saw.

10

9. The saw of claim 1, where the machine is a radial arm
 saw.

10. The saw of claim 1, where the machine is a circular
 saw.

11. The saw of claim 1, where the machine is a hand-held
 circular saw.

12. The saw of claim 1, further including electronics
 associated with the release mechanism, where the electron-
 ics are enclosed within the housing.

13. The saw of claim 1, where the housing is sealed
 against the entry of sawdust.

14. The saw of claim 1, where the detection system is
 capacitively coupled to the blade.

15. The saw of claim 14, where the capacitive coupling
 between the detection system and the blade includes a drive
 electrode and a sense electrode.

16. The saw of claim 1, further including a control system
 adapted to monitor the detection system and control actua-
 tion of the release mechanism.

17. The saw of claim 16, where the control system is
 adapted to shut off the motor when contact between a person
 and the blade is detected.

18. The saw of claim 16, where the control system is
 adapted to verify that the brake cartridge is in the saw before
 power is supplied to the motor.

19. The saw of claim 16, where the control system is
 adapted to test the operability of the release mechanism.

20. The saw of claim 16, where the control system is
 adapted to verify the brake cartridge is positioned in the saw
 so that the blade-contact surface can pivot into contact with
 the cutting edge of the blade to stop the blade.

* * * * *